

ASSIGNMENT 4

Python Programming

Date	27 November 2022
Student Name	Deva. V
Student RollNo	113019106014
Maximum Marks	2 Marks

Import the libraries

```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
from sklearn.model_selection import train_test_split
from tensorflow.keras.preprocessing.sequence import pad_sequences
from sklearn.preprocessing import LabelEncoder
from tensorflow.keras.models import Model
from tensorflow.keras.layers import LSTM, Activation, Dense, Dropout,
Input, Embedding
from tensorflow.keras.optimizers import RMSprop
from tensorflow.keras.preprocessing.text import Tokenizer
from tensorflow.keras.preprocessing import sequence
from tensorflow.keras.utils import to_categorical
from tensorflow.keras.callbacks import EarlyStopping
%matplotlib inline
```

Preprocessing

```
df = pd.read_csv('/content/spam.csv', delimiter=',', encoding='latin-1')
df.head()
```

```
      v1                                     v2 Unnamed: 2
\
0  ham  Go until jurong point, crazy.. Available only ...      NaN
1  ham                                     Ok lar... Joking wif u oni...      NaN
2  spam  Free entry in 2 a wkly comp to win FA Cup fina...      NaN
3  ham  U dun say so early hor... U c already then say...      NaN
4  ham  Nah I don't think he goes to usf, he lives aro...      NaN

      Unnamed: 3 Unnamed: 4
0      NaN      NaN
```

```
1      NaN      NaN
2      NaN      NaN
3      NaN      NaN
4      NaN      NaN
```


```
df.drop(['Unnamed: 2', 'Unnamed: 3', 'Unnamed:
4'],axis=1,inplace=True)
df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 5572 entries, 0 to 5571
Data columns (total 2 columns):
#   Column  Non-Null Count  Dtype
---  ---
0    v1      5572 non-null    object
1    v2      5572 non-null    object
dtypes: object(2)
memory usage: 87.2+ KB
```

```
sns.countplot(df.v1)
plt.xlabel('Label')
plt.title('Number of ham and spam messages')
```

```
/usr/local/lib/python3.7/dist-packages/seaborn/_decorators.py:43:
FutureWarning: Pass the following variable as a keyword arg: x. From
version 0.12, the only valid positional argument will be `data`, and
passing other arguments without an explicit keyword will result in an
error or misinterpretation.
FutureWarning
```

```
Text(0.5, 1.0, 'Number of ham and spam messages')
```



```
X = df.v2
Y = df.v1
le = LabelEncoder()
Y = le.fit_transform(Y)
Y = Y.reshape(-1,1)

X_train,X_test,Y_train,Y_test = train_test_split(X,Y,test_size=0.15)

max_words = 1000
max_len = 150
tok = Tokenizer(num_words=max_words)
tok.fit_on_texts(X_train)
sequences = tok.texts_to_sequences(X_train)
sequences_matrix = sequence.pad_sequences(sequences,maxlen=max_len)
```

RNN

Create Model

Add Layers (LSTM, Dense-(Hidden Layers), Output)

```
def RNN():
    inputs = Input(name='inputs',shape=[max_len])
    layer = Embedding(max_words,50,input_length=max_len)(inputs)
    layer = LSTM(64)(layer)
    layer = Dense(256,name='FC1')(layer)
    layer = Activation('relu')(layer)
```

```

layer = Dropout(0.5)(layer)
layer = Dense(1,name='out_layer')(layer)
layer = Activation('sigmoid')(layer)
model = Model(inputs=inputs,outputs=layer)
return model

```

Compile the model

```

model = RNN()
model.summary()
model.compile(loss='binary_crossentropy',optimizer=RMSprop(),metrics=[
'accuracy'])

```

Model: "model"

Layer (type)	Output Shape	Param #
inputs (InputLayer)	[(None, 150)]	0
embedding (Embedding)	(None, 150, 50)	50000
lstm (LSTM)	(None, 64)	29440
FC1 (Dense)	(None, 256)	16640
activation (Activation)	(None, 256)	0
dropout (Dropout)	(None, 256)	0
out_layer (Dense)	(None, 1)	257
activation_1 (Activation)	(None, 1)	0
Total params: 96,337		
Trainable params: 96,337		
Non-trainable params: 0		

Model Fit

```

model.fit(sequences_matrix,Y_train,batch_size=128,epochs=10,

```

```

validation_split=0.2,callbacks=[EarlyStopping(monitor='val_loss',min_d
elta=0.0001)])

```

Epoch 1/10

```

30/30 [=====] - 11s 279ms/step - loss: 0.3399
- accuracy: 0.8630 - val_loss: 0.1440 - val_accuracy: 0.9473

```

Epoch 2/10

```
30/30 [=====] - 9s 305ms/step - loss: 0.0906  
- accuracy: 0.9747 - val_loss: 0.0538 - val_accuracy: 0.9895  
<keras.callbacks.History at 0x7f53650b6a10>
```

Save the model

```
model.save('spam.h5')
```

Test the model

```
test_sequences = tok.texts_to_sequences(X_test)  
test_sequences_matrix =  
sequence.pad_sequences(test_sequences,maxlen=max_len)  
  
accr = model.evaluate(test_sequences_matrix,Y_test)  
  
27/27 [=====] - 1s 21ms/step - loss: 0.0696 -  
accuracy: 0.9844  
  
print('Test set\n Loss: {:.3f}\n Accuracy:  
{:.3f}'.format(accr[0],accr[1]))  
  
Test set  
Loss: 0.070  
Accuracy: 0.984
```