EMERGING METHODS FOR EARLY DETECTION OF FOREST FIRES

VIDEO ANALYSIS

OPEN CV FOR VIDEO PROCESSING

Date	04 November 2022
Team ID	PNT2022TMID08411
Project Name	Emerging Methods for Early Detection of Forest Fires

Importing The ImageDataGenerator Library import keras from keras.preprocessing.image import ImageDataGenerator ***Define the parameters/arguments for ImageDataGenerator class*** train_datagen=ImageDataGenerator(rescale=1./255,shear_range=0.2,rot ati on_range=180,zoom_range=0.2, horizontal_flip=True) test_datagen=ImageDataGenerator(rescale=1./255) ***Applying ImageDataGenerator functionality to trainset*** x_train=train_datagen.flow_from_directory(r'/content/drive/MyDri

```
v e/ Dataset/train_set',target_size=(128,128),batch_size=32,
class_mode='binary')
```

Found 436 images belonging to 2 classes.
Applying ImageDataGenerator functionality to testset

```
x_test=test_datagen.flow_from_directory(r'/content/drive/MyDrive
/ Dataset/test_set',target_size=(128,128),batch_size=32,
class_mode='binary')
```

Found 121 images belonging to 2 classes.

Import model building libraries

```
#To define Linear initialisation import Sequential
from keras.models import Sequential #To add
layers import Dense from keras.layers import
Dense
#To create Convolution kernel import Convolution2D
from keras.layers import Convolution2D
#import Maxpooling layer
from keras.layers import MaxPooling2D
#import flatten layer from
keras.layers import Flatten
import warnings
warnings.filterwarnings('ignore'
)
```


Initializing the model

```
model=Sequential()
```


Add CNN Layer

```
model.add(Convolution2D(32,
(3,3),input_shape=(128,128,3),activation='relu'))
```

#add maxpooling layer

```python
model.add(MaxPooling2D(pool_size=(2,2)))
#add flatten layer
model.add(Flatten())
```
Add Hidden Layer

```python
#add hidden layer model.add(Dense(150,activation='relu'))
#add output layer
model.add(Dense(1,activation='sigmoid')
)
```

Configure the learning process
```python
model.compile(loss='binary_crossentropy',optimizer="adam",metrics=["ac curacy"])
```

Train   the   model
```python
model.fit_generator(x_train,steps_per_epoch=14,epochs=10,validati on_ da ta=x_test,validation_steps=4)
```

```
Epoch 1/10
14/14 [==============================] - 97s 7s/step - loss: 1.3060 - accuracy: 0.7775 - val_loss: 0.5513 - val_accuracy: 0.8512
Epoch 2/10
14/14 [==============================] - 26s 2s/step - loss: 0.3178 - accuracy: 0.8807 - val_loss: 0.1299 - val_accuracy: 0.9421
Epoch 3/10
14/14 [==============================] - 26s 2s/step - loss: 0.2226 - accuracy: 0.9106 - val_loss: 0.1311 - val_accuracy: 0.9421
Epoch 4/10
14/14 [==============================] - 31s 2s/step - loss:
```

0.1836 - accuracy: 0.9174 - val_loss: 0.1129 - val_accuracy: 0.9339
Epoch 5/10
14/14 [==============================] - 30s 2s/step - loss: 0.1675 - accuracy: 0.9243 - val_loss: 0.0925 - val_accuracy: 0.9669
Epoch 6/10
14/14 [==============================] - 26s 2s/step - loss: 0.1884 - accuracy: 0.9289 - val_loss: 0.1287 - val_accuracy: 0.9339
Epoch 7/10
14/14 [==============================] - 28s 2s/step - loss: 0.1724 - accuracy: 0.9335 - val_loss: 0.0926 - val_accuracy: 0.9752
Epoch 8/10
14/14 [==============================] - 26s 2s/step - loss: 0.1510 - accuracy: 0.9404 - val_loss: 0.0757 - val_accuracy: 0.9752 Epoch 9/10
14/14 [==============================] - 26s 2s/step - loss: 0.173 - 2
accuracy: 0.9174 - val_loss: 0.0537 - val_accuracy: 0.9835
Epoch 10/10
14/14 [==============================] - 26s 2s/step - loss: 0.154 - 6
accuracy: 0.9312 - val_loss: 0.0573 - val_accuracy: 0.9835
<keras.callbacks.History at 0x7f05d66a9c90>

Save The Model

model.save("forest1.h5")

Predictions

```python
#import load_model from keras.model
from keras.models import load_model
#import image class from keras
from tensorflow.keras.preprocessing import image
#import numpy
import numpy as np
#import cv2
import cv2
#load the saved model
model = load_model("forest1.h5")
img=image.load_img(r'/content/drive/MyDrive/Dataset/te st_set/forest/0.48007200_1530881924_final_forest.jpg')
x=image.img_to_array(img)
res = cv2.resize(x, dsize=(128, 128), interpolation=cv2.INTER_CUBIC)
#expand the image shape
x=np.expand_di ms(res,axis=0)
pred= model.predict(x)
```

```
1/1 [==============================] - 0s 126ms/step
pred
array([[0.]], dtype=float32)
```

OpenCV

For Video Processing

pip install twilio

Looking in indexes: https://pypi.org/simple, https://us-python.pkg.dev/colab-wheels/public/simple/
Requirement already satisfied: twilio in /usr/local/lib/python3.7/dist-packages (7.15.1)

Requirement already satisfied: pytz in /usr/local/lib/python3.7/dist-packages (from twilio) (2022.5)
Requirement already satisfied: requests>=2.0.0 in /usr/local/lib/python3.7/dist-packages (from twilio) (2.23.0)
Requirement already satisfied: PyJWT<3.0.0,>=2.0.0 in /usr/local/lib/python3.7/dist-packages (from twilio) (2.6.0) Requirement already satisfied: urllib3!=1.25.0,!=1.25.1,<1.26,>=1.21.1 in /usr/local/lib/python3.7/dist-packages (from requests>=2.0.0- >twilio) (1.24.3)
Requirement already satisfied: certifi>=2017.4.17 in /usr/local/lib/python3.7/dist-packages (from requests>=2.0.0->twilio) (2022.9.24)
Requirement already satisfied: idna<3,>=2.5 in /usr/local/lib/python3.7/dist-packages (from requests>=2.0.0->twilio) (2.10)
Requirement already satisfied: chardet<4,>=3.0.2 in /usr/local/lib/python3.7/dist-packages (from requests>=2.0.0->twilio) (3.0.4)

pip install playsound

Looking in indexes: https://pypi.org/simple, https://us-python.pkg.dev/colab-wheels/public/simple/
Requirement already satisfied: playsound in /usr/local/lib/python3.7/dist-packages (1.3.0)

```python
#import opencv library
import cv2 #import
numpy import numpy
as np
#import image function from keras
from keras.preprocessing import
image #import load_model from
keras
from keras.models import load_model
#import client from twilio API from
twilio.rest import Client
```

```python
#import playsound package
from playsound import playsound
```

WARNING:playsound:playsound is relying on another python subprocess. Please use `pip install pygobject` if you want playsound to run more efficiently.

```python
#load the saved model
model=load_model("forest1.h5")
#define video
video=cv2.VideoCapture(0)
#define the features
name=['forest','with fire']
```