

Command Line Interface for IBM Aspera products

ascli 4.22.0.pre

Laurent MARTIN

2025/04/18

Contents

1	Introduction	7
1.1	BUGS, FEATURES, CONTRIBUTION	7
1.2	When to use and when not to use	7
1.3	Notations, Shell, Examples	8
2	Quick Start	9
2.1	First use	9
2.2	Going further	10
3	Installation	11
3.1	<code>ascli</code> executable	11
3.2	Ruby	11
3.2.1	Windows: Installer	12
3.2.2	macOS: <code>brew</code>	12
3.2.3	Linux: Package	12
3.2.4	Unix-like: RVM: Single user installation (not root)	13
3.2.5	Linux as non-root	13
3.2.6	Other Unixes (AIX)	13
3.2.7	JRuby	14
3.2.8	Optional gems	14
3.3	Ruby Gem: <code>aspera-cli</code>	15
3.3.1	Gem installation with signature verification	15
3.4	FASP Protocol: <code>ascp</code>	15
3.4.1	Installation of <code>ascp</code> through <code>transferd</code>	15
3.4.2	Installation of <code>ascp</code> through other component	16
3.5	Installation in air gapped environment	16
3.5.1	Gem files and dependencies	16
3.5.2	Unix-like	16
3.5.3	Windows	17
3.6	Container	17
3.6.1	Container: Quick start	17
3.6.2	Container: Details	18
3.6.3	Container: Sample start script	19
3.6.4	Container: Offline installation	19
3.6.5	Container: <code>aspera.conf</code>	19
3.6.6	Container: Singularity	20
3.7	SSL library	20
3.8	SSL CA certificate bundle	20
4	Command Line Interface	22
4.1	<code>ascp</code> command line	22
4.2	Command line parsing, Special Characters	23
4.2.1	Shell parsing for Unix-like systems: Linux, macOS, AIX	23
4.2.2	Shell parsing for Windows	23
4.2.3	Shell parsing for Windows: <code>cmd.exe</code>	24
4.2.4	Shell parsing for Windows: Powershell	24

4.2.5	Extended Values (JSON, Ruby, ...)	24
4.2.6	Testing Extended Values	24
4.2.7	Using a shell variable, parsed by shell, in an extended value	25
4.2.8	Double quote in strings in command line	25
4.2.9	Shell and JSON or Ruby special characters in extended value	25
4.2.10	Reading special characters interactively	26
4.2.11	Command line arguments from a file	26
4.2.12	Extended value using special characters read from environmental variables or files	26
4.3	Positional Arguments and Options	26
4.3.1	Positional Arguments	27
4.3.2	Options	27
4.4	Interactive Input	28
4.5	Output	28
4.5.1	Types of output data	29
4.5.2	Option: <code>format</code>	29
4.5.3	Option: <code>table_style</code>	29
4.5.4	Option: <code>flat_hash</code> : <code>..</code> -join keys	29
4.5.5	Option: <code>multi_single</code>	30
4.5.6	Option: <code>display</code> : Verbosity of output	30
4.5.7	Option: <code>show_secrets</code> : Hide or show secrets in results	30
4.5.8	Option: <code>fields</code> : Selection of output object fields	30
4.5.9	Option: <code>select</code>	31
4.5.10	Percent selector	31
4.6	Extended Value Syntax	31
4.7	Configuration and Persistency Folder	33
4.8	Temporary files	34
4.9	Configuration file	34
4.9.1	Option Preset	34
4.9.2	Special Option Preset: <code>config</code>	35
4.9.3	Special Option Preset: <code>default</code>	35
4.9.4	Plugin: <code>config</code> : Configuration	35
4.10	Config sample commands	36
4.10.1	Format of file	37
4.10.2	Evaluation order of options	38
4.10.3	Wizard	39
4.10.4	Example of configuration for a plugin	39
4.11	Secret Vault	39
4.11.1	Vault: System keychain	40
4.11.2	Vault: Encrypted file	40
4.11.3	Vault: Operations	40
4.11.4	Configuration Finder	40
4.11.5	Securing passwords and secrets	40
4.12	Private Key	41
4.12.1	<code>ascli</code> for key generation	41
4.12.2	<code>ssh-keygen</code>	41
4.12.3	<code>openssl</code>	41
4.12.4	Using an application to generate a key pair	41
4.13	Image and video thumbnails	42
4.14	Graphical Interactions: Browser and Text Editor	42
4.15	Logging, Debugging	42
4.16	Learning Aspera Product APIs (REST)	43
4.17	HTTP socket parameters	43
4.18	Proxy	43
4.18.1	Proxy for REST and HTTP Gateway	43
4.18.2	Proxy for Legacy Aspera HTTP/S Fallback	44
4.18.3	FASP proxy (forward) for transfers	44
4.19	FASP configuration	44

4.19.1	Show path of currently used <code>ascp</code>	45
4.19.2	Selection of <code>ascp</code> location for <code>direct</code> agent	45
4.19.3	Installation of Connect Client on command line	46
4.20	Transfer Clients: Agents	47
4.20.1	Agent: Direct	47
4.20.2	Agent: Connect Client	50
4.20.3	Agent: Desktop Client	50
4.20.4	Agent: Node API	50
4.20.5	Agent: HTTP Gateway	50
4.20.6	Agent: Transfer SDK	51
4.21	Transfer Specification	51
4.22	Transfer Parameters	52
4.22.1	Destination folder for transfers	57
4.22.2	List of files for transfers	57
4.22.3	Source directory structure on destination	58
4.22.4	Multi-session transfer	59
4.22.5	Content protection	60
4.22.6	Transfer Spec Examples	60
4.23	Transfer progress bar	60
4.24	Scheduler	60
4.24.1	Windows Scheduler	60
4.24.2	Unix-like Scheduler	60
4.25	Locking for exclusive execution	61
4.26	"Provençal"	61
4.27	<code>faux:</code> for testing	62
4.28	Usage	63
4.29	Bulk creation and deletion of resources	68
4.30	Option: <code>query</code>	68
4.31	Plugins	68
5	Plugin: <code>aoc</code> : IBM Aspera on Cloud	70
5.1	Configuration: Using Wizard	70
5.2	Configuration: Using manual setup	71
5.2.1	Configuration details	71
5.2.2	API Client Registration	71
5.2.3	Configuration for Aspera on Cloud	71
5.2.4	Authentication with private key	72
5.2.5	User key registration	72
5.2.6	Option Preset modification for JWT	73
5.2.7	Public and private links	73
5.2.8	AoC: First Use	73
5.3	Calling AoC APIs from command line	73
5.4	Administration	74
5.4.1	Listing resources	74
5.4.2	Selecting a resource	74
5.4.3	Creating a resource	75
5.4.4	Access Key secrets	75
5.4.5	Activity	75
5.4.6	Transfer: Using specific transfer ports	76
5.4.7	Using ATS	76
5.4.8	Files with type <code>link</code>	76
5.4.9	Example: Bulk creation of users	76
5.4.10	Example: Find with filter and delete	77
5.4.11	Example: Find deactivated users since more than 2 years	77
5.4.12	Example: Display current user's workspaces	77
5.4.13	Example: Create a sub access key in a <code>node</code>	77
5.4.14	Example: Display transfer events (ops/transfer)	77
5.4.15	Example: Display node events (events)	78
5.4.16	Example: Display members of a workspace	78

5.4.17	Example: Add all members of a workspace to another workspace	78
5.4.18	Example: Get users who did not log since a date	78
5.4.19	Example: List Limited users	79
5.4.20	Example: Create a group, add to workspace and add user to group	79
5.4.21	Example: Perform a multi Gbps transfer between two remote shared folders	79
5.4.22	Example: Create registration key to register a tethered node	80
5.4.23	Example: Delete all registration keys	80
5.4.24	Example: Create a Node	80
5.5	List of files to transfer	81
5.6	Packages	81
5.6.1	Send a Package	81
5.6.2	List packages	81
5.6.3	Example: Send a package with one file to two users, using their email	82
5.6.4	Example: Send a package to a shared inbox with metadata	82
5.6.5	Example: List packages in a given shared inbox	82
5.6.6	Example: Receive all packages from a given shared inbox	82
5.6.7	Example: Send a package with files from the Files app	83
5.6.8	Receive new packages only (Cargo)	83
5.7	Example: Content of a received Package	83
5.8	Files	83
5.8.1	Download Files	83
5.8.2	Shared folders	84
5.8.3	Cross Organization transfers	85
5.8.4	Find Files	85
5.9	Aoc sample commands	85
6	Plugin: <code>ats</code> : IBM Aspera Transfer Service	89
6.1	IBM Cloud ATS : Creation of API key	89
6.2	ATS Access key creation parameters	90
6.3	Misc. Examples	90
6.4	Ats sample commands	90
7	Plugin: <code>server</code> : IBM Aspera High Speed Transfer Server (SSH)	92
7.1	Server sample commands	92
7.2	Authentication on Server with SSH session	93
7.3	Other session channels for <code>server</code>	94
7.4	Examples: <code>server</code>	94
8	Plugin: <code>node</code> : IBM Aspera High Speed Transfer Server Node	95
8.1	File Operations	95
8.1.1	Browse	95
8.2	Operation <code>find</code> on <code>gen4/access key</code>	96
8.3	Listing transfer events	96
8.4	Central	97
8.5	Sync	97
8.6	FASP Stream	97
8.7	Watchfolder	97
8.8	Out of Transfer File Validation	97
8.9	Example: SHOD to ATS	98
8.10	Node file information	98
8.11	Create access key	98
8.12	Generate and use bearer token	98
8.12.1	Bearer token: Environment	99
8.12.2	Bearer token: Preparation	99
8.12.3	Bearer token: Configuration for user	100
8.12.4	Bearer token: User side	100
8.13	Node sample commands	100
9	Plugin: <code>faspex5</code> : IBM Aspera Faspex v5	103

9.1 Faspex 5 JWT authentication	104
9.2 Faspex 5 web authentication	104
9.3 Faspex 5 bootstrap authentication	105
9.4 Faspex5 sample commands	105
9.5 Faspex 5: Inbox selection	106
9.6 Faspex 5: Send a package	107
9.7 Faspex 5: Send a package with metadata	107
9.8 Faspex 5: List packages	107
9.9 Faspex 5: Content of a received Package	108
9.10 Faspex 5: Receive a package	108
9.11 Faspex 5: List all shared inboxes and work groups	108
9.12 Faspex 5: Create Metadata profile	109
9.13 Faspex 5: Create a Shared inbox with specific metadata profile	109
9.14 Faspex 5: List content in Shared folder and send package from remote source	109
9.15 Faspex 5: Receive all packages (cargo)	109
9.16 Faspex 5: Invitations	110
9.17 Faspex 5: Cleanup packages	110
9.18 Faspex 5: Admin: Unlock user	110
9.19 Faspex 5: Faspex 4-style post-processing	110
9.20 Faspex 5: Faspex 4 Gateway	111
9.21 Faspex 5: Get Bearer token to use API	112
10 Plugin: faspex : IBM Aspera Faspex v4	113
10.1 Listing Packages	113
10.1.1 Option box	113
10.1.2 Option recipient	113
10.1.3 Option query	113
10.1.4 Example: List packages in dropbox	114
10.2 Receiving a Package	114
10.3 Sending a Package	114
10.4 Email notification on transfer	114
10.5 Operations on dropbox	115
10.6 Remote sources	115
10.7 Automated package download (cargo)	115
10.8 Faspex sample commands	115
11 Plugin: shares : IBM Aspera Shares v1	117
11.1 Shares sample commands	117
12 Plugin: console : IBM Aspera Console	119
12.1 Console sample commands	119
13 Plugin: orchestrator :IBM Aspera Orchestrator	120
13.1 Orchestrator sample commands	120
14 Plugin: cos : IBM Cloud Object Storage	121
14.1 Using endpoint, API key and Resource Instance ID (CRN)	121
14.2 Using service credential file	121
14.3 Operations, transfers	122
14.4 Cos sample commands	122
15 Plugin: httpgw : HTTP Gateway	123
15.1 Httpgw sample commands	123
16 Plugin: faspio : Faspio Gateway	124
16.1 Faspio sample commands	124
17 Plugin: alee : Aspera License Entitlement Engine	125
17.1 Alee sample commands	125

18 Plugin: <code>preview</code> : Preview generator for AoC	126
18.1 Aspera Server configuration	126
18.2 External tools: Linux	126
18.2.1 Image: ImageMagick and <code>optipng</code>	127
18.2.2 Video: FFmpeg	127
18.2.3 Office: <code>unoconv</code> and LibreOffice	127
18.3 Configuration	127
18.4 Options for generated files	128
18.5 Execution	128
18.6 Configuration for Execution in scheduler	128
18.7 Candidate detection for creation or update (or deletion)	128
18.8 Preview File types	129
18.9 Supported input Files types	129
18.10 <code>mimemagic</code>	129
18.11 Generation: Read source files and write preview	130
18.12 Preview sample commands	130
19 IBM Aspera Sync	131
19.1 <code>async</code> API and <code>conf</code> format	131
19.2 <code>async</code> options mapping	131
20 Hot folder	133
20.1 Requirements	133
20.2 Setup procedure	133
20.2.1 <code>ascp</code> features	133
20.2.2 Server side and configuration	133
20.2.3 Scheduling	134
20.3 Example: Upload hot folder	134
20.4 Example: Unidirectional synchronization (upload) to server	134
20.5 Example: Unidirectional synchronization (download) from Aspera on Cloud Files	134
21 Health check and Nagios	135
22 SMTP for email notifications	136
22.1 Example of configuration	136
22.2 Email templates	136
22.3 Test	137
22.4 Notifications for transfer status	137
23 Tool: <code>asession</code>	138
23.1 Comparison of interfaces	138
23.2 Simple session	139
23.3 Asynchronous commands and Persistent session	139
23.4 Example of language wrapper	139
23.5 Help	139
24 Ruby Module: <code>Aspera</code>	141
25 History	142
26 Common problems	143
26.1 Error: "Remote host is not who we expected"	143
26.2 Error "can't find header files for ruby"	143
26.3 ED25519 key not supported	143

Chapter 1

Introduction

Version : 4.22.0.pre

Laurent/2016-2025

This gem provides the `ascli` CLI (Command Line Interface) to IBM Aspera software.

`ascli` is also great tool to learn Aspera APIs.

Ruby Gem: <https://rubygems.org/gems/aspera-cli>

Ruby Doc: <https://www.rubydoc.info/gems/aspera-cli>

Minimum required Ruby version: ≥ 3.1 .

I *Deprecation notice: the minimum Ruby version will be 3.2 in a future version.*

[Aspera APIs on IBM developer Link 2](#)

Release notes: see [CHANGELOG.md](#)

A PDF version of this documentation is available here: [docs/Manual.pdf](#).

1.1 BUGS, FEATURES, CONTRIBUTION

Refer to [BUGS.md](#) and [CONTRIBUTING.md](#).

This documentation does not provide ALL the detailed description of all options and commands. The reason is that most commands and payloads are directly Rest API calls on the various Aspera products. So, to get the full description of all options and commands, refer to the official Aspera API documentation. (To see which API is used, set option `--log-level=debug`)

1.2 When to use and when not to use

`ascli` is designed to be used as a command line tool to:

- Execute commands remotely on Aspera products
- Transfer to/from Aspera products

It is designed for:

- Interactive operations on a text terminal (typically, VT100 compatible), e.g. for maintenance
- Scripting, e.g. batch operations in (shell) scripts (e.g. cron job)

`ascli` can be seen as a command line tool integrating:

- A configuration file (`config.yaml`)
- Advanced command line options (**Extended Value**)
- `curl` (for REST calls)
- Aspera transfer (`ascp`)

If the need is to perform operations programmatically in languages such as: C, Go, Python, NodeJS, ... then it is better to directly use [Aspera APIs](#)

- Product APIs (REST) : e.g. AoC, Faspex, node
- Transfer SDK : with gRPC interface and language stubs (C, C++, Python, .NET/C#, java, Go, Ruby, Rust, etc...)

Using APIs (application REST API and transfer SDK) will prove to be easier to develop and maintain. Code examples here: <https://github.com/laurent-martin/aspera-api-examples>

For scripting and ad'hoc command line operations, `ascli` is perfect.

So, which is Aspera's CLI ? `ascli` or `ascp`

`ascp` is the low level Aspera command line for transfers. It is in fact the implementation of the FASP protocol. So, ANY Aspera transfer leads to one `ascp` process running on client side and another on server side. `ascp` can be used as a command line, but it is very low level, and practically it can be used on command line only if there is no Aspera web app (AoC, Faspex, etc...) and ONLY to do a transfer (send/receive), not for any operation on Aspera apps (e.g. listing remote files). `ascp` does not provide a configuration file to store credentials or options, it does not resume automatically on transfer error.

In fact, `ascli` can do everything that `ascp` does, and much more, and in an easier way.

1.3 Notations, Shell, Examples

Command line operations examples are shown using a shell such as: `bash` or `zsh`.

Command line arguments beginning with `my_` in examples, e.g. `my_param_value`, are user-provided value and not fixed value commands.

`ascli` is an API Client toward the remote Aspera application Server (Faspex, HSTS, etc...)

Some commands will start an Aspera transfer (e.g. `upload`). The transfer is not directly implemented in `ascli`, rather `ascli` uses one of the external Aspera Transfer Clients called **Transfer Agents**.

*Note: A **Transfer Agent** is a client for the remote Transfer Server (HSTS). A **Transfer Agent** can be local or remote... For example a remote Aspera Server may be used as a transfer agent (using Node API). i.e. using option `--transfer=node`*

Chapter 2

Quick Start

This section guides you from installation, first use and advanced use.

First, follow section: **Installation** (Ruby, Gem, FASP) to start using `ascli`.

Once the gem is installed, `ascli` shall be accessible:

```
$ ascli --version
4.22.0.pre
```

2.1 First use

Once installation is completed, you can proceed to the first use with a demo server:

If you want to test with Aspera on Cloud, jump to section: **Wizard**.

To test with Aspera demo transfer server, set up the environment and then test:

```
ascli config initdemo
```

```
ascli server browse /
```

zmode	zuid	zgid	size	mtime	name
dr-xr-xr-x	xfer	demousers	4096	2014-11-05 16:01:56 +0100	aspera-test-dir-large
drwxrwxr-x	xfer	demousers	94208	2025-03-31 11:27:33 +0200	Upload
dr-xr-xr-x	xfer	demousers	4096	2014-11-05 16:01:56 +0100	aspera-test-dir-small
dr-xr-xr-x	xfer	demousers	4096	2014-11-05 16:01:56 +0100	aspera-test-dir-tiny

If you want to use `ascli` with another server, and in order to make further calls more convenient, it is advised to define an **Option Preset** for the server's authentication options. The following example will:

- Create an **Option Preset**
- Define it as default for the `server` plugin
- List files in a folder
- Download a file

```
ascli config preset update myserver --url=ssh://demo.asperasoft.com:33001 --username=asperaweb
↪ --password=my_password_here
```

```
Updated: myserver
Saving config file.
```

```
ascli config preset set default server myserver
```

```
Updated: default: server <- myserver
Saving config file.
```

```
ascli server browse /aspera-test-dir-large
```

zmode	zuid	zgid	size	mtime	name
-rw-r--r--	xfer	demousers	5368709120	2014-11-05 16:01:56 +0100	5GB
-rw-r--r--	xfer	demousers	524288000	2014-11-05 16:01:56 +0100	500MB
-rw-r--r--	xfer	demousers	209715200	2014-11-05 16:01:56 +0100	200MB
-rw-r--r--	xfer	demousers	1048576000	2014-11-05 16:01:56 +0100	1GB
-rw-r--r--	xfer	demousers	104857600	2014-11-05 16:01:56 +0100	100MB
-rw-r--r--	xfer	demousers	10737418240	2014-11-05 16:01:56 +0100	10GB

```

ascli server download /aspera-test-dir-large/200MB
Time: 00:00:02 ===== 100% 100 Mbps Time: 00:00:00
complete

```

2.2 Going further

Get familiar with configuration, options, commands : [Command Line Interface](#).

Then, follow the section relative to the product you want to interact with (Aspera on Cloud, Faspex, ...) : [Application Plugins](#)

Chapter 3

Installation

It is possible to install either directly on the host operating system (Linux, macOS, Windows) or as a **container** (`docker`, `podman`, `singularity`).

The direct installation is recommended and consists in installing:

- **Ruby**
- `aspera-cli`
- **Aspera SDK** (`ascp`)

Ruby version: ≥ 3.1 .

| *Deprecation notice: the minimum Ruby version will be 3.2 in a future version.*

The following sections provide information on the various installation methods.

An internet connection is required for the installation. If you don't have internet for the installation, refer to section **Installation without internet access**.

A package with pre-installed Ruby, gem and `ascp` may also be provided.

3.1 `ascli` executable

It is planned to provide `ascli` as a single platform-dependent executable. [Releases can be found here](#).

Note: This is an Alpha feature. On Linux, the executable requires a minimum GLIBC version.

On Linux, check your GLIBC version with `ldd` :

```
$ ldd --version | head -n1
ldd (GNU libc) 2.34
```

Check an executable's min required version:

```
$ objdump -p /bin/bash | sed -n 's/^.*GLIBC_//p' | sort -V | tail -n1
2.34
```

| *Note: if `objdump` is not available use `strings` or `grep -z 'GLIBC_' | tr \0 \n`*

The `ascli` executable still requires installation of `ascp` : Refer to **Install `ascp`**.

3.2 Ruby

A Ruby interpreter is required to run `ascli`.

Required Ruby version: ≥ 3.1 .

| *Deprecation notice: the minimum Ruby version will be 3.2 in a future version.*

Ruby can be installed using any method : `rpm`, `yum`, `dnf`, `rvm`, `brew`, Windows installer, ...

In priority, refer to the official Ruby documentation:

- [Download Ruby](#)
- [Installation Guide](#)

For convenience, you may refer to the following sections for a proposed method for specific operating systems.

Latest version of `ascli` requires a ruby version [at least under maintenance support](#). If an older Ruby version is needed, then use an older version of `ascli` that supports it.

3.2.1 Windows: Installer

Manual installation:

- Navigate to <https://rubyinstaller.org/> → Downloads.
- Download the latest Ruby installer "with devkit". (`Msys2` is needed to install some native extensions, such as `grpc`)
- Execute the installer which installs by default in: `C:\RubyVV-x64` (`VV` is the version number)
- At the end of the installation procedure, the `Msys2` installer is automatically executed, select option 3 (`Msys2` and `mingw`)
- Then install the `aspera-cli` gem and Aspera SDK (see next sections)

Automated installation, with internet access:

The Ruby installer supports silent installation, to see the options, execute it with `/help` , or refer to the [Ruby Installer FAQ](#)

Download the Ruby installer executable from <https://rubyinstaller.org/downloads/> and then install:

```
rubyinstaller-devkit-3.2.2-1-x64.exe /silent /currentuser /noicons /dir=C:\aspera-cli
```

3.2.2 macOS: brew

macOS comes with Ruby 2.6. It is an old unsupported version and [Apple has deprecated it](#), and it will be removed in the future. Do not use it.

The recommended way is to either use [Homebrew](#) or [RVM](#).

```
brew install ruby
```

This installs a recent ruby suitable for `ascli` .

If using `rvm` , one way to force use of OpenSSL 3.0 is:

```
RUBY_CONFIGURE_OPTS="--with-openssl-dir=$(brew --prefix openssl@3.0)" rvm install 3.4.0
```

3.2.3 Linux: Package

If your Linux distribution provides a standard Ruby package, you can use it provided that the version supported.

Example: RHEL 8+, Rocky Linux 8+: with extensions to compile native gems

- Check available Ruby versions:

```
dnf module list ruby
```

- If Ruby was already installed with an older version, remove it:

```
dnf module -y reset ruby
```

- Install packages needed to build native gems:

```
dnf install -y make automake gcc gcc-c++ kernel-devel
```

- Enable the Ruby version you want:

```
dnf module -y enable ruby:3.1
dnf install -y ruby-devel
```

Example: Ubuntu

```
apt-get install -y ruby-full
```

Other examples:

```
yum install -y ruby ruby-devel rubygems ruby-json
```

```
apt install -y ruby ruby-dev rubygems ruby-json
```

One can remove all installed gems, for example to start fresh:

```
gem uninstall -axI $(ls $(gem env gemdir)/gems/ | sed -e 's/-[^-]*$//' | sort -u)
```

3.2.4 Unix-like: RVM: Single user installation (not root)

Install `rvm`. Follow <https://rvm.io/>.

Execute the shell/curl command. As regular user, it installs in the user's home: `~/.rvm`.

```
\curl -sSL https://get.rvm.io | bash -s stable
```

Follow on-screen instructions to install keys, and then re-execute the command.

Upon RVM installation, open a new terminal or initialize with:

```
source ~/.rvm/scripts/rvm
```

It is advised to get one of the pre-compiled Ruby version, you can list with:

```
rvm list --remote
```

Install the chosen pre-compiled Ruby version:

```
rvm install 3.2.2
```

Ruby is now installed for the user, go to [Gem installation](#).

Alternatively RVM can be installed system-wide, for this execute as `root`. It then installs by default in `/usr/local/rvm` for all users and creates `/etc/profile.d/rvm.sh`. One can install in another location with:

```
curl -sSL https://get.rvm.io | bash -s -- --path /usr/local
```

As root, make sure this will not collide with other application using Ruby (e.g. Faspex). If so, one can rename the environment script so that it is not loaded by default:

```
mv /etc/profile.d/rvm.sh /etc/profile.d/rvm.sh.ok
```

To activate Ruby (and ascli) later, source it:

```
source /etc/profile.d/rvm.sh.ok
```

```
rvm version
```

3.2.5 Linux as non-root

If you don't have root access, you can install Ruby in your home directory using `rbenv` see [rbenv-installer](#):

```
curl -fsSL https://github.com/rbenv/rbenv-installer/raw/HEAD/bin/rbenv-installer | bash
```

Then open a new terminal, or `source` the shell initialization script:

```
source ~/.bashrc
```

Then install Ruby:

```
rbenv install 3.2.2
```

3.2.6 Other Unixes (AIX)

Ruby is sometimes made available as an installable package through third party providers. For example for AIX, one can look at:

<https://www.ibm.com/support/pages/aix-toolbox-open-source-software-downloads-alpha#R>

If your Unix does not provide a pre-built Ruby, you can get it using one of those [methods](#).

For instance to build from source and install in `/opt/ruby`:

```
wget https://cache.ruby-lang.org/pub/ruby/2.7/ruby-2.7.2.tar.gz
gzip -d ruby-2.7.2.tar.gz
tar xvf ruby-2.7.2.tar
cd ruby-2.7.2
./configure --prefix=/opt/ruby
make ruby.imp
make
make install
```

3.2.7 JRuby

`ascli` can also run with the [JRuby](#) interpreter. All what is needed is a JVM (Java Virtual Machine) on your system (`java`). The JRuby package comes pre-compiled and does not require compilation of native extensions. Use a version of JRuby compatible with Ruby version supported by `ascli` . Refer to [the Wikipedia page](#) to match JRuby and Ruby versions. Choose the latest version from:

<https://www.jruby.org/download>

Note: The startup time is slightly longer using `jruby` than the native Ruby, refer to the [JRuby wiki](#) for details. This can be reduced by using the `--dev` option. The transfer speed is not impacted (executed by `ascp` binary).

Note: JRuby can be [installed](#) using `rum` .

Example: start `ascli` with JRuby and reduce startup time:

```
export JRUBY_OPTS="--dev
ascli -v
```

or

```
JRUBY_OPTS="--dev ascli -v
```

3.2.8 Optional gems

Some additional gems are required for some specific features, see [Gemfile](#):

name	version	comment
grpc	~> 1.65	for transferSDK
mimemagic	~> 0.4	for preview
rmagick	~> 5.5	for terminal view
symmetric-encryption	~> 4.6	for file vault
bigdecimal	~> 3.1.9	if RUBY_VERSION >= '3.4' for symmetric-encryption ?

Install like this:

```
gem install grpc -v '~> 1.65'
gem install mimemagic -v '~> 0.4'
gem install rmagick -v '~> 5.5'
gem install symmetric-encryption -v '~> 4.6'
gem install bigdecimal -v '~> 3.1.9'
```

Note: Those are not installed as part of dependencies because they involve compilation of native code.

3.3 Ruby Gem: **aspera-cli**

Once you have Ruby and rights to install gems, install the **aspera-cli** gem and its dependencies:

```
gem install aspera-cli --pre
```

To upgrade to the latest version:

```
gem update aspera-cli
```

During its execution, **ascli** checks every week if a new version is available and notifies the user in a WARN log. To deactivate this feature, globally set the option **version_check_days** to **0**, or specify a different period in days.

To check if a new version is available (independently of **version_check_days**):

```
ascli config check_update
```

3.3.1 Gem installation with signature verification

The gem is signed with a private key, and the public certificate is available in the GitHub repository (**certs/aspera-cli-public-cert.pem**). When installing the gem, the signature can be optionally verified.

For [secure installation](#), one can install the gem with the public key:

Import the verification certificate:

```
gem cert --add <(curl -Ls  
↪ https://raw.githubusercontent.com/IBM/aspera-cli/main/certs/aspera-cli-public-cert.pem)
```

The user installs the gem with **HighSecurity** or **MediumSecurity**: this will succeed only if the gem is trusted:

```
gem install -P MediumSecurity aspera-cli
```

3.4 FASP Protocol: **ascp**

Most file transfers will be executed using the **FASP** protocol, using **ascp**. Only two additional files are required to perform an Aspera Transfer, which are part of Aspera SDK:

- **ascp**
- **aspera-license** (in same folder, or **../etc**)

This can be installed either by installing an Aspera transfer software or using an **ascli** command.

3.4.1 Installation of **ascp** through **transferrd**

The easiest option to install **ascp** is through the use of the IBM Aspera Transfer Daemon.

Supported platforms are listed in the [Release Notes](#) and archives can be downloaded from [Downloads](#).

Install using **ascli** for the current platform with:

```
ascli config ascp install
```

or

```
ascli config transferrd install
```

The installation of the transfer binary follows those steps:

- Check the value of option **sdk_url**: if the value is the default value **DEF**, then the procedure follows, else it specifies a URL where to take the archive from.
- The location of archives is retrieved from the URL specified by option **locations_url** whose default value is https://ibm.biz/sdk_location
- The archive for the current system architecture (CPU and OS) is selected and downloaded.

The option **locations_url** can be set to override the URL where the list of versions is located, in case of air-gap environment or for testing. Option **sdk_url** can be set to specify a direct location for the transfer binaries.

Available Transfer Daemon versions available from `locations_url` can be listed with: `ascli config transferd list`

To install a specific version, e.g. 1.1.3:

```
ascli config ascp install 1.1.3
```

To get the download URL for a specific platform and version:

```
ascli config transferd list --select=@json: '{"platform": "osx-arm64", "version": "1.1.3"}'
↪ --fields=url
```

To download it, pipe to `config download`:

```
ascli config transferd list --select=@json: '{"platform": "osx-arm64", "version": "1.1.3"}'
↪ --fields=url | ascli config download @stdin:
```

If installation from a local file preferred instead of fetching from internet: one can specify the location of the SDK file with option `sdk_url`:

```
ascli config ascp install --sdk-url=file:///macos-arm64-1.1.3-c6c7a2a.zip
```

The format is: `file:///<path>`, where `<path>` can be either a relative path (not starting with `/`), or an absolute path.

3.4.2 Installation of `ascp` through other component

If the embedded method is not used, the following packages are also suitable:

- IBM Aspera Connect Client (Free)
- IBM Aspera Desktop Client (Free)
- IBM Aspera High Speed Transfer Server (Licensed)
- IBM Aspera High Speed Transfer Endpoint (Licensed)

For instance, Aspera Connect Client can be installed by visiting the page: <https://www.ibm.com/aspera/connect/>.

`ascli` will detect most of Aspera transfer products in standard locations and use the first one found by default. Refer to section **FASP** for details on how to select a client or set path to the FASP protocol.

Several methods are provided to start a transfer. Use of a local client (`direct` transfer agent) is one of them, but other methods are available. Refer to section: **Transfer Agents**

3.5 Installation in air gapped environment

I *Note: No pre-packaged version is provided yet.*

3.5.1 Gem files and dependencies

The sample script: [examples/build_package.sh](#) can be used to download all necessary gems and dependencies in a `tar.gz`.

```
$ ./build_package.sh aspera-cli 4.18.0
Archive: aspera-cli-4.18.0-gems.tgz
```

3.5.2 Unix-like

A method to build one is provided here:

The procedure:

- Follow the non-root installation procedure with RVM, including gem
- Archive (zip, tar) the main RVM folder (includes `ascli`):

```
cd $HOME && tar zcvf rvm-ascli.tgz .rvm
```

- Download the SDK archive for the selected architecture, follow **Install** `ascp`

- Transfer those 2 files to the target system
- On target system

```
cd $HOME
tar zxvf rvm-ascli.tgz
source ~/.rvm/scripts/rvm
ascli config ascp install --sdk-url=file:/// [SDK archive file path]
```

- Add those lines to shell environment (`.profile`)

```
source ~/.rvm/scripts/rvm
```

3.5.3 Windows

Installation without network:

It is essentially the same procedure as installation for Windows with internet, but instead of retrieving files from internet, copy the files from a machine with internet access, and then install from those archives:

- Download the Ruby installer from <https://rubyinstaller.org/downloads/>

```
v=$(curl -s https://rubyinstaller.org/downloads/ | sed -nEe
↪ 's|.*(https://.*/releases/download/.*exe).*\|1|p' | head -n 1)
curl -o ${v#*/} $v
```

- Create an archive with necessary gems like in previous section
- Download the SDK following: Install `ascp`
- Create a Zip with all those files and transfer to the target system.

Then, on the target system:

- Unzip the archive
- Execute the installer:

```
rubyinstaller-devkit-3.2.2-1-x64.exe /silent /currentuser /noicons /dir=C:\aspera-cli
```

- Install the gems: Extract the gem archive and then:

```
gem install --force --local *.gem
```

- Install the SDK

```
ascli config ascp install --sdk-url=file:///sdk.zip
```

Note: An example of installation script is provided: [docs/install.bat](#)

3.6 Container

The container image is: [docker.io/martinlaurent/ascli](https://hub.docker.com/r/martinlaurent/ascli). The container contains: Ruby, `ascli` and the Aspera Transfer SDK. To use the container, ensure that you have `podman` (or `docker`) installed.

```
podman --version
```

3.6.1 Container: Quick start

Wanna start quickly ? With an interactive shell ? Execute this:

```
podman run --rm --tty --interactive --entrypoint bash docker.io/martinlaurent/ascli:latest
```

Note: This command changes the entry point to an interactive shell instead of direct execution of `ascli`.

Then, execute individual `ascli` commands such as:

```
ascli config init
ascli config preset overview
ascli config ascp info
ascli server ls /
```

That is simple, but there are limitations:

- Everything happens in the container
- Any generated file in the container will be lost on container (shell) exit. Including configuration files and downloaded files.
- No possibility to upload files located on the host system

3.6.2 Container: Details

The container image is built from this [Dockerfile](#). The entry point is `ascli` and the default command is `help`.

The container can be executed for individual commands like this: (add `ascli` commands and options at the end of the command line, e.g. `-v` to display the version)

```
podman run --rm --tty --interactive docker.io/martinlaurent/ascli:latest
```

For more convenience, you may define a shell alias:

```
alias ascli='podman run --rm --tty --interactive docker.io/martinlaurent/ascli:latest'
```

Then, you can execute the container like a local command:

```
ascli -v
```

4.22.0.pre

In order to keep persistency of configuration on the host, you should specify your user's configuration folder as a volume for the container. To enable write access, a possibility is to run as `root` in the container (and set the default configuration folder to `/home/cliuser/.aspera/ascli`). Add options:

```
--user root --env ASCII_HOME=/home/cliuser/.aspera/ascli --volume
↪ $HOME/.aspera/ascli:/home/cliuser/.aspera/ascli
```

Note: If you are using a `podman machine`, e.g. on macOS, make sure that the folder is also shared between the VM and the host, so that sharing is: container → VM → Host:
`podman machine init ... --volume="/Users:/Users"`

As shown in the quick start, if you prefer to keep a running container with a shell and `ascli` available, you can change the entry point, add option:

```
--entrypoint bash
```

You may also probably want that files downloaded in the container are directed to the host. In this case you need also to specify the shared transfer folder as a volume:

```
--volume $HOME/xferdir:/xferfiles
```

Note: `ascli` is run inside the container, so transfers are also executed inside the container and do not have access to host storage by default.

And if you want all the above, simply use all the options:

```
alias asclish="podman run --rm --tty --interactive --user root --env
↪ ASCII_HOME=/home/cliuser/.aspera/ascli --volume
↪ $HOME/.aspera/ascli:/home/cliuser/.aspera/ascli --volume $HOME/xferdir:/xferfiles
↪ --entrypoint bash docker.io/martinlaurent/ascli:latest"
```

```
export xferdir=$HOME/xferdir
mkdir -p $xferdir
chmod -R 777 $xferdir
mkdir -p $HOME/.aspera/ascli
asclish
```

3.6.3 Container: Sample start script

A convenience sample script is also provided: download the script `dascli` from the [GIT repo](#) :

Note: If you have installed `ascli` , the script `dascli` can also be found:
`cp $(ascli config gem path)/../examples/dascli ascli`

Some environment variables can be set for this script to adapt its behavior:

env var	Description	Default	Example
<code>ASCLI_HOME</code>	Configuration folder (persistency)	<code>\$HOME/.aspera/ascli</code>	<code>\$HOME/.ascli_config</code>
<code>docker_args</code>	Additional options to <code>podman</code>	<empty>	<code>--volume /Users:/Users</code>
<code>image</code>	Container image name	<code>docker.io/martinlaurent/ascli</code>	
<code>version</code>	Container image version	Latest	<code>4.8.0.pre</code>

The wrapping script maps the folder `$ASCLI_HOME` on host to `/home/cliuser/.aspera/ascli` in the container. (value expected in the container). This allows having persistent configuration on the host.

To add local storage as a volume, you can use the env var `docker_args` :

Example of use:

```
curl -o ascli https://raw.githubusercontent.com/IBM/aspera-cli/main/examples/dascli
chmod a+x ascli
export xferdir=$HOME/xferdir
mkdir -p $xferdir
chmod -R 777 $xferdir
export docker_args="--volume $xferdir:/xferfiles"

./ascli config init

echo 'Local file to transfer' > $xferdir/samplefile.txt
./ascli server upload /xferfiles/samplefile.txt --to-folder=/Upload
```

Note: The local file (`samplefile.txt`) is specified relative to storage view from container (`/xferfiles`) mapped to the host folder `$HOME/xferdir`

Note: Do not use too many volumes, as the legacy `aufs` limits the number. (anyway, prefer to use `overlay2`)

3.6.4 Container: Offline installation

- First create the image archive:

```
podman pull docker.io/martinlaurent/ascli
podman save docker.io/martinlaurent/ascli|gzip>ascli_image_latest.tar.gz
```

- Then, on air-gapped system:

```
podman load -i ascli_image_latest.tar.gz
```

3.6.5 Container: `aspera.conf`

`ascp` 's configuration file `aspera.conf` is located in the container at: `/ibm_aspera/aspera.conf` (see Dockerfile). As the container is immutable, it is not recommended modifying this file. If one wants to change the content, it is possible to tell `ascp` to use another file using `ascp` option `-f` , e.g. by locating it on the host folder `$HOME/.aspera/ascli` mapped to the container folder `/home/cliuser/.aspera/ascli` :

```
echo '<CONF/>' > $HOME/.aspera/ascli/aspera.conf
```

Then, tell `ascp` to use that other configuration file:

```
--transfer-info=@json:'{"ascp_args":["-f", "/home/cliuser/.aspera/ascli/aspera.conf"]}'
```

3.6.6 Container: Singularity

Singularity is another type of use of container.

On Linux install:

```
dnf install singularity-ce
```

Build an image like this:

```
singularity build ascli.sif docker://docker.io/martinlaurent/ascli
```

Then, start `ascli` like this:

```
singularity run ascli.sif
```

Or get a shell with access to `ascli` like this:

```
singularity shell ascli.sif
```

3.7 SSL library

`ascli` uses the Ruby `openssl` gem which uses by default the system's `openssl` library and its CA certificate bundle.

To display the version of `OpenSSL` used in `ascli`:

```
ascli config echo @ruby:OpenSSL::OPENSSL_VERSION --format=text
```

It is possible to specify to use another SSL library or version by executing:

```
gem install openssl -- --with-openssl-dir=[openssl library folder]
```

Where `[openssl library folder]` is the path to the folder containing the `lib` and `include` folders of the `openssl` library.

For example, on macOS, to use the `openssl@3` library installed with `brew`:

```
$ openssl version -e | sed -n 's|ENGINESDIR: "\(.*\)\/lib[\/]*\/.*|1|p'
/opt/homebrew/Cellar/openssl@3/3.3.0
$ gem install openssl -- --with-openssl-dir=/opt/homebrew/Cellar/openssl@3/3.3.0
```

3.8 SSL CA certificate bundle

SSL certificates are validated using a certificate store, by default it is the one of the system's `openssl` library.

To display trusted certificate store locations:

```
ascli --show-config --fields=cert_stores
```

Certificates are checked against the [Ruby default certificate store](#) `OpenSSL::X509::DEFAULT_CERT_FILE` and `OpenSSL::X509::DEFAULT_CERT_DIR`, which are typically the ones of `openssl` on Unix-like systems (Linux, macOS, etc...). Ruby's default values can be overridden using env vars: `SSL_CERT_FILE` and `SSL_CERT_DIR`.

One can display those default values:

```
ascli config echo @ruby:OpenSSL::X509::DEFAULT_CERT_DIR --format=text
ascli config echo @ruby:OpenSSL::X509::DEFAULT_CERT_FILE --format=text
```

In order to get certificate validation, the CA certificate bundle must be up-to-date. Check this repository on how to update the system's CA certificate bundle: <https://github.com/millermatt/osca>.

For example on RHEL/Rocky Linux:

```
dnf install -y ca-certificates
update-ca-trust extract
```

The SSL CA certificate bundle can be specified using option `cert_stores`, which is a list of files or folders. By default, it uses Ruby's default certificate store.

If you use this option, then default locations are not used. Default locations can be added using special value `DEF`. The value can be either an `Array` or `String` (path). Successive options add paths incrementally. All files of a folder are added.

JRuby uses its own implementation and CA bundles.

For example, on Linux to force the use the system's certificate store:

```
--cert-stores=$(openssl version -d|cut -f2 -d' ')/cert.pem
```

`ascp` also needs to validate certificates when using WSS for transfer TCP part (instead of SSH).

By default, `ascp` uses a hard coded root location `OPENSSLDIR`. Original `ascp`'s hard coded locations can be found using:

```
ascli config ascp info --fields=openssldir
```

E.g. on macOS: `/Library/Aspera/ssl`. Then trusted certificates are taken from `[OPENSSLDIR]/cert.pem` and files in `[OPENSSLDIR]/certs`. `ascli` overrides the default hard coded location used by `ascp` for WSS and uses the same locations as specified in `cert_stores` (using the `-i` option of `ascp`).

To update trusted root certificates for `ascli`: Display the trusted certificate store locations used by `ascli`. Typically done by updating the system's root certificate store.

An up-to-date version of the certificate bundle can also be retrieved with:

```
ascli config echo @uri:https://curl.haxx.se/ca/cacert.pem --format=text
```

To download that certificate store:

```
ascli config echo @uri:https://curl.haxx.se/ca/cacert.pem --format=text --output=/tmp/cacert.pem
```

Then, use this store by setting the option `cert_stores` (or env var `SSL_CERT_FILE`).

To trust a specific certificate (e.g. self-signed), provided that the `CN` is correct, save the certificate chain to a file:

```
ascli config remote_certificate chain https://localhost:9092 --insecure=yes --output=myserver.pem
```

Note: Use command `name` to display the remote common name of the remote certificate.

Then, use this file as certificate store (e.g. here, Node API):

```
ascli config echo @uri:https://localhost:9092/ping --cert-stores=myserver.pem
```

Chapter 4

Command Line Interface

The command line tool is: `ascli`

The `aspera-cli` gem provides a command line interface (CLI) which interacts with Aspera Products (mostly using REST APIs):

- IBM Aspera High Speed Transfer Server (FASP and Node)
- IBM Aspera on Cloud (including ATS)
- IBM Aspera Faspex
- IBM Aspera Shares
- IBM Aspera Console
- IBM Aspera Orchestrator
- And more...

`ascli` provides the following features:

- Commands to Aspera server products (on-premise and SaaS)
- Any command line options (products URL, credentials or any option) can be provided on command line, in configuration file, in env var, in files, ...
- Commands, Options, and Option values shortcuts
- FASP **Transfer Agents** can be: local `ascp`, or Connect Client, or any transfer node
- Transfer parameters can be altered by modification of `transfer-spec`, this includes requiring multi-session
- Allows transfers from products to products, essentially at node level (using the node transfer agent)
- faspstream creation (using Node API)
- Watchfolder creation (using Node API)
- Additional command plugins can be written by the user
- Download of Faspex and Aspera on Cloud "external" links
- Legacy SSH based FASP transfers and remote commands (`ascmd`)

Basic usage is displayed by executing:

```
ascli -h
```

Refer to sections: **Usage**.

I Note: `ascli` features are not fully documented here, the user may explore commands on the command line.

4.1 `ascp` command line

If you want to use `ascp` directly as a command line, refer to IBM Aspera documentation of either [Desktop Client](#), [Endpoint](#) or [Transfer Server](#) where a section on `ascp` can be found.

Using `ascli` with plugin `server` for command line gives advantages over `ascp` :

- Automatic resume on error
- Configuration file
- Choice of transfer agents
- Integrated support of multi-session

All `ascp` options are supported either through transfer spec parameters (listed with `conf ascp spec`) and with the possibility to provide `ascp` arguments directly when the `direct` agent is used (`ascp_args` in `transfer_info`).

4.2 Command line parsing, Special Characters

`ascli` is typically executed in a shell, either interactively or in a script. `ascli` receives its arguments on the command line. The way arguments are parsed and provided to `ascli` depend on the Operating System and shell.

4.2.1 Shell parsing for Unix-like systems: Linux, macOS, AIX

Linux command line parsing is well-defined: It is fully documented in the shell's documentation.

On Unix-like environments, this is typically a POSIX-like shell (`bash`, `zsh`, `ksh`, `sh`). A c-shell (`csh`, `tcsh`) or other shell can also be used. In this environment the shell parses the command line, possibly replacing variables, etc... See [bash shell operation](#). The shell builds the list of arguments and then `fork / exec` Ruby with that list. Ruby receives a list command line arguments from shell and gives it to `ascli`. Special character handling (quotes, spaces, env vars, ...) is handled by the shell for any command executed.

4.2.2 Shell parsing for Windows

Command line parsing first depends on the shell used. MS Windows command line parsing is not like Unix-like systems simply because Windows does not provide a list of arguments to the executable (Ruby): it provides the whole command line as a single string, but the shell may interpret some special characters.

So command line parsing is not handled by the shell (`cmd.exe`), not handled by the operating system, but it is handled by the executable. Typically, Windows executables use the [Microsoft library for this parsing](#).

As far as `ascli` is concerned: the executable is Ruby. It has its own parsing algorithm, close to a Linux shell parsing.

Thankfully, `ascli` provides a command to check the value of an argument after parsing: `config echo`. One can also run `ascli` with option `--log-level=debug` to display the command line after parsing.

It is also possible to display arguments received by Ruby using this command:

```
C:> ruby -e 'puts ARGV' "Hello World" 1 2
Hello World
1
2
```

Note: Use `pp` instead of `puts` to display as ruby Array.

Once the shell has dealt with the command line "special" characters for it, the shell calls Windows' `CreateProcess` with just the whole command line as a single string. (Unlike Unix-like systems where the command line is split into arguments by the shell.)

It's up to the program to split arguments:

- [Windows: How Command Line Parameters Are Parsed](#)
- [Understand Quoting and Escaping of Windows Command Line Arguments](#)

is a Ruby program, so Ruby parses the command line into arguments and provides them to the program. Ruby vaguely follows the Microsoft C/C++ parameter parsing rules. (See `w32_cmdvector` in Ruby source [win32.c](#)):

- Space characters: split arguments (space, tab, newline)
- Backslash: `\` escape single special character
- Globing characters: `*?[]{}|` for file globing
- Double quotes: `"`
- Single quotes: `'`

4.2.3 Shell parsing for Windows: `cmd.exe`

The following examples give the same result on Windows using `cmd.exe` :

- Single quote protects the double quote

```
ascli config echo @json:'{"url":"https://..."}'
```

- Triple double quotes are replaced with a single double quote

```
ascli config echo @json:{""url"":""https://...""}
```

- Double quote is escaped with backslash within double quotes

```
ascli config echo @json:"{\url\":"https://...\}"
```

`cmd.exe` handles some special characters: `^"<>|%&` . Basically it handles I/O redirection (`<>`), shell variables (`%`), multiple commands (`&`) and handles those special characters from the command line. Eventually, all those special characters are removed from the command line unless escaped with `^` or `"` . `"` are kept and given to the program.

4.2.4 Shell parsing for Windows: Powershell

For Powershell, it actually depends on the version of it.

A difficulty is that Powershell parses the command line for its own use and manages special characters, but then it passes the command line to the program (Ruby) as a single string, possibly without the special characters.

Details can be found here:

- [Passing arguments with quotes](#)
- [quoting rules](#)

The following examples give the same result on Windows using Powershell:

```
PS C:\> echo $psversiontable.psversion
```

```
Major  Minor  Build  Revision
-----
5      1      19041  4046
```

```
PS C:\> ascli config echo --% @json:'{"k":"v","x":"y"}'
```

```
PS C:\> ascli config echo @json:'{"k":"v","x":"y"}'
```

| *Note: The special Powershell argument `--%` places Powershell in legacy parsing mode.*

4.2.5 Extended Values (JSON, Ruby, ...)

Some values provided to `ascli` (options, Command Parameters) are expected to be **Extended Values**, i.e. not a simple `String` , but a composite structure (`Hash` , `Array`). Typically, the `@json:` modifier is used, it expects a **JSON** string. JSON itself has some special syntax: for example `"` is used to enclose a `String` .

4.2.6 Testing Extended Values

In case of doubt of argument values after parsing, one can test using command `config echo` . `config echo` takes exactly one argument which can use the **Extended Value** syntax. Unprocessed command line arguments are shown in the error message.

Example: The shell parses three arguments (as `String` : `1` , `2` and `3`), so the additional two arguments are not processed by the `echo` command.

```
ascli config echo 1 2 3
```

```
"1"
ERROR: Argument: unprocessed values: ["2", "3"]
```

`config echo` displays the value of the first argument using Ruby syntax: it surrounds a string with `"` and add `\` before special characters.

Note: It gets its value after shell command line parsing and `ascli` extended value parsing.

In the following examples (using a POSIX shell, such as `bash`), several equivalent commands are provided. For all example, most special character handling is not specific to `ascli`: It depends on the underlying syntax: shell, JSON, etc... Depending on the case, a different `format` option is used to display the actual value.

For example, in the simple string `Hello World`, the space character is special for the shell, so it must be escaped so that a single value is represented.

Double quotes are processed by the shell to create a single string argument. For POSIX shells, single quotes can also be used in this case, or protect the special character (space) with a backslash.

```
ascli config echo "Hello World" --format=text
ascli config echo 'Hello World' --format=text
ascli config echo Hello\ World --format=text
```

```
Hello World
```

4.2.7 Using a shell variable, parsed by shell, in an extended value

To be evaluated by shell, the shell variable must not be in single quotes. Even if the variable contains spaces it results only in one argument for `ascli` because word parsing is made before variable expansion by shell.

Note: We use a shell variable here: the variable is not necessarily an environment variable (`export`).

```
MYVAR="Hello World"
ascli config echo @json:{"title":"$MYVAR"} --format=json
ascli config echo @json:{\"title\": \"$MYVAR\"} --format=json
{"title": "Hello World"}
```

4.2.8 Double quote in strings in command line

Double quote is a shell special character. Like any shell special character, it can be protected either by preceding with a backslash or by enclosing in a single quote.

```
ascli config echo \"
ascli config echo ' '
"
```

Double quote in JSON is a little tricky because `"` is special both for the shell and JSON. Both shell and JSON syntax allow protecting `"`, but only the shell allows protection using single quote.

```
ascli config echo @json: '\"' --format=text
ascli config echo @json: \"\\\"\\\" --format=text
ascli config echo @ruby: '\"' --format=text
"
```

Here a single quote or a backslash protects the double quote to avoid shell processing, and then an additional `\` is added to protect the `"` for JSON. But as `\` is also shell special, then it is protected by another `\`.

4.2.9 Shell and JSON or Ruby special characters in extended value

Construction of values with special characters is done like this:

- First select a syntax to represent the extended value, e.g. JSON or Ruby
- Write the expression using this syntax, for example, using JSON:

```
{"title": "Test \" ' & \\"}
```

or using Ruby:

```
{"title" => "Test \" ' & \\"}
{'title' => %q{Test \" ' & \\"}}
```

Both `"` and `\` are special characters for JSON and Ruby and can be protected with `\` (unless Ruby's extended single quote notation `%q` is used).

- Then, since the value will be evaluated by shell, any shell special characters must be protected, either using preceding `\` for each character to protect, or by enclosing in single quote:

```
ascli config echo @json:{\"title\\\": \"Test\\ \\\\\"' \\\\\"&\\ \\\\\"}\" --format=json
ascli config echo @json: '{\"title\": \"Test \\\\\"' \\\\\" & \\\\\"}' --format=json
ascli config echo @ruby: \"{ 'title' => %q{Test \\\\\"' \\\\\" & \\\\\"}}\" --format=json

{ \"title\": \"Test \\\\\"' \\\\\" & \\\\\" }
```

4.2.10 Reading special characters interactively

If `ascli` is used interactively (a user typing on terminal), it is easy to require the user to type values:

```
ascli config echo @ruby:"{'title'=>gets.chomp}" --format=json
```

`gets` is Ruby's method of terminal input (terminated by `\n`), and `chomp` removes the trailing `\n`.

4.2.11 Command line arguments from a file

If you need to provide a list of command line argument from lines that are in a file, on Linux you can use the `xargs` command:

```
xargs -a lines.txt -d \\n ascii config echo
```

This is equivalent to execution of:

```
ascli config echo [line1] [line2] [line3] ...
```

If there are spaces in the lines, those are not taken as separator, as we provide option `-d \\n` to `xargs`.

4.2.12 Extended value using special characters read from environmental variables or files

Using a text editor or shell: create a file `title.txt` (and env var) that contains exactly the text required:
Test " ' & \ :

```
export MYTITLE='Test " \'\' & \'\'
echo -n $MYTITLE > title.txt
```

Using those values will not require any escaping of characters since values do not go through shell or JSON parsing.

If the value is to be assigned directly to an option of `ascli`, then you can directly use the content of the file or env var using the `@file:` or `@env:` readers:

```
ascli config echo @file:title.txt --format=text
ascli config echo @env:MYTITLE --format=text
```

Test " ' & \

If the value to be used is in a more complex structure, then the `@ruby:` modifier can be used: it allows any Ruby code in expression, including reading from file or env var. In those cases, there is no character to protect because values are not parsed by the shell, or JSON or even Ruby.

```
ascli config echo @Ruby:"{'title'=>File.read('title.txt')}\" --format=json
ascli config echo @ruby:"{'title'=>ENV['MYTITLE']}\" --format=json
```

```
{"title":"Test \" ' & \\"\"}"
```

4.3 Positional Arguments and Options

Command line arguments are the units of command line typically separated by spaces (the `argv` of C). The tokenization of the command line is typically done by the shell, refer to the previous section [Command Line Parsing](#).

`ascli` handles two types of command line arguments:

- Positional Arguments : position is significant
- Options : only order is significant, but not absolute position

For example:

```
ascli command subcommand --option-name=VAL1 VAL2
```

- Executes Command and its Command Parameters (Positional Arguments): `command subcommand VAL2`
- With one Option: `option_name` and its value: `VAL1`

If the value of a command, option or argument is constrained by a fixed list of values, then it is possible to use a few of the first letters of the value, provided that it uniquely identifies the value. For example `ascli config pre ov` is the same as `ascli config preset overview`.

The value of Options and Positional Arguments is evaluated with the **Extended Value Syntax**.

4.3.1 Positional Arguments

Positional Arguments are either:

- Commands, typically at the beginning
- Command Parameters, mandatory arguments, e.g. creation data or entity identifier

When options are removed from the command line, the remaining arguments are typically Positional Arguments with a pre-defined order.

Commands are typically entity types (e.g. `users`) or verbs (e.g. `create`) to act on those entities. Its value is a String that must belong to a fixed list of values in a given context.

Example:

```
ascli config ascp info
```

- `ascli` is the executable executed by the shell
- `conf` is the first level command: name of the plugin to be used
- `ascp` is the second level command: name of the component (singleton)
- `info` is the third level command: action to be performed

Typically, Commands are located at the beginning of the command line. Order is significant. The provided command must match one of the supported commands in the given context. If wrong, or no command is provided when expected, an error message is displayed and the list of supported commands is displayed.

Standard Commands are: `create`, `show`, `list`, `modify`, `delete`. Some entities also support additional commands. When those additional commands are related to an entity also reachable in another context, then those commands are located below command `do`. For example sub-commands appear after entity selection (identifier), e.g. `ascli aoc admin node do 1234 browse /`: `browse` is a sub-command of `node`.

Command Parameters are typically mandatory values for a command, such as entity creation data or entity identifier.

*Note: It could also have been designed as an option. But since it is mandatory and typically these data do not need to be set in a configuration file, it is better designed as a Command Parameter, rather than as an additional specific option. The advantages of using a Command Parameter instead of an option for the same are that the command line is shorter (no option name, just the position), the value is clearly mandatory and position clearly indicates its role. The disadvantage is that it is not possible to define a default value in a configuration file or environment variable using an option value. Nevertheless, **Extended Values** syntax is supported, so it is possible to retrieve a value from the configuration file (using `@preset:`) or environment variable (using `@env:`).*

If a Command Parameter begins with `-`, then either use the `@val:` syntax (see **Extended Values**), or use the `--` separator (see below).

A few Command Parameters are optional, they are always located at the end of the command line.

4.3.2 Options

All options, e.g. `--log-level=debug`, are command line arguments that:

- Start with `--`
- Have a name, in lowercase, using `-` as word separator in name (e.g. `--log-level=debug`)
- Have a value, separated from name with a `=`
- Can be used by prefix (not recommended), provided that it is unique. E.g. `--log-l=debug` is the same as `--log-level=debug`
- Is optional on command line (it has a default value or no value)

- whose position is not significant, but order is significant

Exceptions:

- Some options accept a short form, e.g. `-Ptoto` is equivalent to `--preset=toto`, refer to the manual or `-h`.
- Some options (flags) don't take a value, e.g. `-N`
- The special option `--` stops option processing and is ignored, following command line arguments are taken as Positional Arguments, including the ones starting with a `-`.

Example:

```
ascli config echo -- --sample
```

```
--sample"
```

Note: Here, `--sample` is taken as an argument, and not as an option, due to `--`.

Options may have a (hard coded) default value.

Options can be placed anywhere on command line and are evaluated in order. Usually the last value evaluated overrides previous values, but some options are cumulative, e.g. `ts`.

Options are typically optional: to change the default behavior. But some are mandatory, so they can be placed in a configuration file, for example: connection information.

The value for any options can come from the following locations (in this order, last value evaluated overrides previous value):

- Configuration file
- Environment variable
- Command line

Environment variable starting with prefix: `ASCLI_` are taken as option values, e.g. `ASCLI_OPTION_NAME` is for `--option-name`.

Option `show_config` dry runs the configuration, and then returns currently set values for options. `ascli --show-config` outputs global options only, and `ascli [plugin] --show-config` outputs global and plugin default options. In addition, option `--show-config` can be added at the end of any full command line, this displays the options that would be used for the command.

A command line argument is typically designed as option if:

- It is optional, or
- It is a mandatory parameter with a default value that would benefit from being set persistently (i.e. in a configuration file or environment variable, e.g. URL and credentials).

4.4 Interactive Input

Some options and Command Parameters are mandatory and other optional. By default, `ascli` will ask for missing mandatory options or Command Parameters for interactive execution.

The behavior can be controlled with:

- `--interactive=<yes|no>` (default=yes if STDIN is a terminal, else no)
 - yes : missing mandatory parameters/arguments are asked to the user
 - no : missing mandatory parameters/arguments raise an error message
- `--ask-options=<yes|no>` (default=no)
 - optional parameters/arguments are asked to user

4.5 Output

Command execution will result in output (terminal, stdout/stderr). The information displayed depends on the action.

To redirect results to a file, use option `output`.

4.5.1 Types of output data

Depending on action, the output will contain:

Result Type	Description
<code>single_object</code>	displayed as a 2 dimensional table: one line per field, first column is field name, and second is field value. Nested hashes are collapsed.
<code>object_list</code>	displayed as a 2 dimensional table: one line per item, one column per field.
<code>value_list</code>	a table with one column.
<code>empty</code>	nothing
<code>status</code>	a message
<code>other_struct</code>	a complex structure that cannot be displayed as an array

4.5.2 Option: `format`

The style of output can be set using the `format` option:

<code>format</code>	Output formatting
<code>table</code>	Text table (default)
<code>text</code>	Value as <code>String</code>
<code>ruby</code>	Ruby code
<code>json</code>	JSON code
<code>jsonpp</code>	JSON pretty printed
<code>yaml</code>	YAML
<code>csv</code>	Comma Separated Values
<code>image</code>	Image URL or Image data

By default, result of type `single_object` and `object_list` are displayed using format `table`.

4.5.3 Option: `table_style`

The table style can be customized with option: `table_style` which expects a `Hash`, options are the ones described in gem [terminal-table](#).

For example, to display a table with thick Unicode borders:

```
ascli config preset over --table-style=@ruby: '{border: :unicode_thick_edge}'
```

| *Note: Other border styles exist, not limited to: `:unicode`, `:unicode_round`.*

4.5.4 Option: `flat_hash`: `.-`-join keys

This option controls how object fields are displayed for complex objects.

Effective only when `format` is `table` to display `single_object` or `object_list`.

If value is `no`, then object's `field` names are only the first level keys of the `Hash` result and values that are `Hash` are displayed as such in Ruby syntax.

If value is `yes` (default), then object are flattened, i.e. deep `Hash` are transformed into 1-level Hash, where keys are `.-`-junction of deep keys. In this case, it is possible to filter fields using the option `fields` using the compound field name using `.-` (dot) as separator.

Example: Result of command is a list of objects with a single object:

```
$ ascli config echo @json: '[{"user":{"id":1,"name":"toto"},"project":"blah"}]'
```

user.id	user.name	project
---------	-----------	---------

1	toto	blah
---	------	------

```
$ ascli config echo @json:'[{"user":{"id":1,"name":"toto"},"project":"blah"}]' --flat-hash=no
```

user	project
{"id"=>1, "name"=>"toto"}	blah

4.5.5 Option: **multi_single**

This option controls if object fields are displayed as columns or lines.

If value is **no** (default), **object_list** are displayed with one object per line, with fields as columns (see above). **single_object** are displayed with one field per line (and columns are: **field**, **value**).

If a **object_list** has a single element, it is possible to have **ascli** display the object as a single object (one field per line instead of columns) with option: **multi_single** set to **single**.

This parameter can be set as a global default with:

```
ascli config preset set GLOBAL multi_single single
```

In case multiple objects are returned, it is possible to display one table per object with option **multi_single** set to **yes**.

```
$ ascli config echo @json:'[{"user":{"id":1,"name":"toto"},"project":"blash"}]'
↪ --multi-single=yes
```

field	value
user.id	1
user.name	toto
project	blash

4.5.6 Option: **display** : Verbosity of output

Output messages are categorized in 3 types:

- **info** output contain additional information, such as number of elements in a table
- **data** output contain the actual output of the command (object, or list of objects)
- **error** output contain error messages

The option **display** controls the level of output:

- **info** displays all messages: **info**, **data**, and **error**
- **data** display **data** and **error** messages
- **error** display only error messages.

4.5.7 Option: **show_secrets** : Hide or show secrets in results

- If value is **no** (default), then secrets are redacted from command results.
- If value is **yes**, then secrets shown in clear in results.
- If **display** is **data**, secrets are included to allow piping results.

4.5.8 Option: **fields** : Selection of output object fields

Depending on the command, results may include by default all fields, or only some selected fields. It is possible to define specific columns to be displayed, by setting the **fields** option.

The **fields** option is a list that can be either a comma separated list or an extended value **Array**.

Individual elements of the list can be:

- `property` : add property to the current list
- `- property` : remove property from the current list
- `DEF` : default list of fields (that's the default, when not set)
- `ALL` : all fields
- A Ruby `RegEx` : using `@ruby: '/.../'`, or `@re:...` add those matching to the list

Examples:

- `a,b,c` : the list of attributes specified as a comma separated list (overrides the all default)
- `@json: '["a","b","c"]'` : `Array` extended value: same as above
- `b,DEF,-a` : default property list, remove `a` and add `b` in first position
- `@ruby: '/^server/'` : Display all fields whose name begin with `server`

4.5.9 Option: `select`

Table output (`object_list`) can be filtered using option `select`. This option is either a `Hash` or `Proc`. The `Proc` takes as argument a line (`Hash`) in the table and is a Ruby lambda expression that shall return `true` to select or `false` to remove an entry.

Example:

```
ascli aoc admin user list --fields=name,email,ats_admin --query=@json: '{"sort": "name"}'
↪ --select=@json: '{"ats_admin": true}'
```

name	email	ats_admin
John Curtis	john@example.com	true
Laurent Martin	laurent@example.com	true

Note: Option `select` filters elements from the result of command, while the `query` option gives filtering parameters to the API when listing elements.

In above example, the same result is obtained with option:

```
--select=@ruby: '->(i){i["ats_admin"]}'
```

4.5.10 Percent selector

The percent selector allows identification of an entity by another unique identifier other than the native identifier.

Syntax: `%<field>:<value>`

When a command is executed on a single entity, the entity is identified by a unique identifier that follows the command. For example, in the following command, `1234` is the user's identifier:

```
ascli aoc admin user show 1234
```

Some commands provide the following capability: If the entity can also be uniquely identified by a name, then the name can be used instead of the identifier, using the percent selector. For example, if the name of the user is `john` and a field for this entity named `name` has a value `john`:

```
ascli aoc admin user show %name:john
```

4.6 Extended Value Syntax

Most options and arguments are specified by a simple string (e.g. `username` or `url`). Sometimes it is convenient to read a value from a file: for example read the PEM value of a private key, or a list of files. Some options expect a more complex value such as `Hash` or `Array`.

The Extended Value Syntax allows to specify such values and even read values from other sources than the command line itself.

The syntax is:

```
<0 or more decoders><some text value or nothing>
```

Decoders act like a function with its parameter on right-hand side and are recognized by the prefix: `@` and suffix `:`

The following decoders are supported:

Decoder	Parameter	Returns	Description
<code>base64</code>	<code>String</code>	<code>String</code>	Decode a base64 encoded string
<code>csvt</code>	<code>String</code>	<code>Array</code>	Decode a titled CSV value
<code>env</code>	<code>String</code>	<code>String</code>	Read from a named env var name, e.g. <code>--password=@env:MYPASSVAR</code>
<code>file</code>	<code>String</code>	<code>String</code>	Read value from specified file (prefix <code>~/</code> is replaced with the users home folder), e.g. <code>--key=@file:~/ssh/mykey</code>
<code>json</code>	<code>String</code>	Any	Decode JSON values (convenient to provide complex structures)
<code>lines</code>	<code>String</code>	<code>Array</code>	Split a string in multiple lines and return an array
<code>list</code>	<code>String</code>	<code>Array</code>	Split a string in multiple items taking first character as separator and return an array
<code>none</code>	None	Nil	A null value
<code>path</code>	<code>String</code>	<code>String</code>	Performs path expansion on specified path (prefix <code>~/</code> is replaced with the users home folder), e.g. <code>--config-file=@path:~/sample_con</code>
<code>preset</code>	<code>String</code>	<code>Hash</code>	Get whole option preset value by name. Sub-values can also be used, using <code>.</code> as separator. e.g. <code>foo.bar</code> is <code>conf[foo][bar]</code>
<code>extend</code>	<code>String</code>	<code>String</code>	Evaluates embedded extended value syntax in string
<code>re</code>	<code>String</code>	<code>Regexp</code>	Ruby Regular Expression (short for <code>@ruby:/.../</code>)
<code>ruby</code>	<code>String</code>	Any	Execute specified Ruby code
<code>secret</code>	None	<code>String</code>	Ask password interactively (hides input)
<code>stdin</code>	None	<code>String</code>	Read from stdin in text mode (no value on right)
<code>stdbin</code>	None	<code>String</code>	Read from stdin in binary mode (no value on right)
<code>uri</code>	<code>String</code>	<code>String</code>	Read value from specified URL, e.g. <code>--fpac=@uri:http://serv/f.pac</code>
<code>val</code>	<code>String</code>	<code>String</code>	Prevent decoders on the right to be decoded. e.g. <code>--key=@val:@file:foo</code> sets the option <code>key</code> to value <code>@file:foo</code> .
<code>yaml</code>	<code>String</code>	Any	Decode YAML
<code>zlib</code>	<code>String</code>	<code>String</code>	Decompress data using Zlib

Note: A few commands support a value of type `Proc` (lambda expression). For example, the `Extended Value` `@ruby:'->(i){i["attr"]}'` is a lambda expression that returns the value for key `attr` of the `Hash` `i`.

To display the result of an extended value, use the `config echo` command.

The `extend` decoder is useful to evaluate embedded extended value syntax in a string. It expects a `@` to close the embedded extended value syntax.

Example: Create a `Hash` value with the convenient `@json:` decoder:

```
ascli config echo @json: '{"key1": "value1", "key2": "value2"}'
```

Example: read the content of the specified file, then, base64 decode, then unzip:

```
ascli config echo @zlib:@base64:@file:myfile.dat
```

Example: Create a `Hash` value with one key and the value is read from a file:

```
ascli config echo @ruby: '{"token_verification_key" => File.read("mykey.txt")}'
```

Example: read a CSV file and create an `Array` of `Hash` for bulk provisioning:

```
cat test.csv
```

```
name,email
lolo,laurent@example.com
toto,titi@tutu.tata
```

```
ascli config echo @csvt:@file:test.csv
```

```
+-----+-----+
| name |      email      |
+-----+-----+
| lolo | laurent@example.com |
| toto | titi@tutu.tata      |
+-----+-----+
```

Example: create a `Hash` with values coming from a preset named `config`

```
ascli config echo @json:@extend: '{"hello": true, "version": "@preset:config.version@"}'
```

field	value
hello	true
version	4.21.1

Example: Create a `Hash` from YAML provided as shell Here document:

```
ascli config echo @yaml:@stdin: --format=json<<EOF
key1: value1
key2:
- item1
- item2
key3:
  key4: value4
  key5: value5
EOF
```

```
 '{"key1": "value1", "key2": ["item1", "item2"], "key3": {"key4": "value4", "key5": "value5"} }'
```

4.7 Configuration and Persistency Folder

`ascli` configuration and persistency files (token cache, file lists, persistency files) are stored by default in `[User's home folder]/.aspera/ascli`.

Note: `[User's home folder]` is found using Ruby's `Dir.home` (`rb_w32_home_dir`). It uses the `HOME` env var primarily, and on MS Windows it also looks at `%HOMEDRIVE%%HOMEPATH%` and `%USERPROFILE%`. `ascli` sets the env var `%HOME%` to the value of `%USERPROFILE%` if set and exists. So, on Windows `%USERPROFILE%` is used as it is more reliable than `%HOMEDRIVE%%HOMEPATH%`.

The configuration folder can be displayed using :

```
ascli config folder
```

```
/Users/kenji/.aspera/ascli
```

It can be overridden using option `home` .

Example (Windows):

```
set ASCII_HOME=C:\Users\Kenji\.aspera\ascli
```

```
ascli config folder
```

```
C:\Users\Kenji\.aspera\ascli
```

When OAuth is used (AoC, Faspex5) `ascli` keeps a cache of generated bearer tokens in folder `persist_store` in configuration folder by default. Option `cache_tokens` (yes/no) allows controlling if OAuth tokens are cached on file system, or generated for each request. The command `config tokens flush` clears that cache. Tokens are kept on disk for a maximum of 30 minutes (`TOKEN_CACHE_EXPIRY_SEC`) and garbage collected after that. When a token has expired, then a new token is generated, either using a `refresh_token` if it is available, or by the default method.

4.8 Temporary files

Some temporary files may be needed during runtime. The temporary folder may be specified with option: `temp_folder` . Temporary files are deleted at the end of execution unless option: `clean_temp` is set to `no` .

4.9 Configuration file

On the first execution of `ascli` , an empty configuration file is created in the configuration folder (`ascli config folder`). There is no mandatory information required in this file. The use of it is optional as any option can be provided on the command line.

Although the file is a standard `YAML` file, `ascli` provides commands to read and modify it using the `config` command.

All options for `ascli` can be set on command line, or by env vars, or using **Option Preset** in the configuration file.

A configuration file provides a way to define default values, especially for authentication options, thus avoiding to always having to specify those options on the command line.

The default configuration file is: `$HOME/.aspera/ascli/config.yaml` (this can be overridden with option `--config-file=path` or its env var).

The configuration file is a catalog of named lists of options, called: **Option Preset**. Then, instead of specifying some common options on the command line (e.g. address, credentials), it is possible to invoke the ones of an **Option Preset** (e.g. `mypreset`) using the option `preset` : `--preset=mypreset` or its shortcut: `-Pmypreset` .

4.9.1 Option Preset

An **Option Preset** is a collection of options and their associated values in a named section in the configuration file.

A named **Option Preset** can be modified directly using `ascli` , which will update the configuration file :

```
ascli config preset set|delete|show|initialize|update <option preset>
```

The command `update` allows the easy creation of **Option Preset** by simply providing the options in their command line format, e.g. :

```
ascli config preset update demo_server --url=ssh://demo.asperasoft.com:33001 --username=asperaweb  
↪ --password=my_password_here --ts=@json: '{"precalculate_job_size":true}'
```

- This creates an **Option Preset** `demo_server` with all provided options.

The command `set` allows setting individual options in an **Option Preset**.

```
ascli config preset set demo_server password my_password_here
```

The command `initialize`, like `update` allows to set several options at once, but it deletes an existing configuration instead of updating it, and expects a **Hash Extended Value**.

```
ascli config preset initialize demo_server @json: '{"url": "ssh://demo.asperasoft.com:33001",  
↪  "username": "asperaweb", "password": "my_pass_here", "ts": {"precalculate_job_size": true}}'
```

A full terminal based overview of the configuration can be displayed using:

```
ascli config preset over
```

A list of **Option Preset** can be displayed using:

```
ascli config preset list
```

A good practice is to not manually edit the configuration file and use modification commands instead. If necessary, the configuration file can be opened in a text editor with:

```
ascli config open
```

Note: This starts the editor specified by env var `EDITOR` if defined.

The former format for commands is still supported:

```
ascli config preset set|delete|show|initialize|update <name>  
ascli config preset over  
ascli config preset list
```

It is possible to load an **Option Preset** from within another **Option Preset** using the `preset` option. For example if `pcommon` is a preset with common options, and `pspecific` is a preset with specific options, then `pspecific` can load `pcommon` using:

```
ascli config preset set pspecific preset pcommon
```

When `pspecific` is loaded, then cumulative option `preset` will be set, and it will also load `pcommon`.

4.9.2 Special Option Preset: `config`

This preset name is reserved and contains a single key: `version`. This is the version of `ascli` which created the file.

4.9.3 Special Option Preset: `default`

This preset name is reserved and contains an array of key-value, where the key is the name of a plugin, and the value is the name of another preset.

When a plugin is invoked, the preset associated with the name of the plugin is loaded, unless the option `--no-default` (or `-N`) is used.

Note: Special plugin name: `config` can be associated with a preset that is loaded initially, typically used for default values.

Operations on this preset are done using regular `config` operations:

```
ascli config preset set default _plugin_name_ _default_preset_for_plugin_  
ascli config preset get default _plugin_name_  
"_default_preset_for_plugin_"
```

4.9.4 Plugin: `config`: Configuration

Plugin `config` provides general commands for `ascli`:

- Option Preset, configuration file operations
- `wizard`
- `vault`
- `ascp`

The default preset for `config` is read for any plugin invocation, this allows setting global options, such as `--log-level` or `--interactive`. When `ascli` starts, it looks for the `default` Option Preset and checks the value for `config`. If set, it loads the options independently of the plugin used.

Note: If no global default is set by the user, `ascli` will use `global_common_defaults` when setting global options (e.g. `config ascp use`)

Note: If you don't know the name of the global preset, you can use `GLOBAL` to refer to it.

Show current default (global) Option Preset (`config` plugin):

```
$ ascli config preset get default config
global_common_defaults
```

```
ascli config preset set GLOBAL version_check_days 0
```

If the default global Option Preset is not set, and you want to use a different name:

```
ascli config preset set GLOBAL version_check_days 0
ascli config preset set default config my_common_defaults
```

4.10 Config sample commands

Note: Add `ascli config` in front of the commands:

```
ascp connect info 'Aspera Connect for Windows'
ascp connect list
ascp connect version 'Aspera Connect for Windows' download 'Windows Installer' --to-folder=.
ascp connect version 'Aspera Connect for Windows' list
ascp connect version 'Aspera Connect for Windows' open documentation
ascp errors
ascp info --sdk-folder=sdk_test_dir
ascp install
ascp install --sdk-folder=sdk_test_dir
ascp install 1.1.3
ascp products list
ascp products use 'IBM Aspera Connect'
ascp show
ascp spec
check_update
coffee
coffee --ui=text
coffee --ui=text --image=@json: '{"text":true,"double":false}'
coffee --ui=text --image=@json: '{"text":true}'
detect https://faspex5.example.com/path
detect https://node.example.com/path
detect https://shares.example.com/path shares
detect https://tst.example.com/path faspio
detect https://tst.example.com/path httpgw
detect my_org aoc
doc
doc transfer-parameters
echo '<svg viewBox="0 0 100 100" xmlns="http://www.w3.org/2000/svg"><circle cx="50" cy="50"
↵ r="50" fill="#006699"/></svg>' --format=image
echo -- --special-string
echo @base64:SGVsbG8gV29ybGQK
echo @csvt:@stdin:
echo @env:USER
echo @json: '[{"user":{"id":1,"name":"foo"},"project":"bar"}]' --multi-single=single
echo @json: '[{"user":{"id":1,"name":"foo"},"project":"bar"}]' --multi-single=yes
echo @lines:@stdin:
echo @list:,1,2,3
echo @secret:
echo @uri:/etc/hosts
echo @uri:file:/etc/hosts
echo @uri:http://ifconfig.me
echo @uri:https://ifconfig.me
```

```

echo @vault:my_preset.password
echo @zlib:@stdin:
echo hello
email_test --notify-to=my_email_external
file
file --logger=syslog --log-level=debug
folder
gem name
gem path
gem version
genkey my_key
genkey my_key 4096
image https://eudemo.asperademo.com/wallpaper.jpg
initdemo
open
plugins create my_command
plugins list
preset delete conf_name
preset initialize conf_name @json: '{"p1": "v1", "p2": "v2"}'
preset list
preset overview
preset set GLOBAL version_check_days 0
preset set conf_name param value
preset set default shares conf_name
preset show conf_name
preset unset conf_name param
preset update conf_name --p1=v1 --p2=v2
proxy_check --fpac=@file:examples/proxy.pac https://eudemo.asperademo.com
  ↪ --proxy-credentials=@list:,user,pass
pubkey @file:my_key
remote_certificate chain https://node.example.com/path
remote_certificate name https://node.example.com/path
remote_certificate only https://node.example.com/path
smtp_settings
tokens flush
transferd install
transferd list
vault create my_label @json: '{"password": "my_password_here", "description": "my secret"}'
vault delete my_label
vault info
vault list
vault show my_label
wizard https://console.example.com/path console
wizard https://faspex4.example.com/path faspex --username=test --password=test
wizard https://faspex5.example.com/path faspex5 --key-path=my_private_key
wizard https://node.example.com/path node --username=test --password=test
wizard https://orch.example.com/path orchestrator --username=test --password=test
wizard https://shares.example.com/path shares --username=test --password=test
wizard my_org aoc --key-path=my_private_key --username=my_user_email
wizard my_org aoc --key-path=my_private_key --username=my_user_email --use-generic-client=yes

```

4.10.1 Format of file

The configuration file is a `Hash` in a YAML file. Example:

```

config:
  version: 0.3.7
default:
  config: cli_default
  server: demo_server
cli_default:
  interactive: no
demo_server:
  url: ssh://demo.asperasoft.com:33001
  username: asperaweb

```

```
password: my_password_here
```

We can see here:

- The configuration was created with `ascli` version 0.3.7
- The default **Option Preset** to load for `server` plugin is: `demo_server`
- The **Option Preset** `demo_server` defines some options: the URL and credentials
- The default **Option Preset** to load in any case is: `cli_default`

Two **Option Presets** are reserved:

- `config` contains a single value: `version` showing the version used to create the configuration file. It is used to check compatibility.
- `default` is reserved to define the default **Option Preset** name used for known plugins.

The user may create as many **Option Preset** as needed. For instance, a particular **Option Preset** can be created for a particular application instance and contain URL and credentials.

Values in the configuration also follow the **Extended Value Syntax**.

*Note: If the user wants to use the **Extended Value Syntax** inside the configuration file, using the `config preset update` command, the user shall use the `@val:` prefix. Example:*

```
ascli config preset set my_aoc_org private_key @val:@file:"$HOME/.aspera/ascli/my_private_key"
```

This creates the **Option Preset**:

```
my_aoc_org:
private_key: "@file:/Users/laurent/.aspera/ascli/my_private_key"
```

So, the key file will be read only at execution time, but not be embedded in the configuration file.

4.10.2 Evaluation order of options

Some options are global, some options are available only for some plugins. (the plugin is the first level command).

Options are loaded using this algorithm:

- If option `--no-default` (or `-N`) is specified, then no default value is loaded for the plugin
- Else it looks for the name of the plugin as key in section `default`, the value is the name of the default **Option Preset** for it, and loads it.
- If option `--preset=<name or extended value hash>` is specified (or `-Pxxxx`), this reads the **Option Preset** specified from the configuration file, or if the value is a `Hash`, it uses it as options values.
- Environment variables are evaluated
- Command line options are evaluated

Options are evaluated in the order of command line.

To avoid loading the default **Option Preset** for a plugin, use: `-N`

On command line, words in option names are separated by a dash (`-`). In configuration file, separator is an underscore. E.g. `--xxx-yyy` on command line gives `xxx_yyy` in configuration file.

The main plugin name is `config`, so it is possible to define a default **Option Preset** for the main plugin with:

```
ascli config preset set cli_default interactive no
```

```
ascli config preset set default config cli_default
```

An **Option Preset** value can be removed with `unset`:

```
ascli config preset unset cli_default interactive
```

Example: Define options using command line:

```
ascli -N --url=_url_here_ --password=my_password_here --username=_name_here_ node --show-config
```

Example: Define options using a `Hash`:

```
ascli -N
↪ --preset=@json: '{"url": "_url_here_", "password": "my_password_here", "username": "_name_here_" }'
↪ node --show-config
```

4.10.3 Wizard

The wizard is a command that asks the user for information and creates an **Option Preset** with the provided information.

It takes an optional argument: the URL of the application, and an option: **query** which allows limiting the detection to a given plugin.

The simplest invocation is:

```
ascli config wizard
```

4.10.4 Example of configuration for a plugin

For Faspex, Shares, Node (including ATS, Aspera Transfer Service), Console, only username/password and URL are required (either on command line, or from configuration file). Those can be usually provided on the command line:

```
ascli shares repo browse / --url=https://10.25.0.6 --username=john --password=my_password_here
```

This can also be provisioned in a configuration file:

- Build **Option Preset**

```
ascli config preset set shares06 url https://10.25.0.6
ascli config preset set shares06 username john
ascli config preset set shares06 password my_password_here
```

This can also be done with one single command:

```
ascli config preset init shares06
↪ @json: '{"url": "https://10.25.0.6", "username": "john", "password": "my_password_here"}'
```

or

```
ascli config preset update shares06 --url=https://10.25.0.6 --username=john
↪ --password=my_password_here
```

- Define this **Option Preset** as the default **Option Preset** for the specified plugin (**shares**)

```
ascli config preset set default shares shares06
```

- Display the content of configuration file in table format

```
ascli config preset overview
```

- Execute a command on the Shares application using default options

```
ascli shares repo browse /
```

4.11 Secret Vault

Secrets (e.g. passwords) are usually command options. They can be provided on command line, env vars, files etc.

For security reasons, those secrets shall not be exposed in clear, either:

- On terminal during input
- In logs
- In command output

Instead, they shall be hidden or encrypted.

Terminal output secret removal is controlled by option **show_secrets** (default: **no**). Log secret removal is controlled by option **log_secrets** (default: **no**). Mandatory command line options can be requested interactively (e.g. password) using option **interactive**. Or it is possible to use extended value **@secret:[name]** to ask for a secret interactively. It is also possible to enter an option as an environment variable, e.g. **ASCLI_PASSWORD** for option **password** and read the env var like this:

```
read -s ASCLI_PASSWORD
export ASCLI_PASSWORD
```


Another possibility is to retrieve values from a secret vault.

The vault is used with options `vault` and `vault_password`.

`vault` shall be a `Hash` describing the vault:

```
{"type": "system", "name": "ascli"}
```

`vault_password` specifies the password for the vault.

Although it can be specified on command line, for security reason you should avoid exposing the secret. For example, it can be securely specified on command line like this:

```
read -s ASCII_VAULT_PASSWORD
export ASCII_VAULT_PASSWORD
```

4.11.1 Vault: System keychain

| *Note: macOS only*

It is possible to manage secrets in macOS keychain (only read supported currently).

```
--vault=@json: '{"type": "system", "name": "ascli"}'
```

4.11.2 Vault: Encrypted file

It is possible to store and use secrets encrypted in a file using option `vault` set to:

```
{"type": "file", "name": "vault.bin"}
```

`name` is the file path, absolute or relative to the configuration folder `ASCLI_HOME`.

4.11.3 Vault: Operations

For this use the `config vault` command.

Then secrets can be manipulated using commands:

- `create`
- `show`
- `list`
- `delete`

```
ascli config vault create mylabel @json: '{"password": "my_password_here", "description": "for this  
↪ account"}'
```

4.11.4 Configuration Finder

When a secret is needed by a sub command, the command can search for existing configurations in the configuration file.

The lookup is done by comparing the service URL and username (or access key).

4.11.5 Securing passwords and secrets

A password can be saved in clear in an **Option Preset** together with other account information (URL, username, etc...). Example:

```
ascli config preset update myconf --url=... --username=... --password=...
```

For a more secure storage one can do:

```
ascli config preset update myconf --url=... --username=... --password=@val:@vault:myconf.password
```

```
ascli config vault create myconf @json: '{"password": "my_password_here"}
```

| *Note: Use `@val:` in front of `@vault:` so that the extended value is not evaluated.*

4.12 Private Key

Some Aspera applications allow the user to be authenticated using [Public Key Cryptography](#):

- for SSH: Server
- for OAuth JWT: AoC, Faspex5, Faspex, Shares

It consists in using a pair of associated keys: a private key and a public key. The same pair can be used for multiple applications. The file containing the private key (key pair) can optionally be protected by a passphrase. If the key is protected by a passphrase, then it will be prompted when used. (some plugins support option `passphrase`)

The following sample commands use the shell variable `KEY_PAIR_PATH` . Set it to the desired safe location of the private key. Typically, located in folder `$HOME/.ssh` or `$HOME/.aspera/ascli` . For example:

```
KEY_PAIR_PATH=~/.aspera/ascli/my_private_key
```

Several methods can be used to generate a key pair.

The format expected for keys is [PEM](#).

If another format is used, such as `DER` , it can be converted to `PEM` , e.g. using `openssl` .

4.12.1 `ascli` for key generation

The generated key is of type `RSA` , by default: `4096` bit. For convenience, the public key is also extracted with extension `.pub` . The key is not passphrase protected.

```
ascli config genkey ${KEY_PAIR_PATH} 4096
```

To display the public key of a private key:

```
ascli config pubkey @file:${KEY_PAIR_PATH}
```

4.12.2 `ssh-keygen`

Both private and public keys are generated, option `-N` is for passphrase.

```
ssh-keygen -t rsa -b 4096 -m PEM -N '' -f ${KEY_PAIR_PATH}
```

4.12.3 `openssl`

To generate a key pair with a passphrase the following can be used on any system:

```
openssl genrsa -passout pass:_passphrase_here_ -out ${KEY_PAIR_PATH} 4096
openssl rsa -pubout -in ${KEY_PAIR_PATH} -out ${KEY_PAIR_PATH}.pub
```

`openssl` is sometimes compiled to support option `-nodes` (no DES, i.e. no passphrase, e.g. on macOS). In that case, add option `-nodes` instead of `-passout pass:_passphrase_here_` to generate a key without passphrase.

If option `-nodes` is not available, the passphrase can be removed using this method:

```
openssl rsa -passin pass:_passphrase_here_ -in ${KEY_PAIR_PATH} -out ${KEY_PAIR_PATH}.no_des
mv ${KEY_PAIR_PATH}.no_des ${KEY_PAIR_PATH}
```

To change (or add) the passphrase for a key do:

```
openssl rsa -des3 -in ${KEY_PAIR_PATH} -out ${KEY_PAIR_PATH}.with_des
mv ${KEY_PAIR_PATH}.with_des ${KEY_PAIR_PATH}
```

4.12.4 Using an application to generate a key pair

Many applications are available, including on internet, to generate key pairs. For example: <https://cryptotools.net/rsagen>

Note: Be careful that private keys are sensitive information, and shall be kept secret (like a password), so using online tools is risky.

4.13 Image and video thumbnails

`ascli` can display thumbnails for images and videos in the terminal. This is available:

- In the `thumbnail` command of `node` when using `gen4/access key` API.
- When using the `show` command of `preview` plugin.
- `coffee` and `image` commands of `config` plugin.
- Any displayed value which is a URL to image can be displayed with option `format` set to `image`

The following options can be specified in the option `image` :

Option	Type	Description
reserve	Integer	Lines reserved to display a status
text	Bool	Display text instead of image
double	Bool	Display double text resolution (half characters)
font_ratio	Float	Font height/width ratio in terminal

```
ascli config image https://eudemo.asperademo.com/wallpaper.jpg --ui=text
↪ --image=@json: '{"text":true}'
```

```
curl -so - https://eudemo.asperademo.com/wallpaper.jpg | ascli config image @stdbin:
```

```
echo -n https://eudemo.asperademo.com/wallpaper.jpg | ascli config image @uri:@stdin:
```

4.14 Graphical Interactions: Browser and Text Editor

Some actions may require the use of a graphical tool:

- A browser for Aspera on Cloud authentication (web auth method)
- A text editor for configuration file edition

By default, `ascli` assumes that a graphical environment is available on Windows, and on other systems, rely on the presence of the `DISPLAY` environment variable. It is also possible to force the graphical mode with option `--ui` :

- `--ui=graphical` forces a graphical environment, a browser will be opened for URLs or a text editor for file edition.
- `--ui=text` forces a text environment, the URL or file path to open is displayed on terminal.

4.15 Logging, Debugging

The gem is equipped with traces, mainly for debugging and learning APIs. By default, logging level is `warn` and the output channel is `stderr`. To increase debug level, use option `log_level` (e.g. using command line `--log-level=xx`, env var `ASCLI_LOG_LEVEL`, or an `Option Preset`).

By default, passwords and secrets are redacted from logs. Set option `log_secrets` to `yes` to include secrets in logs.

Option `logger`: `stdout`, `stderr`, `syslog`.

Option `log_level`: `debug`, `info`, `warn`, `error`.

Note: When using the `direct` agent (`ascp`), additional transfer logs can be activated using `ascp` options and `ascp_args`, see `direct`.

Examples:

- Display debugging log on `stdout` :

```
ascli config pre over --log-level=debug --logger=stdout
```

- Log errors to `syslog` :

```
ascli config pre over --log-level=error --logger=syslog
```

When `ascli` is used interactively in a shell, the shell itself will usually log executed commands in the history file.

4.16 Learning Aspera Product APIs (REST)

`ascli` uses mainly REST APIs to interact with Aspera applications.

To get traces of execution, with dump of API calls, use argument : `--log-level=debug`.

To display HTTP/S traffic set option `log_level` to `trace2`: `--log-level=trace2`. It will display the exact content of HTTP requests and responses.

4.17 HTTP socket parameters

To ignore SSL certificate for any address/port, use option: `insecure`, i.e. `--insecure=yes`. To ignore SSL certificate for a list of specific address/port, use option `ignore_certificate`, set to an Array of URL for which certificate will be ignored (only the address and port are matched), e.g. `--ignore-certificate=@list:,https://127.0.0.1:9092`

| *Note: Ignoring certificate also applies to `ascp` WSS.*

Ignoring a certificate is not recommended, it is better to add the certificate to the trusted store. So, a warning is displayed when a certificate is ignored. To disable the warning, use option `silent_insecure` set to `no`.

HTTP connection parameters (not `ascp` WSS) can be adjusted using option `http_options`:

Parameter	Default	Where
<code>read_timeout</code>	60	ruby
<code>write_timeout</code>	60	ruby
<code>open_timeout</code>	60	ruby
<code>keep_alive_timeout</code>	2	ruby
<code>user_agent</code>	<code>ascli</code>	<code>ascli</code>
<code>download_partial_suffix</code>	<code>.http_partial</code>	<code>ascli</code>
<code>retry_on_error</code>	0	<code>ascli</code>
<code>retry_sleep</code>	<code>nil</code>	<code>ascli</code>

Time values are in set seconds and can be of type either `Integer` or `Float`. Default values are the ones of Ruby: For a full list, refer to the Ruby library: [Net::HTTP](#).

Like any other option, those can be set either on command line, or in configuration file, either in a global preset or server-specific one.

Example:

```
ascli aoc admin package list --http-options=@json: '{"read_timeout":10.0}'
```

4.18 Proxy

There are several types of network connections, each of them use a different mechanism to define a (forward) proxy:

- REST calls (APIs) and HTTP Gateway
- `ascp` WSS and Legacy Aspera HTTP/S Fallback
- `ascp` SSH and UDP (Aspera FASP)

Refer to the following sections.

4.18.1 Proxy for REST and HTTP Gateway

REST API calls and transfers based on HTTP Gateway both use Ruby's `Net::HTTP` class. Refer to [Ruby find proxy](#).

When Ruby HTTP is used, there are two possibilities to define an HTTP proxy to be used.

The `http_proxy` environment variable (lower case) can be set to the URL of the proxy (with optional credentials). Syntax is: `(http|https)://[user:password@]host:port` . E.g. `http://myproxy.org.net:3128` .

Note: Ruby expects a URL and `myproxy.org.net:3128` alone is not valid.

Credentials for proxy are optional but can also be specified:

```
export http_proxy=http://user:password@proxy.example.com:3128
```

Option `http_proxy` does the same (set env var) but on command line:

```
ascli --http-proxy=http://username:password@host:port ...
```

Alternatively, the `fpac` option (function for proxy auto config) can be set to a [Proxy Auto Configuration \(PAC\)](#) JavaScript value.

Note that proxy credentials are not supported in PAC files.

To read the script from a URL (`http:` , `https:` and `file:`), use prefix: `@uri:` . A minimal script can be specified to define the use of a local proxy:

```
ascli --fpac='function FindProxyForURL(url, host){return "PROXY localhost:3128"}' ...
```

The result of a PAC file can be tested with command: `config proxy_check` . Example, using command line option:

```
ascli config proxy_check --fpac='function FindProxyForURL(url, host) {return "PROXY  
↪ proxy.example.com:3128;DIRECT";}' http://example.com
```

```
PROXY proxy.example.com:1234;DIRECT
```

```
ascli config proxy_check --fpac=@file:./proxy.pac http://www.example.com
```

```
PROXY proxy.example.com:8080
```

```
ascli config proxy_check --fpac=@uri:http://server/proxy.pac http://www.example.com
```

```
PROXY proxy.example.com:8080
```

If the proxy found with the PAC requires credentials, then use option `proxy_credentials` with username and password provided as an `Array` :

```
ascli --proxy-credentials=@json:'["__username_here__","__password_here__"]' ...
```

```
ascli --proxy-credentials=@list:__:__username_here__:__password_here__ ...
```

4.18.2 Proxy for Legacy Aspera HTTP/S Fallback

Only supported with the `direct` agent: To specify a proxy for legacy HTTP fallback, use `ascp` native option `-x` and `ascp_args` : `--transfer-info=@json:'{"ascp_args":["-x","url_here"]}'` .

4.18.3 FASP proxy (forward) for transfers

To specify a FASP proxy (forward), set the `transfer-spec` parameter: `proxy` (only supported with the `direct` agent).

For example, for an Aspera forward proxy not encrypted (HTTP) without authentication running on port 9091, the option would be:

```
--ts=@json:'{"proxy":"dnat://proxy.example.org:9091"}'
```

Or, alternatively, (prefer transfer spec like above, generally):

```
--transfer-info=@json:'{"ascp_args":["--proxy","dnat://proxy.example.org:9091"]}'
```

4.19 FASP configuration

`ascli` uses one of the transfer agents to execute transfers.

By default, it uses the `direct` agent, which is basically a local `ascp`. Nevertheless, `ascli` does not come with `ascp` installed. This is the reason why it is advised to install the Aspera Transfer SDK during installation (`ascli config ascp install`).

By default, `ascli` uses the `ascp` binary found in well known locations, i.e. typical Aspera product installation paths.

The way to specify the location of `ascp` is to use either options:

- `ascp_path`
- `use_product`

The `config` plugin allows finding and specifying the location of `ascp`. It provides the following commands for `ascp` sub-command:

- `show` : shows the path of `ascp` used
- `use` : specify the `ascp` path to use
- `products` : list Aspera transfer products available locally
- `connect` : list and download connect client versions available on internet

4.19.1 Show path of currently used `ascp`

```
ascli config ascp show
```

```
/Users/laurent/.aspera/ascli/sdk/ascp
```

```
ascli config ascp info
```

field	value
ascp	/Users/john/.aspera/sdk/ascp
...	

4.19.2 Selection of `ascp` location for `direct` agent

By default, `ascli` uses any found local product with `ascp`, including Transfer SDK.

To override and use an alternate `ascp` path use option `ascp_path` (`--ascp-path=`)

For a permanent change, the command `config ascp use` sets the same option for the global default.

Using a POSIX shell:

```
ascli config ascp use @path: '~/Applications/Aspera CLI/bin/ascp'
```

```
ascp version: 4.0.0.182279
```

```
Updated: global_common_defaults: ascp_path <- /Users/laurent/Applications/Aspera CLI/bin/ascp
```

```
Saved to default global preset global_common_defaults
```

Windows:

```
ascli config ascp use C:\Users\admin\.aspera\ascli\sdk\ascp.exe
```

```
ascp version: 4.0.0.182279
```

```
Updated: global_common_defaults: ascp_path <- C:\Users\admin\.aspera\ascli\sdk\ascp.exe
```

```
Saved to default global preset global_common_defaults
```

If the path has spaces, read section: [Shell and Command line parsing](#).

If option `ascp_path` is not set, then the product identified with option `use_product` is used.

If `use_product` is not set, then the first product found is used, this is equivalent to using option: `--use-product=FIRST`.

Locally installed Aspera products can be listed with:

```
ascli config ascp products list
```

name	app_root
IBM Aspera SDK	/Users/laurent/.aspera/ascli/sdk
Aspera Connect	/Applications/Aspera Connect.app
IBM Aspera CLI	/Users/laurent/Applications/Aspera CLI
IBM Aspera High-Speed Transfer Server	/Library/Aspera

Using the option `use_product` finds the `ascp` binary of the selected product.

To permanently use the `ascp` of a product:

```
ascli config ascp products use 'Aspera Connect'
saved to default global preset /Users/laurent/Applications/Aspera
  ↳ Connect.app/Contents/Resources/ascp
```

4.19.3 Installation of Connect Client on command line

```
ascli config ascp connect list
```

id	title	version
urn:uuid:589F9EE5-0489-4F73-9982-A612FAC70C4E	Aspera Connect for Windows	3.11.2.63
urn:uuid:A3820D20-083E-11E2-892E-0800200C9A66	Aspera Connect for Windows 64-bit	3.11.2.63
urn:uuid:589F9EE5-0489-4F73-9982-A612FAC70C4E	Aspera Connect for Windows XP	3.11.2.63
urn:uuid:55425020-083E-11E2-892E-0800200C9A66	Aspera Connect for Windows XP 64-bit	3.11.2.63
urn:uuid:D8629AD2-6898-4811-A46F-2AF386531BFF	Aspera Connect for Mac Intel	3.11.2.63
urn:uuid:97F94DF0-22B1-11E2-81C1-0800200C9A66	Aspera Connect for Linux 64	3.11.2.63

```
ascli config ascp connect version 'Aspera Connect for Mac Intel' list
```

title	type	href
Mac Intel Installer	application/octet-stream	bin/IBMASperaConnectInstaller-3.11.2.63.dmg
Mac Intel Installer	application/octet-stream	bin/IBMASperaConnectInstallerOneClick-3.11.2.63.dmg
Aspera Connect for Mac HTML Documentation	text/html	https://www.ibm.com/docs/en/aspera-connect/3.11?topic=aspera-connect-user-guide-macos
Aspera Connect for Mac Release Notes	text/html	https://www.ibm.com/docs/en/aspera-connect/3.11?topic=notes-release-aspera-connect-3112

```
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
↔ -----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
↔ -----+
```

```
ascli config ascp connect version 'Aspera Connect for Mac Intel' download enclosure --to-folder=.
Time: 00:00:02 ===== 100% 27766 KB/sec Time: 00:00:02
Downloaded: IBMAsperaConnectInstaller-3.11.2.63.dmg
```

4.20 Transfer Clients: Agents

Some actions on Aspera Applications lead to file transfers (upload and download) using the FASP protocol (`ascp`). Transfers will be executed by a transfer client, here called Transfer Agent.

The following agents are supported and selected with option `transfer` :

<code>transfer</code>	location	Description of agent
<code>direct</code>	local	direct execution of <code>ascp</code>
<code>transferd</code>	local	Aspera Transfer Daemon
<code>connect</code>	local	Aspera Connect Client
<code>desktop</code>	local	Aspera for Desktop
<code>node</code>	remote	Aspera Transfer Node
<code>httpgw</code>	remote	Aspera HTTP Gateway

Note: All transfer operations are seen from the point of view of the agent. For example, an agent executing an upload, or package send operation will effectively push files to the related server from the system where the agent runs.

All above agents (including `direct`) receive transfer parameters as a `transfer-spec`. Parameters in transfer-spec can be modified with option `ts` .

Specific options for agents are provided with option `transfer_info` .

Note: Parameters in `transfer_info` are specific for each agent type and are described in the agents respective sections.

4.20.1 Agent: Direct

The `direct` agent directly executes a local `ascp` in `ascli` . This is the default agent for `ascli` (option `--transfer=direct`). `ascli` will locally search installed Aspera products, including SDK, and use `ascp` from that component. Refer to section **FASP**.

The `transfer_info` option accepts the following optional parameters to control multi-session, Web Socket Session, Resume policy and add any argument to `ascp` :

Name	Type	Description
<code>wss</code>	<code>Bool</code>	Web Socket SessionEnable use of web socket session in case it is availableDefault: <code>true</code>
<code>quiet</code>	<code>Bool</code>	If <code>true</code> , then <code>ascp</code> progress bar is not shown.Default: <code>false</code>
<code>trusted_certs</code>	<code>Array</code>	List of repositories for trusted certificates.
<code>client_ssh_key</code>	<code>String</code>	SSH Keys to use for token-based transfers. One of: <code>dsa_rsa</code> , <code>rsa</code> , <code>per_client</code> . Default: <code>rsa</code>
<code>ascp_args</code>	<code>Array</code>	Array of strings with native <code>ascp</code> arguments.Default: <code>[]</code>

Name	Type	Description
<code>spawn_timeout_sec</code>	Float	Multi sessionVerification time that <code>ascp</code> is runningDefault: <code>3</code>
<code>spawn_delay_sec</code>	Float	Multi sessionDelay between startup of sessionsDefault: <code>2</code>
<code>multi_incr_udp</code>	Bool	Multi SessionIncrement UDP port on multi-sessionIf <code>true</code> , each session will have a different UDP port starting at <code>fasp_port</code> (or default 33001)Else, each session will use <code>fasp_port</code> (or <code>ascp</code> default)Default: <code>true</code> on Windows, else <code>false</code>
<code>resume</code>	Hash	Resume parameters. See below
<code>resume.iter_max</code>	Integer	Max number of retry on errorDefault: <code>7</code>
<code>resume.sleep_initial</code>	Integer	First Sleep before retryDefault: <code>2</code>
<code>resume.sleep_factor</code>	Integer	Multiplier of sleep period between attemptsDefault: <code>2</code>
<code>resume.sleep_max</code>	Integer	Default: <code>60</code>
<code>monitor</code>	Bool	Use management port.Default: <code>true</code>

In case of transfer interruption, the agent will `resume` a transfer up to `iter_max` time. Sleep between iterations is given by the following formula where `iter_index` is the current iteration index, starting at 0:

```
max( sleep_max, sleep_initial * sleep_factor ^ iter_index )
```

To display the native progress bar of `ascp`, use `--progress-bar=no --transfer-info=@json:'{"quiet":false}'`.

To skip usage of management port (which disables custom progress bar), set option `monitor` to `false`. In that, use the native progress bar: `--transfer-info=@json:'{"monitor":false,"quiet":false}'`

By default, Ruby's root CA store is used to validate any HTTPS endpoint used by `ascp` (e.g. WSS). In order to use a custom certificate store, use the `trusted_certs` option of direct agent's option `transfer_info`. To use `ascp`'s default, use option: `--transfer-info=@json:'{"trusted_certs":null}'`.

Some transfer errors are considered `retry-able` (e.g. timeout) and some other not (e.g. wrong password). The list of known protocol errors and retry level can be listed:

```
ascli config ascp errors
```

Examples:

```
ascli ... --transfer-info=@json:'{"wss":true,"resume":{"iter_max":20}}'
ascli ... --transfer-info=@json:'{"spawn_delay_sec":2.5,"multi_incr_udp":false}'
```

This can be useful to activate logging using option `-L` of `ascp`. For example, to activate debug level 2 for `ascp` (`DD`), and display those logs on the terminal (`-`):

```
--transfer-info=@json:'{"ascp_args":["-DDL-"]}'
```

This is useful to debug if a transfer fails.

To store `ascp` logs in file `aspera-scp-transfer.log` in a folder, use `--transfer-info=@json:'{"ascp_args":["-DDL-"]}'`.

Note: When transfer agent `direct` is used, the list of files to transfer is provided to `ascp` using either `--file-list` or `--file-pair-list` and a file list (or pair) file generated in a temporary folder. (unless `--file-list` or `--file-pair-list` is provided using `transfer_info` parameter `ascp_args`).

In addition to standard methods described in section [File List](#), it is possible to specify the list of file using those additional methods:

- Using option `transfer_info` parameter `ascp_args`

```
--sources=@ts --transfer-info=@json: '{"ascp_args":["--file-list","myfilelist"]}'
```

Note: File lists is shown here, there are also similar options for file pair lists.

Note: Those 2 additional methods avoid the creation of a copy of the file list: if the standard options `--sources=@lines:@file:... --src-type=...` are used, then the file is list read and parsed, and a new file list is created in a temporary folder.

*Note: Those methods have limitations: they apply only to the **direct** transfer agent (i.e. local `ascp`) and not for Aspera on Cloud.*

This agent supports a local configuration file: `aspera.conf` where Virtual links can be configured:

On a server (HSTS), the following commands can be used to set a global virtual link:

```
asconfigurator -x 'set_trunk_data;id,1;trunk_name,in;trunk_capacity,45000;trunk_on,true'
asconfigurator -x 'set_trunk_data;id,2;trunk_name,out;trunk_capacity,45000;trunk_on,true'
asconfigurator -x 'set_node_data;transfer_in_bandwidth_aggregate_trunk_id,1'
asconfigurator -x 'set_node_data;transfer_out_bandwidth_aggregate_trunk_id,2'
```

But this command is not available on clients, so edit the file `aspera.conf`, you can find the location with: `ascli config ascp info --fields=aspera_conf` and modify the sections `default` and `trunks` like this for a global 100 Mbps virtual link:

```
<?xml version='1.0' encoding='UTF-8'?>
<CONF version="2">
  <default>
    <transfer>
      <in>
        <bandwidth>
          <aggregate>
            <trunk_id>1</trunk_id>
          </aggregate>
        </bandwidth>
      </in>
      <out>
        <bandwidth>
          <aggregate>
            <trunk_id>2</trunk_id>
          </aggregate>
        </bandwidth>
      </out>
    </transfer>
  </default>
  <trunks>
    <trunk>
      <id>1</id>
      <name>in</name>
      <on>true</on>
      <capacity>
        <schedule format="ranges">1000000</schedule>
      </capacity>
    </trunk>
    <trunk>
      <id>2</id>
      <name>out</name>
      <capacity>
        <schedule format="ranges">1000000</schedule>
      </capacity>
      <on>true</on>
    </trunk>
  </trunks>
</CONF>
```

It is also possible to set a schedule with different time and days, for example for the value of `schedule` :

```
start=08 end=19 days=mon,tue,wed,thu capacity=900000;1000000
```

4.20.2 Agent: Connect Client

By specifying option: `--transfer=connect`, `ascli` will start transfers using the locally installed IBM Aspera Connect Client. There are no option for `transfer_info` .

4.20.3 Agent: Desktop Client

By specifying option: `--transfer=desktop`, `ascli` will start transfers using the locally installed IBM Aspera Desktop Client. There are no option for `transfer_info` .

4.20.4 Agent: Node API

By specifying option: `--transfer=node`, `ascli` starts transfers in an Aspera Transfer Server using the Node API, either on a local or remote node. This is especially useful for direct node-to-node transfers.

Parameters provided in option `transfer_info` are:

Parameter	Type	Description
<code>url</code>	String	URL of the Node API Mandatory
<code>username</code>	String	Node API user or access key Mandatory
<code>password</code>	String	Password, secret or bearer token Mandatory
<code>root_id</code>	String	Root file ID Mandatory only for bearer token

Like any other option, `transfer_info` can get its value from a pre-configured **Option Preset** :

```
--transfer-info=@preset:_name_here_
```

or be specified using the extended value syntax :

```
--transfer-info=@json: '{"url": "https://...", "username": "_user_here_", "password": "my_password_here"}'
```

If `transfer_info` is not specified and a default node has been configured (name in `node` for section `default`) then this node is used by default.

If the `password` value begins with `Bearer` then the `username` is expected to be an access key and the parameter `root_id` is mandatory and specifies the file ID of the top folder to use on the node using this access key. It can be either the access key's root file ID, or any authorized file ID underneath it.

4.20.5 Agent: HTTP Gateway

The Aspera HTTP Gateway is a service that allows to send and receive files using HTTPS.

By specifying option: `--transfer=httpgw`, `ascli` will start transfers using the Aspera HTTP Gateway.

Parameters provided in option `transfer_info` are:

Name	Type	Description
<code>url</code>	String	URL of the HTTP GW Mandatory
<code>upload_chunk_size</code>	Integer	Size in bytes of chunks for upload Default: <code>64000</code>
<code>api_version</code>	String	Force use of version (<code>v1</code> , <code>v2</code>) Default: <code>v2</code>
<code>synchronous</code>	Bool	Wait for each message acknowledgment Default: <code>false</code>

Example:

```
ascli faspex package recv 323 --transfer=httpgw
↪ --transfer-info=@json: '{"url": "https://asperagw.example.com:9443/aspera/http-gwy"}'
```

Note: The gateway only supports transfers authorized with a token.

If the application, e.g. AoC or Faspex 5, is configured to use the HTTP Gateway, then `ascli` will automatically use the gateway URL if `--transfer=httpgw` is specified, so `transfer_info` becomes optional.

4.20.6 Agent: Transfer SDK

Another possibility is to use the Transfer SDK daemon (`asperatransferd`). Set option `transfer` to `transferd`.

Options for `transfer_info` are:

Name	Type	Description
<code>url</code>	<code>String</code>	IP address and port listened by the daemonMandatoryDefault: <code>:0</code>
<code>start</code>	<code>Bool</code>	Start a new daemon.Default: <code>true</code>
<code>stop</code>	<code>Bool</code>	Stop daemon when exiting <code>ascli</code> Default: <code>true</code>

Note: If port zero is specified in the URL, then the daemon will listen on a random available port. If no address is specified, then `127.0.0.1` is used.

The gem `grpc` was removed from dependencies, as it requires compilation of a native part. So, to use the Transfer SDK you should install this gem:

```
gem install grpc
```

On Windows the compilation may fail for various reasons (3.1.1):

- `cannot find -lx64-ucrt-ruby310`
→ copy the file `[Ruby main dir]\lib\libx64-ucrt-ruby310.dll.a` to `[Ruby main dir]\lib\libx64-ucrt-` (remove the `dll` extension)
- `conflicting types for 'gettimeofday'`
→ edit the file `[Ruby main dir]/include/ruby-[version]/ruby/win32.h` and change the signature of `gettimeofday` to `gettimeofday(struct timeval *, void *)`, i.e. change `struct timezone` to `void`

4.21 Transfer Specification

Some commands lead to file transfer (upload/download). All parameters necessary for this transfer are described in a [transfer-spec](#) (Transfer Specification), such as:

- Server address
- Transfer username
- Credentials
- File list
- Etc...

`ascli` builds the [transfer-spec](#) internally as a `Hash`. It is not necessary to provide additional parameters on the command line for this transfer.

It is possible to modify or add any of the supported [transfer-spec](#) parameter using the `ts` option. The `ts` option accepts a `Hash Extended Value` containing one or several [transfer-spec](#) parameters. Multiple `ts` options on command line are cumulative, and the `Hash` value is deeply merged. To remove a (deep) key from transfer spec, set the value to `null`.

Note: Default transfer spec values can be displayed with command: `config ascp info --flat-hash=no` under field `ts`.

It is possible to specify `ascp` options when the `transfer` option is set to `direct` using `transfer_info` option parameter: `ascp_args`. Example: `--transfer-info=@json: '{"ascp_args":["-l", "100m"]}'`. This is especially useful for `ascp` command line parameters not supported in the transfer spec.

The use of a `transfer-spec` instead of `ascp` command line arguments has the advantage of:

- Common to all **Transfer Agent**
- Not dependent on command line limitations (special characters...)

4.22 Transfer Parameters

All standard `transfer-spec` parameters can be specified. A `transfer-spec` can also be saved/overridden in the configuration file.

References:

- [Aspera Node API Documentation](#) → /opt/transfers
- [Aspera Transfer SDK Documentation](#) → Guides → API Ref → Transfer Spec V1
- [Aspera Connect SDK](#) → search `The parameters for starting a transfer.`

Parameters can be displayed with commands:

```
ascli config ascp spec
ascli config ascp spec --select=@json: '{"d": "Y"}' --fields=-d,n,c
```

Columns:

- D=Direct (local `ascp` execution)
- N=Node API
- C=Connect Client
- T=Transfer SDK
- H=HTTP Gateway

`ascp` argument or environment variable is provided in description.

Field	Type	D	N	D	T	H	C	Description
apply_local_docroot	bool	Y		Y				Apply local docroot to source paths.(--apply-local-docroot)
authentication	string						Y	value=token for SSH bypass keys, else password asked if not provided.(<code><ignored></code>)
cipher	string	Y	Y	Y	Y	Y	Y	In transit encryption type.Allowed values: none, aes-128, aes-192, aes-256, aes-128-cfb, aes-192-cfb, aes-256-cfb, aes-128-gcm, aes-192-gcm, aes-256-gcm(-c (conversion){enum})
cipher_allowed	string	Y	Y	Y	Y	Y	Y	returned by node API. Valid literals include "aes-128" and "none".(<code><ignored></code>)
compression	int							ascp4 only, 0 / 1?(<code><ignored></code>)
content_protection	string	Y	Y	Y	Y	Y	Y	Enable client-side encryption at rest. (CSEAR, content protection)Allowed values: encrypt, decrypt(--file-crypt {enum})
content_protection_password	string	Y	Y	Y	Y	Y	Y	Specifies CSEAR password. (content protection)(env:ASPERA_SCP_FILEPASS)
cookie	string	Y	Y	Y	Y	Y	Y	Metadata for transfer specified by application(env:ASPERA_SCP_COOKIE)
create_dir	bool	Y	Y	Y	Y	Y	Y	Specifies whether to create new directories.(<code>-d</code>)

Field	Type	D	N	D	T	H	C	Description
delete_before_transfer	bool	Y	Y	Y	Y	Y	Y	Before transfer, delete files that exist at the destination but not at the source. The source and destination arguments must be directories that have matching names. Objects on the destination that have the same name but different type or size as objects on the source are not deleted. (--delete-before-transfer)
delete_source	bool	Y	Y	Y				Remove SRC files after transfer success (--remove-after-transfer)
destination_root	string	Y	Y	Y	Y	Y	Y	Destination root directory. (<special>)
destination_root_id	string							The file ID of the destination root directory. Required when using Bearer token auth for the destination node. (<ignored>)
dgram_size	int	Y	Y	Y	Y	Y	Y	UDP datagram size in bytes (-Z {int})
direction	string	Y	Y	Y	Y	Y	Y	Direction of transfer (on client side) Allowed values: send, receive (--mode (conversion){enum})
exclude_newer_than	string	Y	Y	Y	Y	Y	Y	Exclude files, but not directories, from the transfer if they are newer than the specified number of seconds added to the source computer's epoch. e.g. "-86400" for newer than a day back. (--exclude-newer-than {string})
exclude_older_than	string	Y	Y	Y	Y	Y	Y	Exclude files, but not directories, from the transfer if they are older than the specified number of seconds added to the source computer's epoch. e.g. "-86400" for older than a day back. (--exclude-older-than {string})
fasp_port	int	Y	Y	Y	Y	Y	Y	Specifies fasp (UDP) port. (-O {int})
fasp_url	string							Only used in Faspex. (<ignored>)
file_checksum	string	Y	Y	Y				Enable checksum reporting for transferred files by specifying the hash to use. Allowed values: sha-512, sha-384, sha-256, sha1, md5, none (<ignored>)
http_fallback	boolstring	Y	Y	Y	Y	Y	Y	When true(1), attempts to perform an HTTP transfer if a FASP transfer cannot be performed. (-y (conversion){bool}{{string}})
http_fallback_port	int	Y		Y				Specifies http port when no cipher is used (-t {int})
https_fallback_port	int	Y	Y	Y	Y	Y	Y	Specifies https port when cipher is used (-t {int})
keepalive	bool	Y		Y				The session is running in persistent session mode. (--keepalive)
lock_min_rate	bool	Y	Y	Y	Y	Y	Y	TODO: remove ? (<ignored>)
lock_min_rate_kbps	bool						Y	If true, lock the minimum transfer rate to the value set for min_rate_kbps. If false, users can adjust the transfer rate up to the value set for target_rate_cap_kbps. (<ignored>)
lock_rate_policy	bool						Y	If true, lock the rate policy to the default value. (<ignored>)
lock_target_rate	bool	Y	Y	Y	Y	Y	Y	TODO: remove ? (<ignored>)

Field	Type	D	N	D	T	H	C	Description
lock_target_rate_kbps	bool	Y	Y	Y	Y	Y	Y	If true, lock the target transfer rate to the default value set for target_rate_kbps.If false, users can adjust the transfer rate up to the value set for target_rate_cap_kbps.(<i><ignored></i>)
min_rate_cap_kbps	int	Y	Y	Y	Y	Y	Y	The highest minimum rate that an incoming transfer can request, in kilobits per second.Client minimum rate requests that exceed the minimum rate cap are ignored.The default value of unlimited applies no cap to the minimum rate. (Default: 0)(<i><ignored></i>)
min_rate_kbps	int	Y	Y	Y	Y	Y	Y	Set the minimum transfer rate in kilobits per second.(-m {int})
move_after_transfer	string	Y	Y	Y				The relative path to which the files will be moved after the transfer at the source side. Available as of 3.8.0.(--move-after-transfer {string})
multi_session	int	Y	Y	Y	Y	Y	Y	Use multi-session transfer. max 128.Each participant on one host needs an independent UDP (-O) port.Large files are split between sessions only when transferring with resume_policy=none.(<i><special></i>)
multi_session_threshold	int	Y	Y	Y				Split files across multiple ascp sessions if their size in bytes is greater than or equal to the specified value.(0=no file is split)(--multi-session-threshold {int})
obfuscate_file_names	bool					Y		HTTP Gateway obfuscates file names when set to true.(<i><ignored></i>)
overwrite	string	Y	Y	Y	Y	Y	Y	Overwrite destination files with the source files of the same name.Allowed values: never, always, diff, older, diff+older(--overwrite {enum})
password	string		Y					Password for local Windows user when transfer user associated with node api user is not the same as the one running asperanoded.Allows impersonating the transfer user and have access to resources (e.g. network shares).Windows only, node api only.(<i><ignored></i>)
paths	array	Y	Y	Y	Y	Y	Y	Array of path to the source (required) and a path to the destination (optional).(<i><special></i>)
precalculate_job_size	bool	Y	Y	Y	Y	Y	Y	Specifies whether to precalculate the job size.(--precalculate-job-size)
preserve_access_time	bool	Y	Y	Y	Y	Y	Y	Preserve the source-file access timestamps at the destination.Because source access times are updated by the transfer operation,the timestamp that is preserved is the one just before to the transfer.(--preserve-access-time)
preserve_acls	string	Y		Y				Preserve access control lists.Allowed values: none, native, metafile(--preserve-acls {enum})

Field	Type	D	N	D	T	H	C	Description
preserve_creation_time	bool	Y	Y	Y	Y	Y	Y	(Windows only) Preserve source-file creation timestamps at the destination. Only Windows systems retain information about creation time. If the destination is not a Windows computer, this option is ignored. (--preserve-creation-time)
preserve_extended_attrs	string							Preserve the extended attributes. Allowed values: none, native, metafile(--preserve-xattrs {enum})
preserve_file_owner_gid	bool	Y		Y				Preserve the group ID for a file owner(--preserve-file-owner-gid)
preserve_file_owner_uid	bool	Y		Y				Preserve the user ID for a file owner(--preserve-file-owner-uid)
preserve_modification_time	bool	Y	Y	Y	Y	Y	Y	Set the modification time, the last time a file or directory was modified (written), of a transferred file to the modification of the source file or directory. Preserve source-file modification timestamps at the destination. (--preserve-modification-time)
preserve_remote_acls	string	Y		Y				Preserve remote access control lists. Allowed values: none, native, metafile(--remote-preserve-acls {enum})
preserve_source_access_time	bool	Y		Y				Preserve the time logged for when the source file was accessed(--preserve-source-access-time)
preserve_times	bool		Y					Preserve file timestamps. (--preserve-times)
proxy	string	Y		Y				Specify the address of the Aspera high-speed proxy server. dnats://[user[:password]]@server:port Default ports for DNAT and DNATS protocols are 9091 and 9092. Password, if specified here, overrides the value of environment variable ASPERA_PROXY_PASS. (--proxy {string})
rate_policy	string	Y	Y	Y	Y	Y	Y	The transfer rate policy to use when sharing bandwidth. Allowed values: low, fair, high, fixed(--policy {enum})
rate_policy_allowed	string						Y	Specifies most aggressive rate policy that is allowed. Returned by node API. Allowed values: low, fair, high, fixed(<ignored>) ascp4 only(<ignored>)
read_threads	int							
remote_access_key	string							The access key ID of the access key that was used to construct the bearer token that is used to authenticate to the remote node. (<ignored>)
remote_host	string	Y	Y	Y	Y	Y	Y	IP or fully qualified domain name of the remote server(--host {string})
remote_password	string	Y	Y	Y	Y	Y	Y	SSH session password(env:ASPERA_SCP_PASS)
remote_user	string	Y	Y	Y	Y	Y	Y	Remote user. Default value is "xfer" on node or connect. (--user {string})
remove_after_transfer	bool	Y	Y	Y				Remove SRC files after transfer success(--remove-after-transfer)

Field	Type	D	N	D	T	H	C	Description
remove_empty_directories	bool	Y	Y	Y				Specifies whether to remove empty directories. (--remove-empty-directories)
remove_empty_source_directory	bool	Y		Y				Remove empty source subdirectories and remove the source directory itself, if empty (--remove-empty-source-directory)
remove_skipped	bool	Y	Y	Y			Y	Must also have remove_after_transfer set to true, Defaults to false, if true, skipped files will be removed as well. (--remove-skipped)
resume_policy	string	Y	Y	Y	Y	Y	Y	If a transfer is interrupted or fails to finish, resume without re-transferring the whole files. Allowed values: none, attrs, sparse_csum, full_csum (-k (conversion){enum})
retry_duration	stringint		Y				Y	Specifies how long to wait before retrying transfer. (e.g. "5min") (<ignored>)
source_root	string	Y	Y	Y	Y	Y	Y	Path to be prepended to each source path. This is either a conventional path or it can be a URI but only if there is no root defined. (--source-prefix64 (conversion){string})
source_root_id	string		Y					The file ID of the source root directory. Required when using Bearer token auth for the source node. (<ignored>)
src_base	string	Y	Y	Y				Specify the prefix to be stripped off from each source object. The remaining portion of the source path is kept intact at the destination. Special care must be taken when used with cloud storage. (--src-base64 (conversion){string})
ssh_args	string							Array of arguments to pass to SSH. Use with caution. (<ignored>)
ssh_port	int	Y	Y	Y	Y	Y	Y	Specifies SSH (TCP) port. Default: local:22, other:33001 (-P {int})
ssh_private_key	string	Y		Y				Private key used for SSH authentication. Shall look like: -----BEGIN RSA PRIVATE KEY-----\nMII... Note the JSON encoding: \n for newlines. (env: ASPERA_SCP_KEY)
ssh_private_key_passphrase	string	Y		Y				The passphrase associated with the transfer user's SSH private key. Available as of 3.7.2. (env: ASPERA_SCP_PASS)
sshfp	string	Y	Y	Y	Y	Y	Y	Check it against server SSH host key fingerprint (--check-sshfp {string})
symlink_policy	string	Y	Y	Y	Y	Y	Y	Handle source side symbolic links. Allowed values: follow, copy, copy+force, skip (--symbolic-links {enum})
tags	hash	Y	Y	Y	Y	Y	Y	Metadata for transfer as JSON. Key aspera is reserved. Key aspera.xfer_retry specified a retry timeout for node api initiated transfers. (--tags64 (conversion){hash})
tar-get_rate_cap_kbps	int						Y	Returned by upload/download_setup node API. (<ignored>)

Field	Type	D	N	D	T	H	C	Description
target_rate_kbps	int	Y	Y	Y	Y	Y	Y	Specifies desired speed for the transfer.(-l{int})
target_rate_percentage	string	Y	Y	Y	Y	Y	Y	TODO: remove ?(<ignored>)
title	string		Y				Y	Title of the transfer(<ignored>)
token	string	Y	Y	Y	Y	Y	Y	Authorization token: Bearer, Basic or ATM (Also arg -W)(env:ASPERA_SCP_TOKEN)
use_ascp4	bool	Y	Y	Y				specify version of protocol(<special>)
use_system_ssh	string							TODO, comment...(<ignored>)
write_threads	int							ascp4 only(<ignored>)
wss_enabled	bool	Y	Y	Y	Y	Y	Y	Server has Web Socket service enabled(<special>)
wss_port	int	Y	Y	Y	Y	Y	Y	TCP port used for websocket service feed(<special>)
xfer_max_retries	int		Y					maximum number of retries, for node API initiated transfers. Shall not exceed aspera.conf <code>transfer_manager_max_retries</code> (default 5).(<ignored>)

4.22.1 Destination folder for transfers

The destination folder is set by `ascli` by default to:

- `.` for downloads
- `/` for uploads

It is specified by the `transfer-spec` parameter `destination_root`. As such, it can be modified with option: `--ts=@json:'{"destination_root":"<path>"}'`. The option `to_folder` provides an equivalent and convenient way to change this parameter: `--to-folder=<path>`.

4.22.2 List of files for transfers

When uploading, downloading or sending files, the user must specify the list of files to transfer.

By default, the list of files to transfer is simply provided on the command line.

The list of (source) files to transfer is specified by (extended value) option `sources` (default: `@args`). The list is either simply the list of source files, or a combined source/destination list (see below) depending on value of option `src_type` (default: `list`).

In `ascli`, all transfer parameters, including file list, are provided to the transfer agent in a `transfer-spec` so that execution of a transfer is independent of the transfer agent (direct, connect, node, transfer daemon...). So, eventually, the list of files to transfer is provided to the transfer agent using the `transfer-spec` field: `"paths"` which is a list (array) of pairs of `"source"` (mandatory) and `"destination"` (optional). The `sources` and `src_type` options provide convenient ways to populate the transfer spec with the source file list.

Possible values for option `sources` are:

- `@args` : (default) the list of files (or file pair) is directly provided on the command line (after commands): unused arguments (not starting with `-`) are considered as source files. So, by default, the list of files to transfer will be simply specified on the command line. Example:

```
ascli server upload ~/first.file secondfile
```

This is the same as (with default values):

```
ascli server upload --sources=@args --src-type=list ~/mysample.file secondfile
```

- An **Extended Value** with type `Array of String`

Note: extended values can be tested with the command `config echo`

Examples:

- Using extended value

Create the file list:

```
echo ~/mysample.file > myfilelist.txt
echo secondfile >> myfilelist.txt
```

Use the file list: one path per line:

```
--sources=@lines:@file:myfilelist.txt
```

- Using JSON array

```
--sources=@json:'["file1","file2"]'
```

- Using STDIN, one path per line

```
--sources=@lines:@stdin:
```

- Using Ruby code (one path per line in file)

```
--sources=@ruby:'File.read("myfilelist.txt").split("\n")'
```

- `@ts` : the user provides the list of files directly in the `paths` field of transfer spec (option `ts`). Examples:

- Using transfer spec

```
--sources=@ts --ts=@json:'{"paths":[{"source":"file1"}, {"source":"file2"}]}'
```

The option `src_type` allows specifying if the list specified in option `sources` is a simple file list or if it is a file pair list.

Note: Option `src_type` is not used if option `sources` is set to `@ts`

Supported values for `src_type` are:

- `list` : (default) the path of destination is the same as source and each entry is a source file path
- `pair` : the first element is the first source, the second element is the first destination, and so on.

Example: Source file `200KB.1` is renamed `sample1` on destination:

```
ascli server upload --src-type=pair ~/Documents/Samples/200KB.1 /Upload/sample1
```

Note: There are some specific rules to specify a file list when using *Aspera on Cloud*, refer to the *AoC plugin* section.

4.22.3 Source directory structure on destination

This section is not specific to `ascli` it is `ascp` behavior.

The transfer destination is normally expected to designate a destination folder.

But there is one exception: The destination specifies the new item name when the following are met:

- There is a single source item (file or folder)
- Transfer spec `create_dir` is not set to `true` (`ascp` option `-d` not provided)
- Destination is not an existing folder
- The `dirname` of destination is an existing folder

For this reason it is recommended to set `create_dir` to `true` for consistent behavior between single and multiple items transfer, this is the default in `ascli`.

If a simple source file list is provided (no `destination` in `paths`, i.e. no `file_pair_list` provided), the destination folder is used as destination folder for each source file, and source file folder names are not preserved.

The inner structure of source items that are folder is preserved on destination.

A leading `/` on destination is ignored (relative to docroot) unless docroot is not set (relative to home).

In the following table source folder `d3` contains 2 files: `f1` and `d4/f2`.

Source files	Destination	Folders on Dest.	create_dir	Destination Files
f1	d/f	-	false	Error: d does not exist.
f1	d/f	d	false	d/f (renamed)
f1	d/f/.	d	false	d/f (renamed)
f1	d/f	d/f	false	d/f/f1
f1 f2	d	d	false	d/f1 d/f2
d3	d	-	false	d/f1 d/f2 (renamed)
f1	d	-	true	d/f1
f1 f2	d	-	true	d/f1 d/f2
d1/f1 d2/f2	d	-	true	d/f1 d/f2
d3	d	-	true	d/d3/f1 d/d3/d4/f2

If a file pair list is provided then it is possible to rename or specify a different destination folder for each source (relative to the destination).

If transfer spec has a `src_base`, it has the side effect that the simple source file list is considered as a file pair list, and so the lower structure of source folders is preserved on destination.

Source files	Destination	src_base	Destination Files
d1/d2/f2 d1/d3/f3	d	d1	d/d2/f2 d/d3/f3

Advanced Example: Send files `./file1` and `./folder2/files2` to server (e.g. `/Upload`) and keep the original file names and folders, i.e. send `file1` to `/Upload/file1` and `files2` to `/Upload/folder2/files2`.

- If files are specified as `./file1 ./folder2/files2`, then destination will be: `/Upload/file1 /Upload/files2`
- One possibility is to specify a file pair list: `--src-type=pair file1 file1 folder2/files2 folder2/files2`
- Another possibility is to specify a source base: `--src-base=$PWD $PWD/file1 $PWD/folder2/files2` (note that `.` cannot be used as source base)
- Similarly, create a temporary soft link (Linux): `ln -s . tmp_base` and use `--src-base=tmp_base tmp_base/file1`
- One can also similarly use `--sources=@ts` and specify the list of files in the `paths` field of transfer spec with both `source` and `destination` for each file.

4.22.4 Multi-session transfer

Multi session, i.e. starting a transfer of a file set using multiple sessions (one `ascp` process per session) is supported on `direct` and `node` agents, not yet on `connect`.

- `--transfer=node`

```
--ts=@json: '{"multi_session":10,"multi_session_threshold":1}'
```

Multi-session is directly supported by the node daemon.

- `--transfer=direct`

```
--ts=@json: '{"multi_session":5,"multi_session_threshold":1,"resume_policy":"none"}'
```

Note: `resume_policy` set to `attr` may cause problems: `none` or `sparse_csum` shall be preferred.

`ascli` starts multiple `ascp` for Multi-session using `direct` agent.

When multi-session is used, one separate UDP port is used per session (refer to `ascp` manual page).

4.22.5 Content protection

Also known as Client-side encryption at rest (CSEAR), content protection allows a client to send files to a server which will store them encrypted (upload), and decrypt files as they are being downloaded from a server, both using a passphrase, only known by users sharing files. Files stay encrypted on server side.

Activating CSEAR consists in using transfer spec parameters:

- `content_protection` : activate encryption (`encrypt` for upload) or decryption (`decrypt` for download)
- `content_protection_password` : the passphrase to be used.

Example: parameter to download a Faspex package and decrypt on the fly

```
--ts=@json: '{"content_protection": "decrypt", "content_protection_password": "my_password_here"}'
```

4.22.6 Transfer Spec Examples

- Change target rate

```
--ts=@json: '{"target_rate_kbps": 500000}'
```

- Override the FASP SSH port to a specific TCP port:

```
--ts=@json: '{"ssh_port": 33002}'
```

- Force HTTP fallback mode:

```
--ts=@json: '{"http_fallback": "force"}'
```

- Activate progress when not activated by default on server

```
--ts=@json: '{"precalculate_job_size": true}'
```

4.23 Transfer progress bar

File transfer operations are monitored, and a progress bar is displayed on the terminal if option `progress_bar` (`Bool`) is set to `yes` (default if the output is a terminal).

The same progress bar is used for any type of transfer, using `ascp` , server to server, using HTTPS, etc...

4.24 Scheduler

It is useful to configure automated scheduled execution. `ascli` does not provide an internal scheduler. Instead, use the service provided by the Operating system:

4.24.1 Windows Scheduler

Windows provides the [Task Scheduler](#). It can be configured:

- Using utility `schtasks.exe`
- Using Powershell function `scheduledtasks`
- Using `taskschd.msc` (UI)

4.24.2 Unix-like Scheduler

Unix-like systems (Linux, ...) provide `cron` , configured using a `crontab`

Linux also provides `anacron` , if tasks are hourly or daily.

For example, on Linux it is convenient to create a wrapping script, e.g. `cron_ascli` that will set up the environment (e.g. Ruby) to properly start `ascli` :

```
#!/bin/bash
# load the Ruby environment
. /etc/profile.d/rvm.sh
rvm use 2.6 --quiet
# set a timeout protection, just in case ascli is frozen
tmout=30m
# forward arguments to ascli
exec timeout ${tmout} ascli "${@}"
```

Example of cronjob created for user `xfer`.

```
crontab<<EOF
0 * * * * /home/xfer/cron_ascli preview scan --logger=syslog --display=error
2-59 * * * * /home/xfer/cron_ascli preview trev --logger=syslog --display=error
EOF
```

Note: Logging options are kept here in the `cron` file instead of configuration file to allow execution on command line with output on command line.

4.25 Locking for exclusive execution

In some cases one needs to ensure that `ascli` is not executed several times in parallel.

When `ascli` is executed automatically on a schedule basis, one generally desires that a new execution is not started if a previous execution is still running because an ongoing operation may last longer than the scheduling period:

- Executing instances may pile-up and kill the system
- The same file may be transferred by multiple instances at the same time.
- `preview` may generate the same files in multiple instances.

Usually the OS native scheduler already provides some sort of protection against parallel execution:

- The Windows scheduler does this by default
- Linux `cron` can leverage the utility `flock` to do the same:

```
/usr/bin/flock -w 0 /var/cron.lock ascli ...
```

`ascli` natively supports a locking mechanism with option `lock_port`. (Technically, this opens a local TCP server port, and fails if this port is already used, providing a local lock. Lock is released when process exits).

Testing `ascli` locking:

Run this same command in two separate terminals within less than 30 seconds:

```
ascli config echo @ruby:'sleep(30)' --lock-port=12345
```

The first instance will sleep 30 seconds, the second one will immediately exit like this:

```
WARN -- : Another instance is already running (Address already in use - bind(2) for "127.0.0.1"
↪ port 12345).
```

4.26 "Provençal"

`ascp`, the underlying executable implementing Aspera file transfer using FASP, has a capability to not only access the local file system (using system's `open`, `read`, `write`, `close` primitives), but also to do the same operations on other data storage such as S3, Hadoop and others. This mechanism is called PVCL (from Provençal, a restaurant located in Sophia Antipolis). Several PVCL adapters are available, one is embedded in `ascp`, the others are provided in shared libraries and must be activated.

The list of supported PVCL adapters can be retrieved with command:

```
ascli config ascp info --fields=@re:'^pvcl'
```

```
process v1
shares v1
noded v1
faux v1
file v1
```

```
stdio v1
stdio-tar v1
```

Here we can see the adapters: `process`, `shares`, `noded`, `faux`, `file`, `stdio`, `stdio-tar`.

Those adapters can be used wherever a file path is used in `ascp` including configuration. They act as a pseudo drive.

The simplified format is:

```
<adapter>:///<sub file path>?<arg1>=<val1>&...
```

One of the adapters, used in this manual, for testing, is `faux`. It is a pseudo file system allowing generation of file data without actual storage (on source or destination).

4.27 **faux: for testing**

This adapter can be used to simulate a file or a directory. This is a feature of `ascp`, not `ascli`. The following is an extract of the man page of `ascp`.

To discard data at the destination, the destination argument is set to `faux://`.

To send uninitialized data in place of an actual source file, the source file is replaced with an argument of the form:

```
faux:///filename?filesize
```

where:

- `filename` is the name that will be assigned to the file on the destination
- `filesize` is the number of bytes that will be sent (in decimal).

Note: Characters `?` and `&` are shell special characters (wildcard and background), so `faux` file specification on command line should be protected (using quotes or `\`). If not, the shell may give error: `no matches found` or equivalent.

For all sizes, a suffix can be added (case-insensitive) to the size: k, m, g, t, p, e (values are power of 2, e.g. 1M is 220, i.e. 1 mebibyte, not megabyte). The maximum allowed value is 8×260 . Very large `faux` file sizes (petabyte range and above) will likely fail due to lack of destination storage unless destination is `faux://`.

To send uninitialized data in place of a source directory, the source argument is replaced with an argument of the form:

```
faux:///dirname?<arg1>=<val1>&...
```

where:

- `dirname` is the folder name and can contain `/` to specify a subfolder.
- Supported arguments are:

Name	Type	Description
count	int	Number of filesMandatory
file	string	Basename for filesDefault: <code>file</code>
size	int	Size of first file.Default: 0
inc	int	Increment applied to determine next file sizeDefault: 0
seq	enum	Sequence in determining next file sizeValues: random, sequentialDefault: sequential
buf_init	enum	How source data is initializedOption 'none' is not allowed for downloads.Values:none, zero, randomDefault:zero

The sequence parameter is applied as follows:

- If `seq` is `random` then each file size is:
 - `size +/- (inc * rand())`
 - Where `rand` is a random number between 0 and 1

- Note that file size must not be negative, inc will be set to size if it is greater than size
- Similarly, overall file size must be less than 8260. If size + inc is greater, inc will be reduced to limit size + inc to 7260.

- If `seq` is `sequential` then each file size is:

- `size + ((file_index - 1) * inc)`
- Where first file is index 1
- So file1 is `size` bytes, file2 is `size + inc` bytes, file3 is `size + inc * 2` bytes, etc.
- As with `random`, `inc` will be adjusted if `size + (count * inc)` is not less than 8*260.

Filenames generated are of the form: `<file>_<00000 ... count>_<filesize>`

Examples:

- Upload 20 gibibyte of random data to file `myfile` to directory `/Upload`

```
ascli server upload faux:///myfile?20g --to-folder=/Upload
```

- Upload a file `/tmp/sample` but do not save results to disk (no docroot on destination)

```
ascli server upload /tmp/sample --to-folder=faux://
```

- Upload a faux directory `mydir` containing 1 million files, sequentially with sizes ranging from 0 to 2 Mebibyte - 2 bytes, with the base name of each file being `testfile` to `/Upload`

```
ascli server upload "faux:///mydir?file=testfile&count=1m&size=0&inc=2&seq=sequential"
↪ --to-folder=/Upload
```

4.28 Usage

```
ascli -h
```

NAME

ascli -- a command line tool for Aspera Applications (v4.22.0.pre)

SYNOPSIS

ascli COMMANDS [OPTIONS] [ARGS]

DESCRIPTION

Use Aspera application to perform operations on command line.

Documentation and examples: <https://rubygems.org/gems/aspera-cli>

execute: `ascli conf doc`

or visit: <https://www.rubydoc.info/gems/aspera-cli>

source repo: <https://github.com/IBM/aspera-cli>

ENVIRONMENT VARIABLES

Any option can be set as an environment variable, refer to the manual

COMMANDS

To list first level commands, execute: `ascli`

Note that commands can be written shortened (provided it is unique).

OPTIONS

Options begin with a '-' (minus), and value is provided on command line.

Special values are supported beginning with special prefix `@pfx:`, where `pfx` is one of:

`val`, `base64`, `csvt`, `env`, `file`, `uri`, `json`, `lines`, `list`, `none`, `path`, `re`, `ruby`, `secret`,

↪ `stdin`, `stdbin`, `yaml`, `zlib`, `extend`, `preset`, `vault`

Dates format is '`DD-MM-YY HH:MM:SS`', or '`now`' or '`-'<num>h`'

ARGS

Some commands require mandatory arguments, e.g. a path.

OPTIONS: global

`--interactive=ENUM`

Use interactive input of missing params: [no], yes

`--ask-options=ENUM`

Ask even optional options: [no], yes

`--struct-parser=ENUM`

Default parser when expected value is a struct: json, ruby

`--format=ENUM`

Output format: text, nagios, ruby, json, jsonpp, yaml,

↪ [table], csv, image

--output=VALUE	Destination for results (String)
--display=ENUM	Output only some information: [info], data, error
--fields=VALUE	Comma separated list of: fields, or ALL, or DEF (String,
↪ Array, Regexp, Proc)	
--select=VALUE	Select only some items in lists: column, value (Hash, Proc)
--table-style=VALUE	Table display style (Hash)
--flat-hash=ENUM	(Table) Display deep values as additional keys: no, [yes]
--multi-single=ENUM	(Table) Control how object list is displayed as single
↪ table, or multiple objects: [no], yes, single	
--show-secrets=ENUM	Show secrets on command output: [no], yes
--image=VALUE	Options for image display (Hash)
-h, --help	Show this message
--bash-comp	Generate bash completion for command
--show-config	Display parameters used for the provided action
-v, --version	Display version
--ui=ENUM	Method to start browser: text, [graphical]
--log-level=ENUM	Log level: trace2, trace1, debug, info, [warn], error,
↪ fatal, unknown	
--logger=ENUM	Logging method: [stderr], stdout, syslog
--lock-port=VALUE	Prevent dual execution of a command, e.g. in cron (Integer)
--once-only=ENUM	Process only new items (some commands): [no], yes
--log-secrets=ENUM	Show passwords in logs: [no], yes
--clean-temp=ENUM	Cleanup temporary files on exit: no, [yes]
--pid-file=VALUE	Write process identifier to file, delete on exit (String)
--home=VALUE	Home folder for tool (String)
--config-file=VALUE	Path to YAML file with preset configuration
--secret=VALUE	Secret for access keys
--vault=VALUE	Vault for secrets (Hash)
--vault-password=VALUE	Vault password
--query=VALUE	Additional filter for for some commands (list/delete) (Hash,
↪ Array)	
--property=VALUE	Name of property to set (modify operation)
--bulk=ENUM	Bulk operation (only some): [no], yes
--bfail=ENUM	Bulk operation error handling: no, [yes]
-N, --no-default	Do not load default configuration for plugin
-P, --preset=VALUE	Load the named option preset from current config file
--version-check-days=VALUE	Period in days to check new version (zero to disable)
--plugin-folder=VALUE	Folder where to find additional plugins
--override=ENUM	Wizard: override existing value: [no], yes
--default=ENUM	Wizard: set as default configuration for specified plugin
↪ (also: update): no, [yes]	
--test-mode=ENUM	Wizard: skip private key check step: [no], yes
--key-path=VALUE	Wizard: path to private key for JWT
--ascp-path=VALUE	Path to ascp
--use-product=VALUE	Use ascp from specified product
--sdk-url=VALUE	URL to get Aspera Transfer Daemon
--locations-url=VALUE	URL to get locations of Aspera Transfer Daemon
--sdk-folder=VALUE	SDK folder path
--progress-bar=ENUM	Display progress bar: [no], yes
--smtp=VALUE	SMTP configuration (Hash)
--notify-to=VALUE	Email recipient for notification of transfers
--notify-template=VALUE	Email ERB template for notification of transfers
--insecure=ENUM	Do not validate any HTTPS certificate: [no], yes
--ignore-certificate=VALUE	Do not validate HTTPS certificate for these URLs (Array)
--silent-insecure=ENUM	Issue a warning if certificate is ignored: no, [yes]
--cert-stores=VALUE	List of folder with trusted certificates (Array, String)
--http-options=VALUE	Options for HTTP/S socket (Hash)
--http-proxy=VALUE	URL for HTTP proxy with optional credentials (String)
--cache-tokens=ENUM	Save and reuse OAuth tokens: no, [yes]
--fpac=VALUE	Proxy auto configuration script
--proxy-credentials=VALUE	HTTP proxy credentials for fpac: user, password (Array)
--ts=VALUE	Override transfer spec values (Hash)
--to-folder=VALUE	Destination folder for transferred files
--sources=VALUE	How list of transferred files is provided (@args,@ts,Array)
--src-type=ENUM	Type of file list: [list], pair

```

--transfer=ENUM          Type of transfer agent: desktop, node, [direct], transferd,
↪ httpgw, connect
--transfer-info=VALUE    Parameters for transfer agent (Hash)

COMMAND: config
SUBCOMMANDS: ascp check_update coffee detect documentation download echo email_test file folder
↪ gem genkey image initdemo open platform plugins preset proxy_check pubkey remote_certificate
↪ smtp_settings test tokens transferd vault wizard

COMMAND: shares
SUBCOMMANDS: admin files health
OPTIONS:
--url=VALUE              URL of application, e.g.
↪ https://faspex.example.com/aspera/faspex
--username=VALUE         User's name to log in
--password=VALUE         User's password

COMMAND: node
SUBCOMMANDS: access_keys api_details asperabrowser async basic_token bearer_token browse central
↪ delete download events health http_node_download info license mkdir mkfile mklink rename
↪ search service simulator slash space ssync stream sync transfer transport upload watch_folder
OPTIONS:
--url=VALUE              URL of application, e.g.
↪ https://faspex.example.com/aspera/faspex
--username=VALUE         User's name to log in
--password=VALUE         User's password
--validator=VALUE        Identifier of validator (optional for central)
--asperabrowserurl=VALUE URL for simple aspera web ui
--sync-name=VALUE        Sync name
--default-ports=ENUM     Use standard FASP ports or get from node api (gen4): no,
↪ [yes]
--node-cache=ENUM        Set to no to force actual file system read (gen4): no, [yes]
--root-id=VALUE          File id of top folder when using access key (override AK
↪ root id)
--sync-info=VALUE        Information for sync instance and sessions (Hash)

COMMAND: faspio
SUBCOMMANDS: bridges health
OPTIONS:
--url=VALUE              URL of application, e.g.
↪ https://faspex.example.com/aspera/faspex
--username=VALUE         User's name to log in
--password=VALUE         User's password
--auth=ENUM              OAuth type of authentication: jwt, basic
--client-id=VALUE        OAuth client identifier
--private-key=VALUE       OAuth JWT RSA private key PEM value (prefix file path with
↪ @file:)
--passphrase=VALUE       OAuth JWT RSA private key passphrase

COMMAND: orchestrator
SUBCOMMANDS: health info plugins processes workflow
OPTIONS:
--url=VALUE              URL of application, e.g.
↪ https://faspex.example.com/aspera/faspex
--username=VALUE         User's name to log in
--password=VALUE         User's password
--result=VALUE           Specify result value as: 'work_step:parameter'
--synchronous=ENUM       Wait for completion: [no], yes
--ret-style=ENUM         How return type is requested in api: header, [arg], ext
--auth-style=ENUM        Authentication type: arg_pass, [head_basic], apikey

```

COMMAND: alee
 SUBCOMMANDS: entitlement health
 OPTIONS:

- url=VALUE URL of application, e.g.
 ↪ https://faspex.example.com/aspera/faspex
- username=VALUE User's name to log in
- password=VALUE User's password

COMMAND: ats
 SUBCOMMANDS: access_key api_key aws_trust_policy cluster
 OPTIONS:

- ibm-api-key=VALUE IBM API key, see https://cloud.ibm.com/iam/apikeys
- instance=VALUE ATS instance in ibm cloud
- ats-key=VALUE ATS key identifier (ats_xxx)
- ats-secret=VALUE ATS key secret
- params=VALUE Parameters access key creation (@json:)
- cloud=VALUE Cloud provider
- region=VALUE Cloud region

COMMAND: faspex5
 SUBCOMMANDS: admin bearer_token gateway health invitations packages postprocessing shared_folders
 ↪ user version
 OPTIONS:

- url=VALUE URL of application, e.g.
 ↪ https://faspex.example.com/aspera/faspex
- username=VALUE User's name to log in
- password=VALUE User's password
- client-id=VALUE OAuth client identifier
- client-secret=VALUE OAuth client secret
- redirect-uri=VALUE OAuth redirect URI for web authentication
- auth=ENUM OAuth type of authentication: web, [jwt], boot
- private-key=VALUE OAuth JWT RSA private key PEM value (prefix file path with
 ↪ @file:)
- passphrase=VALUE OAuth JWT RSA private key passphrase
- box=VALUE Package inbox, either shared inbox name or one of: inbox,
 ↪ inbox_history, inbox_all, inbox_all_history, outbox, outbox_history, pending,
 ↪ pending_history, all or ALL
- shared-folder=VALUE Send package with files from shared folder
- group-type=ENUM Type of shared box: [shared_inboxes], workgroups

COMMAND: cos
 SUBCOMMANDS: node
 OPTIONS:

- bucket=VALUE Bucket name
- endpoint=VALUE Storage endpoint (URL)
- apikey=VALUE Storage API key
- crn=VALUE Resource instance id (CRN)
- service-credentials=VALUE IBM Cloud service credentials (Hash)
- region=VALUE Storage region
- identity=VALUE Authentication URL (https://iam.cloud.ibm.com/identity)

COMMAND: httpgw
 SUBCOMMANDS: health info
 OPTIONS:

- url=VALUE URL of application, e.g. https://app.example.com/aspera/app

COMMAND: faspex
 SUBCOMMANDS: address_book dropbox health login_methods me package source v4
 OPTIONS:

```

--url=VALUE          URL of application, e.g.
↪ https://faspex.example.com/aspera/faspex
--username=VALUE     User's name to log in
--password=VALUE      User's password
--link=VALUE          Public link for specific operation
--delivery-info=VALUE Package delivery information (Hash)
--remote-source=VALUE Remote source for package send (id or %name:)
--storage=VALUE        Faspex local storage definition (for browsing source)
--recipient=VALUE     Use if recipient is a dropbox (with *)
--box=ENUM            Package box: [inbox], archive, sent

COMMAND: preview
SUBCOMMANDS: check events scan show test trevents
OPTIONS:
--url=VALUE          URL of application, e.g.
↪ https://faspex.example.com/aspera/faspex
--username=VALUE     User's name to log in
--password=VALUE      User's password
--skip-format=ENUM    Skip this preview format (multiple possible): png, mp4
--folder-reset-cache=ENUM Force detection of generated preview by refresh cache: [no],
↪ header, read
--skip-types=VALUE    Skip types in comma separated list
--previews-folder=VALUE Preview folder in storage root
--temp-folder=VALUE   Path to temp folder
--skip-folders=VALUE  List of folder to skip
--base=VALUE          Basename of output for for test
--scan-path=VALUE     Subpath in folder id to start scan in (default=/)
--scan-id=VALUE       Folder id in storage to start scan in, default is access key
↪ main folder id
--mimemagic=ENUM      Use Mime type detection of gem mimemagic: [no], yes
--overwrite=ENUM      When to overwrite result file: always, never, [mtime]
--file-access=ENUM    How to read and write files in repository: [local], remote
--max-size=VALUE      Maximum size (in bytes) of preview file
--thumb-vid-scale=VALUE Png: video: size (ffmpeg scale argument)
--thumb-vid-fraction=VALUE Png: video: time percent position of snapshot
--thumb-img-size=VALUE Png: non-video: height (and width)
--thumb-text-font=VALUE Png: plaintext: font for text rendering: `magick identify
↪ -list font`
--video-conversion=ENUM Mp4: method for preview generation: [reencode], blend, clips
--video-png-conv=ENUM   Mp4: method for thumbnail generation: [fixed], animated
--video-scale=VALUE     Mp4: all: video scale (ffmpeg scale argument)
--video-start-sec=VALUE Mp4: all: start offset (seconds) of video preview
--reencode-ffmpeg=VALUE Mp4: reencode: options to ffmpeg
--blend-keyframes=VALUE Mp4: blend: # key frames
--blend-pauseframes=VALUE Mp4: blend: # pause frames
--blend-transframes=VALUE Mp4: blend: # transition blend frames
--blend-fps=VALUE       Mp4: blend: frame per second
--clips-count=VALUE     Mp4: clips: number of clips
--clips-length=VALUE    Mp4: clips: length in seconds of each clips

COMMAND: aoc
SUBCOMMANDS: admin automation bearer_token files gateway organization packages reminder servers
↪ tier_restrictions user
OPTIONS:
--url=VALUE          URL of application, e.g.
↪ https://faspex.example.com/aspera/faspex
--username=VALUE     User's name to log in
--password=VALUE      User's password
--auth=ENUM          OAuth type of authentication: web, [jwt]
--client-id=VALUE     OAuth API client identifier
--client-secret=VALUE OAuth API client secret
--scope=VALUE         OAuth scope for AoC API calls
--redirect-uri=VALUE  OAuth API client redirect URI

```

```

--private-key=VALUE      OAuth JWT RSA private key PEM value (prefix file path with
↪ @file:)
--passphrase=VALUE      RSA private key passphrase (String)
--workspace=VALUE       Name of workspace (String, NilClass)
--new-user-option=VALUE  New user creation option for unknown package recipients
↪ (Hash)
--validate-metadata=ENUM Validate shared inbox metadata: no, [yes]

COMMAND: server
SUBCOMMANDS: browse cp delete df download du health info ls md5sum mkdir mv rename rm sync upload
OPTIONS:
--url=VALUE              URL of application, e.g.
↪ https://faspex.example.com/aspera/faspex
--username=VALUE         User's name to log in
--password=VALUE         User's password
--ssh-keys=VALUE         SSH key path list (Array or single)
--passphrase=VALUE       SSH private key passphrase
--ssh-options=VALUE       SSH options (Hash)
--sync-info=VALUE        Information for sync instance and sessions (Hash)

COMMAND: console
SUBCOMMANDS: health transfer
OPTIONS:
--url=VALUE              URL of application, e.g.
↪ https://faspex.example.com/aspera/faspex
--username=VALUE         User's name to log in
--password=VALUE         User's password
--filter-from=DATE       Only after date
--filter-to=DATE         Only before date

```

Note: Commands and parameter values can be written in short form.

4.29 Bulk creation and deletion of resources

Bulk creation and deletion of resources are possible using option `bulk` (`yes`, `no` (default)). In that case, the operation expects an `Array` of `Hash` instead of a simple `Hash` using the **Extended Value Syntax**. This option is available only for some resources: if you need it: try and see if the entities you try to create or delete support this option.

4.30 Option: `query`

The `query` option can generally be used to add URL parameters to commands that list resources. It takes either a `Hash` or an `Array`, corresponding to key/value pairs that appear in the query part of request.

For example: `--query=@json: '{"p1": "v1", "p2": "v2"}'` leads to query: `?p1=v1&p2=v2`.

If the same parameter needs to be provided several times, then it's possible as well to provide an `Array` or 2-element `Array`: `--query=@json: '[[{"p1": "v1"}, {"p2": "v2"}]'` leads to the same result as previously.

If PHP's style array is used, then one can use either:

- `--query=@json: '{"a": ["v1", "v2"]}'`
- `--query=@json: '[[{"a": "v1"}, {"a": "v2"}]'`

Both result in: `?a[]=v1&a[]=v2`.

4.31 Plugins

`ascli` uses a plugin mechanism. The first level command (just after `ascli` on the command line) is the name of the concerned plugin which will execute the command. Each plugin usually represents commands sent to a specific

application. For instance, the plugin `faspex` allows operations on Aspera Faspex.

Available plugins can be found using command:

```
ascli config plugin list
```

plugin	detect	wizard	path
shares	Y	Y	.../aspera-cli/lib/aspera/cli/plugins/shares.rb
node	Y	Y	.../aspera-cli/lib/aspera/cli/plugins/node.rb
...			

Most plugins will take the URL option: `url` to identify their location.

REST APIs of Aspera legacy applications (Aspera Node, Faspex 4, Shares, Console, Orchestrator) use simple username/password authentication: HTTP Basic Authentication using options: `username` and `password`.

Aspera on Cloud and Faspex 5 rely on OAuth.

By default, plugins are looked-up in folders specified by (multi-value) option `plugin_folder`:

```
ascli --show-config --fields=plugin_folder
```

You can create the skeleton of a new plugin like this:

```
ascli config plugin create foo .
```

```
Created ./foo.rb
```

```
ascli --plugin-folder=. foo
```

Chapter 5

Plugin: `aoc` : IBM Aspera on Cloud

Aspera on Cloud API requires the use of OAuth v2 mechanism for authentication (HTTP Basic authentication is not supported).

It is recommended to use the wizard to set it up, although manual configuration is also possible.

5.1 Configuration: Using Wizard

`ascli` provides a configuration wizard.

The wizard guides you through the steps to create a new configuration preset for Aspera on Cloud.

The first

Here is a sample invocation :

```
ascli config wizard
option: url> https://_your_instance_.ibmaspera.com
Detected: Aspera on Cloud
Preparing preset: aoc_myorg
Please provide path to your private RSA key, or empty to generate one:
option: key_path>
using existing key:
/Users/myself/.aspera/ascli/aspera_aoc_key
Using global client_id.
option: username> john@example.com
Updating profile with new key
creating new config preset: aoc_myorg
Setting config preset as default for aspera
saving configuration file
Done.
You can test with:
ascli aoc user profile show
```

Note: In above example, replace `https://_your_instance_.ibmaspera.com` with your actual AoC URL.

Optionally, it is possible to create a new organization-specific integration, i.e. client application identification. For this, specify the option: `--use-generic-client=no`.

If you already know the application, and want to limit the detection to it, provide URL and plugin name:

```
ascli config wizard _your_instance_ aoc
```

Note: In above example, replace `_your_instance_` with the first part of your actual AoC URL: `https://_your_instance_.ibmaspera.com`.

5.2 Configuration: Using manual setup

I *Note: If you used the wizard (recommended): skip this section.*

5.2.1 Configuration details

Several types of OAuth authentication are supported:

- JSON Web Token (JWT) : authentication is secured by a private key (recommended for `ascli`)
- Web based authentication : authentication is made by user using a browser
- URL Token : external user's authentication with URL tokens (public links)

The authentication method is controlled by option `auth`.

For a quick start, follow the mandatory and sufficient section: **API Client Registration** (`auth=web`) as well as **[Option Preset](#option-preset)** for Aspera on Cloud.

For a more convenient, browser-less, experience follow the **JWT** section (`auth=jwt`) in addition to Client Registration.

In OAuth, a Bearer token is generated to authenticate REST calls. Bearer tokens are valid for a period of time defined (by the AoC app, configurable by admin) at its creation. `ascli` saves generated tokens in its configuration folder, tries to re-use them or regenerates them when they have expired.

5.2.2 API Client Registration

I Optional

If you use the built-in `client_id` and `client_secret`, skip this and do not set them in next section.

Else you can use a specific OAuth API `client_id`, the first step is to declare `ascli` in Aspera on Cloud using the admin interface.

([AoC documentation: Registering an API Client](#)).

Let's start by a registration with web based authentication (`auth=web`):

- Open a web browser, log to your instance: e.g. `https://_your_instance_.ibmaspera.com/` (use your actual AoC instance URL)
- Go to Apps → Admin → Organization → Integrations
- Click Create New
 - Client Name: `ascli`
 - Redirect URIs: `http://localhost:12345`
 - Origins: `localhost`
 - uncheck Prompt users to allow client to access
 - leave the JWT part for now
- Save

I *Note: For web based authentication, `ascli` listens on a local port (e.g. specified by the `redirect_uri`, in this example: 12345), and the browser will provide the OAuth code there. For `ascli`, HTTP is required, and 12345 is the default port.*

Once the client is registered, a Client ID and Secret are created, these values will be used in the next step.

5.2.3 Configuration for Aspera on Cloud

If you did not use the wizard, you can also manually create an **Option Preset** for `ascli` in its configuration file.

Let's create an **Option Preset** called: `my_aoc_org` using `ask` for interactive input (client info from previous step):

```
ascli config preset ask my_aoc_org url client_id client_secret
option: url> https://_your_instance_.ibmaspera.com/
option: client_id> my_client_id_here
option: client_secret> my_client_secret_here
updated: my_aoc_org
```

I *Note: In above example, replace `https://_your_instance_.ibmaspera.com` with your actual AoC URL.*

(This can also be done in one line using the command `config preset update my_aoc_org --url=...`)

Define this **Option Preset** as default configuration for the `aspera` plugin:

```
ascli config preset set default aoc my_aoc_org
```

Note: Default `auth` method is `web` and default `redirect_uri` is `http://localhost:12345`. Leave those default values.

5.2.4 Authentication with private key

For a Browser-less, Private Key-based authentication, use the following steps.

In order to use JSON Web Token (JWT) for Aspera on Cloud API client authentication, a **private/public key pair** must be used.

5.2.4.1 API Client JWT activation

If you are not using the built-in `client_id` and secret, JWT needs to be authorized in Aspera on Cloud. This can be done in two manners:

- Graphically
 - Open a web browser, log to your instance: `https://_your_instance_.ibmaspera.com/` (Use your actual AoC instance URL)
 - Go to Apps → Admin → Organization → Integrations
 - Click on the previously created application
 - select tab : JSON Web Token Auth
 - Modify options if necessary, for instance: activate both options in section Settings
 - Save
- Using command line

```
ascli aoc admin client list
```

```
+-----+-----+
|   id   |  name   |
+-----+-----+
| my_BJbQiFw | my-client-app |
+-----+-----+
```

```
ascli aoc admin client modify my_BJbQiFw
```

```
↪ @json: '{"jwt_grant_enabled":true,"explicit_authorization_required":false}'
```

```
modified
```

5.2.5 User key registration

The public key must be assigned to your user. This can be done in two manners:

5.2.5.1 Graphically

Open the previously generated public key located here: `$HOME/.aspera/ascli/my_private_key.pub`

- Open a web browser, log to your instance: `https://_your_instance_.ibmaspera.com/` (Use your actual AoC instance URL)
- Click on the user's icon (top right)
- Select Account Settings
- Paste the Public Key PEM value in the Public Key section
- Click on Submit

5.2.5.2 Using command line

```
ascli aoc admin user list
```

```
+-----+-----+
|   id   |   name   |
+-----+-----+
| 109952 | Tech Support |
| 109951 | LAURENT MARTIN |
+-----+-----+
```

```
ascli aoc user profile modify
↪ @ruby:'{"public_key"=>File.read(File.expand_path("~/aspera/ascli/my_private_key.pub"))}'
modified
```

Note: The `aspera user info show` command can be used to verify modifications.

5.2.6 Option Preset modification for JWT

To activate default use of JWT authentication for `ascli` using the **Option Preset**, do the following:

- Change auth method to JWT
- Provide location of private key
- Provide username to login as (OAuth subject)

Execute:

```
ascli config preset update my_aoc_org --auth=jwt
↪ --private-key=@val:@file:~/aspera/ascli/my_private_key --username=someuser@example.com
```

Note: The private key argument represents the actual PEM string. In order to read the content from a file, use the `@file:` prefix. But if the `@file:` argument is used as is, it will read the file and set in the configuration file. So, to keep the `@file:` tag in the configuration file, the `@val:` prefix is added.

After this last step, commands do not require web login anymore.

5.2.7 Public and private links

AoC gives the possibility to generate public links for both the `Files` and `Packages` modules. Public links embed the authorization of access. Provide the public link using option `url` alone.

In addition, the `Files` application supports private links. Private links require the user to authenticate. So, provide the same options as for regular authentication, and provide the private link using option `url`.

A user may not be part of any workspace, but still have access to shared folders (using private links). In that case, it is possible to list those shared folder by using a value for option `workspace` equal to `@none:` or `@json:null` or `@ruby:nil`.

5.2.8 AoC: First Use

Once client has been registered and **Option Preset** created: `ascli` can be used:

```
ascli aoc files br /
```

```
Current Workspace: Default Workspace (default)
empty
```

5.3 Calling AoC APIs from command line

The command `ascli aoc bearer` can be used to generate an OAuth token suitable to call any AoC API (use the `scope` option to change the scope, default is `user:all`). This can be useful when a command is not yet available.

Example:

```
curl -s -H "Authorization: $(ascli aoc bearer_token)"
↪ 'https://api.ibmaspera.com/api/v1/group_memberships?embed[]=dropbox&embed[]=workspace'|jq -r
↪ '.[.](.workspace.name + " -> " + .dropbox.name)'
```

It is also possible to get the bearer token for node, as user or as admin using:

```
ascli aoc files bearer_token_node /
```

```
ascli aoc admin node v4 1234 --secret=_ak_secret_here_ bearer_token_node /
```

5.4 Administration

The `admin` command allows several administrative tasks (and require admin privilege).

It allows actions (create, update, delete) on `resources`: users, group, nodes, workspace, etc... with the `admin resource` command.

5.4.1 Listing resources

The command `aoc admin <type> list` lists all entities of given type. It uses paging and multiple requests if necessary.

The option `query` can be optionally used. It expects a `Hash` using [Extended Value Syntax](#), generally provided using: `--query=@json:{...}`. Values are directly sent to the API call and used as a filter on server side.

The following parameters are supported:

- `q` : a filter on name of resource (case-insensitive, matches if value is contained in name)
- `sort` : name of fields to sort results, prefix with `-` for reverse order.
- `max` : maximum number of items to retrieve (stop pages when the maximum is passed)
- `pmax` : maximum number of pages to request (stop pages when the maximum is passed)
- `page` : native API parameter, in general do not use (added by `ascli`)
- `per_page` : native API parameter, number of items par API call, in general do not use
- Other specific parameters depending on resource type.

Both `max` and `pmax` are processed internally in `ascli`, not included in actual API call and limit the number of successive pages requested to API. `ascli` will return all values using paging if not provided.

Other parameters are directly sent as parameters to the GET request on API.

`page` and `per_page` are normally added by `ascli` to build successive API calls to get all values if there are more than 1000. (AoC allows a maximum page size of 1000).

`q` and `sort` are available on most resource types.

Other parameters depend on the type of entity (refer to AoC API).

Examples:

- List users with `laurent` in name:

```
ascli aoc admin user list --query=@json:{"q":"laurent"}
```

- List users who logged-in before a date:

```
ascli aoc admin user list --query=@json:{"q":"last_login_at:<2018-05-28"}
```

- List external users and sort in reverse alphabetical order using name:

```
ascli aoc admin user list --query=@json:{"member_of_any_workspace":false,"sort":"-name"}
```

Refer to the AoC API for full list of query parameters, or use the browser in developer mode with the web UI.

| *Note: The option `select` can also be used to further refine selection, refer to [section earlier](#).*

5.4.2 Selecting a resource

Resources are identified by a unique `id`, as well as a unique `name` (case-insensitive).

To execute an action on a specific resource, select it using one of those methods:

- recommended: give ID directly on command line after the action: `aoc admin node show 123`
- Give name on command line after the action: `aoc admin node show name abc`
- Provide option `id` : `aoc admin node show 123`
- Provide option `name` : `aoc admin node show --name=abc`


```
We received <%=ev['files_completed']%> files for a total of <%=ev['transferred_bytes']%> bytes,
↳ starting with file:
<%=ev['content']%>

Thank you.
```

The environment provided contains the following additional variable:

- **ev** : all details on the transfer event

Example:

```
ascli aoc admin analytics transfers --once-only=yes --lock-port=12345
↳ --query=@json:'{"status":"completed","direction":"receive"}' --notify-to=active
↳ --notify-template=@file:mytemplate.erb
```

Options:

- **once_only** keep track of last date it was called, so next call will get only new events
- **query** filter (on API call)
- **notify** send an email as specified by template, this could be places in a file with the **@file** modifier.

Note: This must not be executed in less than 5 minutes because the analytics interface accepts only a period of time between 5 minutes and 6 months. The period is [date of previous execution]..[now].

5.4.6 Transfer: Using specific transfer ports

By default, transfer nodes are expected to use ports TCP/UDP 33001. The web UI enforces that. The option **default_ports** ([yes]/no) allows **ascli** to retrieve the server ports from an API call (download_setup) which reads the information from **aspera.conf** on the server.

5.4.7 Using ATS

Refer to section [Examples](#) of **ATS** and substitute command **ats** with **aoc admin ats**.

5.4.8 Files with type **link**

Aspera on Cloud Shared folders are implemented through a special type of file: **link**. A **link** is the equivalent of a symbolic link on a file system: it points to another folder (not file).

Listing a link (in terminal position of path) will information on the link itself, not the content of the folder it points to. To list the target folder content, add a **/** at the end of the path.

Example:

```
$ ascli aoc files br the_link
Current Workspace: Default (default)
+-----+-----+-----+-----+-----+-----+
| name      | type | recursive_size | size | modified_time      | access_level |
+-----+-----+-----+-----+-----+-----+
| the_link  | link |                |      | 2021-04-28T09:17:14Z | edit         |
+-----+-----+-----+-----+-----+-----+

$ ascli aoc files br the_link/
Current Workspace: Default (default)
+-----+-----+-----+-----+-----+-----+
| name      | type | recursive_size | size | modified_time      | access_level |
+-----+-----+-----+-----+-----+-----+
| file_inside | file |                |      | 2021-04-26T09:00:00Z | edit         |
+-----+-----+-----+-----+-----+-----+
```

5.4.9 Example: Bulk creation of users

```
ascli aoc admin user create --bulk=yes
↳ @json:'[{"email":"dummyuser1@example.com"}, {"email":"dummyuser2@example.com"}]'
```

```
+-----+-----+
| id | status |
+-----+-----+
| 98398 | created |
| 98399 | created |
+-----+-----+
```

5.4.10 Example: Find with filter and delete

```
ascli aoc admin user list --query='@json:{"q":"dummyuser"}' --fields=id,email
```

```
+-----+-----+
| id | email |
+-----+-----+
| 98398 | dummyuser1@example.com |
| 98399 | dummyuser2@example.com |
+-----+-----+
```

```
ascli aoc admin user list --query='@json:{"q":"dummyuser"}' --fields=id --display=data
↪ --format=csv | ascli aoc admin user delete @lines:@stdin: --bulk=yes
```

```
+-----+-----+
| id | status |
+-----+-----+
| 98398 | deleted |
| 98399 | deleted |
+-----+-----+
```

5.4.11 Example: Find deactivated users since more than 2 years

```
ascli aoc admin user list --query=@ruby:'{"deactivated"=>true,"q"=>"last_login_at:<#{DateTime.}
↪ now.to_time.utc-2*365*86400).iso8601}"}
```

To delete them use the same method as before

5.4.12 Example: Display current user's workspaces

```
ascli aoc user workspaces list
```

```
+-----+-----+
| id | name |
+-----+-----+
| 16 | Engineering |
| 17 | Marketing |
| 18 | Sales |
+-----+-----+
```

5.4.13 Example: Create a sub access key in a `node`

Creation of a sub-access key is like creation of access key with the following difference: authentication to Node API is made with access key (master access key) and only the path parameter is provided: it is relative to the storage root of the master key. (id and secret are optional)

```
ascli aoc admin resource node --name=_node_name_ --secret=_secret_ v4 access_key create
↪ @json: '{"storage":{"path":"/folder1"}'}
```

5.4.14 Example: Display transfer events (ops/transfer)

```
ascli aoc admin node --secret=_secret_ v3 transfer list --query=@json:'[["q","*"],["count",5]]'
```

Examples of query:

```
{ "q": "type(file_upload OR file_delete OR file_download OR file_rename OR folder_create OR
↪ folder_delete OR folder_share OR folder_share_via_public_link)", "sort": "-date" }
```

```
{ "tag": "aspera.files.package_id=LA80U3p8w" }
```

5.4.15 Example: Display node events (events)

```
ascli aoc admin node --secret=_secret_ v3 events
```

5.4.16 Example: Display members of a workspace

```
ascli aoc admin workspace_membership list --fields=member_type,manager,member.email  
↪ --query=@json: '{"embed": "member", "inherited": false, "workspace_id": 11363, "sort": "name"}'
```

member_type	manager	member.email
user	true	john.curtis@email.com
user	false	someuser@example.com
user	false	jean.dupont@me.com
user	false	another.user@example.com
group	false	
user	false	aspera.user@gmail.com

Other query parameters:

```
 '{"workspace_membership_through": true, "include_indirect": true}'
```

5.4.17 Example: Add all members of a workspace to another workspace

a- Get ID of first workspace

```
WS1='First Workspace'  
WS1ID=$(ascli aoc admin workspace list --query=@json: '{"q": "'$WS1'"}'  
↪ --select=@json: '{"name": "'$WS1'"}' --fields=id --format=csv)
```

b- Get ID of second workspace

```
WS2='Second Workspace'  
WS2ID=$(ascli aoc admin workspace list --query=@json: '{"q": "'$WS2'"}'  
↪ --select=@json: '{"name": "'$WS2'"}' --fields=id --format=csv)
```

c- Extract membership information

```
ascli aoc admin workspace_membership list --fields=manager,member_id,member_type,workspace_id  
↪ --query=@json: '{"workspace_id": "'$WS1ID'"}' --format=jsonpp --output=ws1_members.json
```

d- Convert to creation data for second workspace:

```
grep -Eve '(direct|effective_manager|_count|storage|"id")' ws1_members.json | sed '/workspace_id/  
↪ s/"'$WS1ID'"/"'$WS2ID'"/g' > ws2_members.json
```

or, using **jq**:

```
jq '[.[] | {member_type,member_id,workspace_id,manager,workspace_id:"'$WS2ID'"}]'  
↪ ws1_members.json > ws2_members.json
```

e- Add members to second workspace

```
ascli aoc admin workspace_membership create --bulk=yes @json:@file:ws2_members.json
```

5.4.18 Example: Get users who did not log since a date

```
ascli aoc admin user list --fields=email --query=@json: '{"q": "last_login_at:<2018-05-28"}'
```

email
John.curtis@acme.com
Jean.Dupont@tropfort.com

5.4.19 Example: List Limited users

```
ascli aoc admin user list --fields=email --select=@json:'{"member_of_any_workspace":false}'
```

5.4.20 Example: Create a group, add to workspace and add user to group

- Create the group and take note of `id`

```
ascli aoc admin group create @json:'{"name":"group 1","description":"my super group"}'
```

Group: 11111

- Get the workspace ID

```
ascli aoc admin workspace list --query=@json:'{"q":"myworkspace"}' --fields=id --format=csv  
↪ --display=data
```

Workspace: 22222

- Add group to workspace

```
ascli aoc admin workspace_membership create  
↪ @json:'{"workspace_id":22222,"member_type":"user","member_id":11111}'
```

- Get a user's ID

```
ascli aoc admin user list --query=@json:'{"q":"manu.macron@example.com"}' --fields=id  
↪ --format=csv --display=data
```

User: 33333

- Add user to group

```
ascli aoc admin group_membership create  
↪ @json:'{"group_id":11111,"member_type":"user","member_id":33333}'
```

5.4.21 Example: Perform a multi Gbps transfer between two remote shared folders

In this example, a user has access to a workspace where two shared folders are located on different sites, e.g. different cloud regions.

First, set up the environment (skip if already done)

```
ascli config wizard --url=https://sedemo.ibmaspera.com --username=someuser@example.com
```

```
Detected: Aspera on Cloud  
Preparing preset: aoc_sedemo  
Using existing key:  
/Users/laurent/.aspera/ascli/aspera_aoc_key  
Using global client_id.  
Please Login to your Aspera on Cloud instance.  
Navigate to your "Account Settings"  
Check or update the value of "Public Key" to be:  
-----BEGIN PUBLIC KEY-----  
SOME PUBLIC KEY PEM DATA HERE  
-----END PUBLIC KEY-----  
Once updated or validated, press enter.  
  
creating new config preset: aoc_sedemo  
Setting config preset as default for aspera  
saving configuration file  
Done.  
You can test with:  
ascli aoc user profile show
```

This creates the option preset `aoc_[org name]` to allow seamless command line access and sets it as default for Aspera on Cloud.

Then, create two shared folders located in two regions, in your files home, in a workspace.

Then, transfer between those:


```
ascli -Paoc_show aoc files transfer --from-folder='IBM Cloud SJ' --to-folder='AWS Singapore'
↪ 100GB.file
↪ --ts=@json: '{"target_rate_kbps": "1000000", "multi_session": 10, "multi_session_threshold": 1}'
```

5.4.22 Example: Create registration key to register a tethered node

The following command will create and display a secret token to register a self-managed Aspera Transfer Server:

```
ascli aoc admin client_registration_token create @json: '{"data": {"name": "laurentnode",
↪ "client_subject_scopes": ["alee", "aejd"], "client_subject_enabled": true}}' --fields=token
↪ --show-secrets=yes
```

5.4.23 Example: Delete all registration keys

```
ascli aoc admin client_registration_token list --fields=id --format=csv | ascli aoc admin
↪ client_registration_token delete @lines:@stdin: --bulk=yes
```

```
+-----+-----+
| id | status |
+-----+-----+
| 99 | deleted |
| 100 | deleted |
| 101 | deleted |
| 102 | deleted |
+-----+-----+
```

5.4.24 Example: Create a Node

AoC nodes are actually composed with two related entities:

- An access key created on the Transfer Server (HSTS/ATS)
- A `node` resource in the AoC application.

The web UI allows creation of both entities in one shot. For more flexibility, `ascli` allows this in two separate steps.

Note: When selecting *Use existing access key* in the web UI, this actually skips access key creation (first step).

So, for example, the creation of a node using ATS in IBM Cloud looks like (see other example in this manual):

- Create the access key on ATS

The creation options are the ones of ATS API, refer to the [section on ATS](#) for more details and examples.

```
ascli aoc admin ats access_key create --cloud=softlayer --region=eu-de
↪ --params=@json: '{"storage": {"type": "ibm-s3", "bucket": "mybucket", "credentials":
↪ {"access_key_id": "mykey", "secret_access_key": "mysecret"}, "path": "/"}}'
```

Once executed, the access key `id` and `secret`, randomly generated by the Node API, is displayed.

Note: Once returned by the API, the secret will not be available anymore, so store this preciously. ATS secrets can only be reset by asking IBM support.

- Create the AoC node entity

First, Retrieve the ATS node address

```
ascli aoc admin ats cluster show --cloud=softlayer --region=eu-de --fields=transfer_setup_url
↪ --format=csv
```

Then use the returned address for the `url` key to actually create the AoC Node entity:

```
ascli aoc admin node create
↪ @json: '{"name": "myname", "access_key": "myaccesskeyid", "ats_access_key": true,
↪ "ats_storage_type": "ibm-s3", "url": "https://ats-sl-fra-all.aspera.io"}'
```

Creation of a node with a self-managed node is similar, but the command `aoc admin ats access_key create` is replaced with `node access_key create` on the private node itself.

5.5 List of files to transfer

Source files are provided as a list with the `sources` option. Refer to section [File list](#)

Note: A special case is when the source files are located on [Aspera on Cloud](#) (i.e. using access keys and the `file ID` API).

Source files are located on [Aspera on cloud](#), when :

- The server is Aspera on Cloud, and executing a `download` or `recv`
- The agent is Aspera on Cloud, and executing an `upload` or `send`

In this case:

- If there is a single file : specify the full path
- Else, if there are multiple files:
 - All source files must be in the same source folder
 - Specify the source folder as first item in the list
 - followed by the list of file names.

5.6 Packages

The web-mail-like application.

5.6.1 Send a Package

General syntax:

```
ascli aoc packages send [package extended value] [other parameters such as file list and transfer  
↪ parameters]
```

Package creation parameter are sent as [Command Parameter](#). Refer to the AoC package creation API, or display an existing package in JSON to list attributes.

List allowed shared inbox destinations with:

```
ascli aoc packages shared_inboxes list
```

Use fields: `recipients` and/or `bcc_recipients` to provide the list of recipients: [user](#) or [shared inbox](#):

- Provide either IDs as expected by API: `"recipients": [{"type": "dropbox", "id": "1234"}]`
- or just names: `"recipients": [{"The Dest"}]`.

ascli will resolve the list of email addresses and dropbox names to the expected type/ID list, based on case-insensitive partial match.

If a user recipient (email) is not already registered and the workspace allows external users, then the package is sent to an external user, and:

- if the option `new_user_option` is `@json:{"package_contact":true}` (default), then a public link is sent and the external user does not need to create an account
- if the option `new_user_option` is `@json:{}`, then external users are invited to join the workspace

5.6.2 List packages

By default, when using `aoc packages list`, the following `query` is performed:

query parameter	value
<code>archived</code>	<code>false</code>
<code>has_content</code>	<code>true</code>
<code>received</code>	<code>true</code>
<code>completed</code>	<code>true</code>
<code>workspace_id</code>	based on current workspace

query parameter	value
<code>exclude_dropbox_packages</code>	<code>true</code> if watching a dropbox, or <code>false</code> if not
<code>dropbox_id</code>	set according to <code>dropbox_name</code>

5.6.3 Example: Send a package with one file to two users, using their email

```
ascli aoc packages send @json:'{"name":"my title","note":"my
↪ note","recipients":["someuser@example.com","other@example.com"]}' my_file.dat
```

5.6.4 Example: Send a package to a shared inbox with metadata

```
ascli aoc packages send --workspace="my ws" @json:'{"name":"my pack title","recipients":["Shared
↪ Inbox With Meta"],"metadata":{"Project
↪ Id":"123","Type":"Opt2","CheckThose":["Check1","Check2"],"Optional
↪ Date":"2021-01-13T15:02:00.000Z"}}' ~/Documents/Samples/200KB.1
```

It is also possible to use identifiers and API parameters:

```
ascli aoc packages send --workspace="my ws" @json:'{"name":"my pack title","recipients":
↪ [{"type":"dropbox","id":"12345"}],"metadata":[{"input_type":"single-text","name":"Project
↪ Id","values":["123"]},{input_type":"single-dropdown","name":"Type","values":["Opt2"]},
↪ {"input_type":"multiple-checkbox","name":"CheckThose","values":["Check1","Check2"]},
↪ {"input_type":"date","name":"Optional Date","values":["2021-01-13T15:02:00.000Z"]}]}'
↪ ~/Documents/Samples/200KB.1
```

5.6.5 Example: List packages in a given shared inbox

When user packages are listed, the following query is used:

```
{"archived":false,"exclude_dropbox_packages":true,"has_content":true,"received":true}
```

To list packages in a shared inbox, the query has to be specified with the shared inbox by name or its identifier. Additional parameters can be specified, as supported by the API (to find out available filters, consult the API definition, or use the web interface in developer mode). The current workspace is added unless specified in the query.

Note: By default, `exclude_dropbox_packages` is set to `true` for user packages, and to `false` for shared inbox packages. This can be overridden in the query.

Using shared inbox name:

```
ascli aoc packages list --query=@json:'{"dropbox_name":"My Shared
↪ Inbox","archived":false,"received":true,"has_content":true,"exclude_dropbox_packages":false,
↪ "include_draft":false,"sort":"-received_at"}'
```

Using shared inbox identifier: first retrieve the ID of the shared inbox, and then list packages with the appropriate filter.

```
shared_box_id=$(ascli aoc packages shared_inboxes show --name='My Shared Inbox' --format=csv
↪ --display=data --fields=id)
```

```
ascli aoc packages list --query=@json:'{"dropbox_id":"$shared_box_id","archived":false,
↪ "received":true,"has_content":true,"exclude_dropbox_packages":false,"include_draft":false,
↪ "sort":"-received_at"}'
```

5.6.6 Example: Receive all packages from a given shared inbox

```
ascli aoc packages recv ALL --workspace=_workspace_ --once-only=yes --lock-port=12345
↪ --query=@json:'{"dropbox_name":"_shared_inbox_name_","archived":false,"received":true,
↪ "has_content":true,"exclude_dropbox_packages":false,"include_draft":false}'
↪ --ts=@json:'{"resume_policy":"sparse_csum","target_rate_kbps":50000}'
```

5.6.7 Example: Send a package with files from the Files app

Find files in Files app:

```
ascli aoc files browse /src_folder
```

name	type	recursive_size	size	modified_time	access_level
sample_video	link			2020-11-29T22:49:09Z	edit
100G	file		107374182400	2021-04-21T18:19:25Z	edit
10M.dat	file		10485760	2021-05-18T08:22:39Z	edit
Test.pdf	file		1265103	2022-06-16T12:49:55Z	edit

Let's send a package with the file `10M.dat` from subfolder `/src_folder` in a package:

```
ascli aoc files node_info /src_folder --format=json --display=data | ascli aoc packages send
↪ @json: '{"name": "test", "recipients": ["someuser@example.com"]}' 10M.dat --transfer=node
↪ --transfer-info=@json:@stdin:
```

5.6.8 Receive new packages only (Cargo)

It is possible to automatically download new packages, like using Aspera Cargo:

```
ascli aoc packages recv ALL --once-only=yes --lock-port=12345
```

- `ALL` (case-sensitive) will download all packages
- `--once-only=yes` keeps memory of any downloaded package in persistency files located in the configuration folder
- `--lock-port=12345` ensures that only one instance is started at the same time, to avoid running two downloads in parallel

Typically, one would execute this command on a regular basis, using the method of your choice: see [Scheduler](#).

5.7 Example: Content of a received Package

Some `node` operations are available for a package, such as `browse` and `find`.

To list the content of a package, use command `packages browse <package id> <folder>`:

```
ascli aoc package browse my5CnbeWng /
```

To list recursively, use command `find`.

To download only some files listed in the package, just add the path of the files on the command line.

For advanced users, it's also possible to pipe node information for the package and use node operations:

```
ascli aoc package node_info <package ID here> / --format=json --show-secrets=yes --display=data |
↪ ascli node -N --preset=@json:@stdin: access_key do self browse /
```

5.8 Files

The Files application presents a `Home` folder to users in a given workspace. Files located here are either user's files, or shared folders.

Note: All commands under `files` are the same as under `access_keys do self` for plugin `node`, i.e. `gen4/access key operations`.

5.8.1 Download Files

The general download command is:

```
ascli aoc files download <source folder path> <source filename 1> ...
```

I.e. the first argument is the source folder, and the following arguments are the source file names in this folder.

If a single file or folder is to be downloaded, then a single argument can be provided.

```
ascli aoc files download <single file path>
```

5.8.2 Shared folders

Like in AoC web UI, "Shared Folders" can be created and shared with either Private or Public links. Private links require the collaborator to log in to access the shared folder. Public links include a passcode that enables the user to access the shared folder without login-in.

Shared folders can be created either:

- by users in a workspace: they can share personal folders with other users in the same workspace: `aoc files perm`
- by administrators: they can share a folder with users in any workspace: `aoc admin node do [node ID] perm`

Technically (API), shared folder are managed through [permissions](#) on node and an event is sent to AoC to create a [link](#) in the user's home folder to the shared folder. In both cases, it is necessary to specify a workspace.

The basic payload (last argument at creation usually specified with `@json:`) is:

```
{
  "file_id": "50",
  "access_levels": ["list", "read", "write", "delete", "mkdir", "rename", "preview"],
  "access_type": "user",
  "access_id": "john@example.com",
  "tags": {...},
}
```

`ascli` expects the same payload for creation. `ascli` automatically populates this payload like this:

- `file_id` : the ID of the folder to share whose path is specified in the command line
- `access_levels` : are set by default to full access.
- `tags` : are set with expected values for AoC: username who creates, and workspace in which the shared folder is created.
- `access_type` and `access_id` : need to be set by the user, or using special key as follows.

To change `access_levels`, just provide the list of levels in the `@json:` payload.

In order to declare/create the shared folder in the workspace, a special value for `access_id` is used: `ASPERA_ACCESS_KEY_ADMIN_WS_[workspace ID]`. This is conveniently set by `ascli` using an empty string for the pseudo key `with`. In order to share a folder with a different, special tags are set, but this is conveniently done by `ascli` using the `as` key.

The following optional additional helper keys are supported by `ascli`:

- `with` : Recipient of shared folder. Can be a username, a group name, or a workspace name. `ascli` will resolve the name to the proper type and ID in fields `access_type` and `access_id`. If the value is the empty string, then it declares the shared folder in the workspace (first action to do, see below).
- `link_name` : The name of the link file created in the user's home folder for private links.
- `as` : The name of the link file created in the user's home folder for admin shared folders.
- List permissions on a shared folder as user

```
ascli aoc files perm /shared_folder_test1 list
```

- Share a personal folder with other users

```
ascli aoc files perm /shared_folder_test1 create @json: '{"with": "laurent"}'
```

- Revoke shared access

```
ascli aoc files perm /shared_folder_test1 delete 6161
```

Public and Private short links can be managed with command:

```
ascli aoc files short_link _path_here_ private create
ascli aoc files short_link _path_here_ private list
ascli aoc files short_link _path_here_ public list
ascli aoc files short_link public delete _id_
```

- Create an admin shared folder and shared with a user or group or workspace

```
ascli aoc admin node do 1234 mkdir folder_on_node
ascli aoc admin node do 1234 perm folder_on_node create
  ↳ @json: '{"with":"","as":"folder_for_users"}' --workspace="my ws"
ascli aoc admin node do 1234 perm folder_on_node create
  ↳ @json: '{"with":"john@example.com","as":"folder_for_users"}' --workspace="my ws"
ascli aoc admin node do 1234 perm folder_on_node create @json: '{"with":"group
  ↳ 1","as":"folder_for_users"}' --workspace="my ws"
ascli aoc admin node do 1234 perm folder_on_node create @json: '{"with":"my
  ↳ ws","as":"folder_for_users"}' --workspace="my ws"
```

| *Note:* The node can be conveniently identified using the percent selector instead of numerical ID.

5.8.3 Cross Organization transfers

It is possible to transfer files directly between organizations without having to first download locally and then upload...

Although optional, the creation of **Option Preset** is recommended to avoid placing all parameters in the command line.

Procedure to send a file from org1 to org2:

- Get access to Organization 1 and create an **Option Preset**: e.g. `org1`, for instance, use the **Wizard**
- Check that access works and locate the source file e.g. `mysourcefile`, e.g. using command `files browse`
- Get access to Organization 2 and create an **Option Preset**: e.g. `org2`
- Check that access works and locate the destination folder `mydestfolder`
- Execute the following:

```
ascli -Porg1 aoc files node_info /mydestfolder --format=json --display=data | ascli -Porg2 aoc
  ↳ files upload mysourcefile --transfer=node --transfer-info=@json:@stdin:
```

Explanation:

- `-Porg1 aoc` use Aspera on Cloud plugin and load credentials for `org1`
- `files node_info /mydestfolder` generate transfer information including Node API credential and root ID, suitable for the next command
- `--format=json` format the output in JSON (instead of default text table)
- `--display=data` display only the result, and remove other information, such as workspace name
- `|` the standard output of the first command is fed into the second one
- `-Porg2 aoc` use Aspera on Cloud plugin and load credentials for `org2`
- `files upload mysourcefile` upload the file named `mysourcefile` (located in `org1`)
- `--transfer=node` use transfer agent type `node` instead of default `direct`
- `--transfer-info=@json:@stdin:` provide `node` transfer agent information, i.e. Node API credentials, those are expected in JSON format and read from standard input

5.8.4 Find Files

The command `aoc files find` allows searching for files in a given workspace.

It works also on `node` resource using the `v4` command:

```
ascli aoc admin node --name='my node name' --secret='my_secret_here' v4 find ...
```

For instructions, refer to section `find` for plugin `node`.

5.9 Aoc sample commands

| *Note:* Add `ascli aoc` in front of the commands:

```

admin analytics transfers nodes
admin analytics transfers organization
  ↪ --query=@json: '{"status": "completed", "direction": "receive", "limit": 2}'
  ↪ --notify-to=my_email_external --notify-template=@ruby: '%Q{From: <%=from_name%>
  ↪ <<%=from_email%>>\nTo: <<%=to%>>\nSubject: <%=ev["files_completed"]%> files
  ↪ received\n\n<%=ev.to_yaml%>}'
admin analytics transfers users --once-only=yes
admin application list
admin ats access_key create --cloud=aws --region=my_region
  ↪ --params=@json: '{"id": "ak_aws", "name": "my test key
  ↪ AWS", "storage": {"type": "aws_s3", "bucket": "my_bucket", "credentials": {"access_key_id":
  ↪ "my_access_key", "secret_access_key": "my_secret_key"}, "path": "/"}}'
admin ats access_key create --cloud=softlayer --region=my_region
  ↪ --params=@json: '{"id": "ak1ibmcloud", "secret": "my_secret_here", "name": "my test
  ↪ key", "storage": {"type": "ibm-s3", "bucket": "my_bucket", "credentials": {"access_key_id":
  ↪ "my_access_key", "secret_access_key": "my_secret_key"}, "path": "/"}}'
admin ats access_key delete ak1ibmcloud
admin ats access_key list --fields=name,id
admin ats access_key node ak1ibmcloud --secret=my_secret_here browse /
admin ats cluster clouds
admin ats cluster list
admin ats cluster show --cloud=aws --region=eu-west-1
admin ats cluster show 1f412ae7-869a-445c-9c05-02ad16813be2
admin auth_providers list
admin client list
admin client_access_key list
admin client_registration_token create @json: '{"data": {"name": "test_client_reg1",
  ↪ "client_subject_scopes": ["alee", "aejd"], "client_subject_enabled": true}}'
admin client_registration_token delete client_reg_id
admin client_registration_token list
admin contact list
admin dropbox list
admin dropbox_membership list
admin group list
admin kms_profile list
admin node do %name:my_node_name --secret=my_ak_secret browse /
admin node do %name:my_node_name --secret=my_ak_secret browse /folder_sub --node-cache=no
admin node do %name:my_node_name --secret=my_ak_secret delete /folder1
admin node do %name:my_node_name --secret=my_ak_secret delete /folder_sub
admin node do %name:my_node_name --secret=my_ak_secret mkdir /folder1
admin node do %name:my_node_name --secret=my_ak_secret mkdir /folder_sub
admin node do %name:my_node_name --secret=my_ak_secret v3 access_key create
  ↪ @json: '{"id": "testsub1", "storage": {"path": "/folder_sub"}}'
admin node do %name:my_node_name --secret=my_ak_secret v3 access_key delete testsub1
admin node do %name:my_node_name --secret=my_ak_secret v3 events
admin node do %name:my_node_name delete test_shared_folder
admin node do %name:my_node_name mkdir test_shared_folder
admin node do %name:my_node_name perm test_shared_folder create
  ↪ @json: '{"with": "", "as": "other_name_shared"}' --workspace=my_workspace_shared_inbox
admin node do %name:my_node_name perm test_shared_folder create
  ↪ @json: '{"with": "my_user_email", "as": "other_name_shared"}'
  ↪ --workspace=my_workspace_shared_inbox
admin node do %name:my_node_name perm test_shared_folder create
  ↪ @json: '{"with": "my_user_group", "as": "other_name_shared"}'
  ↪ --workspace=my_workspace_shared_inbox
admin node list
admin operation list
admin organization show
admin package list --http-options=@json: '{"read_timeout": 120.0}'
admin saml_configuration list
admin self show
admin short_link list
admin subscription account
admin subscription usage
admin subscription usage MONTH

```



```

admin user list
admin user modify %name:my_user_email @json: '{"deactivated":false}'
admin workspace list
admin workspace_membership list
admin workspace_membership list --fields=ALL --query=@json: '{"page":1,"per_page":50,"embed":
  ↳ "member","inherited":false,"workspace_id":11363,"sort":"name"}'
automation workflow action wf_id create @json: '{"name":"toto"}' \
automation workflow create @json: '{"name":"test_workflow"}'
automation workflow delete wf_id
automation workflow list
automation workflow list --query=@json: '{"show_org_workflows":"true"}' --scope=admin:all
automation workflow list --select=@json: '{"name":"test_workflow"}' --fields=id --format=csv
  ↳ --display=data --output=test
bearer_token --display=data --scope=user:all
files bearer /
files bearer_token_node / --cache-tokens=no
files browse /
files browse / --url=my_private_link
files browse / --url=my_public_link_folder_no_pass
files browse / --url=my_public_link_folder_pass --password=my_public_link_password
files browse my_remote_file
files browse my_remote_folder
files browse my_remote_folder/
files delete /testsrc
files download --transfer=connect testdst/test_file.bin
files download --transfer=desktop testdst/test_file.bin
files find /
files find / '\.partial$'
files find / @ruby: '->(f){f["type"].eq?("file")}'
files http_node_download --to-folder=. testdst/test_file.bin
files mkdir /testsrc
files modify my_test_folder
files permission my_test_folder list
files rename /some_folder testdst
files short_link /testdst private create
files short_link /testdst private list
files short_link /testdst public create
files show %id:aoc_file_id
files show /
files show testdst/test_file.bin
files sync admin status --sync-info=@json: '{"name":"my_aoc_sync2","reset":true,"direction":
  ↳ "pull","local":{"path":"/data/local_sync"},"remote":{"path":"/testdst"}}'
files sync admin status --sync-info=@json: '{"sessions":[{"name":"my_aoc_sync1","direction":
  ↳ "pull","local_dir":"/data/local_sync","remote_dir":"/testdst","reset":true}]}'
files sync start --sync-info=@json: '{"name":"my_aoc_sync1","reset":true,"direction":"pull",
  ↳ "local":{"path":"/data/local_sync"},"remote":{"path":"/testdst"}}'
files sync start --sync-info=@json: '{"name":"my_aoc_sync2","reset":true,"direction":"pull",
  ↳ "local":{"path":"/data/local_sync"},"remote":{"path":"/testdst"}}'
files sync start --sync-info=@json: '{"sessions":[{"name":"my_aoc_sync1","direction":"pull",
  ↳ "local_dir":"/data/local_sync","remote_dir":"/testdst","reset":true}]}'
files sync start pull /testdst /data/local_sync --sync-info=@json: '{"reset":true,"quiet":false}'
files sync start pull /testdst /data/local_sync --sync-info=@json: '{"sessions":[{"reset":true}]}'
files thumbnail my_test_folder/video_file.mpg
files thumbnail my_test_folder/video_file.mpg --query=@json: '{"text":true,"double":true}'
files transfer push /testsrc --to-folder=/testdst test_file.bin
files upload --to-folder=/ test_file.bin --url=my_public_link_folder_no_pass
files upload --to-folder=/testsrc test_file.bin
files upload --workspace=my_other_workspace --to-folder=my_other_folder test_file.bin
  ↳ --transfer=node --transfer-info=@json:@stdin:
files v3 info
gateway --pid-file=pid_aocfxgw https://localhost:12345/aspera/faspex &
org --url=my_public_link_recv_from_aoc_user
organization
packages browse package_id3 /

```



```

packages list
packages list --query=@json: '{"dropbox_name": "my_shared_inbox_name", "sort": "-received_at",
↪ "archived": false, "received": true, "has_content": true, "exclude_dropbox_packages": false}'
packages receive ALL --once-only=yes --to-folder=. --lock-port=12345
packages receive ALL --once-only=yes --to-folder=. --lock-port=12345
↪ --query=@json: '{"dropbox_name": "my_shared_inbox_name", "archived": false, "received": true,
↪ "has_content": true, "exclude_dropbox_packages": false, "include_draft": false}'
↪ --ts=@json: '{"resume_policy": "sparse_csum", "target_rate_kbps": 50000}'
packages receive INIT --once-only=yes --query=@json: '{"dropbox_name": "my_shared_inbox_name"}'
packages receive package_id3 --to-folder=.
packages receive package_id3 --to-folder=. /
packages send --workspace=my_workspace_shared_inbox --validate-metadata=yes
↪ @json: '{"name": "$(notdir test) PACKAGE_TITLE_BASE", "recipients": ["my_shared_inbox_meta"],
↪ "metadata": [{"input_type": "single-text", "name": "Project
↪ Id", "values": ["123"]}, {"input_type": "single-dropdown", "name": "Type", "values": ["Opt2"]},
↪ {"input_type": "multiple-checkbox", "name": "CheckThose", "values": ["Check1", "Check2"]},
↪ {"input_type": "date", "name": "Optional Date", "values": ["2021-01-13T15:02:00.000Z"]}]}'
↪ test_file.bin
packages send --workspace=my_workspace_shared_inbox --validate-metadata=yes
↪ @json: '{"name": "$(notdir test)
↪ PACKAGE_TITLE_BASE", "recipients": ["my_shared_inbox_meta"], "metadata": {"Project
↪ Id": "456", "Type": "Opt2", "CheckThose": ["Check1", "Check2"], "Optional
↪ Date": "2021-01-13T15:02:00.000Z"}' test_file.bin
packages send --workspace=my_workspace_shared_inbox --validate-metadata=yes
↪ @json: '{"name": "$(notdir test) PACKAGE_TITLE_BASE", "recipients": ["my_shared_inbox_meta"],
↪ "metadata": {"Type": "Opt2", "CheckThose": ["Check1", "Check2"], "Optional
↪ Date": "2021-01-13T15:02:00.000Z"}' test_file.bin
packages send --workspace=my_workspace_shared_inbox @json: '{"name": "$(notdir test)
↪ PACKAGE_TITLE_BASE", "recipients": ["my_shared_inbox_name"]}' test_file.bin
packages send @json: '{"name": "$(notdir test)
↪ PACKAGE_TITLE_BASE", "recipients": ["my_email_external"]}'
↪ --new-user-option=@json: '{"package_contact": true}' test_file.bin
packages send @json: '{"name": "$(notdir test)
↪ PACKAGE_TITLE_BASE", "recipients": ["my_email_internal"], "note": "my note"}' test_file.bin
packages send @json: '{"name": "$(notdir test) PACKAGE_TITLE_BASE"}' test_file.bin
↪ --url=my_public_link_send_aoc_user --password=my_public_link_send_use_pass
packages send @json: '{"name": "$(notdir test) PACKAGE_TITLE_BASE"}' test_file.bin
↪ --url=my_public_link_send_shared_inbox
packages shared_inboxes list
packages shared_inboxes show %name:my_shared_inbox_name
remind --username=my_user_email
servers
tier_restrictions
user pref modify @json: '{"default_language": "en-us"}'
user pref show
user profile modify @json: '{"name": "dummy change"}'
user profile show
user workspaces current
user workspaces list

```

Chapter 6

Plugin: **ats** : IBM Aspera Transfer Service

ATS is usable either :

- From an AoC subscription : `ascli aoc admin ats` : use AoC authentication
- Or from an IBM Cloud subscription : `ascli ats` : use IBM Cloud API key authentication

6.1 IBM Cloud ATS : Creation of API key

This section is about using ATS with an IBM cloud subscription. If you are using ATS as part of AoC, then authentication is through AoC, not IBM Cloud.

First get your IBM Cloud API key. For instance, it can be created using the IBM Cloud web interface, or using command line:

```
ibmcloud iam api-key-create mykeyname -d 'my sample key'
```

```
OK
API key mykeyname was created
```

Please preserve the API key! It cannot be retrieved after it's created.

Name	mykeyname
Description	my sample key
Created At	2019-09-30T12:17:0000
API Key	my_secret_api_key_here
Locked	false
UUID	ApiKey-05b8fadf-e7fe-4bc4-93a9-6fd348c5ab1f

References:

- https://console.bluemix.net/docs/iam/userid_keys.html#userapikey
- <https://ibm.ibmaspera.com/helpcenter/transfer-service>

Then, to register the key by default for the **ats** plugin, create a preset. Execute:

```
ascli config preset update my_ibm_ats --ibm-api-key=my_secret_api_key_here
```

```
ascli config preset set default ats my_ibm_ats
```

```
ascli ats api_key instances
```

```
+-----+
| instance |
+-----+
| aaaaaaaa-bbbb-cccc-dddd-eeeeeeeeeeee |
+-----+
```

```
ascli config preset update my_ibm_ats --instance=aaaaaaa-bbbb-cccc-dddd-eeeeeeeeeeee
```

```
ascli ats api_key create
```

```
+-----+-----+
| field | value |
+-----+-----+
| id     | ats_XXXXXXXXXXXXXXXXXXXXXXX |
| secret | YYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYY |
+-----+-----+
ascli config preset update my_ibm_ats --ats-key=ats_XXXXXXXXXXXXXXXXXXXXXXX
↪ --ats-secret=YYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYYY
```

6.2 ATS Access key creation parameters

When creating an ATS access key, the option `params` must contain an extended value with the creation parameters. Those are directly the parameters expected by the [ATS API](#).

6.3 Misc. Examples

Example: create access key on IBM Cloud (Softlayer):

```
ascli ats access_key create --cloud=softlayer --region=ams --params=@json: '{"storage":{"type": "softlayer_swift", "container": "_container_name_", "credentials":{"api_key": "my_secret_here", "username": "_name_: _usr_name_", "path": "/"}, "id": "_optional_id_", "name": "_optional_name_"}}'
```

Example: create access key on AWS:

```
ascli ats access_key create --cloud=aws --region=eu-west-1
↪ --params=@json: '{"id": "myaccesskey", "name": "laurent key AWS", "storage":{"type": "aws_s3", "bucket": "my-bucket", "credentials":{"access_key_id": "_access_key_id_here_", "secret_access_key": "my_secret_here"}, "path": "/laurent"}}'
```

Example: create access key on Azure SAS:

```
ascli ats access_key create --cloud=azure --region=eastus
↪ --params=@json: '{"id": "myaccesskey", "name": "laurent key azure", "storage":{"type": "azure_sas", "credentials":{"shared_access_signature": "https://containername.blob.core.windows.net/blobname?sr=c&...", "path": "/"}}'
```

Note: The blob name is mandatory after server address and before parameters, and that parameter `sr=c` is mandatory.

Example: create access key on Azure:

```
ascli ats access_key create --cloud=azure --region=eastus
↪ --params=@json: '{"id": "myaccesskey", "name": "laurent key azure", "storage":{"type": "azure", "credentials":{"account": "myaccount", "key": "myaccesskey", "storage_endpoint": "myblob"}, "path": "/"}}'
```

delete all my access keys:

```
ascli ats access_key list --field=id --format=csv | ascli ats access_key delete @lines:@stdin:
↪ --bulk=yes
```

The parameters provided to ATS for access key creation are the ones of [ATS API](#) for the `POST /access_keys` endpoint.

6.4 Ats sample commands

Note: Add `ascli ats` in front of the commands:

```
access_key cluster ak2ibmcloud --secret=my_secret_here
access_key create --cloud=aws --region=my_region --params=@json: '{"id": "ak_aws", "name": "my test key AWS", "storage":{"type": "aws_s3", "bucket": "my_bucket", "credentials":{"access_key_id": "my_access_key", "secret_access_key": "my_secret_key"}, "path": "/"}}'
```

```

access_key create --cloud=softlayer --region=my_region
↪ --params=@json: '{"id": "ak2ibmcloud", "secret": "my_secret_here", "name": "my test
↪ key", "storage": {"type": "ibm-s3", "bucket": "my_bucket", "credentials": {"access_key_id":
↪ "my_access_key", "secret_access_key": "my_secret_key"}, "path": "/"}}'
access_key delete ak2ibmcloud
access_key delete ak_aws
access_key entitlement ak2ibmcloud
access_key list --fields=name,id
access_key node ak2ibmcloud browse / --secret=my_secret_here
access_key show ak2ibmcloud
api_key create
api_key instances
api_key list
cluster clouds
cluster list
cluster show --cloud=aws --region=eu-west-1
cluster show 1f412ae7-869a-445c-9c05-02ad16813be2

```

Chapter 7

Plugin: `server` : IBM Aspera High Speed Transfer Server (SSH)

The `server` plugin is used for operations on Aspera HSTS using SSH authentication. It is the original way of accessing an Aspera Server, often used for server to server transfers. An SSH session is established, authenticated with either a password or an SSH private key, then commands `ascp` (for transfers) and `ascmd` (for file operations) are executed.

The URL to be provided with option `url` shall be like `ssh://_server_address_:33001`, then option `username` is used to specify the transfer user, and finally either option `password` or `ssh_keys` (with one or several paths) for the authentication.

Typically:

```
`ascli` server --url=ssh://hsts.example.com:33001 --username=john --password=_something_here_ ...
`ascli` server --url=ssh://hsts.example.com:33001 --username=john --ssh-keys=~/.ssh/id_rsa ...
```

7.1 Server sample commands

I *Note: Add `ascli server` in front of the commands:*

```
browse /
browse / --password=@none: --ssh-options=@json: '{"number_of_password_prompts":0}'
↪ --ssh-keys=$aspera_key_path
browse my_inside_folder/test_file.bin
browse my_upload_folder/target_hot
cp my_inside_folder/test_file.bin my_upload_folder/200KB.2
delete my_inside_folder
delete my_upload_folder/to.delete
df
download my_inside_folder/test_file.bin --to-folder=.
↪ --transfer-info=@json: '{"wss":false,"resume":{"iter_max":1}}'
download my_large_file --to-folder=my_upload_folder --transfer=node
↪ --ts=@json: '{"resume_policy":"none"}'
du /
health transfer --to-folder=my_upload_folder --format=nagios
info
md5sum my_inside_folder/test_file.bin
mkdir my_inside_folder --logger=stdout
mkdir my_upload_folder/target_hot
mv my_upload_folder/200KB.2 my_upload_folder/to.delete
sync admin status --sync-info=@json: '{"name":"sync2","local":{"path":"/data/local_sync"}}'
sync admin status --sync-info=@json: '{"name":"sync2"}'
sync admin status my_srv_sync
↪ --sync-info=@json: '{"sessions":[{"name":"my_srv_sync","local_dir":"/data/local_sync"}]}'
```

```

sync start --sync-info=@json: '{"instance":{"quiet":false},"sessions":[{"name":"my_srv_sync",
  ↳ "direction":"pull","remote_dir":"my_inside_folder","local_dir":"/data/local_sync","reset":
  ↳ true}]}'
sync start --sync-info=@json: '{"name":"sync2","local":{"path":"/data/local_sync"},"remote":
  ↳ {"path":"my_inside_folder"},"reset":true,"quiet":false}'
upload 'faux:///test1?100m' 'faux:///test2?100m' --to-folder=/Upload
  ↳ --ts=@json: '{"target_rate_kbps":1000000,"resume_policy":"none","precalculate_job_size":true}'
upload 'faux:///test1?100m' 'faux:///test2?100m' --to-folder=/Upload
  ↳ --ts=@json: '{"target_rate_kbps":1000000,"resume_policy":"none","precalculate_job_size":true}'
  ↳ --transfer-info=@json: '{"quiet":false}' --progress=no
upload 'test_file.bin' --to-folder=my_inside_folder --ts=@json: '{"multi_session":3,
  ↳ "multi_session_threshold":1,"resume_policy":"none","target_rate_kbps":100000}'
  ↳ --transfer-info=@json: '{"spawn_delay_sec":2.5,"multi_incr_udp":false}' --progress-bar=yes
upload --sources=@ts --transfer-info=@json: '{"ascp_args":["--file-list","filelist.txt"]}'
  ↳ --to-folder=my_inside_folder
upload --sources=@ts
  ↳ --transfer-info=@json: '{"ascp_args":["--file-pair-list","file_pair_list.txt"]}'
upload --sources=@ts --ts=@json: '{"paths":[{"source":"test_file.bin","destination":
  ↳ "my_inside_folder/other_name_4"}]}' --transfer=transferd
upload --src-type=pair 'test_file.bin' my_inside_folder/other_name_2
  ↳ --notify-to=my_email_external --transfer-info=@json: '{"ascp_args":["-1","100m"]}'
upload --src-type=pair --sources=@json: '["test_file.bin","my_inside_folder/other_name_3"]'
  ↳ --transfer-info=@json: '{"quiet":false}' --progress=no
upload --src-type=pair test_file.bin my_upload_folder/other_name_5 --ts=@json: '{"cipher":"aes-
  ↳ 192-gcm","content_protection":"encrypt","content_protection_password":"my_secret_here",
  ↳ "cookie":"biscuit","create_dir":true,"delete_before_transfer":false,"delete_source":false,
  ↳ "exclude_newer_than":"-1","exclude_older_than":"-10000","fasp_port":33001,"http_fallback":
  ↳ false,"multi_session":0,"overwrite":"diff+older","precalculate_job_size":true,
  ↳ "preserve_access_time":true,"preserve_creation_time":true,"rate_policy":"fair",
  ↳ "resume_policy":"sparse_csum","symlink_policy":"follow"}'
upload --to-folder=my_upload_folder/target_hot --lock-port=12345
  ↳ --transfer-info=@json: '{"ascp_args":["--remove-after-transfer","--remove-empty-directories",
  ↳ "--exclude-newer-than=-8","--src-base","source_hot"]}' source_hot

```

7.2 Authentication on Server with SSH session

If SSH is the session protocol (by default i.e. not WSS), then following session authentication methods are supported:

- `password` : SSH password
- `ssh_keys` : SSH keys (Multiple SSH key paths can be provided.)

If `username` is not provided then the default transfer user `xfer` is used.

If neither SSH password nor key is provided and a transfer token is provided in transfer spec (option `ts`), then standard SSH bypass key(s) is used.

Example:

```

ascli server --url=ssh://_server_address_:33001 ... --ts=@json: '{"token":"Basic _token_here_"}'

```

Note: If you need to use the Aspera public keys, then specify an empty token: `--ts=@json: '{"token":""}'` : Aspera public SSH keys will be used, but the protocol will ignore the empty token.

The value of the `ssh_keys` option can be a single value or an `Array`. Each value is a path to a private key and is expanded (`~` is replaced with the user's home folder).

Examples:

```

ascli server --ssh-keys=~/.ssh/id_rsa
ascli server --ssh-keys=@list:~/.ssh/id_rsa
ascli server --ssh-keys=@json: '["~/.ssh/id_rsa"]'

```

For file operation command (browse, delete), the Ruby SSH client library `Net::SSH` is used and provides several options settable using option `ssh_options`.

For a list of SSH client options, refer to the Ruby documentation of `Net::SSH`.

Among the 50 available SSH options:

- `verbose`
- `use_agent`
- `passphrase`

By default, the SSH library will check if a local `ssh-agent` is running.

On Linux, if you get an error message such as:

```
ERROR -- net.ssh.authentication.agent: could not connect to ssh-agent: Agent not configured
```

or on Windows:

```
ERROR -- net.ssh.authentication.agent: could not connect to ssh-agent: pageant process not  
↪ running
```

This means that your environment suggests using an agent, but you don't have such an SSH agent running, then:

- Check env var: `SSH_AGENT_SOCK`
- Check your file: `$HOME/.ssh/config`
- Check if the SSH key is protected with a passphrase (then, use the `passphrase` SSH option)
- [Check the Ruby SSH manual](#)
- To disable the use of `ssh-agent`, use the option `ssh_options` like this:

```
ascli server --ssh-options=@json: '{"use_agent": false}' ...
```

Note: This can also be set using a preset.

If one of the SSH private keys is passphrase-protected, then option `passphrase` can be used. It is equivalent to setting both options `ssh_options.passphrase` and `ts.ssh_private_key_passphrase`.

7.3 Other session channels for `server`

URL schemes `local` and `https` are also supported (mainly for testing purpose). (`--url=local:` , `--url=https://...`)

- `local` will execute `ascmd` locally, instead of using an SSH connection.
- `https` will use Web Socket Session: This requires the use of a transfer token. For example a `Basic` token can be used.

As, most of the time, SSH is used, if a `http` scheme is provided without token, the plugin will fallback to SSH and port 33001.

7.4 Examples: `server`

One can test the `server` application using the well known demo server:

```
ascli config initdemo  
ascli server browse /aspera-test-dir-large  
ascli server download /aspera-test-dir-large/200MB
```

`initdemo` creates an **Option Preset** `demoserver` and set it as default for plugin `server`.

If an SSH private key is used for authentication with a passphrase, the passphrase needs to be provided to both options: `ssh_options` (for browsing) and `ts` (for transfers):

```
ascli server --url=ssh://_server_address_here_:33001 --username=_user_here_  
↪ --ssh_keys=_private_key_path_here_ --passphrase=_passphrase_here_
```

Chapter 8

Plugin: `node` : IBM Aspera High Speed Transfer Server Node

This plugin gives access to capabilities provided by the HSTS Node API.

The authentication is `username` and `password` or `access_key` and `secret` through options: `username` and `password`.

Note: Capabilities of this plugin are used in other plugins which access to the Node API, such as `aoc`, `ats`, `shares`.

Note: This plugin can be used with any type of Aspera Node, either on premise or ATS, provided that you have Node API credentials. Those credentials can be either Node API user or Access Key (e.g. on ATS).

8.1 File Operations

It is possible to do `gen3/node user` operations:

- `browse`
- Transfer (`upload` / `download` / `sync`)
- `delete`
- ...

When using an access key, so called `gen4/access key` API is also supported through sub commands using `access_keys do self`.

Example:

- `ascli node browse /` : list files with `gen3/node user` API
- `ascli node access_key do self browse /` : list files with `gen4/access key` API

8.1.1 Browse

Native API parameters can be placed in option `query`.

Special parameters can be placed in option `query` for "gen3" browse:

Parameter	Description
<code>recursive</code>	Recursively list files
<code>max</code>	Maximum number of files to list
<code>self</code>	Offset in the list

Option `node_cache` can be set to `no` to avoid use of folder cache (Redis) and force actual read of file system.

8.2 Operation `find` on `gen4/access key`

The command `find <folder> [filter_expr]` is available for `gen4/access key`, under `access_keys do self`.

The argument `<folder>` is mandatory and is the root from which search is performed. The argument `[filter_expr]` is optional and represent the matching criteria.

It recursively scans storage to find files/folders matching criteria and then returns a list of matching entries.

`[filter_expr]` is either:

- Optional (default) : all files and folder are selected
- Type `String` : the expression is similar to shell globbing, refer to `Ruby` function: `File.fnmatch`
- Type `Proc` : the expression is a `Ruby` lambda that takes one argument: a `Hash` that contains the current folder entry to test. Refer to the following examples.

Examples of expressions:

- Find all files and folders under `/`

```
ascli node access_keys do self find
```

- Find all text files `/Documents`

```
ascli node access_keys do self find /Documents '*.txt'
```

The following are examples of `Ruby` lambda code to be provided in the following template command:

```
ascli node access_keys do self find / @ruby:'->(f){[code here]}'
```

Note: Single quotes are used here above to protect the whole `Ruby` expression from the shell. Then double quotes are used for strings in the `Ruby` expression to not mix with the shell.

- Find files more recent than 100 days

```
->(f){f["type"].eq?("file") and (DateTime.now-DateTime.parse(f["modified_time"]))<100}
```

- Find files older than 1 year

```
->(f){f["type"].eq?("file") and (DateTime.now-DateTime.parse(f["modified_time"]))>365}
```

- Find files larger than 1 MB

```
->(f){f["type"].eq?("file") and f["size"].to_i>1000000}
```

- Filter out files beginning with `._` or named `.DS_Store` :

```
->(f){!(f["name"].start_with?("_") or f["name"].eq?(".DS_Store"))}
```

- Match files using a `Ruby` `Regex` : `\.gif$`

```
->(f){f["name"].match?(/\.gif$/)}
```

`ascli` commands can be piped in order to combine operations, such as `find` and `delete`:

```
ascli node access_keys do self find / @ruby:'->(f){f["type"].eq?("file") and  
↪ (DateTime.now-DateTime.parse(f["modified_time"]))>365}' --fields=path --format=csv | ascli  
↪ node --bulk=yes delete @lines:@stdin:
```

Note: The pipe `|` character on the last line.

8.3 Listing transfer events

When a transfer is run, its information is stored (typically, 1 day) in the HSTS database (Redis). This information can be retrieved with command: `transfer list`.

If the number of transfers is too large, then the list will be retrieved using several API calls.

In addition, it is possible to list "only new information" using option `once_only`.

```
ascli node transfer list --once-only=yes
```

The `iteration_token` that keeps memory of the latest event is stored in the persistence repository of `ascli`. To reset it, add option: `--query=@json:{"reset": true}`. To list only a number of events, use the `max` parameter in query. Other parameters are directly transmitted to the underlying API (`GET /ops/transfers`).

8.4 Central

The central sub-command uses the `reliable_query` API (session and file). It allows listing transfer sessions and transferred files.

Filtering can be applied:

```
ascli node central file list
```

By providing the `validator` option, offline transfer validation can be done.

Note: See later in this doc, refer to HSTS doc.

8.5 Sync

There are three sync types of operations:

- `sync` : perform a local sync, by executing `async` locally
- `async` : calls legacy `async` API on node : `/async`
- `ssync` : calls newer `async` API on node : `/asyncs`

8.6 FASP Stream

It is possible to start a faspstream session using the Node API:

Use the command `ascli node stream create --ts=@json:<value>`, with `transfer-spec`:

```
{"direction": "send", "source": "udp://233.3.3.4:3000?loopback=1&ttl=2", "destination": "udp://233.3.3.3:3001/", "remote_host": "localhost", "remote_user": "stream", "remote_password": "my_pass_here"}
```

8.7 Watchfolder

Refer to [Aspera documentation](#) for watch folder creation.

`ascli` supports remote operations through the Node API. Operations are:

- Start `watchd` and `watchfolderd` services running as a system user having access to files
- Configure a `Watchfolder` to define automated transfers

```
ascli node service create @json:{"id": "mywatchd", "type": "WATCHD", "run_as": {"user": "user1"}}
ascli node service create
  @json:{"id": "mywatchfolderd", "type": "WATCHFOLDERD", "run_as": {"user": "user1"}}
ascli node watch_folder create @json:{"id": "mywfolder", "source_dir": "/watch1", "target_dir": "/",
  "transport": {"host": "10.25.0.4", "user": "user1", "pass": "mypassword"}}
```

8.8 Out of Transfer File Validation

Follow the Aspera Transfer Server configuration to activate this feature.

The following command lists one file that requires validation, and assign it to the unique validator identifier provided:

```
ascli node central file list --validator=ascli @json:{"file_transfer_filter": {"max_result": 1}}
```

session_uuid	file_id	status	path
1a74444c-...	084fb181-...	validating	/home/xfer.../PKG - my title/200KB.1

To update the status of the file, use the following command:

```
ascli node central file update --validator=ascli @json:'{"files":[{"session_uuid":  
↪ "1a74444c-...", "file_id": "084fb181-...", "status": "completed"}]}'
```

updated

8.9 Example: SHOD to ATS

Scenario: Access to a Shares on Demand (SHOD) server on AWS is provided by a partner. We need to transfer files from this third party SHOD instance into our Azure BLOB storage. Simply create an Aspera Transfer Service instance, which provides access to the Node API. Then create a configuration for the SHOD instance in the configuration file: in section `shares`, a configuration named: `aws_shod`. Create another configuration for the Azure ATS instance: in section `node`, named `azure_ats`. Then execute the following command:

```
ascli node download /share/sourcefile --to-folder=/destination_folder --preset=aws_shod  
↪ --transfer=node --transfer-info=@preset:azure_ats
```

This will get transfer information from the SHOD instance and tell the Azure ATS instance to download files.

8.10 Node file information

When Node API is used with an Access key, extra information can be retrieved, such as preview.

Note: Display of preview on terminal requires installation of extra gem: `rmagick`

```
dnf install -y ImageMagick-devel  
gem install rmagick rainbow
```

For example, it is possible to display the preview of a file, if it exists, using an access key on node:

```
ascli node access_key do self thumbnail /preview_samples/Aspera.mpg
```

Previews are mainly used in AoC, this also works with AoC:

```
ascli aoc files thumbnail /preview_samples/Aspera.mpg
```

Note: To specify the file by its file ID, use the selector syntax: `%id:_file_id_here_`

*Note: To force textual display of the preview on iTerm, prefix command with:
`env -u TERM_PROGRAM -u LC_TERMINAL` or use option: “*

8.11 Create access key

```
ascli node access_key create @json:'{"id":"myaccesskey","secret":"my_secret_here","storage":  
↪ {"type":"local","path":"/data/mydir"}{'
```

Note: The `id` and `secret` are optional. If not provided, they will be generated and returned into the result.

Access keys support extra overriding parameters using parameter: `configuration` and sub keys `transfer` and `server`. For example, an access key can be modified or created with the following options:

```
{"configuration":{"transfer":{"target_rate_cap_kbps":500000}}}
```

The list of supported options can be displayed using command:

```
ascli node info --field=@ruby:'/^access_key_configuration_capabilities.*/'
```

8.12 Generate and use bearer token

Bearer tokens are part of the gen4/access key API. It follows the model of OAuth 2. For example, they are used in Aspera on Cloud. This is also available for developers for any application integrating Aspera. In this API, files, users and groups are identified by an ID (a `String`, e.g. `"125"`, not necessarily numerical).

Bearer tokens are typically generated by the authentication application and then recognized by the Node API. A bearer token is authorized on the node by creating `permissions` on a `folder`.

Bearer tokens can be generated using command `bearer_token` : it takes two arguments:

- The private key used to sign the token.
- The token information, which is a `Hash` containing the following elements:

Parameter	Default	Type	Description
<code>_scope</code>	<code>user:all</code>	Special	Either <code>user:all</code> or <code>admin:all</code>
<code>_validity</code>	86400	Special	Validity in seconds from now.
<code>user_id</code>	-	Mandatory	Identifier of user
<code>scope</code>	<code>node.<access_key>:<scope></code>	Mandatory	API scope, e.g. <code>node.<access_key>:<node scope></code>
<code>expires_at</code>	<code>now+<_validity></code>	Mandatory	Format: <code>%Y-%m-%dT%H:%M:%SZ</code> e.g. <code>2021-12-31T23:59:59Z</code>
<code>auth_type</code>	<code>access_key</code>	Optional	<code>access_key</code> , <code>node_user</code>
<code>group_ids</code>	-	Optional	List of group IDs
<code>organization_id</code>	-	Optional	Organization ID
<code>watermarking_json_base64</code>	-	Optional	Watermarking information (not used)

Note: For convenience, `ascli` provides additional parameters `_scope` and `_validity`. They are not part of the API and are removed from the final payload. They are used respectively to easily set a value for `scope` and `expires_at`.

8.12.1 Bearer token: Environment

An access key shall be created to grant access for transfers to its storage. The access key and its secret represent administrative access to the storage as it has access rights to the whole storage of the access key.

The way to create access keys depends slightly on the type of HSTS:

- If a self-managed Aspera node is used, then a `node user admin` must be created: It has no `docroot` but has at least one file restriction (for testing, one can use `*` to accept creation of an access key with any storage root path). Refer to the Aspera HSTS documentation.
- If Cloud Pak for integration is used, then the node admin is created automatically.
- If Aspera on Cloud or ATS is used, then the SaaS API for access key creation is used.

8.12.2 Bearer token: Preparation

Let's assume that the access key was created, and a default configuration is set to use this access key. Using `ascli`, an access key can be created using the `access_key create` on the node (using main node credentials) or ATS.

- Create a private key (organization key) that will be used to sign bearer tokens:

```
my_private_pem=./myorgkey.pem
ascli config genkey $my_private_pem
```

Note: This key is not used for authentication, it is used to sign bearer tokens. Refer to section [private key](#) for more details on generation.

- The corresponding public key shall be placed as an attribute of the `access key`:

```
ascli node access_key set_bearer_key self @file:$my_private_pem
```

Note: Either the public or private key can be provided, and only the public key is used. This will enable to check the signature of the bearer token. Above command is executed with access key credentials.

Alternatively, use the following equivalent command, as `ascli` kindly extracts the public key with extension `.pub` :

```
ascli node access_key modify %id:self @ruby:'{token_verification_key:
↳ File.read("'$my_private_pem'.pub")}'
```

8.12.3 Bearer token: Configuration for user

- Select a folder for which we want to grant access to a user, and get its identifier:

```
my_folder_id=$(ascli node access_key do self show / --fields=id)
```

Note: Here we simply select `/`, but any folder can be selected in the access key storage.

- Let's designate a user by its ID:

```
my_user_id=777
```

Note: This is an arbitrary identifier, typically managed by the web application. Not related to Linux user IDs or anything else.

- Grant this user access to the selected folder:

```
ascli node access_key do self permission %id:$my_folder_id create
↳ @json:'{"access_type":"user","access_id":"'$my_user_id'"}'
```

- Create a Bearer token for the user:

```
ascli node bearer_token @file:./myorgkey.pem
↳ @json:'{"user_id":"'$my_user_id',"_validity":3600}' --output=bearer.txt
```

8.12.4 Bearer token: User side

Now, let's assume we are the user, the only information received are:

- The URL of the Node API
- A Bearer token
- A file ID for which we have access

Let's use it:

```
ascli node -N --url=... --password="Bearer $(cat bearer.txt)" --root-id=$my_folder_id access_key
↳ do self br /
```

8.13 Node sample commands

Note: Add `ascli node` in front of the commands:

```
--url=https://tst.example.com/path --password="Bearer bearer_666" --root-id=root_id access_key do
↳ self br /
access_key create @json:'{"id":"my_username","secret":"my_password_here","storage":{"type":
↳ "local","path":"/"}'
access_key delete my_username
access_key do my_ak_name browse /
access_key do my_ak_name delete /test_nd_ak2
access_key do my_ak_name delete test_nd_ak3
access_key do my_ak_name download test_nd_ak3 --to-folder=.
access_key do my_ak_name find my_test_folder
access_key do my_ak_name find my_test_folder @ruby:'->(f){f["name"].end_with?(".jpg")}'
access_key do my_ak_name mkdir /tst_nd_ak
access_key do my_ak_name node_info /
access_key do my_ak_name rename /tst_nd_ak test_nd_ak2
access_key do my_ak_name show %id:1
access_key do my_ak_name show /test_nd_ak3
access_key do my_ak_name upload 'faux:///test_nd_ak3?100k' --default-ports=no
access_key do self permission %id:root_id create @json:'{"access_type":"user","access_id":"666"}'
access_key do self permission / show 1
access_key do self show / --fields=id --output=root_id
access_key list
access_key set_bearer_key self @file:my_private_key
access_key show %id:self
```

```

api_details
asperabrowser
async bandwidth 1
async counters 1
async files 1
async list
async show 1
async show ALL
basic_token
bearer_token @file:my_private_key @json:'{"user_id":"666"}' --output=bearer_666
browse / --log-level=trace2
central file list
central file modify --validator=1 @json:'{"files":[]}'
central session list
delete @list:my_upload_folder/a_folder,my_upload_folder/tdlink,my_upload_folder/a_file
delete my_upload_folder/test_file.bin
download my_upload_folder/test_file.bin --to-folder=.
health
http_node_download my_upload_folder/test_file.bin --to-folder=.
info --fpac='function FindProxyForURL(url,host){return "DIRECT"}'
license
mkdir my_upload_folder/a_folder
mkfile my_upload_folder/a_file1 "hello world"
mklink my_upload_folder/a_folder my_upload_folder/tdlink
rename my_upload_folder a_file1 a_file
search / --query=@json:'{"sort":"mtime"}'
service create @json:'{"id":"service1","type":"WATCHD","run_as":{"user":"user1"}}'
service delete service1
service list
slash
space /
ssync bandwidth %name:my_node_sync
ssync counters %name:my_node_sync
ssync create @json:'{"configuration":{"name":"my_node_sync","local":{"path":
↪ "my_local_path_real"},"remote":{"host":"my_host","port":my_port,"user":"my_username","pass":
↪ "my_password_here"},"path":"my_remote_path"}}}'
ssync delete %name:my_node_sync
ssync files %name:my_node_sync
ssync list
ssync show %name:my_node_sync
ssync start %name:my_node_sync
ssync state %name:my_node_sync
ssync stop %name:my_node_sync
ssync summary %name:my_node_sync
stream list
sync admin status --sync-info=@json:'{"name":"my_node_sync2","reset":true,"direction":"pull",
↪ "local":{"path":"/data/local_sync"},"remote":{"path":"/aspera-test-dir-tiny"}}'
sync admin status --sync-info=@json:'{"sessions":[{"name":"my_node_sync1","direction":"pull",
↪ "local_dir":"/data/local_sync","remote_dir":"/aspera-test-dir-tiny","reset":true}}}'
sync start --sync-info=@json:'{"name":"my_node_sync1","reset":true,"quiet":false,"direction":
↪ "pull","local":{"path":"/data/local_sync"},"remote":{"path":"/aspera-test-dir-tiny"}}'
sync start --sync-info=@json:'{"name":"my_node_sync2","reset":true,"direction":"pull","local":
↪ {"path":"/data/local_sync"},"remote":{"path":"/aspera-test-dir-tiny"}}'
transfer list --once-only=yes
transfer list --query=@json:'{"active_only":true}'
transfer list --query=@json:'{"reset":true}' --once-only=yes
transfer sessions
transport
upload --to-folder=my_upload_folder --sources=@ts --ts=@json:'{"paths":[{"source":"/aspera-test-
↪ dir-small/10MB.2"}],"precalculate_job_size":true}' --transfer=node
↪ --transfer-info=@json:'{"url":"https://node.example.com/path@", "username":"my_username",
↪ "password":"my_password_here"}'
upload --username=my_ak_name --password=my_ak_secret test_file.bin
upload test_file.bin --to-folder=my_upload_folder --ts=@json:'{"target_rate_cap_kbps":10000}'

```

watch_folder list

Chapter 9

Plugin: **faspex5** : IBM Aspera Faspex v5

IBM Aspera's newer self-managed application.

3 authentication methods are supported (option `auth`):

Method	Description
<code>jwt</code>	General purpose, private-key based authentication
<code>web</code>	Requires authentication with web browser
<code>boot</code>	Use authentication token copied from browser (experimental)
<code>public_link</code>	Public link authentication (set when option <code>url</code> is a public link)

Note: If you have a Faspex 5 public link, provide it, unchanged, through the option `url`

For a quick start, one can use the wizard, which will help to create an **Option Preset**:

```
ascli config wizard
```

```
argument: url> faspex5.example.com
Multiple applications detected:
+-----+-----+-----+
| product | url                                     | version |
+-----+-----+-----+
| faspex5 | https://faspex5.example.com/aspera/faspex | F5.0.6  |
| server  | ssh://faspex5.example.com:22              | OpenSSH_8.3 |
+-----+-----+-----+
product> faspex5
Using: Faspex at https://faspex5.example.com/aspera/faspex
Please provide the path to your private RSA key, or nothing to generate one:
option: key_path>
Using existing key:
/Users/someuser/.aspera/ascli/my_key
option: username> someuser@example.com
Ask the ascli client ID and secret to your Administrator.
Admin should login to: https://faspex5.example.com/aspera/faspex
Navigate to: :: → Admin → Configurations → API clients
Create an API client with:
- name: ascli
- JWT: enabled
Then, logged in as someuser@example.com go to your profile:
() → Account Settings → Preferences -> Public Key in PEM:
-----BEGIN PUBLIC KEY-----
redacted
-----END PUBLIC KEY-----
Once set, fill in the parameters:
option: client_id> _my_key_here_
option: client_secret> ****
Preparing preset: faspex5_example_com_user
```



```
Setting config preset as default for faspex5
Done.
You can test with:
ascli faspex5 user profile show
Saving configuration file.
```

Note: Include the public key **BEGIN** and **END** lines when pasting in the user profile.

For details on the JWT method, see the following section.

9.1 Faspex 5 JWT authentication

This is the general purpose and recommended method to use.

Activation is in two steps:

- The administrator must create an API client in Faspex with JWT support

This operation is generally done only once:

- As Admin, Navigate to the web UI: Admin → Configurations → API Clients → Create
- Give a name, like **ascli**
- Activate JWT
- There is an option to set a global public key allowing the owner of the private key to impersonate any user. Unless you want to do this, leave this field empty.
- Click on **Create** Button
- Take note of Client ID (and Client Secret, but not used in current version)

- The user will authenticate with a private key and set the public key in his Faspex 5 profile.

Note: If you don't have a private key refer to section **Private Key** to generate one.

This operation is done by each user using the CLI.

- As user, click on the user logo, left to the app switcher on top right.
- Select **Account Settings**
- on the bottom in the text field: **Public key in PEM format** paste the public key corresponding to the private key used by the user.

Then use these options:

```
--auth=jwt
--client-id=_client_id_here_
--client-secret=my_secret_here
--username=_username_here_
--private-key=@file:../path/to/key.pem
```

Note: The **private_key** option must contain the PEM value (not file path) of the private key which can be read from a file using the modifier: **@file:**, e.g. **@file:/path/to/key.pem**.

As usual, typically a user will create preset to avoid having to type these options each time.

Example:

```
ascli config preset update myf5 --auth=jwt --client-id=_client_id_here_
↪ --client-secret=my_secret_here --username=_username_here_
↪ --private-key=@file:../path/to/key.pem

ascli config preset set default faspex5 myf5

ascli faspex5 user profile show
```

9.2 Faspex 5 web authentication

The administrator must create an API client in Faspex for an external web app support:

- As Admin, Navigate to the web UI: Admin → Configurations → API Clients → Create

- Do not Activate JWT
- Set Redirect URI to `https://127.0.0.1:8888`
- Click on **Create** Button
- Take note of the Client Id (and Client Secret, but not used in current version)

The user will use the following options:

```
--auth=web
--client-id=_client_id_here_
--client-secret=my_secret_here
--redirect-uri=https://127.0.0.1:8888
```

9.3 Faspex 5 bootstrap authentication

For **boot** method: (will be removed in future)

- As user: Open a Web Browser
- Start developer mode
- Login to Faspex 5
- Find the first API call with **Authorization** header, and copy the value of the token (series of base64 values with dots)

Use this token as password and use `--auth=boot`.

```
ascli config preset update f5boot --url=https://localhost/aspera/faspex --auth=boot
↪ --password=_token_here_
```

9.4 Faspex5 sample commands

I *Note: Add `ascli faspex5` in front of the commands:*

```
admin accounts list
admin alternate_addresses list
admin clean_deleted
admin contacts list
admin distribution_lists create @json:'{"name":"test4","contacts":[{"name":"john@example.com"}]}'
admin distribution_lists delete %name:test4
admin distribution_lists list --query=@json:'{"type":"global"}'
admin event app --query=@json:'{"max":20}'
admin event web
admin jobs list --query=@json:'{"job_type":"email","status":"failed"}' --fields=id,error_desc
admin metadata_profiles list
admin node browse %name:Local
admin node list
admin node shared_folders %name:Local list
admin node shared_folders %name:Local show %name:Main
admin node shared_folders %name:Local user %name:Main list
admin node show %name:Local
admin oauth_clients list --query=@json:'[["client_types[]","public"]]'
admin registrations list
admin saml_configs list
admin shared_inboxes invite %name:my_shared_box_name johnny@example.com
admin shared_inboxes list
admin shared_inboxes list --query=@json:'{"all":true}'
admin shared_inboxes members %name:my_shared_box_name create %name:john@example.com
admin shared_inboxes members %name:my_shared_box_name delete %name:john@example.com
admin shared_inboxes members %name:my_shared_box_name delete %name:johnny@example.com
admin shared_inboxes members %name:my_shared_box_name list
admin smtp show
admin smtp test my_email_external
admin workgroups list
bearer_token
gateway --pid-file=pid_f5_fxgw https://localhost:12346/aspera/faspex &
health
```

```

invitation list
invitations create @json: '{"email_address": "aspera.user1+u@gmail.com"}'
packages browse f5_pack_id --query=@json: '{"recursive": true}'
packages delete f5_pack_id
packages list --box=my_shared_box_name
packages list --box=my_workgroup --group-type=workgroups
packages list --query=@json: '{"mailbox": "inbox", "status": "completed"}'
packages receive --box=my_shared_box_name package_box_id1 --to-folder=.
packages receive --box=my_workgroup --group-type=workgroups workgroup_package_id1 --to-folder=.
packages receive ALL --once-only=yes --to-folder=.
packages receive INIT --once-only=yes
packages receive f5_pack_id --to-folder=.
  ↪ --ts=@json: '{"content_protection_password": "my_secret_here"}'
packages send --shared-folder=%name:my_shared_folder_name @json: '{"title": "test
  ↪ title", "recipients": ["my_email_internal"]}' my_shared_folder_file --fields=id --display=data
  ↪ --output=f5_pack_id
packages send --url=my_public_link_send_f5_user @json: '{"title": "test title"}' test_file.bin
packages send --url=my_public_link_send_shared_box @json: '{"title": "test title"}' test_file.bin
packages send @json: '{"title": "test
  ↪ title", "recipients": ["my_shared_box_name"], "metadata": {"Options": "Opt1", "TextInput": "example
  ↪ text"}}' test_file.bin
packages send @json: '{"title": "test title", "recipients": ["my_workgroup"]}' test_file.bin
packages send @json: '{"title": "test title", "recipients": [{"name": "my_username"}]my_meta}'
  ↪ test_file.bin --ts=@json: '{"content_protection_password": "my_secret_here"}'
packages show --box=my_shared_box_name package_box_id1
packages show --box=my_workgroup --group-type=workgroups workgroup_package_id1
packages show f5_pack_id
packages status f5_pack_id
postprocessing --pid-file=pid_f5_postproc
  ↪ @json: '{"url": "http://localhost:8088/asclihook", "processing": {"script_folder": ""}}' &
shared browse %name:my_src
shared list
shared_folders browse %name:my_shared_folder_name
shared_folders list
user profile modify @json: '{"preference": {"connect_disabled": false}}'
user profile show

```

Most commands are directly REST API calls. Parameters to commands are carried through option `query`, as extended value, for `list`, or through Command Parameter for creation. One can conveniently use the JSON format with prefix `@json:`.

Note: The API is listed in [Faspex 5 API Reference](#) under [IBM Aspera Faspex API](#).

9.5 Faspex 5: Inbox selection

By default, package operations (send, receive, list) are done on the user's inbox.

To select another inbox, use option `box` with one of the following values:

- `inbox`
- `inbox_history`
- `inbox_all`
- `inbox_all_history`
- `outbox`
- `outbox_history`
- `pending`
- `pending_history`
- `all`
- `ALL` (admin only, all inboxes of all users)
- name of a shared inbox or workgroup

Note: In case the name of the `box` is specific, use option `group_type` with either `shared_inboxes` or `workgroups` to be more specific.

9.6 Faspex 5: Send a package

A package can be sent with the command:

```
ascli faspex5 packages send [extended value: Hash with package info ] [files...]
```

The `Hash` creation Command Parameter provided to command corresponds to the Faspex 5 API: `POST /packages` (refer to the API reference for a full list of parameters, or look at request in browser).

Required fields are `title` and `recipients`.

Example (assuming a default preset is created for the connection information):

```
ascli faspex5 packages send @json:'{"title":"some title","recipients":["user@example.com"]}'  
↪ mybygfile1
```

Longer example for the payload of `@json:`:

```
{"title":"some title","recipients":[{"recipient_type":"user","name":"user@example.com"}]}
```

`recipient_type` is one of (Refer to API):

- `user`
- `workgroup`
- `external_user`
- `distribution_list`
- `shared_inbox`

`ascli` adds some convenience: The API expects the field `recipients` to be an `Array` of `Hash`, each with field `name` and optionally `recipient_type`. `ascli` also accepts an `Array` of `String`, with simply a recipient name. Then, `ascli` will look up existing contacts among all possible types, use it if a single match is found, and set the `name` and `recipient_type` accordingly. Else an exception is sent.

Note: The lookup is case-insensitive and on partial matches.

```
{"title":"some title","recipients":["user@example.com"]}
```

If the lookup needs to be only on certain types, you can specify the field: `recipient_types` with either a single value or an `Array` of values (from the list above). e.g.:

```
{"title":"test  
↪ title","recipient_types":"user","recipients":["user1@example.com","user2@example.com"]}
```

9.7 Faspex 5: Send a package with metadata

It's the same as sending a package, but with an extra field `metadata` in the package info.

```
{"title":"test title","recipients":["my shared inbox"],"metadata":{"Confidential":"Yes","Drop  
↪ menu":"Option 1"}}}
```

Basically, add the field `metadata`, with one key per metadata and the value is directly the metadata value. (Refer to API documentation for more details).

9.8 Faspex 5: List packages

Option `box` can be used to list packages from a specific box (see [Inbox Selection](#) above).

Option `query` can be used to filter the list of packages, based on native API parameters, directly sent to [Faspex 5 API GET /packages](#).

Parameter	Type	Description
<code>offset</code>	Native	Managed by <code>ascli</code> : Offset of first package. Default: 0
<code>limit</code>	Native	Managed by <code>ascli</code> : # of packages per API call. Default: 100

Parameter	Type	Description
<code>q</code>	Native	General search string (case-insensitive, matches if value is contained in several fields)
...	Native	Other native parameters are supported (Refer to API documentation)
<code>max</code>	Special	Maximum number of items to retrieve (stop pages when the maximum is passed)
<code>pmax</code>	Special	Maximum number of pages to request (stop pages when the maximum is passed)

A Command Parameter in last position, of type `Proc`, can be used to filter the list of packages. This advantage of this method is that the expression can be any test, even complex, as it is Ruby code. But the disadvantage is that the filtering is done in `ascli` and not in Faspex 5, so it is less efficient.

Examples:

- List only available packages: (filtering is done in Faspex)

```
ascli faspex5 packages list --query=@json: '{"status": "completed"}'
```

- Similar, using filtering in `ascli`:

```
ascli faspex5 packages list @ruby: '->(p){p["state"].eq?("released")}'
```

9.9 Faspex 5: Content of a received Package

| *Note:* Listing content also applies to shares folder, nodes, and received packages (using `--box=outbox`).

To list the content of a package, use command `faspex5 packages browse /`.

Option `query` is available.

To list recursively add option `--query=@json: '{"recursive": true}'`.

| *Note:* Option `recursive` makes recursive API calls, so it can take a long time on large packages.

To limit the number of items retrieved, use option `--query=@json: {"max": 10}`.

9.10 Faspex 5: Receive a package

To receive one, or several packages at once, use command `faspex5 packages receive`. Provide either a single package ID, or an extended value `Array` of package IDs, e.g. `@list: 1,2,3` as argument.

The same options as for `faspex5 packages list` can be used to select the box and filter the packages to download. I.e. options `box` and `query`, as well as last Command Parameter `Proc` (filter).

Option `--once-only=yes` can be used, for "cargo-like" behavior. Special package ID `INIT` initializes the persistency of already received packages when option `--once-only=yes` is used.

Special package ID `ALL` selects all packages (of the selected box). In this case, typically, only `completed` packages should be downloaded, so use option `--query=@json: '{"status": "completed"}'`.

If a package is password protected, then the content protection password is asked interactively. To keep the content encrypted, use option: `--ts=@json: '{"content_protection": null}'`, or provide the password instead of `null`.

| *Tip:* If you use option `query` and/or positional `filter`, you can use the `list` command for a dry run.

9.11 Faspex 5: List all shared inboxes and work groups

If you are a regular user, to list work groups you belong to:

```
ascli faspex5 admin workgroup list
```

If you are admin or manager, add option: `--query=@json: '{"all":true}'`, this will list items you manage, even if you do not belong to them. Example:

```
ascli faspex5 admin shared list --query=@json: '{"all":true}' --fields=id,name
```

Shared inbox members can also be listed, added, removed, and external users can be invited to a shared inbox.

```
ascli faspex5 admin shared_inboxes invite '%name:the shared inbox' john@example.com
```

It is equivalent to:

```
ascli faspex5 admin shared_inboxes invite '%name:the shared inbox'
↪ @json: '{"email_address": "john@example.com"}'
```

Other payload parameters are possible for `invite` in this last `Hash Command Parameter`:

```
{"description": "blah", "prevent_http_upload": true, "custom_link_expiration_policy": false,
↪ "invitation_expires_after_upload": false, "set_invitation_link_expiration": false,
↪ "invitation_expiration_days": 3}
```

9.12 Faspex 5: Create Metadata profile

```
ascli faspex5 admin metadata_profiles create @json: '{"name": "the
↪ profile", "default": false, "title": {"max_length": 200, "illegal_chars": []}, "note": {"max_length":
↪ 400, "illegal_chars": [], "enabled": false}, "fields": [{"ordering": 0, "name": "field1", "type":
↪ "text_area", "require": true, "illegal_chars": [], "max_length": 100}, {"ordering": 1, "name": "fff2",
↪ "type": "option_list", "require": false, "choices": ["opt1", "opt2"]}']'
```

9.13 Faspex 5: Create a Shared inbox with specific metadata profile

```
ascli faspex5 admin shared create @json: '{"name": "the shared inbox", "metadata_profile_id": 1}'
```

9.14 Faspex 5: List content in Shared folder and send package from remote source

```
ascli faspex5 shared_folders list --fields=id,name
```

```
+---+-----+
| id | name      |
+---+-----+
| 3  | partages  |
+---+-----+
```

```
ascli faspex5 shared_folders br %name:partages /folder
```

```
ascli faspex5 packages send @json: '{"title": "hello", "recipients": [{"name": "_recipient_here_"}]}'
↪ --shared-folder=%name:partages /folder/file
```

Note: The shared folder can be identified by its numerical `id` or by name using percent selector: `%<field>:<value>`. e.g. `--shared-folder=3`

9.15 Faspex 5: Receive all packages (cargo)

To receive all packages, only once, through persistency of already received packages:

```
ascli faspex5 packages receive ALL --once-only=yes --query=@json: '{"status": "completed"}'
```

To initialize, and skip all current package so that next time `ALL` is used, only newer packages are downloaded:

```
ascli faspex5 packages receive INIT --once-only=yes
```

9.16 Faspex 5: Invitations

There are two types of invitations of package submission: public or private.

Public invitations are for external users, provide just the email address.

```
ascli faspex5 invitations create @json: '{"email_address": "john@example.com"}' --fields=access_url
```

Private invitations are for internal users, provide the user or shared inbox identifier through field `recipient_name`.

9.17 Faspex 5: Cleanup packages

| *Note: Operation requires admin level.*

The default automated cleanup period can be displayed with:

```
ascli faspex5 admin configuration show --fields=days_before_deleting_package_records
```

This parameter can be modified with:

```
ascli faspex5 admin configuration modify @json: '{"days_before_deleting_package_records": 30}'
```

To start package purge, i.e. permanently remove packages marked for deletion older than `days_before_deleting_package_records`, use command:

```
ascli faspex5 admin clean_deleted
```

| *Note: The expiration period taken by default is the one from `admin configuration show`. To use a different period than the default, specify it on command line with: `@json: '{"days_before_deleting_package_records": 15}'`*

To delete all packages, one can use the following command:

```
ascli faspex5 packages list --box=ALL --format=yaml --fields=id | ascli faspex5 packages delete  
↪ @yaml:@stdin:
```

| *Note: Above command will mark all packages for deletion, and will be permanently removed after the configured period (`clean_deleted` command). It is possible to add a filter to the list command to only delete packages matching some criteria, e.g. using `--select=@ruby: '->(p){...}'` on `packages list`.*

9.18 Faspex 5: Admin: Unlock user

To unlock a user, you can deactivate and then re-activate the user:

```
ascli faspex5 admin accounts modify %name:some.user@example.com  
↪ @json: '{"account_activated": false}'
```

```
ascli faspex5 admin accounts modify %name:some.user@example.com  
↪ @json: '{"account_activated": true}'
```

| *Note: Here we use the convenient percent selector, but the numerical ID can be used as well.*

To send a password reset link to a user, use command `reset_password` on the `account`.

9.19 Faspex 5: Faspex 4-style post-processing

The command `ascli faspex5 postprocessing` emulates Faspex 4 post-processing script execution in Faspex 5. It implements Faspex 5 web hooks and calls a script with the same environment variables as set by Faspex 4. Environment variables are set to the values provided by the web hook which are the same as Faspex 4 post-processing.

It allows to quickly migrate workflows to Faspex 5 while preserving scripts. Nevertheless, on long term, a native approach shall be considered, such as using Aspera Orchestrator or other workflow engine.

It is invoked like this:

```
ascli faspex5 postprocessing @json: '{"url": "http://localhost:8080/processing"}'
```

The following parameters are supported in the extended value `Hash` :

Parameter	Type	Default	Description
<code>url</code>	<code>String</code>	<code>http://localhost:8080</code>	Base URL. On which requests are listened, a path can be provided.
<code>certificate</code>	<code>Hash</code>	<code>nil</code>	Certificate information (if URL is HTTPS)
<code>certificate.key</code>	<code>String</code>	<code>nil</code>	Path to private key file
<code>certificate.cert</code>	<code>String</code>	<code>nil</code>	Path to certificate
<code>certificate.chain</code>	<code>String</code>	<code>nil</code>	Path to certificate chain
<code>processing</code>	<code>Hash</code>	<code>nil</code>	Behavior of post-processing
<code>processing.script_folder</code>	<code>String</code>	<code>.</code>	Prefix added to script path
<code>processing.fail_on_error</code>	<code>Bool</code>	<code>false</code>	Fail if true and process exits with non-zero code
<code>processing.timeout_second</code>	<code>Integer</code>	<code>60</code>	Time out before script is killed

Parameter `url` (base URL) defines:

- If `http` or `https` is used
- The local port number (default 443 for HTTPS, 80 for HTTP)
- The `base path`, i.e. the path under which requests are received, if a reverse proxy is used this can be used to route.

When a request is received the following happens:

- `ascli` gets the path of the URL called
- It removes the `base path` of base URL.
- It prepends it with the value of `script_folder`
- It executes the script
- Upon success, a success code is returned

For example:

The base URL is defined as: `http://localhost:8080/processing`. The parameter `script_folder` is set to `/opt/scripts`

In Faspex 5, the URL of the webhook endpoint shall be reachable from within Faspex containers. For example, if `ascli` is running in the base host, the URL hostname shall not be `localhost`, as this refers to the local address inside Faspex container. Instead, one can specify the IP address of the host or `host.containers.internal`.

Webhook endpoint URI: `http://host.containers.internal:8080/processing/script1.sh`

Then the post-processing script executed will be `/opt/scripts/script1.sh`.

9.20 Faspex 5: Faspex 4 Gateway

I *Note: This is not a feature for production. It's provided for testing only.*

For legacy Faspex client applications that use the `send` API (only) of Faspex v4, the command `gateway` provides the capability to present an API compatible with Faspex 4, and it will call the Faspex 5 API.

It takes a single argument which is the URL at which the gateway will be located (locally):

```
ascli faspex5 gateway https://localhost:12345/aspera/faspex
```

There are many limitations:

- It's only to emulate the Faspex 4 `send` API (send package).
- No support for remote sources, only for an actual file transfer by the client.
- The client must use the transfer spec returned by the API (not `faspe: URL`).
- Tags returned in transfer spec must be used in transfer.
- Only a single authentication is possible (per gateway) on Faspex5.
- No authentication of F4 side (ignored).

Behavior: The API client calls the Faspex 4 API on the gateway, then the gateway transforms this into a Faspex5 API call, which returns a transfer spec, which is returned to the calling client. The calling client uses this to start a transfer to HSTS which is actually managed by Faspex 5.

9.21 Faspex 5: Get Bearer token to use API

If a command is missing, then it is still possible to execute command by calling directly the API on the command line using `curl`:

```
curl -H "Authorization: $(ascli ascli bearer)"  
↪ https://faspex5.example.com/aspera/faspex/api/v5/api_endpoint_here
```

Chapter 10

Plugin: **faspex** : IBM Aspera Faspex v4

*Note: Faspex v4 is end of support since Sept. 30th, 2024. So this plugin for Faspex v4 is deprecated. If you still need to use Faspex4, then use **ascli** version 4.19.0 or earlier.*

Note: For full details on Faspex API, refer to: [Reference on Developer Site](#)

This plugin uses APIs versions 3 Faspex v4. The **v4** command requires the use of API v4, refer to the Faspex Admin manual on how to activate.

10.1 Listing Packages

Command: **faspex package list**

10.1.1 Option **box**

By default, it looks in box **inbox** , but the following boxes are also supported: **archive** and **sent** , selected with option **box** .

10.1.2 Option **recipient**

A user can receive a package because the recipient is:

- The user himself (default)
- The user is member of a dropbox/workgroup: filter using option **recipient** set with value ***<name of dropbox/workgroup>**

10.1.3 Option **query**

As inboxes may be large, it is possible to use the following query parameters:

Parameter	Evaluation	Description
count	API	Number of items in one API call result (default=0, equivalent to 10)
page	API	ID of page in call (default=0)
startIndex	API	Index of item to start (default=0)
max	ascli	Maximum number of items
pmax	ascli	Maximum number of pages

(SQL query is **LIMIT <startIndex>, <count>**)

The API is listed in [Faspex 4 API Reference](#) under [Services \(API v.3\)](#).

If no parameter **max** or **pmax** is provided, then all packages will be listed in the inbox, which result in paged API calls (using parameter: **count** and **page**). By default, **count** is **0** (**10**), it can be increased to issue less HTTP calls.

10.1.4 Example: List packages in dropbox

```
ascli faspex package list --box=inbox --recipient='*my_dropbox'
↪ --query=@json: '{"max":20,"pmax":2,"count":20}'
```

List a maximum of 20 items grouped by pages of 20, with maximum 2 pages in received box (inbox) when received in dropbox `*my_dropbox`.

10.2 Receiving a Package

The command is `package recv`, possible methods are:

- Provide a package ID with option `id`
- Provide a public link with option `link`
- Provide a `faspe:` URI with option `link`

```
ascli faspex package recv 12345
ascli faspex package recv --link=faspe://...
```

If the package is in a specific `dropbox/workgroup`, add option `recipient` for both the `list` and `recv` commands.

```
ascli faspex package list --recipient='*dropbox_name'
ascli faspex package recv 125 --recipient='*dropbox_name'
```

If `id` is set to `ALL`, then all packages are downloaded, and if option `once_only` is used, then a persistency file is created to keep track of already downloaded packages.

10.3 Sending a Package

The command is `faspex package send`. Package information (title, note, metadata, options) is provided in option `delivery_info`. The content of `delivery_info` is directly the contents of the `send` v3 [API of Faspex 4](#).

Example:

```
ascli faspex package send --delivery-info=@json: '{"title":"my
↪ title","recipients":["someuser@example.com"]}' /tmp/file1 /home/bar/file2
```

If the recipient is a dropbox or workgroup: provide the name of the dropbox or workgroup preceded with `*` in the `recipients` field of the `delivery_info` option: `"recipients":["*MyDropboxName"]`

Additional optional parameters in mandatory option `delivery_info`:

- Package Note: : `"note":"note this and that"`
- Package Metadata: `"metadata":{"Meta1":"Val1","Meta2":"Val2"}`

It is possible to send from a remote source using option `remote_source`, providing either the numerical ID, or the name of the remote source using percent selector: `%name:<name>`.

Remote source can be browsed if option `storage` is provided. `storage` is a `Hash` extended value. The key is the storage name, as listed in `source list` command. The value is a `Hash` with the following keys:

- `node` is a `Hash` with keys: `url`, `username`, `password`
- `path` is the sub-path inside the node, as configured in Faspex

10.4 Email notification on transfer

Like for any transfer, a notification can be sent by email using options: `notify_to` and `notify_template`.

Example:

```
ascli faspex package send --delivery-info=@json: '{"title":"test pkg
↪ 1","recipients":["aspera.user1@gmail.com"]}' ~/Documents/Samples/200KB.1
↪ --notify-to=aspera.user1@gmail.com --notify-template=@ruby: '%Q{From: <%=from_name%>
↪ <<%=from_email%>>\nTo: <<%=to%>>\nSubject: Package sent:
↪ <%=ts["tags"]["aspera"]["faspex"]["metadata"]["_pkg_name"]%> files received\n\nTo user:
↪ <%=ts["tags"]["aspera"]["faspex"]["recipients"].first["email"]%>}'
```

In this example the notification template is directly provided on command line. Package information placed in the message are directly taken from the tags in transfer spec. The template can be placed in a file using modifier: `@file:`

10.5 Operations on dropbox

Example:

```
ascli faspex v4 dropbox create @json:'{"dropbox":{"e_wg_name":"test1","e_wg_desc":"test1"}}'
ascli faspex v4 dropbox list
ascli faspex v4 dropbox delete 36
```

10.6 Remote sources

Faspex lacks an API to list the contents of a remote source (available in web UI). To work around this, the Node API is used, for this it is required to set option: `storage` that links a storage name to a node configuration and sub path.

Example:

```
my_faspex_conf:
  url: https://10.25.0.3/aspera/faspex
  username: admin
  password: MyUserPassword
  storage:
    my_storage:
      node: "@preset:my_faspex_node"
      path: /mydir
my_faspex_node:
  url: https://10.25.0.3:9092
  username: node_faspex
  password: MyNodePassword
```

In this example, a Faspex storage named `my_storage` exists in Faspex, and is located under the docroot in `/mydir` (this must be the same as configured in Faspex). The node configuration name is `my_faspex_node` here.

Note: The v4 API provides an API for nodes and shares.

10.7 Automated package download (cargo)

It is possible to tell `ascli` to download newly received packages, much like the official cargo client, or drive. Refer to the [same section](#) in the Aspera on Cloud plugin:

```
ascli faspex packages recv ALL --once-only=yes --lock-port=12345
```

10.8 Faspex sample commands

Note: Add `ascli faspex` in front of the commands:

```
address_book
dropbox list --recipient="*my_dbx"
health
login_methods
me
package list --box=sent --query=@json:'{"max":1}' --fields=package_id --display=data --format=csv
  ↳ --output=f4_prs2
package list --query=@json:'{"max":1}' --fields=package_id --display=data --format=csv
  ↳ --output=f4_prs1
package list --query=@json:'{"max":5}'
package list --recipient="*my_dbx" --format=csv --fields=package_id --query=@json:'{"max":1}'
  ↳ --output=f4_db_id1
package list --recipient="*my_wkg" --format=csv --fields=package_id --query=@json:'{"max":1}'
  ↳ --output=f4_db_id2
package receive --to-folder=. --link=https://app.example.com/recv_from_user_path
```

```

package receive ALL --once-only=yes --to-folder=. --query=@json: '{"max":10}'
package receive f4_db_id1 --recipient="*my_dbx" --to-folder=.
package receive f4_db_id2 --recipient="*my_wkg" --to-folder=.
package receive f4_pri1 --to-folder=.
package receive f4_prs2 --to-folder=. --box=sent
package send --delivery-info=@json: '{"title":"$(notdir test)
↳ PACKAGE_TITLE_BASE","recipients":["*my_dbx"]}' test_file.bin
package send --delivery-info=@json: '{"title":"$(notdir test)
↳ PACKAGE_TITLE_BASE","recipients":["*my_wkg"]}' test_file.bin
package send --delivery-info=@json: '{"title":"$(notdir test)
↳ PACKAGE_TITLE_BASE","recipients":["my_email_internal","my_username"]}' test_file.bin
package send --delivery-info=@json: '{"title":"$(notdir test)
↳ PACKAGE_TITLE_BASE","recipients":["my_email_internal"]}' --remote-source=%name:my_src
↳ sample_source.txt
package send --link=https://app.example.com/send_to_dropbox_path
↳ --delivery-info=@json: '{"title":"$(notdir test) PACKAGE_TITLE_BASE"}' test_file.bin
package send --link=https://app.example.com/send_to_user_path
↳ --delivery-info=@json: '{"title":"$(notdir test) PACKAGE_TITLE_BASE"}' test_file.bin
source info %name:my_src --storage=@preset:faspex4_storage
source list
source node %name:my_src br / --storage=@preset:faspex4_storage
v4 dmembership list
v4 dropbox list
v4 metadata_profile list
v4 user list
v4 wmembership list
v4 workgroup list

```

Chapter 11

Plugin: **shares** : IBM Aspera Shares v1

Aspera Shares supports the Node API for the file transfer part.

Supported commands are listed in Share's API documentation:

<https://developer.ibm.com/apis/catalog/aspera--aspera-shares-api/Introduction>

Example:

```
ascli shares admin share create
↪ @json: '{"node_id":1,"name":"test1","directory":"test1","create_directory":true}'

share_id=$(ascli shares admin share list --select=@json: '{"name":"test1"}' --fields=id)

user_id=$(ascli shares admin user list --select=@json: '{"username":"entity1"}' --fields=id)

ascli shares admin share user_permissions $share_id create
↪ @json: '{"user_id":'$user_id',"browse_permission":true, "download_permission":true,
↪ "mkdir_permission":true,"delete_permission":true,"rename_permission":true,
↪ "content_availability_permission":true,"manage_permission":true}'
```

To figure out an entity's payload, for example for creation, refer to the API documentation above.

11.1 Shares sample commands

I *Note: Add `ascli shares` in front of the commands:*

```
admin group all list
admin node list
admin share list --fields=DEF,-status,status_message
admin share user_permissions 3 list
admin user all app_authorizations 1 modify @json: '{"app_login":true}'
admin user all app_authorizations 1 show
admin user all list
admin user all share_permissions 1 list
admin user all share_permissions 1 show 3
admin user ldap add the_name
admin user local list
admin user saml import @json: '{"id":"the_id","name_id":"the_name"}'
files browse /
files delete my_share1/new_folder
files delete my_share1/test_file.bin
files download --to-folder=. my_share1/test_file.bin
files download --to-folder=. my_share1/test_file.bin my_share1/test_file.bin --transfer=httpgw
↪ --transfer-info=@json: '{"url":"https://tst.example.com/path@"}'
files mkdir my_share1/new_folder
files upload --to-folder=https://shares.share1 'faux:///testfile?1m' --transfer=httpgw
↪ --transfer-info=@json: '{"url":"my_example.com/path@","synchronous":true,"api_version":"v1",
↪ "upload_chunk_size":100000}'
```

```
files upload --to-folder=https://shares.share1 sendfolder --transfer=httpgw
↳ --transfer-info=@json: '{"url": "my_example.com/path@", "synchronous": true, "api_version": "v1", }'
↳ "upload_chunk_size": 100000}'
files upload --to-folder=my_share1 test_file.bin
files upload --to-folder=my_share1 test_file.bin --transfer=httpgw
↳ --transfer-info=@json: '{"url": "https://tst.example.com/path@"}'
health
```

Chapter 12

Plugin: `console` : IBM Aspera Console

12.1 Console sample commands

I *Note: Add `ascli console` in front of the commands:*

```
health
transfer current list
transfer smart list
transfer smart sub my_smart_id
↪ @json: '{"source":{"paths":["my_smart_file"]},"source_type":"user_selected"}'
```


Chapter 13

Plugin: `orchestrator` :IBM Aspera Orchestrator

13.1 Orchestrator sample commands

I *Note: Add `ascli orchestrator` in front of the commands:*

```
health
info
plugins
processes
workflow details my_workflow_id
workflow export my_workflow_id
workflow inputs my_workflow_id
workflow list
workflow start my_workflow_id @json:'{"Param":"world !"}'
workflow start my_workflow_id @json:'{"Param":"world !"}'
  ↪ --result=ResultStep:Complete_status_message
workflow status ALL
workflow status my_workflow_id
```

Chapter 14

Plugin: **cos** : IBM Cloud Object Storage

The IBM Cloud Object Storage provides the possibility to execute transfers using FASP. It uses the same transfer service as Aspera on Cloud, called Aspera Transfer Service (ATS). Available ATS regions: <https://status.aspera.io>

There are two possibilities to provide credentials. If you already have the endpoint, API key and Resource Instance ID (CRN), use the first method. If you don't have credentials but have access to the IBM Cloud console, then use the second method.

14.1 Using endpoint, API key and Resource Instance ID (CRN)

If you have those parameters already, then following options shall be provided:

- **bucket** bucket name
- **endpoint** storage endpoint URL, e.g. `https://s3.hkg02.cloud-object-storage.appdomain.cloud`
- **apikey** API Key
- **crn** resource instance ID

For example, let us create a default configuration:

```
ascli config preset update mycos --bucket=mybucket
↪ --endpoint=https://s3.us-east.cloud-object-storage.appdomain.cloud --apikey=abcdefgh
↪ --crn=crn:v1:bluemix:public:iam-identity::a/xxxxxxx
ascli config preset set default cos mycos
```

Then, jump to the **transfer example**.

14.2 Using service credential file

If you are the COS administrator and don't have yet the credential: Service credentials are directly created using the IBM cloud Console (web UI). Navigate to:

- → Navigation Menu
- → [Resource List](#)
- → [Storage](#)
- → Select your storage instance
- → Service Credentials
- → New credentials (Leave default role: Writer, no special options)
- → Copy to clipboard

Then save the copied value to a file, e.g. : `$HOME/cos_service_creds.json`

or using the IBM Cloud CLI:

```
ibmcloud resource service-keys
ibmcloud resource service-key _service_key_name_here_ --output JSON|jq
↪ '.[0].credentials'>$HOME/service_creds.json
```

(if you don't have `jq` installed, extract the structure as follows)

It consists in the following structure:

```
{
  "apikey": "my_api_key_here",
  "cos_hmac_keys": {
    "access_key_id": "my_access_key_here",
    "secret_access_key": "my_secret_here"
  },
  "endpoints": "https://control.cloud-object-storage.cloud.ibm.com/v2/endpoints",
  "iam_apikey_description": "my_description_here",
  "iam_apikey_name": "my_key_name_here",
  "iam_role_crn": "crn:v1:bluemix:public:iam::::serviceRole:Writer",
  "iam_serviceid_crn": "crn:v1:bluemix:public:iam-identity::a/xxxxxxx.....",
  "resource_instance_id": "crn:v1:bluemix:public:cloud-object-storage:global:a/xxxxxxx....."
}
```

The field `resource_instance_id` is for option `crn`

The field `apikey` is for option `apikey`

Note: endpoints for regions can be found by querying the `endpoints` URL from file or from the IBM Cloud Console.

The required options for this method are:

- `bucket` bucket name
- `region` bucket region, e.g. `eu-de`
- `service_credentials` see below

For example, let us create a default configuration:

```
ascli config preset update mycos --bucket=laurent
↪ --service-credentials=@val:@json:@file:~/service_creds.json --region=us-south
ascli config preset set default cos mycos
```

14.3 Operations, transfers

Let's assume you created a default configuration from one of the two previous steps (else specify the access options on command lines).

A subset of `node` plugin operations are supported, basically Node API:

```
ascli cos node info
ascli cos node upload 'faux:///sample1G?1g'
```

Note: A dummy file `sample1G` of size 2 GB is generated using the `faux` PVCL scheme (see previous section and `man ascp`), but you can, of course, send a real file by specifying a real file path instead.

14.4 Cos sample commands

Note: Add `ascli cos` in front of the commands:

```
node download test_file.bin --to-folder=.
node info --bucket=my_bucket --endpoint=my_endpoint --apikey=my_api_key
↪ --crn=my_resource_instance_id
node info --bucket=my_bucket --region=my_region --service-credentials=@json:@file:my_cos_svc_cred
node info --log-level=trace2
node upload test_file.bin
```

Chapter 15

Plugin: `httpgw` : HTTP Gateway

15.1 Httpgw sample commands

| *Note:* Add `ascli httpgw` in front of the commands:

```
health  
info
```

Chapter 16

Plugin: **faspio** : Faspio Gateway

16.1 Faspio sample commands

| *Note: Add `ascli faspio` in front of the commands:*

```
bridges create @json: '{"name": "test1", "local": {"protocol": "tcp", "tls_enabled": false, "port": ↵  
↵ "3000", "bind_address": "127.0.0.1"}, "forward": {"protocol": "fasp", "tls_enabled": false, "port": ↵  
↵ "3994", "bind_address": "127.0.0.1", "host": ["10.0.0.1"]}}'  
bridges delete --bulk=yes @json:@stdin:  
bridges list  
health
```

Chapter 17

Plugin: `a1ee` : Aspera License Entitlement Engine

Retrieve information on subscription.

17.1 Alee sample commands

I *Note: Add `ascli alee` in front of the commands:*

```
entitlement  
health -N
```

Chapter 18

Plugin: `preview` : Preview generator for AoC

The `preview` generates thumbnails (office, images, video) and video previews on storage for use primarily in the Aspera on Cloud application. It uses the Node API of Aspera HSTS and requires use of Access Keys and its `storage root`. Several options can be used to tune several aspects:

- Methods for detection of new files needing generation
- Methods for generation of video preview
- Parameters for video handling

See also <https://github.com/IBM/aspera-on-cloud-file-previews>

18.1 Aspera Server configuration

Specify the preview's folder as shown in:

https://ibmaspera.com/help/admin/organization/installing_the_preview_maker

By default, the `preview` plugin expects previews to be generated in a folder named `previews` located in the storage root. On the transfer server execute:

```
PATH=/opt/aspera/bin:$PATH
asconfigurator -x "server;preview_dir,previews"
asnodeadmin --reload
```

Note: The configuration `preview_dir` is relative to the storage root, no need leading or trailing `/`. In general just set the value to `previews`

If another folder is configured on the HSTS, then specify it to `ascli` using the option `previews_folder`.

The HSTS Node API limits any preview file to a parameter: `max_request_file_create_size_kb` (1 KB is 1024 Bytes). This size is internally capped to `1<<24` Bytes (16777216), i.e. 16384 KB, i.e. 16 MB.

To change this parameter in `aspera.conf`, use `asconfigurator`. To display the value, use `asuserdata`:

```
asuserdata -a | grep max_request_file_create_size_kb
max_request_file_create_size_kb: "1024"
asconfigurator -x "server; max_request_file_create_size_kb,16384"
```

If you use a value different from `16777216`, then specify it using option `max_size`.

Note: The HSTS parameter (`max_request_file_create_size_kb`) is in kilo Bytes while the generator parameter is in Bytes (factor of 1024).

18.2 External tools: Linux

`ascli` requires the following external tools available in the `PATH`:

- ImageMagick v7+: `magick composite`
- OptiPNG: `optipng`
- FFmpeg: `ffmpeg ffprobe`
- LibreOffice: `unoconv`

Here shown on Red Hat/Rocky Linux.

Other OSes should work as well, but are not tested.

To check if all tools are found properly, execute:

```
ascli preview check
```

18.2.1 Image: ImageMagick and `optipng`

```
dnf install -y ImageMagick optipng
```

You may also install `ghostscript` which adds fonts to ImageMagick. Available fonts, used to generate PNG for text, can be listed with `magick identify -list font`. Prefer ImageMagick version ≥ 7 .

More info on ImageMagick at <https://imagemagick.org/>

18.2.2 Video: FFmpeg

The easiest method is to download and install the latest released version of `ffmpeg` with static libraries from <https://johnvansickle.com/ffmpeg/>

```
curl -s https://johnvansickle.com/ffmpeg/releases/ffmpeg-release-amd64-static.tar.xz | (mkdir -p
↪ /opt && cd /opt && rm -f ffmpeg /usr/bin/{ffmpeg,ffprobe} && rm -fr ffmpeg-*-amd64-static &&
↪ tar xJvf - && ln -s ffmpeg-* ffmpeg && ln -s /opt/ffmpeg/{ffmpeg,ffprobe} /usr/bin)
```

18.2.3 Office: `unoconv` and LibreOffice

If you don't want to have preview for office documents or if it is too complex you can skip office document preview generation by using option: `--skip-types=office`

The generation of preview is based on the use of LibreOffice's `unoconv`.

- RHEL 8/Rocky Linux 8+

```
dnf install unoconv
```

- Amazon Linux

```
amazon-linux-extras enable libreoffice
yum clean metadata
yum install libreoffice-core libreoffice-calc libreoffice-opensymbol-fonts libreoffice-ure
↪ libreoffice-writer libreoffice-pyuno libreoffice-impress
wget https://raw.githubusercontent.com/unoconv/unoconv/master/unoconv
mv unoconv /usr/bin
chmod a+x /usr/bin/unoconv
```

18.3 Configuration

The preview generator should be executed as a non-user. When using object storage, any user can be used, but when using local storage it is usually better to use the user `xfer`, as uploaded files are under this identity: this ensures proper access rights. (we will assume this)

Like any `ascli` commands, options can be passed on command line or using a configuration **Option Preset**. The configuration file must be created with the same user used to run so that it is properly used on runtime.

The `xfer` user has a special protected shell: `aspshell`, so in order to update the configuration, and when changing identity, specify an alternate shell. E.g.:


```
su -s /bin/bash - xfer

ascli config preset update mypreviewconf --url=https://localhost:9092 --username=my_access_key
↪ --password=my_secret --skip-types=office --lock-port=12346

ascli config preset set default preview mypreviewconf
```

Here we assume that Office file generation is disabled, else remove this option. `lock_port` prevents concurrent execution of generation when using a scheduler.

One can check if the access key is well configured using:

```
ascli -Ppreviewconf node browse /
```

This shall list the contents of the storage root of the access key.

18.4 Options for generated files

When generating preview files, some options are provided by default. Some values for the options can be modified on command line. For video preview, the whole set of options can be overridden with option `reencode_ffmpeg`: it is a `Hash` with two keys: `in` and `out`, each is an `Array` of strings with the native options to `ffmpeg`.

18.5 Execution

`ascli` intentionally supports only a one shot mode (no infinite loop) in order to avoid having a hanging process or using too many resources (calling REST API too quickly during the scan or event method). It needs to be run on a regular basis to create or update preview files. For that use your best reliable scheduler, see [Scheduler](#).

Typically, for Access key access, the system/transfer is `xfer`. So, in order to be consistent, and generate the appropriate access rights, the generation process should be run as user `xfer`.

Let's do a one shot test, using the configuration previously created:

```
su -s /bin/bash - xfer

ascli preview scan --overwrite=always
```

When the preview generator is first executed it will create a file: `.aspera_access_key` in the preview's folder which contains the access key used. On subsequent run it reads this file and check that previews are generated for the same access key, else it fails. This is to prevent clash of different access keys using the same root.

18.6 Configuration for Execution in scheduler

Details are provided in section [Scheduler](#).

Shorter commands can be specified if a configuration preset was created as shown previously.

For example the timeout value can be differentiated depending on the option: event versus scan:

```
case "$*" in
  *trev*) tmout=10m ;;
  *) tmout=30m ;;
esac
```

18.7 Candidate detection for creation or update (or deletion)

`ascli` generates preview files using those commands:

- `trevnts` : only recently uploaded files will be tested (transfer events)
- `events` : only recently uploaded files will be tested (file events: not working)
- `scan` : recursively scan all files under the access key's storage root
- `test` : test using a local file

Once candidate are selected, once candidates are selected, a preview is always generated if it does not exist already, else if a preview already exist, it will be generated using one of three values for the `overwrite` option:

- `always` : preview is always generated, even if it already exists and is newer than original
- `never` : preview is generated only if it does not exist already
- `mtime` : preview is generated only if the original file is newer than the existing

Deletion of preview for deleted source files: not implemented yet (TODO).

If the `scan` or `events` detection method is used, then the option : `skip_folders` can be used to skip some folders. It expects a list of path relative to the storage root (docroot) starting with slash, use the `@json:` notation, example:

```
ascli preview scan --skip-folders=@json:'["/not_here"]'
```

The option `folder_reset_cache` forces the node service to refresh folder contents using various methods.

When scanning the option `query` has the same behavior as for the `node access_keys do self find` command.

Refer to that section for details.

18.8 Preview File types

Two types of preview can be generated:

- `png` : thumbnail
- `mp4` : video preview (only for video)

Use option `skip_format` to skip generation of a format.

18.9 Supported input Files types

The preview generator supports rendering of those file categories:

- `image`
- `pdf`
- `plaintext`
- `office`
- `video`

To avoid generation for some categories, specify a list using option `skip_types` .

Each category has a specific rendering method to produce the PNG thumbnail.

The mp4 video preview file is only for category `video`

File type is primarily based on file extension detected by the Node API and translated into a mime type returned by the Node API.

18.10 mimemagic

By default, the Mime type used for conversion is the one returned by the Node API, based on file name extension.

It is also possible to detect the mime type using option `mimemagic` . To use it, set option `mimemagic` to `yes` : `--mimemagic=yes` .

This requires to manually install the `mimemagic` gem: `gem install mimemagic` .

In this case the `preview` command will first analyze the file content using `mimemagic` , and if no match, will try by extension.

If the `mimemagic` gem complains about missing mime info file:

- Any OS:
 - Examine the error message
 - Download the file: freedesktop.org.xml.in

- move and rename this file to one of the locations expected by `mimemagic` as specified in the error message
- Windows:
 - Download the file: `freedesktop.org.xml.in`
 - Place this file in the root of Ruby (or elsewhere): `C:\RubyVV-x64\freedesktop.org.xml.in`
 - Set a global variable using `SystemPropertiesAdvanced.exe` or using `cmd` (replace `VV` with version) to the exact path of this file:

```
SETX FREEDESKTOP_MIME_TYPES_PATH C:\RubyVV-x64\freedesktop.org.xml.in
```

- Close the `cmd` and restart a new one if needed to get refreshed env vars
- Linux RHEL 8+:

```
dnf install shared-mime-info
```

- macOS:

```
brew install shared-mime-info
```

18.11 Generation: Read source files and write preview

Standard open source tools are used to create thumbnails and video previews. Those tools require that original files are accessible in the local file system and also write generated files on the local file system. `ascli` provides 2 ways to read and write files with the option: `file_access`

If the preview generator is run on a system that has direct access to the file system, then the value `local` can be used. In this case, no transfer happen, source files are directly read from the storage, and preview files are directly written to the storage.

If the preview generator does not have access to files on the file system (it is remote, no mount, or is an object storage), then the original file is first downloaded, then the result is uploaded, use method `remote`.

18.12 Preview sample commands

I *Note: Add `ascli preview` in front of the commands:*

```
check --skip-types=office
events --once-only=yes --skip-types=office --log-level=info
scan --scan-id=1 --skip-types=office --log-level=info --file-access=remote
  ↳ --ts=@json: '{"target_rate_kbps":1000000}'
scan --skip-types=office --log-level=info
show --base=test my_docx
show --base=test my_mpg --video-png-conv=animated
show --base=test my_mpg --video-png-conv=fixed
show --base=test my_mpg mp4 --video-conversion=clips
show --base=test my_mpg mp4 --video-conversion=reencode
show --base=test my_pdf
test --base=test my_dcm
test --base=test my_mxf mp4 --video-conversion=blend --query=@json: '{"text":true,"double":true}'
test --mimemagic=yes --base=test my_dcm
test --mimemagic=yes --base=test my_jpg_unk
trevents --once-only=yes --skip-types=office --log-level=info
```

Chapter 19

IBM Aspera Sync

An interface for the `async` utility is provided in the following plugins:

- `server sync`
- `node sync`
- `aoc files sync` (uses node)
- `shares files sync` (uses node)

One advantage over the `async` command line is the possibility to use a configuration file, using standard options of `ascli`. Moreover, `ascli` supports sync with application requiring token-based authorization.

Some `sync` parameters are filled by the related plugin using transfer spec parameters (e.g. including token).

Note: All `sync` commands require an `async` enabled license and availability of the `async` executable (and `asynadmin`). The Transfer SDK 1.3 includes this.

`sync` supports 0 or 3 arguments:

- direction
- local folder
- remote folder

Additional options can be provided with option `sync_info`, for which two syntax are possible, as follows.

19.1 `async` API and `conf` format

It is the same payload as specified on the option `--conf` of `async` or in Node API `/asyns`. This is the preferred syntax and allows a single session definition.

Note: No progress, nor error messages is provided on terminal.

Documentation on Async Node API can be found on [IBM Developer Portal](#).

If 3 arguments are provided they are mapped to:

- `direction`
- `local.path`
- `remote.path`

19.2 `async` options mapping

`ascli` defines a JSON equivalent to regular `async` options. It is based on a JSON representation of `async` command line options. It allows definition of multiple sync sessions in a single command, although usually only one sync session is defined.

This is the mode selection if there are either keys `sessions` or `instance` in option `sync_info`.

I *Note: Progress and error messages are provided on terminal like regular command line invocation of `async` .*

If 3 arguments are provided, they are applied to the first (and only) session and mapped to:

- `direction`
- `local_dir`
- `remote_dir`

Chapter 20

Hot folder

20.1 Requirements

`ascli` maybe used as a simple hot folder engine. A hot folder being defined as a tool that:

- Locally (or remotely) detects new files in a top folder
- Send detected files to a remote (respectively, local) repository
- Only sends new files, do not re-send already sent files
- Optionally: sends only files that are not still growing
- Optionally: after transfer of files, deletes or moves to an archive

In addition: the detection should be made continuously or on specific time/date.

20.2 Setup procedure

The general idea is to rely on :

- Existing `ascp` features for detection and transfer
- Take advantage of `ascli` configuration capabilities and server side knowledge
- The OS scheduler for reliability and continuous operation

20.2.1 `ascp` features

Interesting `ascp` features are found in its arguments: (see `ascp` manual):

- `ascp` already takes care of sending only new files: option `-k 1,2,3` (`resume_policy`)
- `ascp` has some options to remove or move files after transfer: `--remove-after-transfer`, `--move-after-transfer`, `--remove-empty-directories` (`remove_after_transfer`, `move_after_transfer`, `remove_empty_directories`)
- `ascp` has an option to send only files not modified since the last X seconds: `--exclude-newer-than`, `--exclude-older-than` (`exclude_newer_than`, `exclude_older_than`)
- `--src-base` (`src_base`) if top level folder name shall not be created on destination

Note: `ascli` takes transfer parameters exclusively as a transfer-spec, with `ts` option.

Note: Usual native `ascp` arguments are available as standard transfer-spec parameters, but not special or advanced options.

Note: Only for the direct transfer agent (not others, like connect or node), native `ascp` arguments can be provided with parameter `ascp_args` of option `transfer_info`.

20.2.2 Server side and configuration

Virtually any transfer on a repository on a regular basis might emulate a hot folder.

Note: File detection is not based on events (`inotify` , etc...), but on a simple folder scan on source side.

*Note: Options may be saved in an **Option Preset** and used with `-P` .*

20.2.3 Scheduling

Once `ascli` command line arguments are defined, run the command using the OS native scheduler, e.g. every minute, or 5 minutes, etc... Refer to section **Scheduler**. (on use of option `lock_port`)

20.3 Example: Upload hot folder

```
ascli server upload source_hot --to-folder=/Upload/target_hot --lock-port=12345
↪ --ts=@json: '{"remove_after_transfer":true,"remove_empty_directories":true,}
↪ "exclude_newer_than":-8,"src_base":"source_hot"}'
```

The local folder (here, relative path: `source_hot`) is sent (upload) to an Aspera server. Source files are deleted after transfer. Growing files will be sent only once they don't grow anymore (based on an 8-second cool-off period). If a transfer takes more than the execution period, then the subsequent execution is skipped (`lock_port`) preventing multiple concurrent runs.

20.4 Example: Unidirectional synchronization (upload) to server

```
ascli server upload source_sync --to-folder=/Upload/target_sync --lock-port=12345
↪ --ts=@json: '{"resume_policy":"sparse_csum","exclude_newer_than":-8,"src_base":"source_sync"}'
```

This can also be used with other folder-based applications: Aspera on Cloud, Shares, Node.

20.5 Example: Unidirectional synchronization (download) from Aspera on Cloud Files

```
ascli aoc files download . --to-folder=. --lock-port=12345 --progress-bar=no --display=data
↪ --ts=@json: '{"resume_policy":"sparse_csum","target_rate_kbps":50000,"exclude_newer_than":-8,}
↪ "delete_before_transfer":true}'
```

Note: Option `delete_before_transfer` will delete files locally, if they are not present on remote side.

Note: Options `progress` and `display` limit output for headless operation (e.g. cron job)

Chapter 21

Health check and Nagios

Most plugin provide a `health` command that will check the health status of the application. Example:

```
ascli console health
```

```
+-----+-----+-----+
| status | component | message |
+-----+-----+-----+
| ok      | console api | accessible |
+-----+-----+-----+
```

Typically, the health check uses the REST API of the application with the following exception: the `server` plugin allows checking health by:

- Issuing a transfer to the server
- Checking web app status with `asctl all:status`
- Checking daemons process status

`ascli` can be called by Nagios to check the health status of an Aspera server. The output can be made compatible to Nagios with option `--format=nagios` :

```
ascli server health transfer --to-folder=/Upload --format=nagios --progress-bar=no
```

```
OK - [transfer:ok]
```


Chapter 22

SMTP for email notifications

`ascli` can send email, for that setup SMTP configuration. This is done with option `smtp`.

The `smtp` option is a `Hash` (extended value) with the following fields:

field	Default	example	Description
<code>server</code>	-	<code>smtp.gmail.com</code>	SMTP server address
<code>tls</code>	<code>true</code>	<code>true</code>	Enable <code>STARTTLS</code> (port 587)
<code>ssl</code>	<code>false</code>	<code>false</code>	Enable <code>TLS</code> (port 465)
<code>port</code>	<code>587</code> or <code>465</code> or <code>25</code>	<code>587</code>	Port for service
<code>domain</code>	<code>domain of server</code>	<code>gmail.com</code>	Email domain of user
<code>username</code>	-	<code>john@example.com</code>	User to authenticate on SMTP server, leave empty for open auth.
<code>password</code>	-	<code>my_password_here</code>	Password for above username
<code>from_email</code>	username if defined	<code>johnny@example.com</code>	Address used if receiver replies
<code>from_name</code>	same as email	<code>John Wayne</code>	Display name of sender

22.1 Example of configuration

```
ascli config preset set smtp_google server smtp.google.com
ascli config preset set smtp_google username john@gmail.com
ascli config preset set smtp_google password my_password_here
```

or

```
ascli config preset init smtp_google @json: '{"server": "smtp.google.com", "username": "john@gmail.com", "password": "my_password_here"}'
```

or

```
ascli config preset update smtp_google --server=smtp.google.com --username=john@gmail.com
↪ --password=my_password_here
```

Set this configuration as global default, for instance:

```
ascli config preset set cli_default smtp @val:@preset:smtp_google
ascli config preset set default config cli_default
```

22.2 Email templates

Sent emails are built using a template that uses the `ERB` syntax.

The template is the full SMTP message, including headers.

The following variables are defined by default:

- `from_name`
- `from_email`
- `to`

Other variables are defined depending on context.

22.3 Test

Check settings with `smtp_settings` command. Send test email with `email_test`.

```
ascli config --smtp=@preset:smtp_google smtp
ascli config --smtp=@preset:smtp_google email --notify-to=sample.dest@example.com
```

22.4 Notifications for transfer status

An e-mail notification can be sent upon transfer success and failure (one email per transfer job, one job being possibly multi session, and possibly after retry).

To activate, use option `notify_to`.

A default e-mail template is used, but it can be overridden with option `notify_template`.

The environment provided contains the following additional variables:

- `subject` : a default subject including transfer status
- `status` : global status of transfer
- `ts` : the [transfer-spec](#) used for the transfer
- `from_email` : email of sender (from `smtp` configuration)
- `from_name` : name of sender (from `smtp` configuration)
- `to` : recipient of the email (from `notify_to`)

Example of template:

```
From: <%=from_name%> <%=from_email%>>
To: <<%=to%>>
Subject: <%=subject%>

Transfer is: <%=status%>
```

Chapter 23

Tool: `asession`

This gem comes with a second executable tool providing a simplified standardized interface to start a FASP session: `asession`.

It aims at simplifying the startup of a FASP session from a programmatic standpoint as formatting a [transfer-spec](#) is:

- Common to Aspera Node API (HTTP POST /ops/transfer)
- Common to Aspera Connect API (browser JavaScript `startTransfer`)
- Easy to generate by using any third party language specific JSON library

Hopefully, IBM integrates this directly in `ascp`, and this tool is made redundant.

This makes it easy to integrate with any language provided that one can spawn a sub process, write to its STDIN, read from STDOUT, generate and parse JSON.

`ascli` expect one single argument: a session specification that contains parameters and a [transfer-spec](#).

If no argument is provided, it assumes a value of: `@json:@stdin:`, i.e. a JSON formatted on stdin.

Note: If JSON is the format, specify `@json:` to tell `ascli` to decode the `Hash` using JSON syntax.

During execution, it generates all low level events, one per line, in JSON format on stdout.

Top level parameters supported by `asession`:

Parameter	Description
<code>spec</code>	the transfer-spec
<code>agent</code>	same parameters as transfer-info for agent <code>direct</code>
<code>loglevel</code>	log level of <code>asession</code>
<code>file_list_folder</code>	the folder used to store (for garbage collection) generated file lists. By default, it is <code>[system tmp folder]/[username]_asession_filelists</code>

23.1 Comparison of interfaces

feature/tool	Transfer SDK	FASPManger	<code>ascp</code>	<code>asession</code>
language integration	Many	C/C++/C#/.netGoPythonjava	Any	Any
required additional components to <code>ascp</code>	Daemon	Library(+headers)	-	RubyAspera gem
startup	Daemon	API	Command line arguments	JSON on stdin(standard APIs:JSON.generateProcess.spawn)

feature/tool	Transfer SDK	FASPManger	ascp	asession
events	Poll	Callback	Possibility to open management port and proprietary text syntax	JSON on stdout
platforms	Any with ascp and transfer daemon	Any with ascp (and SDK if compiled)	Any with ascp	Any with Ruby and ascp

23.2 Simple session

Create a file `session.json` with:

```
{
  "remote_host": "demo.asperasoft.com",
  "remote_user": "asperaweb",
  "ssh_port": 33001,
  "remote_password": "my_password_here",
  "direction": "receive",
  "destination_root": "./test.dir",
  "paths": [
    {
      "source": "/aspera-test-dir-tiny/200KB.1"
    }
  ],
  "resume_level": "none"
}
```

Then start the session:

```
asession < session.json
```

23.3 Asynchronous commands and Persistent session

`asession` also supports asynchronous commands (on the management port). Instead of the traditional text protocol as described in `ascp` manual, the format for commands is: one single line per command, formatted in JSON, where parameters shall be snake style, for example: `LongParameter` → `long_parameter`

This is particularly useful for a persistent session (with the `transfer-spec` parameter: `"keepalive":true`)

```
asession
{"remote_host": "demo.asperasoft.com", "ssh_port": 33001, "remote_user": "asperaweb",
  "remote_password": "my_password_here", "direction": "receive", "destination_root": ".",
  "keepalive": true, "resume_level": "none"}
{"type": "START", "source": "/aspera-test-dir-tiny/200KB.2"}
{"type": "DONE"}
```

(events from FASP are not shown in above example. They would appear after each command)

23.4 Example of language wrapper

NodeJS: <https://www.npmjs.com/package/aspera>

23.5 Help

```
asession -h
USAGE
  asession
  asession -h|--help
  asession [<session spec extended value>]

If no argument is provided, default will be used: @json:@stdin
-h, --help display this message
<session spec extended value> a dictionary (Hash)
```

The value can be either:

the JSON description itself, e.g. @json: '{"xx": "yy", ...}'

@json:@stdin, if the JSON is provided from stdin

@json:@file:<path>, if the JSON is provided from a file

The following keys are recognized in session spec:

spec : mandatory, contains the transfer spec

loglevel : modify log level (to stderr)

agent : modify transfer agent parameters, e.g. ascp_args

file_list_folder : location of temporary files

sdk : location of SDK (ascp)

Asynchronous commands can be provided on STDIN, examples:

```
{ "type": "START", "source": "/aspera-test-dir-tiny/200KB.2" }
```

```
{ "type": "START", "source": "xx", "destination": "yy" }
```

```
{ "type": "DONE" }
```

EXAMPLES

```
asession @json: '{ "spec": { "remote_host": "demo.asperasoft.com", "remote_user": "asperaweb",
```

```
  ↪ "ssh_port": 33001, "remote_password": "demoaspera", "direction": "receive",
```

```
  ↪ "destination_root": "./test.dir", "paths": [ { "source": "/aspera-test-dir-tiny/200KB.1" } ] } } '
```

```
echo '{ "spec": { "remote_host": ... } }' | asession @json:@stdin
```

Chapter 24

Ruby Module: Aspera

Main components:

- `Aspera` generic classes for REST and OAuth
- `Aspera::Agent::Direct`: starting and monitoring transfers. It can be considered as a FASPManger class for Ruby.
- `Aspera::Cli`: `ascli`.

Working examples can be found in repo: <https://github.com/laurent-martin/aspera-api-examples> in Ruby examples.

Chapter 25

History

When I joined Aspera, there was only one CLI: `ascp`, which is the implementation of the FASP protocol, but there was no CLI to access the various existing products (Server, Faspex, Shares). Once, Serban (founder) provided a shell script able to create a Faspex Package using Faspex REST API. Since all products relate to file transfers using FASP (`ascp`), I thought it would be interesting to have a unified CLI for transfers using FASP. Also, because there was already the `ascp` tool, I thought of an extended tool: `eascp.pl` which was accepting all `ascp` options for transfer but was also able to transfer to Faspex and Shares (destination was a kind of URI for the applications).

There were a few pitfalls:

- `ascli` was written in the aging `perl` language while most Aspera web application products (but the Transfer Server) are written in `ruby`.
- `ascli` was only for transfers, but not able to call other products APIs

So, it evolved into `ascli`:

- Portable: works on platforms supporting `ruby` (and `ascp`)
- Easy to install with the `gem` utility
- Supports transfers with multiple **Transfer Agents**, that's why transfer parameters moved from `ascp` command line to `transfer-spec` (more reliable, more standard)
- `ruby` is consistent with other Aspera products

Over the time, a supported command line tool `aspera` was developed in C++, it was later on deprecated. It had the advantage of being relatively easy to installed, as a single executable (well, still using `ascp`), but it was too limited IMHO, and lacked a lot of the features of this CLI.

Enjoy a coffee on me:

```
ascli config coffee --ui=text
ascli config coffee --ui=text --image=@json: '{"text":true}'
ascli config coffee
```

Chapter 26

Common problems

`ascli` detects common problems and provides hints to solve them.

26.1 Error: "Remote host is not who we expected"

Cause: `ascp` $\geq 4.x$ checks fingerprint of the highest server host key, including ECDSA. `ascp` < 4.0 (3.9.6 and earlier) support only to RSA level (and ignore ECDSA presented by server). `aspera.conf` supports a single fingerprint.

Workaround on client side: To ignore the certificate (SSH fingerprint) add option on client side (this option can also be added permanently to the configuration file):

```
--ts=@json: '{"sshfp":null}'
```

Workaround on server side: Either remove the fingerprint from `aspera.conf`, or keep only RSA host keys in `sshd_config`.

References: ES-1944 in release notes of 4.1 and to [HSTS admin manual section "Configuring Transfer Server Authentication With a Host-Key Fingerprint"](#).

26.2 Error "can't find header files for ruby"

Some Ruby gems dependencies require compilation of native parts (C). This also requires Ruby header files. If Ruby was installed as a Linux Packages, then also install Ruby development package: `ruby-dev` or `ruby-devel`, depending on distribution.

26.3 ED25519 key not supported

ED25519 keys are deactivated since `ascli` version 0.9.24 as it requires additional gems that require native compilation and thus caused problems. This type of key will just be ignored.

To re-activate, set env var `ASCLI_ENABLE_ED25519` to `true`.

Without this deactivation, if such key was present in user's `.ssh` folder then the following error was generated:

```
OpenSSH keys only supported if ED25519 is available
```

Which meant that you do not have Ruby support for ED25519 SSH keys. You may either install the suggested Gems, or remove your ed25519 key from your `.ssh` folder to solve the issue.

In addition, host keys of type: `ecdsa-sha2` and `ecdh-sha2` are also deactivated by default. To re-activate, set env var `ASCLI_ENABLE_ECDSA2` to `true`.

End of document