

API	v1/tools/plugin_bindings
Method	POST
Payload	Payload: <pre>{ "team_id": { "policies": [{ "tools": [<str>], # <tool_name>/"*" (all tools) "plugin": <str>, # "OUTPUT_LENGTH_GAUARD"/"RATE_LIMITER"/"SECRETS_DETECTION", "mode": <str>, # "enforce"/"permissive"/"disabled", "priority": <int>, "config": { ... } }] }, # Plugin specific config "team_id": { ... } }</pre> Sample Payload: Output Length Gaurd, Rate Limiter, Secrets Detection <pre>{ "team_id": { "policies": [{ "tool_ids": ["tool_a", "tool_b"], "plugin_id": "OUTPUT_LENGTH_GUARD", "mode": "enforce", "priority": 10, "config": { "min_chars": 0, # should be >=0 "max_chars": 2000, # should be >1 "strategy": "truncate", # "truncate"/"block", "ellipsis": "..." # Suffix appended on truncation } }, { "tool_ids": ["tool_c"], "plugin_id": "RATE_LIMITER", "mode": "enforce", "priority": 20, "config": { "by_user": "60/m", # Rate limit per user per minute(e.g., '60/m') "by_tenant": "600/m", # Rate limit per tenant per minute (e.g., '600/m') "by_tool": "10/m", # Rate limit per tool per minute (e.g., '10/m') } }, { "tool_ids": ["tool_a"], "plugin_id": "SECRETS_DETECTION", </pre>

	<pre>"mode": "disabled", "priority": 100, "config": { "enabled": { "aws_key": true, "github_token": true }, # Map of pattern names to whether they are enabled "redact": true, # Whether to redact detected secrets "redaction_text": "[REDACTED]", # Text to replace secrets with when redacting "block_on_detection": false, # Whether to block when secrets are detected (true/false) "min_findings_to_block": 1, # Minimum number of findings required to block } }] } }</pre> NOTE: 1. Each payload can have multiple teams with multiple policies 2. Each policy should be configured only for one plugin (eg: output length guard/secrets detection) 3. Each policy can be configured for one or more tools
Response	<pre>{ [{ team_id: <team_id> tool_name: <str>, plugin: <str>, config: { } created_on: <datetime> created_by: <str> }, { team_id: <team_id> tool_name: <str>, plugin: <str>, config: { } created_on: <datetime> created_by: <str> },] }</pre>

API	v1/tools/plugin_bindings/<team_id> NOTE: 1. team_id is optional to pass in. 2. If team_id is not passed in, all tool configurations will be returned. 3. If team_id is passed in, all tool configuration within that team will be returned
Method	GET
Payload	NA
Response	{ [{ team_id: <team_id> tool_name: <str>, plugin: <str>, config: { } created_on: <datetime> created_by: <str> }, { team_id: <team_id> tool_name: <str>, plugin: <str>, config: { } created_on: <datetime> created_by: <str> },] }