SPAWAR
Systems Center
PACIFIC

Introduction to
Automated Identification System (AIS)

SPAWAR Systems Center PACIFIC

Disclaimer

- Though SSC Pacific makes every effort to perform quality assurance on its training materials, the material in this presentation may inadvertently include technical inaccuracies or other errors. We would be grateful if users notify us of any errors or inaccuracies they may find.
- The presentation contains references to links and to third-party websites. These are provided for the convenience and interest of users and this implies neither responsibility for, nor approval of, information contained in these websites on the part of the U.S. Government. The USG makes no warranty, either express or implied, as to the accuracy, availability or content of information, text, graphics in the links/third party websites. The USG has not tested any software located at these sites and does not make any representation as to the quality, safety, reliability or suitability of such software, nor does this presentation serve to endorse the use of such sites.

SPAWAR Systems Center PACIFIC

Overview of Talk

- Overview/History of AIS
- Terrestrial AIS vs. Satellite AIS
- Sources of AIS, How to View/Record AIS
- AIS message specifications and decoding AIS messages
- Example – Reading AIS log file, decoding messages, and writing vessel tracks to file

What is Automated Identification System?

- System allowing vessels to automatically report their position and navigational information to all recievers within range, and simultaneously to receive other vessels positions.

- Consists of transceiver, VHF antenna, and GPS antenna

- Operates at VHF maritime channels
  - 87B (161.975 MHz)
  - 88B (162.025MHz)

- Primary Uses-
  - Search and Rescue
  - Collision Avoidance
  - Accident investigation

What is Automated Identification System?

- Typical range of AIS signal is 30 nm in horizontal
  - In vertical, range is much higher…can be received by satellites

- Two main classes of AIS for vessels
  - Class A and Class B



SPAWAR Systems Center PACIFIC

History of AIS

- 1998 - International Maritime Organization's (IMO)International Convention passes Safety of Life at Sea (SOLAS)
  - Requires AIS be fitted aboard international voyaging ships with gross tonnage (GT) of 300 or more tons, and all passenger ships regardless of size NLT 31 December, 2004
  - Estimated 40,000 ships currently carry class A AIS equipment.

- 2007- Class B AIS standard introduced which enabled a new generation of low cost AIS transceivers.
  - Class B equipment now required in many nations (Singapore, China, Turkey and North America) → 100,000 vessels

4 Types of AIS Systems

Class A
Integrated display showing other AIS transmissions
12W transmitting power
Interface to ship navigation systems (GNSS, gyrocompass)
Transmission rate every 3-5 seconds

Class B
2W transmission power
Transmission rate every 30 seconds
Requires at least GPS and VHF antenna

Base Stations
Shore-based AIS transceivers able to control/interrogate individual transponders within range

Aids to Navigation (AtoN)
Shore or buoy based transceiver designed to collect and transmit sea and weather condition messages

Class A AIS Transciever Details

- A vessel Class A AIS systems consist of 3 main components;
  - AIS Transciever – transmits binary formated messages at regular intervals.
  - VHF antenna – recieves and transmits AIS messages to be decoded by the AIS transciever
  - GPS antenna – used to provided GPS position of vessel in AIS messages
  - In addition, the AIS transciever will often be hooked into ship-board gyro

Class A AIS Transponder Details

- The vessel's Maritime Mobile Service Identity (MMSI) – a unique nine digit identification number.
- Navigation status – "at anchor", "under way using engine(s)", "not under command", etc.
- Rate of turn – right or left, from 0 to 720 degrees per minute
- Speed over ground – 0.1-knot (0.19 km/h) resolution from 0 to 102 knots (189 km/h)
- Positional accuracy:
- Longitude – to 0.0001 minutes
- Latitude – to 0.0001 minutes
- Course over ground – relative to true north to 0.1°
- True heading – 0 to 359 degrees (for example from a gyro compass)
- Time stamp – UTC time accurate to the nearest second when these data were generated

SPAWAR Systems Center PACIFIC

Class A AIS Transponder Details

- In addition, the following data are broadcast every 6 minutes:
- IMO ship identification number – a seven digit number that remains unchanged upon transfer of the ship's registration to another country
- Radio call sign – international radio call sign, up to seven characters, assigned to the vessel by its country of registry
- Name – 20 characters to represent the name of the vessel
- Type of ship/cargo
- Dimensions of ship – to nearest meter
- Location of positioning system's (e.g., GPS) antenna on board the vessel - in meters aft of bow and meters port of starboard
- Type of positioning system – such as GPS, DGPS or LORAN-C.
- Draught of ship – 0.1 meter to 25.5 meters
- Destination – max. 20 characters
- ETA (estimated time of arrival) at destination – UTC month/date hour:minute

Class B AIS Transponder Details

- Transmits at lower 2.5W
    - Range is consequently lower than for class A AIS.

- Transmits with lower frequency (30seconds – 5 minutes)
- Does not require integrated display (may act only as transponder)
- Much cheaper, easier to mount/install, good solution for smaller vessels.
- Receives both class A and class B AIS messages (aware of surrounding ship traffic)

Web-based Sources for AIS

http://www.shippingexplorer.net/ - Live Vessel Tracking

http://www.marinetraffic.com/ais/default.aspx?language=_EN – Marine Traffic

http://www.digital-seas.com/ - Worldwide real time vessel tracking

http://Vesseltracker.com - Worldwide AIS tracking Website

http://www.vtexplorer.com/ - AIS vessel tracking based on standalone VT Explorer application

http://www.ios-hellas.gr/ais - Vessels from around the world update every sec!!

http://www.mariweb.gr/ecs - On-Line tracking of vessels from around the world, weather reports and live cameras!

http://www.shipspotting.com/modules/myalbum/ais.php - Shipspotting.com - Vessels in Northern Europe

http://www.vesseltrax.com/ - Vessels in the Gulf of Mexico and Texas Ports

http://www.shipais.com/ - Vessels in the Irish Sea, around Great Britain, United Kingdom, and Ireland

http://www.lrfairplay.com/ - Loyds register of ship information

http://www.atlanticsource.es/sat/ - Vessels around the world

http://www.shipplotter.dk/dk-kort.html - Vessels around Denmark

http://www.northernbaltic.se/ais/ - Live AIS @ Landsort Vessels in Northern Baltic Sea around Landsort!

http://www.trackaship.com - Ship and vessel tracking world wide. Includes maps optimized for mobile devices. Free iPhone App for live tracking.

Web-based Sources for AIS

- The U.S. Department of Transportation's VOLPE Center takes AIS feeds from around the world and pushes them onto the MSSIS network.

- AIS on this network is viewable using several web tools (VRMTC-A and the Non-Classified Enclave (NCE)). Data can also be viewed/logged using the TV-32 application.

Satellite AIS

- Vertical range of VHF transmission is much greater than horizontal range
  - ~74km horizontal vs. ~400km vertical
- Collected by LEO, Polar orbiting satellites
- First satellites launched in June 2008
- Two main data providers
  - ORBCOMM
  - exactEarth



SatAIS provided by ExactEarth over Gulf of Guinea

SPAWAR Systems Center PACIFIC

Satellite AIS

- Example of SatAIS over the Gulf of Guinea
- Shows Contacts
- Shows ship tracks
- Combination



SatAIS provided by ExactEarth over Gulf of Guinea

AIS Binary Message Formats

- AIS is decoded as binary message in format called NMEA 0183
- Several standards exists (NMEA 3.0 and NMEA 4.0)

- Two main types of AIS messages
  1. Dynamic messages (types 1, 2, and 3 for class A, types 18 and 19 for class B).
  2. Static messages (type 5 for class A, types 18,19, 24 for class B)
  3. Message types 1,3, 5, 18, & 24 are the most common

- 26 total possible messages

- ***Details of AIS messages (AIVDO and AIVDM messages) found at*** http://gpsd.berlios.de/AIVDM.html

SPAWAR
Systems Center
PACIFIC

AIS Message Formats



AIS Message Formats

```
!AIVDM,1,1,,A,1Ch6tkg000NBs10USArVOGsd08oR,0*77,1255391874,1255392000
```



AIS Message Formats

```
!AIVDM,1,1,,A,1Ch6tkg000NBs10USArVOGsd08oR,0*77,1255391874,1255392000
```



AIS Message Formats



AIS Message Formats



AIS Message Formats



AIS Message Formats



AIS Message Formats



AIS Message Formats



AIS Message Formats – Data Payload

```
!AIVDM,1,1,,A,1Ch6tkg000NBs10USArVOGsd08oR,0*77,1255391874,1255392000
```

Data payload, described later

- Data payload uses 6-bit ASCII
- After recovering each 6-bit sequence they are combined together to provide the full binary of the data payload
- Each binary sequence then corresponds to information about the track
- Details of AIS messages (AIVDO and AIVDM messages) found at http://gpsd.berlios.de/AIVDM.html

Table 2. Sixbit ASCII

000000	0	"@"	010000	16	"P"	100000	32	" "	110000	48	"0"
000001	1	"A"	010001	17	"Q"	100001	33	"!"	110001	49	"1"
000010	2	"B"	010010	18	"R"	100010	34	"""	110010	50	"2"
000011	3	"C"	010011	19	"S"	100011	35	"\#"	110011	51	"3"
000100	4	"D"	010100	20	"T"	100100	36	"$"	110100	52	"4"
000101	5	"E"	010101	21	"U"	100101	37	"%"	110101	53	"5"
000110	6	"F"	010110	22	"V"	100110	38	"&"	110110	54	"6"
000111	7	"G"	010111	23	"W"	100111	39	"\'"	110111	55	"7"
001000	8	"H"	011000	24	"X"	101000	40	"("	111000	56	"8"
001001	9	"I"	011001	25	"Y"	101001	41	")"	111001	56	"9"
001010	10	"J"	011010	26	"Z"	101010	42	"*"	111010	58	":"
001011	11	"K"	011011	27	"["	101011	43	"\+"	111011	59	";"
001100	12	"L"	011100	28	"\"	101100	44	","	111100	60	"<"
001101	13	"M"	011101	29	"]"	101101	45	"-"	111101	61	"="
001110	14	"N"	011110	30	"\^"	101110	46	"."	111110	62	">"
001111	15	"O"	011111	31	"_"	101111	47	"/"	111111	63	"?"

AIS Message Formats – Data Payload

```
!AIVDM,1,1,,A,1Ch6tkg000NBs10USArVOGsd08oR,0*77,1255391874,1255392000
```

- This is the field that includes all of the data that typically is desired to be parsed out

  - Latitude and Longitude
  - Time stamp
  - Ship Name
  - Ship dimensions
  - MMSI – Mobile Marine Service Identifier
  - IMO ship identification number
  - Departure and Arrival ports
  - ETA
  - Can include shipping manifests

SPAWAR
Systems Center
PACIFIC

NMEA 3.0 AIS Parser and KML File Writer

AIS Parser and KML Output Writer

- C++ code to parse NMEA 3.0 AIS messages, form vessel tracks, and write to KML output files
- Support for all 26 messages types
- Sorts all AIS messages by MMSI/IMO and then by time to create “tracks”
- Combines static and dynamic message information to create track data

SPAWAR
Systems Center
PACIFIC

AIS Parser and KML Output Writer



SPAWAR
Systems Center
PACIFIC

AIS Parser and KML Output Writer



SPAWAR Systems Center PACIFIC

Overview of Talk

- AIS/IMINT Refresher
- Idea of Fusion
- Code Example
- Conclusions

- Slides located at:

http://midnightsignal.com/chile/day_13

AIS Refresher

- AIS (Automatic Identification System)
  - Automated tracking system used on ships and vessels
  - Mandatory on large ships
  - Broadcasts information about the ship
    - Identification number
    - Ship name
    - Geo-location
    - Velocity
    - Cargo

My name is ChileBoat.
I am travelling 10km/hour
I am located at (33 S, 150 W)

IMINT Overview

- IMINT – Imagery INTelligence
  - Intelligence gather via (satellites or aerial photography)
  - Possible to contain information such as geo-location, heading, size, etc…



AIS / IMINT Fusion

- Fusion of two distinct intelligence sources to create a more complete picture of the environment
- Can be used to confirm IMINT detections of ships
- May find vessels which are large enough to have AIS, but do not have it enabled



AIS / IMINT Fusion

- Example of vessels detected via SAR imagery, not broadcasting AIS

- Series of “bright” objects on the ocean can be interpreted as ships

- Detection algorithm collects geolocation information for the contacts

- This information can be displayed in a wide variety of ways



AIS / IMINT Fusion

- Example of vessels detected via SAR imagery, not broadcasting AIS
- Pink contacts are from SAR detection
- Green contacts are AIS



AIS / IMINT Fusion

- Example of vessels detected via SAR imagery and AIS – 12 hours apart

- Pink contacts are from SAR detection
- Green contacts are AIS
- Even 12 hours later you can still see some correlation!

AIS / IMINT Fusion

- Example of vessels detected via SAR imagery and AIS – 12 hours apart

- Pink contacts are from SAR detection
- Green contacts are AIS
- Even 12 hours later you can still see some correlation!



SPAWAR Systems Center PACIFIC

OpenCV Matching

- OpenCV provides methods to find “keypoints” in an image
- Keypoints are interesting points in an image that are likely to be found in various lighting conditions and scales/rotations of the object
- We can compute “descriptor” vectors from those keypoints
- Descriptors are vectors that describe the keypoints mathematically (e.g. mean, standard deviation, etc of the surrounding keypoint)

SPAWAR Systems Center PACIFIC

OpenCV Matching

- Basic flow of matching
  - Find keypoints of image (using SIFT/SURF/HarrisCorners... etc)
  - Find descriptor vectors from those keypoints (sometimes based on local histograms)
  - Define a metric for distance between descriptors
  - Match descriptors from one set with descriptors from another set in a way that minimizes the distance

SPAWAR Systems Center PACIFIC

Code Example

- OpenCV has classes for matching descriptors
- We can use these classes to develop a simple AIS/IMINT correlator
- We used the BruteForceMatcher for this example. There are a few more with different functionality… check out the documentation for more information
- ..\Day5\codigo\AIS_IMINT_FUSION.zip

SPAWAR
Systems Center
PACIFIC

Code Example - Diagram



SPAWAR
Systems Center
PACIFIC

Questions?