



AIS IMINT Fusion



Disclaimer

- Though SSC Pacific makes every effort to perform quality assurance on its training materials, the material in this presentation may inadvertently include technical inaccuracies or other errors. We would be grateful if users notify us of any errors or inaccuracies they may find.
- The presentation contains references to links and to third-party websites. These are provided for the convenience and interest of users and this implies neither responsibility for, nor approval of, information contained in these websites on the part of the U.S. Government. The USG makes no warranty, either express or implied, as to the accuracy, availability or content of information, text, graphics in the links/third party websites. The USG has not tested any software located at these sites and does not make any representation as to the quality, safety, reliability or suitability of such software, nor does this presentation serve to endorse the use of such sites.



Overview of Talk

- AIS/IMINT Refresher
- Idea of Fusion
- Code Example
- Conclusions
- Slides located at:

http://midnightsignal.com/chile/day_13



AIS REFRESHER

AIS (Automatic Identification System)

- Automated tracking system used on ships and vessels
- Mandatory on large ships
- Broadcasts information about the ship
 - Identification number
 - Ship name
 - Geo-location
 - Velocity
 - Cargo


My name is ChileBoat. I am travelling 10km/hour I am located at (33 S, 150 W)





IMINT REFRESHER


- •IMINT (Imagery Intellegence)
 - •Intelligence gathered via imagery (e.g. Satellite Imagery)
 - Possible to contain information such as:
 - Geo-location
 - Heading
 - Size





AIS IMINT FUSION

- •Fusion of two distinct intelligence sources to create a more complete picture of the environment
- Can be used to confirm IMINT detections of ships
- May find vessels which are large enough to have AIS, but do not have it enabled
 - Law enforcement may want to investigate





OPENCY MATCHING

OpenCV provides methods to

- Find "Keypoints" in an image
 - •Keypoints are interesting points in an image that are likely to be found in various lighting conditions and scales/rotations of the object
- Compute "Descriptor" vectors from those keypoints
 - •Descriptors are vectors that describe the keypoints mathematically. (e.g. mean, standard deviation... etc of the area surrounding the keypoint)



OPENCY MATCHING

Basic flow of matching

- Find keypoints of image (using SIFT/SURF/HarrisCorners... etc)
- •Find descriptor vectors from those keypoints (sometimes based on local histograms)
- Define a metric for distance between descriptors
- Match descriptors from one set with descriptors from another set in a way that minimizes the distance



CODE EXAMPLE

OpenCV has classes for matching descriptors
We can use these classes to develop a simple AIS/IMINT correlator

We used the BruteForceMatcher for this example. There are a few more with different functionality... check out the documentation for more information.

Open AIS_IMINT_FUSION.zip



CODE EXAMPLE - DIAGRAM

