



Components of an OSSIM Filter

Disclaimer

- Though SSC Pacific makes every effort to perform quality assurance on its training materials, the material in this presentation may inadvertently include technical inaccuracies or other errors. We would be grateful if users notify us of any errors or inaccuracies they may find.
- The presentation contains references to links and to third-party websites. These are provided for the convenience and interest of users and this implies neither responsibility for, nor approval of, information contained in these websites on the part of the U.S. Government. The USG makes no warranty, either express or implied, as to the accuracy, availability or content of information, text, graphics in the links/third party websites. The USG has not tested any software located at these sites and does not make any representation as to the quality, safety, reliability or suitability of such software, nor does this presentation serve to endorse the use of such sites.

Overview of Talk

-
- Conclusions

MAIN TYPES OF FILTERS

- Combiners
- Imagesource

COMBINERS

- Used for combining two input sources into one
 - `ossimEquationCombiner`
 - Allows creation of images from arbitrary mathematical operations on image bands

IMAGE SOURCES

- Used to process a single image
 - Edge filter
 - FFT filter
 - Image Sharpen filter

COMMON FEATURES OF ALL FILTERS

- Connectable objects that can be inserted into a chain
 - The have inputs/outputs
 - Save state / load state
 - Process the image tile by tile
 - getTile() function
 - this is called when the chain is executed

CREATING YOUR OWN FILTER

- The easiest way to create your own filter is to find an existing filter that has a similar function and extending it