
CSC209 Notes

Software Tools and Systems Programming

<https://github.com/icprplshelp/>

Last updated January 12, 2023

1 Introduction

This course is about:

- Software tools
 - Using the command line and not clicking on UIs (apparently linux addicts hate them)
- Systems programming
 - No, this course isn't learning to program
 - It's about the pieces of C we haven't seen yet
 - And the systems part of programming in C (the file system, the notion of processes, and communications over the network)

1.1 Unix Principles

- Unix is different fundamentally than an IDE or an application with a UI.
 - An IDE gives you a button for everything.
- Unix has simple tiny tools that can be combined to do interesting tasks.
 - A lot of them are programs that do one things, maybe with a few variations, but all the same thing
 - We have a way to connect these tools together in different combinations to do more interesting tasks
- To do everything together, **they work with plain text files.**
- **None of the UNIX tools (should) require human-interactive input** (e.g. `input()` in python)
 - Why? So we can automate things and put commands into scripts, so they can run without having us involved
 - We want a simple output format, so the output format is the simple format that the next tool can take the input

- I/O streams
 - * In Java, we have `System.out.println()` (standard output) and `System.err.print()`
 - * For every process, we have a `stdin` (most of the time, it's a keyboard).

1.2 Commands

UNIX is short on vowels and you'll rarely see them. Commands are short.

- `cd` for change directory
- `ls` is for list all the commands on the path or the current directory
 - a.k.a. all your files... probably I'm wrong on this
 - `ls -F` lists them with an extra slash, listing all files with a `/` at the end if it is a directory. For example: `file1.txt file2.txt folder/`
 - `-lF` gives us the long listing (and combines the effects of `-F` - more verbose and looks like file explorer but with text)
- `cat <file>` (stands for concatenate) shows me the files content... but
 - The `cat` command is running. It takes the argument `<file>` and uses it as the filename it should open and read for standard input.
 - `cat` takes what comes in standard input and push it to standard output
 - Then the shell displays the standard output in the window for us.
 - Multiple arguments? `cat` stands for concatenate, so it concats all the inputs and sends the output to standard output.
`cat <file> <file> <file>` puts file three times into the standard output.
 - `cat document document > double_document` - you know what this does. That's exactly how you concat stuff into a new file.
- `sort` sorts each line in lexical order and puts it in standard output.
- `wc document` (gives me the word count. It gives me
`LINE_COUNT WORD_COUNT CHARACTERS` (words are tokens?))
- `sed "<regex>"` (stream editor)

- Applies the regex to ALL lines and sends it into the standard output.
- Example: `sed 's/, /XXX/' document`
 - * Search for `,` and replace it with `XXX` (similar to find and replace)
- Let's do this again: `sed 's/\(.*\), \(.*\)/\2 \1/' document...`
good luck figuring that out (basically transforms `LastName, FirstName` to `FirstName LastName`)
- Piping: the pipe symbol – whatever process is on the LEFT, the standard output from THE LEFT becomes the standard input on the RIGHT. For example:
 - `sed 's/\(.*\), \(.*\)/\2 \1/' document | sort`
 - * We don't sort by first name, so maybe sort first?
 - `sort document | sed 's/\(.*\), \(.*\)/\2 \1/'`
 - Now, this command, if `document` were a text file filled with `LastName, FirstNames` on each line, it sorts by last name first THEN does the swap.
- `man <command>` gives us the manual page for the command. For example, `man sort` gives us a help page.
- `cut -d " " -f 1` has the same effect as `line.split(' ')[0]` for every line in the file.
- `unique`... you know this... **NOT**.
 - Filters out **ADJACENT** matching lines.
 - If you really want to get rid of duplicates, SORT FIRST

UNIX is user-friendly; it's just choosy about its friends.

Become a friend of UNIX.

1.2.1 The Grep Command

Grep: search for (a string of characters) using grep.

It's in the dictionary. It means **global regular expression and print**. The idea of gripping is you're searching an RE on a file and you're sending in standard output the lines that match.

For example, find all the lines that match this RE and print it.

And do you want to grep but get the numbers of occurrences? Pipe it into `wc`.

1.2.2 Shell

The interface between me and the OS. When we type in the shell, the `$` is a shell prompt (we can redefine that if we want) and will probably already be there.

```
1 $ wc hello.c
```

- the text `wc hello.c` is a command for the cell
- `wc` is the name of an executable file or program to run
 - `wc` is in the `PATH` variables
- The remaining text `hello.c` is an argument to the program

The shell

- targets the executable
- passes in the arguments

Know the tools!! Memorize their name, but not the options. You can look them up using the `man` page. Experts underestimate how much they use them, so it will boost your speed if you memorize them.

- `head`, `tail`, `cd`, `mkdir`, `ls`, `cp` (copy), `mv` (move/rename), `rm`, `diff`, `comm`, `cut`, `cat`, `wc`, `grep`.

2 File System

File systems are trees... or are they? The `/` is the root directory, and inside the `/` directory, there are a bunch of other directories, and so on.

2.1 File System Hierarchy

- Everything starts in the root directory, name `/`
- A directory is a file that contains directory entries
- A directory entry maps a file name to an `inode`
 - A data structure that contains information about the file (size, owner, access/modified/creation time, perms, and so on).
 - Includes direct pointers to file blocks.

2.1.1 LS Outputs

- The leftmost from the table generated from `ls -lF` is the permissions, except for the first character, which is the type. hence, the table is:
- type, permissions
- owner
- group
- size
- date last modified
- file name, ends with `*` if executable and `/` if directory

2.1.2 Permissions

```
1 -rwxr-xr-x
```

- (ignore the first char, that's for something else. afterwards)
- first 3 chars are for the owner
- next three are for the user group associated with the owner, but not necessarily the owner
- last three is for everyone else

File permissions:

- read, write, executes
- For directories:
 - Read:
 - * Can run `ls` on dir
 - write:
 - * Can create or delete files in dir
 - execute:
 - * Can pass through directory even without the read perms

2.2 chmod

```
1 chmod <mode> <path>
```

Change permissions. Look at the slides for how to run the commands.

Two approaches:

- Using octals (more concise but harder to learn; check the slides). Learn octal to binary, and the other way around.
 - This completely overwrites the permissions and does not preserve anything.
- Or the more readable approach
 - `chmod <u/g/o><+/-><r/w/x> ...`
 - Adds or takes away permissions
 - `chmod go-x ...` takes away `x` perms from both `g` and `o` – these categories of users

Use `*` to target ALL files (except for `-`) (run for all files). Similar but not exactly REs; they are called `globbing`

You need to know both, because you'll have to accommodate people who are addicted with either approach

2.3 Globbing

A little like regular expressions but different

- `*` matches any no. of any character (equivalent to `.*` in RE)
- `?` matches any one character (equiv to `?` in RE)
- `[list of chars]`
- `[1-5]` or `[a-z]` or `[a-xz]`

That's the basic stuff. You should probably memorize that

To be used if you want to mention a file... but not targeting all files. And you can also mention multiple files at once:

```
1 chmod o-r day.txt e1.pdf emptydir
```

2.4 Running a Program

In Python, we would write a program in a plain text file normally named ending in `.py`. We run it using the command `python3 hello.py` (normally) from the command line.

- program being run is `python3` and takes the argument `hello.py`

For a C program: we have a file `hello.c`. We compile it with

```
1 $ gcc -Wall -g -std=gnu99 -o hello hello.c
```

See the other arguments? You MUST use them. Get a macro or something

The arguments:

- `-Wall` (show me all the warnings – if you have warnings, usually something is wrong and also you'll lose marks. It is not a style warning, and it is on something you've done that is likely wrong)
- `-g` (when I build the executable, leave in the information inside the executable so that we can run the debugger. otherwise the file will be kinda obfuscated)

- `-st=gnu99` tells us the version
- `-o` (The next argument is the name you should store the executable. If you do not put that in, the executable defaults and goes out to `a.out`. Apparently, lots of people had trouble with it)
- `hello.c` (The source file you want to target)

Turns it into an executable. We'll be using `gcc` (make sure it works on `teach.cs` but I can use another C compiler if I want when practicing).

Run `./hello` to execute the file. The `./` states the directory: `.` means the current directory I'm in (cwd), and `/` is "IN THE DIRECTORY".

Some users can do this without `./` – it may be due to a configuration in your path. Probably not a good idea, as you don't want a file named `ls` in any of your directories. I wouldn't.