

CSC 211: Computer Programming

Expressions and Selection Statements

Michael Conti

Department of Computer Science and Statistics
University of Rhode Island

Spring 2022



Original design and development by Dr. Marco Alvarez

Administrative Announcements

- A01 due 02/15
- MC02 due 02/13
- Exam#01 - 02/24

2

Expressions

Common arithmetic operators



- Can be used with any numeric type (integers and floating point numbers)
- Result of the **operator** depends on the type of the **operands**
- Be aware of the **integer division** (fractional part discarded)
 - 22/4 is 5

Integer Division

$$\begin{array}{r} 4 \longleftarrow 12/3 \\ 3 \overline{)12} \\ \underline{12} \\ 0 \longleftarrow 12\%3 \end{array}$$

$$\begin{array}{r} 4 \longleftarrow 14/3 \\ 3 \overline{)14} \\ \underline{12} \\ 2 \longleftarrow 14\%3 \end{array}$$

from: Problem Solving with C++, 10th Edition, Walter Savitch

5

“Rules”

- Use parentheses !
 - even when redundant
- Use whitespaces !

$(b*b-4*a*c)/(2*a)$ 🙅

$((b * b) - (4 * a * c)) / (2 * a)$ 👍

6

Boolean expressions

- Expressions that evaluate to either **true** or **false**
- Can use comparison operators

== < > >= <= !=

- Can use logical operators

! && ||

7

Truth Tables

AND

Exp_1	Exp_2	Exp_1 && Exp_2
true	true	true
true	false	false
false	true	false
false	false	false

OR

Exp_1	Exp_2	Exp_1 Exp_2
true	true	true
true	false	true
false	true	true
false	false	false

NOT

Exp	!(Exp)
true	false
false	true

from: Problem Solving with C++, 10th Edition, Walter Savitch

8

Comparison Operators

Math Symbol	English	C++ Notation	C++ Sample	Math Equivalent
=	equal to	==	x + 7 == 2*y	$x + 7 = 2y$
≠	not equal to	!=	ans != 'n'	$\text{ans} \neq 'n'$
<	less than	<	count < m + 3	$\text{count} < m + 3$
≤	less than or equal to	<=	time <= limit	$\text{time} \leq \text{limit}$
>	greater than	>	time > limit	$\text{time} > \text{limit}$
≥	greater than or equal to	>=	age >= 21	$\text{age} \geq 21$

from: Problem Solving with C++, 10th Edition, Walter Savitch

9

Precedence Rules

The unary operators +, -, ++, --, and !.

The binary arithmetic operations *, /, %

The binary arithmetic operations +, -

The Boolean operations <, >, <=, >=

The Boolean operations ==, !=

The Boolean operations &&

The Boolean operations ||

Highest precedence
(done first)



Lowest precedence
(done last)

from: Problem Solving with C++, 10th Edition, Walter Savitch

10

What is the value of this expression?

`(x + 1) > 2 || (x + 1) < -3`

Recommended style

`((x + 1) > 2) || ((x + 1) < -3)`

11

In C++ any non-zero value is **true** and zero is **false**

12

What is the value of this expression?

false
(! 32 > 64)

(0 > 64)

false

13

What is the value of this expression?

true
(! 0 > 64)

(1 > 64)

false

14

What is the value of this expression?

a = 0; b = 1; c = 15; d = 5; e = 20;

(!b && !c) || (d == e) || (!a && ((d + e) % 10 == 0));

15

Selection Statements
if and switch

if statements

- Allow conditional execution of code
- General idea:

```
if (expression)
    true statement
else
    false statement
```

17

The if statement (basic syntax)

```
if (expression) statementA
else if (expressionB) statementB
.
.
.
else statementN
```

18

Example

```
int value;

std::cout << "Enter a number: ";
std::cin >> value;

if (value > 0) {
    std::cout << "positive number" << std::endl;
} else if (value < 0) {
    std::cout << "negative number" << std::endl;
} else {
    std::cout << "zero" << std::endl;
}
```

19

Compound statements

```
if (expression) {
    statementA
    statementB
    statementC
    ...
} else {
    statementL
    statementM
    statementN
    ...
}
```

- ✓ Recommended to **always use braces**, even with single statements
- ✓ Develop a good and consistent programming style

20

Compound statements

```
2 #include <iostream>
3
4 int main( )
5 {
6     double fuelGaugeReading;
7
8     std::cout << "Enter fuel gauge reading: ";
9     std::cin >> fuelGaugeReading;
10
11     std::cout << "First with braces:\n";
12     if (fuelGaugeReading < 0.75)
13     {
14         if (fuelGaugeReading < 0.25)
15             std::cout << "Fuel very low. Caution!\n";
16     }
17     else
18     {
19         std::cout << "Fuel over 3/4. Dont stop now!\n";
20     }
21
22     std::cout << "Now without braces:\n";
23     if (fuelGaugeReading < 0.75)
24     if (fuelGaugeReading < 0.25)
25         std::cout << "Fuel very low. Caution!\n";
26     else
27         std::cout << "Fuel over 3/4. Don't stop now!\n";
28
29     return 0;
30 }
```

21

Compound Statements Used with *if-else*

```
if (my_score > your_score)
{
    cout << "I win!\n";
    wager = wager + 100;
}
else
{
    cout << "I wish these were golf scores.\n";
    wager = 0;
}
```

from: Problem Solving with C++, 10th Edition, Walter Savitch

22

Exercise

- Write a program in C++ (**on paper**) that:
 - reads the number of **hours**
 - calculates payment:
 - if number of hours no greater than 40, **payment** is calculated using the regular hourly rate of \$35
 - if overtime, **payment** is calculated using the regular hourly rate for the first 40 hours and the special rate of \$50 for the remaining hours
 - prints the calculated **payment**

23

An *if-else* Statement within an *if* Statement

```
if (count > 0)
{
    if (score > 5)
    {
        cout << "count > 0 and score > 5\n";
    }
    else
    {
        cout << "count > 0 and score <= 5\n";
    }
}
```

from: Problem Solving with C++, 10th Edition, Walter Savitch

24

switch statements

- Allow conditional execution of code based on the value of an **integer** expression

- Basic syntax:

```
switch (expression) {  
    case valueA:  
        statementA  
    case valueB:  
        statementB  
    .  
    .  
    case valueN:  
        statementN  
    default:  
        statement  
}
```

if expression equals to a value, control executes corresponding statement (can be a compound statement), then continue executing statements until **break** is encountered

25

switch statements

```
3 #include <iostream>  
4 int main() {  
5     int x = 2;  
6     switch (x)  
7     {  
8         case 1:  
9             std::cout << "Choice is 1 \n";  
10            break;  
11        case 2:  
12            std::cout << "Choice is 2 \n";  
13            break;  
14        case 3:  
15            std::cout << "Choice is 3 \n";  
16            break;  
17        default:  
18            std::cout << "Choice other than 1, 2 and 3 \n";  
19            break;  
20    }  
21    return 0;  
22 }
```

```
65:Desktop labmanager$ g++ switch.cpp -o switch  
65:Desktop labmanager$ ./switch  
Choice is 2  
65:Desktop labmanager$
```

26

switch statements

```
4 int main() {  
5     int x = 2;  
6     switch (x)  
7     {  
8         case 1:  
9             std::cout << "Choice is 1 \n";  
10            //break;  
11        case 2:  
12            std::cout << "Choice is 2 \n";  
13            //break;  
14        case 3:  
15            std::cout << "Choice is 3 \n";  
16            //break;  
17        default:  
18            std::cout << "Choice other than 1, 2 and 3 \n";  
19            //break;  
20    }  
21    return 0;  
22 }
```

```
65:Desktop labmanager$ ./switch  
Choice is 2  
Choice is 3  
Choice other than 1, 2 and 3  
65:Desktop labmanager$
```

27

A switch Statement (part 1 of 2)

```
//Program to illustrate the switch statement.  
#include <iostream>  
using namespace std;  
  
int main()  
{  
    char grade;  
  
    cout << "Enter your midterm grade and press Return: ";  
    cin >> grade;  
  
    switch (grade)  
    {  
        case 'A':  
            cout << "Excellent. "  
                << "You need not take the final.\n";  
            break;  
        case 'B':  
            cout << "Very good. ";  
            grade = 'A';  
            cout << "Your midterm grade is now "  
                << grade << endl;  
            break;  
        case 'C':  
            cout << "Passing.\n";  
            break;  
        case 'D':  
            cout << "Not good. "  
                << "Go study.\n";  
            break;  
        case 'F':  
            cout << "Not good. "  
                << "Go study.\n";  
            break;  
        default:  
            cout << "That is not a possible grade.\n";  
    }  
  
    cout << "End of program.\n";  
    return 0;  
}
```

characters (ascii values) can also be used in switch statements

A switch Statement (part 2 of 2)

Sample Dialogue 1

```
Enter your midterm grade and press Return: A  
Excellent. You need not take the final.  
End of program.
```

Sample Dialogue 2

```
Enter your midterm grade and press Return: B  
Very good. Your midterm grade is now A.  
End of program.
```

Sample Dialogue 3

```
Enter your midterm grade and press Return: D  
Not good. Go study.  
End of program.
```

Sample Dialogue 4

```
Enter your midterm grade and press Return: E  
That is not a possible grade.  
End of program.
```

28