

## General Information

Detailed information about the lecture, tutorials and homework assignments can be found on the lecture website<sup>1</sup>. Solutions have to be submitted to Moodle<sup>2</sup>. Make sure your uploaded documents are readable. Blurred images will be rejected. Use Piazza<sup>3</sup> to ask questions and discuss with your fellow students.

## Assignment 1.1 (L) Recap: Implications

Remember that an implication  $A \implies B$  states an *if-then* relation: If  $A$  is satisfied, then  $B$  is satisfied as well. Let  $x, y \in \mathbb{Z}$  and let  $A, B$  be arbitrary formula. Decide, which of the following implications hold:

1. ☒  $x = 1 \implies 0 < x$

2. ☐  $x < 6 \implies x = 3$

3. ☒  $x > 0 \implies x \geq 0$

4. ☒  $x = -2 \implies x < -1 \vee x > 1$

5. ☒  $x = 0 \vee x = 7 \implies 4 \neq x$

6. ☐  $x = 1 \implies x \leq 3 \wedge y > 0$

7. ☒  $x < 8 \wedge y = x \implies y \neq 12$

8. ☐  $x = 1 \vee y = 1 \implies x > 0$

9. ☐  $x \neq 5 \implies false$

10. ☐  $true \implies x \neq y$

11. ☒  $false \implies x = 1$

12. ☐  $x \geq 1 \implies 2x + 3 = 5$

13. ☒  $A \wedge x = y \implies A$

14. ☒  $B \implies A \vee B$

15. ☒  $A \implies (B \implies A)$

16. ☐  $(A \implies B) \implies A$


<sup>1</sup><https://www.in.tum.de/i02/lehre/wintersemester-1819/vorlesungen/functional-programming-and-verification/>

<sup>2</sup><https://www.moodle.tum.de/course/view.php?id=44932>

<sup>3</sup><https://piazza.com/tum.de/fall2018/in0003/home>

## Assignment 1.2 (L) Assertions

Consider the following control flow graph:



1. Which of the following assertions hold at point A?

- |  |  |   |
|--|--|---|
| (a) <input checked="" type="checkbox"/> $i \geq 0$ | (c) <input type="checkbox"/> $i \leq 10 \wedge x \neq 0$ | (e) <input checked="" type="checkbox"/> $i = 0$ |
| (b) <input type="checkbox"/> $x = 0$               | (d) <input checked="" type="checkbox"/> $true$           | (f) <input type="checkbox"/> $x = i$            |

2. Which of the following assertions hold at point B?

- |   |  |  |
|---|--|--|
| (a) <input type="checkbox"/> $x = 0 \wedge i = 0$ | (c) <input type="checkbox"/> $i < x$                       | (e) <input type="checkbox"/> $i \geq 0 \wedge x \geq 0$        |
| (b) <input type="checkbox"/> $x = i$              | (d) <input checked="" type="checkbox"/> $0 \leq i \leq 10$ | (f) <input checked="" type="checkbox"/> $n = 1 \implies x = i$ |

3. Which of the following assertions hold at point C?

- |  |   |   |
|--|---|---|
| (a) <input checked="" type="checkbox"/> $i \geq 0$ | (c) <input checked="" type="checkbox"/> $i > 0$ | (e) <input checked="" type="checkbox"/> $x = 10n$                 |
| (b) <input checked="" type="checkbox"/> $i = 10$   | (d) <input type="checkbox"/> $x \neq n$         | (f) <input checked="" type="checkbox"/> $x = i * n \wedge i = 10$ |

### Assignment 1.3 (L) The Strong and the Weak

Again consider the assertions that hold at point  $C$  of assignment 1.2. Discuss the following questions:

1. When annotating the control flow graph, can you say that one of the given assertions is “better” than the others?
2. Can you arrange the given assertions in a meaningful order?
3. How can you define a *stronger than* relation formally?
4. How do *true* and *false* fit in and what is their meaning as an assertion?
5. What are the strongest assertions that still hold at  $A, B$  and  $C$ ?

### Suggested Solution 1.3

1. When we want to make a statement about the state (the values of variables) at a program point, the “best” assertion is the one that gives the most precise description of the values that are actually possible in the program. Therefore, an assertion  $i = 10$  is “better” than  $i \geq 0$ , because the information it provides is more precise. We thus say that  $i = 10$  is *stronger* than  $i \geq 0$ . Intuitively,  $x = i * n \wedge i = 10$  is the strongest among the given assertions.
2. Following the above argument, we can at least say the following:
  - $x = i * n \wedge i = 10$  stronger than  $i = 10$  stronger than  $i > 0$  stronger than  $i \geq 0$
  - $x = i * n \wedge i = 10$  stronger than  $x = 10n$

However, one cannot say that  $i = 10$  is *stronger* than  $x = 10n$  or vice versa, since the information they provide is not “better” or “worse”, but just different or incomparable.

3. In some sense, an assertion  $A$  is *stronger* than an assertion  $B$ , if  $A$  extends or includes the information of  $B$ . In other words, whenever  $A$  is satisfied,  $B$  is satisfied as well. Hence,

$$A \text{ stronger than } B := A \implies B$$

is a partial order (reflexive, transitive and anti-symmetric). We can now rewrite the above statements:


- $(x = i * n \wedge i = 10 \implies i = 10) \wedge (i = 10 \implies i > 0) \wedge (i > 0 \implies i \geq 0)$
  - $x = i * n \wedge i = 10 \implies x = 10n$
  - Neither  $i = 10 \implies x = 10n$ , nor  $i = 10 \Leftarrow x = 10n$
4. Since  $false \implies A$  and  $A \implies true$  hold for all  $A$ , *false* and *true* are the strongest and weakest assertions, respectively. While *true* is always satisfied, there is no assignment of variable values that can ever satisfy *false*. The only way for a program not to violate an assertion *false* is to never reach the respective program point.

5. For  $A$  and  $C$  the strongest assertions are already given with  $i = 0$  and  $x = i * n \wedge i = 10$ , respectively. However, for point  $B$  we can still find a stronger assertion:  $x = i * n \wedge 0 \leq i \leq 10$

### Assignment 1.4 (L) Strongest Postconditions

Using our understanding of strong and weak assertions, it is now possible to look at statements individually and, given an assertion  $A$  that holds before a statement  $s$ , find the strongest assertion  $B$  that holds after the statement. We call  $B$  the *strongest postcondition* (of  $A$  at statement  $s$ ).

For each of the following statements, find the *strongest postcondition*  $B$ :



### Suggested Solution 1.4

1.  $B \equiv x = 5$
2.  $B \equiv x = 18 \wedge y = 2$
3.  $B \equiv x \geq 5 \wedge y = -2$
4.  $B \equiv x = 3(i - 1) \wedge i \geq 1$
5.  $B \equiv true$

6.  $B \equiv false$
7.  $B_{yes} \equiv n > 3 \wedge x = 12$  and  $B_{no} \equiv (n = 2 \vee n = 3) \wedge x = 12$
8.  $B_{yes} \equiv false$  and  $B_{no} \equiv x = 2i \wedge 0 > i$
9.  $B \equiv (i = 0 \wedge x > 0) \vee (i \neq 0 \wedge y = 1)$   
or  $B \equiv (i = 0 \implies x > 0) \wedge (i \neq 0 \implies y = 1)$

### Assignment 1.5 (H) Proving Ground: Implications

[4 Points]

Prove or refute the following claims. Whenever you rewrite any terms, annotate the rule that was used.

1. It exists an  $A$  such that

- $x < 0 \wedge y = 2 \implies A$  and
- $A \implies x < -2 \wedge y > 0$

are both satisfied.

2. No  $A$  and  $B$  exist such that

- $A \implies B \wedge x > 2$ ,
- $B \implies x > 5$  and
- $x > 2 \implies A$


hold.

3.  $(A \wedge B \implies C) \iff B \vee C \equiv A \wedge \neg C \implies \neg B$
4.  $(x < 0 \implies A) \wedge (\neg A \implies x < -2) \implies (y = 3 \implies A) \equiv true$

# Assignment 1.6 (H) Powerful Assertions

[7.5 Points]


In the following control flow graph, find the strongest assertions  $A - O$  that hold at the correspondingly labeled edge:



# Assignment 1.7 (H) Lost Statements

[4.5 Points]

The following control flow graph's edges are annotated with the strongest assertions that hold at the respective program point. Find the statements and conditions of the program.



## Assignment 1.8 (H) Return of the Penguins

[4 Points]

One day, while wandering around in the furthest corners of the university to find your exercise room, you walk by some laboratory, where a small penguin girl is tinkering on a strange device. After taking note of you watching her, she excitedly starts talking to you.

Hi there! I am Julia. I'm an informatics student! We penguins loooooooooove informatics! But now that I'm in third semester, I miss all my penguin friends from last year \*sad\*. There were so many other penguins, but now they are all gone .... \*sad\*. And that is why I built thiiiiiiis time machine \*excitedly pointing to the device\*. Everything is ready for the first test, but before I can go back to the wonderful penguin times, I need to compute the correct parameters for the flux capacitor. I was planning to write a program for that, but sadly, I only learned how to write a compiler so far \*sad\*.



What did you say? You can help me with the programming and you already know about assertions?! Wow, this is aweeeesome! Then I can give you the formal specification of my program and you can write it for me: The program reads two inputs  $a$  and  $b$ , that must not be modified within the program, once they are read. The program then computes the flux capacitor parameter  $p$  such that

$$(a > b \implies p = -1) \wedge (a \leq b \implies (a \geq 0 \implies p = \frac{b!}{a!} * \sum_{k=a}^b k) \wedge (a < 0 \implies p = \sum_{k=0}^b k))$$

holds at the end of the program. Can you help me?

Help Julia and implement this program in MiniJava. Inputs  $a$  and  $b$  must not be modified within the program once they are read from the user.