Regenerative braking limitations in electric trucks

"When a heavy electric truck is fully charged or running hot, the system automatically shuts off regenerative braking to protect the battery. This forces the vehicle to rely entirely on mechanical brakes, causing extreme overheating, rapid pad wear, and dangerous brake fade on highways and slopes. Current fixes just use heavy resistors to dump this massive amount of power as wasted heat. i want to learn more about this problem and related research towards it and any current fixes or solutions" *Generated by LeapSpace*

Regenerative Braking Limits and Energy-Absorption Remedies in Heavy Electric Trucks: Quick Insights

Key Findings Table

Key finding	What it means for heavy electric trucks	Evidence base	Citations
Regen cutback is primarily driven by battery charge-acceptance limits	Near full charge and unfavorable battery temperatures can force regen torque to zero or sharply reduce it, regardless of available motor braking capability	Heavy-truck and broader heavy-EV control studies; field data in adjacent heavy vehicles	[1] [2] [3] [4] [5] [6] [7] [8] [9]
High SOC is a recurring shutdown threshold	Several studies treat SOC > 0.9 as a condition where charging stops and regenerative braking is disabled or strongly limited	Control-oriented studies	[4] [5] [10]
Loss of regen shifts braking energy into friction brakes	On long descents, this raises brake temperature, wear, cracking risk, and stopping-distance/fade concerns	Heavy-vehicle brake thermal and wear studies	[11] [12] [13] [14]
Smooth brake blending is safer than abrupt cutoff	Research consistently favors coordinated torque handoff to friction brakes rather than sudden regen removal	Blended-braking control literature	[15] [16] [17] [18] [19] [20]

Key finding	What it means for heavy electric trucks	Evidence base	Citations
Resistor dumps are practical but inefficient	Choppers and resistors provide an energy sink when the battery cannot accept charge, but waste energy as heat and can create transition/jolt problems	Electrical braking and resistor studies	[21] [22] [23]
Auxiliary buffers are the strongest emerging remedy	Supercapacitors and hybrid buffer systems repeatedly appear as ways to absorb high-power braking pulses without overloading the main battery	Heavy-duty and related vehicle energy-buffer studies	[24] [25] [26] [27] [28] [29] [30] [31]
Hydraulic storage can be attractive on mass/packaging grounds	Comparative work suggests hydraulic options can be smaller and lighter than some electrical alternatives, though not all are well-suited to long downhill capture	Comparative heavy-vehicle storage studies	[32] [33] [34] [35]
Evidence is real but truck-specific measurements are sparse	There are few published datasets linking SOC, battery temperature, regen cutback, and brake temperatures in production heavy trucks on long descents	Cross-source gap identified in the retrieved set	[7] [11] [13] [14] [36] [37]

Direct Answer

Yes—this is a real engineering and safety problem, and the literature supports the mechanism you described: when a heavy EV battery is near full charge or outside a favorable thermal window, the battery management system can sharply reduce or fully disable regenerative braking to prevent overcharge or battery stress, forcing the vehicle to rely more heavily on friction brakes [1] [2] [3] [4] [5] [8] [9]. On long descents, that substitution can raise brake temperatures, accelerate wear, and increase fade and cracking risk [11] [12] [13] [14].

The current fix set is real but imperfect. Three solution families dominate the retrieved research:

1. **Better brake blending/control**, so loss of regen is gradual and stable rather than abrupt [15] [16] [17] [18] [20].
2. **Dump loads/resistors**, which preserve electrical braking availability when the battery cannot accept charge, but waste energy and create thermal-management burdens [21] [23].

3. **Auxiliary storage buffers**, especially supercapacitors, which are the most promising research direction for absorbing short high-power braking pulses when the main battery is charge-limited [24] [25] [26] [28] [30] [31].

Taken together, the best currently supported path is **not resistor-only dumping**, but a layered strategy: keep SOC headroom before major descents, maintain the battery in a favorable thermal window, use predictive grade-aware brake management, and add a secondary energy buffer so regen does not depend entirely on the traction battery [2] [24] [28] [36] [38] [39].
Confidence level: High — the central mechanism and remedy directions are consistently supported across the retrieved sources, though truck-specific field quantification is limited [36] [37].

Study Scope

- **Time period covered by the retrieved set:** approximately 2010-2025, with emphasis on 2015-2025 control and heavy-vehicle electrification studies [40] [41] [42].
- **Disciplines represented:** battery management, vehicle control, brake systems, thermal management, and energy storage/recovery [13] [32] [43].
- **Methods represented:** simulation-heavy controller studies, controller-in-the-loop work, some bench brake testing, and selected real-world bus/trolleybus datasets [7] [37] [43] [44].
  Confidence level: High — this characterization follows directly from the retrieved evidence summaries [37] [43] [44].

Assumptions & Limitations

- The strongest direct evidence for SOC- and temperature-limited regen exists, but much of the detailed quantitative evidence comes from buses, trolleybuses, rail, or generic EV control studies rather than production heavy electric trucks [7] [23] [37].
- The retrieved set does **not** provide robust truck-specific numbers for exact lost regen power at high SOC/high temperature or matched field measurements of the resulting brake temperature increase on long descents [7] [36] [37].
- OEM/fleet operating guidance for departure SOC targets and mountain-route procedures is sparse in the retrieved evidence [45].
  Confidence level: High — these are explicit evidence gaps in the provided material [36] [45].

Suggested Further Research

- Instrumented downhill truck trials linking **SOC, battery temperature, charge-power limit, grade, vehicle mass, regen cutback, and brake temperature** in one dataset [11] [36].
- Common-duty-cycle comparisons of **resistor dumps vs supercapacitors vs hydraulic storage vs auxiliary loads** under freight-truck downhill use [2] [21] [33].
- OEM-facing studies on **recommended departure SOC windows** and route-aware warnings for long descents [4] [45].

- Validation of **fault-tolerant blend-out strategies** for sudden regen loss on low-μ surfaces and high grades [17] [46] [47].
- Retrofit feasibility studies for **buffer modules or add-on recovery systems** in existing heavy EV fleets [42] [48].

Full Report

Foundational Context

Regenerative braking is only available when the traction motor can operate as a generator **and** the electrical system has somewhere safe to send the recovered power [2]. In battery-electric heavy vehicles, that "somewhere" is usually the traction battery, so the practical ceiling on regen is often the battery's **charge acceptance**, not the motor's braking capability [4] [5] [8]. If the battery is near full, too cold, too hot, or otherwise charge-limited, the BMS may restrict or stop charging to protect the pack, which directly reduces or eliminates regenerative torque [1] [3] [6] [9].

That makes heavy trucks a difficult case. They can encounter very large sustained braking loads on long grades, precisely where regen would be most valuable, yet those same routes may begin after a full charge or may push the battery and braking system into thermal limits [34] [36] [49]. Taken together, the literature frames the problem as a **three-way tradeoff** among battery protection, energy recovery, and friction-brake thermal safety [36] [43] [49] [50].

Confidence level: High — this framing is directly supported across the meta-synthesis and source learnings [36] [43] [50].

1. Why Regen Is Cut Back in Heavy Electric Trucks

1.1 State-of-charge limits and overcharge protection

The most consistent trigger in the retrieved evidence is **high SOC**. Multiple studies in the set treat **SOC above 0.9** as a condition where battery charging stops or regenerative torque is set to zero to avoid overcharge [4] [5]. A broader heavy-duty truck summary likewise reports that SOC above 90% reduced regenerative recovery by up to 50% due to protective protocols [1]. Other control studies explicitly design braking-force allocation around SOC ceilings to improve anti-overcharging behavior [3] [6] [10].

The practical implication is straightforward: a truck leaving a charger at or near full SOC may have reduced downhill energy-absorption capability from the first descent onward [4] [36]. This is not a failure of the motor; it is a normal battery protection response [5] [6].

1.2 Thermal constraints and temperature-sensitive acceptance

Battery temperature is the second major limit. The retrieved literature emphasizes that battery performance is best maintained within a relatively stable temperature window, with one review citing **15-35 °C** as preferred [8] [9]. Cold conditions raise internal resistance and reduce lithium-ion mobility, while hot conditions increase thermal stress, both of which can reduce efficient charge acceptance during braking [1] [8]. Real-world bus and trolleybus data further show that regen efficiency depends materially on ambient temperature, with stronger performance in warmer months and weaker performance in winter [7] [37].

However, the truck-specific literature in the retrieved set does not provide exact heavy-truck thermal derating thresholds for regen suppression [7] [37]. The evidence supports the phenomenon, but not a universal truck cutoff number.

1.3 Why the problem is structural on long descents

A key contradiction emerges across the sources: long descents create large recoverable braking energy, but they also commonly coincide with the conditions that suppress battery acceptance—high departure SOC, rising battery temperature, or explicit battery charging-power limits [4] [17] [34] [36]. This pattern implies that the worst operational case is not rare edge behavior but a structurally predictable one for route segments with sustained negative grade [36] [49].

Confidence level: High — high-SOC protection is directly evidenced; the “structural contradiction” is a clearly labeled cross-source inference based on consistent findings [4] [34] [36].

2. What Happens When Regen Disappears

When battery acceptance collapses, the missing braking torque must be supplied elsewhere. In practice, that means friction brakes, electrical dump hardware, or both [21] [51]. The safety consequence depends heavily on how the torque handoff is managed [15] [17].

Heavy-vehicle brake studies in the retrieved set report that prolonged constant braking on descents can cause **brake fade**, **longer stopping distance**, **severe drum/disc temperatures**, increased wear, and even **thermal cracking** [11] [13] [14]. Additional evidence places wear-related temperature thresholds around **130 °C on-road** and **150 °C in laboratory measurements**, above which wear increases [12]. Bench fade-and-recovery testing further reflects the concern about repeated high-temperature events under heavy braking [44].

This means that if regen is heavily reduced on a loaded descent, the service-brake system may be forced to absorb energy it was not intended to carry continuously at that magnitude [11] [13]. The literature supports the risk, though it does not yet provide a strong truck-specific field dataset quantifying the exact thermal penalty for production battery-electric trucks [11] [36].

Confidence level: High for the existence of the risk; **Medium** for precise heavy-truck quantification because the retrieved set lacks matched field measurements [11] [36].

3. Brake Blending and Control Strategies

3.1 Ramped blend-out versus abrupt cutoff

Across the braking-control literature, smoother **ramp-down** of regenerative braking and coordinated increase in friction braking are favored over abrupt regen cutoff [15] [16] [17]. Reported benefits include improved deceleration behavior, stopping performance, and ride comfort, including on dry and icy surfaces and under load [15] [16]. The meta-level synthesis also identifies abrupt loss of motor braking as a hazardous case even where direct heavy-truck comparative data remain sparse [17] [47] [52].

This is one of the most actionable findings for current systems: even if regen must be limited, **how it disappears** matters greatly for safety [15] [17].

3.2 Main controller families

The retrieved work includes several controller classes for torque allocation:

- **Hierarchical control**: upper layers optimize safety and energy recovery; lower layers enforce actuator and battery charging-power limits [18] [19] [43].
- **Fuzzy/PID methods**: used to handle changing slope, road condition, and braking severity with stable torque allocation and short settling time [20] [53].
- **Slip-ratio-based methods**: prioritize wheel-slip control, using motor braking first up to its limit, then blending in hydraulic braking as needed [54] [55].
- **Observer/allocation architectures**: combine command interpretation, state observers, and wheel pressure control to avoid lock/slip while distributing braking force [56].

Taken together, these studies suggest the field is moving away from “maximize regen whenever possible” toward **constrained optimization under battery, stability, and thermal limits** [18] [43].

3.3 Emergency fallback and stability

For emergency or low-regen conditions, the literature emphasizes that the hydraulic/friction system must carry the remaining braking demand while maintaining stability [51] [57] [58] [59]. Some studies propose more demanding evaluation maneuvers than standard road tests for hybrid/electric braking systems, precisely because blend behavior and safety-system interactions are not fully captured by conventional testing [46].

Confidence level: High — the control-strategy evidence is consistent across multiple studies, though many are simulation-based [18] [20] [46].

4. Resistor Banks, Choppers, and Dynamic Braking Dumps

Resistive dump loads are a real and established fallback when the battery cannot accept charge [21] [22]. In this mode, the vehicle preserves electrical braking by sending generated energy into braking resistors rather than the battery [22]. This can prevent immediate overreliance on friction brakes, but the retrieved research treats it as a compromise rather than an ideal solution [21].

The main drawbacks are:

- **Energy is wasted as heat** rather than stored [21] [22].
- **Thermal management becomes a system problem**, with resistor heating capable of affecting nearby equipment and control performance [23].
- **Handoff quality can suffer**, including excessive end-of-braking torque or a jolt when transitioning to mechanical brakes [21].

This matches your concern closely: the literature supports the view that resistor-only approaches solve the immediate electrical problem but merely relocate it into heat rejection and control smoothness [21] [23].

Confidence level: High — multiple retrieved studies directly support this characterization [21] [23].

5. Alternative Energy-Absorption Remedies

5.1 Supercapacitors and hybrid electrical buffers

The strongest recurring remedy in the retrieved set is **auxiliary buffer storage**, especially supercapacitors/ultracapacitors [24] [25] [26] [27] [28] [29] [30]. These devices are repeatedly proposed because they can absorb short, high-power braking pulses more readily than the main battery, reducing peak battery current and improving transient energy capture [24] [25] [28]. One truck-oriented study reported regenerative braking energy could be absorbed efficiently and reliably, with maximum regenerative efficiency up to **88%** [31].

The provided content does not include full battery-only comparison metrics for wear reduction or exact current reduction in all cases, but the direction of benefit is consistent [31].

5.2 Auxiliary loads as energy sinks

Another concept is using **vehicle auxiliary electrical loads** as temporary energy sinks when the battery cannot accept regen, enabling some battery-independent recuperative braking [2]. Taken together, these findings suggest a useful "sink hierarchy": battery first, then buffer storage or auxiliaries, and only then resistor dumping and friction brakes [2] [21] [24].
Inferred: this layered hierarchy is a synthesis across separate studies rather than a directly validated single architecture.
Confidence level: Low — promising but not directly tested as an integrated heavy-truck system [2] [21] [24].

5.3 Hydraulic and compressed-air alternatives

Comparative work for heavy goods vehicles suggests **hydraulic storage** can be lighter and smaller than the nearest electrical alternative, with one comparison reporting it as about **33% smaller** and **20% lighter** [33] [35]. However, **compressed-air** storage appears less attractive because storage efficiency was reported at only **20.4%** in one heavy-duty model [60]. For long downhill operation specifically, a hydraulic-pneumatic recovery system recovered much less energy on long downward slopes than in full-stop urban braking, implying weaker suitability for sustained downhill capture [34] [41].

The implication is that hydraulic systems may help on packaging grounds, but they are not a universal answer to prolonged grade braking [34].

5.4 Retrofit and add-on architectures

Retrofit-style regenerative braking concepts do appear in the retrieved set, including external subassemblies for non-hybrid vehicles and specialized bus integrations [40] [41] [42] [61]. The clearest OEM-agnostic retrofit concept is the external regenerative-braking subassembly using a DC generator [42]. But most heavy-vehicle examples still require meaningful drivetrain or system integration, so the evidence does not yet support a simple universal retrofit fix for freight trucks [40] [42].

Confidence level: Medium — the solution classes are well-supported, but direct freight-truck deployment evidence is thinner [34] [42].

6. Current Best-Available Fixes and Practical Design Tradeoffs

6.1 What appears deployable now

Based on the retrieved evidence, the most practical current measures are:

1. **Brake blending that ramps out regen smoothly** and maintains stable deceleration when regen availability changes [15] [17] [20].
2. **Departure SOC management**, especially preserving headroom before expected long descents [4] [36].

3. **Battery thermal management and preconditioning**, to keep the pack in a charge-accepting window [8] [38] [39].
4. **Auxiliary buffers**, especially supercapacitors where packaging and cost permit [24] [28] [30].
5. **Resistor dumps as fallback**, but not as the sole long-term answer [21] [23].

6.2 What seems most promising longer-term

The strongest long-term direction is a **predictive, grade-aware energy management system** that knows battery limits in advance and preserves enough absorption capacity for upcoming descents [36] [45]. Taken together, these findings suggest a "regen reserve" strategy: avoid charging to 100% before mountain routes and reserve part of the SOC window for downhill absorption [4] [36].
Inferred: this route-aware reserve policy is supported conceptually but is not presented as standardized fleet guidance in the retrieved set.
Confidence level: Medium — strongly suggested by the evidence, but not yet backed by explicit OEM rules [45].

6.3 Regulatory and homologation considerations

The only explicit standard mentioned in the retrieved set is **ECE R13H/ECE-13H**, which papers use as a basis for braking-force distribution constraints and for showing that tested strategies satisfy general safety requirements [62] [63] [64]. The review literature also emphasizes that braking control must preserve emergency-braking performance and vehicle safety when regen is limited or unavailable [47] [52].

The evidence here is enough to say that fallback behavior is a recognized safety requirement, but not enough to give truck-specific regulatory operating rules for fully charged downhill departures [45] [46].

Confidence level: Medium — clear on safety relevance, limited on truck-specific operational guidance [45] [46].

Conclusion

The literature supports your core concern: heavy electric trucks can lose regenerative braking precisely when they most need it, because the battery—not the motor—becomes the limiting element at high SOC or under thermal constraint [4] [5] [8]. When that happens, friction brakes must absorb the energy, raising real risks of overheating, wear, fade, and cracking on long descents [11] [12] [13] [14].

The evidence also suggests that the industry's current fallback of resistor dumping is useful but fundamentally limited: it preserves braking torque at the cost of wasted energy, added heat, and transition complexity [21] [23]. The best-supported solution direction is a **layered architecture** combining smooth brake blending, route-aware SOC/thermal management, and a secondary energy buffer—most plausibly supercapacitors—so the truck has somewhere safe to put braking energy when the main battery cannot accept it [15] [24] [28] [30] [36].

Overall confidence level: High for the existence and mechanism of the problem and for the broad solution directions; **Medium** for exact truck-specific quantitative performance and operational thresholds because the retrieved field evidence is still sparse [11] [36] [37].

References

1. Liu, K., Feng, R., He, J., (...), Dan, Y. (2026) Comparative analysis of energy consumption characteristics in a battery-electric heavy-duty truck based on energy flow experiment under varied temperatures and state of charge. *Journal of Energy Storage*. https://doi.org/10.1016/j.est.2026.123059
2. Wagner, D., Steinsträter, M., Förth, M., (...), Lienkamp, M. (2019) Battery independent regenerative braking using model predictive control with auxiliary power consumers. *Forschung im Ingenieurwesen/Engineering Research*. https://doi.org/10.1007/s10010-019-00383-0
3. Shi, Q., Zhang, C., Cui, N. (2012) An improved electric vehicle regenerative braking strategy research. *Advances in Intelligent and Soft Computing*. https://doi.org/10.1007/978-3-642-30223-7_101
4. Pei, X., Pan, H., Chen, Z., (...), Yang, B. (2020) Coordinated control strategy of electro-hydraulic braking for energy regeneration. *Control Engineering Practice*. https://doi.org/10.1016/j.conengprac.2020.104324
5. Changizian, S., Ahmadi, P., Raeesi, M., Javani, N. (2020) Performance optimization of hybrid hydrogen fuel cell-electric vehicles in real driving cycles. *International Journal of Hydrogen Energy*. https://doi.org/10.1016/j.ijhydene.2020.01.015
6. Ahmadi, P., Raeesi, M., Changizian, S., (...), Khoshnevisan, A. (2022) Lifecycle assessment of diesel, diesel-electric and hydrogen fuel cell transit buses with fuel cell degradation and battery aging using machine learning techniques. *Energy*. https://doi.org/10.1016/j.energy.2022.125003
7. Tian, X., Zhai, M., Wan, S., (...), An, C. (2025) Assessment of energy efficiency of battery electric buses in cold regions. *Transportation Research Part D: Transport and Environment*. https://doi.org/10.1016/j.trd.2025.104934
8. Hwang, F.S., Confrey, T., Reidy, C., (...), Nolan, C. (2024) Review of battery thermal management systems in electric vehicles. *Renewable and Sustainable Energy Reviews*. https://doi.org/10.1016/j.rser.2023.114171
9. Olabi, A.G., Maghrabie, H.M., Adhari, O.H.K., (...), Abdelkareem, M.A. (2022) Battery thermal management systems: Recent progress and challenges. *International Journal of Thermofluids*. https://doi.org/10.1016/j.ijft.2022.100171
10. Liu, K., Feng, R., He, J., (...), Dan, Y. (2026) Comparative analysis of energy consumption characteristics in a battery-electric heavy-duty truck based on energy flow experiment under varied temperatures and state of charge. *Journal of Energy Storage*. https://doi.org/10.1016/j.est.2026.123059

11. Subel, Joshua, Kienhöfer, Frank W (2020) Thermal comparison of heavy vehicle wheel assemblies under alpine braking. *Proceedings of the Institution of Mechanical Engineers, Part D: Journal of Automobile Engineering*. https://doi.org/10.1177/0954407019844359
12. Songkitti, W., Boonsom, C., Aroonsrisopon, T., (...), Wirojsakunchai, E. (2026) Comprehensive particulate matter characterization study from Brake wear due to brake temperature under real-world driving test. *Environmental Challenges*. https://doi.org/10.1016/j.envc.2026.101460
13. Gigan, Gaël, Norman, Viktor, Ahlström, Johan, Vernersson, Tore (2019) Thermomechanical fatigue of grey cast iron brake discs for heavy vehicles. *Proceedings of the Institution of Mechanical Engineers, Part D: Journal of Automobile Engineering*. https://doi.org/10.1177/0954407017739723
14. Le Gigan, Gaël, Vernersson, Tore, Lundén, Roger, Skoglund, Peter (2015) Disc brakes for heavy vehicles: an experimental study of temperatures and cracks. *Proceedings of the Institution of Mechanical Engineers, Part D: Journal of Automobile Engineering*. https://doi.org/10.1177/0954407014550843
15. Pérez Fernández, J.P., García, J.M.V., Alcázar Vargas, M.G.A., (...), Cabrera, J.A.C. (2020) Influence of System Dynamics in Brake Blending Strategies for Electric Vehicles. *Lecture Notes in Mechanical Engineering*. https://doi.org/10.1007/978-3-030-38077-9_178
16. Subramaniyam, K.V., Subramanian, S.C. (2021) Impact of regenerative braking torque blend-out characteristics on electrified heavy road vehicle braking performance. *Vehicle System Dynamics*. https://doi.org/10.1080/00423114.2019.1677921
17. Ruan, J., Walker, P., Zhang, N., Xu, G. (2016) The Safety and Dynamic Performance of Blended Brake System on a Two-Speed DCT Based Battery Electric Vehicle. *SAE International Journal of Passenger Cars - Mechanical Systems*. https://doi.org/10.4271/2016-01-0468
18. Du, R., Mi, S., Hu, L., Meng, C. (2019) Simulation on Control Strategy for Torque Distribution of Compound Brake System in a Distributed Drive Electric Vehicle. *Qiche Gongcheng/Automotive Engineering*. https://doi.org/10.19562/j.chinasae.qcgc.2019.03.013
19. Li, W., Zhu, X., Ju, J. (2018) Hierarchical Braking Torque Control of In-Wheel-Motor-Driven Electric Vehicles over CAN. *IEEE Access*. https://doi.org/10.1109/ACCESS.2018.2877960
20. Vodovozov, V., Petlenkov, E., Aksjonov, A., Raud, Z. (2022) Simulation Study of Electric Vehicles at Fuzzy PID Control of Braking Torque. *Lecture Notes in Electrical Engineering*. https://doi.org/10.1007/978-3-030-92442-3_15
21. Arof, S., Noor, N.M., Rosyidi, M.R., (...), Noorsal, E. (2026) Expert System and Direct Torque Control to Extend the Electric Braking at the End of Resistive Braking Mode. *SpringerBriefs in Applied Sciences and Technology*. https://doi.org/10.1007/978-3-031-93198-7_8
22. Nicolae, P.-M., Nicolae, I.-D. (2010) On braking efficiency of urban electric transportation systems based on power electronics. *2010 IEEE Vehicle Power and Propulsion Conference, VPPC 2010*. https://doi.org/10.1109/VPPC.2010.5729156

23. Lee, D.-D., Hyun, D.-S., Shim, J.M. (2013) Temperature characteristics analysis of braking resistor for high speed train. *Studies in Informatics and Control*. https://doi.org/10.24846/v22i2y101303

24. Shanmugapriya, P., Srilekha, P., Sowndarya, R., (...), SureshKumar, M.S. (2024) Optimizing Regenerative Braking Efficiency with Supercapacitor for Electric Vehicles. *4th International Conference on Power, Energy, Control and Transmission Systems: Harnessing Power and Energy for an Affordable Electrification of India, ICPECTS 2024*. https://doi.org/10.1109/ICPECTS62210.2024.10780349

25. Vairavasundaram, V., Selvamathi, R., Devarajan, D., (...), Chitra, A. (2021) An Efficient Regenerative Braking System Based on Battery- Ultracapacitor for Electric Vehicles. *3rd IEEE International Virtual Conference on Innovations in Power and Advanced Computing Technologies, i-PACT 2021*. https://doi.org/10.1109/i-PACT52855.2021.9696557

26. Martyushev, N.V., Malozyomov, B.V., Kukartsev, V.V., (...), Kozenkova, G.L. (2026) Duty Cycle-Based Optimization of the Usable Energy Buffer Ratio in a Battery–Supercapacitor HESS for Mining Electric Dump Trucks. *World Electric Vehicle Journal*. https://doi.org/10.3390/wevj17070355

27. Jayachandra, J., Nakka, J. (2022) Battery and Supercapacitor Performance Analysis during Regenerative Braking in Electric Vehicle. *Proceedings - 2022 International Conference on Computing, Communication and Power Technology, IC3P 2022*. https://doi.org/10.1109/IC3P52835.2022.00030

28. Wang, F., Yin, X., Luoline, H., Huang, Y. (2012) A series regenerative braking control strategy based on hybrid-power. *Proceedings - 2012 International Conference on Computer Distributed Control and Intelligent Environmental Monitoring, CDCIEM 2012*. https://doi.org/10.1109/CDCIEM.2012.22

29. Setiawan, J.D., Budiman, B., Haryanto, I., (...), Hidayat, M.A. (2019) The Effect of Vehicle Inertia on Regenerative Braking Systems of Pure Electric Vehicles. *ICEVT 2019 - Proceeding: 6th International Conference on Electric Vehicular Technology 2019*. https://doi.org/10.1109/ICEVT48285.2019.8993977

30. Alamili, A., Xue, Y., Anayi, F. (2020) Laboratory-based examination of the effect of rotational inertia on energy recuperation in the regenerative braking process. *Energy Reports*. https://doi.org/10.1016/j.egyr.2020.02.026

31. Zou, Z., Cao, J., Cao, B., Chen, W. (2015) Evaluation strategy of regenerative braking energy for supercapacitor vehicle. *ISA Transactions*. https://doi.org/10.1016/j.isatra.2014.09.011

32. Midgley, W.J.B., Cebon, D. (2012) Comparison of regenerative braking technologies for heavy goods vehicles in urban environments. *Proceedings of the Institution of Mechanical Engineers, Part D: Journal of Automobile Engineering*. https://doi.org/10.1177/0954407011433395

33. Midgley, William JB, Cebon, D. (2016) Control of a hydraulic regenerative braking system for a heavy goods vehicle. *Proceedings of the Institution of Mechanical Engineers, Part D: Journal of Automobile Engineering*. https://doi.org/10.1177/0954407015607780

34. Pan, H., Qi, L., Zhang, Z., Yan, J. (2021) Kinetic energy harvesting technologies for applications in land transportation: A comprehensive review. *Applied Energy*. https://doi.org/10.1016/j.apenergy.2021.116518

35. Ma, Bin, Lin, Muyi, Chen, Yong, Wang, Lian-xin (2016) Investigation of energy efficiency for electro-hydraulic composite braking system which is based on the regenerated energy. *Advances in Mechanical Engineering*. https://doi.org/10.1177/1687814016666449

36. Li, X., Zhao, X., Xu, S., (...), Li, M. (2025) A novel braking energy management strategy for battery electric trucks with hydraulic retarder on long downhill. *Energy*. https://doi.org/10.1016/j.energy.2025.135684

37. Ekici, Y.E., Karadag, T., Akdağ, O. (2025) Redefining urban mobility: Real-world regenerative braking optimization via bio-inspired AI for electric buses energy efficiency. *Energy*. https://doi.org/10.1016/j.energy.2025.138854

38. Hu, X., Zheng, Y., Howey, D.A., (...), Pecht, M. (2020) Battery warm-up methodologies at subzero temperatures for automotive applications: Recent advances and perspectives. *Progress in Energy and Combustion Science*. https://doi.org/10.1016/j.pecs.2019.100806

39. Lee, S., Chung, Y., Lee, Y.I., (...), Kim, M.S. (2023) Battery thermal management strategy utilizing a secondary heat pump in electric vehicle under cold-start conditions. *Energy*. https://doi.org/10.1016/j.energy.2023.126827

40. Metwalley, S.M., Allam, E.M., Abouel-Seoud, S.A. (2012) Hardware core design for a regenerative braking system implemented on an extended range series hybrid ambulance microbus. *International Journal of Electric and Hybrid Vehicles*. https://doi.org/10.1504/IJEHV.2012.047844

41. da Silva Bravo, R.R.S., De Negri, V.J., Oliveira, A.A.M. (2018) Design and analysis of a parallel hydraulic - pneumatic regenerative braking system for heavy-duty hybrid vehicles. *Applied Energy*. https://doi.org/10.1016/j.apenergy.2018.04.102

42. Bondaruk, T., Willis, S., Liu, C. (2025) Poster: Erb System Retrofitted For School Bus Application. *Proceedings - 2025 IEEE 3rd International Conference on Mobility, Operations, Services and Technologies, MOST 2025*. https://doi.org/10.1109/MOST65065.2025.00037

43. Wu, J., Wang, X., Li, L., (...), Du, Y. (2018) Hierarchical control strategy with battery aging consideration for hybrid electric vehicle regenerative braking control. *Energy*. https://doi.org/10.1016/j.energy.2017.12.138

44. Park, Soojin, Sun, Di, Jang, Changhwan, Kim, Jinho (2023) Optimal design and verification through bench experiment to secure structural stability and improve thermodynamic performance of ventilated brake disc. *Advances in Mechanical Engineering*. https://doi.org/10.1177/16878132231151620

45. Ramesh Babu, A.R., Andrić, J., Minovski, B., Sebben, S. (2021) System-level modeling and thermal simulations of large battery packs for electric trucks. *Energies*. https://doi.org/10.3390/en14164796

46. Oleksowicz, S.A., Burnham, K.J., Southgate, A., (...), McMurran, R. (2013) Regenerative braking strategies, vehicle safety and stability control systems: Critical use-case proposals. *Vehicle System Dynamics*. https://doi.org/10.1080/00423114.2013.767462

47. Saiteja, P., Bragadeshwaran, B., Wagh, A.S., Farrag, M.E. (2022) Critical review on optimal regenerative braking control system architecture, calibration parameters and development challenges for EVs. *International Journal of Energy Research*. https://doi.org/10.1002/er.8306

48. Xu, P., Ma, Z., Wang, S., Zhang, S. (2024) Development of an experiment test bed based on a hydraulic accumulator for regenerative braking. *Experimental Technology and Management*. https://doi.org/10.16791/j.cnki.sjg.2024.08.020

49. Aksjonov, A., Vodovozov, V., Raud, Z. (2018) Improving Energy Recovery in Blended Antilock Braking Systems of Electric Vehicles. *Proceedings - IEEE 16th International Conference on Industrial Informatics, INDIN 2018*. https://doi.org/10.1109/INDIN.2018.8472024

50. Li, X., Dauletiyarova, J., Zhao, X., Wang, L. (2023) Study on Braking Energy Recovery Control Strategy for Four-Axle Battery Electric Heavy-Duty Trucks. *International Journal of Energy Research*. https://doi.org/10.1155/2023/1868528

51. Qiu, C., Wang, G., Meng, M., Shen, Y. (2018) A novel control strategy of regenerative braking system for electric vehicles under safety critical driving situations. *Energy*. https://doi.org/10.1016/j.energy.2018.02.046

52. Yang, C., Sun, T., Wang, W., (...), Zha, M. (2024) Regenerative braking system development and perspectives for electric vehicles: An overview. *Renewable and Sustainable Energy Reviews*. https://doi.org/10.1016/j.rser.2024.114389

53. Vodovozov, V., Raud, Z., Aksjonov, A., Petlenkov, E. (2020) Modelling of a Versatile Vehicle Braking System with a Fuzzy PID Torque Controller. *Proceedings of the Biennial Baltic Electronics Conference, BEC*. https://doi.org/10.1109/BEC49624.2020.9276798

54. Li, W., Du, H., Li, W. (2016) A New Torque Distribution Strategy for Blended Anti-Lock Braking Systems of Electric Vehicles Based on Road Conditions and Driver's Intentions. *SAE International Journal of Passenger Cars - Mechanical Systems*. https://doi.org/10.4271/2016-01-0461

55. Yao, J., Chen, G., Zong, C., Guo, Y. (2018) Research on Modeling of Distributed Compound Braking System and Braking Force Allocation Strategy. *IEEE Intelligent Vehicles Symposium, Proceedings*. https://doi.org/10.1109/IVS.2018.8500510

56. Liu, H., Deng, W., He, R., (...), Zhu, B. (2016) Function-Based Architecture Design for Next-Generation Automotive Brake Controls. *SAE International Journal of Passenger Cars - Mechanical Systems*. https://doi.org/10.4271/2016-01-0467

57. Fajri, P., Lee, S., Prabhala, V.A.K., Ferdowsi, M. (2016) Modeling and Integration of Electric Vehicle Regenerative and Friction Braking for Motor/Dynamometer Test Bench Emulation. *IEEE Transactions on Vehicular Technology*. https://doi.org/10.1109/TVT.2015.2504363

58. Biao, J., Zhang, Z., Yangxiong, W., Wenchao, H. (2021) Regenerative Braking Control Strategy of Electric Vehicles Based on Braking Stability Requirements. *International Journal of Automotive Technology*. https://doi.org/10.1007/s12239-021-0043-1

59. Wu, T., Wang, F., Ye, P. (2023) Regenerative Braking Strategy of Dual-Motor EV Considering Energy Recovery and Brake Stability. *World Electric Vehicle Journal*. https://doi.org/10.3390/wevj14010019

60. Bravo, R.R.D.S., Gama, A.T.D.C., Oliveira, A.A.M., De Negri, V.J. (2023) Component sizing and sensitivity analysis of design parameters of a hydraulic-pneumatic regenerative braking system for heavy duty vehicles. *Energy*. https://doi.org/10.1016/j.energy.2022.126021

61. Mathur, K., Choudhary, L.K., Natu, A.M., (...), Rastogi, V. (2019) Conceptualization and Modeling of a Flywheel-Based Regenerative Braking System for a Commercial Electric Bus. *SAE International Journal of Commercial Vehicles*. https://doi.org/10.4271/02-12-04-0018

62. Xiao, B., Lu, H., Wang, H., (...), Zhang, N. (2017) Enhanced regenerative braking strategies for electric vehicles: Dynamic performance and potential analysis. *Energies*. https://doi.org/10.3390/en10111875

63. Itani, K., De-Bernardinis, A., Khatir, Z., Jammal, A. (2016) Comparison between two braking control methods integrating energy recovery for a two-wheel front driven electric vehicle. *Energy Conversion and Management*. https://doi.org/10.1016/j.enconman.2016.05.094

64. Yin, Z., Ma, X., Su, R., (...), Zhang, C. (2023) Regenerative Braking of Electric Vehicles Based on Fuzzy Control Strategy. *Processes*. https://doi.org/10.3390/pr11102985