

Scan Report

February 11, 2026

Summary

This document reports on the results of an automatic security scan. All dates are displayed using the timezone “Coordinated Universal Time”, which is abbreviated “UTC”. The task was “Scan-Ubuntu-Server”. The scan started at Tue Feb 10 22:47:13 2026 UTC and ended at Wed Feb 11 00:39:23 2026 UTC. The report first summarises the results found. Then, for each host, the report describes every issue found. Please consider the advice given in each description, in order to rectify the issue.

Contents

1	Result Overview	2
1.1	Host Authentications	2
2	Results per Host	2
2.1	192.168.1.166	2
2.1.1	Critical 80/tcp	3
2.1.2	Critical 22/tcp	3
2.1.3	Critical 21/tcp	6
2.1.4	High 80/tcp	7
2.1.5	High 631/tcp	8
2.1.6	High 21/tcp	11
2.1.7	Medium 80/tcp	13
2.1.8	Medium 22/tcp	21
2.1.9	Medium 631/tcp	25
2.1.10	Medium 21/tcp	29
2.1.11	Low 22/tcp	30
2.1.12	Low general/tcp	31

1 Result Overview

Host	Critical	High	Medium	Low	Log	False P.
192.168.1.166	3	3	13	2	0	0
Total: 1	3	3	13	2	0	0

Vendor security updates are not trusted.

Overrides are off. Even when a result has an override, this report uses the actual threat of the result.

Information on overrides is included in the report.

Notes are included in the report.

This report might not show details of all issues that were found.

Issues with the threat level “Log” are not shown.

Issues with the threat level “Debug” are not shown.

Issues with the threat level “False Positive” are not shown.

Only results with a minimum QoD of 70 are shown.

This report contains all 21 results selected by the filtering described above. Before filtering there were 420 results.

1.1 Host Authentications

Host	Protocol	Result	Port/User
192.168.1.166	SMB	Success	Protocol SMB, Port 445, User

2 Results per Host

2.1 192.168.1.166

Host scan start Tue Feb 10 22:50:06 2026 UTC

Host scan end Wed Feb 11 00:39:15 2026 UTC

Service (Port)	Threat Level
80/tcp	Critical
22/tcp	Critical
21/tcp	Critical
80/tcp	High
631/tcp	High
21/tcp	High
80/tcp	Medium
22/tcp	Medium
631/tcp	Medium

... (continues) ...

... (continued) ...

Service (Port)	Threat Level
21/tcp	Medium
22/tcp	Low
general/tcp	Low

2.1.1 Critical 80/tcp

Critical (CVSS: 10.0) NVT: Drupal Coder RCE Vulnerability (SA-CONTRIB-2016-039) - Active Check
Summary Drupal is prone to a remote code execution (RCE) vulnerability.
Quality of Detection (QoD): 95%
Vulnerability Detection Result Vulnerable URL: http://192.168.1.166/drupal/sites/all/modules/coder/coder_upgrade/scripts/coder_upgrade.run.php
Solution: Solution type: VendorFix Install the latest version.
Vulnerability Insight The Coder module checks your Drupal code against coding standards and other best practices. It can also fix coding standard violations and perform basic upgrades on modules. The module doesn't sufficiently validate user inputs in a script file that has the php extension. A malicious unauthenticated user can make requests directly to this file to execute arbitrary php code.
Vulnerability Detection Method Checks for known error message from affected modules. Details: Drupal Coder RCE Vulnerability (SA-CONTRIB-2016-039) - Active Check OID:1.3.6.1.4.1.25623.1.0.105818 Version used: 2023-07-21T05:05:22Z
References url: https://www.drupal.org/node/2765575

[\[return to 192.168.1.166 \]](#)

2.1.2 Critical 22/tcp

Critical (CVSS: 9.8) NVT: SSH Brute Force Logins With Default Credentials Reporting
Summary It was possible to login into the remote SSH server using default credentials.
Quality of Detection (QoD): 95%
Vulnerability Detection Result It was possible to login with the following credentials <User>:<Password> vagrant:vagrant
Impact This issue may be exploited by a remote attacker to e.g. gain access to sensitive information or modify system configuration.
Solution: Solution type: Mitigation Change the password as soon as possible.
Affected Software/OS The following products are known to use the default credentials checked by the VT 'SSH Brute Force Logins With Default Credentials' (OID: 1.3.6.1.4.1.25623.1.0.108013) used for this reporting: - CVE-2017-16523: MitraStar GPT-2541GNAC (HGU) 1.00(VNJ0)b1 and DSL-100HN-T1 ES_113WJY0b16 devices - CVE-2017-20214: FLIR Thermal Camera F/FC/PT/D - CVE-2018-25138: FLIR AX8 Thermal Camera - CVE-2018-25147: Microhard Systems IPn4G - CVE-2019-25241: FaceSentry Access Control System - CVE-2019-25291: INIM Electronics Smartliving SmartLAN/G/SI - CVE-2020-29583: Zyxel Firewall / AP Controller - CVE-2020-36915: Adtec Digital SignEdge Digital Signage Player - CVE-2020-37092: Netis E1+ devices - CVE-2020-9473: S. Siedle & Soehne SG 150-0 Smart Gateway before 1.2.4 - CVE-2021-27797: Brocade Fabric OS - CVE-2021-47744: Cypress Solutions CTM-200/CTM-ONE - CVE-2023-1944: minikube 1.29.0 and probably prior - CVE-2023-53983: Anevia Flamingo XL/XS - CVE-2024-22902: Vinchin Backup & Recovery - CVE-2024-31970: AdTran SRG 834-5 HDC17600021F1 devices (with SmartOS 11.1.1.1) during a window of time when the device is being set up - CVE-2024-46328: VONETS VAP11G-300 v3.3.23.6.9 - CVE-2025-12592: Legacy Vivotek devices - CVE-2025-68718: KAYSUS KS-WR1200 ... continues on next page ...

...continued from previous page ...
- Various additional products like e.g. Ubiquiti EdgeMax / EdgeRouter, Crestron AM-100 and similar for which no CVE was assigned (See 'default_credentials.inc' file on the file system for a full list) Other products might be affected as well.
Vulnerability Insight As the VT 'SSH Brute Force Logins With Default Credentials' (OID: 1.3.6.1.4.1.25623.1.0.108013) might run into a timeout the actual reporting of this vulnerability takes place in this VT instead.
Vulnerability Detection Method Reports default credentials detected by the VT 'SSH Brute Force Logins With Default Credentials' (OID: 1.3.6.1.4.1.25623.1.0.108013). Details: SSH Brute Force Logins With Default Credentials Reporting OID:1.3.6.1.4.1.25623.1.0.103239 Version used: 2026-02-05T05:56:23Z
References cve: CVE-1999-0501 cve: CVE-1999-0502 cve: CVE-1999-0507 cve: CVE-1999-0508 cve: CVE-2005-1379 cve: CVE-2006-5288 cve: CVE-2009-3710 cve: CVE-2012-4577 cve: CVE-2016-1000245 cve: CVE-2017-16523 cve: CVE-2017-20214 cve: CVE-2018-25138 cve: CVE-2018-25147 cve: CVE-2019-25241 cve: CVE-2019-25291 cve: CVE-2020-29583 cve: CVE-2020-36915 cve: CVE-2020-37092 cve: CVE-2020-9473 cve: CVE-2021-27797 cve: CVE-2021-47744 cve: CVE-2023-1944 cve: CVE-2023-53983 cve: CVE-2024-22902 cve: CVE-2024-31970 cve: CVE-2024-46328 cve: CVE-2025-12592 cve: CVE-2025-41696 cve: CVE-2025-68718
... continues on next page ...

...continued from previous page...

url: <https://www.cisa.gov/known-exploited-vulnerabilities-catalog>
cisa: Known Exploited Vulnerability (KEV) catalog
cert-bund: WID-SEC-2025-2760

[\[return to 192.168.1.166 \]](#)

2.1.3 Critical 21/tcp

Critical (CVSS: 10.0)

NVT: ProFTPD 'mod_copy' Unauthenticated Copying Of Files Via SITE CPFR/CPTO Vulnerability (Apr 2015) - Active Check

Summary

ProFTPD is prone to an unauthenticated copying of files vulnerability.

Quality of Detection (QoD): 99%

Vulnerability Detection Result

The target was found to be vulnerable

Impact

Under some circumstances this could result in remote code execution.

Solution:

Solution type: VendorFix

Ask the vendor for an update.

Vulnerability Detection Method

Tries to copy /etc/passwd to /tmp/passwd.copy with SITE CPFR/CPTO command.

Details: ProFTPD 'mod_copy' Unauthenticated Copying Of Files Via SITE CPFR/CPTO Vulnerab.

↪..

OID:1.3.6.1.4.1.25623.1.0.105254

Version used: 2025-09-24T05:39:03Z

References

cve: CVE-2015-3306

url: http://bugs.proftpd.org/show_bug.cgi?id=4169

cert-bund: CB-K15/0791

cert-bund: CB-K15/0553

dfn-cert: DFN-CERT-2015-0839

dfn-cert: DFN-CERT-2015-0576

[\[return to 192.168.1.166 \]](#)

2.1.4 High 80/tcp

High (CVSS: 7.5) NVT: Drupal Core SQLi Vulnerability (SA-CORE-2014-005) - Active Check
Summary Drupal is prone to an SQL injection (SQLi) vulnerability.
Quality of Detection (QoD): 98%
Vulnerability Detection Result Vulnerable URL: <code>http://192.168.1.166/drupal/?q=node&destination=node</code>
Impact Exploiting this issue could allow an attacker to execute arbitrary code, to gain elevated privileges and to compromise the application, access or modify data, or exploit latent vulnerabilities in the underlying database.
Solution: Solution type: VendorFix Updates are available. Please see the references for more information.
Affected Software/OS Drupal 7.x versions prior to 7.32 are vulnerable.
Vulnerability Insight Drupal fails to sufficiently sanitize user-supplied data before using it in an SQL query.
Vulnerability Detection Method Sends a special crafted HTTP POST request and checks the response. Details: Drupal Core SQLi Vulnerability (SA-CORE-2014-005) - Active Check OID:1.3.6.1.4.1.25623.1.0.105101 Version used: 2023-07-26T05:05:09Z
References cve: CVE-2014-3704 url: https://www.drupal.org/forum/newsletters/security-advisories-for-drupal-core/2014-10-15/sa-core-2014-005-drupal-core-sql url: http://www.securityfocus.com/bid/70595 cert-bund: CB-K14/1301 cert-bund: CB-K14/0920 dfn-cert: DFN-CERT-2014-1369 dfn-cert: DFN-CERT-2014-0958

[\[return to 192.168.1.166 \]](#)

2.1.5 High 631/tcp

High (CVSS: 7.5) NVT: SSL/TLS: Report Vulnerable Cipher Suites for HTTPS
Product detection result cpe:/a:ietf:transport_layer_security Detected by SSL/TLS: Report Supported Cipher Suites (OID: 1.3.6.1.4.1.25623.1.0.↪802067)
Summary This routine reports all SSL/TLS cipher suites accepted by a service where attack vectors exists only on HTTPS services.
Quality of Detection (QoD): 98%
Vulnerability Detection Result 'Vulnerable' cipher suites accepted by this service via the TLSv1.0 protocol: TLS_RSA_WITH_3DES_EDE_CBC_SHA (SWEET32) 'Vulnerable' cipher suites accepted by this service via the TLSv1.1 protocol: TLS_RSA_WITH_3DES_EDE_CBC_SHA (SWEET32) 'Vulnerable' cipher suites accepted by this service via the TLSv1.2 protocol: TLS_RSA_WITH_3DES_EDE_CBC_SHA (SWEET32)
Impact This could allow remote attackers to obtain sensitive information or have other, unspecified impacts.
Solution: Solution type: Mitigation The configuration of this services should be changed so that it does not accept the listed cipher suites anymore. Please see the references for more resources supporting you with this task.
Affected Software/OS All services accepting vulnerable SSL/TLS cipher suites via HTTPS.
Vulnerability Insight These rules are applied for the evaluation of the vulnerable cipher suites: - 64-bit block cipher 3DES vulnerable to the SWEET32 attack (CVE-2016-2183).
Vulnerability Detection Method Checks previous collected cipher suites. Details: SSL/TLS: Report Vulnerable Cipher Suites for HTTPS OID:1.3.6.1.4.1.25623.1.0.108031
... continues on next page ...

...continued from previous page ...
Version used: 2025-03-27T05:38:50Z
Product Detection Result Product: cpe:/a:ietf:transport_layer_security Method: SSL/TLS: Report Supported Cipher Suites OID: 1.3.6.1.4.1.25623.1.0.802067)
References cve: CVE-2016-2183 cve: CVE-2016-6329 cve: CVE-2020-12872 url: https://ssl-config.mozilla.org url: https://www.bsi.bund.de/SharedDocs/Downloads/EN/BSI/Publications/TechGuidel ↪ines/TG02102/BSI-TR-02102-1.html url: https://www.bsi.bund.de/EN/Themen/0effentliche-Verwaltung/Mindeststandards/ ↪TLS-Protokoll/TLS-Protokoll_node.html url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Publikationen/Technisch ↪eRichtlinien/TR03116/BSI-TR-03116-4.html url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Mindeststandards/Mindes ↪tstandard_BSI_TLS_Version_2_4.html url: https://web.archive.org/web/20240113175943/https://www.bettercrypto.org url: https://www.enisa.europa.eu/publications/algorithms-key-size-and-parameters ↪-report-2014 url: https://sweet32.info cert-bund: WID-SEC-2026-0180 cert-bund: WID-SEC-2024-1277 cert-bund: WID-SEC-2024-0209 cert-bund: WID-SEC-2024-0064 cert-bund: WID-SEC-2022-2226 cert-bund: WID-SEC-2022-1955 cert-bund: CB-K21/1094 cert-bund: CB-K20/1023 cert-bund: CB-K20/0321 cert-bund: CB-K20/0314 cert-bund: CB-K20/0157 cert-bund: CB-K19/0618 cert-bund: CB-K19/0615 cert-bund: CB-K18/0296 cert-bund: CB-K17/1980 cert-bund: CB-K17/1871 cert-bund: CB-K17/1803 cert-bund: CB-K17/1753 cert-bund: CB-K17/1750 cert-bund: CB-K17/1709 cert-bund: CB-K17/1558 cert-bund: CB-K17/1273
...continues on next page ...

...continued from previous page ...

cert-bund: CB-K17/1202
 cert-bund: CB-K17/1196
 cert-bund: CB-K17/1055
 cert-bund: CB-K17/1026
 cert-bund: CB-K17/0939
 cert-bund: CB-K17/0917
 cert-bund: CB-K17/0915
 cert-bund: CB-K17/0877
 cert-bund: CB-K17/0796
 cert-bund: CB-K17/0724
 cert-bund: CB-K17/0661
 cert-bund: CB-K17/0657
 cert-bund: CB-K17/0582
 cert-bund: CB-K17/0581
 cert-bund: CB-K17/0506
 cert-bund: CB-K17/0504
 cert-bund: CB-K17/0467
 cert-bund: CB-K17/0345
 cert-bund: CB-K17/0098
 cert-bund: CB-K17/0089
 cert-bund: CB-K17/0086
 cert-bund: CB-K17/0082
 cert-bund: CB-K16/1837
 cert-bund: CB-K16/1830
 cert-bund: CB-K16/1635
 cert-bund: CB-K16/1630
 cert-bund: CB-K16/1624
 cert-bund: CB-K16/1622
 cert-bund: CB-K16/1500
 cert-bund: CB-K16/1465
 cert-bund: CB-K16/1307
 cert-bund: CB-K16/1296
 dfn-cert: DFN-CERT-2025-0041
 dfn-cert: DFN-CERT-2021-1618
 dfn-cert: DFN-CERT-2021-0775
 dfn-cert: DFN-CERT-2021-0770
 dfn-cert: DFN-CERT-2021-0274
 dfn-cert: DFN-CERT-2020-2141
 dfn-cert: DFN-CERT-2020-0368
 dfn-cert: DFN-CERT-2019-1455
 dfn-cert: DFN-CERT-2019-0068
 dfn-cert: DFN-CERT-2018-1296
 dfn-cert: DFN-CERT-2018-0323
 dfn-cert: DFN-CERT-2017-2070
 dfn-cert: DFN-CERT-2017-1954
 dfn-cert: DFN-CERT-2017-1885
 dfn-cert: DFN-CERT-2017-1831

...continues on next page ...

...continued from previous page ...

```

dfn-cert: DFN-CERT-2017-1821
dfn-cert: DFN-CERT-2017-1785
dfn-cert: DFN-CERT-2017-1626
dfn-cert: DFN-CERT-2017-1326
dfn-cert: DFN-CERT-2017-1239
dfn-cert: DFN-CERT-2017-1238
dfn-cert: DFN-CERT-2017-1090
dfn-cert: DFN-CERT-2017-1060
dfn-cert: DFN-CERT-2017-0968
dfn-cert: DFN-CERT-2017-0947
dfn-cert: DFN-CERT-2017-0946
dfn-cert: DFN-CERT-2017-0904
dfn-cert: DFN-CERT-2017-0816
dfn-cert: DFN-CERT-2017-0746
dfn-cert: DFN-CERT-2017-0677
dfn-cert: DFN-CERT-2017-0675
dfn-cert: DFN-CERT-2017-0611
dfn-cert: DFN-CERT-2017-0609
dfn-cert: DFN-CERT-2017-0522
dfn-cert: DFN-CERT-2017-0519
dfn-cert: DFN-CERT-2017-0482
dfn-cert: DFN-CERT-2017-0351
dfn-cert: DFN-CERT-2017-0090
dfn-cert: DFN-CERT-2017-0089
dfn-cert: DFN-CERT-2017-0088
dfn-cert: DFN-CERT-2017-0086
dfn-cert: DFN-CERT-2016-1943
dfn-cert: DFN-CERT-2016-1937
dfn-cert: DFN-CERT-2016-1732
dfn-cert: DFN-CERT-2016-1726
dfn-cert: DFN-CERT-2016-1715
dfn-cert: DFN-CERT-2016-1714
dfn-cert: DFN-CERT-2016-1588
dfn-cert: DFN-CERT-2016-1555
dfn-cert: DFN-CERT-2016-1391
dfn-cert: DFN-CERT-2016-1378

```

[\[return to 192.168.1.166 \]](#)

2.1.6 High 21/tcp

High (CVSS: 7.5)
NVT: FTP Brute Force Logins With Default Credentials Reporting

Summary

... continues on next page ...

...continued from previous page ...
It was possible to login into the remote FTP server using weak/known credentials.
Quality of Detection (QoD): 95%
Vulnerability Detection Result It was possible to login with the following credentials <User>:<Password> vagrant:vagrant
Impact This issue may be exploited by a remote attacker to e.g. gain access to sensitive information or modify system configuration.
Solution: Solution type: Mitigation Change the password as soon as possible.
Vulnerability Insight The following devices are / software is known to be affected: - CVE-2001-1594: Codonics printer FTP service as used in GE Healthcare eNTEGRA P&R - CVE-2013-7404: GE Healthcare Discovery NM 750b - CVE-2014-9198: Schneider Electric ETG3000 FactoryCast HMI gateways - CVE-2015-7261: QNAP iArtist Lite distributed with QNAP Signage Station - CVE-2016-8731: Foscam C1 devices - CVE-2017-8218: vsftpd on TP-Link C2 and C20i devices - CVE-2018-9068: IMM2 for IBM and Lenovo System x - CVE-2018-17771: Ingenico Telium 2 PoS terminals - CVE-2018-19063, CVE-2018-19064: Foscam C2 and Opticam i5 devices - CVE-2018-25147: Microhard Systems IPn4G - CVE-2020-36915: Adtec Digital SignEdge Digital Signage Player Note: As the VT 'FTP Brute Force Logins With Default Credentials' (OID: 1.3.6.1.4.1.25623.1.0.108717) might run into a timeout the actual reporting of this vulnerability takes place in this VT instead.
Vulnerability Detection Method Reports weak/known credentials detected by the VT 'FTP Brute Force Logins With Default Credentials' (OID: 1.3.6.1.4.1.25623.1.0.108717). Details: FTP Brute Force Logins With Default Credentials Reporting OID:1.3.6.1.4.1.25623.1.0.108718 Version used: 2026-01-16T15:42:49Z
References cve: CVE-1999-0501 cve: CVE-1999-0502 cve: CVE-1999-0507 cve: CVE-1999-0508 cve: CVE-2001-1594
... continues on next page ...

...continued from previous page ...

```

cve: CVE-2013-7404
cve: CVE-2014-9198
cve: CVE-2015-7261
cve: CVE-2016-8731
cve: CVE-2017-8218
cve: CVE-2018-9068
cve: CVE-2018-17771
cve: CVE-2018-19063
cve: CVE-2018-19064
cve: CVE-2018-25147
cve: CVE-2020-36915

```

[\[return to 192.168.1.166 \]](#)

2.1.7 Medium 80/tcp

Medium (CVSS: 6.1)

NVT: jQuery < 1.9.0 XSS Vulnerability

Summary

jQuery is prone to a cross-site scripting (XSS) vulnerability.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

Installed version: 1.6.2

Fixed version: 1.9.0

Installation

path / port: /phpmyadmin/setup/./js/jquery/jquery-1.6.2.js

Detection info (see OID: 1.3.6.1.4.1.25623.1.0.150658 for more info):

- Identified file: <http://192.168.1.166/phpmyadmin/setup/./js/jquery/jquery-1.6.2.js>
- Referenced at: <http://192.168.1.166/phpmyadmin/setup/>

Solution:

Solution type: VendorFix

Update to version 1.9.0 or later.

Affected Software/OS

jQuery prior to version 1.9.0.

Vulnerability Insight

... continues on next page ...

...continued from previous page ...
The jQuery(strInput) function does not differentiate selectors from HTML in a reliable fashion. In vulnerable versions, jQuery determined whether the input was HTML by looking for the '<' character anywhere in the string, giving attackers more flexibility when attempting to construct a malicious payload. In fixed versions, jQuery only deems the input to be HTML if it explicitly starts with the '<' character, limiting exploitability only to attackers who can control the beginning of a string, which is far less common.
Vulnerability Detection Method Checks if a vulnerable version is present on the target host. Details: jQuery < 1.9.0 XSS Vulnerability OID:1.3.6.1.4.1.25623.1.0.141636 Version used: 2023-07-14T05:06:08Z
References cve: CVE-2012-6708 url: https://bugs.jquery.com/ticket/11290 cert-bund: WID-SEC-2022-0673 cert-bund: CB-K22/0045 cert-bund: CB-K18/1131 dfn-cert: DFN-CERT-2025-1803 dfn-cert: DFN-CERT-2023-1197 dfn-cert: DFN-CERT-2020-0590
Medium (CVSS: 6.1) NVT: jQuery < 1.9.0 XSS Vulnerability
Summary jQuery is prone to a cross-site scripting (XSS) vulnerability.
Quality of Detection (QoD): 80%
Vulnerability Detection Result Installed version: 1.6.2 Fixed version: 1.9.0 Installation path / port: /phpmyadmin/js/jquery/jquery-1.6.2.js Detection info (see OID: 1.3.6.1.4.1.25623.1.0.150658 for more info): - Identified file: http://192.168.1.166/phpmyadmin/js/jquery/jquery-1.6.2.js - Referenced at: http://192.168.1.166/phpmyadmin/
Solution: Solution type: VendorFix Update to version 1.9.0 or later.
Affected Software/OS
... continues on next page ...

jQuery prior to version 1.9.0.	...continued from previous page ...
Vulnerability Insight The jQuery(strInput) function does not differentiate selectors from HTML in a reliable fashion. In vulnerable versions, jQuery determined whether the input was HTML by looking for the '<' character anywhere in the string, giving attackers more flexibility when attempting to construct a malicious payload. In fixed versions, jQuery only deems the input to be HTML if it explicitly starts with the '<' character, limiting exploitability only to attackers who can control the beginning of a string, which is far less common.	
Vulnerability Detection Method Checks if a vulnerable version is present on the target host. Details: jQuery < 1.9.0 XSS Vulnerability OID:1.3.6.1.4.1.25623.1.0.141636 Version used: 2023-07-14T05:06:08Z	
References cve: CVE-2012-6708 url: https://bugs.jquery.com/ticket/11290 cert-bund: WID-SEC-2022-0673 cert-bund: CB-K22/0045 cert-bund: CB-K18/1131 dfn-cert: DFN-CERT-2025-1803 dfn-cert: DFN-CERT-2023-1197 dfn-cert: DFN-CERT-2020-0590	

Medium (CVSS: 5.0) NVT: Sensitive File Disclosure (HTTP)
Summary The script attempts to identify files containing sensitive data at the remote web server.
Quality of Detection (QoD): 70%
Vulnerability Detection Result The following files containing sensitive information were identified: Description: Microsoft IIS / ASP.NET Core Module web.config file accessible. This could contain sensitive information about the structure of the application ↪ / web server and shouldn't be accessible. Match: <configuration> <system.webServer> Used regex: ^\s*<(configuration system\.web(Server)?> Extra match 1: </system.webServer> </configuration> Used regex: ^\s*</(configuration system\.web(Server)?> URL: http://192.168.1.166/drupal/web.config
... continues on next page ...

...continued from previous page ...
Impact Based on the information provided in these files an attacker might be able to gather additional info and/or sensitive data like usernames and passwords.
Solution: Solution type: Mitigation The sensitive files shouldn't be accessible via a web server. Restrict access to it or remove it completely.
Vulnerability Insight Currently the script is checking for files like e.g.: - Software (Blog, CMS) configuration or log files - Web / application server configuration / password files (e.g. .htaccess, .htpasswd, web.config, web.xml, ...) - Cloud (e.g. AWS) configuration files - Files containing API keys for services / providers - Database backup files (e.g. .sql, ...) - Editor / history files (e.g. .lessht, .dbshell, ...) - SSH or SSL/TLS Private Keys - Generic environment files (e.g. .env including the ones from Codeigniter, ...) - CVE-2017-16894: Laravel framework specific environment/.env files
Vulnerability Detection Method Enumerate the remote web server and check if sensitive files are accessible. Details: Sensitive File Disclosure (HTTP) OID:1.3.6.1.4.1.25623.1.0.107305 Version used: 2025-10-29T05:40:29Z
References cve: CVE-2017-16894

Medium (CVSS: 5.0) NVT: Drupal 7.0 Information Disclosure Vulnerability - Active Check
Summary Drupal is prone to an information disclosure vulnerability.
Quality of Detection (QoD): 95%
Vulnerability Detection Result Vulnerable URL: http://192.168.1.166/drupal/modules/simpletest/tests/upgrade/dru ↪pal-6.upload.database.php
Impact ... continues on next page ...

...continued from previous page ...
Successful exploitation will allow attacker to obtain sensitive information that could aid in further attacks.
Solution: Solution type: WillNotFix No known solution was made available for at least one year since the disclosure of this vulnerability. Likely none will be provided anymore. General solution options are to upgrade to a newer release, disable respective features, remove the product or replace the product by another one.
Affected Software/OS Drupal version 7.0 is known to be affected.
Vulnerability Insight The flaw is due to insufficient error checking, allows remote attackers to obtain sensitive information via a direct request to a .php file, which reveals the installation path in an error message.
Vulnerability Detection Method Details: Drupal 7.0 Information Disclosure Vulnerability - Active Check OID:1.3.6.1.4.1.25623.1.0.902574 Version used: 2021-12-01T11:10:56Z
References cve: CVE-2011-3730 url: http://code.google.com/p/inspathx/source/browse/trunk/paths_vuln/!_README url: http://code.google.com/p/inspathx/source/browse/trunk/paths_vuln/drupal-7.0

Medium (CVSS: 5.0) NVT: Unprotected Web App / Device Installers (HTTP)
Summary The script attempts to identify installation/setup pages of various web apps/devices that are publicly accessible and not protected by e.g. account restrictions or having their setup finished.
Quality of Detection (QoD): 80%
Vulnerability Detection Result The following web app/device installers are unprotected/have not finished their ↪setup and are publicly accessible (URL:Description): http://192.168.1.166/phpmyadmin/setup/index.php - CubeCart / phpMyAdmin install ↪r
Impact It is possible to install or reconfigure the software. In doing so, the attacker could overwrite existing configurations. It could be possible for the attacker to gain access to the base system
... continues on next page ...

...continued from previous page ...
Solution: Solution type: Mitigation Setup and/or installation pages for Web Apps should not be publicly accessible via a web server. Restrict access to it, remove it completely or finish the setup of the application / device.
Vulnerability Detection Method Enumerate the remote web server and check if unprotected web apps/devices are accessible for installation. Details: Unprotected Web App / Device Installers (HTTP) OID:1.3.6.1.4.1.25623.1.0.107307 Version used: 2025-12-18T05:46:55Z
Medium (CVSS: 4.8) NVT: Cleartext Transmission of Sensitive Information via HTTP
Summary The host / application transmits sensitive information (username, passwords) in cleartext via HTTP.
Quality of Detection (QoD): 80%
Vulnerability Detection Result The following input fields were identified (URL:input name): http://192.168.1.166/drupal/:pass http://192.168.1.166/drupal/?D=A:pass http://192.168.1.166/payroll_app.php:password http://192.168.1.166/phpmyadmin/:pma_password http://192.168.1.166/phpmyadmin/?D=A:pma_password http://192.168.1.166/phpmyadmin/changelog.php:pma_password http://192.168.1.166/phpmyadmin/index.php:pma_password http://192.168.1.166/phpmyadmin/license.php:pma_password http://192.168.1.166/phpmyadmin/url.php:pma_password
Impact An attacker could use this situation to compromise or eavesdrop on the HTTP communication between the client and the server using a man-in-the-middle attack to get access to sensitive data like usernames or passwords.
Solution: Solution type: Workaround Enforce the transmission of sensitive data via an encrypted SSL/TLS connection. Additionally make sure the host / application is redirecting all users to the secured SSL/TLS connection before allowing to input sensitive data into the mentioned functions.
... continues on next page ...

...continued from previous page ...
Affected Software/OS Hosts / applications which doesn't enforce the transmission of sensitive data via an encrypted SSL/TLS connection.
Vulnerability Detection Method Evaluate previous collected information and check if the host / application is not enforcing the transmission of sensitive data via an encrypted SSL/TLS connection. The script is currently checking the following: - HTTP Basic Authentication (Basic Auth) - HTTP Forms (e.g. Login) with input field of type 'password' Details: Cleartext Transmission of Sensitive Information via HTTP OID:1.3.6.1.4.1.25623.1.0.108440 Version used: 2023-09-07T05:05:21Z
References url: https://www.owasp.org/index.php/Top_10_2013-A2-Broken_Authentication_and_Session_Management url: https://www.owasp.org/index.php/Top_10_2013-A6-Sensitive_Data_Exposure url: https://cwe.mitre.org/data/definitions/319.html

Medium (CVSS: 4.3) NVT: jQuery < 1.6.3 XSS Vulnerability
Summary jQuery is prone to a cross-site scripting (XSS) vulnerability.
Quality of Detection (QoD): 80%
Vulnerability Detection Result Installed version: 1.6.2 Fixed version: 1.6.3 Installation path / port: /phpmyadmin/setup/../../js/jquery/jquery-1.6.2.js Detection info (see OID: 1.3.6.1.4.1.25623.1.0.150658 for more info): - Identified file: http://192.168.1.166/phpmyadmin/setup/../../js/jquery/jquery-1.6.2.js - Referenced at: http://192.168.1.166/phpmyadmin/setup/
Solution: Solution type: VendorFix Update to version 1.6.3 or later.
Affected Software/OS jQuery prior to version 1.6.3.
... continues on next page ...

...continued from previous page ...
Vulnerability Insight Cross-site scripting (XSS) vulnerability in jQuery before 1.6.3, when using location.hash to select elements, allows remote attackers to inject arbitrary web script or HTML via a crafted tag.
Vulnerability Detection Method Checks if a vulnerable version is present on the target host. Details: jQuery < 1.6.3 XSS Vulnerability OID:1.3.6.1.4.1.25623.1.0.141637 Version used: 2023-07-14T05:06:08Z
References cve: CVE-2011-4969 url: https://blog.jquery.com/2011/09/01/jquery-1-6-3-released/ cert-bund: CB-K17/0195 dfn-cert: DFN-CERT-2017-0199 dfn-cert: DFN-CERT-2016-0890
Medium (CVSS: 4.3) NVT: jQuery < 1.6.3 XSS Vulnerability
Summary jQuery is prone to a cross-site scripting (XSS) vulnerability.
Quality of Detection (QoD): 80%
Vulnerability Detection Result Installed version: 1.6.2 Fixed version: 1.6.3 Installation path / port: /phpmyadmin/js/jquery/jquery-1.6.2.js Detection info (see OID: 1.3.6.1.4.1.25623.1.0.150658 for more info): - Identified file: http://192.168.1.166/phpmyadmin/js/jquery/jquery-1.6.2.js - Referenced at: http://192.168.1.166/phpmyadmin/
Solution: Solution type: VendorFix Update to version 1.6.3 or later.
Affected Software/OS jQuery prior to version 1.6.3.
Vulnerability Insight Cross-site scripting (XSS) vulnerability in jQuery before 1.6.3, when using location.hash to select elements, allows remote attackers to inject arbitrary web script or HTML via a crafted tag.
... continues on next page ...

...continued from previous page ...
Vulnerability Detection Method Checks if a vulnerable version is present on the target host. Details: jQuery < 1.6.3 XSS Vulnerability OID:1.3.6.1.4.1.25623.1.0.141637 Version used: 2023-07-14T05:06:08Z
References cve: CVE-2011-4969 url: https://blog.jquery.com/2011/09/01/jquery-1-6-3-released/ cert-bund: CB-K17/0195 dfn-cert: DFN-CERT-2017-0199 dfn-cert: DFN-CERT-2016-0890

[\[return to 192.168.1.166 \]](#)

2.1.8 Medium 22/tcp

Medium (CVSS: 5.3) NVT: Weak Key Exchange (KEX) Algorithm(s) Supported (SSH)											
Product detection result cpe:/a:ietf:secure_shell_protocol Detected by SSH Protocol Algorithms Supported (OID: 1.3.6.1.4.1.25623.1.0.105565 ↪)											
Summary The remote SSH server is configured to allow / support weak key exchange (KEX) algorithm(s).											
Quality of Detection (QoD): 80%											
Vulnerability Detection Result The remote SSH server supports the following weak KEX algorithm(s): <table><tr><th>KEX algorithm</th><th>Reason</th></tr><tr><td colspan="2">-----</td></tr><tr><td colspan="2">↪-----</td></tr><tr><td>diffie-hellman-group-exchange-sha1</td><td> Using SHA-1</td></tr><tr><td>diffie-hellman-group1-sha1</td><td> Using Oakley Group 2 (a 1024-bit MODP group ↪) and SHA-1</td></tr></table>		KEX algorithm	Reason	-----		↪-----		diffie-hellman-group-exchange-sha1	Using SHA-1	diffie-hellman-group1-sha1	Using Oakley Group 2 (a 1024-bit MODP group ↪) and SHA-1
KEX algorithm	Reason										

↪-----											
diffie-hellman-group-exchange-sha1	Using SHA-1										
diffie-hellman-group1-sha1	Using Oakley Group 2 (a 1024-bit MODP group ↪) and SHA-1										
Impact An attacker can quickly break individual connections.											
Solution: Solution type: Mitigation Disable the reported weak KEX algorithm(s) ... continues on next page ...											

...continued from previous page ...
- 1024-bit MODP group / prime KEX algorithms: Alternatively use elliptic-curve Diffie-Hellmann in general, e.g. Curve 25519.
Vulnerability Insight - 1024-bit MODP group / prime KEX algorithms: Millions of HTTPS, SSH, and VPN servers all use the same prime numbers for Diffie-Hellman key exchange. Practitioners believed this was safe as long as new key exchange messages were generated for every connection. However, the first step in the number field sieve-the most efficient algorithm for breaking a Diffie-Hellman connection-is dependent only on this prime. A nation-state can break a 1024-bit prime.
Vulnerability Detection Method Checks the supported KEX algorithms of the remote SSH server. Currently weak KEX algorithms are defined as the following: - non-elliptic-curve Diffie-Hellmann (DH) KEX algorithms with 1024-bit MODP group / prime - ephemeral generated key exchange groups uses SHA-1 - using RSA 1024-bit modulus key Details: Weak Key Exchange (KEX) Algorithm(s) Supported (SSH) OID:1.3.6.1.4.1.25623.1.0.150713 Version used: 2024-06-14T05:05:48Z
Product Detection Result Product: cpe:/a:ietf:secure_shell_protocol Method: SSH Protocol Algorithms Supported OID: 1.3.6.1.4.1.25623.1.0.105565)
References url: https://weakdh.org/sysadmin.html url: https://www.rfc-editor.org/rfc/rfc9142 url: https://www.rfc-editor.org/rfc/rfc9142#name-summary-guidance-for-implem url: https://www.rfc-editor.org/rfc/rfc6194 url: https://www.rfc-editor.org/rfc/rfc4253#section-6.5
Medium (CVSS: 5.3) NVT: Weak Host Key Algorithm(s) (SSH)
Product detection result cpe:/a:ietf:secure_shell_protocol Detected by SSH Protocol Algorithms Supported (OID: 1.3.6.1.4.1.25623.1.0.105565 ↔)
Summary The remote SSH server is configured to allow / support weak host key algorithm(s). ... continues on next page ...

...continued from previous page ...
Quality of Detection (QoD): 80%
Vulnerability Detection Result The remote SSH server supports the following weak host key algorithm(s): host key algorithm Description ----- ↪----- ssh-dss Digital Signature Algorithm (DSA) / Digital Signature Stand ↪ard (DSS)
Solution: Solution type: Mitigation Disable the reported weak host key algorithm(s).
Vulnerability Detection Method Checks the supported host key algorithms of the remote SSH server. Currently weak host key algorithms are defined as the following: - ssh-dss: Digital Signature Algorithm (DSA) / Digital Signature Standard (DSS) Details: Weak Host Key Algorithm(s) (SSH) OID:1.3.6.1.4.1.25623.1.0.117687 Version used: 2024-06-14T05:05:48Z
Product Detection Result Product: cpe:/a:ietf:secure_shell_protocol Method: SSH Protocol Algorithms Supported OID: 1.3.6.1.4.1.25623.1.0.105565)
References url: https://www.rfc-editor.org/rfc/rfc8332 url: https://www.rfc-editor.org/rfc/rfc8709 url: https://www.rfc-editor.org/rfc/rfc4253#section-6.6
Medium (CVSS: 4.3) NVT: Weak Encryption Algorithm(s) Supported (SSH)
Product detection result cpe:/a:ietf:secure_shell_protocol Detected by SSH Protocol Algorithms Supported (OID: 1.3.6.1.4.1.25623.1.0.105565 ↪)
Summary The remote SSH server is configured to allow / support weak encryption algorithm(s).
... continues on next page ...

...continued from previous page ...
Quality of Detection (QoD): 80%
Vulnerability Detection Result The remote SSH server supports the following weak client-to-server encryption al gorithms(s): 3des-cbc aes128-cbc aes192-cbc aes256-cbc arcfour arcfour128 arcfour256 blowfish-cbc cast128-cbc rijndael-cbc@lysator.liu.se The remote SSH server supports the following weak server-to-client encryption al gorithms(s): 3des-cbc aes128-cbc aes192-cbc aes256-cbc arcfour arcfour128 arcfour256 blowfish-cbc cast128-cbc rijndael-cbc@lysator.liu.se
Solution: Solution type: Mitigation Disable the reported weak encryption algorithm(s).
Vulnerability Insight - The 'arcfour' cipher is the Arcfour stream cipher with 128-bit keys. The Arcfour cipher is believed to be compatible with the RC4 cipher [SCHNEIER]. Arcfour (and RC4) has problems with weak keys, and should not be used anymore. - The 'none' algorithm specifies that no encryption is to be done. Note that this method provides no confidentiality protection, and it is NOT RECOMMENDED to use it. - A vulnerability exists in SSH messages that employ CBC mode that may allow an attacker to recover plaintext from a block of ciphertext.
Vulnerability Detection Method Checks the supported encryption algorithms (client-to-server and server-to-client) of the remote SSH server. Currently weak encryption algorithms are defined as the following:
... continues on next page ...

...continued from previous page ...
- Arcfour (RC4) cipher based algorithms - 'none' algorithm - CBC mode cipher based algorithms Details: Weak Encryption Algorithm(s) Supported (SSH) OID: 1.3.6.1.4.1.25623.1.0.105611 Version used: 2024-06-14T05:05:48Z
Product Detection Result Product: cpe:/a:ietf:secure_shell_protocol Method: SSH Protocol Algorithms Supported OID: 1.3.6.1.4.1.25623.1.0.105565)
References url: https://www.rfc-editor.org/rfc/rfc8758 url: https://www.kb.cert.org/vuls/id/958563 url: https://www.rfc-editor.org/rfc/rfc4253#section-6.3

[\[return to 192.168.1.166 \]](#)

2.1.9 Medium 631/tcp

Medium (CVSS: 4.3) NVT: SSL/TLS: Deprecated TLSv1.0 and TLSv1.1 Protocol Detection
Product detection result cpe:/a:ietf:transport_layer_security:1.0 Detected by SSL/TLS: Version Detection (OID: 1.3.6.1.4.1.25623.1.0.105782)
Summary It was possible to detect the usage of the deprecated TLSv1.0 and/or TLSv1.1 protocol on this system.
Quality of Detection (QoD): 98%
Vulnerability Detection Result In addition to TLSv1.2+ the service is also providing the deprecated TLSv1.0 and ↪ TLSv1.1 protocols and supports one or more ciphers. Those supported ciphers c ↪an be found in the 'SSL/TLS: Report Supported Cipher Suites' (OID: 1.3.6.1.4.1 ↪.25623.1.0.802067) VT.
Impact An attacker might be able to use the known cryptographic flaws to eavesdrop the connection between clients and the service to get access to sensitive data transferred within the secured connection.
... continues on next page ...

...continued from previous page ...
Furthermore newly uncovered vulnerabilities in this protocols won't receive security updates anymore.
Solution: Solution type: Mitigation It is recommended to disable the deprecated TLSv1.0 and/or TLSv1.1 protocols in favor of the TLSv1.2+ protocols. Please see the references for more resources supporting you with this task.
Affected Software/OS - All services providing an encrypted communication using the TLSv1.0 and/or TLSv1.1 protocols - CVE-2023-41928: Kiloview P1 4G and P2 4G Video Encoder - CVE-2024-41270: Gorush v1.18.4 - CVE-2025-3200: Multiple products from Wiesemann & Theis
Vulnerability Insight The TLSv1.0 and TLSv1.1 protocols contain known cryptographic flaws like: - CVE-2011-3389: Browser Exploit Against SSL/TLS (BEAST) - CVE-2015-0204: Factoring Attack on RSA-EXPORT Keys Padding Oracle On Downgraded Legacy Encryption (FREAK)
Vulnerability Detection Method Checks the used TLS protocols of the services provided by this system. Details: SSL/TLS: Deprecated TLSv1.0 and TLSv1.1 Protocol Detection OID: 1.3.6.1.4.1.25623.1.0.117274 Version used: 2025-04-30T05:39:51Z
Product Detection Result Product: cpe:/a:ietf:transport_layer_security:1.0 Method: SSL/TLS: Version Detection OID: 1.3.6.1.4.1.25623.1.0.105782)
References cve: CVE-2011-3389 cve: CVE-2015-0204 cve: CVE-2023-41928 cve: CVE-2024-41270 cve: CVE-2025-3200 url: https://ssl-config.mozilla.org url: https://www.bsi.bund.de/SharedDocs/Downloads/EN/BSI/Publications/TechGuidelines/TG02102/BSI-TR-02102-1.html url: https://www.bsi.bund.de/EN/Themen/Oeffentliche-Verwaltung/Mindeststandards/TLS-Protokoll/TLS-Protokoll_node.html url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Publikationen/TechnischeRichtlinien/TR03116/BSI-TR-03116-4.html
... continues on next page ...

...continued from previous page...

```

url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Mindeststandards/Mindes
↪tstandard_BSI_TLS_Version_2_4.html
url: https://web.archive.org/web/20240113175943/https://www.bettercrypto.org
url: https://www.enisa.europa.eu/publications/algorithms-key-size-and-parameters
↪-report-2014
url: https://datatracker.ietf.org/doc/rfc8996/
url: https://vnhacker.blogspot.com/2011/09/beast.html
url: https://web.archive.org/web/20201108095603/https://censys.io/blog/freak
url: https://certvde.com/en/advisories/VDE-2025-031/
url: https://gist.github.com/nyxfqq/cfae38fada582a0f576d154be1aeb1fc
url: https://advisories.ncsc.nl/advisory?id=NCSC-2024-0273
cert-bund: WID-SEC-2026-0180
cert-bund: WID-SEC-2023-1435
cert-bund: CB-K18/0799
cert-bund: CB-K16/1289
cert-bund: CB-K16/1096
cert-bund: CB-K15/1751
cert-bund: CB-K15/1266
cert-bund: CB-K15/0850
cert-bund: CB-K15/0764
cert-bund: CB-K15/0720
cert-bund: CB-K15/0548
cert-bund: CB-K15/0526
cert-bund: CB-K15/0509
cert-bund: CB-K15/0493
cert-bund: CB-K15/0384
cert-bund: CB-K15/0365
cert-bund: CB-K15/0364
cert-bund: CB-K15/0302
cert-bund: CB-K15/0192
cert-bund: CB-K15/0079
cert-bund: CB-K15/0016
cert-bund: CB-K14/1342
cert-bund: CB-K14/0231
cert-bund: CB-K13/0845
cert-bund: CB-K13/0796
cert-bund: CB-K13/0790
dfn-cert: DFN-CERT-2020-0177
dfn-cert: DFN-CERT-2020-0111
dfn-cert: DFN-CERT-2019-0068
dfn-cert: DFN-CERT-2018-1441
dfn-cert: DFN-CERT-2018-1408
dfn-cert: DFN-CERT-2016-1372
dfn-cert: DFN-CERT-2016-1164
dfn-cert: DFN-CERT-2016-0388
dfn-cert: DFN-CERT-2015-1853
dfn-cert: DFN-CERT-2015-1332
... continues on next page ...

```

...continued from previous page ...	
dfn-cert:	DFN-CERT-2015-0884
dfn-cert:	DFN-CERT-2015-0800
dfn-cert:	DFN-CERT-2015-0758
dfn-cert:	DFN-CERT-2015-0567
dfn-cert:	DFN-CERT-2015-0544
dfn-cert:	DFN-CERT-2015-0530
dfn-cert:	DFN-CERT-2015-0396
dfn-cert:	DFN-CERT-2015-0375
dfn-cert:	DFN-CERT-2015-0374
dfn-cert:	DFN-CERT-2015-0305
dfn-cert:	DFN-CERT-2015-0199
dfn-cert:	DFN-CERT-2015-0079
dfn-cert:	DFN-CERT-2015-0021
dfn-cert:	DFN-CERT-2014-1414
dfn-cert:	DFN-CERT-2013-1847
dfn-cert:	DFN-CERT-2013-1792
dfn-cert:	DFN-CERT-2012-1979
dfn-cert:	DFN-CERT-2012-1829
dfn-cert:	DFN-CERT-2012-1530
dfn-cert:	DFN-CERT-2012-1380
dfn-cert:	DFN-CERT-2012-1377
dfn-cert:	DFN-CERT-2012-1292
dfn-cert:	DFN-CERT-2012-1214
dfn-cert:	DFN-CERT-2012-1213
dfn-cert:	DFN-CERT-2012-1180
dfn-cert:	DFN-CERT-2012-1156
dfn-cert:	DFN-CERT-2012-1155
dfn-cert:	DFN-CERT-2012-1039
dfn-cert:	DFN-CERT-2012-0956
dfn-cert:	DFN-CERT-2012-0908
dfn-cert:	DFN-CERT-2012-0868
dfn-cert:	DFN-CERT-2012-0867
dfn-cert:	DFN-CERT-2012-0848
dfn-cert:	DFN-CERT-2012-0838
dfn-cert:	DFN-CERT-2012-0776
dfn-cert:	DFN-CERT-2012-0722
dfn-cert:	DFN-CERT-2012-0638
dfn-cert:	DFN-CERT-2012-0627
dfn-cert:	DFN-CERT-2012-0451
dfn-cert:	DFN-CERT-2012-0418
dfn-cert:	DFN-CERT-2012-0354
dfn-cert:	DFN-CERT-2012-0234
dfn-cert:	DFN-CERT-2012-0221
dfn-cert:	DFN-CERT-2012-0177
dfn-cert:	DFN-CERT-2012-0170
dfn-cert:	DFN-CERT-2012-0146
dfn-cert:	DFN-CERT-2012-0142
...continues on next page ...	

...continued from previous page ...	
dfn-cert:	DFN-CERT-2012-0126
dfn-cert:	DFN-CERT-2012-0123
dfn-cert:	DFN-CERT-2012-0095
dfn-cert:	DFN-CERT-2012-0051
dfn-cert:	DFN-CERT-2012-0047
dfn-cert:	DFN-CERT-2012-0021
dfn-cert:	DFN-CERT-2011-1953
dfn-cert:	DFN-CERT-2011-1946
dfn-cert:	DFN-CERT-2011-1844
dfn-cert:	DFN-CERT-2011-1826
dfn-cert:	DFN-CERT-2011-1774
dfn-cert:	DFN-CERT-2011-1743
dfn-cert:	DFN-CERT-2011-1738
dfn-cert:	DFN-CERT-2011-1706
dfn-cert:	DFN-CERT-2011-1628
dfn-cert:	DFN-CERT-2011-1627
dfn-cert:	DFN-CERT-2011-1619
dfn-cert:	DFN-CERT-2011-1482

[\[return to 192.168.1.166 \]](#)

2.1.10 Medium 21/tcp

Medium (CVSS: 4.8) NVT: FTP Unencrypted Cleartext Login
Summary The remote host is running a FTP service that allows cleartext logins over unencrypted connections.
Quality of Detection (QoD): 70%
Vulnerability Detection Result The remote FTP service accepts logins without a previous sent 'AUTH TLS' command ↪. Response(s): Non-anonymous sessions: 331 Password required for openvasvt Anonymous sessions: 331 Anonymous login ok, send your complete email address ↪ as your password
Impact An attacker can uncover login names and passwords by sniffing traffic to the FTP service.
Solution: Solution type: Mitigation Enable FTPS or enforce the connection via the 'AUTH TLS' command. Please see the manual of the FTP service for more information.
... continues on next page ...

...continued from previous page ...
Vulnerability Detection Method Tries to login to a non FTPS enabled FTP service without sending a 'AUTH TLS' command first and checks if the service is accepting the login without enforcing the use of the 'AUTH TLS' command. Details: FTP Unencrypted Cleartext Login OID:1.3.6.1.4.1.25623.1.0.108528 Version used: 2023-12-20T05:05:58Z

[\[return to 192.168.1.166 \]](#)

2.1.11 Low 22/tcp

Low (CVSS: 2.6) NVT: Weak MAC Algorithm(s) Supported (SSH)
Product detection result cpe:/a:ietf:secure_shell_protocol Detected by SSH Protocol Algorithms Supported (OID: 1.3.6.1.4.1.25623.1.0.105565 ↩)
Summary The remote SSH server is configured to allow / support weak MAC algorithm(s).
Quality of Detection (QoD): 80%
Vulnerability Detection Result The remote SSH server supports the following weak client-to-server MAC algorithm ↩(s): hmac-md5 hmac-md5-96 hmac-md5-96-etm@openssh.com hmac-md5-etm@openssh.com hmac-sha1-96 hmac-sha1-96-etm@openssh.com umac-64-etm@openssh.com umac-64@openssh.com The remote SSH server supports the following weak server-to-client MAC algorithm ↩(s): hmac-md5 hmac-md5-96 hmac-md5-96-etm@openssh.com hmac-md5-etm@openssh.com hmac-sha1-96
... continues on next page ...

...continued from previous page ...
hmac-sha1-96-etm@openssh.com umac-64-etm@openssh.com umac-64@openssh.com
Solution: Solution type: Mitigation Disable the reported weak MAC algorithm(s).
Vulnerability Detection Method Checks the supported MAC algorithms (client-to-server and server-to-client) of the remote SSH server. Currently weak MAC algorithms are defined as the following: - MD5 based algorithms - 96-bit based algorithms - 64-bit based algorithms - 'none' algorithm Details: Weak MAC Algorithm(s) Supported (SSH) OID:1.3.6.1.4.1.25623.1.0.105610 Version used: 2024-06-14T05:05:48Z
Product Detection Result Product: cpe:/a:ietf:secure_shell_protocol Method: SSH Protocol Algorithms Supported OID: 1.3.6.1.4.1.25623.1.0.105565)
References url: https://www.rfc-editor.org/rfc/rfc6668 url: https://www.rfc-editor.org/rfc/rfc4253#section-6.4

[\[return to 192.168.1.166 \]](#)

2.1.12 Low general/tcp

Low (CVSS: 2.6) NVT: TCP Timestamps Information Disclosure
Summary The remote host implements TCP timestamps and therefore allows to compute the uptime.
Quality of Detection (QoD): 80%
Vulnerability Detection Result It was detected that the host implements RFC1323/RFC7323. The following timestamps were retrieved with a delay of 1 seconds in-between: ... continues on next page ...

...continued from previous page...	
Packet 1: 23055462	
Packet 2: 23056548	
Impact	
A side effect of this feature is that the uptime of the remote host can sometimes be computed.	
Solution:	
Solution type: Mitigation To disable TCP timestamps on linux add the line 'net.ipv4.tcp_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime. To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled' Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled. The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment. See the references for more information.	
Affected Software/OS	
TCP implementations that implement RFC1323/RFC7323.	
Vulnerability Insight	
The remote host implements TCP timestamps, as defined by RFC1323/RFC7323.	
Vulnerability Detection Method	
Special IP packets are forged and sent with a little delay in between to the target IP. The responses are searched for a timestamps. If found, the timestamps are reported. Details: TCP Timestamps Information Disclosure OID:1.3.6.1.4.1.25623.1.0.80091 Version used: 2023-12-15T16:10:08Z	
References	
url: https://datatracker.ietf.org/doc/html/rfc1323 url: https://datatracker.ietf.org/doc/html/rfc7323 url: https://web.archive.org/web/20151213072445/http://www.microsoft.com/en-us/download/details.aspx?id=9152 url: https://www.fortiguard.com/psirt/FG-IR-16-090	

[\[return to 192.168.1.166 \]](#)