



ANDROID STATIC ANALYSIS REPORT



 Clínica Veterinaria (1.0.0)

File Name:

app-debug.apk

Package Name:

com.clinicavet.clinica_veterinaria_mobile

Scan Date:

May 1, 2026, 2:21 p.m.

App Security Score:

39/100 (HIGH RISK)

Grade:



FINDINGS SEVERITY

 HIGH	 MEDIUM	 INFO	 SECURE	 HOTSPOT
5	3	2	2	0

FILE INFORMATION

File Name: app-debug.apk

Size: 64.93MB

MD5: 27ef0be5469de62cdb0b5c5659239227

SHA1: 234a7855c6d00caa3d5ffab37e259e0dc18493f8

SHA256: d60478c55eb66e35f30b7924ae9e4d8b80dd9883416bbdb2808ea3bcf663d333

APP INFORMATION

App Name: Clínica Veterinaria

Package Name: com.clinicavet.clinica_veterinaria_mobile

Main Activity: com.clinicavet.clinica_veterinaria_mobile.MainActivity

Target SDK: 36

Min SDK: 24

Max SDK:

Android Version Name: 1.0.0

Android Version Code: 1

APP COMPONENTS

Activities: 1
Services: 0
Receivers: 1
Providers: 1
Exported Activities: 0
Exported Services: 0
Exported Receivers: 1
Exported Providers: 0

CERTIFICATE INFORMATION

Binary is signed
v1 signature: False
v2 signature: True
v3 signature: False
v4 signature: False
X.509 Subject: CN=Android Debug, O=Android, C=US
Signature Algorithm: rsassa_pkcs1v15
Valid From: 2026-05-01 11:46:35+00:00
Valid To: 2056-04-23 11:46:35+00:00
Issuer: CN=Android Debug, O=Android, C=US
Serial Number: 0x1
Hash Algorithm: sha256
md5: c32016bc21f6c32c1a6842c760c00f9d
sha1: 68542dc64b08c85e50b03b193a24bd11aa81af96
sha256: 419bbb9b83a377be13fbaae42d1fcc26d7e56059b2c22bef502e115a4508f73a
sha512: be81f96bad9f878c5d4c3cb11a761632ced44263db2a940cb7eda09a68b8a4c725dad7a74d5f0c67486318a9f5bb0af17199d0c407f3720c61bcd324a45fdc0
PublicKey Algorithm: rsa
Bit Size: 2048
Fingerprint: 6b9c0febf8fc79b7597c2c5d62e46d12b0d09cd642ea5d48ed28356e5f8958e7
Found 1 unique certificates

APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.INTERNET	normal	full Internet access	Allows an application to create network sockets.
com.clinicavet.clinica_veterinaria_mobile.DYNAMIC_RECEIVER_NOT_EXPORTED_PERMISSION	unknown	Unknown permission	Unknown permission from android reference

 APKID ANALYSIS

FILE	DETAILS	
classes.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.MANUFACTURER check
	Compiler	r8
classes2.dex	FINDINGS	DETAILS
	Compiler	r8
classes3.dex	FINDINGS	DETAILS
	Compiler	r8

FILE	DETAILS	
classes4.dex	FINDINGS	DETAILS
	Compiler	r8
classes5.dex	FINDINGS	DETAILS
	Compiler	r8
classes6.dex	FINDINGS	DETAILS
	Compiler	unknown (please file detection issue!)
classes7.dex	FINDINGS	DETAILS
	Compiler	unknown (please file detection issue!)
classes8.dex	FINDINGS	DETAILS
	Compiler	r8

NETWORK SECURITY

HIGH: 0 | WARNING: 0 | INFO: 0 | SECURE: 1

NO	SCOPE	SEVERITY	DESCRIPTION
1	clinica-veterinaria-rxnp.onrender.com	secure	Domain config is securely configured to disallow clear text traffic to these domains in scope.

CERTIFICATE ANALYSIS

HIGH: 1 | WARNING: 0 | INFO: 1

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate
Application signed with debug certificate	high	Application signed with a debug certificate. Production application must not be shipped with a debug certificate.

MANIFEST ANALYSIS

HIGH: 2 | WARNING: 1 | INFO: 0 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	DESCRIPTION
1	App can be installed on a vulnerable unpatched Android version 7.0, [minSdk=24]	high	This application can be installed on an older version of android that has multiple unfixed vulnerabilities. These devices won't receive reasonable security updates from Google. Support an Android version => 10, API 29 to receive reasonable security updates.

NO	ISSUE	SEVERITY	DESCRIPTION
2	App has a Network Security Configuration[android:networkSecurityConfig=@xml/network_security_config]	info	The Network Security Configuration feature lets apps customize their network security settings in a safe, declarative configuration file without modifying app code. These settings can be configured for specific domains and for a specific app.
3	Debug Enabled For App [android:debuggable=true]	high	Debugging was enabled on the app which makes it easier for reverse engineers to hook a debugger to it. This allows dumping a stack trace and accessing debugging helper classes.
4	Broadcast Receiver (androidx.profileinstaller.ProfileInstallReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

</> CODE ANALYSIS

HIGH: 2 | WARNING: 1 | INFO: 2 | SECURE: 0 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	STANDARDS	FILES
				com/it_nomads/fluttersecurestorage/FlutterSecureStorage.java com/it_nomads/fluttersecurestorage/FlutterSecureStoragePlugin.java com/it_nomads/fluttersecurestorage/ciphers/StorageCipher18Implementation.java

NO	ISSUE	SEVERITY	STANDARDS	io/flutter/Log.java io/flutter/embedder/embedding/android/ContentSizingF lag.java
				io/flutter/embedding/android/FlutterActivity. java io/flutter/embedding/android/FlutterActivity AndFragmentDelegate.java io/flutter/embedding/android/FlutterFragme nt.java io/flutter/embedding/android/FlutterFragme ntActivity.java io/flutter/embedding/android/FlutterImageVi ew.java io/flutter/embedding/android/FlutterSurface View.java io/flutter/embedding/android/FlutterTexture View.java io/flutter/embedding/android/FlutterView.jav a io/flutter/embedding/android/KeyEmbedder Responder.java io/flutter/embedding/android/KeyboardMan ager.java io/flutter/embedding/android/SurfaceHolder CallbackCompat.java io/flutter/embedding/engine/FlutterEngine.ja va io/flutter/embedding/engine/FlutterEngineCo nnectionRegistry.java io/flutter/embedding/engine/FlutterJNI.java io/flutter/embedding/engine/dart/DartExecut or.java io/flutter/embedding/engine/dart/DartMesse nger.java io/flutter/embedding/engine/deferredcompo nents/PlayStoreDeferredComponentManager .java io/flutter/embedding/engine/image/Bitmap MetadataReader.java io/flutter/embedding/engine/image/ExifMeta dataReader.java io/flutter/embedding/engine/image/ImageDe

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	coderDefaultImpl.java io/flutter/embedding/engine/image/ImageUtils.java io/flutter/embedding/engine/image/MediaMetadataReader.java io/flutter/embedding/engine/loader/FlutterLoader.java io/flutter/embedding/engine/loader/ResourceExtractor.java io/flutter/embedding/engine/plugins/util/GeneratedPluginRegister.java io/flutter/embedding/engine/renderer/FlutterRenderer.java io/flutter/embedding/engine/systemchannels/AccessibilityChannel.java io/flutter/embedding/engine/systemchannels/BackGestureChannel.java io/flutter/embedding/engine/systemchannels/DeferredComponentChannel.java io/flutter/embedding/engine/systemchannels/KeyEventChannel.java io/flutter/embedding/engine/systemchannels/LifecycleChannel.java io/flutter/embedding/engine/systemchannels/LocalizationChannel.java io/flutter/embedding/engine/systemchannels/MouseCursorChannel.java io/flutter/embedding/engine/systemchannels/NavigationChannel.java io/flutter/embedding/engine/systemchannels/PlatformChannel.java io/flutter/embedding/engine/systemchannels/PlatformViewsChannel.java io/flutter/embedding/engine/systemchannels/PlatformViewsChannel2.java io/flutter/embedding/engine/systemchannels/RestorationChannel.java io/flutter/embedding/engine/systemchannels/ScribeChannel.java io/flutter/embedding/engine/systemchannels/SensitiveContentChannel.java io/flutter/embedding/engine/svstemchannels

NO	ISSUE	SEVERITY	STANDARDS	FILES
				/SettingsChannel.java io/flutter/embedding/engine/systemchannels /SpellCheckChannel.java io/flutter/embedding/engine/systemchannels /SystemChannel.java io/flutter/embedding/engine/systemchannels /TextInputChannel.java io/flutter/plugin/common/BasicMessageChannel.java io/flutter/plugin/common/EventChannel.java io/flutter/plugin/common/FlutterException.java io/flutter/plugin/common/MethodChannel.java io/flutter/plugin/common/StandardMessageCodec.java io/flutter/plugin/editing/InputConnectionAdapter.java io/flutter/plugin/editing/ListenableEditingState.java io/flutter/plugin/editing/TextEditingDelta.java io/flutter/plugin/editing/TextInputPlugin.java io/flutter/plugin/platform/ImageReaderPlatformViewRenderTarget.java io/flutter/plugin/platform/PlatformPlugin.java io/flutter/plugin/platform/PlatformViewWrapper.java io/flutter/plugin/platform/PlatformViewsController.java io/flutter/plugin/platform/PlatformViewsController2.java io/flutter/plugin/platform/SingleViewPresentation.java io/flutter/plugin/platform/SingleViewWindowManager.java io/flutter/plugins/GeneratedPluginRegistrant.java io/flutter/view/AccessibilityBridge.java io/flutter/view/AccessibilityViewEmbedder.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
2	Files may contain hardcoded sensitive information like usernames, passwords, keys etc.	warning	CWE: CWE-312: Cleartext Storage of Sensitive Information OWASP Top 10: M9: Reverse Engineering OWASP MASVS: MSTG-STORAGE-14	com/it_nomads/fluttersecurestorage/ciphers/StorageCipherFactory.java io/flutter/embedding/android/FlutterActivityAndFragmentDelegate.java io/flutter/embedding/android/FlutterActivityLaunchConfigs.java io/flutter/embedding/engine/loader/ApplicationInfoLoader.java io/flutter/embedding/engine/loader/FlutterLoader.java io/flutter/embedding/engine/systemchannels/SettingsChannel.java io/flutter/plugin/editing/SpellCheckPlugin.java
3	This App copies data to clipboard. Sensitive data should not be copied to clipboard as other applications can access it.	info	OWASP MASVS: MSTG-STORAGE-10	io/flutter/plugin/editing/InputConnectionAdapter.java io/flutter/plugin/platform/PlatformPlugin.java
4	Debug configuration enabled. Production builds must not be debuggable.	high	CWE: CWE-919: Weaknesses in Mobile Applications OWASP Top 10: M1: Improper Platform Usage OWASP MASVS: MSTG-RESILIENCE-2	com/it_nomads/fluttersecurestorage/BuildConfig.java io/flutter/BuildConfig.java
5	The App uses the encryption mode CBC with PKCS5/PKCS7 padding. This configuration is vulnerable to padding oracle attacks.	high	CWE: CWE-649: Reliance on Obfuscation or Encryption of Security-Relevant Inputs without Integrity Checking OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-3	com/it_nomads/fluttersecurestorage/ciphers/StorageCipher18Implementation.java

SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	arm64-v8a/libdartjni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
2	armeabi-v7a/libdartjni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	x86_64/libdartjni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
4	x86_64/libflutter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_fwrite_chk', '__vsprintf_chk', '__read_chk', '__write_chk', '__memcpy_chk', '__strcpy_chk', '__pread_chk', '__strlen_chk', '__memmove_chk', '__poll_chk', '__readlink_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
5	arm64-v8a/libdartjni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
6	armeabi-v7a/libdartjni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
7	x86_64/libdartjni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
8	x86_64/libflutter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_fwrite_chk', '__vsprintf_chk', '__read_chk', '__write_chk', '__memcpy_chk', '__strcpy_chk', '__pread_chk', '__strlen_chk', '__memmove_chk', '__poll_chk', '__readlink_chk', '__vsprintf_chk']	True info Symbols are stripped.

NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION
----	------------	-------------	---------	-------------

BEHAVIOUR ANALYSIS

RULE ID	BEHAVIOUR	LABEL	FILES
00022	Open a file from given absolute path of the file	file	com/getkeepsafe/relinker/ReLinkerInstance.java io/flutter/embedding/engine/deferredcomponents/PlayStoreDeferredComponentManager.java io/flutter/embedding/engine/loader/FlutterLoader.java
00125	Check if the given file path exist	file	io/flutter/embedding/engine/loader/FlutterLoader.java
00104	Check if the given path is directory	file	io/flutter/embedding/engine/deferredcomponents/PlayStoreDeferredComponentManager.java
00013	Read file and put it into a stream	file	com/getkeepsafe/relinker/elf/ElfParser.java
00161	Perform accessibility service action on accessibility node info	accessibility service	io/flutter/view/AccessibilityBridge.java io/flutter/view/AccessibilityViewEmbedder.java
00173	Get bounds in screen of an AccessibilityNodeInfo and perform action	accessibility service	io/flutter/view/AccessibilityViewEmbedder.java
00028	Read file from assets directory	file	io/flutter/embedding/engine/loader/ResourceExtractor.java
00209	Get pixels from the latest rendered image	collection	io/flutter/embedding/android/FlutterImageView.java
00210	Copy pixels from the latest rendered image into a Bitmap	collection	io/flutter/embedding/android/FlutterImageView.java

ABUSED PERMISSIONS

TYPE	MATCHES	PERMISSIONS
Malware Permissions	1/25	android.permission.INTERNET
Other Common Permissions	0/44	

Malware Permissions:

Top permissions that are widely abused by known malware.

Other Common Permissions:

Permissions that are commonly abused by known malware.

! OFAC SANCTIONED COUNTRIES

This app may communicate with the following OFAC sanctioned list of countries.

DOMAIN	COUNTRY/REGION
--------	----------------

🔍 DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
www.w3c.orghttp	ok	No Geolocation information available.

DOMAIN	STATUS	GEOLOCATION
dartbug.com	ok	IP: 216.239.38.21 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
docs.flutter.dev	ok	IP: 199.36.158.100 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
www.w3.org	ok	IP: 104.18.23.19 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
www.unicode.org	ok	IP: 104.26.10.47 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map

DOMAIN	STATUS	GEOLOCATION
github.com	ok	IP: 140.82.121.4 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
developer.android.com	ok	IP: 216.58.204.174 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map

EMAILS

EMAIL	FILE
_externalint16array@8027147._uninstant appro@openssl.org	lib/x86_64/libflutter.so
_externalint16array@8027147._uninstant appro@openssl.org	apktool_out/lib/x86_64/libflutter.so

HARDCODED SECRETS

POSSIBLE SECRETS
115792089210356248762697446949407573529996955224135760342422259061068512044369
5ac635d8aa3a93e7b3ebbd55769886bc651d06b0cc53b0f63bce3c3e27d2604b
VGhpcyBpcyB0aGUgcHJlZml4IGZvciBhIHNIY3VyZSBzdG9yYWdlCg
115792089210356248762697446949407573530086143415290314195533631308867097853951
3617de4a96262c6f5d9e98bf9292dc29f8f41dbd289a147ce9da3113b5f0b8c00a60b1ce1d7e819d7a431d7c90ea0e5f
11839296a789a3bc0045c8a5fb42c7d1bd998f54449579b446817afbd17273e662c97ee72995ef42640c550b9013fad0761353c7086a272c24088be94769fd16650
VGhpcyBpcyB0aGUga2V5IGZvciBhIHNIY3XyZZBzdG9yYWdlIEFFUyBLZXkk
VGhpcyBpcyB0aGUga2V5IGZvciBhIHNIY3VyZSBzdG9yYWdlIEFFUyBLZXkk
4fe342e2fe1a7f9b8ee7eb4a7c0f9e162bce33576b315ececbb6406837bf51f5
051953eb9618e1c9a1f929a21a0b68540eea2da725b99b315f3b8b489918ef109e156193951ec7e937b1652c0bd3bb1bf073573df883d2c34f1ef451fd46b503f00
c6858e06b70404e9cd9e3ecb662395b4429c648139053fb521f828af606b4d3dbaa14b5e77efe75928fe1dc127a2ffa8de3348b3c1856a429bf97e7e31c2e5bd66
39402006196394479212279040100143613805079739270465446667948293404245721771496870329047266088258938001861606973112319
aa87ca22be8b05378eb1c71ef320ad746e1d3b628ba79b9859f741e082542a385502f25dbf55296c3a545e3872760ab7
b3312fa7e23ee7e4988e056be3f82d19181d9c6efe8141120314088f5013875ac656398d8a2ed19d2a85c8edd3ec2aef
6b17d1f2e12c4247f8bce6e563a440f277037d812deb33a0f4a13945d898c296

POSSIBLE SECRETS
6864797660130609714981900799081393217269435300143305409394463459185543183397656052122559640661454554977296311391480858037121987999716643812574028291115057151
6864797660130609714981900799081393217269435300143305409394463459185543183397655394245057746333217197532963996371363321113864768612440380340372808892707005449
39402006196394479212279040100143613805079739270465446667946905279627659399113263569398956308152294913554433653942643

SCAN LOGS

Timestamp	Event	Error
2026-05-01 14:21:28	Generating Hashes	OK
2026-05-01 14:21:28	Extracting APK	OK
2026-05-01 14:21:28	Unzipping	OK
2026-05-01 14:21:29	Parsing APK with androguard	OK
2026-05-01 14:21:29	Extracting APK features using aapt/aapt2	OK
2026-05-01 14:21:29	Getting Hardcoded Certificates/Keystores	OK

2026-05-01 14:21:32	Parsing AndroidManifest.xml	OK
2026-05-01 14:21:32	Extracting Manifest Data	OK
2026-05-01 14:21:32	Manifest Analysis Started	OK
2026-05-01 14:21:32	Reading Network Security config from network_security_config.xml	OK
2026-05-01 14:21:32	Parsing Network Security config	OK
2026-05-01 14:21:32	Performing Static Analysis on: Clínica Veterinaria (com.clinicavet.clinica_veterinaria_mobile)	OK
2026-05-01 14:21:33	Fetching Details from Play Store: com.clinicavet.clinica_veterinaria_mobile	OK
2026-05-01 14:21:33	Checking for Malware Permissions	OK
2026-05-01 14:21:33	Fetching icon path	OK
2026-05-01 14:21:33	Library Binary Analysis Started	OK
2026-05-01 14:21:34	Analyzing lib/arm64-v8a/libdartjni.so	OK

2026-05-01 14:21:34	Analyzing lib/armeabi-v7a/libdartjni.so	OK
2026-05-01 14:21:34	Analyzing lib/x86_64/libdartjni.so	OK
2026-05-01 14:21:34	Analyzing lib/x86_64/libflutter.so	OK
2026-05-01 14:21:34	Analyzing apktool_out/lib/arm64-v8a/libdartjni.so	OK
2026-05-01 14:21:34	Analyzing apktool_out/lib/armeabi-v7a/libdartjni.so	OK
2026-05-01 14:21:34	Analyzing apktool_out/lib/x86_64/libdartjni.so	OK
2026-05-01 14:21:34	Analyzing apktool_out/lib/x86_64/libflutter.so	OK
2026-05-01 14:21:35	Reading Code Signing Certificate	OK
2026-05-01 14:21:35	Running APKiD 3.0.0	OK
2026-05-01 14:21:42	Detecting Trackers	OK
2026-05-01 14:21:45	Decompiling APK to Java with JADX	OK

2026-05-01 14:22:04	Converting DEX to Smali	OK
2026-05-01 14:22:04	Code Analysis Started on - java_source	OK
2026-05-01 14:22:05	Android SBOM Analysis Completed	OK
2026-05-01 14:22:07	Android SAST Completed	OK
2026-05-01 14:22:07	Android API Analysis Started	OK
2026-05-01 14:22:08	Android API Analysis Completed	OK
2026-05-01 14:22:09	Android Permission Mapping Started	OK
2026-05-01 14:22:10	Android Permission Mapping Completed	OK
2026-05-01 14:22:10	Android Behaviour Analysis Started	OK
2026-05-01 14:22:11	Android Behaviour Analysis Completed	OK
2026-05-01 14:22:11	Extracting Emails and URLs from Source Code	OK

2026-05-01 14:22:11	Email and URL Extraction Completed	OK
2026-05-01 14:22:11	Extracting String data from APK	OK
2026-05-01 14:22:11	Extracting String data from SO	OK
2026-05-01 14:22:12	Extracting String data from Code	OK
2026-05-01 14:22:12	Extracting String values and entropies from Code	OK
2026-05-01 14:22:13	Performing Malware check on extracted domains	OK
2026-05-01 14:22:14	Saving to Database	OK

Report Generated by - MobSF v4.5.0

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2026 Mobile Security Framework - MobSF | [Ajin Abraham](#) | [OpenSecurity](#).