

# IETF Hackathon: rpl-over-ble

- IETF 104
- 23-24 March, 2019
- Prague




# Hackathon Plan

Bluetooth **IPSP** and **RFC7668** do not specify anything regarding **connection handling in BLE**

- Existing approaches:
  - IPv6 Mesh over BLUETOOTH(R) Low Energy using IPSP (draft-ietf-6lo-blemesh-05)
  - Lee et al.: „A Synergistic Architecture for RPL over BLE“
- Plan: bake a subset of these approaches into a prototype using **RIOT** and **NimBLE**


# Concept

- Put RPL metadata (e.g. dodag id, rank, ...) into advertising packets
- Children scan for potential parents and connect to the most ,promising' one



# Results

- Working RPL-BLE multi-hop network with 6 nodes
  - stable for at least ~10s :-)
- Multiple PRs to RIOT and NimBLE



# What we learned

- The general concept is nice and simple
- But for the detail-devil:
  - multi-layered state handling (GAP vs. L2CAP vs. RPL) is a pain
  - sniffing advertisements impossible in this room :-)
  - BLE connections (once established) are surprisingly robust → thanks to TSCH

# Wrap Up

Team members:

Cenk Gündoğan

Hauke Petersen

First timers @ IETF/Hackathon:

-

Based on:

draft-ietf-6lo-blemesh-05

Lee et al.: „A Synergistic  
Architecture for RPL over  
BLE“