



# **IETF Hackathon**

## **Application-aware G-SRv6 networking**

**IETF 110**  
**March 1-5, 2021**  
**Online**



# Hackathon Plan

- Develop functions of Generalized SRv6 (**G-SRv6**), based on **Linux Kernel**.
- Combine **G-SRv6** with **APN6**, to achieve Application-aware G-SRv6 networking.
  - G-SRv6 IETF drafts:

<a href="#">draft-lc-6man-generalized-srh</a>	Data plane extension for Generalized Segment Routing Header
<a href="#">draft-cl-spring-generalized-srv6-np</a>	Generalized SRv6 Network Programming
<a href="#">draft-cl-spring-generalized-srv6-for-cmpr</a>	Generalized SRv6 Network Programming for SRv6 Compression
  - APN6 IETF drafts:

<a href="#">draft-li-6man-app-aware-ipv6-network</a>	Data plane extension for Application-aware IPv6 Networking (APN6)
<a href="#">draft-li-apn-framework</a>	Application-aware Networking (APN) Framework
<a href="#">draft-peng-apn-scope-gap-analysis</a>	APN Scope and Gap Analysis
  - Open Communities:

<a href="https://github.com/G-SRv6">https://github.com/G-SRv6</a>	G-SRv6 Community
<a href="https://github.com/APN-Community">https://github.com/APN-Community</a>	APN6 Community
<a href="https://www.ipv6plus.net">https://www.ipv6plus.net</a>	IPv6+ Community


# G-SRv6 Introduction

## Problem Statement

- **Transmission overhead** of SRv6 is too high.

## G-SRv6

- **Reduce 75%** size of SID List (transmission overhead).
- **No new** IPv6 address consumption, **no new** route creation.
- **Fully compatible** with SRv6, incremental deployment, deploy on demand.




**12+ Vendors have PASSED Interop-test**

# APN6 Introduction

APN6 makes use of IPv6 Extension Headers



- Convey the application related information, including its SLA requirements, along with the packet to the network.
- Allows the network to quickly adapt and perform the necessary actions for SLA guarantees.



# Application-aware G-SRv6 networking

- Enable application-aware fine-grained strict TE, **with lower transmission overhead.**

- Application-aware control
- Based on service requirements




- More efficient encapsulation
- SLA-guaranteed transmission resources
- Network programmability, fully compatible with SRv6

# Implemented Functions


- We've implemented the demo based on *Linux Kernel* & *Huawei Router*.
- Functions in our demo:
  - G-SRv6:
    1. Identify APN6 info, and select the most suitable G-SRv6 TE tunnel for the specific App / flow.
    2. Encapsulate G-SRv6 Routing Header (*Generalized SRH*).
    3. Implement *COC Flavor for End, End.X behavior*.
    4. Implement End, End.X, *End.DT6* as defined by SRv6 (*G-SRv6 is compatible with SRv6*).
    5. Implement G-SRv6 Local SID Table.
  - APN6:
    1. Encapsulate APN6 Options in IPv6 Hop-by-Hop Options Header, with application-specific info.

# Demo & Result

- Topology with three layers
- Three TE paths with 10+ hops (10+ SIDs in the SID List), for Apps with different SLA requirements.
- Apps:
  - File Downloading (Security checking in a SFC)
  - Interactive Control (Live & Short message)
  - HD Video on demand
- G-SRv6's Forwarding Rate is **55%+ higher** than SRv6's.
- For 128 bytes payload, Overhead is **reduced by 50%+**



Scheme	Application Throughput *	Network Throughput *	FCT *	RTT **	Forwarding Rate **	Bandwidth Utilization *
Best Effort (no APN)	0.94Gbps	0.94Gbps	923s	300.114 ms	/	10.28%
APN SRv6	7.48Gbps	9.01Gbps	114s	0.259 ms	400Mpps	83.07%
APN G-SRv6	8.36Gbps	9.01Gbps	102s	0.259 ms	620Mpps	92.78%



# What we learned

## Feedback to WG:

- G-SRv6 can improve **utilization** and **value of bandwidth significantly**.
- G-SRv6 is fully compatible with SRv6, and **can apply to more scenarios**.
  - e.g. Real-time control, Video on demand, HD Live streams, SFC, etc.
- Combining with APN6, flows of many kinds of Apps can be **distinguished fine-grained**, the SLA requirements of specific Apps can be **guaranteed better**.

## In the future:

- We can make more proof of concept tests in wider area networks, such as [CENI](#).
- We may share our codes of this demo openly in our [Github community](#).
- Processing delay in our Linux prototype is higher than SRv6 now (~1ms), welcome to join us to improve it together!



China Environment of  
Network Innovation



# Thank you :)

## Team members:

- Jianwei Mao, Huawei ([maojianwei@huawei.com](mailto:maojianwei@huawei.com))
- Jiang Liu, BUPT ([liujiang@bupt.edu.cn](mailto:liujiang@bupt.edu.cn))
- Weihong Wu, BUPT ([wwh\\_bupt@foxmail.com](mailto:wwh_bupt@foxmail.com))
- Lin He, Tsinghua ([he-l14@mails.tsinghua.edu.cn](mailto:he-l14@mails.tsinghua.edu.cn))
- Cheng Li, Huawei ([c.l@huawei.com](mailto:c.l@huawei.com))
- Shuping Peng, Huawei ([pengshuping@huawei.com](mailto:pengshuping@huawei.com))

## • Open Communities:

<https://github.com/G-SRv6>

<https://github.com/APN-Community>

<https://www.ipv6plus.net>

## • G-SRv6 Documents:

[draft-lic-6man-generalized-srh](#)

[draft-cl-spring-generalized-srv6-np](#)

[draft-cl-spring-generalized-srv6-for-cmpr](#)

## • APN6 Documents:

[draft-li-6man-app-aware-ipv6-network](#)

[draft-li-apn-framework](#)

[draft-peng-apn-scope-gap-analysis](#)