


# IETF117 Hackathon : OPUS / WebRTC

Analyse and integrate  
**Deep Audio Redundancy (DRED) Extension in Opus** in Gstreamer

**Altanai B (23 July 2023)**

Affiliation : Cisco Meraki



For use case of spike in loss ( heavy jitter ) such as burtsy network which could be a result of NAT rebinding or network handover, the audio codec needs to be resistant to heavy loss. One way is to overcome the missing data by synthetically reconstructing long sequences of lost packets.

This is achieved by **Deep REDundancy (DRED)** which works by adding side information inside the regular Opus packets. OPUS is the default WebRTC audio codec.

More explanation:

<https://www.amazon.science/blog/neural-encoding-enables-more-efficient-recovery-of-lost-audio-packets>

## **Aim of this hackathon project:**

1. To analyse Deep Audio Redundancy (DRED) Extension for the Opus Codec via PSEQ and waveform on large Voice dataset
2. Implement the Coder and Decoder change in Gstreamer base plugin implementation of OPUS

draft-valin-opus-dred-01







<https://datatracker.ietf.org/doc/draft-valin-opus-dred/>

# 1. To analyse Deep Audio Redundancy (DRED) Extension for the Opus Codec via PESQ and waveform

DataSet: PTDB-TUG size:4GB source: <https://www2.spsc.tugraz.at/databases/PTDB-TUG/>


## OPUS DRED extension reference test

### Top 20

Rank	Name	PESQ	Audio (out)	Audio (orig)
1	mic_M10_si2224	4.075	▶ 0:00 / 0:06  ⋮	▶ 0:00 / 0:06  ⋮
2	mic_M10_si2199	4.036	▶ 0:00 / 0:05  ⋮	▶ 0:00 / 0:05  ⋮
3	mic_M07_si1725	4.015	▶ 0:00 / 0:05  ⋮	▶ 0:00 / 0:05  ⋮

Tool Used : lpcnet-testsuite

<https://gitlab.xiph.org/xiph/opus/-/tree/opus-ng/dn/torch/testsuite>



Jupyter notebook :

[https://github.com/altanai/IETF117-OPUS-APPLICATION/blob/main/AudioWaveform\\_OPUS-ng.ipynb](https://github.com/altanai/IETF117-OPUS-APPLICATION/blob/main/AudioWaveform_OPUS-ng.ipynb)

## 2. POC for Coder and Decoder change in Gstreamer plugins-base implementation of OPUS for DRED



Encoder.c :Set `OPUS_SET_DRED_DURATION`  
as 1s and loss percentage to 20%

Also add changes to header file

Decoder Changes : monitor Seq number for loss and invoke `opus_dred_parse` params

OpusDREDDecoder ,  
OpusDRED,  
data,  
len,  
max\_dred\_samples,  
sampling\_rate,  
defer\_processing flag

# Wrap Up

Altanai B ([altanai@outlook.com](mailto:altanai@outlook.com))  
Cisco Meraki

- DRED IETF draft:  
<https://datatracker.ietf.org/doc/draft-valin-opus-dred/>
- Hacathin repo (work in progress )  
<https://github.com/altanai/IETF117-OPUS-APPLICATION>
- Source Code of the OPUS codec with DRED extension  
[https://gitlab.xiph.org/xiph/opus/-/tree/opus-ng?ref\\_type=heads](https://gitlab.xiph.org/xiph/opus/-/tree/opus-ng?ref_type=heads)
- Gstreamer (work in progress - incomplete )  
<https://github.com/altanai/gst-build>

