


Precitec Macro Documentation

02 Circle Detection using Hough

Changelog

Date	Version	Autor	Tested on	Description
2022-06-08	А	Wre	5.16.16	New documentation

Description



Searches for a circle with a radius between minimum and maximum radius.

I1: Image

I2: ROI

I3: minimal search radius [mm]

14: maximal search radius [mm]

O1: Position X in pixel

O2: Position Y in pixel

O3: Position X for Scanner


O4: Position Y for Scanner

O5: Radius [mm]

O6: Matching Score

© Precitec 1 von 3

Macro structure



Searches for a circle with a radius between minimum and maximum radius. Uses downsampling and smoothing before running an edge detection and hough algorithm over the ROI. Besides the position and radius, a matching score will be output as well.

Parameter

NAME	VALUE	Description	UserLevel
00 Downsampling → Verbosity Level	None	Visibility of downsampling	Admin
00 Downsampling → Jumping distance	1	Jumping distance while downsampling	Admin
00 Downsampling → Tile size	1	Tile size to downsample	Admin
01 Median → Verbosity Level	Low	Visibility of smoothed image	Admin
01 Median → Filter Length	3	Filter radius to be averaged on	Admin
02 Edge Detection → Verbosity Level	None	Visibility of edge detection operation	Admin
02 Edge Detection → Method	Sobel	Algorithm used for edge detection	Admin



02 Edge Detection → Scaling	0	Scale factor of edge detection operation	Admin
03 Circle Hough → Verbosity Level	Low	Visibility of circle detection	Admin
03 Circle Hough → Radius Step	5	Radius increase steps in pixel	Admin
03 Circle Hough → Number of max	5	Maximum amount of steps to increase radius	Admin
03 Circle Hough → IntensityThreshold	80	Grey level threshold to detect edges of a circle	Admin
03 Circle Hough → ScoreThreshold	-1	Threshold for matching score. Scores lower than the threshold are not accepted detections1 equals to no score threshold enabled	Admin
03 Circle Hough → SearchOutsideROI	0	Allow the algorithm to search for circles outside the ROI	Admin