2. Closed Hashing

Concept: Hash tables store keys directly within the array. A collision is resolved by trying alternative locations within the array until a free spot is found.

There are two important techniques for trying alternative locations:

a) Linear Probing

b) Quadratic Probing

a) Linear Probing:

Find the index i where the key should be mapped using the hash function.

If a collision occurs at index i, try index i+1, i+2, i+3, etc. until an empty spot is found.

If you reach the end of the array, wraparound.

Example 1: Keys are 22, 31, 10, 23, 95, 70, 63, 48

63

10	31	22	23	70	95	63		48	
0	1	2	3	4	5	6	7	8	9

70

22 % 10 → 2

70 % 10 → 0

63 % 10 → 3

Hash Function

index = (key % 10 + x) % 10

where x = 0, 1, 2, 3, etc.

In general, index = (key % tablesize + x) % table_size

where x = 0, 1, 2, 3, etc.

Example 2: Keys are 22, 32, 42, 97, 87, 57, 62, 77

0	1	2	3	4	5	6	7	8	9
77		22	32	42	62		97	87	57

Problems with linear probing:

1. Tends to form clusters (see example 2)
2. Problem with deletion.

Revisit Example 1

0	1	2	3	4	5	6	7	8	9
10	31	22	~~23~~	70	95	56		48	

Search for 70.
Suppose we delete 23
Then search for 70.

Solution: Lazy Deletion
Do not remove the deleted key, just flag it deleted.
Periodically, the array is flushed, deleted keys are removed, & the remaining keys are rehashed.

b) *Quadratic Probing:*

Find the index i where the key should be mapped using the hash function.

If a collision occurs at index i, try index $i+1^2$, $i+2^2$, $i+3^2$, etc. until an empty spot is found.

If you reach the end of the array, wraparound.

index = (key % table_size + x^2) % table_size

where $x = 0, 1, 2, 3$, etc.

Example 1:

Keys 22, 31, 23, 95, 70, 63, 48, 50

0	1	2	3	4	5	6	7	8	9
70	31	22	23	63	95			48	50

63 $+1^2$

50 $+1^2$ $+2^2$ $+3^2$

Example 2:

Keys 15, 25, 3, 43, 90, 28, 10, 57, 23

0	1	2	3	4	5	6	7	8	9
90	10	23	3	43	15	25	57	28	

28 $+1^2$

Example 3: 22, 32, 42, 52, 97, 87, 57

0	1	2	3	4	5	6	7	8	9
	52	22	32			42	97	87	

52

No spot for 57!

If the table size is prime & the table is less than half full, you can always find a spot for any key.

Applications of Hashing in Cybersecurity

Three cybersecurity goals:

Confidentiality:	No eavesdropping
Integrity:	Message sent = Message Received
Authentication:	You are who you say you are (Sender validation)

Hashing plays a role in these two!

DALHOUSIE UNIVERSITY

Applications of Hashing in Cybersecurity

1. Password Checking:

Let the password used by a client machine be P.

Hash of P is generated: hash(P).

A secret key known to the client and server is used to generate a random number, called Salt.

hash(P) is sent to the server. hash(P)+Salt is verified.
If it is correct, your login is successful.

2. File Modification Detector

For each file F, compute hash(F) and store it securely.

Each time the file is accessed, check if F is modified by verifying hash(F).

DALHOUSIE UNIVERSITY

Applications of Hashing in Cybersecurity

3. Sender verification by Digital Signatures:

Suppose A needs to send a message M to B.

A computes hash(M) – this is called the message digest.

A then encrypts hash(M) using a secret key – this is called the digital signature.

B receives the message and the digital signature.

Independently computes the digital signature and verifies it.

4. Blockchain

	Miner 1		Miner 2		Miner 3
Transaction T→	hash(T)	→	hash(hash(T))	→	hash(hash(hash(T)))

DALHOUSIE UNIVERSITY

LOAD FACTOR

$$\frac{\text{Number of keys hashed}}{\text{Hash Table Size}} = \frac{n}{N}$$

Open Hashing: n can be $> N$

Closed Hashing n must be $<= N$

TIME COMPLEXITY OF HASHING

Best case complexity for search: Open: $O(1)$, Closed: $O(1)$

Worst case complexity for search: Open: $O(n)$ → linked list, unbalanced tree; Closed: $O(n)$

Average case complexity for search (depends upon the load factor):

Open: $O\left(\frac{n}{N}\right)$ in linked list.

$O\left(\log_2\left(\frac{n}{N}\right)\right)$ in Balanced binary search trees

Closed:



REHASHING

When more and more keys are inserted, the current table size may not suffice. At that time, a *rehashing* is done – a new table double its size is created, and all the keys are remapped to the new table.

DOUBLE HASHING

The key is hashed twice to map it.

key is 1230

1230 % 10 = 0

123 % 10 = 3



HASH MAP IN JAVA

Java has a class called HashMap (java.util.HashMap) that lets you store and process keys and values associated with keys in a hash table.

Generics class with 2 parameters <K, V>

K → key

V → value (Record)

Some important methods in the HashMap class

put(K key, V value)	Adds a key and value to the hash table
get (K key)	Returns the value associated with the key; returns null if the key has no value associated with it.
containsKey(K key)	Returns true if the key is found
values()	Returns a collection of values in the table
keySet()	Returns the set of keys in the table
remove(K key)	Deletes the entry with key K
isEmpty()	Returns true if table is empty

```
//Simple illustration of hashmap in java
//Creates a hashmap of student id numbers as keys and student names as records.
import java.util.HashMap;
import java.util.Scanner;
import java.io.*;

public class HashMapDemo
{
	public static void main(String[] args) throws IOException
	{
		HashMap<Integer, String> studentRecord = new HashMap<Integer,String>();
		Integer id;
		String name;
		Scanner keyboard = new Scanner(System.in);
		System.out.print("Enter the filename to read from: ");
		String filename = keyboard.nextLine();

		File file = new File(filename);
		Scanner inputFile = new Scanner(file);

		while (inputFile.hasNext())
		{
			id = Integer.parseInt(inputFile.next());
			name = inputFile.nextLine();
			studentRecord.put(id, name);
		}

		inputFile.close();
		System.out.println(studentRecord.values());
		System.out.println(studentRecord.keySet());

		System.out.print("Enter key: ");
		id = keyboard.nextInt();
		if (studentRecord.containsKey(id)){
			name = studentRecord.get(id);
			System.out.println(id + "\t" + name  + "  found");
		}
		else
			System.out.println(id + " not found");
	}
}
```

key value

Input file:

```
10245 James
23450 Jack
10398 Amar
10009 Boris
51430 Amy
69087 Brenda
88700 Zirui
67568 Xu
22229 Nick
17171 Chandra
```

Sample Run:

```
Enter the filename to read from: students.txt
[ Chandra,  Nick,  Xu,  Jack,  Boris,  Amar,  Amy,  James,  Brenda,  Zirui]
[17171, 22229, 67568, 23450, 10009, 10398, 51430, 10245, 69087, 88700]

Enter the search key: 10398
10398    Amar found

Process completed.
```

Two alternative classes: TreeMap and LinkedHashMap

TreeMap stores the records in a tree data structure and retrieves them in a sorted order. Default sorting is done on the keys.

```
import java.util.TreeMap;
…

TreeMap<Integer,String> studentRecord = new TreeMap<Integer, String>();
```

Sample run:
Enter the filename to read from: students.txt
[Boris, James, Amar, Chandra, Nick, Jack, Amy, Xu, Brenda, Zirui]
[10009, 10245, 10398, 17171, 22229, 23450, 51430, 67568, 69087, 88700]

Enter the search key: 23450
23450 Jack found

LinkedHashMap stores the records using a doubly linked list. Retrieval is in the order of insertion.

```
import java.util.LinkedHashMap;
…

LinkedHashMap<Integer,String> studentRecord = new LinkedHashMap<Integer, String>();
```

Sample run:
Enter the filename to read from: students.txt
[James, Jack, Amar, Boris, Amy, Brenda, Zirui, Xu, Nick, Chandra]
[10245, 23450, 10398, 10009, 51430, 69087, 88700, 67568, 22229, 17171]

Enter the search key: 10009
10009 Boris found

```
import java.util.*;

public class HashMapDemo4 {

    public static void main(String [] args) {


      Scanner keyboard = new Scanner(System.in);

      // create empty map
      HashMap<String,ArrayList<Integer>> data =
          new HashMap<String,ArrayList<Integer>>();

      // read words, one on each line, until "end"
      String word = keyboard.next();
      int lineNumber = 1;
      while (!word.equals("end")) {

       // if the word is not yet in map
            if (data.get(word) == null) {

            // create a new list and add it to the map
            ArrayList<Integer> lines = new ArrayList<Integer>();
            lines.add(lineNumber);
            data.put(word,lines);
          }
          else {

            // get the existing list for this word
            ArrayList<Integer> lines = data.get(word);

            // add the line number to that list
            lines.add(lineNumber);
          }

          // get the next word
          word = keyboard.next();
          lineNumber += 1;
      }

      // print the map
      for (String w : data.keySet()) {
          System.out.println(w + " - " + data.get(w));
      }

    }

}
```

Trace this!