

```

ifer@10:~$ ping -c 2 www.digitalhouse.com.ar
ping: unknown host www.digitalhouse.com.ar
ifer@10:~$ ping -c 2 www.google.com
PING www.google.com (142.251.34.68) 56(84) bytes of data.
64 bytes from 68.34.251.142.in-addr.arpa (142.251.34.68): icmp_seq=1 ttl=57 time=7.99 ms
64 bytes from 68.34.251.142.in-addr.arpa (142.251.34.68): icmp_seq=2 ttl=57 time=7.97 ms

--- www.google.com ping statistics ---
2 packets transmitted, 2 received, 0% packet loss, time 1001ms
rtt min/avg/max/mdev = 7.975/7.983/7.992/0.089 ms
ifer@10:~$

```

```

ifer@10:~$ su root
Password:
root@10:/home/ifer# git --version
git version 2.7.4
root@10:/home/ifer# _

```

```

linuxdh [Corriendo] - Oracle VM VirtualBox
Archivo  Máquina  Ver  Entrada  Dispositivos  Ayuda

GNU nano 2.5.3                                New Buffer                                Modified

Por que un lenguaje de programacion solo puede utilizarse en algunos sistemas operativos y en otros$
Porque puede que ese lenguaje este dise  ado para funcionar solo en ese sistema operativo debido a $

Que tipo de maquina virtual es virtualBox
Es una maquina virtual de tipo 2, hipervisor de texto de nivel aplicacion

Si tengo mas de una maquina virtual instalada, y una se rompe, Eso afecta a las demas y por que ?
No afecta a las demas ya que cada maquina virtual es independiente y esta aislado _

^G Get Help  ^O Write Out  ^W Where Is  ^K Cut Text  ^J Justify  ^C Cur Pos  ^Y Prev Page
^X Exit      ^R Read File  ^_ Replace  ^U Uncut Text  ^T To Spell  ^_ Go To Line  ^U Next Page

```

```

ifer@10:~$ git clone https://github.com/IFer-21/Mochila_Martinez_Iker.git
Cloning into 'Mochila_Martinez_Iker'...
remote: Enumerating objects: 12, done.
remote: Counting objects: 100% (12/12), done.
remote: Compressing objects: 100% (9/9), done.
remote: Total 12 (delta 2), reused 11 (delta 1), pack-reused 0
Unpacking objects: 100% (12/12), done.
Checking connectivity... done.
ifer@10:~$ ls
Mochila_Martinez_Iker  txtOnVM.txt
ifer@10:~$ _

```

```

ifer@10:~$ mv txtOnVM.txt Mochila_Martinez_Iker/Entrega5/
ifer@10:~$ ls
Mochila_Martinez_Iker
ifer@10:~$ cd Mochila_Martinez_Iker/
ifer@10:~/Mochila_Martinez_Iker$ ls -r
Git-Github Entrega6 Entrega5 Entrega4 Entrega2 Entrega1
ifer@10:~/Mochila_Martinez_Iker$ ls
Entrega1 Entrega2 Entrega4 Entrega5 Entrega6 Git-Github
ifer@10:~/Mochila_Martinez_Iker$ ls -R
.:
Entrega1 Entrega2 Entrega4 Entrega5 Entrega6 Git-Github

./Entrega1:
Readme.md

./Entrega2:
Actividad armado de computadoras.pdf Readme.md

./Entrega4:
Entrega4.pdf Readme.md

./Entrega5:
Readme.md txtOnVM.txt

./Entrega6:
Readme.md

./Git-Github:
Readme.md
ifer@10:~/Mochila_Martinez_Iker$ _

```

```

ifer@10:~/Mochila_Martinez_Iker$ git add .
ifer@10:~/Mochila_Martinez_Iker$ git status
On branch main
Your branch is up-to-date with 'origin/main'.
Changes to be committed:
  (use "git reset HEAD <file>..." to unstage)

    new file:   Entrega5/txtOnVM.txt

ifer@10:~/Mochila_Martinez_Iker$ git commit -m "subido desde VM Ubuntu Server"

```

 linuxdh [Corriendo] - Oracle VM VirtualBox

```

Archivo Máquina Ver Entrada Dispositivos Ayuda
ifer@10:~/Mochila_Martinez_Iker$ git config --global credential.helper cache
ifer@10:~/Mochila_Martinez_Iker$ git push origin
HEAD      main      origin/HEAD  origin/main
ifer@10:~/Mochila_Martinez_Iker$ git push origin main
Username for 'https://github.com': IFer-21
Password for 'https://IFer21@github.com':
Counting objects: 4, done.
Compressing objects: 100% (4/4), done.
Writing objects: 100% (4/4), 629 bytes | 0 bytes/s, done.
Total 4 (delta 1), reused 0 (delta 0)
remote: Resolving deltas: 100% (1/1), completed with 1 local object.
remote: To https://github.com/IFer-21/Mochila_Martinez_Iker.git
       8142ee8..05ac7c5  main -> main
ifer@10:~/Mochila_Martinez_Iker$ git pull
Already up-to-date.
ifer@10:~/Mochila_Martinez_Iker$

```