

Preamble

The IHEC metadata standards are extension of the standards used by the Roadmap Epigenomics Project. Please refer to Sections 1 and 2 of original specification (archived at https://github.com/IHEC/ihec-metadata/blob/master/specs/original_docs/IHEC-Metadata.pdf) for the data and metadata model.

This document describes metadata elements extending the SRA XML Schema 1.2

Metadata Elements Extending SRA XML Schema 1.2

(quoting Section 3 Introuction, https://github.com/IHEC/ihec-metadata/blob/master/specs/original_docs/IHEC-Metadata.pdf)

The core SRA XML elements are augmented by additional attributes defined for purposes of the NIH Roadmap Epigenomics as described in the official IHEC ecosystem repository.

The same attribute may be used multiple times in a single XML record. This may be most useful for supplying URIs to multiple ontologies or for supplying multiple references to a single ontology such as in the case of DISEASE_ONTOLOGY_URI.

Documentation for the core SRA XML elements is here:

<http://www.ncbi.nlm.nih.gov/Traces/sra/sra.cgi?view=doc>

The SRA XML schema <http://www.ncbi.nlm.nih.gov/Traces/sra/sra.cgi?view=docas> are here:

- http://www.ncbi.nlm.nih.gov/Traces/sra/sra.cgi?view=xml_schemas

Tags with controlled vocabularies are labelled as “Controlled Vocabulary”

Tags with ontolgies are labelled as “Ontology”

Ontologies

Only terms from following ontologies are acceptable for annotating the metadata:

Sample Ontologies

- Cell Lines - Experimental Factor Ontology (EFO)
- Primary Cells - Cell Ontology (CL)

- Primary Tissue - Uberon

Disease Ontologies

- Disease - NCI Metathesaurus

Experiment Ontologies

- Assays and Platforms - Ontology for Biomedical Investigations (OBI)

IHEC Extensions

Level 0 Data

SAMPLES

Cell Line

MOLECULE - (Controlled Vocabulary) The type of molecule that was extracted from the biological material. Include one of the following: total RNA, polyA RNA, cytoplasmic RNA, nuclear RNA, genomic DNA, protein, or other.

MOLECULE_ONTOLOGY_URI - (Ontology) links to molecule ontology information

SAMPLE_ONTOLOGY_URI - (Ontology) links to sample ontology information.

DISEASE_ONTOLOGY_URI - (Ontology) links to disease ontology information. The NCI metathesaurus term C0277545 “Disease type AND/OR category unknown” should be used for unknown diseases. Phenotypes associated with the disease should be submitted as DISEASE_ONTOLOGY_URIs (if available) or in the free form DISEASE attribute.

DISEASE: Free form field for more specific disease information

BIOMATERIAL_PROVIDER - The name of the company, laboratory or person that provided the biological material.

BIOMATERIAL_TYPE: Cell Line

LINE - The name of the cell line.

LINEAGE - The developmental lineage to which the cell line belongs.

DIFFERENTIATION_STAGE - The stage in cell differentiation to which the cell line belongs.

DIFFERENTIATION__METHOD - The protocol used to differentiate the cell line.

PASSAGE - The number of times the cell line has been re-plated and allowed to grow back to confluency or to some maximum density if using suspension cultures.

MEDIUM - The medium in which the cell line has been grown.

SEX: “Male”, “Female”, “Unknown”, or “Mixed” for pooled samples.

BATCH - The batch from which the cell line is derived. Primarily applicable to initial H1 cell line batches. NA if not applicable.

Primary Cell

MOLECULE - (Controlled Vocabulary) The type of molecule that was extracted from the biological material. Include one of the following: total RNA, polyA RNA, cytoplasmic RNA, nuclear RNA, genomic DNA, protein, or other.

MOLECULE__ONTOLOGY__URI - (Ontology) links to molecule ontology information

SAMPLE__ONTOLOGY__URI - (Ontology) links to sample ontology information.

DISEASE__ONTOLOGY__URI - (Ontology) links to disease ontology information. If dealing with a rare disease consider identifiability issues. The NCI metathesaurus term C0277545 “Disease type AND/OR category unknown” should be used for unknown diseases. Phenotypes associated with the disease should be submitted as DISEASE__ONTOLOGY__URIs (if available) or in the free form DISEASE attribute.

DISEASE: Free form field for more specific disease information. If dealing with a rare disease consider identifiability issues.

BIOMATERIAL__PROVIDER - The name of the company, laboratory or person that provided the biological material.

BIOMATERIAL__TYPE: Primary Cell

CELL__TYPE - The type of cell.

MARKERS - Markers used to isolate and identify the cell type.

DONOR__ID - An identifying designation for the donor that provided the primary cell.

DONOR__AGE - The age of the donor that provided the primary cell. NA if not available. If over 90 years enter as 90+. If entering a range of ages use the format “{age}-{age}”.

DONOR__AGE__UNIT - (Controlled Vocabulary) “year”, “month”, “week”, or “day”.

DONOR__LIFE__STAGE - (Controlled Vocabulary) “fetal”, “newborn”, “child”, “adult”, “unknown”, “embryonic”, “postnatal”

DONOR__HEALTH__STATUS - The health status of the donor that provided the primary cell. NA if not available.

DONOR__SEX - (Controlled Vocabulary) “Male”, “Female”, “Unknown”, or “Mixed” for pooled samples.

DONOR__ETHNICITY - The ethnicity of the donor that provided the primary cell. NA if not available. If dealing with small/vulnerable populations consider identifiability issues.

PASSAGE__IF__EXPANDED - If the primary cell has been expanded, the number of times the primary cell has been re-plated and allowed to grow back to confluency or to some maximum density if using suspension cultures. NA if no expansion.

Primary Cell Culture

MOLECULE - (Controlled Vocabulary) The type of molecule that was extracted from the biological material. Include one of the following: total RNA, polyA RNA, cytoplasmic RNA, nuclear RNA, genomic DNA, protein, or other.

MOLECULE__ONTOLOGY__URI - (Ontology) links to molecule ontology information

SAMPLE__ONTOLOGY__URI - (Ontology) links to sample ontology information.

DISEASE__ONTOLOGY__URI - (Ontology) links to disease ontology information. If dealing with a rare disease consider identifiability issues. The NCImetathesaurus term C0277545 “Disease type AND/OR category unknown” should be used for unknown diseases. Phenotypes associated with the disease should be submitted as DISEASE__ONTOLOGY__URIs (if available) or in the free form DISEASE attribute.

DISEASE - Free form field for more specific disease information. If dealing with a rare disease consider identifiability issues.

BIOMATERIAL__PROVIDER - The name of the company, laboratory or person that provided the biological material.

BIOMATERIAL__TYPE - Primary Cell Culture

CELL__TYPE - The type of cell.

MARKERS - Markers used to isolate and identify the cell type.

CULTURE_CONDITIONS - The conditions under which the primary cell was cultured.

DONOR_ID - An identifying designation for the donor that provided the primary cell.

DONOR_AGE - The age of the donor that provided the primary cell. NA if not available. If over 90 years enter as 90+. If entering a range of ages use the format “{age}-{age}”.

DONOR_AGE_UNIT - (Controlled Vocabulary) “year”, “month”, “week”, or “day”.

DONOR_LIFE_STAGE - (Controlled Vocabulary) “fetal”, “newborn”, “child”, “adult”, “unknown”, “embryonic”, “postnatal”

DONOR_HEALTH_STATUS - The health status of the donor that provided the primary cell. NA if not available.

DONOR_SEX - (Controlled Vocabulary) “Male”, “Female”, “Unknown”, or “Mixed” for pooled samples.

DONOR_ETHNICITY - The ethnicity of the donor that provided the primary cell. NA if not available. If dealing with small/vulnerable populations consider identifiability issues.

PASSAGE_IF_EXPANDED - If the primary cell culture has been expanded, the number of times the cell culture has been re-plated and allowed to grow back to confluency or to some maximum density if using suspension cultures. NA if no expansion.

Primary Tissue

MOLECULE - (Controlled Vocabulary) The type of molecule that was extracted from the biological material. Include one of the following: total RNA, polyA RNA, cytoplasmic RNA, nuclear RNA, genomic DNA, protein, or other.

MOLECULE_ONTOLOGY_URI - (Ontology) links to molecule ontology information

SAMPLE_ONTOLOGY_URI - (Ontology) links to sample ontology information.

DISEASE_ONTOLOGY_URI - (Ontology) links to disease ontology information. If dealing with a rare disease consider identifiability issues.

DISEASE: Free form field for more specific disease information. If dealing with a rare disease consider identifiability issues.

BIOMATERIAL_PROVIDER - The name of the company, laboratory or person that provided the biological material.

BIOMATERIAL__TYPE: Primary Tissue

TISSUE__TYPE - The type of tissue.

TISSUE__DEPOT - Details about the anatomical location from which the primary tissue was collected.

COLLECTION__METHOD - The protocol for collecting the primary tissue.

DONOR__ID - An identifying designation for the donor that provided the primary tissue.

DONOR__AGE - The age of the donor that provided the primary tissue. NA if not available. If over 90 years enter as 90+. If entering a range of ages use the format “{age}-{age}”.

DONOR__AGE__UNIT - (Controlled Vocabulary) “year”, “month”, “week”, or “day”.

DONOR__LIFE__STAGE - (Controlled Vocabulary) “fetal”, “newborn”, “child”, “adult”, “unknown”, “embryonic”, “postnatal”

DONOR__HEALTH__STATUS - The health status of the donor that provided the primary tissue. NA if not available.

DONOR__SEX - (Controlled Vocabulary) “Male”, “Female”, “Unknown”, or “Mixed” for pooled samples.

DONOR__ETHNICITY - The ethnicity of the donor that provided the primary tissue. NA if not available. If dealing with small/vulnerable populations consider identifiability issues.

EXPERIMENTS

Chromatin Accessibility

EXPERIMENT__TYPE: Chromatin Accessibility

EXPERIMENT__ONTOLOGY__URI - (Ontology) links to experiment ontology information.

EXTRACTION__PROTOCOL - The protocol used to isolate the extract material.

DNASE__PROTOCOL - The protocol used for DNase treatment.

WGBS (NOTE: this is a new name to be used instead of Bisulfite-Seq)

EXPERIMENT__TYPE: DNA Methylation

EXTRACTION__PROTOCOL - The protocol used to isolate the extract material.

EXTRACTION_PROTOCOL_TYPE_OF_SONICATOR - The type of sonicator used for extraction.

EXTRACTION_PROTOCOL_SONICATION_CYCLES - The number of sonication cycles used for extraction.

DNA_PREPARATION_INITIAL_DNA_QNTY - The initial DNA quantity used in preparation.

DNA_PREPARATION_FRAGMENT_SIZE_RANGE - The DNA fragment size range used in preparation.

DNA_PREPARATION_ADAPTOR_SEQUENCE - The sequence of the adaptor used in preparation.

DNA_PREPARATION_ADAPTOR_LIGATION_PROTOCOL - The protocol used for adaptor ligation.

DNA_PREPARATION_POST-LIGATION_FRAGMENT_SIZE_SELECTION - The fragment size selection after adaptor ligation.

BISULFITE_CONVERSION_PROTOCOL - The bisulfite conversion protocol.

BISULFITE_CONVERSION_PERCENT - The bisulfite conversion percent and how it was determined.

LIBRARY_GENERATION_PCR_TEMPLATE_CONC - The PCR template concentration for library generation.

LIBRARY_GENERATION_PCR_POLYMERASE_TYPE - The PCR polymerase used for library generation

LIBRARY_GENERATION_PCR_THERMOCYCLING_PROGRAM - The thermocycling program used for library generation.

LIBRARY_GENERATION_PCR_NUMBER_CYCLES - The number of PCR cycles used for library generation.

LIBRARY_GENERATION_PCR_F_PRIMER_SEQUENCE - The sequence of the PCR forward primer used for library generation.

LIBRARY_GENERATION_PCR_R_PRIMER_SEQUENCE - The sequence of the PCR reverse primer used for library generation.

LIBRARY_GENERATION_PCR_PRIMER_CONC - The concentration of the PCR primers used for library generation.

LIBRARY_GENERATION_PCR_PRODUCT_ISOLATION_PROTOCOL - The protocol for isolating PCR products used for library generation.

MeDIP-Seq

EXPERIMENT__TYPE: DNA Methylation

EXPERIMENT__ONTOLOGY__URI - links to experiment ontology information.

EXTRACTION__PROTOCOL - The protocol used to isolate the extract material.

EXTRACTION__PROTOCOL__TYPE__OF__SONICATOR - The type of sonicator used for extraction.

EXTRACTION__PROTOCOL__SONICATION__CYCLES - The number of sonication cycles used for extraction.

MeDIP__PROTOCOL - The MeDIP protocol used.

MeDIP__PROTOCOL__DNA__AMOUNT - The amount of DNA used in the MeDIP protocol.

MeDIP__PROTOCOL__BEAD__TYPE - The type of bead used in the MeDIP protocol.

MeDIP__PROTOCOL__BEAD__AMOUNT - The amount of beads used in the MeDIP protocol.

MeDIP__PROTOCOL__ANTIBODY__AMOUNT - The amount of antibody used in the MeDIP protocol.

MeDIP__ANTIBODY - The specific antibody used in the MeDIP protocol.

MeDIP__ANTIBODY__PROVIDER - The name of the company, laboratory or person that provided the antibody.

MeDIP__ANTIBODY__CATALOG - The catalog from which the antibody was purchased.

MeDIP__ANTIBODY__LOT - The lot identifier of the antibody.

MRE-Seq

EXPERIMENT__TYPE: DNA Methylation

EXPERIMENT__ONTOLOGY__URI - (Ontology) elements that contain links to experiment ontology information.

MRE__PROTOCOL - The MRE protocol.

MRE__PROTOCOL__CHROMATIN__AMOUNT - The amount of chromatin used in the MRE protocol.

MRE__PROTOCOL__RESTRICTION__ENZYME - The restriction enzyme(s) used in the MRE protocol.

MRE_PROTOCOL_SIZE_FRACTION - The size of the fragments selected in the MRE protocol.

Chip-Seq Input

EXPERIMENT_TYPE: ChIP-Seq Input

EXPERIMENT_ONTOLOGY_URI - (Ontology) elements that contain links to sample ontology information.

EXTRACTION_PROTOCOL - The protocol used to isolate the extract material.

EXTRACTION_PROTOCOL_TYPE_OF_SONICATOR - The type of sonicator used for extraction.

EXTRACTION_PROTOCOL_SONICATION_CYCLES - The number of sonication cycles used for extraction.

CHIP_PROTOCOL: Input

CHIP_PROTOCOL_CHROMATIN_AMOUNT- The amount of chromatin used in the ChIP protocol.

Chip-Seq

EXPERIMENT_TYPE: ‘Histone H3K4me1’, ‘Histone H3K4me3’, ‘Histone H3K9me3’, ‘Histone H3K9ac’, ‘Histone H3K27me3’, ‘Histone H3K36me3’, etc.

EXPERIMENT_ONTOLOGY_URI - (Ontology) links to experiment ontology information.

EXTRACTION_PROTOCOL - The protocol used to isolate the extract material.

EXTRACTION_PROTOCOL_TYPE_OF_SONICATOR - The type of sonicator used for extraction.

EXTRACTION_PROTOCOL_SONICATION_CYCLES - The number of sonication cycles used for extraction.

CHIP_PROTOCOL - The ChIP protocol used.

CHIP_PROTOCOL_CHROMATIN_AMOUNT - The amount of chromatin used in the ChIP protocol.

CHIP_PROTOCOL_BEAD_TYPE - The type of bead used in the ChIP protocol.

CHIP_PROTOCOL_BEAD_AMOUNT - The amount of beads used in the ChIP protocol.

CHIP_PROTOCOL_ANTIBODY_AMOUNT - The amount of antibody used in the ChIP protocol.

CHIP_ANTIBODY - The specific antibody used in the ChIP protocol.

CHIP_ANTIBODY_PROVIDER - The name of the company, laboratory or person that provided the antibody.

CHIP_ANTIBODY_CATALOG - The catalog from which the antibody was purchased.

CHIP_ANTIBODY_LOT - The lot identifier of the antibody.

CHIP_PROTOCOL_CROSSLINK_TIME - The timespan in which the chromatin is crosslinked

LIBRARY_GENERATION_FRAGMENT_SIZE_RANGE - The fragment size range of the preparation.

mRNA-seq

EXPERIMENT_TYPE: mRNA-Seq

EXPERIMENT_ONTOLOGY_URI - (Ontology) links to experiment ontology information.

EXTRACTION_PROTOCOL - The protocol used to isolate the extract material.

EXTRACTION_PROTOCOL_MRNA_ENRICHMENT - The mRNA enrichment method used in the extraction protocol.

EXTRACTION_PROTOCOL_FRAGMENTATION - The fragmentation method used in the extraction protocol.

MRNA_PREPARATION_FRAGMENT_SIZE_RANGE - The mRNA fragment size range of the preparation.

RNA_PREPARATION_5'_RNA_ADAPTER_SEQUENCE - The sequence of the 5' RNA adapter used in preparation.

RNA_PREPARATION_3'_RNA_ADAPTER_SEQUENCE - The sequence of the 3' RNA adapter used in preparation.

RNA_PREPARATION_REVERSE_TRANSCRIPTION_PRIMER_SEQUENCE - The sequence of the primer for reverse transcription used in preparation.

RNA_PREPARATION_5'_DEPHOSPHORYLATION - The protocol for 5' dephosphorylation used in preparation.

RNA_PREPARATION_5'_PHOSPHORYLATION - The protocol for 5' phosphorylation used in preparation.

RNA_PREPARATION_3'_RNA_ADAPTER_LIGATION_PROTOCOL - The protocol for 3' adapter ligation used in preparation.

RNA_PREPARATION_5'_RNA_ADAPTER_LIGATION_PROTOCOL - The protocol for 5' adapter ligation used in preparation.

LIBRARY_GENERATION_PCR_TEMPLATE_CONC - The PCR template concentration for library generation.

LIBRARY_GENERATION_PCR_POLYMERASE_TYPE - The PCR polymerase used for library generation

LIBRARY_GENERATION_PCR_THERMOCYCLING_PROGRAM - The thermocycling program used for library generation.

LIBRARY_GENERATION_PCR_NUMBER_CYCLES - The number of PCR cycles used for library generation.

LIBRARY_GENERATION_PCR_F_PRIMER_SEQUENCE - The sequence of the PCR forward primer used for library generation.

LIBRARY_GENERATION_PCR_R_PRIMER_SEQUENCE - The sequence of the PCR reverse primer used for library generation.

LIBRARY_GENERATION_PCR_PRIMER_CONC - The concentration of the PCR primers used for library generation.

LIBRARY_GENERATION_PCR_PRODUCT_ISOLATION_PROTOCOL - The protocol for isolating PCR products used for library generation.

TEMPLATE_TYPE - mRNA or cDNA - The type of template.

AMPLIFIED - True or False - Is the sample amplified?

PREPARATION_INITIAL_MRNA_QNTY -The initial mRNA quantity used in preparation.

PREPARATION_REVERSE_TRANSCRIPTION_PROTOCOL - The protocol for reverse transcription used in preparation.

PREPARATION_PCR_NUMBER_CYCLES - The number of PCR cycles used to amplify.

LIBRARY_GENERATION_PROTOCOL - The protocol used to generate the library.

LIBRARY_GENERATION_FRAGMENTATION - The fragmentation method used in the library protocol.

LIBRARY_GENERATION_FRAGMENT_SIZE_RANGE - The fragment size range of the preparation.

LIBRARY_GENERATION_3'_ADAPTER_SEQUENCE - The sequence of the 3' adapter used for library generation.

LIBRARY_GENERATION_5'_ADAPTER_SEQUENCE - The sequence of the 5' adapter used for library generation.

total-RNA-seq

EXPERIMENT_TYPE: total-RNA-Seq

EXPERIMENT_ONTOLOGY_URI - (Ontology) links to experiment ontology information.

EXTRACTION_PROTOCOL - The protocol used to isolate the extract material.

EXTRACTION_PROTOCOL_MRNA_ENRICHMENT - The mRNA enrichment method used in the extraction protocol.

EXTRACTION_PROTOCOL_FRAGMENTATION - The fragmentation method used in the extraction protocol.

MRNA_PREPARATION_FRAGMENT_SIZE_RANGE - The mRNA fragment size range of the preparation.

RNA_PREPARATION_5'_RNA_ADAPTER_SEQUENCE - The sequence of the 5' RNA adapter used in preparation.

RNA_PREPARATION_3'_RNA_ADAPTER_SEQUENCE - The sequence of the 3' RNA adapter used in preparation.

RNA_PREPARATION_REVERSE_TRANSCRIPTION_PRIMER_SEQUENCE - The sequence of the primer for reverse transcription used in preparation.

RNA_PREPARATION_5'_DEPHOSPHORYLATION - The protocol for 5' dephosphorylation used in preparation.

RNA_PREPARATION_5'_PHOSPHORYLATION - The protocol for 5' phosphorylation used in preparation.

RNA_PREPARATION_3'_RNA_ADAPTER_LIGATION_PROTOCOL - The protocol for 3' adapter ligation used in preparation.

RNA_PREPARATION_5'_RNA_ADAPTER_LIGATION_PROTOCOL - The protocol for 5' adapter ligation used in preparation.

LIBRARY_GENERATION_PCR_TEMPLATE_CONC - The PCR template concentration for library generation.

LIBRARY_GENERATION_PCR_POLYMERASE_TYPE - The PCR polymerase used for library generation

LIBRARY_GENERATION_PCR_THERMOCYCLING_PROGRAM - The thermocycling program used for library generation.

LIBRARY_GENERATION_PCR_NUMBER_CYCLES - The number of PCR cycles used for library generation.

LIBRARY_GENERATION_PCR_F_PRIMER_SEQUENCE - The sequence of the PCR forward primer used for library generation.

LIBRARY_GENERATION_PCR_R_PRIMER_SEQUENCE - The sequence of the PCR reverse primer used for library generation.

LIBRARY_GENERATION_PCR_PRIMER_CONC - The concentration of the PCR primers used for library generation.

LIBRARY_GENERATION_PCR_PRODUCT_ISOLATION_PROTOCOL - The protocol for isolating PCR products used for library generation.

TEMPLATE_TYPE - mRNA or cDNA - The type of template.

AMPLIFIED - True or False - Is the sample amplified?

PREPARATION_INITIAL_MRNA_QNTY - The initial mRNA quantity used in preparation.

PREPARATION_REVERSE_TRANSCRIPTION_PROTOCOL - The protocol for reverse transcription used in preparation.

PREPARATION_PCR_NUMBER_CYCLES - The number of PCR cycles used to amplify.

LIBRARY_GENERATION_PROTOCOL - The protocol used to generate the library.

LIBRARY_GENERATION_FRAGMENTATION - The fragmentation method used in the library protocol.

LIBRARY_GENERATION_FRAGMENT_SIZE_RANGE - The fragment size range of the preparation.

LIBRARY_GENERATION_3'_ADAPTER_SEQUENCE - The sequence of the 3' adapter used for library generation.

LIBRARY_GENERATION_5'_ADAPTER_SEQUENCE - The sequence of the 5' adapter used for library generation.

smRNA-Seq

EXPERIMENT_TYPE - smRNA-Seq

EXPERIMENT_ONTOLOGY_URI - (Ontology) links to experiment ontology information.

EXTRACTION_PROTOCOL - The protocol used to isolate the extract material.

EXTRACTION_PROTOCOL_SMRNA_ENRICHMENT - The smRNA enrichment method used in the extraction protocol.

SMRNA_PREPARATION_INITIAL_SMRNA_QNTY - The initial smRNA quantity used in preparation.

RNA_PREPARATION_5'_RNA_ADAPTER_SEQUENCE - The sequence of the 5' RNA adapter used in preparation.

RNA_PREPARATION_3'_RNA_ADAPTER_SEQUENCE - The sequence of the 3' RNA adapter used in preparation.

RNA_PREPARATION_REVERSE_TRANSCRIPTION_PRIMER_SEQUENCE
- The sequence of the primer for reverse transcription used in preparation.

RNA_PREPARATION_3'_RNA_ADAPTER_LIGATION_PROTOCOL -
The protocol for 3' adapter ligation used in preparation.

RNA_PREPARATION_5'_RNA_ADAPTER_LIGATION_PROTOCOL -
The protocol for 5' adapter ligation used in preparation.

RNA_PREPARATION_REVERSE_TRANSCRIPTION_PROTOCOL
- The protocol for reverse transcription used in preparation.

LIBRARY_GENERATION_PCR_TEMPLATE_CONC - The PCR template concentration for library generation.

LIBRARY_GENERATION_PCR_POLYMERASE_TYPE - The PCR polymerase used for library generation

LIBRARY_GENERATION_PCR_THERMOCYCLING_PROGRAM
- The thermocycling program used for library generation.

LIBRARY_GENERATION_PCR_NUMBER_CYCLES - The number of PCR cycles used for library generation.

LIBRARY_GENERATION_PCR_F_PRIMER_SEQUENCE - The sequence of the PCR forward primer used for library generation.

LIBRARY_GENERATION_PCR_R_PRIMER_SEQUENCE -
The sequence of the PCR reverse primer used for library generation.

LIBRARY_GENERATION_PCR_PRIMER_CONC - The concentration of the PCR primers used for library generation.

LIBRARY_GENERATION_PCR_PRODUCT_ISOLATION_PROTOCOL
- The protocol for isolating PCR products used for library generation.

Level 1 Data

SRA: ANALYSIS_TYPE - REFERENCE_ALIGNMENT

DATA_ANALYSIS_LEVEL - 1

EXPERIMENT_TYPE - The type of experiment (Chromatin Accessibility, Bisulfite-Seq, MeDIP-Seq, MRE-Seq, ChIP-Seq, mRNA-Seq, smRNA-Seq).

EXPERIMENT_ONTOLOGY_URI - (Ontology) links to experiment ontology information.

GENOME_ASSEMBLY - The genome assembly to which the reads are mapped.

SOFTWARE - The name of the software used for mapping.

SOFTWARE_VERSION - The version of the software used for mapping.

SOFTWARE_COMMAND_LINE - The command line used to run the software.

ANALYSIS_PROTOCOL - Description of how the analysis was performed.

MAXIMUM_ALIGNMENT_LENGTH - The maximum read alignment length supported by the software. If the software aligns the entire read use "Read Length".

MISMATCHES_ALLOWED - The number of mismatches allowed in an alignment.

ALIGNMENTS_ALLOWED - The number of locations to which a read is allowed to align.

TREATMENT_OF_MULTIPLE_ALIGNMENTS - How reads aligning to multiple locations are treated.

TREATMENT_OF_IDENTICAL_ALIGNMENTS_OF_MULTIPLE_READS - How multiple reads aligning to the same location are treated. This applies to clonal duplicate removal.

ALIGNMENT_POSTPROCESSING - Any postprocessing applied to the alignments.

NUMBER_OF_MAPPED_READS - The number of mapped reads.

Quality Control

Quality control related analysis attributes. These are dependent on the type of experiment.

Level 2 Data

SRA: ANALYSIS_TYPE - ABUNDANCE_MEASUREMENT

DATA_ANALYSIS_LEVEL: 2

EXPERIMENT_TYPE - The type of experiment (Chromatin Accessibility, Bisulfite-Seq, MeDIP-Seq, MRE-Seq, ChIP-Seq, mRNA-Seq, smRNA-Seq).

EXPERIMENT_ONTOLOGY_URI - (Ontology) links to experiment ontology information.

GENOME_ASSEMBLY - The genome assembly to which the reads are mapped.

SOFTWARE - The name of the software used for determining signal (read density).

SOFTWARE_VERSION - The version of the software used for determining signal (read density).

SOFTWARE_COMMAND_LINE - The command line used to run the software.

ANALYSIS_PROTOCOL - Description of how the analysis was performed.

READ_EXTENSION - If read mappings are extended before determining signal (read density), the length to which the read is extended in bp. NA if not applicable.

GENOMIC_WINDOW - The bp size of the window in which the signal (read density) is calculated.

TREATMENT_OF_REGIONS_PRONE_TO_MULTIPLE_ALIGNMENTS
- Any treatment of regions, such as repeats, which are prone to multiple alignments. NA if not applicable.

NUMBER_OF_MAPPED_READS - The number of mapped reads.

Quality Control

Quality control related analysis attributes. These are dependent on the type of experiment.