HIGHER ABSTRACTION

Assembly checked by assembly DRC and LVS
GDS (interposer + chiplets) + assembly-DRC and assembly-LVS reports

IHP Open ADK
the meta-layer: it governs how chiplets are assembled, not how they are designed

Adapters: the bridge
interposer adapter · where chiplet attachment lands
interconnect adapter · method pitch and spacing
the only place a fab layer number is named

Shared registries + schemas
`rule_params` · interconnect · boundary manifest · layers
one source of truth for every stage
a JSON schema validates each one

Assembly verification has two axes, and neither subsumes the other

Geometric axis: assembly DRC
`SHIPPED IN THIS RELEASE`
`ASM.*` **placement**
overlap · spacing · area · attachment
`IXN.*` **interconnect**
spacing · pitch · cross-method

Connectivity axis: assembly LVS
`SHIPPED IN THIS RELEASE`
reference · the declared nets
die pins and the nets that join them
implementation · the placed layouts
pad landings plus interposer routing

Both axes check one placed assembly, described by its `.chiplet` placement

Chiplet PDKs
several technologies
dies from their own PDK flows

Interposer PDK
IHP IntM4TM2
layers, DRC rules

Interconnect PDK
Cu-pillar / micro-bump
methods (pitch, spacing)

Ordinary PDKs: the ADK sits one layer above these and never touches their fab rules

A PDK is to a single chip what the ADK is to a multi-chip assembly.