

Chapter 2. (Part 2)

Divide-and-Conquer

경북대학교 배준현 교수

[\(joonion@knu.ac.kr\)](mailto:joonion@knu.ac.kr)



2.1 Binary Search

2.2 Mergesort

2.3 The Divide-and-Conquer Approach

2.4 Quicksort (Partition Exchange Sort)

Appendix B. Solving Recurrence Equations

2.5 Strassen's Matrix Multiplication Algorithm

2.6 Arithmetic with Large Integers

2.7 Determining Thresholds

2.8 When Not to Use Divide-and-Conquer



2.5 Strassen's Matrix Multiplication Algorithm

■ *Matrix Multiplication* Algorithm

- Recall that Algorithm 1.4 multiplies two matrices
 - strictly according *to the definition of matrix multiplication*.
 - time complexity: $T(n) = n^3 \in \Theta(n^3)$.
- Is it possible to design an efficient algorithm
 - whose time complexity is better than $\Theta(n^3)$?
- Strassen published an algorithm (in 1969)
 - whose *time complexity* is *better than cubic*
 - in terms of both *multiplication* and *additions/subtractions*.



2.5 Strassen's Matrix Multiplication Algorithm

(Normal)

8 multiplications

4 additions

$$\begin{bmatrix} c_{11} & c_{12} \\ c_{21} & c_{22} \end{bmatrix} = \begin{bmatrix} a_{11} & a_{12} \\ a_{21} & a_{22} \end{bmatrix} \times \begin{bmatrix} b_{11} & b_{12} \\ b_{21} & b_{22} \end{bmatrix}$$

$$m_1 = (a_{11} + a_{22})(b_{11} + b_{22})$$

$$m_2 = (a_{21} + a_{22})b_{11}$$

$$m_3 = a_{11}(b_{12} - b_{22})$$

$$m_4 = a_{22}(b_{21} - b_{11})$$

$$m_5 = (a_{11} + a_{12})b_{22}$$

$$m_6 = (a_{21} - a_{11})(b_{11} + b_{12})$$

$$m_7 = (a_{12} - a_{22})(b_{21} + b_{22})$$

$$C = \begin{bmatrix} m_1 + m_4 - m_5 + m_7 & m_3 + m_5 \\ m_2 + m_4 & m_1 + m_3 - m_2 + m_6 \end{bmatrix}$$

(Strassen's)

7 multiplications

18 additions/subtractions



2.5 Strassen's Matrix Multiplication Algorithm

- Pertaining the Strassen's Method to *Larger Matrices*
 - that are each *divided* into *four submatrices*.

$$\begin{bmatrix} C_{11} & C_{12} \\ C_{21} & C_{22} \end{bmatrix} = \begin{bmatrix} A_{11} & A_{12} \\ A_{21} & A_{22} \end{bmatrix} \times \begin{bmatrix} B_{11} & B_{12} \\ B_{21} & B_{22} \end{bmatrix}$$

$$M_1 = (A_{11} + A_{22})(B_{11} + B_{22})$$

$$M_2 = (A_{21} + A_{22})B_{11}$$

...

$$C = \begin{bmatrix} M_1 + M_4 - M_5 + M_7 & M_3 + M_5 \\ M_2 + M_4 & M_1 + M_3 - M_2 + M_6 \end{bmatrix}$$



2.5 Strassen's Matrix Multiplication Algorithm

$$\begin{bmatrix} C_{11} & C_{12} \\ C_{21} & C_{22} \end{bmatrix} = \begin{bmatrix} 1 & 2 & 3 & 4 \\ 5 & 6 & 7 & 8 \\ 9 & 1 & 2 & 3 \\ 4 & 5 & 6 & 7 \end{bmatrix} \times \begin{bmatrix} 8 & 9 & 1 & 2 \\ 3 & 4 & 5 & 6 \\ 7 & 8 & 9 & 1 \\ 2 & 3 & 4 & 5 \end{bmatrix}$$

$$M_1 = (A_{11} + A_{22})(B_{11} + B_{22}) = \begin{bmatrix} 3 & 5 \\ 11 & 13 \end{bmatrix} \times \begin{bmatrix} 17 & 10 \\ 7 & 9 \end{bmatrix} = \begin{bmatrix} 86 & 75 \\ 278 & 227 \end{bmatrix}$$

$$M_2 = (A_{21} + A_{22})B_{11} = \begin{bmatrix} 11 & 4 \\ 10 & 12 \end{bmatrix} \times \begin{bmatrix} 8 & 9 \\ 3 & 4 \end{bmatrix} = \begin{bmatrix} 104 & 115 \\ 128 & 138 \end{bmatrix}$$

$$M_3 =$$

$$M_4 =$$

$$M_5 =$$

$$M_6 =$$

$$M_7 =$$

$$C = \begin{bmatrix} C_{11} & C_{12} \\ C_{21} & C_{22} \end{bmatrix} = \begin{bmatrix} 43 & 53 & 54 & 37 \\ 123 & 149 & 130 & 93 \\ 95 & 110 & 44 & 41 \\ 103 & 125 & 111 & 79 \end{bmatrix}$$



2.5 Strassen's Matrix Multiplication Algorithm

7

ALGORITHM 2.8: Strassen (*pseudo-code*)

```
void strassen(int n, matrix_t A, matrix_t B, matrix_t& C) {  
    if (n <= threshold) {  
        compute C = A * B using the standard algorithm;  
    }  
    else {  
        partition A into four submatrices A11, A12, A21, A22;  
        partition B into four submatrices B11, B12, B21, B22;  
        compute C = A * B using Strassen's method;  
        // example recursive call:  
        // strassen(n/2, A11 + A22, B11 + B22, M1);  
    }  
}
```



2.5 Strassen's Matrix Multiplication Algorithm

```
typedef vector<vector<int>> matrix_t;
const int threshold = 1;

void print_matrix(int n, matrix_t M);
void resize(int n, matrix_t& mat);
void madd(int n, matrix_t A, matrix_t B, matrix_t& C);
void msub(int n, matrix_t A, matrix_t B, matrix_t& C);
void mmult(int n, matrix_t A, matrix_t B, matrix_t &C);
void partition(int m, matrix_t M,
               matrix_t& M11, matrix_t& M12, matrix_t& M21, matrix_t& M22);
void combine(int m, matrix_t& M,
            matrix_t M11, matrix_t M12, matrix_t M21, matrix_t M22);
void strassen(int n, matrix_t A, matrix_t B, matrix_t &C);
```




2.5 Strassen's Matrix Multiplication Algorithm

9

```
matrix_t A11, A12, A21, A22;  
matrix_t B11, B12, B21, B22;  
matrix_t C11, C12, C21, C22;  
matrix_t M1, M2, M3, M4, M5, M6, M7;  
matrix_t L, R;  
  
int m = n / 2;  
resize(m, A11); resize(m, A12); resize(m, A21); resize(m, A22);  
resize(m, B11); resize(m, B12); resize(m, B21); resize(m, B22);  
resize(m, C11); resize(m, C12); resize(m, C21); resize(m, C22);  
resize(m, C11); resize(m, C12); resize(m, C21); resize(m, C22);  
resize(m, M1); resize(m, M2); resize(m, M3); resize(m, M4); resize(m, M5);  
resize(m, M6); resize(m, M7); resize(m, L); resize(m, R);
```



2.5 Strassen's Matrix Multiplication Algorithm

```
void partition(int m, matrix_t M,
               matrix_t& M11, matrix_t& M12, matrix_t& M21, matrix_t& M22) {
    for (int i = 0; i < m; i++)
        for (int j = 0; j < m; j++) {
            M11[i][j] = M[i][j];
            M12[i][j] = M[i][j + m];
            M21[i][j] = M[i + m][j];
            M22[i][j] = M[i + m][j + m];
        }
}
```



2.5 Strassen's Matrix Multiplication Algorithm

```
void strassen(int n, matrix_t A, matrix_t B, matrix_t &C) {  
    if (n <= threshold) {  
        mmult(n, A, B, C);  
    }  
    else {  
        // Define local variables here.  
  
        partition(m, A, A11, A12, A21, A22);  
        partition(m, B, B11, B12, B21, B22);  
  
        // Implement Strassen's Method Here.  
  
        combine(m, C, C11, C12, C21, C22);  
    }  
}
```



2.5 Strassen's Matrix Multiplication Algorithm

$$m_1 = (a_{11} + a_{22})(b_{11} + b_{22})$$

```
madd(m, A11, A22, L);  
madd(m, B11, B22, R);  
strassen(m, L, R, M1);
```

$$m_2 = (a_{21} + a_{22})b_{11}$$

```
madd(m, A21, A22, L);  
strassen(m, L, B11, M2);
```

$$m_3 = a_{11}(b_{12} - b_{22})$$

```
msub(m, B12, B22, R);  
strassen(m, A11, R, M3);
```

$$m_4 = a_{22}(b_{21} - b_{11})$$

```
msub(m, B21, B11, R);  
strassen(m, A22, R, M4);
```

$$m_5 = (a_{11} + a_{12})b_{22}$$

```
madd(m, A11, A12, L);  
strassen(m, L, B22, M5);
```

... ..



2.5 Strassen's Matrix Multiplication Algorithm

$$C_{11} = m_1 + m_4 - m_5 + m_7$$

```
madd(m, M1, M4, L);  
msub(m, L, M5, R);  
madd(m, R, M7, C11);
```

$$C_{12} = m_3 + m_5$$

```
madd(m, M3, M5, C12);
```

$$C_{21} = m_2 + m_4$$

```
madd(m, M2, M4, C21);
```

$$C_{22} = m_1 + m_3 - m_2 + m_6$$

```
madd(m, M1, M3, L);  
msub(m, L, M2, R);  
madd(m, R, M6, C22);
```

$$C = \begin{bmatrix} C_{11} & C_{12} \\ C_{21} & C_{22} \end{bmatrix}$$

```
combine(m, C, C11, C12, C21, C22);
```



2.5 Strassen's Matrix Multiplication Algorithm

- Time Complexity of *Strassen's (multiplications)*
 - Basic Operation: one *elementary multiplication*.
 - Input Size: n , the *number of rows and columns* in the matrices.
 - For simplicity,
 - we keep dividing until $n = 1$ (*threshold* = 1).
 - Then, we can establish the recurrence:
 - $T(n) = 7T(n/2)$, for $n > 1$, n is a power of 2.
 - $T(1) = 1$.



2.5 Strassen's Matrix Multiplication Algorithm

- Time Complexity of *Strassen's (multiplications)*
 - The recurrence is solved in Example B.2 in Appendix B:
 - $T(n) = n^{\lg 7} \approx n^{2.81} \in \Theta(n^{2.81})$.

$$\left. \begin{aligned}
 T(n) &= 7 \times T\left(\frac{n}{2}\right) \\
 &= 7^2 \times T\left(\frac{n}{2^2}\right) \\
 &= \dots \\
 &= 7^k \times T\left(\frac{n}{2^k}\right) \\
 &= 7^k \times T(1) \\
 &= 7^k
 \end{aligned} \right\} k = \lg n$$

$$\begin{aligned}
 T(n) &= 7^{\lg n} \\
 &= n^{\lg 7} \\
 &\approx n^{2.81} \\
 T(n) &\in \Theta(n^{2.81})
 \end{aligned}$$

- We can also apply the *Master Theorem*.



2.5 Strassen's Matrix Multiplication Algorithm

- Time Complexity of *Strassen's* (*additions/subtractions*)
 - Basic Operation: one *elementary addition* or *subtraction*.
 - Input Size: n , the *number of rows and columns* in the matrices.
 - Again, for simplicity, we keep dividing until $n = 1$.
 - Then, we can establish the recurrence:
 - $T(n) = 7T\left(\frac{n}{2}\right) + 18\left(\frac{n}{2}\right)^2$, for $n > 1$, n is a power of 2. elements들의 덧셈, 곱셈
 - $T(1) = 0$.
 - The recurrence is solved in Example B.20 in Appendix B:
 - $T(n) = 6n^{\lg 7} - 6n^2 \in \Theta(n^{2.81})$
 - We can also apply the Master Theorem.



2.5 Strassen's Matrix Multiplication Algorithm

- Comparing two algorithms:

	Standard Algorithm	Strassen's Algorithm
Multiplications	n^3	$n^{2.81}$
Additions/Subtractions	$n^3 - n^2$	$6n^{2.81} - 6n^2$

- What happen if n is **not** a **power of 2**?
 - Simply, *fill 0s to the matrices* to make the dimension a power of 2.



2.5 Strassen's Matrix Multiplication Algorithm

- *How fast* can we *multiply two matrices*?
 - There are some variants of Strassen's algorithm.
 - Some of them has more efficient complexity, to say, $\Theta(n^{2.38})$.
 - It is *provable* that the complexity requires *at least* $\Omega(n^2)$.
 - This is a *lower bound* of matrix multiplication *problem*.
 - Is it *possible* to design an efficient algorithm with $\Theta(n^2)$?
 - *No one* has ever *developed* an algorithm for it.
 - *No one* has ever *proved* that it is *not possible*.

$$T(n) = 11 * T(n/2) + O(1)$$



2.6 Arithmetic with Large Integers

- Representation of **Large Integers**
 - Suppose that we need to do arithmetic operations on large integers
 - whose size *exceeds* the computer's *hardware capability*.
 - A straightforward way to represent a large integer is
 - to use an array of integers,
 - in which *each array slot* stores only *one digit*.

5	4	3	1	2	7
<i>S[5]</i>	<i>S[4]</i>	<i>S[3]</i>	<i>S[2]</i>	<i>S[1]</i>	<i>S[0]</i>



2.6 Arithmetic with Large Integers

- Data Type and Linear-Time Operations:
 - To represent both *positive* and *negative* integers
 - we need *only* reserve the *high-order* array slot for the *sign*.
 - 0 for positive, 1 for negative.
 - For convenience,
 - we assume that all the large integers are positive.

```
typedef vector<int> LargeInteger;  
const int threshold = 1;
```



2.6 Arithmetic with Large Integers

- Data Type and Linear-Time Operations:
 - Write linear-time algorithms for
 - *addition* & subtraction.
 - *powered* by exponent: $u \times 10^m$
 - divided by exponent: $u \text{ divide } 10^m$
 - returns the *quotient* in integer division.
 - remainder by exponent: $u \text{ rem } 10^m$
 - return the *remainder*.



2.6 Arithmetic with Large Integers

```
void roundup_carry(LargeInteger& v) {  
    int carry = 0;  
    for (int i = 0; i < v.size(); i++) {  
        v[i] += carry;  
        carry = v[i] / 10;  
        v[i] = v[i] % 10;  
    }  
    if (carry != 0)  
        v.push_back(carry);  
}
```



2.6 Arithmetic with Large Integers

```
void ladd(LargeInteger a, LargeInteger b, LargeInteger& c) {  
    c.resize(max(a.size(), b.size()));  
    fill(c.begin(), c.end(), 0);  
    for (int i = 0; i < c.size(); i++) {  
        if (i < a.size()) c[i] += a[i];  
        if (i < b.size()) c[i] += b[i];  
    }  
    roundup_carry(c);  
}
```




2.6 Arithmetic with Large Integers

- *Multiplication of Large Integers:*
 - A simple algorithm for multiplying large integers
 - has a *quadratic* time complexity: $\Theta(n^2)$.

$$\begin{array}{r}
 \begin{array}{r}
 \times \\
 \hline
 \end{array}
 \begin{array}{rrrr}
 & & 1 & 2 & 3 \\
 & & & 4 & 5 \\
 \hline
 & & 5 & 10 & 15 \\
 \\
 \begin{array}{r}
 + \\
 \hline
 \end{array}
 \begin{array}{rrrr}
 & 4 & 8 & 12 & \\
 \hline
 & 4 & 13 & 22 & 15 \\
 \\
 & 5 & 5 & 3 & 5
 \end{array}
 \end{array}$$



2.6 Arithmetic with Large Integers

```
void lmult(LargeInteger a, LargeInteger b, LargeInteger& c) {  
    c.resize(a.size() + b.size() - 1);  
    fill(c.begin(), c.end(), 0);  
    for (int i = 0; i < a.size(); i++)  
        for (int j = 0; j < b.size(); j++)  
            c[i + j] += a[i] * b[j];  
    roundup_carry(c);  
}
```



2.6 Arithmetic with Large Integers

- Operations with Exponents: Power, Divide, and Remainder

$$u = 567,832, m = 3$$

$$u \times 10^m$$

$$u = 567832000$$

$$u \text{ divide } 10^m$$

$$u = 567\cancel{832}$$

$$u \text{ rem } 10^m$$

$$u = \cancel{567}832$$



2.6 Arithmetic with Large Integers

```
void pow_by_exp(LargeInteger u, int m, LargeInteger &v) {  
    if (u.size() == 0)  
        v.resize(0);  
    else {  
        v.resize(u.size() + m);  
        fill(v.begin(), v.end(), 0);  
        copy(u.begin(), u.end(), v.begin() + m);  
    }  
}
```



2.6 Arithmetic with Large Integers

```
void rem_by_exp(LargeInteger u, int m, LargeInteger &v) {  
    if (u.size() == 0)  
        v.resize(0);  
    else {  
        // Note that u.size() can be smaller than m.  
        int k = m < u.size() ? m : u.size();  
        v.resize(k);  
        copy(u.begin(), u.begin() + k, v.begin());  
        remove_leading_zeros(v);  
    }  
}
```



2.6 Arithmetic with Large Integers

- Designing an *Efficient* Multiplication Algorithm:
 - based on the *Divide-and-Conquer* approach
 - to *split* an *n-digit* integer into *two* integers of *approximately n/2* digits.

$$\begin{array}{ccccc} 567,832 & = & 567 \times 10^3 & + & 832 \\ \text{6 digits} & & \text{3 digits} & & \text{3 digits} \end{array}$$

$$\begin{array}{ccccc} 9,423,723 & = & 9,423 \times 10^3 & + & 723 \\ \text{7 digits} & & \text{4 digits} & & \text{3 digits} \end{array}$$

$$\begin{array}{ccccc} u & = & x \times 10^m & + & y \\ n \text{ digits} & & \lfloor n/2 \rfloor \text{ digits} & & \lfloor n/2 \rfloor \text{ digits} \end{array}$$

The exponent m of 10 is given by $m = \lfloor n/2 \rfloor$



2.6 Arithmetic with Large Integers

$$u = x \times 10^m + y$$

$$v = w \times 10^m + z$$

$$\begin{aligned} uv &= (x \times 10^m + y)(w \times 10^m + z) \\ &= xw \times 10^{2m} + (xz + wy) \times 10^m + yz \end{aligned}$$

$$\begin{aligned} 567,832 \times 9,423,723 &= (567 \times 10^3 + 832)(9,423 \times 10^3 + 723) \\ &= 567 \times 9,423 \times 10^6 + (567 \times 723 + 9,423 \times 832) \times 10^3 + 832 \times 723 \\ &= 5,351,091,478,536 \end{aligned}$$



2.6 Arithmetic with Large Integers

ALGORITHM 2.9: Large Integer Multiplication

```
large_integer prod(large_integer u, large_integer v)
{
    large_integer x, y, w, z;
    int n, m;

    n = maximum(number of digits in u, number of digits in v);
    if (u == 0 || v == 0)
        return 0;
    else if (n <= threshold)
        return u × v obtained in the usual way;
    else {
        m = n / 2;
        x = u divide 10m; y = u rem 10m;
        w = v divide 10m; z = v rem 10m;
        return prod(x, w) × 102m + (prod(x, z) + prod(w, y)) × 10m + prod(y, z);
    }
}
```




2.6 Arithmetic with Large Integers

```

void prod(LargeInteger u, LargeInteger v, LargeInteger &r) {
    LargeInteger x, y, w, z;
    LargeInteger t1, t2, t3, t4, t5, t6, t7, t8;
    int n = max(u.size(), v.size());
    if (u.size() == 0 || v.size() == 0)
        r.resize(0);
    else if (n <= threshold)
        lmult(u, v, r);
    else {
        int m = n / 2;
        div_by_exp(u, m, x); rem_by_exp(u, m, y);
        div_by_exp(v, m, w); rem_by_exp(v, m, z);
        // t2 <- prod(x,w) * 10^(2*m)
        prod(x, w, t1); pow_by_exp(t1, 2 * m, t2);
        // t6 <- (prod(x,z)+prod(w,y)) * 10^m
        prod(x, z, t3); prod(w, y, t4); ladd(t3, t4, t5); pow_by_exp(t5, m, t6);
        // r <- t2 + t6 + prod(y, z)
        prod(y, z, t7); ladd(t2, t6, t8); ladd(t8, t7, r);
    }
}

```



2.6 Arithmetic with Large Integers

- Time Complexity of *Algorithm 2.9 (Worst-Case)*
 - Basic Operation: the *manipulation of one decimal digit* in a large integer
 - when *adding*, *subtracting*, or doing *pow*, *div*, and *rem* operations.
 - Input Size: n , the *number of digits* in each of the two integers.
 - The worst-case occurs when
 - both integers have *no digits equal to 0*,
 - because the recursion ends if and only if *threshold* is passed.
 - For simplicity, suppose that n is a power of 2.



2.6 Arithmetic with Large Integers

- Time Complexity of Algorithm 2.9 (Worst-Case)
 - The operations of addition, subtraction, power, divide, and remainder
 - have linear time-complexities in terms of n , because $m = n/2$.
 - We can establish the recurrence equation:
 - $W(n) = 4W(n/2) + cn$, for $n > s$, n is a power of 2.
 - where c is a positive constant.
 - $W(s) = 0$, for $n \leq s$.
 - Therefore,
 - $W(n) \in \Theta(n^{\log_2 4}) = \Theta(n^2)$. (Example B.25 in Appendix B)
 - We can apply the *Master Theorem*.



2.6 Arithmetic with Large Integers

- What's happen?
 - Algorithm 2.9 is still quadratic: $\Theta(n^2)$
 - The algorithm does *four multiplications*
 - on integers with *half* as many digits as the original integers.
 - We should *reduce the number of these multiplications.*
 - to obtain an algorithm that is *better than quadratic.*



2.6 Arithmetic with Large Integers

$$u = x \times 10^m + y$$

$$v = w \times 10^m + z$$

$$uv = xw \times 10^{2m} + (xz + wy) \times 10^m + yz$$

$$r = (x + y)(w + z) = xw + (xz + yw) + yz$$

$$(xz + yw) = r - (xw + yz)$$

$$uv = xw \times 10^{2m} + \left(\overset{r}{(x + y)(w + z)} - (xw + yz) \right) \times 10^m + yz$$

three multiplications



2.6 Arithmetic with Large Integers

ALGORITHM 2.10: Large Integer Multiplication 2

```

large_integer prod2(large_integer u, large_integer v)
{
    large_integer x, y, w, z, r, p, q;
    int n, m;
    n = maximum(number of digits in u, number of digits in v);
    if (u == 0 || v == 0)
        return 0;
    else if (n <= threshold)
        return u × v obtained in the usual way;
    else {
        m = n / 2;
        x = u divide 10m; y = u rem 10m;
        w = v divide 10m; z = v rem 10m;
        r = prod2(x + y, w + z);
        p = prod2(x, w);
        q = prod2(y, z);
        return p × 102m + (r - p - q) × 10m + q;
    }
}

```



2.6 Arithmetic with Large Integers

```
typedef long long largeint;
const int threshold = 1;

largeint karatsuba(largeint u, largeint v) {
    largeint x, y, w, z, p, q, r;
    int n = max(digits(u), digits(v));
    if (u == 0 || v == 0)
        return 0;
    else if (n <= threshold)
        return u * v;
    else {
        int m = n / 2;
        x = div_by_exp(u, m); y = rem_by_exp(u, m);
        w = div_by_exp(v, m); z = rem_by_exp(v, m);
        r = karatsuba(x + y, w + z);
        p = karatsuba(x, w);
        q = karatsuba(y, z);
        return pow_by_exp(p, 2*m) + pow_by_exp(r-p-q, m) + q;
    }
}
```



2.6 Arithmetic with Large Integers

- Time Complexity of **Algorithm 2.10** (Worst-Case)
 - If n is a power of 2, then x , y , w , and z all have $n/2$ digits.
 - $\frac{n}{2} \leq \text{digits in } x + y \leq \frac{n}{2} + 1$.
 - $\frac{n}{2} \leq \text{digits in } w + z \leq \frac{n}{2} + 1$.

n	x	y	$x + y$	Number of Digits in $x + y$
4	10	10	20	$2 = n/2$
4	99	99	198	$3 = n/2 + 1$
8	1000	1000	2000	$4 = n/2$
8	9999	9999	19,998	$5 = n/2 + 1$



2.6 Arithmetic with Large Integers

- Time Complexity of Algorithm 2.10 (Worst-Case)
 - The input sizes for the given function calls:
 - $prod2(x + y, w + z)$: $\frac{n}{2} \leq \text{input size} \leq \frac{n}{2} + 1$.
 - $prod2(x, w)$: input size = $\frac{n}{2}$
 - $prod2(y, z)$: input size = $\frac{n}{2}$
 - Therefore, $W(n)$ satisfies
 - $3W(\frac{n}{2}) + cn \leq W(n) \leq 3W(\frac{n}{2} + 1) + cn$, for $n > s$, n is a power of 2.
 - $W(s) = 0$, for $n \leq s$.



2.6 Arithmetic with Large Integers

- Time Complexity of Algorithm 2.10 (Worst-Case)
 - Owing to the left inequality in the recurrence and the Master Theorem:
 - $W(n) \in \Omega(n^{\log_2 3})$.
 - We can also show that
 - $W(n) \in O(n^{\log_2 3})$. (Refer to the textbook)
 - Therefore, combining these two results,
 - $W(n) \in \Theta(n^{\log_2 3})$.



2.7 Determining Thresholds

- The Effect of *Threshold* Value
 - Recursion requires
 - a fair amount of overhead in terms of computer time.
 - Consider the problem of sorting *only eight keys*:
 - Which is the faster in terms of the *execution* time?
 - Recursive Mergesort: $\Theta(n \lg n)$ or Exchange Sort: $\Theta(n^2)$.
 - We need to develop a method that *determines for what value of n*
 - it is at least as fast to call an alternative algorithm as it is
 - to divide the instance further.



2.7 Determining Thresholds

- Finding an *Optimal Threshold*:
 - An *optimal threshold value* of n is
 - an instance size such that for any smaller instance
 - it would be at least as fast to call the other algorithm as
 - it would be to divide the instance further,
 - and for any larger instance size
 - it would be faster to divide the instance again.



2.7 Determining Thresholds

- Example: Mergesort & Exchange Sort
 - Recurrence of Mergesort (worst-case)
 - $W(n) = 2W(n/2) + 32n \mu s$, $W(1) = 0 \mu s$
 - Mergesort takes $W(n) = 32n \lg n \mu s$, where Exchange Sort takes $\frac{n(n-1)}{2} \mu s$.
 - Solving the inequality $\frac{n(n-1)}{2} < 32n \lg n$, the solution is $n < 591$.
 - Is it optimal to call Exchange Sort when $n < 591$
 - and to call Mergesort otherwise?
 - Note that this analysis is *incorrect*.
 - It only tells us that if we use Mergesort and keep dividing until $n = 1$,
 - then Exchange Sort is better for $n < 591$.



2.7 Determining Thresholds

- The *Optimal Threshold* for Mergesort & Exchange Sort:
 - Suppose we modify Mergesort so that
 - Exchange Sort is called when $n \leq t$ for some threshold t .
 - $$W(n) = \begin{cases} \frac{n(n-1)}{2} \mu s, & \text{for } n \leq t \\ W\left(\left\lfloor \frac{n}{2} \right\rfloor\right) + W\left(\left\lceil \frac{n}{2} \right\rceil\right) + 32n \mu s, & \text{for } n > t \end{cases}$$
 - $W\left(\left\lfloor \frac{t}{2} \right\rfloor\right) + W\left(\left\lceil \frac{t}{2} \right\rceil\right) + 32t = \frac{t(t-1)}{2}$
 - Solving this equation, we can obtain $t = 128$. (Refer to the textbook)
 - Therefore, we have
 - an *optimal threshold* value of 128.



2.8 When not to Use Divide-and-Conquer

- Avoid the Divide-and-Conquer in the following two cases:
 1. An instance of size n is divided into
 - *two or more instances* each *almost size n* .
 - It leads to an *exponential-time* algorithm.
 2. An instance of size n is divided into
 - *almost n instances* of *size n/c* , where c is a constant.
 - It leads to $n^{\Theta(\lg n)}$ algorithm.
- Consider the following problems:
 - n th Fibonacci Term: Algorithm 1.6 (Recursive), 1.7 (Iterative)
 - Towers of Hanoi: *intrinsically* exponential algorithm.



Exercises

- The **n-th Fibonacci Number** using Matrix Exponentiation
 - Can we calculate the n-th Fibonacci Number by *using matrix exponentiation*?
 - Use the following relation:

- $$\begin{bmatrix} F_n \\ F_{n-1} \end{bmatrix} = \begin{bmatrix} 1 & 1 \\ 1 & 0 \end{bmatrix} \times \begin{bmatrix} F_{n-1} \\ F_{n-2} \end{bmatrix}$$

- $$\begin{bmatrix} F_n \\ F_{n-1} \end{bmatrix} = \begin{bmatrix} 1 & 1 \\ 1 & 0 \end{bmatrix}^n \times \begin{bmatrix} 1 \\ 0 \end{bmatrix}$$

Any Questions?

