"कुलांगः १८६६" "AB_AFFIRMED 1996"

IS: 10553 (Part 4) - 1983

Indian Standard

REQUIREMENTS FOR CHLORINATION EQUIPMENT

PART 4 GRAVITY FEED TYPE GASEOUS CHLORINATORS

(First Reprint OCTOBER 1995)

UDC 628.162.84.06

© Copyright 1983

BUREAU OF INDIAN STANDARDS MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

Indian Standard

REQUIREMENTS FOR CHLORINATION EQUIPMENT

PART 4 GRAVITY FEED TYPE GASEOUS CHLORINATORS

Public Health Engineering Equipment Sectional Committee, BDC 40

Chairman

Representing

DR B. B. SUNDARESAN

National Environmental Engineering Research Institute (CSIR), Nagpur

Members

SHRI R. PARAMASIVAM (Alternate to

Dr B. B. Sundaresan)

ADVISER (PHE)
DR S. R. SUKLA (Alternate)

SHRI S. V. BOPARDIKAR

SHRI R. C. P. CHAUDHARY

CHIEF ENGINEER

Ministry of Works & Housing, New Delhi

Directorate General of Technical Development.

New Delhi Engineers India Limited, New Delhi

Department of Health, Government of West Bengal,

Calcutta

SHRI T. N. CHATTERJEE (Alternate)

CHIEF ENGINEER (WATER) SHRI JAI NARAIN (Alternate)

SHRI D. K. CHOUDHURY

SHRI D. R. MALL (Alternate)

SHRI S. K. DASGUPTA

Municipal Corporation of Delhi, Delhi

Geo-Miller & Co, Calcutta

Calcutta Metropolitan Development Authority. Calcutta

SHRI S. J. DUTTA (Alternate) DEPUTY MUNICIPAL COMMISSIONER Municipal Corporation of Greater Bombay. Bombay

HYDRAULIC ENGINEER (Alternate I) CHIEF ENGINEER (SEWERAGE) (Alternate II)

SHRI B. R. N. GUPTA

Engineer-in-Chief's Branch, Army Headquarters, New Delhi

SHRI K. V. KRISHNAMURTHY (Alternate)

Local Administration & Social Welfare (F) SHRI S. P. JAMES Department, Trivandrum

Tamil Nadu Water Supply & Drainage Board, Madras SHRI R. KRISHNASWAMY SHRI S. A. JAGDESAN (Alternate)

(Continued on page 2)

© Copyright 1983

BUREAU OF INDIAN STANDARDS

This publication is protected under the Indian Copyright Act (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

(Continued from page 1)

	man de	~=
Me	,,,,,,,	er s

Representing

SHRI M. Y. MADAN
SHRI C. E. S. RAO (Alternate)

SHRI S. R. MAJUMDAR SHRI A. R. MIR The Hindustan Construction Co Ltd, Bombay

Paterson Engineering Co (India) Ltd, Calcutta Public Health Engineering Department, Government of Jammu & Kashmir, Srinagar

SHRI G. M. KANTH (Alternate)
SHRI S. S. NAIK

SHRI D. R. KENKRE (Alternate)

Hydraulic & General Engineers Pvt Ltd, Bombay

SHRI R. NATARAJAN H

SHRI B. M. RAHUL (Alternate)
SHRI M. M. PATEL I

REPRESENTATIVE
REPRESENTATIVE

Hindustan Dor.-Oliver Ltd, Bombay

Indian Water Works Association, Bombay Public Health Engineering Department, Government of Punjab, Chandigarh

Public Health Engineering Department, Government of Haryana, Chandigarh

M. P. State Prevention and Control of Water

SHRI K. K. GANDHI (Alternate)
PROF S. SUBBA RAO
All India Institute of Hygiene & Public Health.

SHRI A. V. RAO (Alternate)

SHRI A. V. RAO (Alternate)
SHRI T. P. SHARMA

DR G. K. KHARE (Alternate) SHRI S. S. SRIVASTAVA

SHRI S. A. SWAMY SHRI P. S. TENDOLKAR

SHRI C. L. SASTRI (Alternate)
SHRI M. G. VAIDYA

Shri V. Vardarajan

Uttar Pradesh Jal Nigam, Lucknow The Institution of Engineers (India), Calcutta Candy Filters (India) Ltd, Bombay

Pollution Board, Bhopal

Public Health Engineering Department, Government of Madhya Pradesh, Bhopal

Madras Metropolitan Water Supply and Sewerage Board, Madras

SHRI S. DAIVAMANI (Alternate)
SHRI G. RAMAN,
Director (Civ Engg)

Director General, ISI (Ex-officio Member)

Secretary

Calcutta

SHRI A. K. AVASTHY
Assistant Director (Civ Engg), ISI

Water Treatment Equipment Subcommittee, BDC 40:1

Convener

SHRI JAI NARAIN

Indian Water Works Association, Bombay

Members

SHRI K. R. SAHU (Alternate to

Shri Jai Narain) Shri R. R. Bagri

Clear Water Ltd, New Delhi

(Continued on page 10)


Indian Standard

REQUIREMENTS FOR CHLORINATION EQUIPMENT

PART 4 GRAVITY FEED TYPE GASEOUS CHLORINATORS

0. FOREWORD

- **6.1** This Indian Standard was adopted by the Indian Standards Institution on 23 June 1983, after the draft finalized by the Public Health Engineering Equipment Sectional Committee had been approved by the Civil Engineering Division Council.
- 0.2 Gravity feed type gas apparatus by means of which chlorine is added as solution in a minor flow of water, is suitable for cases where it is required to apply chlorine to water flowing through an open channel or to water entering or leaving a sump or well under atmospheric pressure. The apparatus consists of a control panel with provision for connecting the requisite number of chlorine cylinders and a solutionizer or absorption tower with a suitable connection to the point of application.
- 0.3 The apparatus is made in different sizes with chlorine supply up to 15 kg/h.
- **0.4** The line diagram for gravity feed type gaseous chlorinators is given in Fig. 1.
- 0.5 This standard is being published in 5 parts. Other parts in the series are given below:
 - Part 1 General guidelines for chlorination plants including handling, storage and safety of chlorine cylinders and drums.
 - Part 2 Vacuum feed type chlorinators.
 - Part 3 Pressure feed chlorinators.
 - Part 5 Bleaching powder solution dosing equipment.
- 0.6 In the formulation of this standard due weightage has been given to international co-ordination among the standards and practices prevailing in different countries in addition to relating it to the practices in the field in this country.



- I. CHLORINE CYLINDER
 2. AUXILIARY CYLINDER VALVE
- CHLORINE FILTER
- 4. SHUT OFF VALVE

- 7. SHOT OFF VALVE
 5. HIGH PRESSURE GAUGE
 6. LOW PRESSURE GAUGE
 7A. REDUCING VALVE
 7B. REDUCING VALVE IN CASE
 CAPACITY MORE THAN 500 g/h

- 8. REGULATING VALVE 9. ORIFICE

- 10. MANOMETER TUBE
 11. MOISTURE SEAL
 12. WATER AT CONSTANT HEAD
 13. SOLUTION TOWER
 14. CHLORINE SOLUTION LINE
 15. FILTERED WATER CHANNEL

- 16. DIFFUSER

0.7 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS:2-1960*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

1.1 This standard lays down the requirements for materials of construction, types and performance requirements of gravity feed type gaseous chlorinators.

2. TYPES

- 2.1 The chlorinators shall be of the following three types:
 - a) Wall mounted,
 - b) Pedestal mounted, and
 - c) Cylinder mounted.

3. MATERIAL

- 3.1 Control Panel The control panel should be of fibre glass moist chlorine/acid resistance plastics or mild steel with 3 coats of epoxy.
- 3.2 Solutionizer Tower The solutionizer tower should either be made of glazed porcelain, polyvinyl chloride or of rubber lined mild steel plates. The solutionizer tower is generally of a type as shown in Fig. 2 and shall be packed with pebbles of varying sizes. The pebbles shall be of round water worn type. Pumicestone or porcelain or moist chlorine/acid resistant plastic rashing rings may be used as packing materials in place of pebbles.
 - 3.2.1 The water shall be fed in the solutionizer tower at a constant head.
- 3.2.2 The outlet from the solutionizer tower to the water channel shall be designed for maximum flow.
- 3.3 Tubes The tubes used in chlorination plant shall be either phosphorus deoxidised non-arsenical copper conforming to IS:191 (Part 8)-1980† or phosphorus deoxidises arsenical copper conforming to IS:191 (Part 10)-1980‡ or carbon steel conforming to IS:1030-1974§.

^{*}Rules for rounding off numerical values (revised).

[†]Specification for copper: Part 8 Phosphorized copper (DHP) (third revision).

Specification for copper: Part 10 Phosphorus deoxidized arsenical copper (DPA) (third revision).

[§]Specification for carbon steel castings for general engineering purposes (second revision),

Note - Minimum wall thickness for tubes is given below:

	Outside diameter mm	Min Wall Thickness mm	Tolerances mm
For copper tubes	$ \begin{cases} $	0·8 1·0 1·2	$\begin{array}{l} \pm \ 0.08 \\ \pm \ 0.10 \\ \pm \ 0.10 \end{array}$
carbon steel	above 20 up to 30 above 30 up to 40	2·5 3·0 3·2	$\begin{array}{l} \pm \ 0.10 \\ \pm \ 0.15 \\ \pm \ 0.20 \end{array}$




Fig. 2 Solutioniser Tower

- 3.3.1 For carrying moist chlorine, the pipelines should be made of silver, platinum, corrosion resistance alloy steel conforming to grade 19 of IS:3444-1978*, HDEP conforming to IS:4984-1978† or UPVC conforming to IS:4985-1981‡.
- 3.4 Nuts Bolts and Brackets Nuts bolts and brackets shall be of chromium plated brass or cadmium plated mild steel.
- 3.5 Chlorine gas filter media shall be of glass wool.
- 3.6 Other Components The ancillary components incorporate a chlorine gas, filter, pressure reducing valves, manometer or rate of discharge meter, regulating valve, moisture trap, chlorine pressure gauge and a stop valve. All metallic parts coming in contact with gas should be made of silver-plated brass or nickel. Stainless steel may also be used for components coming in contact with dry chlorine gas only. Non-metallic materials used in construction of various components shall be of glass, ebonite and moist chlorine/acid resistant plastic.

4. PERFORMANCE REQUIREMENTS

- 4.1 Concentration of chlorine gas in solution after the solutionizer tower shall be at least 90 percent of the saturation value of chlorine gas at that temperature.
- **4.1.1** Solubility of chlorine gas in water in the solutionzer tower depends on the surrounding temperature. For guidance Table 1 may be adopted for designing solutionizer tower.

5. CHLORINATION REQUIREMENT

5.1 Rate of withdrawal of chlorine from container depends upon the size of container and the surrounding temperature. For guidance Table 2 may be followed.

Note — If the discharge rate of chlorine is exceeded beyond the recommended rate, the liquid chlorine may freeze.

5.2 When the gas discharge rate from a single container may not meet the requirements, two or more containers may be connected to a manifold so as to discharge simultaneously. It is advisable not to couple more than four containers to a manifold.

^{*}Specification for corrosion resistant alloy steel and nickel based castings for genera applications (first revision).

[†]Specification for high density polyethylene pipes for potable water supplies sewage and industrial effluent (second revision).

[‡]Specification for unplasticised PVC pipes for potable water supplies (first revision).

TABLE 1 SOLUBILITY OF CHLORINE IN WATER AT DIFFERENT TEMPERATURES

(Clause 4.1.1)

Temperature °C	Percentage Solubility (wt/wt)	
10	0.997 2	
11	0.965 4	
12	0.934 6	
13	0.905 0	
. 14	0.876 8	
15	0.849 5	
16	0.823 2	
17	0 ·79 7 9	
18	0.773 8	
19	0.751 0	
20	0.729 3	
21	0-710 0	
22	0.691 8	
23	0.673 9	
24	0.657 2	
25	0.641 3	
26	0.625 9	
27	0.611 2	
28	0.597 5	
29	0.584 7	
30	0-572 3	
35	0.510 4	
40	0.459 0	

- 5.2.1 When discharging through a manifold, all the containers shall be at the same temperature, particularly when connecting a new cylinder to the manifold.
- 5.2.2 When more than 3 cylinders are used, the connections should be arranged in groups so that one complete group may be changed at a time.

6. INSTALLATION AND SAFETY

•6.1 For installation of the chlorination plants including handling, storage and safety of chlorine cylinders and drums IS: 10553 (Part 1)-1983* may be followed.

^{*}Requirements of chlorination equipment: Part 1 Guidelines for chlorination plants including handling, storage and safety of chlorine cylinders and drums.

TABLE 2 RATE OF WITHDRAWAL OF CHLORINE FROM CONTAINER

(Clause 5.1)

Temperature °C	kg of Chlorine Discharge per Day		
	Cylinders		Tonne Container
	45 kg	67 kg	
4	2.72	4.08	45
10	6.35	9.5	110
15	10-75	16·10	130
20	14-50	21.54	245
Above 27	18:70	28.12	315

(Continued from page 2)

Members

Representing

DR A. G. BHOLE

Visvesvaraya Regional College of Engineering, Nagpur

DR S. M. DHABADGAONKAR (Alternate)
SHRI D. K. CHOUDHURY Geo-Mill

Geo-Miller & Co Pvt Ltd, Calcutta

SHRI A. K. MAZUMDAR (Alternate)

SHRI M. M. DATTA

Central Public Health and Environmental Engi-

neering Organization, New Delhi

SHRI I. RADHAKRISHNAN (Alternate)

SHRI K. GOVINDAN NAIR

Public Health Engineering Department, Trivandrum University of Roorkee, Roorkee

DR R. P. MATHUR SHRI N. W. MIRCHANDANI

Municipal Corporation of Greater Bombay

SHRI K. MOHAN

Engineers India Ltd, New Delhi

SHRI S. S. NAIK SHRI D. R. KENKRE (Alternate)

Hydraulic & General Engineers (P) Ltd. Bombay

SHRI R. NATARAJAN SHRI B. M. RAHUL (Alternate)

Hindustan Dorr-Oliver Ltd, Bombay

SHRI R. PARAMASIVAM

National Environmental Engineering Research Institute (CSIR), Nagpur

SHRI N. G. SWARNAKAR (Alternate) SHRI N. RAMACHANDRAN

Ion Exchange (India) Ltd, Bombay

SHRI A. M. JOSHI (Alternate)

The Hindustan Construction Co Ltd, Bombay

SHRI C. E. S. RAO SHRI C. L. SASTRI

Candy Filters (India) Ltd, Bombay

SHRI V. SATYAMURTHI

EIMCO — KCP Ltd, Madras

SHRI T. SUBRAHMANYAM (Alternate) SHRI S. S. SRIVASTAVA

Uttar Pradesh Jal Nigam, Lucknow

PROF S. SUBBA RAO

All India Institute of Hygiene & Public Health, Calcutta

SHRI K. J. NATH (Alternate)

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI-110002

Teleiphones: 331 01 31 331 13 75

Telegrams : Manaksanstha

(Common to all Offices)

Regional Offices:					
Central: Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002					
,	331 13 75				
*Eastern: 1/14 CIT Scheme VII M, V.I.P. Road, Maniktola, CALCUTTA 7000543					
Northern : SCO 335-336, Sector 34-A, CHANDIGARH 160 022					
Southern : C.I.T. Campus, IV Cross Road, MADRAS 600113	235 23 15				
†Western : Manakalaya, E9 MIDC, Marol, Andheri (East), BOMBAY 400093	832 92 95				
Branch Offices:					
'Pushpak', Nurmohamed Shaikh Marg, Khanpur, AHMADABAD 380001	30 13 48				
‡Peenya Industrial Area, 1st Stage, Bangalore-Tumkur Road,, BANGALORE 550058	39 49 55				
Gangotri Complex, 5th Floor, Bhadbhada Road, T.T. Nagar, BHOPAL 462003	55 40 21				
Plot No. 21 Satyanagar, BHUBANESHWAR 751007	40 36 27				
Kalaikathir Building, 6/48 Avanashi Road, COIMBATORE 641037	21 01 41				
Plot No. 43, Sector 16 A, Mathura Road, FARIDABAD 121001	8-28 88 01				
Savitri Complex, 116 G.T. Road, GHAZIABAD 201001	8-71 19 96				
53/5 Ward No. 29, R.G. Barua Road, 5th By-lane, GUWAHATI 781003	54 11 37				
5-8-56C L.N. Gupta Marg, Nampally Station Road, HYDERABAD 500001	20 10 83				
R 14 Yudhister Marg, C Scheme, JAIPUR 302005	38 13 74				
117/418 B Sarvodaya Nagar, KANPUR 208005	21 68 76				
Seth Bhawan, 2nd Floor, Behind Leela Cinema, Naval Kishore Road, LUCKNOW 226001	23 89 23				
Patliputra Industrial Estate, PATNA 800013	26 23 05				
C/o Smt. Sunita Mirakhur	_				
66 D/C Annexe, Gandhi Nagar, JAMMU TAWI 180004					
T.C. No. 14/1421, University P.O., Palayam, THIRUVANANTHAPURAM 695034	6 21 17				
Inspection Offices (With Sale Point):					
Pushpanjali, Ist floor, 205-A, West High Court Road, Shankar Nagar Square, NAGPUR 440010	525171				
Institution of Engineers (India) Building 1332 Shivaji Nagar, PUNE 411005	32 36 35				
* Sales Office is at 5 Chowringhee Approach, P.O. Princep Street, CALCUTTA 700072	27 99 65				
†Sales Office is at Novelty Chambers, Grant Road, BOMBAY 400007	309 65 28				
‡Sales Office is at 'F' Block, Unity Building, Narasimharaja Square, BANGALORE 560002	22 39 71				