Indian Standard

METHODS FOR MEASUREMENT OF AIR POLLUTION PART XIX CHLORINE

Third Reprint May 1995

UDC 614.71:628.512:543.272.4

Copyright 1982

BUREAU OF INDIAN STANDARDS MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

Indian Standard

METHODS FOR MEASUREMENT OF AIR POLLUTION

PART XIX CHLORINE

Air Quality Sectional Committee, CDC 53

Chairman

Representing

DR B. B. SUNDARESAN

National Environmental Engineering Research

Members

SHRIP. K. YENNAWAR (Alternate to

Dr B. B. Sundaresan)

SHRI A. L. AGGARWAL

Dr J. S. Ahluwalia

Suri V. S. More (Alternate)

SHRI K. D. AMRE

SHRI H. M. SHAIKH (Alternate) SHELN, G. ASHAR

DR M. S. VAIDYA (Alternate)

Shri A. K. Basu

SHRI RANJIT Kumar SENGUPTA (Alternate)

DR NILAY CHAUDHURT

MEMBER SECRETARY (Alternate) SHRI DALJIT SINGH

DR R. K. DUTTA (Alternate)

SHRI J. M. DAVE DR P. J. DEORAS

DR S. B. CHAPHEKAR (Alternate I) SHRI T. N. MAHADEVAN (Alternate II)

SHRI M. V. DESAL SHRI B. SARAN (Alternate)

SHRI B. D. DESHMUKH

SHRI QAISAR AZEEZ (Alternate) SHRI N. B. ENGINEER

Institute (CSIR), Nagpur

National Institute of Occupational Health (ICMR),

Ahmadabad Indian Oil Corporation Ltd, Faridabad

National Organic Chemical Industries Ltd. Bombay

The Dharamsi Morarji Chemical Co Ltd, Bombay

Calcutta Metropolitan Development Authority Calcutta

Central Board for the Prevention and Control of Water Pollution, New Delhi

Hindustan Steel Ltd, Ranchi

Jawaharlal Nehru University, New Delhi

Society for Clean Environment, Bombay

Chemical Manufacturers Association. Indian Calcutta

Maharashtra Prevention of Water Pollution Board, Bombay

Cement Manufacturers' Association, Bombay

(Continued on page 2)

© Copyright 1982

BUREAU OF INDIAN STANDARDS

This publication is protected under the Indian Copyright Act (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

(Continued from page 1)

Members

Representing

SERI A. K. GUPTA SHRI B. P. PUNDIR (Alternate) Da V. S. GUPTA

Indian Institute of Petroleum (CSIR), Dehra Dun Fertilizer (Planning & Development) India Ltd, Sindri

SMT M. CHANDRA (Alternate) DR H. B. MATHUR DR N. K. MEHROTRA

Indian Institute of Technology, New Delhi Industrial Toxicology Research Centre (CSIR), Lucknow

DR P. N. VISHWANATHAN (Alternate I)

DR J. L. KAW (Alternate II)

SHRIR. S. MEHTA

Gujarat Water Pollution Control Board, Gandhinagar

Shri G. B. Soni (Alternate) Siri A. Moorherjea

S. F. India Ltd, Calcutta SHRI M. CHAUDHURY (Alternate)

Central Fuel Research Institute (CSIR), Dhanbad

DR P. N. MUKHERJEE DR R. U. Roy (Alternate)

DR V. PACHAIYAPAN DR B. PADMANABHAMURTHY SHRI A. R. PANICKER

SHRI Y. G. PATANKAR

SHRI J. D. PATEL (Alternate) SHRI J. R. PATWARDHAN

SHRI V. B. SHIRODKAR (Alternate)

Dr P. K. Ramachandran DR B. V. RAMANI (Alternate)

Meteorological Department, New Delhi Hindustan Insecticides Ltd, New Delhi Union Carbide India Ltd, Calcutta Municipal Corporation of Greater Bombay

The Fertilizer Association of India, New Delhi

Ministry of Defence, Delhi

SHRI V. RAMADURAI

India, Alkali Manufacturers' Association of Bombay

SHRI R. V. RAMANI (Alternate) DR S. S. RAMASWAMY

Directorate General, Factory Advice Service and Labour Institutes, Bombay

Central Mining Research Station (CSIR), Dhanbad

SHRI S. K. DANGWAL (Alternate) SHRI A. N. RAO

Directorate General of Technical Development, New Delhi

Coal India Ltd, Calcutta Bhabha Atomic Research Centre, Bombay

DR V. V. SHIRVAIKAR DR R. K. KAPOOR (Alternate)

SHRI S. B. SARKAR

DR J. K. SINHA SHRI A. K. BOSE (Alternate)

SHRI S. A. SUBRAMANIAN DR HARI BHAGWAN, Director (Chem)

Central Electricity Authority, New Delhi Director General, ISI (Ex-officio Member)

Secretary

SHRI A. K. BAHL Assistant Director (Chem), ISI

Indian Standard

METHODS FOR MEASUREMENT OF AIR POLLUTION PART XIX CHLORINE

O. FOREWORD

- **0.1** This Indian Standard (Part XIX) was adopted by the Indian Standards Institution on 20 May 1982, after the draft finalized by the Air Quality Sectional Committee had been approved by the Chemical Division Council.
- **0.2** Chlorine gas is primarily a respiratory irritant. It is so irritating that concentrations above 9 mg/m³ in air are readily detectable by a normal person
- **0.3** Devices and techniques for determining the concentration of pollutants in the atmosphere are important for the assessment of 'ambient air quality', establishing hazardous levels in the environment, ameliorative measures and appraisal of contamination from a process or source.
- **0.4** In the preparation of this standard, considerable assistance has been derived from the Publication No. 42215-01-70 'Tentative methods of analysis for free chlorine content of the atmosphere (methyl orange method) 'issued by the American Public Health Association.
- 0.5 In reporting the result of a test or analysis made in accordance with this standard, if the final value, observed or calculated, is to be rounded off, it shall be done in accordance with IS: 2-1960*.

1. SCOPE

1.1 This standard (Part XIX) describes the details of methyl orange method for measurement of free chlorine in air.

^{*}Rules for rounding off numerical values (revised).

2. METHYL ORANGE METHOD

2.1 Principle — The colour of methyl orange solution ceases to vary with acidity near a pH value of 3.0. The dye is quantitatively bleached by free chlorine, and the extent of bleaching may be determined colorimetrically. The optimum concentration range is 0.05-1.0 ppm in ambient air (145 μ g to 2.500 μ g per m³ at 25°C and 100 kPa).

Note — It is essential to maintain proper pH

- 2.2 Range and Sensitivity The procedure given is designed to cover the range of 5-100 μ g of free chlorine per 100 ml of sampling solution. For a 30 litre air sample, this corresponds to approximately 0.05-1.0 ppm in air which is the optimum range. Increasing the volume of air samples extends the range at the lower end, but only within limits, since 50 litre of chlorine free air produces the same effect as about 0.01 ppm of chlorine.
- 2.3 Limitations and Interferences Free bromine, which gives the same reaction, interferes in a positive direction. Manganese (III, IV) in concentrations of 0·1 ppm or above also interferes positively. Negative interference from sulphur dioxide is significant both in solution as well as gaseous state. Nitrites impart an off-colour orange to the methyl orange reagent. Nitrogen dioxide interferes positively, reacting as 20 percent chlorine. Sulphur dioxide interferes negatively, decreasing the chlorine by an amount equal to one third the sulphur dioxide concentration.
- **2.4 Precision and Accuracy** Error due to measurement by this procedure is known to be less than \pm 5 percent of the amount present.

2.5 Apparatus

- **2.5.1** Spectrophotometer suitable for measurement at 505 nm, preferably accommodating 5-cm cells.
- **2.5.2** Sampling Train according to IS: 5182 (Part V)-1975* using a large impinger with fritted disc [see Fig. 2 of IS: 5182 (Part V)-1975*] of porosity B (70 to 100 μ m maximum pore diameter).
- 2.6 Reagents Pure chemicals of analytical grade, unless otherwise specified, and distilled water (see IS: 1070-1977†) shall be employed in the test. These shall not contain any impurities that affect the results of analysis.
- 2.6.1 Methyl Orange Stock Solution 0.05 Percent Dissolve 0.500 g of methyl orange in water and dilute to one litre. This solution is stable indefinitely if freshly boiled and cooled distilled water is used.

^{*}Methods for measurement of air pollution: 1'art V Sampling of gaseous pollutants. †Specification for water for general laboratory use (second revision).

- 2.6.2 Methyl Orange Reagent 0.005 Percent Dilute 100 ml of stock solution to one litre with water. Prepare fresh for use.
- 2.6.3 Sampling Solution Dilute 6 ml of 0.005 percent methyl orange reagent to 100 ml with water and add three drops (0.15-0.20 ml) of 5 N hydrochloric acid. One drop of butanol may be added to induce foaming and increase collection efficiency. pH of the solution may be checked using a pH meter.
- 2.6.4 Acidified Water Add three drops (0.15-0.20 ml) of 5 N hydrochloric acid to 100 ml of water.
- **2.6.5** Potassium Dichromate Solution 0.100~0~N Dissolve 4.904~g anhydrous potassium dichromate primary standard grade in water and dilute to one litre.
- 2.6.6 Starch Indicator Solution Prepare a thin paste of 1 g of soluble starch in a few millilitres of water. Bring 200 ml of water to boil, remove from heat, and stir in the starch paste. Prepare fresh before use.
 - 2.6.7 Potassium Iodide reagent grade.
- 2.6.8 Sodium Thiosulphate Solution 0·1N Dissolve 25 g of Na₂S₂O₃. 5H₂O in freshly boiled and cooled water and dilute to one litre. Add 5 ml chloroform as preservative and allow to age for two weeks before standardizing. Take 80 ml water, 1 ml sulphuric acid and 1 g of potassium iodide in a titration flask and pipette into this, with constant stirring, 10 ml of 0·100 0 N potassium dichromate solution. Allow to stand in the dark for 6 minutes. Titrate with 0·1 N thiosulphate solution. Upon approaching the end-point (brown colour changing to yellowish green), add 1 ml of starch indicator solution and continue titrating to the end-point (blue to light green).

Normality of
$$Na_2S_2O_3 = \frac{1.000 \text{ 0}}{V}$$

where

V =volume in ml of sodium thiosulphate solution used.

- **2.6.9** Sodium Thiosulphate Solution 0.01~N- Dilute 100 ml of the aged and standardized 0.1~N sodium thiosulphate solution to 1 litre with freshly boiled and cooled distilled water. Add 5 ml chloroform as preservative and store in a glass-stoppered bottle. Standardize frequently with 0.010~0~N potassium dichromate.
- **2.6.10** Chlorine Solution, Approximately 10 ppm Prepare by serial dilution of household bleach (approximately 50 000 ppm), or by dilution of strong chlorine water made by the bubbling chlorine gas through cold

distilled water. The diluted solution should contain approximately 10 ppm of free (available) chlorine. Prepare one litre.

- 2.7 Procedure Assemble the sampling train. Add 100 ml of sampling solution to the impinger and draw a measured volume of air at a rate of 1-2 l/min for a period of time appropriate to the estimated chlorine concentration. Transfer the solution to a 100-ml volumetric flask and make to volume, if necessary, with acidified water. Measure absorbance at 505 nm in 5-cm cells against water as reference.
- 2.7.1 The volume of sampling solution, the concentration of methyl orange in the sampling solution, the amount of air sampled, the size of impinger and the length of photometer cell may be varied to suit the needs of the situation as long as proper attention is paid to the corresponding changes necessary in the calibration procedure.

2.8 Calibration

- 2.8.1 Prepare a series of six 100-ml volumetric flasks containing 6 ml of 0.005 percent methyl orange reagent, 75 ml water, and 3 drops (0.15-0.20 ml) of 5.0 N hydrochloric acid. Carefully and accurately pipette 0, 0.5, 1.0, 5.0 and 9.0 ml of chlorine solution (approximately 10 ppm) into the respective flasks; holding the pipette tip beneath the surface. Quickly mix and make to volume with acidified water.
- 2.8.2 Immediately standardize the 10 ppm chlorine solution by adding 400 ml of chlorine solution to a flask containing 1 g potassium iodide and 5 ml glacial acetic acid, and swirling to mix. Titrate with 0.01 N sodium thiosulphate until the iodine colour becomes a faint yellow. Add 1 ml of starch indicator solution and continue the titration to the end-point (blue to colourless). One millilitre of 0.010 0 N sodium thiosulphate is equivalent to 0.354 6 mg of free chlorine. Calculate the amounts of free chlorine added to each flask in 2.8.1.
- 2.8.3 Transfer the standards prepared in 2.8.1 to absorption cells and measure absorbance against micrograms of chlorine to draw the standard curve.
- 2.9 Calculations Calculate the chlorine concentration as follows:

Chlorine,
$$\mu g/m^3 = \frac{M}{V}$$

where

M = amount of chlorine found, μg ; and

V =volume of air sampled, m s .

For different temperatures and atmospheric pressures, proper correction for air volume should be made.

2.10 Effect on Storage — The colour of sampled solutions is stable for at least 24 h if protected from direct sunlight, although the presence of certain interferences (Fe III) may cause slow colour change.

(Continued from page 2)

Methods of Sampling and Analysis Subcommittee, CDC 53:2

Convener

Representing

Shri P. K. Yennawar

National Environmental Engineering Research Institute (CSIR), Nagpur

Members

DR G. H. PANDYA (Alternate to Shri P. K., Yennawar)

SHRI A. L. AGGARWAL

DR V. S. GUPTA

National Institute of Occupational Health (ICMR), Ahmadabad

SHRI C. B. RAIYANI (Alternate)
SMT J. M. DESHPANDE

Municipal Corporation of Greater Bombay
The Fertilizer (Planning & Development) India

Ltd, Sindri

SHRI S. B. SINHA (Alternate) SHRI S. C. KALE

Directorate General Factory Advice Service and Labour Institutes, Bømbay

SHRI S. K. DANGWAL (Alternate)
DR D. N. KELKAR
SHRI S. G. KRISHNAN
No

Bhabha Atomic Research Centre, Bombay National Organic Chemical Industries Ltd, Bombay Industrial Toxicology Research Centre (CSIR),

SHRI M. M. LAL Industrial Toxic Lucknow
DR P. N. VISHWANATHAN (Alternate I)

DR J. L. KAW (Alternate II) Shri S. K. Maira

S. F. India Ltd. Calcutta

SHRI S. P. MENE (Alternate)
SHRI S. D. MAKHIJANI

Central Board for the Prevention and Control of Water Pollution, New Delhi

DR H. S. MATHARU (Alternate)

SHRI C. V. RAMASWAMY Hindustan Petroleum Corporation Ltd, Bombay SHRI S. N. CONTRACTOR (Alternate)

DR N. C. SAHA Indian Oil Corporation Ltd, New Delbi SHRI C. V. RAMA MURTHY (Alternate)

SHRI G. V. RAMA MURTHY (Atternate)
DR J. K. Sinha Central Mining Research Station (CSIR),

Dhanbad

PROF R. D. SRIVASTAVA DR M. S. VAIDYA Indian Institute of Technology, Kanpur The Dharamsi Morarji Chemical Co Ltd, Bombay

SHRI H. B. SINGH (Alternate) SHRI S. K. VELINGKER

National Mineral Development Corporation Ltd, Hyderabad

SHRI G. S. R. K. RAO (Alternate)

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI-110002

Telelphones: 331 01 31

331 13 75

Telegrams: Manaksanstha

(Common to all Offices)

Regional Offices:	Telephone
Central: Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002	331 01 31
	331 13 75
*Eastern: 1/14 CIT Scheme VII M, V.I.P. Road, Maniktola, CALCUTTA 70005437 86 62	
Northern: SCO 335-336, Sector 34-A, CHANDIGARH 160 022	60 38 43
Southern : C.I.T. Campus, IV Cross Road, MADRAS 600113	235 23 15
†Western : Manakalaya, E9 MIDC, Marol, Andheri (East), BOMBAY 400093	832 92 95
Branch Offices:	
'Pushpak', Nurmohamed Shaikh Marg, Khanpur, AHMADABAD 380001	30 13 48
‡Peenya Industrial Area, 1st Stage, Bangalore-Tumkur Road,,	39 49 55
BANGALORE 550058	
Gangotri Complex, 5th Floor, Bhadbhada Road, T.T. Nagar, BHOPAL 462003	
Plot No. 21 Satyanagar, BHUBANESHWAR 751007	40 36 27
Kalaikathir Building, 6/48 Avanashi Road, COIMBATORE 641037	21 01 41
Plot No. 43, Sector 16 A, Mathura Road, FARIDABAD 121001	8-28 88 01
Savitri Complex, 116 G.T. Road, GHAZIABAD 201001	8-71 19 96
53/5 Ward No. 29, R.G. Barua Road, 5th By-lane, GUWAHATI 781003	54 11 37
5-8-56C L.N. Gupta Marg, Nampally Station Road, HYDERABAD 500001	20 10 83
R 14 Yudhister Marg, C Scheme, JAIPUR 302005	38 13 74
117/418 B Sarvodaya Nagar, KANPUR 208005	21 68 76
Seth Bḥawan, 2nd Floor, Behind Leela Cinema, Naval Kishore Road, LUCKNOW 226001	23 89 23
Patliputra Industrial Estate, PATNA 800013	26 23 05
C/o Smt. Sunita Mirakhur,,	_
66 D/C Annexe, Gandhi Nagar, JAMMU TAWI 180004	
T.C. No. 14/1421, University P.O., Palayam, THIRUVANANTHAPURAM 695034	6 21 17
Inspection Offices (With Sale Point):	
Pushpanjali, Ist floor, 205-A, West High Court Road, Shankar Nagar Square,	525171
NAGPUR 440010	
Institution of Engineers (India) Building 1332 Shivaji Nagar,	32 36 35
PUNE 411005	
* Sales Office is at 5 Chowringhee Approach, P.O. Princep Street, CALCUTTA 700072	27 99 65
†Sales Office is at Novelty Chambers, Grant Road, BOMBAY 400007	309 65 28
‡Sales Office is at 'F' Block, Unity Building, Narasimharaja Square,	22 39 71
BANGALORE 560002	