IS: 3861 - 1975 (Reaffirmed 1992)

Indian Standard METHOD OF MEASUREMENT OF PLINTH, CARPET AND RENTABLE AREAS OF BUILDINGS

(First Revision)

Fifth Reprint JANUARY 1998

UDC 69.003.12:69.022.92

© Copyright 1975

BUREAU OF INDIAN STANDARDS MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

Indian Standard

METHOD OF MEASUREMENT OF PLINTH. CARPET AND RENTABLE AREAS OF BUILDINGS

(First Revision)

Civil Works Measurement Sectional Committee, BDC 44

Chairman

SHRI V. R. VAISH

Representing

Bureau of Public Enterprises, Ministry of Finance,

Members

SHRI N. P. ACHARYYA

SHRI K. D. ARCOT SHRI T. V. SITARAM (Alternate

SHRI B. G. BALJEKAR

SHRI J. DURAI RAJ (Alternate)

SHRI P. L. BHASIN CHIEF ENGINEER (R & B)

SUPERINTENDING ENGINEER

(P & D) (Alternate)
Shri R. K. Choudhry SHRI I. P. PURI (Alternate)

SHRI V. B. DESAI DIRECTOR, IRI

DIRECTOR (RATES & COSTS) DEPUTY DIRECTOR (RATES & Costs) (Alternate)

SHRI P. K. DOCTOR

SHRI D. S. VIJAYENDRA (Alternate) EXECUTIVE ENGINEER (PLANNING & DESIGNS) NORTHERN

RAILWAY SHRI P. N. GADI

SHRI W. J. DAGAMA SHRI G. V. HINGORANI

New Delhi

The Commissioner for the Port of Calcutta, Calcutta Engineers India Ltd, New Delhi

Hindustan Steelworks Construction Ltd. Calcutta

Institution of Surveyors, New Delhi

Public Works Department, Government of Andhra Pradesh. Hyderabad

Bhakra Management Board, Nangal Township

Hindustan Construction Co Ltd, Bombay Irrigation Department, Government of Uttar Pradesh, Roorkee

Central Water Commission, New Delhi

Concrete Association of India, Bombay

Ministry of Railways

Institution of Engineers (India), Calcutta

Bombay Port Trust, Bombay Gammon India Ltd, Bombay

(Continued on page 2)

© Copyright 1975

BUREAU OF INDIAN STANDARDS

This publication is protected under the Indian Copyright Act (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

(Continued from page 1)

Members	Representing
Shri G. K. C. Iyengar Shri M. L. Jain	Heavy Engineering Corporation Ltd, Ranchi The National Industrial Development Corporation Ltd, New Delhi
SHRI S. L. KATHURIA SHRI V. SIVAGURU (Alternate)	Ministry of Shipping & Transport (Roads Wing)
SHRI H. K. KHOSLA	Irrigation Department, Government of Haryana, Chandigarh
SHRI S. K. KOGEKAR SHRI J. P. SHARMA (Alternate	National Buildings Organization, New Delhi
SHRI K. K. MADHOK SHRI DATTA S. MALIK	Builders Association of India, Bombay Indian Institute of Architects, Bombay
PROF M. K. GODBOLE (Alterna	ate)
SHRI R. S. MURTHY SHRI V. V. SASIDARAN (Alterno	Engineer-in-Chief's Branch, Ministry of Defence ate.)
SHRI C. B. PATEL SHRI B. C. PATEL (Alternate)	M. N. Dastur & Co Pvt Ltd, Calcutta
SHRI K. G. SALVI SHRI S. K. CHATTERJI (Alterna	Hindustan Housing Factory Ltd, New Delhi
DR R. B. SINGH	Banaras Hindu University, Varanasi
	Hindustan Steel Ltd, Ranchi Central Public Works Department, New Delhi
SURVEYOR OF WORKS (1) ATTACHED TO SSW (AVI)	
Works (I)	Central Public Works Department, New Delhi
SURVEYOR OF WORKS (I) ATTACHED TO SSW (I) (All	rernate)
TECHNICAL EXAMINER	Buildings & Communications Department, Government of Maharashtra, Bombay
SHRI D. AJITHA SIMHA, Director (Civ Engg), ISI	Director General, ISI (Ex-officio Member)

Secretary

SHRI K. M. MATHUR Deputy Director (Civ Engg), ISI

Indian Standard

METHOD OF MEASUREMENT OF PLINTH, CARPET AND RENTABLE AREAS OF BUILDINGS

(First Revision)

O. FOREWORD

- 0.1 This Indian Standard (First Revision) was adopted by the Indian Standards Institution on 19 July 1975, after the draft finalized by Civil Works Measurement Sectional Committee had been approved by the Civil Engineering Division Council.
- 0.2 At present different methods for calculating plinth/carpet areas of buildings are followed by various departments. This Indian Standard was formulated in 1966 to provide a basis for uniform method of measurement of such areas of buildings. This revision has been prepared to include rentable area of the building on the basis of recommendations of Central Public Works Department. Opportunity has also been taken to make the contents of the standard up-to-date and deleting provisions relating to cubical contents which is generally not followed.
- 0.3 For the purpose of deciding whether a particular requirement of this standard is complied with, final value, observed or calculated, expressing result of a measurement, shall be rounded off in accordance with IS: 2-1960*. The number of significant places retained in rounded off value should be same as that of the specified value in this standard.

1. SCOPE

1.1 This standard covers method of measurement of plinth, carpet and rentable areas of old and new buildings.

2. TERMINOLOGY

- 2.0 For the purpose of this standard the following definitions shall apply.
- 2.1 Plinth Area shall mean the built up covered area measured at the floor level of the basement or of any storey (see 4).

^{*}Rules for rounding off numerical values (revised).

- 2.2 Carpet Area shall mean the covered area of the usable rooms at any floor level (see 5).
- 2.3 Rentable Area shall mean the usable carpet area at any floor level (see 6).
- 2.4 Balcony A horizontal projection with a hand-rail, balustrade or a parapet, to serve as passage or sitting out place.
- 2.5 Mezzanine Floor An intermediate floor in between two main floors having minimum height of 2.2 m from the floor and having a proper access to it.

Note:—Where rules of the local bodies permit, intermediate floor of minimum 1.8 m clear height, these be also considered as mezzanine floor for the purpose of measurement.

- 2.6 Stair Cover (Mumty) It is a space having a roof over a staircase and its landing, built to enclose only the stairs for the purpose of providing protection from weather and not used for human habitation.
- 2.7 Loft An intermediate storage area in between two main floors.
- 2.8 Porch It is a cover surface supported on pillars or otherwise for the purpose of pedestrian or vehicular approach to a building.

3. GENERAL

- 3.1 Linear measurement shall be measured to nearest 01 m, and areas shall be worked out to the nearest 01 m².
- 3.2 The areas of each of the following categories shall be measured separately:
 - a) Basement,
 - b) Floor without cladding (stilted floor),
 - c) Floors including top floor which may be partly covered*,
 - d) Mezzanine floor, and
 - e) Garrage.

4. MEASUREMENT OF PLINTH AREA

- 4.1 For the purpose of plinth area, following shall be included for the categories mentioned in 3.2.
 - a) Area of the wall at the floor level excluding plinth offsets, if any; when the building consists of columns projecting beyond cladding,

^{*}Partly covered top floor in Delhi area is known as Barsati.

IS: 3861 - 1975

the plinth area shall be taken up to the external face of cladding (in case of corrugated sheet cladding outer edge of corrugation shall be considered);

- b) Internal shaft for sanitary installations and garbage chute, provided these do not exceed 2 m² in area, vertical duct for air-conditioning, lift well including landing;
- c) Stair cover (mumty);
- d) Machine room; and
- e) Porch.
- 4.2 The following shall not be included in the plinth area (see 2.1).
 - a) Additional floor for seating in assembly building/theatres and auditorium, etc;
 - b) Cantilevered porch;
 - c) Balcony;
 - d) Area of loft;
 - e) Internal sanitary shaft and garbage chute provided these are more than 2 m² in area;
 - f) Area of architectural band, cornice, etc;
 - g) Area of vertical sun breaker or box louver projecting out and other architectural feature, for example slabs projection for flower pot, etc;
 - h) Open platform;
 - j) Terrace at floor one;
 - k) Spiral staircase including landing; and
 - m) Towers, turrets, domes projecting above the terrace level at terrace*.

5. MEASUREMENT OF CARPET AREA

- 5.1 From the plinth area as worked out in 4, the area of the wall shall be deducted. Thickness of wall shall be inclusive of finishing and dado if the height of such finish is more than 1 m from floor finish.
 - 5.1.1 The following shall be included in the wall area:
 - a) Door and other openings in the wall;

^{*}This item may also be measured, if required

IS: 3861 - 1975

- b) Intermediate pillars, supports or any other such obstruction within the plinth area irrespective of their location;
- c) Pilaster along wall exceeding 300 cm² in area;
- d) Flues which are within the wall;
- e) Built in cupboard, almirah and shelf appearing within a height of 2.2 m from floor; and
- f) Fire place projecting beyond the face of the wall in living or bed room.
- 5.1.2 The following shall be excluded from the wall area:
 - a) Pilaster along wall not exceeding 300 cm⁹ in area, and
 - b) Chullah platform projecting beyond the face of the wall.
- 5.2 The carpet area shall be the plinth area worked out as in 5.1 excluding the area of the following portion:
 - a) Verandah,
 - b) Corridor and passage;
 - c) Entrance hall and porch;
 - d) Staircase and stair-cover (mumty) (see Note);
 - e) Shaft and machine room for lift;
 - f) Bathroom and lavatory;
 - g) Kitchen and pantry;
 - h) Store;
 - j) Canteen;
 - k) Air-conditioning duct and plant room; and
 - m) Shaft for sanitary piping.

Note—In a hall or basement areas of portion 1 m beyond last step shall be part of the staircase.

5.2.1 The carpet area of category mentioned in 3.2(b) and (e) are not to be accounted for plinth area.

6. MEASUREMENT OF RENTABLE AREA

6.1 Residential Buildings

- 6.1.1 The rentable area shall be the carpet area as worked out in 5 but shall further include the following:
 - a) The carpet area of kitchen, pantry, store, lavatory, bath room; and
 - b) Fifty percent of carpet area of unglazed and 100 percent of glazed verandah.
 - 6.1.1.1 It shall, however, exclude the carpet area of the following:
 - a) Covered portion of the building within portion specified in 5.1, such as storage space on top, landings of staircase, under and first landing and waist slab on floor one.
 - b) Fifty percent of the carpet area of balcony.
- 6.1.2 While accounting the rentable area for the category mentioned in 3.2(b), one-fourth carpet area shall be accounted for when stilts have height more than 2.4 m.
- **6.2** Non-Residential Buildings The rentable area shall be the carpet area as worked out in 5 but shall further include the carpet area of the canteen including store, kitchen and pantry attached to it.
- 6.2.1 It shall, however, not include carpet areas of bathroom and lavatory.
- 6.2.2 While accounting the rentable area for the category mentioned in 3.2(b), one-fourth carpet area shall be accounted for when stilts have height more than 2.4 m.

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002 Telephones: 323 0131, 323 3375, 323 9402

Fax: 91 11 3234062, 91 11 3239399, 91 11 3239382

Fax: 91 11 3234062, 91 11 3239399, 91 11 3239362		
Central Laboratory:	Telegrams : Mar (Common to	
•		•
Plot No. 20/9, Site IV, Sahibabad Industrial Area, Sahibabad 201	010	3-77 00 32
Regional Offices:		70 47
Central : Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002		323 76 17
*Eastern : 1/14 CIT Scheme VII M, V.I.P. Road, Maniktola, CALCUTTA 700054		337 86 62
Northern: SCO 335-336, Sector 34-A, CHANDIGARH 160022		50 38 43
Southern: C.I.T. Campus, IV Cross Road, CHENNAI 600113	2	235 23 15
†Western : Manakalaya, E9, Behind Marol Telephone Exchange, Andheri (East), MUMBAI 400093		332 92 95
Branch Offices::		
'Pushpak', Nurmohamed Shaikh Marg, Khanpur, AHMEDABAD	380001	550 13 48
‡Peenya Industrial Area, 1st Stage, Bangalore-Tumkur Road, BANGALORE 560058	ŧ	339 49 55
Gangotri Complex, 5th Floor, Bhadbhada Road, T.T. Nagar, BHG	DPAL 462003	55 40 21
Plot No. 62-63, Unit VI, Ganga Nagar, BHUBANESHWAR 75100)1 4	40 36 27
Kalaikathir Buildings, 670 Avinashi Road, COIMBATORE 641037		21 01 41
Plot No. 43, Sector 16 A, Mathura Road, FARIDABAD 121001		3-28 88 01
Savitri Complex, 116 G.T. Road, GHAZIABAD 201001	8	3-71 19 96
53/5 Ward No.29, R.G. Barua Road, 5th By-lane, GUWAHATI 78	31003	54 11 37
5-8-56C, L.N. Gupta Marg, Nampally Station Road, HYDERABAD 500001		20 10 83
E-52, Chitaranjan Marg, C- Scheme, JAIPUR 302001		37 29 25
117/418 B, Sarvodaya Nagar, KANPUR 208005	2	21 68 76
Seth Bhawan, 2nd Floor, Behind Leela Cinema, Naval K LUCKNOW 226001	ishore Road, 2	23 89 23
NIT Building, Second Floor, Gokulpat Market, NAGPUR 440010		52 51 71
Patliputra Industrial Estate, PATNA 800013	2	26 23 05
Institution of Engineers (India) Building 1332 Shivaji Nagar, PUNE 411005		32 36 35
T.C. No. 14/1421, University P. O. Palayam, THIRUVANANTHAPUR	IAM 695034 6	5 21 17
*Sales Office is at 5 Chowringhee Approach, P.O. Princep Street CALCUTTA 700072	t, 2	27 10 85
†Sales Office is at Novelty Chambers, Grant Road, MUMBAI 400	0007	309 65 28
‡Sales Office is at 'F' Block, Unity Building, Narashimaraja Squar BANGALORE 560002	re, 2	222 39 71

AMENDMENT NO. 1 OCTOBER 1981

TO

IS:3861-1975 METHOD OF MEASUREMENT OF PLINTH, CARPET AND RENTABLE AREAS OF BUILDINGS

(First Revision)

Addendum

(Page 5, clause 5.1) - Add the following new Note after 5.1:

'NOTE - The various dimensions could be measured internally or externally.'

(BDC 44)

Reprography Unit, BIS, New Delhi, India

AMENDMENT NQ. 2 FEBRUARY 1984

IS:3861-1975 METHOD OF MEASUREMENT OF PLINTH, CARPET AND RENTABLE AREAS OF BUILDINGS

(First Revision)

Addendum

(Page 7, clause 6.2) - Add the following Note after 6.2:

'NOTE - The rentable area for basement meant for storage purposes may also be worked out on cubical content basis in which case after calculating the carpet areas as mentioned in 6.2, cubical content shall be worked out by multiplying the carpet area by the average height between the floor level and bottom of roof.'

(BDC 44)

AMENDMENT NO. 3 OCTOBER 1987

TO.

IS:3861-1975 METHOD OF MEASUREMENT OF PLINTH, CARPET AND RENTABLE AREAS OF BUILDINGS

(First Revision)

- (<u>Page 4</u>, <u>clause 4.1</u>) Add the following new item in the end:
 - 'f) Usable area of slab(s) projected outside walls.'

(BDC 44)