



JavaScript Array Methods

[< Previous](#)[Next >](#)

Converting Arrays to Strings

The JavaScript method `toString()` converts an array to a string of (comma separated) array values.

Example

```
var fruits = ["Banana", "Orange", "Apple", "Mango"];  
document.getElementById("demo").innerHTML = fruits.toString();
```

Result:

Banana,Orange,Apple,Mango

[Try it Yourself »](#)

The `join()` method also joins all array elements into a string.

It behaves just like `toString()`, but in addition you can specify the separator:

Example

```
var fruits = ["Banana", "Orange", "Apple", "Mango"];  
document.getElementById("demo").innerHTML = fruits.join(" * ");
```

Result:



HTML

CSS

MORE ▾

[Try it Yourself »](#)

Popping and Pushing

When you work with arrays, it is easy to remove elements and add new elements.

This is what popping and pushing is:

Popping items **out** of an array, or pushing items **into** an array.

Popping

The `pop()` method removes the last element from an array:

Example

```
var fruits = ["Banana", "Orange", "Apple", "Mango"];
fruits.pop();           // Removes the last element ("Mango") from
fruits
```

[Try it Yourself »](#)

The `pop()` method returns the value that was "popped out":

Example

```
var fruits = ["Banana", "Orange", "Apple", "Mango"];
var x = fruits.pop();    // the value of x is "Mango"
```

[Try it Yourself »](#)



HTML

CSS

MORE ▾



Pushing

The `push()` method adds a new element to an array (at the end):

Example

```
var fruits = ["Banana", "Orange", "Apple", "Mango"];  
fruits.push("Kiwi");           // Adds a new element ("Kiwi") to fruits
```

[Try it Yourself »](#)

The `push()` method returns the new array length:

Example

```
var fruits = ["Banana", "Orange", "Apple", "Mango"];  
var x = fruits.push("Kiwi");    // the value of x is 5
```

[Try it Yourself »](#)

Shifting Elements

Shifting is equivalent to popping, working on the first element instead of the last.

The `shift()` method removes the first array element and "shifts" all other elements to a lower index.

Example

```
var fruits = ["Banana", "Orange", "Apple", "Mango"];  
fruits.shift();                // Removes the first element "Banana" from  
fruits
```



HTML

CSS

MORE ▾



The `shift()` method returns the string that was "shifted out":

Example

```
var fruits = ["Banana", "Orange", "Apple", "Mango"];  
var x = fruits.shift();    // the value of x is "Banana"
```

[Try it Yourself »](#)

The `unshift()` method adds a new element to an array (at the beginning), and "unshifts" older elements:

Example

```
var fruits = ["Banana", "Orange", "Apple", "Mango"];  
fruits.unshift("Lemon");    // Adds a new element "Lemon" to fruits
```

[Try it Yourself »](#)

The `unshift()` method returns the new array length.

Example

```
var fruits = ["Banana", "Orange", "Apple", "Mango"];  
fruits.unshift("Lemon");    // Returns 5
```

[Try it Yourself »](#)

Changing Elements



HTML

CSS

MORE ▾



Array **indexes** start with 0. [0] is the first array element, [1] is the second, [2] is the third ...

Example

```
var fruits = ["Banana", "Orange", "Apple", "Mango"];  
fruits[0] = "Kiwi";           // Changes the first element of fruits to "Kiwi"
```

[Try it Yourself »](#)

The **length** property provides an easy way to append a new element to an array:

Example

```
var fruits = ["Banana", "Orange", "Apple", "Mango"];  
fruits[fruits.length] = "Kiwi";           // Appends "Kiwi" to fruits
```

[Try it Yourself »](#)

Deleting Elements

Since JavaScript arrays are objects, elements can be deleted by using the JavaScript operator **delete**:

Example

```
var fruits = ["Banana", "Orange", "Apple", "Mango"];  
delete fruits[0];           // Changes the first element in fruits to  
undefined
```



HTML

CSS

MORE ▾



Using **delete** may leave undefined holes in the array. Use `pop()` or `shift()` instead.

Splicing an Array

The `splice()` method can be used to add new items to an array:

Example

```
var fruits = ["Banana", "Orange", "Apple", "Mango"];  
fruits.splice(2, 0, "Lemon", "Kiwi");
```

[Try it Yourself »](#)

The first parameter (2) defines the position **where** new elements should be **added** (spliced in).

The second parameter (0) defines **how many** elements should be **removed**.

The rest of the parameters ("Lemon" , "Kiwi") define the new elements to be **added**.

The `splice()` method returns an array with the deleted items:

Example

```
var fruits = ["Banana", "Orange", "Apple", "Mango"];  
fruits.splice(2, 2, "Lemon", "Kiwi");
```

[Try it Yourself »](#)

With clever parameter setting, you can use `splice()` to remove elements without leaving "holes" in the array:

Example

```
var fruits = ["Banana", "Orange", "Apple", "Mango"];  
fruits.splice(0, 1);           // Removes the first element of fruits
```

Try it Yourself »

The first parameter (0) defines the position where new elements should be **added** (spliced in).

The second parameter (1) defines **how many** elements should be **removed**.

The rest of the parameters are omitted. No new elements will be added.

Merging (Concatenating) Arrays

The `concat()` method creates a new array by merging (concatenating) existing arrays:

Example (Merging Two Arrays)

```
var myGirls = ["Cecilie", "Lone"];  
var myBoys = ["Emil", "Tobias", "Linus"];  
var myChildren = myGirls.concat(myBoys); // Concatenates (joins) myGirls  
and myBoys
```

Try it Yourself »

The `concat()` method does not change the existing arrays. It always returns a new array.



HTML

CSS

MORE ▾



The `concat()` method can take any number of array arguments.

Example (Merging Three Arrays)

```
var arr1 = ["Cecilie", "Lone"];
var arr2 = ["Emil", "Tobias", "Linus"];
var arr3 = ["Robin", "Morgan"];
var myChildren = arr1.concat(arr2, arr3); // Concatenates arr1 with arr2
and arr3
```

[Try it Yourself »](#)

The `concat()` method can also take strings as arguments:

Example (Merging an Array with Values)

```
var arr1 = ["Emil", "Tobias", "Linus"];
var myChildren = arr1.concat("Peter");
```

[Try it Yourself »](#)

Slicing an Array

The `slice()` method slices out a piece of an array into a new array.

This example slices out a part of an array starting from array element 1 ("Orange"):

Example

```
var fruits = ["Banana", "Orange", "Lemon", "Apple", "Mango"];
var citrus = fruits.slice(1);
```

[Try it Yourself »](#)

The `slice()` method creates a new array. It does not remove any elements from the source array.

This example slices out a part of an array starting from array element 3 ("Apple"):

Example

```
var fruits = ["Banana", "Orange", "Lemon", "Apple", "Mango"];  
var citrus = fruits.slice(3);
```

Try it Yourself »

The `slice()` method can take two arguments like `slice(1, 3)`.

The method then selects elements from the start argument, and up to (but not including) the end argument.

Example

```
var fruits = ["Banana", "Orange", "Lemon", "Apple", "Mango"];  
var citrus = fruits.slice(1, 3);
```

Try it Yourself »

If the end argument is omitted, like in the first examples, the `slice()` method slices out the rest of the array.

Example

```
var fruits = ["Banana", "Orange", "Lemon", "Apple", "Mango"];  
var citrus = fruits.slice(2);
```

Try it Yourself »



HTML

CSS

MORE ▾



Automatic toString()

JavaScript automatically converts an array to a comma separated string when a primitive value is expected.

This is always the case when you try to output an array.

These two examples will produce the same result:

Example

```
var fruits = ["Banana", "Orange", "Apple", "Mango"];  
document.getElementById("demo").innerHTML = fruits.toString();
```

[Try it Yourself »](#)

Example

```
var fruits = ["Banana", "Orange", "Apple", "Mango"];  
document.getElementById("demo").innerHTML = fruits;
```

[Try it Yourself »](#)

All JavaScript objects have a toString() method.

Finding Max and Min Values in an Array

There are no built-in functions for finding the highest or lowest value in a JavaScript array.

You will learn how you solve this problem in the next chapter of this tutorial.



HTML

CSS

MORE ▾



Sorting arrays are covered in the next chapter of this tutorial.

Complete Array Reference

For a complete reference, go to our [Complete JavaScript Array Reference](#).

The reference contains descriptions and examples of all Array properties and methods.

Test Yourself With Exercises

Exercise:

Use the correct Array method to remove the **last item** of the `fruits` array.

```
var fruits = ["Banana", "Orange", "Apple"];  
 ;
```

Submit Answer »

[Start the Exercise](#)

◀ Previous

Next >

[HTML](#)[CSS](#)[MORE ▾](#)

HOW TO

Tabs
Dropdowns
Accordions
Side Navigation
Top Navigation
Modal Boxes
Progress Bars
Parallax
Login Form
HTML Includes
Google Maps
Range Sliders
Tooltips
Slideshow
Filter List
Sort List

SHARE



CERTIFICATES

HTML
CSS
JavaScript
SQL
Python
PHP
jQuery
Bootstrap
XML

[HTML](#)[CSS](#)[MORE ▼](#)[REPORT ERROR](#)[PRINT PAGE](#)[FORUM](#)[ABOUT](#)

Top Tutorials

[HTML Tutorial](#)
[CSS Tutorial](#)
[JavaScript Tutorial](#)
[How To Tutorial](#)
[SQL Tutorial](#)
[Python Tutorial](#)
[W3.CSS Tutorial](#)
[Bootstrap Tutorial](#)
[PHP Tutorial](#)
[jQuery Tutorial](#)
[Java Tutorial](#)
[C++ Tutorial](#)

Top References

[HTML Reference](#)
[CSS Reference](#)
[JavaScript Reference](#)
[SQL Reference](#)
[Python Reference](#)
[W3.CSS Reference](#)
[Bootstrap Reference](#)
[PHP Reference](#)
[HTML Colors](#)
[jQuery Reference](#)
[Java Reference](#)
[Angular Reference](#)

Top Examples

[HTML Examples](#)
[CSS Examples](#)
[JavaScript Examples](#)
[How To Examples](#)
[SQL Examples](#)
[Python Examples](#)

[HTML](#)[CSS](#)[MORE ▾](#)

[PHP Examples](#)
[jQuery Examples](#)
[Java Examples](#)
[XML Examples](#)

Web Certificates

[HTML Certificate](#)
[CSS Certificate](#)
[JavaScript Certificate](#)
[SQL Certificate](#)
[Python Certificate](#)
[jQuery Certificate](#)
[PHP Certificate](#)
[Bootstrap Certificate](#)
[XML Certificate](#)

[Get Certified »](#)

W3Schools is optimized for learning, testing, and training. Examples might be simplified to improve reading and basic understanding. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using this site, you agree to have read and accepted our terms of use, cookie and privacy policy. Copyright 1999-2020 by Refsnes Data. All Rights Reserved.

Powered by W3.CSS.

