

Joint Power Allocation and Network Slicing In an End to End O-RAN System

1st Mojdeh Karbalaee Motalleb
Electrical and Computer Engineering
Tehran University
Tehran, Iran
mojdeh.karbalaee@ut.ac.ir

2nd Given Name Surname
dept. name of organization (of Aff.)
name of organization (of Aff.)
City, Country
email address

Abstract—

Index Terms—component, formatting, style, styling, insert

I. Introduction

This document is a model and instructions for L^AT_EX. Please observe the conference paper limits.

II. System Model and Problem Formulation

In this section, first, we present the downlink (DL) of O-RAN System. Then we obtain achievable rate and delays. Afterward, the main problem is expressed.

A. System Model

Suppose that there are S Slices Serving V Services. Each Service $v \in \{1, 2, \dots, V\}$, consists of U_v single antenna users that require certain service. Each slice $s \in \{1, 2, \dots, S\}$ consists of R_s RRHs and N_s PRBs. Each RRH $r \in \{1, 2, \dots, R\}$ is connected to BBU pool via an optical fiber link with limited fronthaul capacity. Also each RRH and PRB can serve more than one slice. It is considered that in BBU, the system has 2 processing layer consists of M_1 homogeneous VMs in first layer and M_2 homogeneous VMs in second layer.

B. Achievable Rate

In this subsection, the Achievable Rate is obtained as below. The achievable data rate for i^{th} UE in v^{th} service can be written as

$$R_{u(v,i)} = B \log_2(1 + \rho_{u(v,i)}) \quad (1)$$

where $\rho_{u(v,i)}$ is obtained from

$$\rho_{u(v,i)} = \frac{P_{u(v,i)}}{BN_0 + I_{u(v,i)}} \quad (2)$$

References

Please number citations consecutively within brackets [1]. The sentence punctuation follows the bracket [2]. Refer simply to the reference number, as in [3]—do not use “Ref. [3]” or “reference [3]” except at the beginning of a sentence: “Reference [3] was the first ...”

Number footnotes separately in superscripts. Place the actual footnote at the bottom of the column in which it

was cited. Do not put footnotes in the abstract or reference list. Use letters for table footnotes.

Unless there are six authors or more give all authors' names; do not use “et al.”. Papers that have not been published, even if they have been submitted for publication, should be cited as “unpublished” [4]. Papers that have been accepted for publication should be cited as “in press” [5]. Capitalize only the first word in a paper title, except for proper nouns and element symbols.

For papers published in translation journals, please give the English citation first, followed by the original foreign-language citation [6].

References

- [1] G. Eason, B. Noble, and I. N. Sneddon, “On certain integrals of Lipschitz-Hankel type involving products of Bessel functions,” *Phil. Trans. Roy. Soc. London*, vol. A247, pp. 529–551, April 1955.
- [2] J. Clerk Maxwell, *A Treatise on Electricity and Magnetism*, 3rd ed., vol. 2. Oxford: Clarendon, 1892, pp.68–73.
- [3] I. S. Jacobs and C. P. Bean, “Fine particles, thin films and exchange anisotropy,” in *Magnetism*, vol. III, G. T. Rado and H. Suhl, Eds. New York: Academic, 1963, pp. 271–350.
- [4] K. Elissa, “Title of paper if known,” unpublished.
- [5] R. Nicole, “Title of paper with only first word capitalized,” *J. Name Stand. Abbrev.*, in press.
- [6] Y. Yorozu, M. Hirano, K. Oka, and Y. Tagawa, “Electron spectroscopy studies on magneto-optical media and plastic substrate interface,” *IEEE Transl. J. Magn. Japan*, vol. 2, pp. 740–741, August 1987 [Digests 9th Annual Conf. Magnetics Japan, p. 301, 1982].
- [7] M. Young, *The Technical Writer's Handbook*. Mill Valley, CA: University Science, 1989.

IEEE conference templates contain guidance text for composing and formatting conference papers. Please ensure that all template text is removed from your conference paper prior to submission to the conference. Failure to remove the template text from your paper may result in your paper not being published.