

INDEX

!

- 16-bit architecture, 246-250, 278-282
 - 32-bit architecture, 218-225
 - addressing modes, 219
 - registers, 219
 - 64-bit architecture, 27
 - external memory space, 632
 - 74LS138 decoder, 267, 297
 - 74LS244 octal buffer, 292, 294
 - 74LS245 bidirectional buffer, 304
 - 74LS280 parity generator/checker, 276
 - 74LS373 D latch, 292
 - 80286 microprocessor, 242-246, 532
 - address bus, 243
 - data bus, 243
 - 80386 microprocessor, 530-553
 - bus cycle definition, 541
 - descriptor tables, 549
 - evolution from 80186, 530
 - general registers as pointers, 534
 - major changes, 532
 - new instructions, 537
 - paging, 550
 - pins, 539
 - protected mode, 545
 - real mode, 533
 - registers, 533
 - scaled index addressing mode, 534
 - virtual 8086 mode, 552
 - virtual memory, 545
 - 80486 microprocessor, 590-595
 - enhancements, 590
 - pipelining, 594
 - 8088 microprocessor, 228-233
 - address bus, 228
 - bus timing, 230
 - control bus, 230
 - data bus, 228
 - pins, 231-233
 - 8237 (direct memory access), 404-412
 - all mask register, 411
 - clear mask register, 412
 - command register, 407
 - connection to CPU, 413, 415
 - control registers, 407
 - master clear register, 412
 - mode register, 409
 - pins, 413, 415
 - single mask register, 411
 - status register, 408
 - 8253/54 timer
 - connection, 354
 - control word, 352
 - counter 0, 355
 - counter 1, 356
 - counter 2, 356
 - initialization, 351
 - programming, 353
 - 8255 programmable peripheral interface, 299-310
 - control word, 301
 - mode selection, 300
 - pins, 300
 - 8259 programmable interrupt controller, 377-387
 - from hardware, 393
 - from microprocessor, 393
 - initialization, 388
 - interfacing to x86, 387
 - priority, 394
 - 8284 clock generator, 236-237
 - 8288 bus controller, 233-236
 - 8-bit architecture, 238-242
- ### A
- ADC (analog-to-digital converter), 336-345
 - ADC0848 chip, 337
 - selecting an input channel, 338
 - ADC808/809 chip, 342
 - selecting an input channel, 344
 - programming, 344
 - address bus, 15
 - address decoding, 265-269, 292-294
 - addressing modes. See also 32-bit addressing modes
 - based indexed addressing, 49
 - based relative addressing, 48
 - direct addressing, 47
 - immediate addressing, 47

indexed relative addressing,	48	SHL (shift left logical),	105
register addressing,	46	SHR (shift right logical),	104
register indirect addressing,	48	STD (set the direction flag),	187
segment overrides,	49	STOSx (store string Byte/Word),	188
ASCII,	112	SUB and SBB (subtraction),	96-97
to BCD conversion,	112-117	XLAT (translate),	192
to binary (hex) conversion,	206, 209	XOR (logical),	103
ASCII code,	8	Assembly language	
ASCII codes,	777-778	ADD instruction,	32
Assembly instructions,	716-738	impact on flag register,	44
ADD and ADC (addition),	92-95	assembler,	60
AND (logical),	102	code segment,	58, 79
CALL (call procedure),	369	comments,	56
CBW (convert byte to word),	180	control transfer,	68
CLD (clear direction flag),	187	CALL,	70
CMP (compare),	105-109, 184	FAR and NEAR,	68
CMPSx (compare string Byte/Word),	189	jumps,	68, 69, 70
CWD (convert word to double word),	180	data segment,	57, 79
DAA (decimal adjust for addition),	115-117	directive	
DAS (decimal adjust for subtraction),	117-118	EVEN,	281
DIV (division),	99-101	directives,	56, 740-750
IDIV (integer division),	181	.386 (386 processor and above),	220
IMUL (integer multiplication),	183	.86 (any x86 processor),	220
INT (interrupt),	369	DB (define byte),	73
INTO (interrupt on overflow),	373	DD (define doubleword),	75
IRET (interrupt return),	369	DQ (define quadword),	75
LODSx (load string Byte/Word),	188	DT (define ten bytes),	76
MOVSx (move string Byte/Word),	187	DUP (duplicate),	74
MUL (multiplication),	98-99	DW (define word),	74
OR (logical),	102	END (end),	197
RCL (rotate thru carry left),	120-121	EQU (equate),	75
RCR (rotate thru carry right),	119-120	EXTRN (external),	196
REP prefix (repeat),	187	ORG (origin),	73
REPE prefix.		PAGE and TITLE,	61
See REPZ prefix		PUBLIC (public),	196
REPNE prefix.		SEGMENT (segment),	203
See REPNZ prefix		fields,	56
REPNZ prefix (repeat not zero),	189	files,	60, 62
REPZ prefix (repeat zero),	189	labels,	56, 71, 750
RETF (return FAR),	369	linker,	62
ROL (rotate left),	119-120	MACRO definition,	147-157
ROR (rotate right),	118	mnemonics,	56
SAL (shift arithmetic left).		model definition,	56
See SHL (shift left)		MOV instruction,	30
SAR (shift arithmetic right),	184	operands,	56
SCASx (scan string Byte/Word),	191	programming,	30
		reserved names,	751

sample programs,	63, 64, 65, 66, 67	MC1408 DAC,	332
segment definition,	33, 57, 77, 78, 79	data bus,	14
stack segment,	57, 68, 77	data integrity,	273-277
subroutines,	71	checksum byte,	273
		checksum program,	273
		error detection,	274
		parity bit,	275
B		data segment,	35, 203
BCD number system,	111	address,	36
addition,	114-117	DEBUG	
subtraction,	117-118	A, the assemble command,	702
to ASCII conversion,	114-117	D, the dump command,	707
to ASCII conversion in C,	122-123	E, the enter command,	708
binary logic,	9	entering and exiting,	700
binary to ASCII conversion,	205, 207	examining/altering registers,	700
BIOS ROM,	39	examining/altering the flag register,	710
INT 10H (screen control),	130-137	F, the fill command,	706
INT 16H (keyboard),	162-165	G, the go command,	703
bus boosting,	241	Q, the quit command,	700
		T, the trace command,	705
		U, the unassemble command,	702
C		decimal to binary (hex) conversion,	206
C language,	121	direct memory access (DMA),	402-420
bit testing,	124	16-bit channels,	419
bitwise operators,	121-123	8237 DMA.	
in-line Assembly,	224-225		See 8237 DMA
C/C++ programming,	306-310	channel 1,	417
Linux,	308	channel 2,	419
CGA (color graphics adapter),	440	channel assignment,	416
code segment,	33, 203	channel priority,	419
address,	34	concept,	402
CodeView,	220	initialization,	404
COM files,	83	DMA (direct memory access),	240
computers		DOS INT 21H (I/O),	137-147
memory map,	38	DSP (digital signal processing).	
organization,	14		See MMX
terminology,	13		
CPU (central processing unit)		E	
how it works,	17	EGA (enhanced graphics adapter),	441
inside,	16	emu8086 assembler,	80-82
relation to RAM and ROM,	15	EXE files,	83
CPU identification,	615		
D		F	
DAC (digital-to-analog converter),	332-335	flowcharts,	84-87, 108, 210
DAC808,	332	full segment definition,	200-203
generating a sine wave,	332		

H		soft error,	654
		IEEE floating-point standard,	504-505
hard disks,	492-499	format,	506
boot record,	495	input/output (INT 21H),	137-147
bootable and nonbootable disks,	495	interrupts	
capacity,	492	categories,	370
clusters,	496	handling,	371
disk caching,	498	INT 00 (divide error),	371
disk reliability,	499	INT 01 (single step),	372
ESDI (enhanced small device interface),		INT 02 (nonmaskable interrupt),	372
496		INT 03 (breakpoint),	373
FAT (file allocation table),	494-495	INT 04 (signed number overflow),	373
formatting,	493	INT 10H (input/output),	759-764
IDE (integrated device electronics),	497	INT 12H (memory size),	765
organization,	492	INT 14H (COM port),	765-767
partitioning,	495	INT 16H (keyboard),	767-769
SCSI (small computer system interface),		INT 1AH (timer/time),	770-771
497		INT 21H (operating system),	754-756
speed,	496	INT 33H (mouse),	756-759
hex to decimal conversion,	205	interrupt service routine (ISR),	368
high memory area (HMA),	250	sources,	390
HyperTerminal,	455	vector table,	368, 375
I		ISA bus,	238-242
		8-bit and 16-bit I/O,	668
I/O address maps		address bus,	239, 247
80286,	773	address bus signals,	660
System Information,	774	bus history,	238
IC technology,	638-655	control bus,	240, 247
advances,	642	data bus,	239, 247
capacitance derating,	646	limitations,	675
crosstalk,	652	local bus,	238
decoupling capacitors,	651	memory control signals,	660-662
evolution,	643	PC104 bus and embedded PC,	676
fan-out,	644	peripherals,	673
FIT (failure in time),	653	system bus,	238
gallium arsenide (GaAs) chips,	655	timing,	662-664, 671-672
ground bounce,	650	ISA expansion slot,	248
hard error,	654	K	
history,	641	keyboard (INT 16H),	162-165
input/output characteristics,	640	keyboards	
inverters,	639	BIOS INT 16H,	472
line ringing,	653	buffer,	476
logic families,	639	ECP (extended capability port),	486
mean time between failures (MTBF),	654	EPP (enhanced parallel port),	486
MOS vs. bipolar transistors,	638	first keyboard status byte,	470
power dissipation,	648		

head pointer,	476	cache,	570
operation,	464-468, 469, 474	coherency,	577
overflow,	475	direct-mapped,	572
printing a character,	483	fill block size,	577
programming,	468-478	fully associative,	571
scan codes,	469	levels,	578
second keyboard status byte,	471	organization,	571
SPP (standard parallel port),	484	replacement policy,	577
tail pointer,	476	set associative,	573
		updating main memory,	576
L		capacity,	256
		cycle time,	560
LCD (liquid crystal display),	316-322	DDR (double data rate) RAM,	581
busy flag,	320	DIMM and SIMM memory modules,	665
commands,	317	DRAM	
cursor position,	321	interleaving,	565
pin descriptions,	316	page mode,	566
programming,	322	standard mode,	562
timing,	322	static column mode,	567
little endian convention,	36, 221	types,	562
local bus,	678	DRAM (dynamic RAM),	262
logic design,	10	EDO (extended data-out) DRAM,	578
logic gates,	9	EEPROM (electrically erasable PROM),	258
AND gate,	9		
inverter,	10	EPROM (erasable PROM),	258
NAND and NOR gates,	10	Flash (Flash EEPROM),	259
OR gate,	9	mask ROM,	260
tri-state buffer,	9	memory map,	666
XOR gate,	10	NV-RAM (nonvolatile RAM),	265
logical and physical address,	33, 42	organization,	256
in the code segment,	34	PROM (programmable ROM),	257
in the data segment,	36	RAM (random access memory),	260
in the stack segment,	41	Rambus DRAM,	581
overlapping,	42	ROM (read-only memory),	257
look-up tables,	192	ROM duplicate,	666
looping		SDRAM (synchronous DRAM),	579
using the zero flag,	46	shadow RAM,	667
		speed,	256, 279
M		SRAM (static RAM),	260
		wait states,	560
MASM,	220	memory map,	269-272
MAX232/3 (EIA-232 driver/receiver),	451	BIOS data area,	270
memory,	256-265	conventional memory,	270
access time,	562	reset address,	271
bandwidth,	282	video display RAM,	270
banks,	275, 278	MMX (multimedia extension),	613-618
burst mode,	581	CPUID instruction,	616

data types,	615	performance,	683
DSP (digital signal processing),	613	plug-and-play,	680
register aliasing,	614	Pentium II to Pentium IV microprocessor	
modules,	196-205	cache,	626
pass parameters,	211-213	hyper-threading technology (HTT),	628
monitors,	424-433	multicore technology,	629
character box,	428, 435, 438	streaming SIMD extension (SSE),	630
color,	427	Pentium microprocessor,	596-602
cursor position,	433	features,	597-602
digital vs. analog,	427	overdrive technology,	602
dot pitch,	426	Pentium Pro microprocessor,	609-613
graphic mode,	440-442	architecture,	610
monitor size,	426	branch prediction,	612
phosphors,	427	bus vs. internal frequency,	613
pixel programming,	442	out-of-order execution,	611
scrolling,	435	superpipelined,	610
text mode,	436	superscalar,	610
video controller,	428	pipelining,	27
video modes,	429, 433	printers,	478-486
Moore's law,	635	addresses,	481
mouse (INT 33H),	166-173	BIOS INT 17H,	482
music generation,	359-364	Centronics printer interface,	478
using C#,	364-365	control characters,	482
		control signals,	480
		status signals,	478
		time-out,	481
N		pseudocode,	84-87, 108, 210
number systems,	2		
binary,	2	R	
addition,	6	RAM,	38
binary to and from hexadecimal,	4	video RAM,	39
binary to decimal,	3	registers,	29
counting in bases,	6	Extra Segment (ES),	38
decimal,	2	flag register,	43
decimal to binary,	2	Stack Pointer (SP),	41
hexadecimal,	2, 4	Stack Segment (SS),	41
addition,	7	RISC architecture,	602-609
subtraction,	7	comparison to CISC,	606
hexadecimal to decimal,	5	features,	603-605
		Harvard and von Neumann,	605
P		RS232.	
PCI bus		See serial communication	
bus arbitration,	676		
bus protocol,	676	S	
connector (expansion slot),	681	screen control (INT 10H),	130-137
local bus,	679		
master and slave,	676		

serial communication,	448-454	V	
data communication classification,	452	VGA (video graphics array),	430, 441
data framing,	449	virtual memory,	545
data transfer rate,	450	Visual C/C++ programming,	322
full-duplex transmission,	449	Visual C++,	224-225
half-duplex transmission,	449		
handshaking,	453	X	
MAX232/3 (EIA-232 driver/receiver),	451	x86	
programming,	455-458	data types,	73
signal conditioning,	342	I/O map,	296
signed numbers (integer),	176-186	interrupts.	
overflow,	178-179		See interrupts
speaker,	356	x86 family	
stack segment,	39, 203	80286,	25
access,	40	80386,	25
address,	41	80486,	25
described,	40	8088,	25
stepper motors,	326-332	evolution,	24
four-step sequence,	329	Pentium,	26
programming,	327	Pentium II,	26
speed,	330	Pentium III,	26
step angle,	327	Pentium Pro,	26
timing,	328	x87 math coprocessor,	504-523
torque,	330	arithmetic instructions,	520-522
wave drive sequence,	331	constant instructions,	523
strings,	186-192	control instructions,	524
structured programming,	83, 84	integer instructions,	517, 519
SVGA (super VGA),	442	packed BCD instructions,	520
T		programming,	510
temperature sensors (LM34/35),	341	real number instructions,	519
thermistor,	341	registers,	508
time delay,	357-358	transcendental instructions,	522
		trigonometric instructions,	517
U			
USB (universal serial bus)			
architecture,	689		
cable signals,	692		
enumeration,	693		
features,	688		
hubs,	690-692		
programming,	694		

