




UNIVERSITY OF  
CAMBRIDGE

Department of Physiology, Development  
and Neuroscience



NGSchool.eu :: darogan@gmail.com



# Methylation Analysis

*Using Bisulfite Sequencing*



*Russell S. Hamilton*

Dr Russell S. Hamilton

Email: [rsh46@cam.ac.uk](mailto:rsh46@cam.ac.uk)

Twitter: [@drrshamilton](https://twitter.com/drrshamilton)



# Who am I?



Bioinformatics Facility Manager  
Centre for Trophoblast Research  
University of Cambridge

Support ~30 Groups



Bioinformatician (R&D)  
Cambridge Epigenetix

Bisulfite sequencing kits

*Conflict of Interest*  
Shareholder in CEGX

```
rsync -aurvz USERNAME@ngschool.local:/ngschool/Methylation /ngschool --exclude='.git'
```

## Presentation

- Presentation/Hamilton\_Methylation\_Presentation.pdf

## FastQ files & simple bash scripts:

- SimulatedData/


## Reference genome:

- NGSchool\_GRCh38\_Chr1\_region/


## Pre Processed Data

- SimulatedData\_PreAnalysed/


# What is Methylation?




*cytosine*




*5'-methyl-C*



*5'-hydroxymethyl-C*



*5'-formyl-C*




*5'carboxy-C*

Modifications to cytosine are the most widely studied, however Adenosine also known to be methylated m6A

[Figure adapted from Booth et al., 2013]

# What is Methylation?



[Figure from [www.diagenode.com](http://www.diagenode.com)]


OPINION

Open Access



## Single-cell epigenomics: powerful new methods for understanding gene regulation and cell identity


Stephen J. Clark<sup>1</sup>, Heather J. Lee<sup>1,2\*</sup>, Sébastien A. Smallwood<sup>1,3</sup>, Gavin Kelsey<sup>1,4</sup> and Wolf Reik<sup>1,2,4,5</sup>




# Bisulfite Sequencing (bs or mkbs)

Traditional bisulfite sequencing

Confounded signal 5mC + 5hmC




# Oxidative bisulfite sequencing (oxbs)



Commercialised by Cambridge Epigenetix (CEGX)




# Reductive bisulfite sequencing




Commercialised by Cambridge Epigenetix (CEGX)

## Traditional Bisulfite sequencing (methylC-Seq)



## TET-Assisted Bisulfite Sequencing (TAB-Seq)



Commercialised by WiseGene

## Illumina Array Based

Illumina 450K array

Illumina EPIC (850K) array

## Illumina Sequencing Based

Whole Genome Bisulfite Sequencing (WGBS) inc oxbs/redbs

Antibody Pulldown (e.g. (h)MeDIP)

Reduced Representation Bisulfite Sequencing (RRBS)

Targeted Bisulfite Sequencing (e.g. CpGiant)

Enzymatic conversion (TAB-Seq)

← *Current State of the Art*

## PacBio


Direct reading of cytosine methylation

## Nanopore

Oxford Nanopore direct reading of cytosine methylation

← *Future State of the Art*

# Whole Genome Bisulfite Sequencing



Bisulfite aware genome aligner

• Bismark	<i>conservative</i>	80+%	<i>best supported</i>
• ERNE2	<i>balanced</i>	90+%	<i>fast</i>
• BWA-Meth	<i>leanient</i>	95+%	<i>soft-clipping</i>

## **BIOINFORMATICS APPLICATIONS NOTE**

Vol. 27 no. 11 2011, pages 1571–1572  
doi:10.1093/bioinformatics/btr167

*Sequence analysis*

Advance Access publication April 14, 2011

### **Bismark: a flexible aligner and methylation caller for Bisulfite-Seq applications**


Felix Krueger\* and Simon R. Andrews

Bioinformatics Group, The Babraham Institute, CB22 3AT, Cambridge, UK

Associate Editor: Alfonso Valencia

- Arguable the most widely used bisulfite aware aligner...
- Very well supported (seqanswers.com, GitHub)
- Integrates with downstream tools

[Figure from Krueger F & Andrews SR (2011) Bioinformatics. 27(11):1571-2]



[Figure from Krueger F & Andrews SR (2011) Bioinformatics. 27(11):1571-2]

BS-read corresponds to  
converted original top strand

5' - **TT**GG**C**ATGTTTAA**A****C**G**T** - 3' bisulfite read  
 5' ...**cc**gg**c**atgttttaa**a****c**g**c**t...3' genomic sequence  
 ↓ ↓ ↓ ↓ ↓  
 xz...**H**.....**Z**.h. methylation call

z	unmethylated	C	in	CpG	context
Z	methylated	C	in	CpG	context
x	unmethylated	C	in	CHG	context
X	methylated	C	in	CHG	context
h	unmethylated	C	in	CHH	context
H	methylated	C	in	CHH	context

[Figure from Krueger F & Andrews SR (2011) Bioinformatics. 27(11):1571-2]

## 1. Reference Genome Prepared for Bisulfite Alignment

Human Genome ~3Gb disk space  
With preparation for bs-seq ~11Gb

Very CPU / Memory intensive...

Selected a random 5Mb region from Chr1  
(no N content)

4.9Mb Homo\_sapiens.GRCh38.dna.chromosome.1.region30000000-50000000.fa  
39Mb Bisulfite\_Genome

## 2. Bisulfite Treated and Sequenced Reads

Typically 30x coverage recommended to achieve  
accurate single base resolution methylation calls.

Very CPU / Memory intensive...

Simulated a data set using reference region and  
Sherman

	Read1	Read2
mkbs	1M/36Mb	1M/37Mb
oxbs	1M/38Mb	1M/37Mb



Reference genome must be prepared for bisulfite alignment

```
$ bismark_genome_prepare --bowtie2 NGSchool_GRCh38_Ch1_region
```

```
├─ Homo_sapiens.GRCh38.dna.chromosome.1.region30000000-50000000.fa
├─ Bisulfite_Genome
│   ├── CT_conversion
│   │   ├── BS_CT.1.bt2
│   │   ├── BS_CT.2.bt2
│   │   ├── BS_CT.3.bt2
│   │   ├── BS_CT.4.bt2
│   │   ├── BS_CT.rev.1.bt2
│   │   ├── BS_CT.rev.2.bt2
│   │   └─ genome_mfa.CT_conversion.fa
│   └─ GA_conversion
│       ├── BS_GA.1.bt2
│       ├── BS_GA.2.bt2
│       ├── BS_GA.3.bt2
│       ├── BS_GA.4.bt2
│       ├── BS_GA.rev.1.bt2
│       ├── BS_GA.rev.2.bt2
│       └─ genome_mfa.GA_conversion.fa
```

# Simulating Bisulfite Treated Reads

Simulate a set of 1M bisulfite reads to achieve ~30X coverage Chr1:30000000-5000000


```
$ Sherman \  
  --length 100 \  
  --number_of_seqs 1000000 \  
  --genome_folder NGSchool_GRCh38_Chr1_region/ \  
  --paired_end \  
  --minfrag 70 \  
  --maxfrag 400 \  
  --conversion_rate 99 \  
  --error_rate 0.25 \  
  --variable_length_adapter 100  
  
mv simulated_1.fastq mkbs_sim_1.fastq; gzip mkbs_sim_1.fastq  
mv simulated_2.fastq mkbs_sim_2.fastq; gzip mkbs_sim_2.fastq
```


Simulate a set of 1M oxidative bisulfite reads

As above, but with

```
  --conversion_rate 90  
  
mv simulated_1.fastq oxbs_sim_1.fastq; gzip oxbs_sim_1.fastq  
mv simulated_2.fastq oxbs_sim_2.fastq; gzip oxbs_sim_2.fastq
```

<http://www.bioinformatics.babraham.ac.uk/projects/sherman>





Serial pipeline single core/thread  
MacBook Pro

Bs-seq: 1M reads from 5Mb Region of Chr1

Total Memory: ~1.1Gb  
Run Time: 1000 seconds  
17 minutes

Full Genome  
Total Memory: ~11Gb RAM  
Run Time: ~12 Hours  
depending on #reads

- Processing a large number of samples in a consistent, documented and reproducible manner
- Optimise CPU usage with queuing system GRIDEngine, SLURM etc
- Pipelines can be custom bash scripts, Docker containers or specific pipeline tools.
- Exact versions and command line options should be recorded in log files.




<http://clusterflow.io>

Single command: `$ cf --genome GRCh38 bismark_pipeline *.fa.gz`

Pipeline outline:

```
#fastqc
#trim_galore
#bismark_align
#bismark_deduplicate
#samtools_sort coord
#preseq_lc_extrap
#preseq_bound_pop
#qualimap_bamqc
#picard_insert_size_metrics
#featureCounts
#bismark_methXtract
#bismark_report
#bismark_summary_report
>multiqc
```



FastQC

Version

A quality control tool for high throughput sequence data

0.11.5

Download

<http://www.bioinformatics.babraham.ac.uk/projects/fastqc/>

Terminal:

```
$ fastqc -q mkbs_sim_1000000_0.25_1.fastq.gz } Read 1
$ firefox mkbs_sim_1000000_0.25_1_fastqc.html

$ fastqc -q mkbs_sim_1000000_0.25_2.fastq.gz } Read 2
$ firefox mkbs_sim_1000000_0.25_2_fastqc.html
```


Output:

*HTML Reports*

```
mkbs_sim_1000000_0.25_1_fastqc.html
mkbs_sim_1000000_0.25_2_fastqc.html
```

*Archive of data/images*

```
mkbs_sim_1000000_0.25_1_1_fastqc.zip
mkbs_sim_1000000_0.25_2_fastqc.zip
```



Bioinformatics Top Tip:  
Simon Andrews' <https://sequencing.qcfail.com/>

trim\_galore      A wrapper tool around Cutadapt to consistently apply quality and adapter trimming to FastQ files  
Version            0.4.1  
Download          [http://www.bioinformatics.babraham.ac.uk/projects/trim\\_galore/](http://www.bioinformatics.babraham.ac.uk/projects/trim_galore/)

Terminal:

```
$ trim_galore --paired --gzip -q 20 \  
mkbs_sim_1000000_0.25_1.fastq.gz mkbs_sim_1000000_0.25_1.fastq.gz
```

*Diagram annotations:*

- Treat as paired-end* (bracketed over `--paired`)
- Compress output* (bracketed over `--gzip`)
- Quality score threshold* (bracketed over `-q 20`)
- Read 1* (bracketed under the first input file)
- Read 2* (bracketed under the second input file)

Output:


*Trimmed Fastq files*

```
mkbs_sim_1000000_0.25_1_val_1.fq.gz  
mkbs_sim_1000000_0.25_2_val_2.fq.gz
```

*Trimming report files*

```
mkbs_sim_1000000_0.25_1.fastq.gz_trimming_report.txt  
mkbs_sim_1000000_0.25_2.fastq.gz_trimming_report.txt
```





bismark A tool to map bisulfite converted sequence reads and determine cytosine methylation states  
 Version 0.16.3  
 Download <http://www.bioinformatics.babraham.ac.uk/projects/bismark/>

Terminal:

```

    Use bowtie2 (>50nt)      Reference Genome Location
    ┌──────────┴──────────┐
$ bismark --bowtie2 NGSchool_GRCh38_Ch1_region \
  -1 mkbs_sim_1000000_0.25_1_val_1.fq.gz -2 mkbs_sim_1000000_0.25_2_val_2.fq.gz
    └──────────────────────────────────┘ └──────────────────────────────────┘
                        Read 1                                Read 2
  
```

Output:

```

mkbs_sim_1000000_0.25_1_val_1_bismark_bt2_PE_report.txt
mkbs_sim_1000000_0.25_1_val_1_bismark_bt2_pe.bam
  
```

OSX Trouble Shooting:  
 Some versions of bismark use zcat  
 Fix by using sed to replace zcat with gunzip -c

bismark            A tool to map bisulfite converted sequence reads and determine cytosine methylation states  
Version            0.16.3  
Download           <http://www.bioinformatics.babraham.ac.uk/projects/bismark/>

Terminal:

*Paired-end*    *Output BAM format*    *Bismark alignment BAM file*

```
$ deduplicate_bismark -p -bam mkbs_sim_1000000_0.25_1_val_1_bismark_bt2_pe.bam
```

Output:

```
mkbs_sim_1000000_0.25_1_val_1_bismark_bt2_pe.deduplicated.bam  
mkbs_sim_1000000_0.25_1_val_1_bismark_bt2_pe.deduplication_report.txt
```

bismark                      A tool to map bisulfite converted sequence reads and determine cytosine methylation states  
 Version                      0.16.3  
 Download                      <http://www.bioinformatics.babraham.ac.uk/projects/bismark/>

Terminal:

```
$ bismark_methylation_extractor --ignore_r2 1 --ignore_3prime_r2 2 \
  --bedGraph --gzip -p --no_overlap --report \
  mkbs_sim_1000000_0.25_1_val_1_bismark_bt2_pe.deduplicated.bam
```


Ignore first 5' bp Read 2      Ignore the last 2 3' bp Read 2

Cytosine Methylation   Compress   PE   Ignore PE overlap   Final summary

Bismark deduplicated BAM file

Output:

```
mkbs_sim_1000000_0.25_1_val_1_bismark_bt2_pe.deduplicated.M-bias.txt
mkbs_sim_1000000_0.25_1_val_1_bismark_bt2_pe.deduplicated.M-bias_R1.png
mkbs_sim_1000000_0.25_1_val_1_bismark_bt2_pe.deduplicated.M-bias_R2.png
mkbs_sim_1000000_0.25_1_val_1_bismark_bt2_pe.deduplicated.bedGraph.gz
mkbs_sim_1000000_0.25_1_val_1_bismark_bt2_pe.deduplicated.bismark.cov.gz
mkbs_sim_1000000_0.25_1_val_1_bismark_bt2_pe.deduplicated_splitting_report.txt
```



samtools	Utilities for the Sequence Alignment/Map (SAM) format
Version	1.3.1
Download	<a href="http://www.htslib.org/download">http://www.htslib.org/download</a>

## Terminal:

```
$ samtools sort -o mkbs_sim_1000000_0.25_1_val_1_bismark_bt2_pe.srtd.bam \
mkbs_sim_1000000_0.25_1_val_1_bismark_bt2_pe.bam
```

Output coordinate sorted BAM file

Input name sorted BAM file

## Output:

```
mkbs_sim_1000000_0.25_1_val_1_bismark_bt2_pe.srtd.bam
```

samtools	Utilities for the Sequence Alignment/Map (SAM) format
Version	1.3.1
Download	<a href="http://www.htslib.org/download">http://www.htslib.org/download</a>

Terminal:

```
$ samtools index Input name sorted BAM file  
mkbs_sim_1000000_0.25_1_val_1_bismark_bt2_pe.srted.bam
```

Output:

```
mkbs_sim_1000000_0.25_1_val_1_bismark_bt2_pe.srted.bam.bai
```


Picard Tools for manipulating high-throughput sequencing (HTS) data  
 Version 2.2.4+  
 Download <http://broadinstitute.github.io/picard/>

## Terminal:

```
$ java -jar /usr/local/picard-tools-2.2.4/picard.jar CollectInsertSizeMetrics \
  INPUT=mkbs_sim_1000000_0.25_1_val_1_bismark_bt2_pe.srtd.bam } Input coord sorted BAM file
  OUTPUT=mkbs_sim_1000000_0.25_1_val_1_bismark_bt2_pe.srtd_picard_insert_size_metrics.txt
  HISTOGRAM_FILE=mkbs_sim_1000000_0.25_1_val_1_bismark_bt2_pe.srtd_picard_insert_size_plot.pdf } Outputs
  METRIC_ACCUMULATION_LEVEL=ALL_READS } Look at all reads
```

## Output:

```
mkbs_sim_1000000_0.25_1_val_1_bismark_bt2_pe.srtd_picard_insert_size_metrics.txt
mkbs_sim_1000000_0.25_1_val_1_bismark_bt2_pe.srtd_picard_insert_size_plot.pdf
```



*Usually a distribution  
 Due to simulated data*



preseq                      Predicting and estimating the complexity of a genomic sequencing library  
 Version                    2.0  
 Download                  <http://smithlabresearch.org/software/preseq/>

## Terminal:

*predict the yield for future experiments*

```
$ preseq lc_extrap -B -P -o mkbs_sim_1000000_0.25_1_val_1_bismark_bt2_pe.srtd.preseq.lc_extrap.tsv \
  mkbs_sim_1000000_0.25_1_val_1_bismark_bt2_pe.srtd.bam
```

Diagram annotations for the terminal command:

- Input BAM**: Points to the `-B` flag.
- Paired end**: Points to the `-P` flag.
- Output tab separated values**: Points to the `-o` flag and the output file path.
- Input name sorted BAM file**: Points to the input BAM file path.

## Output:

```
mkbs_sim_1000000_0.25_1_val_1_bismark_bt2_pe.srtd.preseq.lc_extrap.tsv
```

Plots unique molecules Vs molecules sequences

QualiMap	Evaluating next generation sequencing alignment data
Version	2.2
Download	<a href="http://qualimap.bioinfo.cipf.es/">http://qualimap.bioinfo.cipf.es/</a>

## Terminal:

```
$ JAVA_OPTS="-Djava.awt.headless=true"
$ qualimap bamqc -sd -c -bam mkbs_sim_1000000_0.25_1_val_1_bismark_bt2_pe.srtd.bam
```


Run as command line (useful for HPC!)

Paint chromosome limits inside charts      Input name sorted BAM file

skip duplicated alignments      Input BAM format

## Output:

```
mkbs_sim_1000000_0.25_1_val_1_bismark_bt2_pe.srtd_stats/
└─ qualimapReport.html
```



MultiQC	Aggregate results from bioinformatics analyses across many samples into a single report
Version	0.8dev
Download	<a href="http://multiqc.info/">http://multiqc.info/</a>

## Terminal:

```
$ multiqc -f -i "NGSchool.eu" --filename "NGSchool.eu.multiqc_report.html" .
```

*Annotations:*

- A title for your report* (points to "NGSchool.eu")
- Output filename* (points to "NGSchool.eu.multiqc\_report.html")
- Overwrite existing report* (points to "-f")
- “.” Is a special Linux symbol which means the current directory* (points to ".")


```
$ NGSchool.eu.multiqc_report.html
```

## Output:





### *HTML Report*

```
NGSchool.eu.multiqc_report.html
NGSchool.eu.multiqc_report_data
```

## Includes mkbs & oxbx



## Includes mkbs & oxbs







Includes mkbs & oxbs

Reads simulated for ~30X coverage

*After trimming and alignment*


- Average 27X
- ~35% genome covered at 30X




mkbs / oxbs difference = hmC

*(In oxbs hmC oxidised to fC sequences as C, therefore more C expected in oxbs)*

## Picard Insert Size Metrics



## Cutadapt





Methyl-Kit	R package for DNA methylation analysis
Version	v0.99.2
Download	<a href="https://github.com/al2na/methylKit">https://github.com/al2na/methylKit</a>

Terminal:




Custom R-script

```
$ Rscript ngschool.methylkit.R
```

Output:

<i>Plots</i>	NGSchool.eu.methylkit.PCASamples.ward_corr_plot.pdf
	NGSchool.eu.methylkit.CorrelationPlot.pdf
	NGSchool.eu.methylkit.PCASamples.screepLOT.pdf
	NGSchool.eu.methylkit.PCASamples.pdf
	NGSchool.eu.methylkit.diffMethPerChr.pdf
<i>Tables</i>	NGSchool.eu.methylkit.hyper_methylated.tsv
	NGSchool.eu.methylkit.DiffMeth.tsv
	NGSchool.eu.methylkit.hypo_methylated.tsv
	NGSchool.eu.methylkit.differentialy_methylated.tsv

## CpG base pearson cor.




*Note: This is simulated data so biologically meaningless!*


Epigenetics 8:9, 979–989; September 2013; © 2013 Landes Bioscience

RESEARCH PAPER

## Mapping the zebrafish brain methylome using reduced representation bisulfite sequencing

Aniruddha Chatterjee<sup>1,2,\*</sup>, Yuichi Ozaki<sup>3</sup>, Peter A Stockwell<sup>4,5</sup>, Julia A Horsfield<sup>1,2</sup>, Ian M Morison<sup>1,2</sup>, and Shinichi Nakagawa<sup>2,3</sup>





Top 5 by location out of 122K [NGSchool.eu.methylkit.hypo\_methylated.txt]

chr	start	end	strand	pvalue	qvalue	meth.diff
1:3000000-8000000	505	505	*	0.1586	0.0376	13.3333
1:3000000-8000000	794	794	*	0.3040	0.0400	8.3333
1:3000000-8000000	1058	1058	*	0.1974	0.0376	11.1111
1:3000000-8000000	1476	1476	*	0.3003	0.0397	6.2500
1:3000000-8000000	1811	1811	*	0.8925	0.0832	1.6667

Top 5 by location out of 8K [ NGSchool.eu.methylkit.hyper\_methylated.txt]

chr	start	end	strand	pvalue	qvalue	meth.diff
1:3000000-8000000	38	387	*	0.0821	0.0346	-22.2222
1:3000000-8000000	416	416	*	0.1526	0.0376	-15.3846
1:3000000-8000000	417	417	*	0.1667	0.0376	-12.5000
1:3000000-8000000	448	448	*	0.0255	0.0346	-33.3333
1:3000000-8000000	490	490	*	0.1736	0.0376	-11.1111

*Note: This is simulated data so biologically meaningless!*

Load the reference genome (only the 5Mb region)

IGV

└ Genomes

└ Create .genome File...

└ Select

NGSchool\_GRCh38\_Chrl\_region/Homo\_sapiens.GRCh38.dna.chromosome.1.region30000000-50000000.fa

Load the aligned reads BAM files:

IGV

└ File


└ Load From File...

SimulatedData /mkbs\_sim\_1000000\_0.25\_1\_val\_1\_bismark\_bt2\_pe.srtd.bam

SimulatedData /oxbs\_sim\_1000000\_0.25\_1\_val\_1\_bismark\_bt2\_pe.srtd.bam

mkbs

oxbs



## Oxford Nanopore Technologies

**Angewandte  
Communications**

**VIP** Epigenetic Markers

DOI: 10.1002/anie.201300413

### Single-Molecule Detection of 5-Hydroxymethylcytosine in DNA through Chemical Modification and Nanopore Analysis\*\*

Wen-Wu Li, Lingzhi Gong, and Hagan Bayley\*

bioRxiv preprint first posted online Apr. 4, 2016; doi: <http://dx.doi.org/10.1101/047134>. The copyright holder for this preprint (which was not peer-reviewed) is the author/funder. It is made available under a [CC-BY-ND 4.0 International license](#).

#### Cytosine Variant Calling with High-throughput Nanopore Sequencing

Arthur C. Rand\*, Miten Jain\*, Jordan Eizenga\*, Audrey Musselman-Brown, Hugh E.

Olsen, Mark Akeson and Benedict Paten

Department of Biomolecular Engineering, University of California, Santa Cruz.

Genomics Institute, University of California, Santa Cruz.

\*These authors contributed equally to this work.

bioRxiv preprint first posted online Apr. 4, 2016; doi: <http://dx.doi.org/10.1101/047142>. The copyright holder for this preprint (which was not peer-reviewed) is the author/funder. It is made available under a [CC-BY 4.0 International license](#).

#### Detecting DNA Methylation using the Oxford Nanopore Technologies MinION sequencer

Jared T. Simpson<sup>1,2,\*</sup>, Rachael Workman<sup>3</sup>, P.C. Zuzarte<sup>1</sup>, Matei David<sup>1</sup>, L. J. Dursi<sup>1</sup>, Winston Timp<sup>3,\*</sup>

Affiliations:

1 Ontario Institute for Cancer Research, Toronto, Canada

2 Department of Computer Science, University of Toronto, Toronto, Canada

3 Department of Biomedical Engineering, Johns Hopkins University, Baltimore, Maryland

Correspondence to:

[jared.simpson@oicr.on.ca](mailto:jared.simpson@oicr.on.ca)

[wtimp@jhu.edu](mailto:wtimp@jhu.edu)



Dr Russell S. Hamilton


Email: [rsh46@cam.ac.uk](mailto:rsh46@cam.ac.uk)

Web: <http://www.trophoblast.cam.ac.uk/directory/Russell-Hamilton>



UNIVERSITY OF  
CAMBRIDGE

Department of Physiology, Development  
and Neuroscience



License: Attribution-Non Commercial-Share Alike CC BY-NC-SA ( <https://creativecommons.org/licenses/by-nc-sa/> )

Attribution: You must give appropriate credit, provide a link to the license, and indicate if changes were made.

You may do so in any reasonable manner, but not in any way that suggests the licensor endorses you or your use.

NonCommercial: You may not use the material for commercial purposes.

ShareAlike: If you remix, transform, or build upon the material, you must distribute your contributions under the same license as the original.