

Table of Contents

- 1. Initial Settings..... 3
 - 1.1. Create a new github repo..... 3
 - 1.2. Clone an empty repo to a local computer..... 3
 - 1.3. New NPM project..... 3
 - 1.4. Telegram API credentials..... 3
 - 1.5. dotenv..... 5
 - 1.6. Index.js..... 5
 - 1.7. Install package..... 6
 - 1.8. First run..... 6

1. Initial Settings

1.1. Create a new github repo

https://github.com/ILopatenko/adekvat_chatik_bot.git

1.2. Clone an empty repo to a local computer

1.3. New NPM project

npm init -y

npm install telegram dotenv

1.4. Telegram API credentials

Go to <https://my.telegram.org/>

Use your phone number

<https://my.telegram.org/apps> – create a new app

App configuration

App api_id:	32337343	🔒
App api_hash:	ad68b6b7d5510671eaaa73086fee01b3	🔒
App title:	MyChatTestApp	
Short name:	MyChatTestApp	

alphanumeric, 5-32 characters

FCM credentials [Update](#)

WNS credentials [Update](#)

Available MTProto servers

Test configuration:	149.154.167.40:443
---------------------	---

DC 2

Public keys:

```
-----BEGIN RSA PUBLIC KEY-----
MIIBCgKCAQEAYmEdY1aR+sCR3ZSJrtztKTKqigv0/vBfqACJLZtS7QMg
CGXJ6XIR
yy7mx66W8/s0Fa7/1mAZtEoIoKDP3ShoqF4fVNB6XeqgQfaUhd8wJpDw
HcR20Fwv
pLUUI1PLTktZ9uW2WE23b+1xNwJjJGwBDJPQEQFBE+vfmH0JP503wr5I
NS1pohg/
j25sIWeYPHYeOrFp/eXaqhISP6G+q2IeTaWTPwZj4LzXq5Y0pk4bYEQ
6mvRq7D1
aHwFYmLEgepfayR8Q0YqvvhYtMte3ITnuSJs171+GDqpdKcSwHnd6Fud
wG04pcCO
j4WcDuXc2CTHgh8gFTNhp/Y8/SpD0hvn9QIDAQAB
-----END RSA PUBLIC KEY-----
```

Production configuration:	149.154.167.50:443
---------------------------	---

DC 2

Public keys:

```
-----BEGIN RSA PUBLIC KEY-----
MIIBCgKCAQEA6LszBcC1LGzYr992NzE0ieY+BSa0W622Aa9Bd4ZHLl+T
uFQ4L04g
5nKaMbwK/BIB9xUfg0Q29/2mgIR6Zr9krM7HjuIcCzFvDtr+L0GQjae9
H0pRB200
62cECs5SHKhTSDZ98K33vmWlLowc621dQuwKwSQKjWf50XYFw42h21P2K
XUGyp2y/
+aEyz+uVgLLQbRA1dEjSDZ2iGRy12Mk5gpYc397aYp438fsJohIqJ2lg
MvSh7WY9
t6N/byY9Nw9p210g3AoXSL2q/2Ij1wRUhebgAdGVMlV1fku0Q0EzR7Ed
pqTQD9Cs
5+bfo3Nhmcyk5ftB0WkJ9z6bNZ7yxrP8wIDAQAB
-----END RSA PUBLIC KEY-----
```

[Save changes](#) [Cancel](#)

App api_id:

32337343

App api_hash:

ad68b6b7d5510671eaaa73086fee01b3

Test configuration:

149.154.167.40:443

-----BEGIN RSA PUBLIC KEY-----

MIIBCgKCAQEAyMEdY1aR+sCR3ZSJrtztKTKqigvO/vBfqACJLZtS7QMgCGXJ6XIR
yy7mx66W0/sOFa7/1mAZtEoIokDP3ShoqF4fVNB6XeqgQfaUhd8wJpDWHcR2OFwv
plUUI1PLTktZ9uW2WE23b+ixNwJjJGwBDJPQE QFBE+vmH0JP503wr5INS1poWg/
j25sIWeYPHYeOrFp/eXaqhISP6G+q2IeTaWTPwZj4LzXq5YOpk4bYEQ6mvRq7D1
aHWfYmlEGepfaYR8Q0YqvvhYtMte3ITnuSJs171+GDqpdKcSwHnd6FudwGO4pcCO
j4WcDuXc2CTHgH8gFTNhp/Y8/SpDOhvn9QIDAQAB

-----END RSA PUBLIC KEY-----

Production configuration:

149.154.167.50:443

-----BEGIN RSA PUBLIC KEY-----

MIIBCgKCAQEA6LszBcC1LGzyr992NzE0ieY+BSaOW622Aa9Bd4ZHLl+TuFQ4lo4g
5nKaMBwK/BIb9xUfg0Q29/2mgIR6Zr9krM7HjuIcCzFvDtr+L0GQjae9H0pRB2OO
62cECs5HKhT5DZ98K33vmWiLowc621dQuwKWSQKjWf50XYFw42h21P2KXUGyp2y/
+aEyz+uVgLLQbRA1dEjSDZ2iGRy12Mk5gpYc397aYp438fsJoHIgJ2lgMv5h7WY9
t6N/byY9Nw9p21Og3AoXSL2q/2IJ1WRUhebgAdGVMLV1fkuOQoEzR7EdpqtQD9Cs
5+bfo3NhmcyvK5ftB0WkJ9z6bNZ7yxrP8wIDAQAB

-----END RSA PUBLIC KEY-----

1.5. dotenv

Create a new file .env in the root folder of your project

```
API_ID=[API_ID]
```

```
API_HASH=[API_HASH]
```

1.6. Index.js

Create a main file index.js

```
require('dotenv').config();

const fs = require('fs');
const { TelegramClient } = require('telegram');
const { StringSession } = require('telegram/sessions');
const { NewMessage } = require('telegram/events');
const input = require('input');

const API_ID = Number(process.env.API_ID);
const API_HASH = process.env.API_HASH;
const OWNER_ID = '8910735441';

const SESSION_FILE = 'telegram.session';

let session = '';

if (fs.existsSync(SESSION_FILE)) {
  session = fs.readFileSync(SESSION_FILE, 'utf8');
}

const client = new TelegramClient(new StringSession(session), API_ID, API_HASH, {
  connectionRetries: 5,
});

async function main() {
  await client.start({
    phoneNumber: async () => await input.text('Phone number: '),
    password: async () => await input.text('2FA password: '),
    phoneCode: async () => await input.text('Telegram code: '),
    onError: error => console.error(error),
  });

  fs.writeFileSync(SESSION_FILE, client.session.save());

  const me = await client.getMe();

  console.log('Connected!');
  console.log('Logged in as: ${me.firstName || ''}');
  console.log('Telegram ID: ${me.id}');
  console.log('Owner ID: ${OWNER_ID}');
  console.log('Waiting for messages...');

  client.addEventHandler(async event => {
    const message = event.message;

    if (!message) {
      return;
    }

    if (!message.isPrivate) {
      return;
    }

    const senderId = message.senderId?.toString();

    console.log(`Message from: ${senderId}`);

    if (senderId !== OWNER_ID) {
      await message.reply({
        message: 'Ты Кто Такой?',
      });
      return;
    }
  });
}
```

```
    if (!message.message) {  
      return;  
    }  
  
    console.log(`Owner: ${message.message}`);  
  
    await message.reply({  
      message: 'Привет! Я тебя вижу 🙌',  
    });  
  }, new NewMessage({}));  
}  
  
main().catch(console.error);
```

1.7. Install package

npm install input

1.8. First run

Node index.js