

Web API testing end2end





The speaker

Illia Levandovskyi

lead software developer @Luxoft

dotnet trainer

global dotnet chapter lead





The web api

TaxCalculator.App ^{1.0} ^{OAS3}

<https://localhost:7271/swagger/v1/swagger.json>

TaxCalculator



GET

/api/TaxCalculator/Calculate



POST

/api/TaxCalculator/CalculateForRange





Testing controller instance

```
public TaxCalculatorControllerTests(ITestOutputHelper output)
{
    _output = output;
    _scope = new ServiceCollection()
        .AddScoped<ICalculator, Calculator>()
        .AddScoped<IRangeCalculator>(_ => new Mock<IRangeCalculator>().Object) //is not
        .AddScoped<ITaxationRuleProvider, InMemoryTaxationRuleProvider>()
        .Decorate<ITaxationRuleProvider, TaxationRuleRepository>()
        .AddScoped<ITaxationRuleStorage>(_ => new Mock<ITaxationRuleStorage>().Object) //
        .AddScoped<TaxCalculatorController>()
        .BuildServiceProvider(validateScopes: true)
        .CreateScope();

    _controller = _scope.ServiceProvider.GetRequiredService<TaxCalculatorController>();
    _calculator = _scope.ServiceProvider.GetRequiredService<ICalculator>();
}
```

0 references | Cyclomatic complexity: 1

```
public void Dispose() => _scope.Dispose();
```



What is not covered so far

Reading config from appsettings.json

Routing

Serialization/deserialization issues

Request/response caching issues

Middleware and Action/Exception filters

HostedServices

Higher viscosity due to absent Mother Object



How to solve all of these issues?

Reading config from appsettings.json

Routing

Serialization/deserialization issues

Request/response caching issues

Middleware and Action/Exception filters

HostedServices

Higher viscosity due to absent Mother Object



In memory integration tests

Launches Kestrel and your web app in memory, as if you debug the app

- => reads all configuration

- => consumes your app's Composition Root

- => you can send http(s) requests (check routing, serialization, caching, filters & middleware)

- => your tests depend on the web api, not the classes composition (are more robust)

And a cherry on the top - you still can customize it.



Setup steps

Rely on `Microsoft.NET.Sdk.Web`

Install NuGet `Microsoft.AspNetCore.Mvc.Testing`

For xunit use `xunit.runner.json` with `{"shadowCopy": false}`

For test class use `IClassFixture<WebApplicationFactory<Program>>`

requires: `public partial class Program { }`



When you have Startup class

Inject into your test classes `IClassFixture<WebApplicationFactory<Startup>>`

requires:

```
public static IHostBuilder CreateHostBuilder(string[] args) => Host
    .CreateDefaultBuilder(args)
    .ConfigureWebHostDefaults(webBuilder => webBuilder.UseStartup<Startup>());
```



How to customize?

Inherit `WebApplicationFactory<T>`

Override `ConfigureWebHost()`

Use `ConfigureTestServices()` to `Replace()` or `Remove()` DI-registrations.

Provide environment with `UseEnvironment()`



Replacing decorated entities - failure

```
builder.Services.TryAddScoped<ITaxationRuleProvider, InMemoryTaxationRuleProvider>();  
builder.Services.Decorate<ITaxationRuleProvider, TaxationRuleRepository>();  
builder.Services.TryAddScoped<ITaxationRuleStorage>(implementationFactory: sp =>  
    (sp.GetRequiredService<ITaxationRuleProvider>()) as ITaxationRuleStorage)!);
```

ServiceDescriptor

ServiceType: TaxCalculator.App.Calculators.IRangeCalculator Lifetime: Scoped ImplementationType: TaxCalculator.App.Calculators.RangeCalculator

ServiceType: Type: ITaxationRuleProvider+Decorated Lifetime: Scoped ImplementationType: TaxCalculator.App.RuleProviders.InMemoryTaxationRuleProvider

ServiceType: TaxCalculator.App.RuleProviders.ITaxationRuleStorage Lifetime: Scoped ImplementationFactory: TaxCalculator.App.RuleProviders.ITaxationRuleStorage <<Main>\$>b_0_0(System.IServiceProvider)

ServiceType: TaxCalculator.App.Calculators.ICalculator Lifetime: Scoped ImplementationFactory: System.Object <ConfigureWebHost>b_0_1(System.IServiceProvider)

IEnumerable Visualizer

Expression: services

tax



ServiceDescriptor

ServiceType: TaxCalculator.App.Calculators.IRangeCalculator Lifetime: Scoped ImplementationType: TaxCalculator.App.Calculators.RangeCalculator

ServiceType: TaxCalculator.App.RuleProviders.ITaxationRuleStorage Lifetime: Scoped ImplementationFactory: TaxCalculator.App.RuleProviders.ITaxationRuleStorage <<Main>\$>b_0_0(System.IServiceProvider)

ServiceType: TaxCalculator.App.Calculators.ICalculator Lifetime: Scoped ImplementationFactory: System.Object <ConfigureWebHost>b_0_1(System.IServiceProvider)

ServiceType: TaxCalculator.App.RuleProviders.ITaxationRuleProvider Lifetime: Scoped ImplementationType: TaxCalculator.InMemoryTests.InfiniteTaxationRuleProvider



IHostedService || BackgroundService

Is run with in memory tests

Could be removed from the DI-container manually



Microsoft.AspNetCore.Mvc.Testing

test web host

Copies .deps into the test project's bin folder

Sets the content root to the sut

Provides bootstrapping in-memory test server via WebApplicationFactory



Shadow copy

Shadow copying causes the tests to execute in a different directory than the output directory. If your tests rely on loading files relative to `Assembly.Location` and you encounter issues, you might have to disable shadow copying.



References

Microsoft's guide for [Integration tests](#).

Pluralsight trainings by [Steve Gordon](#) and [Steve Smith](#).

Source code is available via the QR-code or by the [link](#).

