SKYWORTH
Your Best Friend of Energy-Saving Solutions

SWS 261kWh

C&I Energy Storage System

MODEL

SWS-P125E261-HC-G2



Smart Control & Monitoring
· Smart load control with dry contacts
· Smart home integration with multi-protocol communications

Friendly & Thoughtful Design
· Plug & Play
· Elegant and compact design

Superb Safety & Reliability
· Optional AFCI on DC side[1]
· Remote Shutdown

Flexible & Adaptable Applications
· Compatible with lithium-ion & lead-acid batteries
· Maximum 16A DC input current per string and high-power module compatibility
· Strong backup power supply

1: Optional functions or devices are purchased separately.

Global-V1.04-2026EN

Shenzhen SKYWORTH Photovoltaic Technology Co., Ltd.
All Rights Reserved @Shenzhen SKYWORTH Photovoltaic Technology Co., LTD. Please refer to the latest version for any updates

Model	SWS-P125E261-HC-G2
Battery Data	
Cell Type	LFP ($LiFePO_4$)
Cell Capacity (Ah)	314
Module Nominal Energy (kWh)	52.25
Number of Packs	5
Rack Nominal Energy (kWh)	261.25
Rack Usable Energy (kWh)	261.25
Nominal Voltage (V)	832
Operating Voltage Range (V)	676 ~ 936
Max. Continuous Charge / Discharge Current (A)	188
Max. Charge / Discharge Current (A)	198.5
Max. Charge / Discharge Rate	0.5P
Depth of Discharge	90% ~ 100% (90% Recommended)
AC Output Data (On-grid)	
Nominal Output Power (kW)	125
Max. Output Power (kW)	137.5@400V AC; 130.6@380V AC
Nominal Apparent Power (kVA)	125
Nominal Apparent Power Output to Utility Grid (kVA)	125
Nominal Apparent Power from Utility Grid (kVA)	125
Max. Apparent Power (kVA)	137.5@400V AC; 130.6@380V AC
Max. Apparent Power Output to Utility Grid (kVA)	137.5@400V AC; 130.6@380V AC
Max. Apparent Power from Utility Grid (kVA)	137.5@400V AC; 130.6@380V AC
Nominal Output Voltage (V)	400 / 380, 3L / N / PE
Output Voltage Range (V)	340 ~ 440 / 323 ~ 418
Nominal AC Grid Frequency (Hz)	50 / 60
AC Grid Frequency Range (Hz)	47.5 ~ 52.5 / 57.5 ~ 62.5
Max. AC Output Current (A)	198.5
Max. AC Current Output to Utility Grid (A)	198.5
Max. AC Current from Utility Grid (A)	198.5
Nominal Output Current (A)	180.4@400V AC; 189.9@380V AC
Power Factor	~1 (0.8 lag to 0.8 lead)
Max. Total Harmonic Distortion	<3%
AC Output Data (Off-grid)	
Nominal Output Power (kW)	125
Max. Output Power (kW)	137.5@400V AC; 130.6@380V AC
Nominal Apparent Power (kVA)	125
Nominal Output Apparent Power to Grid (kVA)	125
Nominal Input Apparent Power from Grid (kVA)	125
Max. Apparent Power (kVA)	137.5@400V AC; 130.6@380V AC
Max. Output Apparent Power to Grid (kVA)	137.5@400V AC; 130.6@380V AC
Max. Input Apparent Power from Grid (kVA)	137.5@400V AC; 130.6@380V AC
Nominal Output Voltage (V)	400 / 380, 3L / N / PE
Output Voltage Range (V)	340 ~ 440 / 323 ~ 418
Nominal Output Frequency (Hz)	50 / 60
AC Grid Frequency Range (Hz)	47.5 ~ 52.5 / 57.5 ~ 62.5
Max. AC Output Current (A)	198.5
Max. AC Current Output to Grid (A)	198.5
Max. AC Current from Grid (A)	198.5
Nominal Output Current (A)	180.4@400V AC; 189.9@380V AC
Power Factor	~1 (0.8 lag to 0.8 lead)
Output THDi (@Linear Load)	<3%
Efficiency	
Max. PCS Efficiency	98.6%
System Efficiency	92.0%
Protection	
Battery Reverse Polarity Protection	●
Anti-islanding Protection	●
AC Overcurrent Protection	●
AC Short Circuit Protection	●
AC Surge Protection	Type II
General Data	
Operation Temperature Range (℃)	-25 ~ +55
Derating Temperature (℃)	45
Storage Temperature (℃)	-20 ~ +45 (One Month); 0 ~ +35 (One Year)
Relative Humidity	10% ~ 95%
Max. Operating Altitude (m)	4000 (2000 derating)
Cooling Method	Pack: Liquid Cooling; PCS: Smart Fan Cooling
User Interface	LED, WLAN + APP
Communication Protocol	Modbus TCP, Modbus RTU
Weight (kg)	2580
Dimension (W × H × D mm)	1050 × 2250 × 1400
Noise Emission (dB)	≤70
Topology	Non-isolated
Ingress Protection Rating	IP54
Anti-Corrosion	C4 (C5 optional)
Configuration of Safety	Aerosol + water-based fire suppression, explosion-proof fan + explosion-proof plates (optional)
Charge / Discharge Switching Time	<60ms

● Integrated ○ Optional

*: Please visit SKYWORTH website for the latest certificates.

SKYWORTH
Your Best Friend of Energy-Saving Solutions

400-063-8989 solar.overseas@skyworth.com www.skyworth-pv.com

Add: Room No.0801, C Block, 5th Building, HuaQiang Creative Park,Guangming Street, Guangming District, Shenzhen