SKYWORTH
Your Best Friend of Energy-Saving Solutions

SWR
5.12/10.24/16.08kWh

MODEL

SWR5.12-L1-WW | SWR10.24-L1-WW | SWR16.08-L1-WW



· 1C/1C continuous charge and discharg
· Max. 16modules parallel

· Flexible installationsaving time and effort
· Battery Equalization
Supports for mixing modules
underdifferent SOC to ensure battery life

· 10 yearsstandard warranty
· All-round Safety
Short-circuit lockout, surge-resistant,
safe, and reliable

· Automatic Self-heating
-20℃ to 55℃operating temperature(optional)
· IP65 Protection
Fearless of outdoor installation,
strong environmental adaptability

Global-V1.07-2026EN

Shenzhen SKYWORTH Photovoltaic Technology Co., Ltd.
All Rights Reserved @Shenzhen SKYWORTH Photovoltaic Technology Co., LTD. Please refer to the latest version for any updates

Product Model	SWR5.12-L1-WW	SWR10.24-L1-WW	SWR16.08-L1-WW
Rated Voltage		51.2V	
Rated Capacity	100Ah	200Ah	314Ah
Rated Energy	5.12kWh	10.24kWh	16.08kWh
Standard Charge Voltage		56.8V	
Discharge Cut-Off Voltage		44.8V	
Max. Charging Curent	100A	150A	200A
Max. Discharging Curent	100A	150A	200A
Dimension L x W x H(mm)	600 x 480 x 180mm (Excluding Wall-Mounted Brackets)	650 x 480 x 245mm (Excluding Wal-Mounted Brackets)	840 x 490 x250mm (Excluding Wheels)
Weight(kg)	52Kg	98Kg	128Kg
Charge Temperature		0~55℃	
Discharging Temperature		-20~55℃	
Cycle Life	>8000 Cycles(25℃±2℃,0.5C,90%DOD)		≥10000 Cycles(25℃±2℃,0.35C,90%DOD)
Installation Method		Wall-Mounted/Floor Standing	
Protection Grade		IP65	
Communication Interface		RS485, RS232, CAN	
Optional		Automatic Heating, Fire Extinguishing Module, WiFi Remote Monitoring	
Max. units in parallel		16 pcs	

*1: Conditions apply, refer to SKYWORTH warranty letter.

SKYWORTH
Your Best Friend of Energy-Saving Solutions

400-063-8989 solar.overseas@skyworth.com www.skyworthsolar.com

Add: Room No.0801, C Block, 5th Building, HuaQiang Creative Park,Guangming Street, Guangming District, Shenzhen