SKYWORTH
Make Every Ray of Sunshine Count

SWO 6000W

Single-Phase Off-grid Solar Storage Inverter

MODEL

SWO6000L-S1-SR



High Performance
· 2 High-Efficiency MPPT Input, efficiency up to 99.9%
· Max. Input Current per MPPT 22A
· Generator peak-shaving function to effectively reduce diesel generator load pressure
· Energy-saving mode reduce no-load energy loss

Friendly & Thoughtful Design
· Large LCD screen with dynamic flow chart design
· Generator port with independent design and smart load compatibility

Superb Safety & Reliability
· Rated IP65, suitable for outdoor use

Smart Control & Monitoring
· 2 power supply modes: PV-only, hybrid charging
· Support time-sharing charge and discharge function
· HOME LOAD mode, supports external load anti-backflow function
· Dual activation function for lithium batteries

1: Optional functions or devices are purchased separately

Global-V1.04-2026EN

Shenzhen SKYWORTH Photovoltaic Technology Co., Ltd.
All Rights Reserved @Shenzhen SKYWORTH Photovoltaic Technology Co., LTD. Please refer to the latest version for any updates

Technical Data	SWO6000L-S1-SR
AC Output	
Rated Output Power	6000W
Max. Peak Power	2 times of rated power,10s
Rated Output Voltage	230Vac (200/208/220/230/240Vac Settable)
Rated Output Current	26.1Aac
Rated Frequency	50Hz / 60Hz
Waveform	Pure sine wave
Switch Time	10ms (Typical)
Battary	
Battery Type	Lithium-ion Battery / Lead-acid Battery / User-defined Battery
Rated Battery Voltage	48Vdc
Battery Voltage Range	40Vdc ~ 60Vdc
Max. Discharging Current	135Adc
Max. Grid/Generator Charging Current	135Adc
Max. PV Charging Current	135Adc
PV Input	
No. of MPPT Trackers	2
Max. Access Power	12000W
Max. PV Input Power	6000W + 6000W
Max. PV Input Current	22Adc + 22Adc
Max. Input Short-Circuit Current	33Adc + 33Adc
Max. Input Voltage	500Vdc / 500Vdc
PV Start-up Voltage	60Vdc / 60Vdc
MPPT Operating Voltage Range	65Vdc ~ 450Vdc / 65Vdc ~ 450Vdc
Grid/Generator Input	
Rated Input Voltage	220Vac / 230Vac
Input Voltage Range	(170Vac ~ 280Vac) ±2%
Input Frequency Range	50Hz : 47Hz ~ 55Hz, with ±0.3Hz accuracy 60Hz : 57Hz ~ 65Hz, with ±0.3Hz accuracy
Bypass Overload Current	40Aac
Efficiency	
MPPT Tracking Efficiency	99.9%
Max. Efficiency	97.5%
GENERAL DATA	
Parallel Capacity	1～6 Units
Dimension	300x460x217.5mm
Cooling Method	Heat sink + intelligent air cooling
Weight	17.5kg
Warranty	5 years
Protection Degree	IP65
Built-in Interface	RS485/CAN/USB/Dry Contact
Temperature	-40 ~ 60°C, >45°C Derated
External Module	WiFi (Optional)
Noise	<55dB
Certificate RoHs	RoHs, IEC 62109-1/-2, EN 61000

PROTECTION

Has PV input current limiting protection、PV input over-voltage、PV night reverse current protection、AC input over-voltage protection、AC input under-voltage protection、Battery over-voltage protection、Battery under-voltage Protection、Battery over-current protection、AC output short-circuit protection、Heat sink over-temperature protection、Inverter over-load protection.

solar.overseas@skyworth.com www.skyworth-pv.com
Add: Room No.0801, C Block, 5th Building, HuaQiang Creative Park,Guangming Street, Guangming District, Shenzhen