SKYWORTH

SWR
5kWh
High Voltage Battery



MODEL

SWR5.12-H1-GS

Smart Control
- Remote diagnosis and update via inverter
- Auto reboot after undervoltage

Friendly & Thoughtful Design
- Sleek and modern design
- Plug and play wiring

Superb Safety & Reliability
- Reliable LFP technology with high cycle stability
- IP66 protection for outdoor installation safety

Flexible & Adaptable Applications
- Modular design for parallel connection
- Supports mixing new and old battery packs for flexible expansion

Model		SWR5.12-H1-GS
MAIN INFO		
Usable Energy (kWh)*1		5
Cell Type		LFP ($LiFePO_4$)
Nominal Voltage (V)		Charge: 435; Discharge: 380
Output Voltage (V)		320 ~ 480
Nominal Power (kW)*2		3
Peak Power*2		5kW, 10s
Operating Temperature Range (°C)		Charge: 0 ~ +53; Discharge: -20 ~ +53
Relative Humidity		0 - 95%
Max. Operating Altitude (m)		4000
Communication		CAN
Weight (kg)		52
Dimensions (W × H × D mm)		700 × 380 × 170
Ingress Protection Rating		IP66
Mounting Method		Floor stacked / Wall-mounted
Standard and Certification	Safety	IEC62619, IEC60730, VDE2510-50, CE, CEC
	EMC	CE, RCM
	Transportation	UN38.3

*1: Test conditions,100% DOD,0.2C charge & discharge at +25 ±3°C for battery system at beginning life. System Usable Energy may vary with different Inverter.

*2: Power derating will occur related to Temperature and SOC.

*: Please visit SKYWORTH website for the latest certificates.

*: All pictures shown are for reference only. Actual appearance may vary.

SKYWORTH
00751.HK
Tel: 400-063-8989 Email: solar.overseas@skyworth.com www.skyworth-pv.com

All Rights Reserved @Shenzhen Skyworth Photovoltaic Technology Co.,Ltd. Please refer to the latest version for any updates.