

Totally Integrated Automation Portal		
--------------------------------------	--	--

HMI_1 [TP900 Comfort]

HMI_1

General

Name	HMI_1
------	-------

Totally Integrated Automation Portal

HMI_1 [TP900 Comfort]

Runtime settings

General

Start screen	La Bilbainada GmbH	Load name information	Enabled	Default template	
Default style of the project	Enabled	Style of the HMI device	WinCC Dark V 1.0.1	Adapt font size to style	Enabled
Screen resolution	800, 480	Color depth	32 bit	Lock task switching	Disabled
Project ID	0	Logging language	Startup language		

Services

Sm@rtAccess or service: start Sm@rtServer	Disabled	Operate as OPC server	Disabled	Sm@rtAccess: SIMATIC HMI HTTP server	Disabled
Sm@rtAccess: Web service (SOAP)	Disabled	Sm@rtService: HTML pages	Disabled	Name of SMTP server	
Port	25	Name of the SMTP sender		SMTP authentication	
SMTP login		Secure connection for SMTP	Disabled		

Screens

Bit selection for appearance analysis	Off	Bit selection for text and graphic lists	Off	Display limit values as a tooltip	Enabled
Show script comments	Disabled	Scrolling mode	Scroll bar		

Keyboard

Use screen keyboard	Enabled	Release button on exit	Disabled
---------------------	---------	------------------------	----------

Good Manufacturing Practice

Configuration conforms to GMP	Disabled
-------------------------------	----------

Alarms

Controller alarms

Buffer overflow	10 %	Acknowledgment group text	QGR	Reporting	Enabled
Use alarm class color	Disabled	Use help texts for system diagnostics	Enabled	System event duration	2 Seconds
S7 diagnostic alarms with numbers only	Disabled	S7 diagnostic alarms with numbers and texts	Disabled	SIMOTION diagnostic alarms	Disabled
PersistentAlarmBuffer	Enabled	Connection	HMI_Connection_2	Display classes	0-16

User administration

Change initial password	Disabled	Change logoff time	Enabled	Enable limit for logon attempts	Enabled
Invalid logon attempts	3	Logon with password	Disabled	Group-specific rights	Disabled
Password aging	Disabled	Validity period	90	Warning period	7
Password generations	3	At least one special character	Disabled	At least one number	Disabled
Minimum password length	3	SIMATIC Logon	Disabled	Apply user administration from	WinDomain
Server name		Port number	16389	Windows domain	
Encrypted SIMATIC Logon	Enabled				

Language & font

Preset runtime language	English (United States)
-------------------------	-------------------------

English (United States)

Runtime language	Enabled	Fallback Font 1	Tahoma	Fallback Font 2	Courier New
Default font	Tahoma, 13 Pixel	Configured font 1		Configured font 2	

OPC settings

OPC UA server port number	4870	OPC UA server URL	opc.tcp://[HostName]:4870	No OPC UA server security	Enabled
No OPC UA server security	Enabled	OPC UA server with 128-bit RSA cryptographic system	Enabled	OPC UA server with 128-bit RSA cryptographic system without signature	Disabled
OPC UA server with 128-bit RSA cryptographic system for signatures	Disabled	OPC UA server with 128-bit cryptographic system for signatures and encryption	Enabled		

Tag settings

Replace the separators on each sub-level of the path of the PLC tag:	Enabled	Compatibility mode: Set '_' between the PLC tags and the first-level element.	Disabled	Replace the '.' character if the name of the HMI tag is created from the PLC tag name	Enabled
Use '_' as the replacement character	Enabled	Use ';' as the replacement character	Disabled	Replace the characters '[' and ']' if the name of the HMI tag is created from the PLC tag name	Enabled
Use '{' and '}' as replacement characters	Enabled	Use '(' and ')' as replacement characters	Disabled		

Settings for the prefix 'PLC' in the HMI tag name

Connection	HMI_Connection_2	PLC name as prefix in the HMI tag name	Disabled
------------	------------------	--	----------

HMI_1 [TP900 Comfort] / Screens

La Bilbainada GmbH

Hardcopy of La Bilbainada GmbH



Pick & Place Cell

Iñigo Mamolar Murias

1Run

3EM

2EoC

5Stop

4Rearm



State

Tray Left

OK Pieces

0000

NOK Pieces

0000

Tray Left

0

Pieces in Tray

0

Current Hole

0

General					
Name	La Bilbainada GmbH	Background color	255, 255, 255	Grid color	255, 255, 255
Number	1	Template	Template_1	Tooltip	

Layers	
Active layer	0

Layer_0	Enabled
Layer_1	Enabled
Layer_2	Enabled
Layer_3	Enabled
Layer_4	Enabled
Layer_5	Enabled
Layer_6	Enabled
Layer_7	Enabled
Layer_8	Enabled
Layer_9	Enabled
Layer_10	Enabled
Layer_11	Enabled
Layer_12	Enabled
Layer_13	Enabled
Layer_14	Enabled
Layer_15	Enabled
Layer_16	Enabled
Layer_17	Enabled
Layer_18	Enabled
Layer_19	Enabled
Layer_20	Enabled
Layer_21	Enabled
Layer_22	Enabled
Layer_23	Enabled
Layer_24	Enabled
Layer_25	Enabled
Layer_26	Enabled
Layer_27	Enabled
Layer_28	Enabled
Layer_29	Enabled
Layer_30	Enabled
Layer_31	Enabled

Dynamizations\Event	
Event name	Loaded

Function list\SetTag	
----------------------	--

Tag	Tag_ScreenNumber	Value	1
-----	------------------	-------	---

Button_1	
----------	--

Type	Button
------	--------

General					
Mode	Feedback with text	Text OFF	Run	Text ON	Run

Totally Integrated Automation Portal						
--------------------------------------	--	--	--	--	--	--

Text list		Graphic OFF		Graphic ON	
Graphic list		Process value		Bit number	
				0	
Appearance					
Background color		Background fill pattern		Corner radius (border)	
99, 101, 113		Vertical gradient		3	
Foreground color		Border width		Line style	
255, 255, 255		2		Solid	
Border color		Border background color			
71, 73, 87		105, 105, 105			
Fill pattern					
Background color gradient (fill pattern)		Gradient 1 (fill pattern)		Color gradient 1 (fill pattern)	
99, 101, 113		Enabled		131, 132, 142	
Offset gradient 1 (fill pattern)		Gradient 2 (fill pattern)		Color gradient 2 (fill pattern)	
15		Enabled		88, 90, 103	
Offset gradient 2 (fill pattern)					
15					
Design					
Focus width		Focus color			
2		148, 182, 231			
Layout					
X position		Y position		Width	
8		40		75	
Height		Fit graphic to size		Horizontal alignment of the graphic	
32		Stretch graphic		Centered	
Vertical alignment of the graphic		Fit object to contents		Margin left text (layout)	
Middle		Disabled		0	
Margin top text (layout)		Margin right text (layout)		Margin bottom text (layout)	
0		0		0	
Margin left graphic (layout)		Margin top graphic (layout)		Margin right graphic (layout)	
0		0		0	
Margin bottom graphic (layout)					
0					
Text format					
Font		Orientation		Horizontal alignment of the text	
Tahoma, 13px, style=Bold		Horizontal		Centered	
Vertical alignment of the text					
Middle					
Flashing					
Flashing					
Disabled					
Styles/Designs					
Use style/design		Style item appearance			
Disabled					
Miscellaneous					
Name		Layer		Tooltip	
Button_1		0 - Layer_0			
Security					
Authorization		Allow operator control			
		Enabled			

Dynamizations\Event	
Event name	Press

Function list\InvertBit	
Tag	Run

Function list\ResetBit	
Tag	Stop

Function list\ResetBit	
Tag	Rearm

Dynamizations\Appearance					
Tag - Cycle	Run -	Data type	Range	Range	1..1
Foreground color	255, 255, 255	Background color	51, 153, 102	Flashing	No

Button_2					
Type	Button				
General					
Mode	Text	Text OFF	EoC	Text ON	Text
Text list		Graphic OFF		Graphic ON	
Graphic list		Process value		Bit number	0
Appearance					
Background color		Background fill pattern		Corner radius (border)	
99, 101, 113		Vertical gradient		3	
Foreground color		Border width		Line style	
255, 255, 255		2		Solid	
Border color		Border background color			
71, 73, 87		105, 105, 105			
Fill pattern					
Background color gradient (fill pattern)		Gradient 1 (fill pattern)		Color gradient 1 (fill pattern)	
99, 101, 113		Enabled		131, 132, 142	
Offset gradient 1 (fill pattern)		Gradient 2 (fill pattern)		Color gradient 2 (fill pattern)	
15		Enabled		88, 90, 103	
Offset gradient 2 (fill pattern)					
15					
Design					
Focus width		Focus color			
2		148, 182, 231			
Layout					
X position		Y position		Width	
224		40		75	
Height		Fit graphic to size		Horizontal alignment of the graphic	
32		Stretch graphic		Centered	

Totally Integrated Automation Portal						
--------------------------------------	--	--	--	--	--	--

Vertical alignment of the graphic	Middle	Fit object to contents	Disabled	Margin left text (lay-out)	0
Margin top text (lay-out)	0	Margin right text (lay-out)	0	Margin bottom text (layout)	0
Margin left graphic (layout)	0	Margin top graphic (layout)	0	Margin right graphic (layout)	0
Margin bottom graphic (layout)	0				
Text format					
Font	Tahoma, 13px, style=Bold	Orientation	Horizontal	Horizontal alignment of the text	Centered
Vertical alignment of the text	Middle				
Flashing					
Flashing	Disabled				
Styles/Designs					
Use style/design	Disabled	Style item appearance			
Miscellaneous					
Name	Button_2	Layer	0 - Layer_0	Tooltip	
Security					
Authorization		Allow operator control	Enabled		

Dynamizations\Event					
Event name		Press			

Function list\InvertBit					
Tag		EoC			

Function list\ResetBit					
Tag		Run			

Dynamizations\Appearance					
Tag - Cycle	EoC -	Data type	Range	Range	1..1
Foreground color	255, 255, 255	Background color	255, 102, 0	Flashing	No

Button_4					
Type	Button				
General					
Mode	Text	Text OFF	EM	Text ON	Text
Text list		Graphic OFF		Graphic ON	
Graphic list		Process value		Bit number	0
Appearance					
Background color	99, 101, 113	Background fill pattern	Vertical gradient	Corner radius (border)	3
Foreground color	255, 255, 255	Border width	2	Line style	Solid
Border color	71, 73, 87	Border background color	105, 105, 105		
Fill pattern					
Background color gradient (fill pattern)	99, 101, 113	Gradient 1 (fill pattern)	Enabled	Color gradient 1 (fill pattern)	131, 132, 142
Offset gradient 1 (fill pattern)	15	Gradient 2 (fill pattern)	Enabled	Color gradient 2 (fill pattern)	88, 90, 103
Offset gradient 2 (fill pattern)	15				
Design					
Focus width	2	Focus color	148, 182, 231		
Layout					
X position	119	Y position	40	Width	75
Height	32	Fit graphic to size	Stretch graphic	Horizontal alignment of the graphic	Centered
Vertical alignment of the graphic	Middle	Fit object to contents	Disabled	Margin left text (lay-out)	0
Margin top text (lay-out)	0	Margin right text (lay-out)	0	Margin bottom text (layout)	0
Margin left graphic (layout)	0	Margin top graphic (layout)	0	Margin right graphic (layout)	0
Margin bottom graphic (layout)	0				
Text format					
Font	Tahoma, 13px, style=Bold	Orientation	Horizontal	Horizontal alignment of the text	Centered
Vertical alignment of the text	Middle				
Flashing					
Flashing	Disabled				
Styles/Designs					
Use style/design	Disabled	Style item appearance			
Miscellaneous					
Name	Button_4	Layer	0 - Layer_0	Tooltip	
Security					
Authorization		Allow operator control	Enabled		

Dynamizations\Event					
Event name		Press			

--	--	--	--	--	--

Totally Integrated Automation Portal						
--------------------------------------	--	--	--	--	--	--

Function list\InvertBit

Tag

EM

Function list\ResetBit

Tag

Run

Dynamizations\Appearance

Tag - Cycle	EM -	Data type	Range	Range	1..1
Foreground color	255, 255, 255	Background color	255, 0, 0	Flashing	No

Button_5

Type	Button				
General					
Mode	Text	Text OFF	Rearm	Text ON	Text
Text list		Graphic OFF		Graphic ON	
Graphic list		Process value		Bit number	0
Appearance					
Background color	99, 101, 113	Background fill pattern	Vertical gradient	Corner radius (border)	3
Foreground color	255, 255, 255	Border width	2	Line style	Solid
Border color	71, 73, 87	Border background color	105, 105, 105		
Fill pattern					
Background color gradient (fill pattern)	99, 101, 113	Gradient 1 (fill pattern)	Enabled	Color gradient 1 (fill pattern)	131, 132, 142
Offset gradient 1 (fill pattern)	15	Gradient 2 (fill pattern)	Enabled	Color gradient 2 (fill pattern)	88, 90, 103
Offset gradient 2 (fill pattern)	15				
Design					
Focus width	2	Focus color	148, 182, 231		
Layout					
X position	121	Y position	102	Width	75
Height	32	Fit graphic to size	Stretch graphic	Horizontal alignment of the graphic	Centered
Vertical alignment of the graphic	Middle	Fit object to contents	Disabled	Margin left text (layout)	0
Margin top text (layout)	0	Margin right text (layout)	0	Margin bottom text (layout)	0
Margin left graphic (layout)	0	Margin top graphic (layout)	0	Margin right graphic (layout)	0
Margin bottom graphic (layout)	0				
Text format					
Font	Tahoma, 13px, style=Bold	Orientation	Horizontal	Horizontal alignment of the text	Centered
Vertical alignment of the text	Middle				
Flashing					
Flashing	Disabled				
Styles/Designs					
Use style/design	Disabled	Style item appearance			
Miscellaneous					
Name	Button_5	Layer	0 - Layer_0	Tooltip	
Security					
Authorization		Allow operator control	Enabled		

Dynamizations\Event

Event name

Press

Function list\InvertBit

Tag

Rearm

Dynamizations\Appearance

Tag - Cycle	Rearm -	Data type	Range	Range	1..1
Foreground color	255, 255, 255	Background color	51, 102, 255	Flashing	No

Button_6

Type	Button				
General					
Mode	Text	Text OFF	Stop	Text ON	Text
Text list		Graphic OFF		Graphic ON	
Graphic list		Process value		Bit number	0
Appearance					
Background color	99, 101, 113	Background fill pattern	Vertical gradient	Corner radius (border)	3
Foreground color	255, 255, 255	Border width	2	Line style	Solid
Border color	71, 73, 87	Border background color	105, 105, 105		
Fill pattern					
Background color gradient (fill pattern)	99, 101, 113	Gradient 1 (fill pattern)	Enabled	Color gradient 1 (fill pattern)	131, 132, 142
Offset gradient 1 (fill pattern)	15	Gradient 2 (fill pattern)	Enabled	Color gradient 2 (fill pattern)	88, 90, 103

--	--	--

Totally Integrated Automation Portal						
--------------------------------------	--	--	--	--	--	--

Offset gradient 2 (fill pattern)		15			
Design					
Focus width		2		Focus color 148, 182, 231	
Layout					
X position		15		Y position 102	
Height		32		Fit graphic to size Stretch graphic	
Vertical alignment of the graphic		Middle		Horizontal alignment of the graphic Centered	
Margin top text (layout)		0		Margin left text (layout) 0	
Margin left graphic (layout)		0		Margin bottom text (layout) 0	
Margin bottom graphic (layout)		0		Margin right graphic (layout) 0	
Text format					
Font		Tahoma, 13px, style=Bold		Orientation Horizontal	
Vertical alignment of the text		Middle		Horizontal alignment of the text Centered	
Flashing					
Flashing		Disabled			
Styles/Designs					
Use style/design		Disabled		Style item appearance	
Miscellaneous					
Name		Button_6		Layer 0 - Layer_0	
Security				Tooltip	
Authorization				Allow operator control Enabled	

Dynamizations\Event	
Event name	Press

Function list\SetBit	
Tag	Stop

Function list\ResetBit	
Tag	Run

Dynamizations\Event	
Event name	Release

Function list\SetBit	
Tag	Stop

Dynamizations\Appearance					
Tag - Cycle	Stop -	Data type	Range	Range	1..1
Foreground color	255, 255, 255	Background color	255, 0, 0	Flashing	No

I/O field_1					
Type	I/O field				
General					
Process value	0	Mode	Output	Display format	Decimal
Shift decimal point	0	Field length	4	Show leading zeros	Disabled
Format pattern		9999			
Appearance					
Background color	255, 255, 255	Background fill pattern	Solid	Corner radius	3
Foreground color	49, 52, 74	Unit		Border width	4
Line style	Double line	Border color	71, 73, 87	Border background color	101, 103, 115
Characteristics					
Hidden input	Disabled				
Layout					
X position	15	Y position	241	Width	96
Height	32	Left margin	3	Top margin	2
Right margin	2	Bottom margin	2	Fit object to contents	Disabled
Text format					
Font	Tahoma, 13px, style=Bold	Orientation	Horizontal	Horizontal alignment	Left
Vertical alignment	Middle	Line break	Disabled		
Flashing					
Flashing	Disabled	Flash on limit violation	Disabled		
Limits					
Color for High limit violated	237, 88, 97	Color for Low limit violated	241, 161, 44		
Styles/Designs					
Use style/design	Disabled	Style item appearance			
Miscellaneous					
Name	I/O field_1	Layer	0 - Layer_0	Tooltip	
Security					
Authorization		Allow operator control	Enabled		

--	--	--

Totally Integrated Automation Portal							
Dynamizations\Tag connection							
Property name		Process value	Tag	contOK_CV			
I/O field_2							
Type		I/O field					
General							
Process value		0	Mode		Output	Display format	Decimal
Shift decimal point		0	Field length		4	Show leading zeros	Disabled
Format pattern		9999					
Appearance							
Background color		255, 255, 255	Background fill pattern		Solid	Corner radius	3
Foreground color		49, 52, 74	Unit			Border width	4
Line style		Double line	Border color		71, 73, 87	Border background color	101, 103, 115
Characteristics							
Hidden input		Disabled					
Layout							
X position		170	Y position		241	Width	96
Height		32	Left margin		3	Top margin	2
Right margin		2	Bottom margin		2	Fit object to contents	Disabled
Text format							
Font		Tahoma, 13px, style=Bold	Orientation		Horizontal	Horizontal alignment	Left
Vertical alignment		Middle	Line break		Disabled		
Flashing							
Flashing		Disabled	Flash on limit violation		Disabled		
Limits							
Color for High limit violated		237, 88, 97	Color for Low limit violated		241, 161, 44		
Styles/Designs							
Use style/design		Disabled	Style item appearance				
Miscellaneous							
Name		I/O field_2	Layer		0 - Layer_0	Tooltip	
Security							
Authorization			Allow operator control		Enabled		
Dynamizations\Tag connection							
Property name		Process value	Tag	contNOK_CV			
I/O field_3							
Type		I/O field					
General							
Process value		0	Mode		Output	Display format	Decimal
Shift decimal point		0	Field length		1	Show leading zeros	Disabled
Format pattern		9					
Appearance							
Background color		255, 255, 255	Background fill pattern		Solid	Corner radius	3
Foreground color		49, 52, 74	Unit			Border width	4
Line style		Double line	Border color		71, 73, 87	Border background color	101, 103, 115
Characteristics							
Hidden input		Disabled					
Layout							
X position		15	Y position		319	Width	96
Height		32	Left margin		3	Top margin	2
Right margin		2	Bottom margin		2	Fit object to contents	Disabled
Text format							
Font		Tahoma, 13px, style=Bold	Orientation		Horizontal	Horizontal alignment	Left
Vertical alignment		Middle	Line break		Disabled		
Flashing							
Flashing		Disabled	Flash on limit violation		Disabled		
Limits							
Color for High limit violated		237, 88, 97	Color for Low limit violated		241, 161, 44		
Styles/Designs							
Use style/design		Disabled	Style item appearance				
Miscellaneous							
Name		I/O field_3	Layer		0 - Layer_0	Tooltip	
Security							
Authorization			Allow operator control		Enabled		
Dynamizations\Tag connection							
Property name		Process value	Tag	Tray_Left			
I/O field_4							
Type		I/O field					
General							
Process value		0	Mode		Output	Display format	Decimal
Shift decimal point		0	Field length		1	Show leading zeros	Disabled
Format pattern		9					

Totally Integrated Automation Portal						
Appearance						
Background color	255, 255, 255	Background fill pattern	Solid	Corner radius	3	
Foreground color	49, 52, 74	Unit		Border width	4	
Line style	Double line	Border color	71, 73, 87	Border background color	101, 103, 115	
Characteristics						
Hidden input	Disabled					
Layout						
X position	170	Y position	319	Width	96	
Height	32	Left margin	3	Top margin	2	
Right margin	2	Bottom margin	2	Fit object to contents	Disabled	
Text format						
Font	Tahoma, 13px, style=Bold	Orientation	Horizontal	Horizontal alignment	Left	
Vertical alignment	Middle	Line break	Disabled			
Flashing						
Flashing	Disabled	Flash on limit violation	Disabled			
Limits						
Color for High limit violated	237, 88, 97	Color for Low limit violated	241, 161, 44			
Styles/Designs						
Use style/design	Disabled	Style item appearance				
Miscellaneous						
Name	I/O field_4	Layer	0 - Layer_0	Tooltip		
Security						
Authorization		Allow operator control	Enabled			
Dynamizations\Tag connection						
Property name	Process value	Tag	contPiece_CV			
I/O field_5						
Type	I/O field					
General						
Process value	0	Mode	Output	Display format	Decimal	
Shift decimal point	0	Field length	1	Show leading zeros	Disabled	
Format pattern	9					
Appearance						
Background color	255, 255, 255	Background fill pattern	Solid	Corner radius	3	
Foreground color	49, 52, 74	Unit		Border width	4	
Line style	Double line	Border color	71, 73, 87	Border background color	101, 103, 115	
Characteristics						
Hidden input	Disabled					
Layout						
X position	100	Y position	383	Width	96	
Height	32	Left margin	3	Top margin	2	
Right margin	2	Bottom margin	2	Fit object to contents	Disabled	
Text format						
Font	Tahoma, 13px, style=Bold	Orientation	Horizontal	Horizontal alignment	Left	
Vertical alignment	Middle	Line break	Disabled			
Flashing						
Flashing	Disabled	Flash on limit violation	Disabled			
Limits						
Color for High limit violated	237, 88, 97	Color for Low limit violated	241, 161, 44			
Styles/Designs						
Use style/design	Disabled	Style item appearance				
Miscellaneous						
Name	I/O field_5	Layer	0 - Layer_0	Tooltip		
Security						
Authorization		Allow operator control	Enabled			
Dynamizations\Tag connection						
Property name	Process value	Tag	Tray_Hole			
Text field_1						
Type	Text field					
General						
Text	OK Pieces					
Appearance						
Background color	255, 102, 0	Background fill pattern	Transparent	Corner radius (border)	3	
Foreground color	49, 52, 74	Border width	0	Line style	Double line	
Border color	255, 0, 0	Border background color	101, 103, 115			
Layout						
X position	24	Y position	215	Width	76	
Height	20	Left margin	3	Top margin	2	
Right margin	2	Bottom margin	2	Fit object to contents	Enabled	
Text format						
Font	Tahoma, 13px, style=Bold	Orientation	Horizontal	Horizontal alignment	Left	
Vertical alignment	Middle	Line break	Disabled			

Totally Integrated Automation Portal						
Flashing						
Flashing	Disabled					
Styles/Designs						
Use style/design	Disabled		Style item appearance			
Miscellaneous						
Name	Text field_1		Layer	0 - Layer_0		
Text field_2						
Type	Text field					
General						
Text	NOK Pieces					
Appearance						
Background color	255, 255, 255		Background fill pattern	Transparent	Corner radius (border)	3
Foreground color	49, 52, 74		Border width	0	Line style	Double line
Border color	71, 73, 87		Border background color	101, 103, 115		
Layout						
X position	181		Y position	213	Width	85
Height	20		Left margin	3	Top margin	2
Right margin	2		Bottom margin	2	Fit object to contents	Enabled
Text format						
Font	Tahoma, 13px, style=Bold		Orientation	Horizontal	Horizontal alignment	Left
Vertical alignment	Middle		Line break	Disabled		
Flashing						
Flashing	Disabled					
Styles/Designs						
Use style/design	Disabled		Style item appearance			
Miscellaneous						
Name	Text field_2		Layer	0 - Layer_0		
Text field_3						
Type	Text field					
General						
Text	Tray Left					
Appearance						
Background color	255, 255, 255		Background fill pattern	Transparent	Corner radius (border)	3
Foreground color	49, 52, 74		Border width	0	Line style	Double line
Border color	71, 73, 87		Border background color	101, 103, 115		
Layout						
X position	24		Y position	292	Width	73
Height	20		Left margin	3	Top margin	2
Right margin	2		Bottom margin	2	Fit object to contents	Enabled
Text format						
Font	Tahoma, 13px, style=Bold		Orientation	Horizontal	Horizontal alignment	Left
Vertical alignment	Middle		Line break	Disabled		
Flashing						
Flashing	Disabled					
Styles/Designs						
Use style/design	Disabled		Style item appearance			
Miscellaneous						
Name	Text field_3		Layer	0 - Layer_0		
Text field_4						
Type	Text field					
General						
Text	Pieces in Tray					
Appearance						
Background color	255, 255, 255		Background fill pattern	Transparent	Corner radius (border)	3
Foreground color	49, 52, 74		Border width	0	Line style	Double line
Border color	71, 73, 87		Border background color	101, 103, 115		
Layout						
X position	170		Y position	293	Width	108
Height	20		Left margin	3	Top margin	2
Right margin	2		Bottom margin	2	Fit object to contents	Enabled
Text format						
Font	Tahoma, 13px, style=Bold		Orientation	Horizontal	Horizontal alignment	Left
Vertical alignment	Middle		Line break	Disabled		
Flashing						
Flashing	Disabled					
Styles/Designs						
Use style/design	Disabled		Style item appearance			
Miscellaneous						
Name	Text field_4		Layer	0 - Layer_0		
Text field_5						
Type	Text field					

Totally Integrated Automation Portal						
General						
Text		Current Hole				
Appearance						
Background color		255, 255, 255		Background fill pattern		Transparent
Foreground color		49, 52, 74		Border width		0
Border color		71, 73, 87		Border background color		101, 103, 115
				Corner radius (border)		3
				Line style		Double line
Layout						
X position		100		Y position		359
Height		20		Left margin		3
Right margin		2		Bottom margin		2
				Width		99
				Top margin		2
				Fit object to contents		Enabled
Text format						
Font		Tahoma, 13px, style=Bold		Orientation		Horizontal
Vertical alignment		Middle		Horizontal alignment		Left
				Line break		Disabled
Flashing						
Flashing		Disabled				
Styles/Designs						
Use style/design		Disabled		Style item appearance		
Miscellaneous						
Name		Text field_5		Layer		0 - Layer_0
Text field_6						
Type		Text field				
General						
Text						
Appearance						
Background color		255, 255, 255		Background fill pattern		Transparent
Foreground color		49, 52, 74		Border width		0
Border color		71, 73, 87		Border background color		101, 103, 115
				Corner radius (border)		3
				Line style		Double line
Layout						
X position		-4200		Y position		110
Height		20		Left margin		3
Right margin		2		Bottom margin		2
				Width		14
				Top margin		2
				Fit object to contents		Enabled
Text format						
Font		Tahoma, 13px, style=Bold		Orientation		Horizontal
Vertical alignment		Middle		Horizontal alignment		Left
				Line break		Disabled
Flashing						
Flashing		Disabled				
Styles/Designs						
Use style/design		Disabled		Style item appearance		
Miscellaneous						
Name		Text field_6		Layer		0 - Layer_0
Graphic view_1						
Type		Graphic view				
General						
Graphic		Graphic_2				
Appearance						
Background color		173, 174, 181		Background fill pattern		Transparent
Transparent color		255, 0, 255		Border width		0
Border color		0, 0, 0		Use transparent color		Disabled
				Line style		Solid
Layout						
X position		235		Y position		95
Height		39		Fit embedded graphic object to screen size		Fit graphic to object size
				Fit graphic to size		Stretch graphic
Fit object to contents		Disabled				
Flashing						
Flashing		Disabled				
Miscellaneous						
Name		Graphic view_1		Layer		0 - Layer_0
Dynamizations\Visibility						
Tag - Cycle		FB_Emergence_DB_X63 -		Data type		Range
End range		1		Visibility		Visible
				Start range		1
Text field_9						
Type		Text field				
General						
Text		State				
Appearance						
Background color		255, 255, 255		Background fill pattern		Transparent
Foreground color		49, 52, 74		Border width		0
Border color		71, 73, 87		Border background color		101, 103, 115
				Corner radius (border)		3
				Line style		Double line
Layout						
X position		67		Y position		150
Height		20		Left margin		3
Right margin		2		Bottom margin		2
				Width		46
				Top margin		2
				Fit object to contents		Enabled
Text format						
Font		Tahoma, 13px, style=Bold		Orientation		Horizontal
				Horizontal alignment		Left

Totally Integrated Automation Portal							
--------------------------------------	--	--	--	--	--	--	--

Vertical alignment		Middle	Line break		Disabled		
Flashing							
Flashing		Disabled					
Styles/Designs							
Use style/design		Disabled	Style item appearance				
Miscellaneous							
Name		Text field_9	Layer		0 - Layer_0		

Text field_10

Type		Text field					
General							
Text		Tray Left					
Appearance							
Background color		255, 255, 255	Background fill pattern		Transparent	Corner radius (border)	3
Foreground color		49, 52, 74	Border width		0	Line style	Double line
Border color		71, 73, 87	Border background color		101, 103, 115		
Layout							
X position		118	Y position		148	Width	73
Height		20	Left margin		3	Top margin	2
Right margin		2	Bottom margin		2	Fit object to contents	Enabled
Text format							
Font		Tahoma, 13px, style=Bold	Orientation		Horizontal	Horizontal alignment	Left
Vertical alignment		Middle	Line break		Disabled		
Flashing							
Flashing		Disabled					
Styles/Designs							
Use style/design		Disabled	Style item appearance				
Miscellaneous							
Name		Text field_10	Layer		0 - Layer_0		

Circle_1

Type		Circle					
Appearance							
Background color		217, 217, 217	Background fill pattern		Solid	Border width	1
Line style		Solid	Border color		24, 28, 49		
Layout							
X position		79	Y position		172	Width	18
Height		18	Radius		9		
Flashing							
Flashing		Disabled					
Styles/Designs							
Use style/design		Disabled	Style item appearance				
Miscellaneous							
Name		Circle_1	Layer		0 - Layer_0		
Dynamizations\Appearance							
Tag - Cycle		Light_State -	Data type		Range	Range	0..0
Foreground color		24, 28, 49	Background color		217, 217, 217	Flashing	No
Range		1..1	Foreground color		24, 28, 49	Background color	255, 204, 0
Flashing		No	Range		2..2	Foreground color	24, 28, 49
Background color		0, 255, 0	Flashing		No	Range	3..3
Foreground color		24, 28, 49	Background color		255, 102, 0	Flashing	No
Range		4..4	Foreground color		24, 28, 49	Background color	255, 0, 0
Flashing		No					

Circle_2

Type		Circle					
Appearance							
Background color		217, 217, 217	Background fill pattern		Solid	Border width	1
Line style		Solid	Border color		24, 28, 49		
Layout							
X position		146	Y position		172	Width	18
Height		18	Radius		9		
Flashing							
Flashing		Disabled					
Styles/Designs							
Use style/design		Disabled	Style item appearance				
Miscellaneous							
Name		Circle_2	Layer		0 - Layer_0		
Dynamizations\Appearance							
Tag - Cycle		Light_Tray -	Data type		Range	Range	0..0
Foreground color		24, 28, 49	Background color		217, 217, 217	Flashing	No
Range		1..1	Foreground color		24, 28, 49	Background color	0, 255, 0
Flashing		No	Range		2..2	Foreground color	24, 28, 49
Background color		255, 255, 0	Flashing		No	Range	3..3
Foreground color		24, 28, 49	Background color		255, 102, 0	Flashing	No
Range		4..4	Foreground color		24, 28, 49	Background color	255, 0, 0
Flashing		No					

HMI_1 [TP900 Comfort] / Screen management / Templates

Template_1

Hardcopy of Template_1



General					
Name	Template_1	Background color	182, 182, 182	Grid color	0, 0, 0
Tab sequence in foreground	Enabled				
Layers					
Active layer	0				
Layer_0			Enabled		
Layer_1			Enabled		
Layer_2			Enabled		
Layer_3			Enabled		
Layer_4			Enabled		
Layer_5			Enabled		
Layer_6			Enabled		
Layer_7			Enabled		
Layer_8			Enabled		
Layer_9			Enabled		
Layer_10			Enabled		
Layer_11			Enabled		
Layer_12			Enabled		
Layer_13			Enabled		
Layer_14			Enabled		
Layer_15			Enabled		
Layer_16			Enabled		
Layer_17			Enabled		
Layer_18			Enabled		
Layer_19			Enabled		
Layer_20			Enabled		
Layer_21			Enabled		
Layer_22			Enabled		
Layer_23			Enabled		
Layer_24			Enabled		
Layer_25			Enabled		
Layer_26			Enabled		
Layer_27			Enabled		
Layer_28			Enabled		
Layer_29			Enabled		
Layer_30			Enabled		
Layer_31			Enabled		

Totally Integrated Automation Portal		
HMI_1 [TP900 Comfort] / Screen management Pop-up screens This folder is empty.		

Totally Integrated Automation Portal

HMI_1 [TP900 Comfort] / Screen management / Slide-in screens

Slide-in screen bottom


Hardcopy of Slide-in screen bottom

General					
Name	Slide-in screen bottom	Background color	182, 182, 182	Grid color	0, 0, 0
Activate slide-in screen	Disabled				
Layout					
Width	800	Height	160		
Layers					
Active layer	0				
Layer_0				Enabled	
Layer_1				Enabled	
Layer_2				Enabled	
Layer_3				Enabled	
Layer_4				Enabled	
Layer_5				Enabled	
Layer_6				Enabled	
Layer_7				Enabled	
Layer_8				Enabled	
Layer_9				Enabled	
Layer_10				Enabled	
Layer_11				Enabled	
Layer_12				Enabled	
Layer_13				Enabled	
Layer_14				Enabled	
Layer_15				Enabled	
Layer_16				Enabled	
Layer_17				Enabled	
Layer_18				Enabled	
Layer_19				Enabled	
Layer_20				Enabled	
Layer_21				Enabled	
Layer_22				Enabled	
Layer_23				Enabled	
Layer_24				Enabled	
Layer_25				Enabled	
Layer_26				Enabled	
Layer_27				Enabled	
Layer_28				Enabled	
Layer_29				Enabled	
Layer_30				Enabled	
Layer_31				Enabled	
Handle					
Line color	223, 223, 223	Alternative line color	32, 32, 32	Color of operable area	128, 128, 128
Visibility	Hide handle automatically				
Security					
Authorization		Operator control enabled	Enabled		

HMI_1 [TP900 Comfort] / Screen management / Slide-in screens

Slide-in screen left

Hardcopy of Slide-in screen left



General					
Name	Slide-in screen left	Background color	182, 182, 182	Grid color	0, 0, 0
Activate slide-in screen	Disabled				
Layout					
Width	267	Height	480		
Layers					
Active layer	0				
Layer_0			Enabled		
Layer_1			Enabled		
Layer_2			Enabled		
Layer_3			Enabled		
Layer_4			Enabled		
Layer_5			Enabled		
Layer_6			Enabled		
Layer_7			Enabled		
Layer_8			Enabled		
Layer_9			Enabled		
Layer_10			Enabled		
Layer_11			Enabled		
Layer_12			Enabled		
Layer_13			Enabled		
Layer_14			Enabled		
Layer_15			Enabled		
Layer_16			Enabled		
Layer_17			Enabled		
Layer_18			Enabled		
Layer_19			Enabled		
Layer_20			Enabled		
Layer_21			Enabled		
Layer_22			Enabled		
Layer_23			Enabled		
Layer_24			Enabled		
Layer_25			Enabled		
Layer_26			Enabled		
Layer_27			Enabled		
Layer_28			Enabled		
Layer_29			Enabled		
Layer_30			Enabled		
Layer_31			Enabled		
Handle					
Line color	223, 223, 223	Alternative line color	32, 32, 32	Color of operable area	128, 128, 128
Visibility	Hide handle automatically				
Security					
Authorization		Operator control enabled	Enabled		

Totally Integrated Automation Portal		
--------------------------------------	--	--

HMI_1 [TP900 Comfort] / Screen management / Slide-in screens

Slide-in screen right

Hardcopy of Slide-in screen right

General					
Name	Slide-in screen right	Background color	182, 182, 182	Grid color	0, 0, 0
Activate slide-in screen	Disabled				
Layout					
Width	267	Height	480		
Layers					
Active layer	0				
Layer_0				Enabled	
Layer_1				Enabled	
Layer_2				Enabled	
Layer_3				Enabled	
Layer_4				Enabled	
Layer_5				Enabled	
Layer_6				Enabled	
Layer_7				Enabled	
Layer_8				Enabled	
Layer_9				Enabled	
Layer_10				Enabled	
Layer_11				Enabled	
Layer_12				Enabled	
Layer_13				Enabled	
Layer_14				Enabled	
Layer_15				Enabled	
Layer_16				Enabled	
Layer_17				Enabled	
Layer_18				Enabled	
Layer_19				Enabled	
Layer_20				Enabled	
Layer_21				Enabled	
Layer_22				Enabled	
Layer_23				Enabled	
Layer_24				Enabled	
Layer_25				Enabled	
Layer_26				Enabled	
Layer_27				Enabled	
Layer_28				Enabled	
Layer_29				Enabled	
Layer_30				Enabled	
Layer_31				Enabled	
Handle					
Line color	223, 223, 223	Alternative line color	32, 32, 32	Color of operable area	128, 128, 128
Visibility	Hide handle automatically				
Security					
Authorization		Operator control enabled	Enabled		

--	--	--

Totally Integrated Automation Portal

HMI_1 [TP900 Comfort] / Screen management / Slide-in screens

Slide-in screen top

Hardcopy of Slide-in screen top

General					
Name	Slide-in screen top	Background color	182, 182, 182	Grid color	0, 0, 0
Activate slide-in screen	Disabled				
Layout					
Width	800	Height	160		
Layers					
Active layer	0				
Layer_0				Enabled	
Layer_1				Enabled	
Layer_2				Enabled	
Layer_3				Enabled	
Layer_4				Enabled	
Layer_5				Enabled	
Layer_6				Enabled	
Layer_7				Enabled	
Layer_8				Enabled	
Layer_9				Enabled	
Layer_10				Enabled	
Layer_11				Enabled	
Layer_12				Enabled	
Layer_13				Enabled	
Layer_14				Enabled	
Layer_15				Enabled	
Layer_16				Enabled	
Layer_17				Enabled	
Layer_18				Enabled	
Layer_19				Enabled	
Layer_20				Enabled	
Layer_21				Enabled	
Layer_22				Enabled	
Layer_23				Enabled	
Layer_24				Enabled	
Layer_25				Enabled	
Layer_26				Enabled	
Layer_27				Enabled	
Layer_28				Enabled	
Layer_29				Enabled	
Layer_30				Enabled	
Layer_31				Enabled	
Handle					
Line color	223, 223, 223	Alternative line color	32, 32, 32	Color of operable area	128, 128, 128
Visibility	Hide handle automatically				
Security					
Authorization		Operator control enabled	Enabled		

HMI_1 [TP900 Comfort] / Screen management

Global screen

Hardcopy of Global screen



General					
Name	Global screen	Background color	182, 182, 182	Grid color	0, 0, 0

HMI_1 [TP900 Comfort] / Screen management

Permanent area

Hardcopy of Permanent area



Pick & Place Cell
Iñigo Mamolar Murias

General

Name	Permanent area	Background color	192, 192, 192	Grid color	0, 0, 0
Height	60				

Layers

Active layer	0
--------------	---

Layer_0	Enabled
Layer_1	Enabled
Layer_2	Enabled
Layer_3	Enabled
Layer_4	Enabled
Layer_5	Enabled
Layer_6	Enabled
Layer_7	Enabled
Layer_8	Enabled
Layer_9	Enabled
Layer_10	Enabled
Layer_11	Enabled
Layer_12	Enabled
Layer_13	Enabled
Layer_14	Enabled
Layer_15	Enabled
Layer_16	Enabled
Layer_17	Enabled
Layer_18	Enabled
Layer_19	Enabled
Layer_20	Enabled
Layer_21	Enabled
Layer_22	Enabled
Layer_23	Enabled
Layer_24	Enabled
Layer_25	Enabled
Layer_26	Enabled
Layer_27	Enabled
Layer_28	Enabled
Layer_29	Enabled
Layer_30	Enabled
Layer_31	Enabled

HmiScreenItemData

Type	Text field
------	------------

General

Text	Iñigo Mamolar Murias
------	----------------------

Appearance

Background color	255, 255, 255	Background fill pattern	Transparent	Corner radius (border)	3
Foreground color	0, 0, 0	Border width	0	Line style	Double line
Border color	156, 154, 165	Border background color	226, 225, 225		

Layout

X position	156	Y position	32	Width	199
Height	22	Left margin	3	Top margin	2
Right margin	2	Bottom margin	2	Fit object to contents	Disabled

Text format

Font	Tahoma, 17px, style=Bold	Orientation	Horizontal	Horizontal alignment	Centered
Vertical alignment	Middle	Line break	Disabled		

Flashing

Flashing	Disabled
----------	----------

Styles/Designs

Use style/design	Disabled	Style item appearance	
------------------	----------	-----------------------	--

Miscellaneous

Name	HmiScreenItemData	Layer	0 - Layer_0
-------------	-------------------	--------------	-------------

Graphic view_2

Type	Graphic view
------	--------------

General

Graphic	ChatGPT Image 13 jul 2026, 18_37_50
---------	--

Appearance

Background color	173, 174, 181	Background fill pattern	Transparent	Use transparent color	Disabled
Transparent color	255, 0, 255	Border width	0	Line style	Solid
Border color	0, 0, 0				

Totally Integrated Automation Portal						
--------------------------------------	--	--	--	--	--	--

Layout

X position	4	Y position	3	Width	152
Height	55	Fit embedded graphic object to screen size	Fit graphic to object size	Fit graphic to size	Stretch graphic
Fit object to contents	Disabled				

Flashing

Flashing	Disabled				
----------	----------	--	--	--	--

Miscellaneous

Name	Graphic view_2	Layer	0 - Layer_0		
------	----------------	-------	-------------	--	--

Text field_7

Type	Text field				
------	------------	--	--	--	--

General

Text	Pick & Place Cell				
------	-------------------	--	--	--	--

Appearance

Background color	255, 255, 255	Background fill pattern	Transparent	Corner radius (border)	3
Foreground color	49, 52, 74	Border width	0	Line style	Double line
Border color	71, 73, 87	Border background color	101, 103, 115		

Layout

X position	169	Y position	9	Width	159
Height	23	Left margin	3	Top margin	2
Right margin	2	Bottom margin	2	Fit object to contents	Enabled

Text format

Font	Tahoma, 16px, style=Bold	Orientation	Horizontal	Horizontal alignment	Left
Vertical alignment	Middle	Line break	Disabled		

Flashing

Flashing	Disabled				
----------	----------	--	--	--	--

Styles/Designs

Use style/design	Disabled	Style item appearance			
------------------	----------	-----------------------	--	--	--

Miscellaneous

Name	Text field_7	Layer	0 - Layer_0		
------	--------------	-------	-------------	--	--

--	--	--

Totally Integrated Automation Portal

HMI_1 [TP900 Comfort] / HMI tags

Default tag table [38]

Tag_ScreenNumber

General					
Name	Tag_ScreenNumber	Display name		Connection	<Internal tag>
Data type	UInt	Array elements	0	Length	2
Address		Access mode	<symbolic access>	PLC tag	
Coding	Binary	PLC name			
Settings					
Acquisition cycle	1 s	Acquisition mode	Cyclic in operation		
Limits					
Upper 2		Upper 1		Lower 1	
Lower 2					
Linear scaling					
Linear scaling	Disabled	PLC value range end value	10	PLC value range start value	0
HMI device value range end value	100	HMI device value range start value	0		
Values					
ID tag		Start value			
Comment					
Comment		Source comment			
Multiplexing					
Multiplexing	Disabled	Index tag			
Logging					
Data log					
GMP (Good Manufacturing Practice)					
Confirmation type	None	GMP relevant	Disabled	Comment required	Disabled

Run

General					
Name	Run	Display name		Connection	HMI_Connection_2
Data type	Bool	Array elements	0	Length	1
Address		Access mode	<symbolic access>	Coding	Binary
PLC name	PLC_OPC				
Settings					
Acquisition cycle	1 s	Acquisition mode	Cyclic in operation		
Limits					
Upper 2		Upper 1		Lower 1	
Lower 2					
Linear scaling					
Linear scaling	Disabled	PLC value range end value	10	PLC value range start value	0
HMI device value range end value	100	HMI device value range start value	0		
Values					
ID tag		Start value			
Comment					
Comment		Source comment			
Multiplexing					
Multiplexing	Disabled	Index tag			
Logging					
Data log					
GMP (Good Manufacturing Practice)					
Confirmation type	None	GMP relevant	Disabled	Comment required	Disabled

Run

EoC

General					
Name	EoC	Display name		Connection	HMI_Connection_2
Data type	Bool	Array elements	0	Length	1
Address		Access mode	<symbolic access>	Coding	Binary
PLC name	PLC_OPC				
Settings					
Acquisition cycle	1 s	Acquisition mode	Cyclic in operation		
Limits					
Upper 2		Upper 1		Lower 1	
Lower 2					
Linear scaling					
Linear scaling	Disabled	PLC value range end value	10	PLC value range start value	0
HMI device value range end value	100	HMI device value range start value	0		
Values					
ID tag		Start value			
Comment					
Comment		Source comment			
Multiplexing					
Multiplexing	Disabled	Index tag			
Logging					
Data log					

Totally Integrated Automation Portal						
GMP (Good Manufacturing Practice)						
Confirmation type	None	GMP relevant	Disabled	Comment required	Disabled	
EoC						
EM						
General						
Name	EM	Display name		Connection	HMI_Connection_2	
Data type	Bool	Array elements	0	Length	1	
Address		Access mode	<symbolic access>	Coding	Binary	
PLC name	PLC_OPC					
Settings						
Acquisition cycle	1 s	Acquisition mode	Cyclic in operation			
Limits						
Upper 2		Upper 1		Lower 1		
Lower 2						
Linear scaling						
Linear scaling	Disabled	PLC value range end value	10	PLC value range start value	0	
HMI device value range end value	100	HMI device value range start value	0			
Values						
ID tag		Start value				
Comment						
Comment		Source comment				
Multiplexing						
Multiplexing	Disabled	Index tag				
Logging						
Data log						
GMP (Good Manufacturing Practice)						
Confirmation type	None	GMP relevant	Disabled	Comment required	Disabled	
EM						
Stop						
General						
Name	Stop	Display name		Connection	HMI_Connection_2	
Data type	Bool	Array elements	0	Length	1	
Address		Access mode	<symbolic access>	Coding	Binary	
PLC name	PLC_OPC					
Settings						
Acquisition cycle	1 s	Acquisition mode	Cyclic in operation			
Limits						
Upper 2		Upper 1		Lower 1		
Lower 2						
Linear scaling						
Linear scaling	Disabled	PLC value range end value	10	PLC value range start value	0	
HMI device value range end value	100	HMI device value range start value	0			
Values						
ID tag		Start value				
Comment						
Comment		Source comment				
Multiplexing						
Multiplexing	Disabled	Index tag				
Logging						
Data log						
GMP (Good Manufacturing Practice)						
Confirmation type	None	GMP relevant	Disabled	Comment required	Disabled	
Stop						
Rearm						
General						
Name	Rearm	Display name		Connection	HMI_Connection_2	
Data type	Bool	Array elements	0	Length	1	
Address		Access mode	<symbolic access>	Coding	Binary	
PLC name	PLC_OPC					
Settings						
Acquisition cycle	1 s	Acquisition mode	Cyclic in operation			
Limits						
Upper 2		Upper 1		Lower 1		
Lower 2						
Linear scaling						
Linear scaling	Disabled	PLC value range end value	10	PLC value range start value	0	
HMI device value range end value	100	HMI device value range start value	0			
Values						
ID tag		Start value				
Comment						
Comment		Source comment				
Multiplexing						
Multiplexing	Disabled	Index tag				

Totally Integrated Automation Portal							
Logging							
Data log							
GMP (Good Manufacturing Practice)							
Confirmation type		None	GMP relevant	Disabled	Comment required	Disabled	
Rearm							
Alarm							
General							
Name		Alarm	Display name			Connection	HMI_Connection_2
Data type		Bool	Array elements		0	Length	1
Address			Access mode		<symbolic access>	Coding	Binary
PLC name		PLC_OPC					
Settings							
Acquisition cycle		1 s	Acquisition mode		Cyclic in operation		
Limits							
Upper 2			Upper 1			Lower 1	
Lower 2							
Linear scaling							
Linear scaling		Disabled	PLC value range end value		10	PLC value range start value	0
HMI device value range end value		100	HMI device value range start value		0		
Values							
ID tag			Start value				
Comment							
Comment			Source comment				
Multiplexing							
Multiplexing		Disabled	Index tag				
Logging							
Data log							
GMP (Good Manufacturing Practice)							
Confirmation type		None	GMP relevant	Disabled	Comment required	Disabled	
Alarm							
contOK_CV							
General							
Name		contOK_CV	Display name			Connection	HMI_Connection_2
Data type		Int	Array elements		0	Length	2
Address			Access mode		<symbolic access>	PLC tag	contOK.CV
Coding		Binary	PLC name		PLC_OPC		
Settings							
Acquisition cycle		1 s	Acquisition mode		Cyclic in operation		
Limits							
Upper 2			Upper 1			Lower 1	
Lower 2							
Linear scaling							
Linear scaling		Disabled	PLC value range end value		10	PLC value range start value	0
HMI device value range end value		100	HMI device value range start value		0		
Values							
ID tag			Start value				
Comment							
Comment			Source comment				
Multiplexing							
Multiplexing		Disabled	Index tag				
Logging							
Data log							
GMP (Good Manufacturing Practice)							
Confirmation type		None	GMP relevant	Disabled	Comment required	Disabled	
contNOK_CV							
General							
Name		contNOK_CV	Display name			Connection	HMI_Connection_2
Data type		Int	Array elements		0	Length	2
Address			Access mode		<symbolic access>	PLC tag	contNOK.CV
Coding		Binary	PLC name		PLC_OPC		
Settings							
Acquisition cycle		1 s	Acquisition mode		Cyclic in operation		
Limits							
Upper 2			Upper 1			Lower 1	
Lower 2							
Linear scaling							
Linear scaling		Disabled	PLC value range end value		10	PLC value range start value	0
HMI device value range end value		100	HMI device value range start value		0		
Values							
ID tag			Start value				
Comment							
Comment			Source comment				
Multiplexing							
Multiplexing		Disabled	Index tag				

Totally Integrated Automation Portal					
--------------------------------------	--	--	--	--	--

Logging

Data log		
----------	--	--

GMP (Good Manufacturing Practice)

Confirmation type	None	GMP relevant	Disabled	Comment required	Disabled
-------------------	------	--------------	----------	------------------	----------

contTray_CV

General

Name	contTray_CV	Display name		Connection	HMI_Connection_2
Data type	Int	Array elements	0	Length	2
Address		Access mode	<symbolic access>	PLC tag	contTray.CV
Coding	Binary	PLC name	PLC_OPC		

Settings

Acquisition cycle	1 s	Acquisition mode	Cyclic in operation		
-------------------	-----	------------------	---------------------	--	--

Limits

Upper 2		Upper 1		Lower 1	
Lower 2					

Linear scaling

Linear scaling	Disabled	PLC value range end value	10	PLC value range start value	0
HMI device value range end value	100	HMI device value range start value	0		

Values

ID tag		Start value			
--------	--	-------------	--	--	--

Comment

Comment		Source comment			
---------	--	----------------	--	--	--

Multiplexing

Multiplexing	Disabled	Index tag			
--------------	----------	-----------	--	--	--

Logging

Data log		
----------	--	--

GMP (Good Manufacturing Practice)

Confirmation type	None	GMP relevant	Disabled	Comment required	Disabled
-------------------	------	--------------	----------	------------------	----------

contPiece_CV

General

Name	contPiece_CV	Display name		Connection	HMI_Connection_2
Data type	Int	Array elements	0	Length	2
Address		Access mode	<symbolic access>	PLC tag	contPiece.CV
Coding	Binary	PLC name	PLC_OPC		

Settings

Acquisition cycle	1 s	Acquisition mode	Cyclic in operation		
-------------------	-----	------------------	---------------------	--	--

Limits

Upper 2		Upper 1		Lower 1	
Lower 2					

Linear scaling

Linear scaling	Disabled	PLC value range end value	10	PLC value range start value	0
HMI device value range end value	100	HMI device value range start value	0		

Values

ID tag		Start value			
--------	--	-------------	--	--	--

Comment

Comment		Source comment			
---------	--	----------------	--	--	--

Multiplexing

Multiplexing	Disabled	Index tag			
--------------	----------	-----------	--	--	--

Logging

Data log		
----------	--	--

GMP (Good Manufacturing Practice)

Confirmation type	None	GMP relevant	Disabled	Comment required	Disabled
-------------------	------	--------------	----------	------------------	----------

contHole_CV

General

Name	contHole_CV	Display name		Connection	HMI_Connection_2
Data type	Int	Array elements	0	Length	2
Address		Access mode	<symbolic access>	PLC tag	contHole.CV
Coding	Binary	PLC name	PLC_OPC		

Settings

Acquisition cycle	1 s	Acquisition mode	Cyclic in operation		
-------------------	-----	------------------	---------------------	--	--

Limits

Upper 2		Upper 1		Lower 1	
Lower 2					

Linear scaling

Linear scaling	Disabled	PLC value range end value	10	PLC value range start value	0
HMI device value range end value	100	HMI device value range start value	0		

Values

ID tag		Start value			
--------	--	-------------	--	--	--

Comment

Comment		Source comment			
---------	--	----------------	--	--	--

Multiplexing

Multiplexing	Disabled	Index tag			
--------------	----------	-----------	--	--	--

Logging

Data log		
----------	--	--

GMP (Good Manufacturing Practice)

Confirmation type	None	GMP relevant	Disabled	Comment required	Disabled
-------------------	------	--------------	----------	------------------	----------

Totally Integrated Automation Portal		
--------------------------------------	--	--

FB_Emergence_DB_X64

General					
Name	FB_Emergence_DB_X64	Display name		Connection	HMI_Connection_2
Data type	Bool	Array elements	0	Length	1
Address		Access mode	<symbolic access>	PLC tag	FB_Emergency_DB.X64
Coding	Binary	PLC name	PLC_OPC		
Settings					
Acquisition cycle	1 s	Acquisition mode	Cyclic in operation		
Limits					
Upper 2		Upper 1		Lower 1	
Lower 2					
Linear scaling					
Linear scaling	Disabled	PLC value range end value	10	PLC value range start value	0
HMI device value range end value	100	HMI device value range start value	0		
Values					
ID tag		Start value			
Comment					
Comment		Source comment			
Multiplexing					
Multiplexing	Disabled	Index tag			
Logging					
Data log					
GMP (Good Manufacturing Practice)					
Confirmation type	None	GMP relevant	Disabled	Comment required	Disabled

FB_Emergence_DB_X63

General					
Name	FB_Emergence_DB_X63	Display name		Connection	HMI_Connection_2
Data type	Bool	Array elements	0	Length	1
Address		Access mode	<symbolic access>	PLC tag	FB_Emergency_DB.X63
Coding	Binary	PLC name	PLC_OPC		
Settings					
Acquisition cycle	1 s	Acquisition mode	Cyclic in operation		
Limits					
Upper 2		Upper 1		Lower 1	
Lower 2					
Linear scaling					
Linear scaling	Disabled	PLC value range end value	10	PLC value range start value	0
HMI device value range end value	100	HMI device value range start value	0		
Values					
ID tag		Start value			
Comment					
Comment		Source comment			
Multiplexing					
Multiplexing	Disabled	Index tag			
Logging					
Data log					
GMP (Good Manufacturing Practice)					
Confirmation type	None	GMP relevant	Disabled	Comment required	Disabled

Tray_Left

General					
Name	Tray_Left	Display name		Connection	HMI_Connection_2
Data type	Int	Array elements	0	Length	2
Address		Access mode	<symbolic access>	Coding	Binary
PLC name	PLC_OPC				
Settings					
Acquisition cycle	1 s	Acquisition mode	Cyclic in operation		
Limits					
Upper 2		Upper 1		Lower 1	
Lower 2					
Linear scaling					
Linear scaling	Disabled	PLC value range end value	10	PLC value range start value	0
HMI device value range end value	100	HMI device value range start value	0		
Values					
ID tag		Start value			
Comment					
Comment		Source comment			
Multiplexing					
Multiplexing	Disabled	Index tag			
Logging					
Data log					
GMP (Good Manufacturing Practice)					
Confirmation type	None	GMP relevant	Disabled	Comment required	Disabled

--	--	--

Totally Integrated Automation Portal

Tray_Left

Tray_Hole

General					
Name	Tray_Hole	Display name		Connection	HMI_Connection_2
Data type	Int	Array elements	0	Length	2
Address		Access mode	<symbolic access>	Coding	Binary
PLC name	PLC_OPC				
Settings					
Acquisition cycle	1 s	Acquisition mode	Cyclic in operation		
Limits					
Upper 2		Upper 1		Lower 1	
Lower 2					
Linear scaling					
Linear scaling	Disabled	PLC value range end value	10	PLC value range start value	0
HMI device value range end value	100	HMI device value range start value	0		
Values					
ID tag		Start value			
Comment					
Comment		Source comment			
Multiplexing					
Multiplexing	Disabled	Index tag			
Logging					
Data log					
GMP (Good Manufacturing Practice)					
Confirmation type	None	GMP relevant	Disabled	Comment required	Disabled

Tray_Hole

Tray_Sensorinit

General					
Name	Tray_Sensorinit	Display name		Connection	HMI_Connection_2
Data type	Bool	Array elements	0	Length	1
Address		Access mode	<symbolic access>	Coding	Binary
PLC name	PLC_OPC				
Settings					
Acquisition cycle	1 s	Acquisition mode	Cyclic in operation		
Limits					
Upper 2		Upper 1		Lower 1	
Lower 2					
Linear scaling					
Linear scaling	Disabled	PLC value range end value	10	PLC value range start value	0
HMI device value range end value	100	HMI device value range start value	0		
Values					
ID tag		Start value			
Comment					
Comment		Source comment			
Multiplexing					
Multiplexing	Disabled	Index tag			
Logging					
Data log					
GMP (Good Manufacturing Practice)					
Confirmation type	None	GMP relevant	Disabled	Comment required	Disabled

Tray_Sensorinit

Tray_Sensor1

General					
Name	Tray_Sensor1	Display name		Connection	HMI_Connection_2
Data type	Bool	Array elements	0	Length	1
Address		Access mode	<symbolic access>	Coding	Binary
PLC name	PLC_OPC				
Settings					
Acquisition cycle	1 s	Acquisition mode	Cyclic in operation		
Limits					
Upper 2		Upper 1		Lower 1	
Lower 2					
Linear scaling					
Linear scaling	Disabled	PLC value range end value	10	PLC value range start value	0
HMI device value range end value	100	HMI device value range start value	0		
Values					
ID tag		Start value			
Comment					
Comment		Source comment			
Multiplexing					
Multiplexing	Disabled	Index tag			
Logging					
Data log					
GMP (Good Manufacturing Practice)					
Confirmation type	None	GMP relevant	Disabled	Comment required	Disabled

Totally Integrated Automation Portal

Tray_Sensor1

Tray_Sensor2

General					
Name	Tray_Sensor2	Display name		Connection	HMI_Connection_2
Data type	Bool	Array elements	0	Length	1
Address		Access mode	<symbolic access>	Coding	Binary
PLC name	PLC_OPC				
Settings					
Acquisition cycle	1 s	Acquisition mode	Cyclic in operation		
Limits					
Upper 2		Upper 1		Lower 1	
Lower 2					
Linear scaling					
Linear scaling	Disabled	PLC value range end value	10	PLC value range start value	0
HMI device value range end value	100	HMI device value range start value	0		
Values					
ID tag		Start value			
Comment					
Comment		Source comment			
Multiplexing					
Multiplexing	Disabled	Index tag			
Logging					
Data log					
GMP (Good Manufacturing Practice)					
Confirmation type	None	GMP relevant	Disabled	Comment required	Disabled

Tray_Sensor2

Tray_Sensor3

General					
Name	Tray_Sensor3	Display name		Connection	HMI_Connection_2
Data type	Bool	Array elements	0	Length	1
Address		Access mode	<symbolic access>	Coding	Binary
PLC name	PLC_OPC				
Settings					
Acquisition cycle	1 s	Acquisition mode	Cyclic in operation		
Limits					
Upper 2		Upper 1		Lower 1	
Lower 2					
Linear scaling					
Linear scaling	Disabled	PLC value range end value	10	PLC value range start value	0
HMI device value range end value	100	HMI device value range start value	0		
Values					
ID tag		Start value			
Comment					
Comment		Source comment			
Multiplexing					
Multiplexing	Disabled	Index tag			
Logging					
Data log					
GMP (Good Manufacturing Practice)					
Confirmation type	None	GMP relevant	Disabled	Comment required	Disabled

Tray_Sensor3

Tray_Sensorend

General					
Name	Tray_Sensorend	Display name		Connection	HMI_Connection_2
Data type	Bool	Array elements	0	Length	1
Address		Access mode	<symbolic access>	Coding	Binary
PLC name	PLC_OPC				
Settings					
Acquisition cycle	1 s	Acquisition mode	Cyclic in operation		
Limits					
Upper 2		Upper 1		Lower 1	
Lower 2					
Linear scaling					
Linear scaling	Disabled	PLC value range end value	10	PLC value range start value	0
HMI device value range end value	100	HMI device value range start value	0		
Values					
ID tag		Start value			
Comment					
Comment		Source comment			
Multiplexing					
Multiplexing	Disabled	Index tag			
Logging					
Data log					
GMP (Good Manufacturing Practice)					
Confirmation type	None	GMP relevant	Disabled	Comment required	Disabled

Totally Integrated Automation Portal						
--------------------------------------	--	--	--	--	--	--

Tray_Sensorend

Pick_Sensor

General					
Name	Pick_Sensor	Display name		Connection	HMI_Connection_2
Data type	Bool	Array elements	0	Length	1
Address		Access mode	<symbolic access>	Coding	Binary
PLC name	PLC_OPC				
Settings					
Acquisition cycle	1 s	Acquisition mode	Cyclic in operation		
Limits					
Upper 2		Upper 1		Lower 1	
Lower 2					
Linear scaling					
Linear scaling	Disabled	PLC value range end value	10	PLC value range start value	0
HMI device value range end value	100	HMI device value range start value	0		
Values					
ID tag		Start value			
Comment					
Comment		Source comment			
Multiplexing					
Multiplexing	Disabled	Index tag			
Logging					
Data log					
GMP (Good Manufacturing Practice)					
Confirmation type	None	GMP relevant	Disabled	Comment required	Disabled

Pick_Sensor

Pick_Done

General					
Name	Pick_Done	Display name		Connection	HMI_Connection_2
Data type	Bool	Array elements	0	Length	1
Address		Access mode	<symbolic access>	Coding	Binary
PLC name	PLC_OPC				
Settings					
Acquisition cycle	1 s	Acquisition mode	Cyclic in operation		
Limits					
Upper 2		Upper 1		Lower 1	
Lower 2					
Linear scaling					
Linear scaling	Disabled	PLC value range end value	10	PLC value range start value	0
HMI device value range end value	100	HMI device value range start value	0		
Values					
ID tag		Start value			
Comment					
Comment		Source comment			
Multiplexing					
Multiplexing	Disabled	Index tag			
Logging					
Data log					
GMP (Good Manufacturing Practice)					
Confirmation type	None	GMP relevant	Disabled	Comment required	Disabled

Pick_Done

Piece_Tray_done

General					
Name	Piece_Tray_done	Display name		Connection	HMI_Connection_2
Data type	Bool	Array elements	0	Length	1
Address		Access mode	<symbolic access>	Coding	Binary
PLC name	PLC_OPC				
Settings					
Acquisition cycle	1 s	Acquisition mode	Cyclic in operation		
Limits					
Upper 2		Upper 1		Lower 1	
Lower 2					
Linear scaling					
Linear scaling	Disabled	PLC value range end value	10	PLC value range start value	0
HMI device value range end value	100	HMI device value range start value	0		
Values					
ID tag		Start value			
Comment					
Comment		Source comment			
Multiplexing					
Multiplexing	Disabled	Index tag			
Logging					
Data log					
GMP (Good Manufacturing Practice)					
Confirmation type	None	GMP relevant	Disabled	Comment required	Disabled

--	--	--

Totally Integrated Automation Portal						
--------------------------------------	--	--	--	--	--	--

Piece_Tray_done

Piece_Bin_done

General					
Name	Piece_Bin_done	Display name		Connection	HMI_Connection_2
Data type	Bool	Array elements	0	Length	1
Address		Access mode	<symbolic access>	Coding	Binary
PLC name	PLC_OPC				
Settings					
Acquisition cycle	1 s	Acquisition mode	Cyclic in operation		
Limits					
Upper 2		Upper 1		Lower 1	
Lower 2					
Linear scaling					
Linear scaling	Disabled	PLC value range end value	10	PLC value range start value	0
HMI device value range end value	100	HMI device value range start value	0		
Values					
ID tag		Start value			
Comment					
Comment		Source comment			
Multiplexing					
Multiplexing	Disabled	Index tag			
Logging					
Data log					
GMP (Good Manufacturing Practice)					
Confirmation type	None	GMP relevant	Disabled	Comment required	Disabled

Piece_Bin_done

Scan_Done

General					
Name	Scan_Done	Display name		Connection	HMI_Connection_2
Data type	Bool	Array elements	0	Length	1
Address		Access mode	<symbolic access>	Coding	Binary
PLC name	PLC_OPC				
Settings					
Acquisition cycle	1 s	Acquisition mode	Cyclic in operation		
Limits					
Upper 2		Upper 1		Lower 1	
Lower 2					
Linear scaling					
Linear scaling	Disabled	PLC value range end value	10	PLC value range start value	0
HMI device value range end value	100	HMI device value range start value	0		
Values					
ID tag		Start value			
Comment					
Comment		Source comment			
Multiplexing					
Multiplexing	Disabled	Index tag			
Logging					
Data log					
GMP (Good Manufacturing Practice)					
Confirmation type	None	GMP relevant	Disabled	Comment required	Disabled

Scan_Done

Piece_OK

General					
Name	Piece_OK	Display name		Connection	HMI_Connection_2
Data type	Bool	Array elements	0	Length	1
Address		Access mode	<symbolic access>	Coding	Binary
PLC name	PLC_OPC				
Settings					
Acquisition cycle	1 s	Acquisition mode	Cyclic in operation		
Limits					
Upper 2		Upper 1		Lower 1	
Lower 2					
Linear scaling					
Linear scaling	Disabled	PLC value range end value	10	PLC value range start value	0
HMI device value range end value	100	HMI device value range start value	0		
Values					
ID tag		Start value			
Comment					
Comment		Source comment			
Multiplexing					
Multiplexing	Disabled	Index tag			
Logging					
Data log					
GMP (Good Manufacturing Practice)					
Confirmation type	None	GMP relevant	Disabled	Comment required	Disabled

--	--	--

Totally Integrated Automation Portal

Piece_OK

Tray_Out

General					
Name	Tray_Out	Display name		Connection	HMI_Connection_2
Data type	Bool	Array elements	0	Length	1
Address		Access mode	<symbolic access>	Coding	Binary
PLC name	PLC_OPC				
Settings					
Acquisition cycle	1 s	Acquisition mode	Cyclic in operation		
Limits					
Upper 2		Upper 1		Lower 1	
Lower 2					
Linear scaling					
Linear scaling	Disabled	PLC value range end value	10	PLC value range start value	0
HMI device value range end value	100	HMI device value range start value	0		
Values					
ID tag		Start value			
Comment					
Comment		Source comment			
Multiplexing					
Multiplexing	Disabled	Index tag			
Logging					
Data log					
GMP (Good Manufacturing Practice)					
Confirmation type	None	GMP relevant	Disabled	Comment required	Disabled

Tray_Out

Move_Tray_Conveyor

General					
Name	Move_Tray_Conveyor	Display name		Connection	HMI_Connection_2
Data type	Bool	Array elements	0	Length	1
Address		Access mode	<symbolic access>	Coding	Binary
PLC name	PLC_OPC				
Settings					
Acquisition cycle	1 s	Acquisition mode	Cyclic in operation		
Limits					
Upper 2		Upper 1		Lower 1	
Lower 2					
Linear scaling					
Linear scaling	Disabled	PLC value range end value	10	PLC value range start value	0
HMI device value range end value	100	HMI device value range start value	0		
Values					
ID tag		Start value			
Comment					
Comment		Source comment			
Multiplexing					
Multiplexing	Disabled	Index tag			
Logging					
Data log					
GMP (Good Manufacturing Practice)					
Confirmation type	None	GMP relevant	Disabled	Comment required	Disabled

Move_Tray_Conveyor

Move_Piece_Conveyor

General					
Name	Move_Piece_Conveyor	Display name		Connection	HMI_Connection_2
Data type	Bool	Array elements	0	Length	1
Address		Access mode	<symbolic access>	Coding	Binary
PLC name	PLC_OPC				
Settings					
Acquisition cycle	1 s	Acquisition mode	Cyclic in operation		
Limits					
Upper 2		Upper 1		Lower 1	
Lower 2					
Linear scaling					
Linear scaling	Disabled	PLC value range end value	10	PLC value range start value	0
HMI device value range end value	100	HMI device value range start value	0		
Values					
ID tag		Start value			
Comment					
Comment		Source comment			
Multiplexing					
Multiplexing	Disabled	Index tag			
Logging					
Data log					
GMP (Good Manufacturing Practice)					
Confirmation type	None	GMP relevant	Disabled	Comment required	Disabled

Totally Integrated Automation Portal		
--------------------------------------	--	--

Move_Piece_Conveyor

Move_Tray_Conveyor_Exit

General					
Name	Move_Tray_Conveyor_Exit	Display name		Connection	HMI_Connection_2
Data type	Bool	Array elements	0	Length	1
Address		Access mode	<symbolic access>	Coding	Binary
PLC name	PLC_OPC				
Settings					
Acquisition cycle	1 s	Acquisition mode	Cyclic in operation		
Limits					
Upper 2		Upper 1		Lower 1	
Lower 2					
Linear scaling					
Linear scaling	Disabled	PLC value range end value	10	PLC value range start value	0
HMI device value range end value	100	HMI device value range start value	0		
Values					
ID tag		Start value			
Comment					
Comment		Source comment			
Multiplexing					
Multiplexing	Disabled	Index tag			
Logging					
Data log					
GMP (Good Manufacturing Practice)					
Confirmation type	None	GMP relevant	Disabled	Comment required	Disabled

Move_Tray_Conveyor_Exit

Pick

General					
Name	Pick	Display name		Connection	HMI_Connection_2
Data type	Bool	Array elements	0	Length	1
Address		Access mode	<symbolic access>	Coding	Binary
PLC name	PLC_OPC				
Settings					
Acquisition cycle	1 s	Acquisition mode	Cyclic in operation		
Limits					
Upper 2		Upper 1		Lower 1	
Lower 2					
Linear scaling					
Linear scaling	Disabled	PLC value range end value	10	PLC value range start value	0
HMI device value range end value	100	HMI device value range start value	0		
Values					
ID tag		Start value			
Comment					
Comment		Source comment			
Multiplexing					
Multiplexing	Disabled	Index tag			
Logging					
Data log					
GMP (Good Manufacturing Practice)					
Confirmation type	None	GMP relevant	Disabled	Comment required	Disabled

Pick

Scan

General					
Name	Scan	Display name		Connection	HMI_Connection_2
Data type	Bool	Array elements	0	Length	1
Address		Access mode	<symbolic access>	Coding	Binary
PLC name	PLC_OPC				
Settings					
Acquisition cycle	1 s	Acquisition mode	Cyclic in operation		
Limits					
Upper 2		Upper 1		Lower 1	
Lower 2					
Linear scaling					
Linear scaling	Disabled	PLC value range end value	10	PLC value range start value	0
HMI device value range end value	100	HMI device value range start value	0		
Values					
ID tag		Start value			
Comment					
Comment		Source comment			
Multiplexing					
Multiplexing	Disabled	Index tag			
Logging					
Data log					
GMP (Good Manufacturing Practice)					
Confirmation type	None	GMP relevant	Disabled	Comment required	Disabled

--	--	--

Totally Integrated Automation Portal						
Scan						
OK_Piece						
General						
Name	OK_Piece	Display name		Connection	HMI_Connection_2	
Data type	Bool	Array elements	0	Length	1	
Address		Access mode	<symbolic access>	Coding	Binary	
PLC name	PLC_OPC					
Settings						
Acquisition cycle	1 s	Acquisition mode	Cyclic in operation			
Limits						
Upper 2		Upper 1		Lower 1		
Lower 2						
Linear scaling						
Linear scaling	Disabled	PLC value range end value	10	PLC value range start value	0	
HMI device value range end value	100	HMI device value range start value	0			
Values						
ID tag		Start value				
Comment						
Comment		Source comment				
Multiplexing						
Multiplexing	Disabled	Index tag				
Logging						
Data log						
GMP (Good Manufacturing Practice)						
Confirmation type	None	GMP relevant	Disabled	Comment required	Disabled	
OK_Piece						
NOK_Piece						
General						
Name	NOK_Piece	Display name		Connection	HMI_Connection_2	
Data type	Bool	Array elements	0	Length	1	
Address		Access mode	<symbolic access>	Coding	Binary	
PLC name	PLC_OPC					
Settings						
Acquisition cycle	1 s	Acquisition mode	Cyclic in operation			
Limits						
Upper 2		Upper 1		Lower 1		
Lower 2						
Linear scaling						
Linear scaling	Disabled	PLC value range end value	10	PLC value range start value	0	
HMI device value range end value	100	HMI device value range start value	0			
Values						
ID tag		Start value				
Comment						
Comment		Source comment				
Multiplexing						
Multiplexing	Disabled	Index tag				
Logging						
Data log						
GMP (Good Manufacturing Practice)						
Confirmation type	None	GMP relevant	Disabled	Comment required	Disabled	
NOK_Piece						
Light_State						
General						
Name	Light_State	Display name		Connection	HMI_Connection_2	
Data type	Int	Array elements	0	Length	2	
Address		Access mode	<symbolic access>	Coding	Binary	
PLC name	PLC_OPC					
Settings						
Acquisition cycle	1 s	Acquisition mode	Cyclic in operation			
Limits						
Upper 2		Upper 1		Lower 1		
Lower 2						
Linear scaling						
Linear scaling	Disabled	PLC value range end value	10	PLC value range start value	0	
HMI device value range end value	100	HMI device value range start value	0			
Values						
ID tag		Start value				
Comment						
Comment		Source comment				
Multiplexing						
Multiplexing	Disabled	Index tag				
Logging						
Data log						
GMP (Good Manufacturing Practice)						
Confirmation type	None	GMP relevant	Disabled	Comment required	Disabled	

Totally Integrated Automation Portal					
--------------------------------------	--	--	--	--	--

Light_State

Light_Tray

General					
Name	Light_Tray	Display name		Connection	HMI_Connection_2
Data type	Int	Array elements	0	Length	2
Address		Access mode	<symbolic access>	Coding	Binary
PLC name	PLC_OPC				
Settings					
Acquisition cycle	1 s	Acquisition mode	Cyclic in operation		
Limits					
Upper 2		Upper 1		Lower 1	
Lower 2					
Linear scaling					
Linear scaling	Disabled	PLC value range end value	10	PLC value range start value	0
HMI device value range end value	100	HMI device value range start value	0		
Values					
ID tag		Start value			
Comment					
Comment		Source comment			
Multiplexing					
Multiplexing	Disabled	Index tag			
Logging					
Data log					
GMP (Good Manufacturing Practice)					
Confirmation type	None	GMP relevant	Disabled	Comment required	Disabled

Light_Tray

--	--	--	--

Totally Integrated Automation Portal

HMI_1 [TP900 Comfort]

Connections

HMI_Connection_2

Name	HMI_Connection_2	Communication driver	SIMATIC S7 1500	Comment	
Online	Enabled	Station	S7-1500/ET200MP station_2	Partner	PLC_OPC
Node	CPU 1511-1 PN, PROFINET interface (R0/S1)	HMI time synchronization mode	Master		

Parameter

HMI device					
Interface	ETHERNET	Address	192.168.1.51	Access point	S7ONLINE
PLC					
Address	192.168.1.50				

Totally Integrated Automation Portal		
HMI_1 [TP900 Comfort] / HMI alarms Discrete alarms This folder is empty.		

Totally Integrated Automation Portal		
HMI_1 [TP900 Comfort] / HMI alarms Analog alarms This folder is empty.		

Totally Integrated Automation Portal		
--------------------------------------	--	--

HMI_1 [TP900 Comfort] / HMI alarms

Alarm groups

Alarm_group_1

Subtype	Alarm group	
General		
Name	Alarm_group_1	ID1

Alarm_group_10

Subtype	Alarm group	
General		
Name	Alarm_group_10	ID10

Alarm_group_11

Subtype	Alarm group	
General		
Name	Alarm_group_11	ID11

Alarm_group_12

Subtype	Alarm group	
General		
Name	Alarm_group_12	ID12

Alarm_group_13

Subtype	Alarm group	
General		
Name	Alarm_group_13	ID13

Alarm_group_14

Subtype	Alarm group	
General		
Name	Alarm_group_14	ID14

Alarm_group_15

Subtype	Alarm group	
General		
Name	Alarm_group_15	ID15

Alarm_group_16

Subtype	Alarm group	
General		
Name	Alarm_group_16	ID16

Alarm_group_2

Subtype	Alarm group	
General		
Name	Alarm_group_2	ID2

Alarm_group_3

Subtype	Alarm group	
General		
Name	Alarm_group_3	ID3

Alarm_group_4

Subtype	Alarm group	
General		
Name	Alarm_group_4	ID4

Alarm_group_5

Subtype	Alarm group	
General		
Name	Alarm_group_5	ID5

Alarm_group_6

Subtype	Alarm group	
General		
Name	Alarm_group_6	ID6

Alarm_group_7

Subtype	Alarm group	
General		
Name	Alarm_group_7	ID7

Alarm_group_8

Subtype	Alarm group	
General		
Name	Alarm_group_8	ID8

--	--	--

Totally Integrated Automation Portal		
--------------------------------------	--	--

Alarm_group_9

Subtype	Alarm group		
General			
Name	Alarm_group_9	ID	9

--	--	--

Totally Integrated Automation Portal

HMI_1 [TP900 Comfort] / HMI alarms

Alarm classes

Acknowledgement

General					
Name	Acknowledgement	Display name	A	ID	33
Common alarm class	Acknowledgement	Alarm log	<No log>	E-mail address	
Acknowledgment					
State machine	Alarm with single-mode acknowledg-ment				
State texts					
Text for "Incoming"	I	Text for "Outgoing"	O	Text for "Acknowl- edged"	A
Colors					
Background "Incom- ing/Acknowledged"	255, 255, 255	"Incoming/Acknowl- edged" flashing	Disabled	Background "Incom- ing"	255, 0, 0
"Incoming" flashing	Disabled	Background "In- coming/Outgoing/Ac- knowledgeed"	255, 255, 255	"Incoming/Outgo- ing/Acknowledged" flashing	Disabled
Background "Incom- ing/Outgoing"	255, 0, 0	"Incoming/Outgoing" flashing	Disabled		

Diagnosis events

General					
Name	Diagnosis events	Display name	S7	ID	4
Common alarm class	<No alarm class>	Alarm log	<No log>	E-mail address	
Acknowledgment					
State machine	Alarm without acknowledgment				
State texts					
Text for "Incoming"	I	Text for "Outgoing"	O	Text for "Acknowl- edged"	A
Colors					
Background "Incom- ing/Acknowledged"	255, 255, 255	"Incoming/Acknowl- edged" flashing	Disabled	Background "Incom- ing"	255, 255, 255
"Incoming" flashing	Disabled	Background "In- coming/Outgoing/Ac- knowledgeed"	255, 255, 255	"Incoming/Outgo- ing/Acknowledged" flashing	Disabled
Background "Incom- ing/Outgoing"	255, 255, 255	"Incoming/Outgoing" flashing	Disabled		

Errors

General					
Name	Errors	Display name	!	ID	1
Common alarm class	<No alarm class>	Alarm log	<No log>	E-mail address	
Acknowledgment					
State machine	Alarm with single-mode acknowledg-ment				
State texts					
Text for "Incoming"	I	Text for "Outgoing"	O	Text for "Acknowl- edged"	A
Colors					
Background "Incom- ing/Acknowledged"	255, 255, 255	"Incoming/Acknowl- edged" flashing	Disabled	Background "Incom- ing"	255, 0, 0
"Incoming" flashing	Disabled	Background "In- coming/Outgoing/Ac- knowledgeed"	255, 255, 255	"Incoming/Outgo- ing/Acknowledged" flashing	Disabled
Background "Incom- ing/Outgoing"	255, 0, 0	"Incoming/Outgoing" flashing	Disabled		

No Acknowledgement

General					
Name	No Acknowledgement	Display name	NA	ID	34
Common alarm class	No Acknowledgement	Alarm log	<No log>	E-mail address	
Acknowledgment					
State machine	Alarm without acknowledgment				
State texts					
Text for "Incoming"	I	Text for "Outgoing"	O	Text for "Acknowl- edged"	A
Colors					
Background "Incom- ing/Acknowledged"	255, 255, 255	"Incoming/Acknowl- edged" flashing	Disabled	Background "Incom- ing"	255, 0, 0
"Incoming" flashing	Disabled	Background "In- coming/Outgoing/Ac- knowledgeed"	255, 255, 255	"Incoming/Outgo- ing/Acknowledged" flashing	Disabled
Background "Incom- ing/Outgoing"	255, 0, 0	"Incoming/Outgoing" flashing	Disabled		

System

General					
Name	System	Display name	\$	ID	3
Common alarm class	<No alarm class>	Alarm log	<No log>	E-mail address	
Acknowledgment					
State machine	Alarm without acknowledgment				

Totally Integrated Automation Portal		
HMI_1 [TP900 Comfort] / HMI alarms Controller alarms This folder is empty.		

Totally Integrated Automation Portal		
HMI_1 [TP900 Comfort] / HMI alarms System events This folder is empty.		

Totally Integrated Automation Portal		
HMI_1 [TP900 Comfort] Recipes This folder is empty.		

Totally Integrated Automation Portal		
HMI_1 [TP900 Comfort] / Historical data Datalogs This folder is empty.		

Totally Integrated Automation Portal		
HMI_1 [TP900 Comfort] / Historical data AlarmLogs This folder is empty.		

Totally Integrated Automation Portal		
HMI_1 [TP900 Comfort] / Scripts VB scripts This folder is empty.		

Totally Integrated Automation Portal		
HMI_1 [TP900 Comfort] Scheduled tasks This folder is empty.		

Totally Integrated Automation Portal		
--------------------------------------	--	--

HMI_1 [TP900 Comfort]

Cycles

1 h

General					
Name	1 h	Cycle time	1	Cycle unit	hours
Comment					
Comment					

1 min

General					
Name	1 min	Cycle time	1	Cycle unit	minutes
Comment					
Comment					

1 s

General					
Name	1 s	Cycle time	1	Cycle unit	seconds
Comment					
Comment					

10 min

General					
Name	10 min	Cycle time	10	Cycle unit	minutes
Comment					
Comment					

10 s

General					
Name	10 s	Cycle time	10	Cycle unit	seconds
Comment					
Comment					

100 ms

General					
Name	100 ms	Cycle time	100	Cycle unit	milliseconds
Comment					
Comment					

2 s

General					
Name	2 s	Cycle time	2	Cycle unit	seconds
Comment					
Comment					

5 min

General					
Name	5 min	Cycle time	5	Cycle unit	minutes
Comment					
Comment					

5 s

General					
Name	5 s	Cycle time	5	Cycle unit	seconds
Comment					
Comment					

500 ms

General					
Name	500 ms	Cycle time	500	Cycle unit	milliseconds
Comment					
Comment					

--	--	--

Totally Integrated Automation Portal		
HMI_1 [TP900 Comfort] Reports This folder is empty.		

Totally Integrated Automation Portal		
--------------------------------------	--	--

HMI_1 [TP900 Comfort] / Text and graphic lists

Text lists

TextList_ScreenNames

Name	TextList_ScreenNames	List range	Value/Range	Comment	
Value: 1					
Entry type	Single value	Text	La Bilbainada GmbH		

--	--	--

Totally Integrated Automation Portal		
HMI_1 [TP900 Comfort] / Text and graphic lists Graphic lists This folder is empty.		

Totally Integrated Automation Portal		
--------------------------------------	--	--

HMI_1 [TP900 Comfort] / User administration

User

Administrator

General			
Name	Administrator	Number	1
Automatic logoff			
Automatic logoff	Enabled	Logoff time	5
Comment			
Comment	The user 'Administrator' is assigned to the 'Administrator' group.		
Groups			
Groups	Administrator group;		

--	--	--

Totally Integrated Automation Portal		
--------------------------------------	--	--

HMI_1 [TP900 Comfort] / User administration

Groups

Administrator group

General					
Name	Administrator group	Display name	Administrator group	Number	1
Password aging	Disabled				
Comment					
Comment	The 'Administrator' group is initially granted all rights.				
Authorizations					
Authorizations	User administration; Monitor; Operate;				

Users

General					
Name	Users	Display name	Users	Number	2
Password aging	Disabled				
Comment					
Comment	The 'Users' group is initially granted 'Operating' rights.				
Authorizations					
Authorizations	Operate;				

--	--	--

Totally Integrated Automation Portal		
--------------------------------------	--	--

HMI_1 [TP900 Comfort] / User administration

Authorizations

Monitor

General					
Name	Monitor	Authorization	Monitor	Authorization number	2
Comment					
Comment	'Monitor' authorization.				

Operate

General					
Name	Operate	Authorization	Operate	Authorization number	3
Comment					
Comment	'Operate' authorization.				

User administration

General					
Name	User administration	Authorization	User administration	Authorization number	1
Comment					
Comment	Authorization 'User administration' for managing users in the user view in Runtime.				

--	--	--