

**Date Submitted:** 10/2/2019**Task 01:**Youtube Link: <https://www.youtube.com/watch?v=90R0ljE34W4>

Modified Schematic (if applicable):

Modified Code:

```
// Insert code here
#include <stdint.h>
#include <stdbool.h>
#include "inc/hw_memmap.h"
#include "inc/hw_types.h"
#include "driverlib/debug.h"
#include "driverlib/sysctl.h"
#include "driverlib/adc.h"
#include "driverlib/gpio.h"

#ifdef DEBUG
void __error__(char *pcFilename, uint32_t ui32Line)
{
}
#endif

int main(void)
{
    uint32_t ui32ADC0Value[4];
    volatile uint32_t ui32TempAvg;
    volatile uint32_t ui32TempValueC;
    volatile uint32_t ui32TempValueF;

    SysCtlClockSet(SYSCTL_SYSDIV_5|SYSCTL_USE_PLL|SYSCTL_OSC_MAIN|SYSCTL_XTAL_16MHZ);

    SysCtlPeripheralEnable(SYSCTL_PERIPH_ADC0);
    ADCHardwareOversampleConfigure(ADC0_BASE, 64);
    SysCtlPeripheralEnable(SYSCTL_PERIPH_GPIOF);
    GPIOPinTypeGPIOOutput(GPIO_PORTF_BASE, GPIO_PIN_1|GPIO_PIN_2|GPIO_PIN_3);

    ADCSequenceConfigure(ADC0_BASE, 2, ADC_TRIGGER_PROCESSOR, 0);
    ADCSequenceStepConfigure(ADC0_BASE, 2, 0, ADC_CTL_TS);
    ADCSequenceStepConfigure(ADC0_BASE, 2, 1, ADC_CTL_TS);
    ADCSequenceStepConfigure(ADC0_BASE, 2, 2, ADC_CTL_TS);
    ADCSequenceStepConfigure(ADC0_BASE, 2, 3, ADC_CTL_TS|ADC_CTL_IE|ADC_CTL_END);
    ADCSequenceEnable(ADC0_BASE, 2);

    while(1)
    {
```

**Grading scheme:** 30% Coding, 30% Documentation, 40% Execution/Video.

```

ADCIntClear(ADC0_BASE, 2);
ADCProcessorTrigger(ADC0_BASE, 2);

while(!ADCIntStatus(ADC0_BASE, 2, false))
{
}

ADCSequenceDataGet(ADC0_BASE, 2, ui32ADC0Value);
ui32TempAvg = (ui32ADC0Value[0] + ui32ADC0Value[1] + ui32ADC0Value[2] +
ui32ADC0Value[3] + 2)/4;
ui32TempValueC = (1475 - ((2475 * ui32TempAvg)) / 4096)/10;
ui32TempValueF = ((ui32TempValueC * 9) + 160) / 5;
if(ui32TempValueF>=75)
{
    GPIOPinWrite(GPIO_PORTF_BASE, GPIO_PIN_1|GPIO_PIN_2|GPIO_PIN_3,4);
}
else
{
    GPIOPinWrite(GPIO_PORTF_BASE, GPIO_PIN_1|GPIO_PIN_2|GPIO_PIN_3,2);
}
}
}
-----

```

**Task 02:**

Youtube Link: <https://www.youtube.com/watch?v=1OG2hm5Ji4U>

Modified Schematic (if applicable):

Modified Code:

```

// Insert code here
int main(void)
{

    SysCtlClockSet(SYSCTL_SYSDIV_5|SYSCTL_USE_PLL|SYSCTL_OSC_MAIN|SYSCTL_XTAL_16MHZ);

    SysCtlPeripheralEnable(SYSCTL_PERIPH_ADC0);
    ADCHardwareOversampleConfigure(ADC0_BASE, 32);
    SysCtlPeripheralEnable(SYSCTL_PERIPH_GPIOF);
    GPIOPinTypeGPIOOutput(GPIO_PORTF_BASE, GPIO_PIN_1|GPIO_PIN_2|GPIO_PIN_3);

    ADCSequenceConfigure(ADC0_BASE, 2, ADC_TRIGGER_PROCESSOR, 0);
    ADCSequenceStepConfigure(ADC0_BASE, 2, 0, ADC_CTL_TS);
    ADCSequenceStepConfigure(ADC0_BASE, 2, 1, ADC_CTL_TS);
    ADCSequenceStepConfigure(ADC0_BASE, 2, 2, ADC_CTL_TS);
    ADCSequenceStepConfigure(ADC0_BASE, 2, 3, ADC_CTL_TS|ADC_CTL_IE|ADC_CTL_END);
    ADCSequenceEnable(ADC0_BASE, 2);

    SysCtlPeripheralEnable(SYSCTL_PERIPH_TIMER1);
    TimerConfigure(TIMER1_BASE, TIMER_CFG_PERIODIC);

    TimerLoadSet(TIMER1_BASE, TIMER_A, SysCtlClockGet()/2);
}

```

**Grading scheme:** 30% Coding, 30% Documentation, 40% Execution/Video.

```
IntEnable(INT_TIMER1A);
TimerIntEnable(TIMER1_BASE, TIMER_TIMA_TIMEOUT);
IntMasterEnable();
TimerEnable(TIMER1_BASE, TIMER_A);

ADCIntEnable(ADC0_BASE, 2);

while(1)
{
}

void Timer1AHandler(void)
{
    TimerIntClear(TIMER1_BASE, TIMER_TIMA_TIMEOUT);
    ADCIntClear(ADC0_BASE, 2);
    ADCProcessorTrigger(ADC0_BASE, 2);
    while(!ADCIntStatus(ADC0_BASE, 2, false))
    {
    }

    ADCSequenceDataGet(ADC0_BASE, 2, ui32ADC0Value);
    ui32TempAvg = (ui32ADC0Value[0] + ui32ADC0Value[1] + ui32ADC0Value[2] +
ui32ADC0Value[3] + 2)/4;
    ui32TempValueC = (1475 - ((2475 * ui32TempAvg)) / 4096)/10;
    ui32TempValueF = ((ui32TempValueC * 9) + 160) / 5;
    if(ui32TempValueF >= 75)
    {
        GPIOPinWrite(GPIO_PORTF_BASE, GPIO_PIN_1|GPIO_PIN_2|GPIO_PIN_3, 4);
    }
    else
    {
        GPIOPinWrite(GPIO_PORTF_BASE, GPIO_PIN_1|GPIO_PIN_2|GPIO_PIN_3, 2);
    }
}
```

---