List of JsonObjects output by the Plan Generator

(27 August, 2015 Shirley Crompton, STFC)

Note: The table applies to update and create operations. If an object is being removed, only the name attribute will be provided.

Object	Attribute	Type	Optional	Description
ApplicationTask	name	String		Application name as in Camel model, e.g. Scalarm
	objType	String		hardcoded to "application"
	description	String	yes	Description of the application.
	version	String		Application version.
	owner	String		Organisation that owns this application.
ApplicationInstanceTask	name	String		Application name as in Camel model appended with Instance, e.g. ScalarmInstance
	objType	String		hardcoded to "applicationInstance"
	type	String		Application type name, i.e. the Application name
VMInstanceTask	name	String		VM Instance name
	objType	String		hardcoded to "vmInstance"
	type	String		VM/Component type name
	cloud	String		Cloud provider name
	locations	String Array	yes	Cloud provider location.
	driver	String		Driver class for a particular cloud provider. Note that the value may be an empty String.
	endpoint	String		Endpoint for the cloud provider
	credential	Json object		This currently contains two key-value pairs : username and password Strings
	~~cloudLocation~~	~~String~~	~~yes~~	~~Geographical region of the CloudLocation. It may not be populated. ()A dataCentre's location is a choice of cloudLocation, geographicalRegion, country.)~~
	vmType	String		VM flavour name
	providedHostInstances	String Array		Array of provided host instance names
	providedCommunicationInstances	String Array	yes	Array of provided communication instance names
VMTypeTask	name	String		VM Type name
	objType	String		hardcoded to "VM"
	osImage	String	yes	OS image name. An object only contains either osImage or os. Not both.
	os	String	yes	OS name. An object only contains either osImage or os. Not both.
	os64bit	boolean	yes	True if IS is 64bit, else false. This is an attribute of os.
	configName	String	yes	(Configuration) name
	downloadCmd	String	yes	(Configuration) download command
	configureCmd	String	yes	(Configuration) configure command
	installCmd	String	yes	(Configuration) install command
	startCmd	String	yes	(Configuration) start command
	StopCmd	String	yes	(Configuration) stop command
	uploadCmd	String	yes	(Configuration) upload command
	providedHosts	String Array		Array of provided host names
	providedCommunications	String Array	yes	Array of provided communication names
ComponentInstanceTask	name	String		Internal component instance name
	objType	String		hardcoded to "internalComponentInstance"
	type	String		Internal component type name
	~~initialInstance~~	~~int~~		~~Initial instance. Currently hardcoded to 1. This attribute may be removed in a later release.~~
	providedHostInstances	String Array	yes	Array of provided host instance names
	requiredHostInstance	String		Required communication instance name
	providedCommunicationInstances	String Array	yes	Array of provided communication instance names
	requiredCommunicationInstances	String Array		Array of required communication instance names
ComponentTypeTask	name	String		Internal component type name
	objType	String		hardcoded to "internalComponent"
	configName	String	yes	(Configuration) name
	downloadCmd	String	yes	(Configuration) download command
	configureCmd	String	yes	(Configuration) configure command
	installCmd	String	yes	(Configuration) install command
	startCmd	String	yes	(Configuration) start command
	StopCmd	String	yes	(Configuration) stop command
	uploadCmd	String	yes	(Configuration) upload command
	providedHosts	String Array	yes	Array of provided host names
	requiredHost	String		Required host name
	providedCommunications	String Array	yes	Array of provided host names
	requiredCommunications	String Array		Array of required communication names
CommunicationInstanceTask	name	String		Communication instance name
	objType	String		hardcoded to "communicationInstance"
	type	String		Communication type name
	providerInstance	String		Communication provider instance name
	providerCompInstanceTask	String	yes	ComponentInstanceTask name - owner of the providerInstance
	consumerInstance	String		Communication consumer instance name

	consumerCompInstanceTask	String	yes	ComponentInstanceTask name - owner of the consumerInstance
CommunicationTypeTask	name	String		Communication type name
	objType	String		hardcoded to "communication"
	communicationType	String		LOCAL, REMOTE, ANY
	provider	String		Provider name
	providerCompTypeTask	String	yes	ComponentTypeTask name - owner of the Provider
	providerPort	int		Provider port number
	providedPortconfigName	String	yes	(Configuration) name
	providedPortdownloadCmd	String	yes	(Configuration) download command
	providedPortconfigureCmd	String	yes	(Configuration) configure command
	providedPortinstallCmd	String	yes	(Configuration) install command
	providedPortstartCmd	String	yes	(Configuration) start command
	providedPortStopCmd	String	yes	(Configuration) stop command
	providedPortuploadCmd	String	yes	(Configuration) upload command
	consumer	String		Consumer name
	consumerCompTypeTask	String	yes	ComponntTypeTask name - owner of the Consumer
	isMandatory	boolean		True if consumer depends on this communication, else false
	consumerPort	int		Consumer port number
	requiredPortconfigName	String	yes	(Configuration) name
	requiredPortdownloadCmd	String	yes	(Configuration) download command
	requiredPortconfigureCmd	String	yes	(Configuration) configure command
	requiredPortinstallCmd	String	yes	(Configuration) install command
	requiredPortstartCmd	String	yes	(Configuration) start command
	requiredPortStopCmd	String	yes	(Configuration) stop command
	requiredPortuploadCmd	String	yes	(Configuration) upload command
HostingInstanceTask	name	String		Hosting instance name
	objType	String		hardcoded to "hostingInstance"
	type	String		Hosting type name
	providerInstance	String		Hosting provider instance name. The provider could be of type VM or an Internal Component.
	providerCompInstanceTask	String	yes	ComponentInstanceTask name - owner of the providerInstance
	consumerInstance	String		Hosting consumer instance name
	consumerCompInstanceTask	String	yes	ComponentInstanceTask name - owner of the consumerInstance
HostingTypeTask	name	String		Hosting name
	objType	String		hardcoded to "hosting"
	provider	String		Provider name
	providerCompTypeTask	String	yes	ComponentTypeTask name - owner of the Provider
	providedHostconfigName	String	yes	(Configuration) name
	providedHostdownloadCmd	String	yes	(Configuration) download command
	providedHostconfigureCmd	String	yes	(Configuration) configure command
	providedHostinstallCmd	String	yes	(Configuration) install command
	providedHoststartCmd	String	yes	(Configuration) start command
	providedHostStopCmd	String	yes	(Configuration) stop command
	providedHostuploadCmd	String	yes	(Configuration) upload command
	consumer	String		Consumer name
	consumerCompTypeTask	String	yes	ComponentTypeTask name - owner of the Consumer
	requiredHostconfigName	String	yes	(Configuration) name
	requiredHostdownloadCmd	String	yes	(Configuration) download command
	requiredHostconfigureCmd	String	yes	(Configuration) configure command
	requiredHostinstallCmd	String	yes	(Configuration) install command
	requiredHoststartCmd	String	yes	(Configuration) start command
	requiredHostStopCmd	String	yes	(Configuration) stop command
	requiredHostuploadCmd	String	yes	(Configuration) upload command