



ZAP by
Checkmarx

ZAP by Checkmarx Scanning Report

Sites: <https://firefox-settings-attachments.cdn.mozilla.net> <http://172.30.26.1>

Generated on Sun, 26 Jul 2026 17:06:17

ZAP Version: 2.17.0

ZAP by [Checkmarx](#)

Summary of Alerts

Risk Level	Number of Alerts
High	0
Medium	5
Low	2
Informational	5
False Positives:	0

Alerts

Name	Risk Level	Number of Instances
Absence of Anti-CSRF Tokens	Medium	1
CSP: Failure to Define Directive with No Fallback	Medium	1
CSP: script-src unsafe-eval	Medium	1
CSP: script-src unsafe-inline	Medium	1
CSP: style-src unsafe-inline	Medium	1
CSP: Notices	Low	1
Cookie without SameSite Attribute	Low	4
CSP: X-Content-Security-Policy	Informational	1
CSP: X-WebKit-CSP	Informational	1
Modern Web Application	Informational	1
Obsolete Content Security Policy (CSP) Header Found	Informational	1
Session Management Response Identified	Informational	1

Alert Detail

Medium	Absence of Anti-CSRF Tokens
	No Anti-CSRF tokens were found in a HTML submission form.

Description	A cross-site request forgery is an attack that involves forcing a victim to send an HTTP request to a target destination without their knowledge or intent in order to perform an action as the victim. The underlying cause is application functionality using predictable URL /form actions in a repeatable way. The nature of the attack is that CSRF exploits the trust that a web site has for a user. By contrast, cross-site scripting (XSS) exploits the trust that a user has for a web site. Like XSS, CSRF attacks are not necessarily cross-site, but they can be. Cross-site request forgery is also known as CSRF, XSRF, one-click attack, session riding, confused deputy, and sea surf. CSRF attacks are effective in a number of situations, including: * The victim has an active session on the target site. * The victim is authenticated via HTTP auth on the target site. * The victim is on the same local network as the target site. CSRF has primarily been used to perform an action against a target site using the victim's privileges, but recent techniques have been discovered to disclose information by gaining access to the response. The risk of information disclosure is dramatically increased when the target site is vulnerable to XSS, because XSS can be used as a platform for CSRF, allowing the attack to operate within the bounds of the same-origin policy.
URL	http://172.30.26.1:80
Node Name	http://172.30.26.1
Method	GET
Attack	
Evidence	<form method="post" action="index.php" name="login_form" class="disableAjax login hide js-show">
Other Info	No known Anti-CSRF token [anticsrf, CSRFToken, __RequestVerificationToken, csrfmiddlewaretoken, authenticity_token, OWASP_CSRFTOKEN, anoncsrf, csrf_token, _csrf, _csrfSecret, __csrf_magic, CSRF, _token, _csrf_token, _csrfToken] was found in the following HTML form: [Form 2: "collation_connection" "input_go" "input_password" "input_username" "lang" "server" "target" "token"].
Instances	1
Solution	Phase: Architecture and Design Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. For example, use anti-CSRF packages such as the OWASP CSRFGuard. Phase: Implementation Ensure that your application is free of cross-site scripting issues, because most CSRF defenses can be bypassed using attacker-controlled script. Phase: Architecture and Design Generate a unique nonce for each form, place the nonce into the form, and verify the nonce upon receipt of the form. Be sure that the nonce is not predictable (CWE-330). Note that this can be bypassed using XSS. Identify especially dangerous operations. When the user performs a dangerous operation, send a separate confirmation request to ensure that the user intended to perform that operation. Note that this can be bypassed using XSS. Use the ESAPI Session Management control.

	This control includes a component for CSRF. Do not use the GET method for any request that triggers a state change. Phase: Implementation Check the HTTP Referer header to see if the request originated from an expected page. This could break legitimate functionality, because users or proxies may have disabled sending the Referer for privacy reasons.
Reference	https://cheatsheetseries.owasp.org/cheatsheets/Cross-Site_Request_Forgery_Prevention_Cheat_Sheet.html https://cwe.mitre.org/data/definitions/352.html
CWE Id	352
WASC Id	9
Plugin Id	10202

Medium	CSP: Failure to Define Directive with No Fallback
Description	The Content Security Policy fails to define one of the directives that has no fallback. Missing /excluding them is the same as allowing anything.
URL	http://172.30.26.1:80
Node Name	http://172.30.26.1
Method	GET
Attack	
Evidence	default-src 'self' ;script-src 'self' 'unsafe-inline' 'unsafe-eval' ;;style-src 'self' 'unsafe-inline' ;referrer no-referrer;img-src 'self' data: *.tile.openstreetmap.org;
Other Info	The directive(s): frame-ancestors, form-action is/are among the directives that do not fallback to default-src.
Instances	1
Solution	Ensure that your web server, application server, load balancer, etc. is properly configured to set the Content-Security-Policy header.
Reference	https://www.w3.org/TR/CSP/ https://caniuse.com/#search=content+security+policy https://content-security-policy.com/ https://github.com/HtmlUnit/htmlunit-csp https://web.dev/articles/csp#resource-options
CWE Id	693
WASC Id	15
Plugin Id	10055

Medium	CSP: script-src unsafe-eval
Description	Content Security Policy (CSP) is an added layer of security that helps to detect and mitigate certain types of attacks. Including (but not limited to) Cross Site Scripting (XSS), and data injection attacks. These attacks are used for everything from data theft to site defacement or distribution of malware. CSP provides a set of standard HTTP headers that allow website owners to declare approved sources of content that browsers should be allowed to load on that page — covered types are JavaScript, CSS, HTML frames, fonts, images and embeddable objects such as Java applets, ActiveX, audio and video files.
URL	http://172.30.26.1:80
Node Name	http://172.30.26.1
Method	GET
Attack	

Evidence	default-src 'self' ;script-src 'self' 'unsafe-inline' 'unsafe-eval' ;;style-src 'self' 'unsafe-inline' ;referrer no-referrer;img-src 'self' data: *.tile.openstreetmap.org;
Other Info	script-src includes unsafe-eval.
Instances	1
Solution	Ensure that your web server, application server, load balancer, etc. is properly configured to set the Content-Security-Policy header.
Reference	https://www.w3.org/TR/CSP/ https://caniuse.com/#search=content+security+policy https://content-security-policy.com/ https://github.com/HtmlUnit/htmlunit-csp https://web.dev/articles/csp#resource-options
CWE Id	693
WASC Id	15
Plugin Id	10055

Medium	CSP: script-src unsafe-inline
Description	Content Security Policy (CSP) is an added layer of security that helps to detect and mitigate certain types of attacks. Including (but not limited to) Cross Site Scripting (XSS), and data injection attacks. These attacks are used for everything from data theft to site defacement or distribution of malware. CSP provides a set of standard HTTP headers that allow website owners to declare approved sources of content that browsers should be allowed to load on that page — covered types are JavaScript, CSS, HTML frames, fonts, images and embeddable objects such as Java applets, ActiveX, audio and video files.
URL	http://172.30.26.1:80
Node Name	http://172.30.26.1
Method	GET
Attack	
Evidence	default-src 'self' ;script-src 'self' 'unsafe-inline' 'unsafe-eval' ;;style-src 'self' 'unsafe-inline' ;referrer no-referrer;img-src 'self' data: *.tile.openstreetmap.org;
Other Info	script-src includes unsafe-inline.
Instances	1
Solution	Ensure that your web server, application server, load balancer, etc. is properly configured to set the Content-Security-Policy header.
Reference	https://www.w3.org/TR/CSP/ https://caniuse.com/#search=content+security+policy https://content-security-policy.com/ https://github.com/HtmlUnit/htmlunit-csp https://web.dev/articles/csp#resource-options
CWE Id	693
WASC Id	15
Plugin Id	10055

Medium	CSP: style-src unsafe-inline
Description	Content Security Policy (CSP) is an added layer of security that helps to detect and mitigate certain types of attacks. Including (but not limited to) Cross Site Scripting (XSS), and data injection attacks. These attacks are used for everything from data theft to site defacement or distribution of malware. CSP provides a set of standard HTTP headers that allow website owners to declare approved sources of content that browsers should be allowed to load on that page — covered types are JavaScript, CSS, HTML frames, fonts, images and embeddable objects such as Java applets, ActiveX, audio and video files.
URL	http://172.30.26.1:80

Node Name	http://172.30.26.1
Method	GET
Attack	
Evidence	default-src 'self' ;script-src 'self' 'unsafe-inline' 'unsafe-eval' ;;style-src 'self' 'unsafe-inline' ;referrer no-referrer;img-src 'self' data: *.tile.openstreetmap.org;
Other Info	style-src includes unsafe-inline.
Instances	1
Solution	Ensure that your web server, application server, load balancer, etc. is properly configured to set the Content-Security-Policy header.
Reference	https://www.w3.org/TR/CSP/ https://caniuse.com/#search=content+security+policy https://content-security-policy.com/ https://github.com/HtmlUnit/htmlunit-csp https://web.dev/articles/csp#resource-options
CWE Id	693
WASC Id	15
Plugin Id	10055

Low	CSP: Notices
Description	Content Security Policy (CSP) is an added layer of security that helps to detect and mitigate certain types of attacks. Including (but not limited to) Cross Site Scripting (XSS), and data injection attacks. These attacks are used for everything from data theft to site defacement or distribution of malware. CSP provides a set of standard HTTP headers that allow website owners to declare approved sources of content that browsers should be allowed to load on that page — covered types are JavaScript, CSS, HTML frames, fonts, images and embeddable objects such as Java applets, ActiveX, audio and video files.
URL	http://172.30.26.1:80
Node Name	http://172.30.26.1
Method	GET
Attack	
Evidence	default-src 'self' ;script-src 'self' 'unsafe-inline' 'unsafe-eval' ;;style-src 'self' 'unsafe-inline' ;referrer no-referrer;img-src 'self' data: *.tile.openstreetmap.org;
Other Info	Warnings: The referrer directive has been deprecated in favor of the Referrer-Policy header
Instances	1
Solution	Ensure that your web server, application server, load balancer, etc. is properly configured to set the Content-Security-Policy header.
Reference	https://www.w3.org/TR/CSP/ https://caniuse.com/#search=content+security+policy https://content-security-policy.com/ https://github.com/HtmlUnit/htmlunit-csp https://web.dev/articles/csp#resource-options
CWE Id	693
WASC Id	15
Plugin Id	10055

Low	Cookie without SameSite Attribute

Description	A cookie has been set without the SameSite attribute, which means that the cookie can be sent as a result of a 'cross-site' request. The SameSite attribute is an effective counter measure to cross-site request forgery, cross-site script inclusion, and timing attacks.
URL	http://172.30.26.1:80
Node Name	http://172.30.26.1
Method	GET
Attack	
Evidence	Set-Cookie: phpMyAdmin
Other Info	
URL	http://172.30.26.1:80
Node Name	http://172.30.26.1
Method	GET
Attack	
Evidence	Set-Cookie: pma_collation_connection
Other Info	
URL	http://172.30.26.1:80
Node Name	http://172.30.26.1
Method	GET
Attack	
Evidence	Set-Cookie: pma_lang
Other Info	
URL	http://172.30.26.1:80
Node Name	http://172.30.26.1
Method	GET
Attack	
Evidence	Set-Cookie: pmaCookieVer
Other Info	
Instances	4
Solution	Ensure that the SameSite attribute is set to either 'lax' or ideally 'strict' for all cookies.
Reference	https://datatracker.ietf.org/doc/html/draft-ietf-httpbis-cookie-same-site
CWE Id	1275
WASC Id	13
Plugin Id	10054

Informational	CSP: X-Content-Security-Policy
Description	Content Security Policy (CSP) is an added layer of security that helps to detect and mitigate certain types of attacks. Including (but not limited to) Cross Site Scripting (XSS), and data injection attacks. These attacks are used for everything from data theft to site defacement or distribution of malware. CSP provides a set of standard HTTP headers that allow website owners to declare approved sources of content that browsers should be allowed to load on

	that page — covered types are JavaScript, CSS, HTML frames, fonts, images and embeddable objects such as Java applets, ActiveX, audio and video files.
URL	http://172.30.26.1:80
Node Name	http://172.30.26.1
Method	GET
Attack	
Evidence	default-src 'self' ;options inline-script eval-script;referrer no-referrer;img-src 'self' data: *.tile.openstreetmap.org;
Other Info	The header X-Content-Security-Policy was found on this response. While it is a good sign that CSP is implemented to some degree the policy specified in this header has not been analyzed by ZAP. To ensure full support by modern browsers ensure that the Content-Security-Policy header is defined and attached to responses.
Instances	1
Solution	Ensure that your web server, application server, load balancer, etc. is properly configured to set the Content-Security-Policy header.
Reference	https://www.w3.org/TR/CSP/ https://caniuse.com/#search=content+security+policy https://content-security-policy.com/ https://github.com/HtmlUnit/htmlunit-csp https://web.dev/articles/csp#resource-options
CWE Id	693
WASC Id	15
Plugin Id	10055

Informational	CSP: X-WebKit-CSP
Description	Content Security Policy (CSP) is an added layer of security that helps to detect and mitigate certain types of attacks. Including (but not limited to) Cross Site Scripting (XSS), and data injection attacks. These attacks are used for everything from data theft to site defacement or distribution of malware. CSP provides a set of standard HTTP headers that allow website owners to declare approved sources of content that browsers should be allowed to load on that page — covered types are JavaScript, CSS, HTML frames, fonts, images and embeddable objects such as Java applets, ActiveX, audio and video files.
URL	http://172.30.26.1:80
Node Name	http://172.30.26.1
Method	GET
Attack	
Evidence	default-src 'self' ;script-src 'self' 'unsafe-inline' 'unsafe-eval';referrer no-referrer;style-src 'self' 'unsafe-inline' ;img-src 'self' data: *.tile.openstreetmap.org;
Other Info	The header X-WebKit-CSP was found on this response. While it is a good sign that CSP is implemented to some degree the policy specified in this header has not been analyzed by ZAP. To ensure full support by modern browsers ensure that the Content-Security-Policy header is defined and attached to responses.
Instances	1
Solution	Ensure that your web server, application server, load balancer, etc. is properly configured to set the Content-Security-Policy header.
Reference	https://www.w3.org/TR/CSP/ https://caniuse.com/#search=content+security+policy https://content-security-policy.com/ https://github.com/HtmlUnit/htmlunit-csp https://web.dev/articles/csp#resource-options
CWE Id	693

WASC Id	15
Plugin Id	10055

Informational	Modern Web Application
Description	The application appears to be a modern web application. If you need to explore it automatically then the Ajax Spider may well be more effective than the standard one.
URL	http://172.30.26.1:80
Node Name	http://172.30.26.1
Method	GET
Attack	
Evidence	<noscript><style>html{display:block}</style></noscript>
Other Info	A noScript tag has been found, which is an indication that the application works differently with JavaScript enabled compared to when it is not.
Instances	1
Solution	This is an informational alert and so no changes are required.
Reference	
CWE Id	
WASC Id	
Plugin Id	10109

Informational	Obsolete Content Security Policy (CSP) Header Found
Description	The "X-Content-Security-Policy" and "X-WebKit-CSP" headers are no longer recommended.
URL	http://172.30.26.1:80
Node Name	http://172.30.26.1
Method	GET
Attack	
Evidence	
Other Info	
Instances	1
Solution	Ensure that your web server, application server, load balancer, etc. is configured to set the Content-Security-Policy header.
Reference	https://developer.mozilla.org/en-US/docs/Web/HTTP/Guides/CSP https://cheatsheetseries.owasp.org/cheatsheets/Content_Security_Policy_Cheat_Sheet.html https://www.w3.org/TR/CSP/ https://w3c.github.io/webappsec-csp/ https://web.dev/articles/csp https://caniuse.com/#feat=contentsecuritypolicy https://content-security-policy.com/
CWE Id	693
WASC Id	15
Plugin Id	10038

Informational	Session Management Response Identified
Description	The given response has been identified as containing a session management token. The 'Other Info' field contains a set of header tokens that can be used in the Header Based Session Management Method. If the request is in a context which has a Session

	Management Method set to "Auto-Detect" then this rule will change the session management to use the tokens identified.
URL	http://172.30.26.1:80
Node Name	http://172.30.26.1
Method	GET
Attack	
Evidence	pma_collation_connection
Other Info	cookie:pma_collation_connection cookie:phpMyAdmin
Instances	1
Solution	This is an informational alert rather than a vulnerability and so there is nothing to fix.
Reference	https://www.zaproxy.org/docs/desktop/addons/authentication-helper/session-mgmt-id/
CWE Id	
WASC Id	
Plugin Id	10112