



My Basic Network Scan

Report generated by Tenable Nessus™

Thu, 23 Jul 2026 18:43:32 EDT


TABLE OF CONTENTS

Vulnerabilities by Host

• 172.30.1.1.....	4
• 172.30.2.2.....	131
• 172.30.4.1.....	176
• 172.30.6.3.....	210
• 172.30.7.1.....	234
• 172.30.9.1.....	251
• 172.30.9.2.....	271
• 172.30.9.3.....	301
• 172.30.15.1.....	329
• 172.30.15.2.....	353
• 172.30.30.1.....	378
• 172.30.40.7.....	398
• 172.30.40.8.....	423
• 172.31.1.1.....	459
• 172.31.1.3.....	467
• 172.31.1.5.....	475
• 172.31.1.50.....	483
• 172.31.1.97.....	502

Vulnerabilities by Host

172.30.1.1



Scan Information

Start time: Thu Jul 23 18:30:17 2026

End time: Thu Jul 23 18:39:10 2026

Host Information

Netbios Name: 8E45B17A1053

IP: 172.30.1.1

MAC Address: D6:25:D6:70:75:0C

OS: Linux Kernel 2.6 on Ubuntu 8.04 (hardy)

Vulnerabilities

201352 - Canonical Ubuntu Linux SEoL (8.04.x)

Synopsis

An unsupported version of Canonical Ubuntu Linux is installed on the remote host.

Description

According to its version, Canonical Ubuntu Linux is 8.04.x. It is, therefore, no longer maintained by its vendor or provider.

Lack of support implies that no new security patches for the product will be released by the vendor. As a result, it may contain security vulnerabilities.

See Also

<http://www.nessus.org/u?3bdb2d2e>

Solution

Upgrade to a version of Canonical Ubuntu Linux that is currently supported.

Risk Factor

Critical

CVSS v3.0 Base Score

10.0 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H)

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

Plugin Information

Published: 2024/07/03, Modified: 2025/03/26

Plugin Output

tcp/80/www

OS : Ubuntu Linux 8.04
Security End of Life : May 9, 2013
Time since Security End of Life (Est.) : >= 13 years

32314 - Debian OpenSSH/OpenSSL Package Random Number Generator Weakness

Synopsis

The remote SSH host keys are weak.

Description

The remote SSH host key has been generated on a Debian or Ubuntu system which contains a bug in the random number generator of its OpenSSL library.

The problem is due to a Debian packager removing nearly all sources of entropy in the remote version of OpenSSL.

An attacker can easily obtain the private part of the remote key and use this to set up decipher the remote session or set up a man in the middle attack.

See Also

<http://www.nessus.org/u?107f9bdc>

<http://www.nessus.org/u?f14f4224>

Solution

Consider all cryptographic material generated on the remote host to be guessable. In particular, all SSH, SSL and OpenVPN key material should be re-generated.

Risk Factor

Critical

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

8.3 (CVSS2#E:F/RL:OF/RC:C)

References

BID	29179
CVE	CVE-2008-0166
XREF	CWE:310

Exploitable With

Core Impact (true)

Plugin Information

Published: 2008/05/14, Modified: 2024/07/24

Plugin Output

tcp/22/ssh

32321 - Debian OpenSSH/OpenSSL Package Random Number Generator Weakness (SSL check)

Synopsis

The remote SSL certificate uses a weak key.

Description

The remote x509 certificate on the remote SSL server has been generated on a Debian or Ubuntu system which contains a bug in the random number generator of its OpenSSL library.

The problem is due to a Debian packager removing nearly all sources of entropy in the remote version of OpenSSL.

An attacker can easily obtain the private part of the remote key and use this to decipher the remote session or set up a man in the middle attack.

See Also

<http://www.nessus.org/u?107f9bdc>

<http://www.nessus.org/u?f14f4224>

Solution

Consider all cryptographic material generated on the remote host to be guessable. In particular, all SSH, SSL and OpenVPN key material should be re-generated.

Risk Factor

Critical

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

8.3 (CVSS2#E:F/RL:OF/RC:C)

References

BID	29179
CVE	CVE-2008-0166
XREF	CWE:310

Exploitable With

Core Impact (true)

Plugin Information

Published: 2008/05/15, Modified: 2020/11/16

Plugin Output

tcp/5432/postgresql

20007 - SSL Version 2 and 3 Protocol Detection

Synopsis

The remote service encrypts traffic using a protocol with known weaknesses.

Description

The remote service accepts connections encrypted using SSL 2.0 and/or SSL 3.0. These versions of SSL are affected by several cryptographic flaws, including:

- An insecure padding scheme with CBC ciphers.
- Insecure session renegotiation and resumption schemes.

An attacker can exploit these flaws to conduct man-in-the-middle attacks or to decrypt communications between the affected service and clients.

Although SSL/TLS has a secure means for choosing the highest supported version of the protocol (so that these versions will be used only if the client or server support nothing better), many web browsers implement this in an unsafe way that allows an attacker to downgrade a connection (such as in POODLE). Therefore, it is recommended that these protocols be disabled entirely.

NIST has determined that SSL 3.0 is no longer acceptable for secure communications. As of the date of enforcement found in PCI DSS v3.1, any version of SSL will not meet the PCI SSC's definition of 'strong cryptography'.

See Also

<https://www.schneier.com/academic/paperfiles/paper-ssl.pdf>

<http://www.nessus.org/u?b06c7e95>

<http://www.nessus.org/u?247c4540>

<https://www.openssl.org/~bodo/ssl-poodle.pdf>

<http://www.nessus.org/u?5d15ba70>

<https://www.imperialviolet.org/2014/10/14/poodle.html>

<https://tools.ietf.org/html/rfc7507>

<https://tools.ietf.org/html/rfc7568>

Solution

Consult the application's documentation to disable SSL 2.0 and 3.0.

Use TLS 1.2 (with approved cipher suites) or higher instead.

Risk Factor

Critical

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

Plugin Information

Published: 2005/10/12, Modified: 2026/04/13

Plugin Output

tcp/5432/postgresql

- SSLv3 is enabled and the server supports at least one cipher.
Explanation: TLS 1.0 and SSL 3.0 cipher suites may be used with SSLv3

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	---	-----	---
EDH-RSA-DES-CBC3-SHA		DHE	RSA	3DES-CBC(168)	
SHA1					
DES-CBC3-SHA		RSA	RSA	3DES-CBC(168)	
SHA1					

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	---	-----	---
DHE-RSA-AES128-SHA		DHE	RSA	AES-CBC(128)	
SHA1					
DHE-RSA-AES256-SHA		DHE	RSA	AES-CBC(256)	
SHA1					
AES128-SHA		RSA	RSA	AES-CBC(128)	
SHA1					
AES256-SHA		RSA	RSA	AES-CBC(256)	
SHA1					
RC4-SHA		RSA	RSA	RC4(128)	
SHA1					

The fields above are :

{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}

42873 - SSL Medium Strength Cipher Suites Supported (SWEET32)

Synopsis

The remote service supports the use of medium strength SSL ciphers.

Description

The remote host supports the use of SSL ciphers that offer medium strength encryption. Nessus regards medium strength as any encryption that uses key lengths at least 64 bits and less than 112 bits, or else that uses the 3DES encryption suite.

Note that it is considerably easier to circumvent medium strength encryption if the attacker is on the same physical network.

See Also

<http://www.nessus.org/u?df5555f5>

<https://sweet32.info>

Solution

Reconfigure the affected application if possible to avoid use of medium strength ciphers.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:N/A:N)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

References

CVE CVE-2016-2183

Plugin Information

Published: 2009/11/23, Modified: 2025/02/12

Plugin Output

tcp/5432/postgresql

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
EDH-RSA-DES-CBC3-SHA	0x00, 0x16	DHE	RSA	3DES-CBC(168)	
SHA1					
DES-CBC3-SHA	0x00, 0x0A	RSA	RSA	3DES-CBC(168)	
SHA1					

The fields above are :

```
{Tenable ciphernamex}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}
```

90509 - Samba Badlock Vulnerability

Synopsis

An SMB server running on the remote host is affected by the Badlock vulnerability.

Description

The version of Samba, a CIFS/SMB server for Linux and Unix, running on the remote host is affected by a flaw, known as Badlock, that exists in the Security Account Manager (SAM) and Local Security Authority (Domain Policy) (LSAD) protocols due to improper authentication level negotiation over Remote Procedure Call (RPC) channels. A man-in-the-middle attacker who is able to intercept the traffic between a client and a server hosting a SAM database can exploit this flaw to force a downgrade of the authentication level, which allows the execution of arbitrary Samba network calls in the context of the intercepted user, such as viewing or modifying sensitive security data in the Active Directory (AD) database or disabling critical services.

See Also

<https://www.samba.org/samba/security/CVE-2016-2118.html>

Solution

Upgrade to Samba version 4.2.11 / 4.3.8 / 4.4.2 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:H/PR:N/UI:R/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

6.8 (CVSS2#AV:N/AC:M/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.0 (CVSS2#E:U/RL:OF/RC:C)

References

BID	86002
CVE	CVE-2016-2118

XREF

CERT:813296

Plugin Information

Published: 2016/04/13, Modified: 2025/11/17

Plugin Output

tcp/445/cifs

Nessus detected that the Samba Badlock patch has not been applied.

10205 - rlogin Service Detection

Synopsis

The rlogin service is running on the remote host.

Description

The rlogin service is running on the remote host. This service is vulnerable since data is passed between the rlogin client and server in cleartext. A man-in-the-middle attacker can exploit this to sniff logins and passwords. Also, it may allow poorly authenticated logins without passwords. If the host is vulnerable to TCP sequence number guessing (from any network) or IP spoofing (including ARP hijacking on a local network) then it may be possible to bypass authentication.

Finally, rlogin is an easy way to turn file-write access into full logins through the .rhosts or rhosts.equiv files.

Solution

Comment out the 'login' line in /etc/inetd.conf and restart the inetd process. Alternatively, disable this service and use SSH instead.

Risk Factor

High

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

References

CVE CVE-1999-0651

Exploitable With

Metasploit (true)

Plugin Information

Published: 1999/08/30, Modified: 2022/04/11

Plugin Output

tcp/513/rlogin

10245 - rsh Service Detection

Synopsis

The rsh service is running on the remote host.

Description

The rsh service is running on the remote host. This service is vulnerable since data is passed between the rsh client and server in cleartext. A man-in-the-middle attacker can exploit this to sniff logins and passwords. Also, it may allow poorly authenticated logins without passwords. If the host is vulnerable to TCP sequence number guessing (from any network) or IP spoofing (including ARP hijacking on a local network) then it may be possible to bypass authentication.

Finally, rsh is an easy way to turn file-write access into full logins through the .rhosts or rhosts.equiv files.

Solution

Comment out the 'rsh' line in /etc/inetd.conf and restart the inetd process. Alternatively, disable this service and use SSH instead.

Risk Factor

High

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

References

CVE CVE-1999-0651

Exploitable With

Metasploit (true)

Plugin Information

Published: 1999/08/22, Modified: 2022/04/11

Plugin Output

tcp/514/rsh

11213 - HTTP TRACE / TRACK Methods Allowed

Synopsis

Debugging functions are enabled on the remote web server.

Description

The remote web server supports the TRACE and/or TRACK methods. TRACE and TRACK are HTTP methods that are used to debug web server connections.

See Also

<http://www.nessus.org/u?e979b5cb>

<http://www.apacheweek.com/issues/03-01-24>

<https://download.oracle.com/sunalerts/1000718.1.html>

Solution

Disable these HTTP methods. Refer to the plugin output for more information.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

References

BID	9506
BID	9561
BID	11604
BID	33374

BID	37995
CVE	CVE-2003-1567
CVE	CVE-2004-2320
CVE	CVE-2010-0386
XREF	CERT:288308
XREF	CERT:867593
XREF	CWE:16
XREF	CWE:200

Plugin Information

Published: 2003/01/23, Modified: 2024/04/09

Plugin Output

tcp/80/www

To disable these methods, add the following lines for each virtual host in your configuration file :

```
RewriteEngine on
RewriteCond %{REQUEST_METHOD} ^(TRACE|TRACK)
RewriteRule .* - [F]
```

Alternatively, note that Apache versions 1.3.34, 2.0.55, and 2.2 support disabling the TRACE method natively via the 'TraceEnable' directive.

Nessus sent the following TRACE request : \n\n----- snip
-----\nTRACE /Nessus698589963.html HTTP/1.1

Connection: Close
Host: metasploitable2.labvulnerabilities_vulnnet
Pragma: no-cache
User-Agent: Mozilla/4.0 (compatible; MSIE 8.0; Windows NT 5.1; Trident/4.0)
Accept: image/gif, image/x-xbitmap, image/jpeg, image/pjpeg, image/png, */*
Accept-Language: en
Accept-Charset: iso-8859-1,*,utf-8

----- snip -----\n\nand received the
following response from the remote server : \n\n----- snip
-----\nHTTP/1.1 200 OK

Date: Thu, 23 Jul 2026 22:33:07 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
Keep-Alive: timeout=15, max=100
Connection: Keep-Alive
Transfer-Encoding: chunked
Content-Type: message/http

TRACE /Nessus698589963.html HTTP/1.1
Connection: Keep-Alive
Host: metasploitable2.labvulnerabilities_vulnnet
Pragma: no-cache
User-Agent: Mozilla/4.0 (compatible; MSIE 8.0; Windows NT 5.1; Trident/4.0)
Accept: image/gif, image/x-xbitmap, image/jpeg, image/pjpeg, image/png, */*
Accept-Language: en
Accept-Charset: iso-8859-1,*,utf-8

----- snip -----\n

50686 - IP Forwarding Enabled

Synopsis

The remote host has IP forwarding enabled.

Description

The remote host has IP forwarding enabled. An attacker can exploit this to route packets through the host and potentially bypass some firewalls / routers / NAC filtering.

Unless the remote host is a router, it is recommended that you disable IP forwarding.

Solution

On Linux, you can disable IP forwarding by doing :

```
echo 0 > /proc/sys/net/ipv4/ip_forward
```

On Windows, set the key 'IPEnableRouter' to 0 under

HKEY_LOCAL_MACHINE\System\CurrentControlSet\Services\Tcpip\Parameters

On Mac OS X, you can disable IP forwarding by executing the command :

```
sysctl -w net.inet.ip.forwarding=0
```

For other systems, check with your vendor.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:A/AC:L/PR:L/UI:N/S:C/C:L/I:L/A:L)

CVSS v2.0 Base Score

5.8 (CVSS2#AV:A/AC:L/Au:N/C:P/I:P/A:P)

References

CVE CVE-1999-0511

Plugin Information

Published: 2010/11/23, Modified: 2023/10/17

Plugin Output

tcp/0

IP forwarding appears to be enabled on the remote host.

Detected local MAC Address : e68cc3441691
Response from local MAC Address : e68cc3441691

Detected Gateway MAC Address : d625d670750c
Response from Gateway MAC Address : d625d670750c

57608 - SMB Signing not required

Synopsis

Signing is not required on the remote SMB server.

Description

Signing is not required on the remote SMB server. An unauthenticated, remote attacker can exploit this to conduct man-in-the-middle attacks against the SMB server.

See Also

<http://www.nessus.org/u?df39b8b3>

<http://technet.microsoft.com/en-us/library/cc731957.aspx>

<http://www.nessus.org/u?74b80723>

<https://www.samba.org/samba/docs/current/man-html/smb.conf.5.html>

<http://www.nessus.org/u?a3cac4ea>

Solution

Enforce message signing in the host's configuration. On Windows, this is found in the policy setting 'Microsoft network server: Digitally sign communications (always)'. On Samba, the setting is called 'server signing'. See the 'see also' links for further details.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

Plugin Information

Published: 2012/01/19, Modified: 2022/10/05

Plugin Output

tcp/445/cifs

90317 - SSH Weak Algorithms Supported

Synopsis

The remote SSH server is configured to allow weak encryption algorithms or no algorithm at all.

Description

Nessus has detected that the remote SSH server is configured to use the Arcfour stream cipher or no cipher at all. RFC 4253 advises against using Arcfour due to an issue with weak keys.

See Also

<https://tools.ietf.org/html/rfc4253#section-6.3>

Solution

Contact the vendor or consult product documentation to remove the weak ciphers.

Risk Factor

Medium

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2016/04/04, Modified: 2026/01/12

Plugin Output

tcp/22/ssh

The following weak server-to-client encryption algorithms are supported :

aes128-cbc,3des-cbc,blowfish-cbc,cast128-cbc,arcfour128,arcfour256,arcfour,aes192-cbc,aes256-cbc,rijndael-cbc@lysator.liu.se,aes128-ctr,aes192-ctr,aes256-ctr

The following weak client-to-server encryption algorithms are supported :

aes128-cbc,3des-cbc,blowfish-cbc,cast128-cbc,arcfour128,arcfour256,arcfour,aes192-cbc,aes256-cbc,rijndael-cbc@lysator.liu.se,aes128-ctr,aes192-ctr,aes256-ctr

51192 - SSL Certificate Cannot Be Trusted

Synopsis

The SSL certificate for this service cannot be trusted.

Description

The server's X.509 certificate cannot be trusted. This situation can occur in three different ways, in which the chain of trust can be broken, as stated below :

- First, the top of the certificate chain sent by the server might not be descended from a known public certificate authority. This can occur either when the top of the chain is an unrecognized, self-signed certificate, or when intermediate certificates are missing that would connect the top of the certificate chain to a known public certificate authority.
- Second, the certificate chain may contain a certificate that is not valid at the time of the scan. This can occur either when the scan occurs before one of the certificate's 'notBefore' dates, or after one of the certificate's 'notAfter' dates.
- Third, the certificate chain may contain a signature that either didn't match the certificate's information or could not be verified. Bad signatures can be fixed by getting the certificate with the bad signature to be re-signed by its issuer. Signatures that could not be verified are the result of the certificate's issuer using a signing algorithm that Nessus either does not support or does not recognize.

If the remote host is a public host in production, any break in the chain makes it more difficult for users to verify the authenticity and identity of the web server. This could make it easier to carry out man-in-the-middle attacks against the remote host.

See Also

<https://www.itu.int/rec/T-REC-X.509/en>

<https://en.wikipedia.org/wiki/X.509>

Solution

Purchase or generate a proper SSL certificate for this service.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

CVSS v2.0 Base Score

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:N)

Plugin Information

Published: 2010/12/15, Modified: 2025/06/16

Plugin Output

tcp/5432/postgresql

The following certificate was part of the certificate chain sent by the remote host, but it has expired :

```
| -Subject   : C=XX/ST=There is no such thing outside US/L=Everywhere/O=OCOSA/OU=Office for  
Complication of Otherwise Simple Affairs/CN=ubuntu804-base.localdomain/E=root@ubuntu804-  
base.localdomain  
| -Not After : Apr 16 14:07:45 2010 GMT
```

The following certificate was at the top of the certificate chain sent by the remote host, but it is signed by an unknown certificate authority :

```
| -Subject : C=XX/ST=There is no such thing outside US/L=Everywhere/O=OCOSA/OU=Office for  
Complication of Otherwise Simple Affairs/CN=ubuntu804-base.localdomain/E=root@ubuntu804-  
base.localdomain  
| -Issuer  : C=XX/ST=There is no such thing outside US/L=Everywhere/O=OCOSA/OU=Office for  
Complication of Otherwise Simple Affairs/CN=ubuntu804-base.localdomain/E=root@ubuntu804-  
base.localdomain
```

15901 - SSL Certificate Expiry

Synopsis

The remote server's SSL certificate has already expired.

Description

This plugin checks expiry dates of certificates associated with SSL- enabled services on the target and reports whether any have already expired.

Solution

Purchase or generate a new SSL certificate to replace the existing one.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

Plugin Information

Published: 2004/12/03, Modified: 2025/12/08

Plugin Output

tcp/5432/postgresql

The SSL certificate has already expired :

```
Subject      : C=XX, ST=There is no such thing outside US, L=Everywhere, O=OCOSA,
OU=Office for Complication of Otherwise Simple Affairs, CN=ubuntu804-base.localdomain,
emailAddress=root@ubuntu804-base.localdomain
Issuer       : C=XX, ST=There is no such thing outside US, L=Everywhere, O=OCOSA,
OU=Office for Complication of Otherwise Simple Affairs, CN=ubuntu804-base.localdomain,
emailAddress=root@ubuntu804-base.localdomain
Not valid before : Mar 17 14:07:45 2010 GMT
Not valid after  : Apr 16 14:07:45 2010 GMT
```

45411 - SSL Certificate with Wrong Hostname

Synopsis

The SSL certificate for this service is for a different host.

Description

The 'commonName' (CN) attribute of the SSL certificate presented for this service is for a different machine.

Solution

Purchase or generate a proper SSL certificate for this service.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

Plugin Information

Published: 2010/04/03, Modified: 2020/04/27

Plugin Output

tcp/5432/postgresql

The identities known by Nessus are :

```
172.30.1.1
8e45b17a1053
172.30.1.1
```

The Common Name in the certificate is :

```
ubuntu804-base.localdomain
```

Synopsis

The remote service supports the use of the RC4 cipher.

Description

The remote host supports the use of RC4 in one or more cipher suites.

The RC4 cipher is flawed in its generation of a pseudo-random stream of bytes so that a wide variety of small biases are introduced into the stream, decreasing its randomness.

If plaintext is repeatedly encrypted (e.g., HTTP cookies), and an attacker is able to obtain many (i.e., tens of millions) ciphertexts, the attacker may be able to derive the plaintext.

See Also

<https://www.rc4nomore.com/>

<http://www.nessus.org/u?ac7327a0>

<http://cr.yp.to/talks/2013.03.12/slides.pdf>

<http://www.isg.rhul.ac.uk/tls/>

https://www.imperva.com/docs/HII_Attacking_SSL_when_using_RC4.pdf

Solution

Reconfigure the affected application, if possible, to avoid use of RC4 ciphers. Consider using TLS 1.2 with AES-GCM suites subject to browser and web server support.

Risk Factor

Medium

CVSS v3.0 Base Score

5.9 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:N/A:N)

CVSS v3.0 Temporal Score

5.4 (CVSS:3.0/E:U/RL:X/RC:C)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

4.2 (CVSS2#E:U/RL:ND/RC:C)

References

BID 58796
BID 73684
CVE CVE-2013-2566
CVE CVE-2015-2808

Plugin Information

Published: 2013/04/05, Modified: 2025/05/09

Plugin Output

tcp/5432/postgresql

List of RC4 cipher suites supported by the remote server :

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
RC4-SHA	0x00, 0x05	RSA	RSA	RC4(128)	
SHA1					

The fields above are :

{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}

57582 - SSL Self-Signed Certificate

Synopsis

The SSL certificate chain for this service ends in an unrecognized self-signed certificate.

Description

The X.509 certificate chain for this service is not signed by a recognized certificate authority. If the remote host is a public host in production, this nullifies the use of SSL as anyone could establish a man-in-the-middle attack against the remote host.

Note that this plugin does not check for certificate chains that end in a certificate that is not self-signed, but is signed by an unrecognized certificate authority.

Solution

Purchase or generate a proper SSL certificate for this service.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

CVSS v2.0 Base Score

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:N)

Plugin Information

Published: 2012/01/17, Modified: 2022/06/14

Plugin Output

tcp/5432/postgresql

The following certificate was found at the top of the certificate chain sent by the remote host, but is self-signed and was not found in the list of known certificate authorities :

```
| -Subject : C=XX/ST=There is no such thing outside US/L=Everywhere/O=0C0SA/OU=Office for  
Complication of Otherwise Simple Affairs/CN=ubuntu804-base.localdomain/E=root@ubuntu804-  
base.localdomain
```

104743 - TLS Version 1.0 Protocol Detection

Synopsis

The remote service encrypts traffic using an older version of TLS.

Description

The remote service accepts connections encrypted using TLS 1.0. TLS 1.0 has a number of cryptographic design flaws. Modern implementations of TLS 1.0 mitigate these problems, but newer versions of TLS like 1.2 and 1.3 are designed against these flaws and should be used whenever possible.

As of March 31, 2020, Endpoints that aren't enabled for TLS 1.2 and higher will no longer function properly with major web browsers and major vendors.

PCI DSS v3.2 requires that TLS 1.0 be disabled entirely by June 30, 2018, except for POS POI terminals (and the SSL/TLS termination points to which they connect) that can be verified as not being susceptible to any known exploits.

See Also

<https://tools.ietf.org/html/draft-ietf-tls-oldversions-deprecate-00>

Solution

Enable support for TLS 1.2 and 1.3, and disable support for TLS 1.0.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:L/A:N)

CVSS v2.0 Base Score

6.1 (CVSS2#AV:N/AC:H/Au:N/C:C/I:P/A:N)

References

XREF CWE:327

Plugin Information

Published: 2017/11/22, Modified: 2026/04/13

Plugin Output

tcp/5432/postgresql

TLSv1 is enabled and the server supports at least one cipher.

42263 - Unencrypted Telnet Server

Synopsis

The remote Telnet server transmits traffic in cleartext.

Item	Description
1	...
2	...
3	...
4	...
5	...
6	...
7	...
8	...
9	...
10	...
11	...
12	...
13	...
14	...
15	...
16	...
17	...
18	...
19	...
20	...
21	...
22	...
23	...
24	...
25	...
26	...
27	...
28	...
29	...
30	...
31	...
32	...
33	...
34	...
35	...
36	...
37	...
38	...
39	...
40	...
41	...
42	...
43	...
44	...
45	...
46	...
47	...
48	...
49	...
50	...
51	...
52	...
53	...
54	...
55	...
56	...
57	...
58	...
59	...
60	...
61	...
62	...
63	...
64	...
65	...
66	...
67	...
68	...
69	...
70	...
71	...
72	...
73	...
74	...
75	...
76	...
77	...
78	...
79	...
80	...
81	...
82	...
83	...
84	...
85	...
86	...
87	...
88	...
89	...
90	...
91	...
92	...
93	...
94	...
95	...
96	...
97	...
98	...
99	...
100	...

The remote host is running a Telnet server over an unencrypted channel.

Using Telnet over an unencrypted channel is not recommended as logins, passwords, and commands are transferred in cleartext. This allows a remote, man-in-the-middle attacker to eavesdrop on a Telnet session to obtain credentials or other sensitive information and to modify traffic exchanged between a client and server.

SSH is preferred over Telnet since it protects credentials from eavesdropping and can tunnel additional data streams such as an X11 session.

Solution

Disable the Telnet service and use SSH instead.

Risk Factor	Impact	Control
1. Lack of industry connections	Reduced visibility and networking opportunities	Attend industry conferences and seminars
2. Limited marketing budget	Reduced reach and brand awareness	Utilize social media and content marketing
3. Niche or experimental sound	Reduced mainstream appeal	Collaborate with established acts
4. Limited live performance opportunities	Reduced fan base growth	Seek out local venues and festivals
5. Inconsistent output	Reduced fan engagement	Establish a regular release schedule
6. Limited live performance opportunities	Reduced fan base growth	Seek out local venues and festivals
7. Limited live performance opportunities	Reduced fan base growth	Seek out local venues and festivals
8. Limited live performance opportunities	Reduced fan base growth	Seek out local venues and festivals
9. Limited live performance opportunities	Reduced fan base growth	Seek out local venues and festivals
10. Limited live performance opportunities	Reduced fan base growth	Seek out local venues and festivals

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

CVSS v2.0 Base Score

5.8 (CVSS2#AV:N/AC:M/Au:N/C:P/I:P/A:N)

Plugin Information

Published: 2009/10/27, Modified: 2024/01/16

Plugin Output

tcp/23/telnet

[illegible]

```
Nessus collected the following banner from the remote Telnet server :

----- snip -----

_ _ _ _ _ | _ _ _ _ _ | _ _ _ _ _ ( _ ) _ _ _ _ _ | _ _ _ _ _ | _ _ _ _ _ \
| _ _ _ _ _ \ _ _ _ _ _ / _ _ _ _ _ \ _ _ _ _ _ / _ _ _ _ _ | _ _ _ _ _ | _ _ _ _ _ \ _ _ _ _ _ ) | | | | | | | | | | | | | | | | | |
| | | | | | _ _ _ _ _ / | | ( _ ) \ _ _ _ _ _ | | ( _ ) | | | | | ( _ ) | | | | | _ _ _ _ _ / _ _ _ _ _ |
| _ _ _ _ _ | _ _ _ _ _ \ _ _ _ _ _ / _ _ _ _ _ \ _ _ _ _ _ / _ _ _ _ _ \ _ _ _ _ _ \ _ _ _ _ _ | _ _ _ _ _ |
| _ _ _ _ _ | _ _ _ _ _ \ _ _ _ _ _ / _ _ _ _ _ \ _ _ _ _ _ \ _ _ _ _ _ \ _ _ _ _ _ \ _ _ _ _ _ | _ _ _ _ _ |

Warning: Never expose this VM to an untrusted network!
```

[illegible]

```
Nessus collected the following banner from the remote Telnet server :  
  
----- snip -----  
  
_ _ _ _ _ | _ _ _ _ _ | _ _ _ _ _ ( _ ) _ _ _ _ _ | _ _ _ _ _ \_  
| '_ _ _ _ _ \ / _ _ _ _ _ \ / _ _ _ _ _ \ / _ _ _ _ _ \ / _ _ _ _ _ \_  
| | | | | | _ / || ( _ ) \ _ _ _ _ _ | | | | | | ( _ ) | | | | | _ / \ / \_  
|_| |_| |_| \ _ _ _ _ _ \ _ _ _ _ _ \ _ _ _ _ _ \ _ _ _ _ _ \ _ _ _ _ _ \_  
                                     | _ |  
Warning: Never expose this VM to an untrusted network!
```

```
Contact: msfdev[at]metasploit.com
Login with msfadmin/msfadmin to get started
8e45b17a1053 login:
----- snip -----
```

10114 - ICMP Timestamp Request Remote Date Disclosure

Synopsis

It is possible to determine the exact time set on the remote host.

Description

The remote host answers to an ICMP timestamp request. This allows an attacker to know the date that is set on the targeted machine, which may assist an unauthenticated, remote attacker in defeating time-based authentication protocols.

Timestamps returned from machines running Windows Vista / 7 / 2008 / 2008 R2 are deliberately incorrect, but usually within 1000 seconds of the actual system time.

Solution

Filter out the ICMP timestamp requests (13), and the outgoing ICMP timestamp replies (14).

Risk Factor

Low

CVSS v2.0 Base Score

2.1 (CVSS2#AV:L/AC:L/Au:N/C:P/I:N/A:N)

References

CVE	CVE-1999-0524
XREF	CWE:200

Plugin Information

Published: 1999/08/01, Modified: 2024/10/07

Plugin Output

icmp/0

```
The remote clock is synchronized with the local clock.
```

70658 - SSH Server CBC Mode Ciphers Enabled

Synopsis

The SSH server is configured to use Cipher Block Chaining.

Description

The SSH server is configured to support Cipher Block Chaining (CBC) encryption. This may allow an attacker to recover the plaintext message from the ciphertext.

Note that this plugin only checks for the options of the SSH server and does not check for vulnerable software versions.

Solution

Contact the vendor or consult product documentation to disable CBC mode cipher encryption, and enable CTR or GCM cipher mode encryption.

Risk Factor

Low

CVSS v3.0 Base Score

3.7 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

1.9 (CVSS2#E:U/RL:OF/RC:C)

References

BID	32319
CVE	CVE-2008-5161
XREF	CERT:958563
XREF	CWE:200

Plugin Information

Published: 2013/10/28, Modified: 2026/01/12

Plugin Output

tcp/22/ssh

The following client-to-server Cipher Block Chaining (CBC) algorithms are supported :

aes128-cbc,3des-cbc,blowfish-cbc,cast128-cbc,arcfour128,arcfour256,arcfour,aes192-cbc,aes256-cbc,rijndael-cbc@lysator.liu.se,aes128-ctr,aes192-ctr,aes256-ctr

The following server-to-client Cipher Block Chaining (CBC) algorithms are supported :

aes128-cbc,3des-cbc,blowfish-cbc,cast128-cbc,arcfour128,arcfour256,arcfour,aes192-cbc,aes256-cbc,rijndael-cbc@lysator.liu.se,aes128-ctr,aes192-ctr,aes256-ctr

153953 - SSH Weak Key Exchange Algorithms Enabled

Synopsis

The remote SSH server is configured to allow weak key exchange algorithms.

Description

The remote SSH server is configured to allow key exchange algorithms which are considered weak.

This is based on the IETF draft document Key Exchange (KEX) Method Updates and Recommendations for Secure Shell (SSH) RFC9142. Section 4 lists guidance on key exchange algorithms that SHOULD NOT and MUST NOT be enabled. This includes:

diffie-hellman-group-exchange-sha1

diffie-hellman-group1-sha1

gss-gex-sha1-*

gss-group1-sha1-*

gss-group14-sha1-*

rsa1024-sha1

Note that this plugin only checks for the options of the SSH server, and it does not check for vulnerable software versions.

See Also

<https://datatracker.ietf.org/doc/html/rfc9142>

Solution

Contact the vendor or consult product documentation to disable the weak algorithms.

Risk Factor

Low

CVSS v3.0 Base Score

3.7 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2021/10/13, Modified: 2026/01/12

Plugin Output

tcp/22/ssh

The following weak key exchange algorithms are enabled :

diffie-hellman-group-exchange-sha256,diffie-hellman-group-exchange-sha1,diffie-hellman-group14-sha1,diffie-hellman-group1-sha1
diffie-hellman-group-exchange-sha256,diffie-hellman-group-exchange-sha1,diffie-hellman-group14-sha1,diffie-hellman-group1-sha1

71049 - SSH Weak MAC Algorithms Enabled

Synopsis

The remote SSH server is configured to allow MD5 and 96-bit MAC algorithms.

Description

The remote SSH server is configured to allow either MD5 or 96-bit MAC algorithms, both of which are considered weak.

Note that this plugin only checks for the options of the SSH server, and it does not check for vulnerable software versions.

Solution

Contact the vendor or consult product documentation to disable MD5 and 96-bit MAC algorithms.

Risk Factor

Low

CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2013/11/22, Modified: 2026/01/12

Plugin Output

tcp/22/ssh

The following client-to-server Message Authentication Code (MAC) algorithms are supported :

hmac-md5, hmac-sha1, umac-64@openssh.com, hmac-ripemd160, hmac-ripemd160@openssh.com, hmac-sha1-96, hmac-md5-96

The following server-to-client Message Authentication Code (MAC) algorithms are supported :

hmac-md5, hmac-sha1, umac-64@openssh.com, hmac-ripemd160, hmac-ripemd160@openssh.com, hmac-sha1-96, hmac-md5-96

78479 - SSLv3 Padding Oracle On Downgraded Legacy Encryption Vulnerability (POODLE)

Synopsis

It is possible to obtain sensitive information from the remote host with SSL/TLS-enabled services.

Description

The remote host is affected by a man-in-the-middle (MitM) information disclosure vulnerability known as POODLE. The vulnerability is due to the way SSL 3.0 handles padding bytes when decrypting messages encrypted using block ciphers in cipher block chaining (CBC) mode.

MitM attackers can decrypt a selected byte of a cipher text in as few as 256 tries if they are able to force a victim application to repeatedly send the same data over newly created SSL 3.0 connections.

As long as a client and service both support SSLv3, a connection can be 'rolled back' to SSLv3, even if TLSv1 or newer is supported by the client and service.

The TLS Fallback SCSV mechanism prevents 'version rollback' attacks without impacting legacy clients; however, it can only protect connections when the client and service support the mechanism. Sites that cannot disable SSLv3 immediately should enable this mechanism.

This is a vulnerability in the SSLv3 specification, not in any particular SSL implementation. Disabling SSLv3 is the only way to completely mitigate the vulnerability.

See Also

<https://www.imperialviolet.org/2014/10/14/poodle.html>

<https://www.openssl.org/~bodo/ssl-poodle.pdf>

<https://tools.ietf.org/html/draft-ietf-tls-downgrade-scsv-00>

Solution

Disable SSLv3.

Services that must support SSLv3 should enable the TLS Fallback SCSV mechanism until SSLv3 can be disabled.

Risk Factor

Medium

CVSS v3.0 Base Score

3.4 (CVSS:3.0/AV:N/AC:H/PR:N/UI:R/S:C/C:L/I:N/A:N)

CVSS v3.0 Temporal Score

3.1 (CVSS:3.0/E:P/RL:O/RC:C)

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.4 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	70574
CVE	CVE-2014-3566
XREF	CERT:577193

Plugin Information

Published: 2014/10/15, Modified: 2026/04/13

Plugin Output

tcp/5432/postgresql

Nessus determined that the remote server supports SSLv3 with at least one CBC cipher suite, indicating that this server is vulnerable.

It appears that TLSv1 or newer is supported on the server. However, the fallback SCSV mechanism is not supported, allowing connections to be "rolled back" to SSLv3.

46180 - Additional DNS Hostnames

Synopsis

Nessus has detected potential virtual hosts.

Description

Hostnames different from the current hostname have been collected by miscellaneous plugins. Nessus has generated a list of hostnames that point to the remote host. Note that these are only the alternate hostnames for vhosts discovered on a web server.

Different web servers may be hosted on name-based virtual hosts.

See Also

https://en.wikipedia.org/wiki/Virtual_hosting

Solution

If you want to test them, re-scan using the special vhost syntax, such as :

`www.example.com[192.0.32.10]`

Risk Factor

None

Plugin Information

Published: 2010/04/29, Modified: 2022/08/15

Plugin Output

tcp/0

```
The following hostnames point to the remote host :  
- 8e45b17a1053
```

18261 - Apache Banner Linux Distribution Disclosure

Synopsis

The name of the Linux distribution running on the remote host was found in the banner of the web server.

Description

Nessus was able to extract the banner of the Apache web server and determine which Linux distribution the remote host is running.

Solution

If you do not wish to display this information, edit 'httpd.conf' and set the directive 'ServerTokens Prod' and restart Apache.

Risk Factor

None

Plugin Information

Published: 2005/05/15, Modified: 2025/03/31

Plugin Output

tcp/0

```
The Linux distribution detected was :  
- Ubuntu 8.04 (gutsy)
```

48204 - Apache HTTP Server Version

Synopsis

It is possible to obtain the version number of the remote Apache HTTP server.

Description

The remote host is running the Apache HTTP Server, an open source web server. It was possible to read the version number from the banner.

See Also

<https://httpd.apache.org/>

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0030

XREF IAVT:0001-T-0530

Plugin Information

Published: 2010/07/30, Modified: 2026/01/22

Plugin Output

tcp/80/www

```
URL      : http://172.30.1.1/
Version  : 2.2.8
Source   : Server: Apache/2.2.8 (Ubuntu) DAV/2
backported : 1
modules  : DAV/2
os       : Ubuntu
```

84574 - Backported Security Patch Detection (PHP)

Synopsis

Security patches have been backported.

Description

Security patches may have been 'backported' to the remote PHP install without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/07/07, Modified: 2024/11/22

Plugin Output

tcp/80/www

Give Nessus credentials to perform local checks.

39520 - Backported Security Patch Detection (SSH)

Synopsis

Security patches are backported.

Description

Security patches may have been 'backported' to the remote SSH server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/06/25, Modified: 2026/01/22

Plugin Output

tcp/22/ssh

Give Nessus credentials to perform local checks.

39521 - Backported Security Patch Detection (WWW)

Synopsis

Security patches are backported.

Description

Security patches may have been 'backported' to the remote HTTP server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/06/25, Modified: 2026/01/22

Plugin Output

tcp/80/www

Give Nessus credentials to perform local checks.

45590 - Common Platform Enumeration (CPE)

Synopsis

It was possible to enumerate CPE names that matched on the remote system.

Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

See Also

<http://cpe.mitre.org/>

<https://nvd.nist.gov/products/cpe>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/04/21, Modified: 2026/06/16

Plugin Output

tcp/0

Following application CPE's matched on the remote system :

```
cpe:/a:apache:http_server:2.2.8 -> Apache Software Foundation Apache HTTP Server
cpe:/a:mysql:mysql -> MySQL MySQL
cpe:/a:openbsd:openssh:4.7 -> OpenBSD OpenSSH
cpe:/a:openbsd:openssh:4.7p1 -> OpenBSD OpenSSH
cpe:/a:php:php:5.2.4 -> PHP PHP
cpe:/a:php:php:5.2.4-2ubuntu5.10 -> PHP PHP
cpe:/a:postgresql:postgresql -> PostgreSQL
cpe:/a:samba:samba:3.0.20 -> Samba Samba
```

54615 - Device Type

Synopsis

It is possible to guess the remote device type.

Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/05/23, Modified: 2025/03/12

Plugin Output

tcp/0

```
Remote device type : general-purpose  
Confidence level : 95
```

86420 - Ethernet MAC Addresses

Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/10/16, Modified: 2025/06/10

Plugin Output

tcp/0

```
The following is a consolidated list of detected MAC addresses:  
- D6:25:D6:70:75:0C
```

10092 - FTP Server Detection

Synopsis

An FTP server is listening on a remote port.

Description

It is possible to obtain the banner of the remote FTP server by connecting to a remote port.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0030

XREF IAVT:0001-T-0943

Plugin Information

Published: 1999/10/12, Modified: 2023/08/17

Plugin Output

tcp/21/ftp

The remote FTP banner is :

220 (vsFTPd 2.3.4)

10107 - HTTP Server Type and Version

Synopsis

A web server is running on the remote host.

Description

This plugin attempts to determine the type and the version of the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0931

Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

Plugin Output

tcp/80/www

The remote web server type is :
Apache/2.2.8 (Ubuntu) DAV/2

12053 - Host Fully Qualified Domain Name (FQDN) Resolution

Synopsis

It was possible to resolve the name of the remote host.

Description

Nessus was able to resolve the fully qualified domain name (FQDN) of the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/02/11, Modified: 2025/03/13

Plugin Output

tcp/0

```
172.30.1.1 resolves as metasploitable2.labvulnerabilities_vulnnet.
```

24260 - HyperText Transfer Protocol (HTTP) Information

Synopsis

Some information about the remote HTTP configuration can be extracted.

Category	Description
1	...
2	...
3	...
4	...
5	...
6	...
7	...
8	...
9	...
10	...
11	...
12	...
13	...
14	...
15	...
16	...
17	...
18	...
19	...
20	...
21	...
22	...
23	...
24	...
25	...
26	...
27	...
28	...
29	...
30	...
31	...
32	...
33	...
34	...
35	...
36	...
37	...
38	...
39	...
40	...
41	...
42	...
43	...
44	...
45	...
46	...
47	...
48	...
49	...
50	...
51	...
52	...
53	...
54	...
55	...
56	...
57	...
58	...
59	...
60	...
61	...
62	...
63	...
64	...
65	...
66	...
67	...
68	...
69	...
70	...
71	...
72	...
73	...
74	...
75	...
76	...
77	...
78	...
79	...
80	...
81	...
82	...
83	...
84	...
85	...
86	...
87	...
88	...
89	...
90	...
91	...
92	...
93	...
94	...
95	...
96	...
97	...
98	...
99	...
100	...

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

Solution

Risk Factor	Impact	Control
1. Lack of industry connections	Reduced sales and market penetration	Networking and strategic partnerships
2. Limited marketing budget	Low brand awareness and visibility	Targeted digital marketing and social media
3. Intense competition	Price wars and reduced profit margins	Product differentiation and customer loyalty programs
4. Economic downturn	Reduced consumer spending and demand	Cost-cutting measures and flexible pricing
5. Technological changes	Obsolescence of products and services	Continuous innovation and R&D investment
6. Regulatory changes	Increased compliance costs and legal risks	Proactive legal counsel and industry engagement
7. Supply chain disruptions	Increased costs and delivery delays	Diversification of suppliers and inventory management
8. Talent acquisition challenges	Reduced productivity and innovation	Competitive compensation and employee development
9. Customer churn	Reduced revenue and market stability	Excellent customer service and loyalty programs
10. Financial mismanagement	Debt accumulation and cash flow issues	Transparent financial reporting and prudent spending

None

Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

Plugin Output

tcp/80/www

Response Code : HTTP/1.1 200 OK

```
Protocol version : HTTP/1.1
```

```
HTTP/2 TLS Support: No
```

HTTP/2 Cleartext Support: No

SSL : no

Keep-Alive : yes

Options allowed : (Not implemented)

Headers :

Date: Thu, 23 Jul 2026 22:33:19 GMT

Server: Apache/2.2.8 (Ubuntu) DAV/2

X-Powered-By: PHP/5.2.4-2ubuntu5.10

Keep-Alive: timeout=15, max=98

Connection: Keep-Alive

Transfer-Encoding: chunked

Content-Type: text/html

Response Body :

```
<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>
```


|_| |_| |_| _| _| _|, |_| |_| ._| / |_| _| / |_| _|, |_| ._| / |_| _| |_| |
|_|

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started

```
</pre>
<ul>
<li><a href="/twiki/">Twiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></li>
<li><a href="/dav/">WebDAV</a></li>
</ul>
</body>
</html>
```

10397 - Microsoft Windows SMB LanMan Pipe Server Listing Disclosure

Synopsis

It is possible to obtain network information.

Description

It was possible to obtain the browse list of the remote Windows system by sending a request to the LANMAN pipe. The browse list is the list of the nearest Windows systems of the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2000/05/09, Modified: 2022/02/01

Plugin Output

tcp/445/cifs

```
Here is the browse list of the remote host :
```

```
8E45B17A1053 ( os : 0.0 )
```

10785 - Microsoft Windows SMB NativeLanManager Remote System Information Disclosure

Synopsis

It was possible to obtain information about the remote operating system.

Description

Nessus was able to obtain the remote operating system name and version (Windows and/or Samba) by sending an authentication request to port 139 or 445. Note that this plugin requires SMB to be enabled on the host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2001/10/17, Modified: 2021/09/20

Plugin Output

tcp/445/cifs

```
The remote Operating System is : Unix
The remote native LAN manager is : Samba 3.0.20-Debian
The remote SMB Domain Name is : 8E45B17A1053
```

11011 - Microsoft Windows SMB Service Detection

Synopsis

A file / print sharing service is listening on the remote host.

Description

The remote service understands the CIFS (Common Internet File System) or Server Message Block (SMB) protocol, used to provide shared access to files, printers, etc between nodes on a network.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/06/05, Modified: 2021/02/11

Plugin Output

tcp/139/smb

```
An SMB server is running on this port.
```

11011 - Microsoft Windows SMB Service Detection

Synopsis

A file / print sharing service is listening on the remote host.

Description

The remote service understands the CIFS (Common Internet File System) or Server Message Block (SMB) protocol, used to provide shared access to files, printers, etc between nodes on a network.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/06/05, Modified: 2021/02/11

Plugin Output

tcp/445/cifs

```
A CIFS server is running on this port.
```

100871 - Microsoft Windows SMB Versions Supported (remote check)

Synopsis

It was possible to obtain information about the version of SMB running on the remote host.

Description

Nessus was able to obtain the version of SMB running on the remote host by sending an authentication request to port 139 or 445.

Note that this plugin is a remote check and does not work on agents.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2017/06/19, Modified: 2019/11/22

Plugin Output

tcp/445/cifs

```
The remote host supports the following versions of SMB :  
SMBv1
```

106716 - Microsoft Windows SMB2 and SMB3 Dialects Supported (remote check)

Synopsis

It was possible to obtain information about the dialects of SMB2 and SMB3 available on the remote host.

Description

Nessus was able to obtain the set of SMB2 and SMB3 dialects running on the remote host by sending an authentication request to port 139 or 445.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2018/02/09, Modified: 2020/03/11

Plugin Output

tcp/445/cifs

```
The remote host does NOT support the following SMB dialects :
 _version_  _introduced in windows version_
2.0.2      Windows 2008
2.1        Windows 7
2.2.2      Windows 8 Beta
2.2.4      Windows 8 Beta
3.0        Windows 8
3.0.2      Windows 8.1
3.1        Windows 10
3.1.1      Windows 10
```

10719 - MySQL Server Detection

Synopsis

A database server is listening on the remote port.

Description

The remote host is running MySQL, an open source database server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0802

Plugin Information

Published: 2001/08/13, Modified: 2025/09/24

Plugin Output

tcp/3306/mysql

```
Service : mysql  
Version : unknown
```


Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/21/ftp

```
Port 21/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/22/ssh

```
Port 22/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/23/telnet

```
Port 23/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/80/www

```
Port 80/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/139/smb

Port 139/tcp was found to be open

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/445/cifs

```
Port 445/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/512

```
Port 512/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/513/rlogin

```
Port 513/tcp was found to be open
```


Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/514/rsh

```
Port 514/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/1524

```
Port 1524/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/3306/mysql

```
Port 3306/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/5432/postgresql

```
Port 5432/tcp was found to be open
```

19506 - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2026/07/10

Plugin Output

tcp/0

Information about this scan :

```
Nessus version : 10.12.2
Nessus build : 20029
Plugin feed version : 202607231328
Scanner edition used : Nessus
Scanner OS : LINUX
Scanner distribution : ubuntu1604-x86-64
Scan type : Normal
Scan name : My Basic Network Scan
```

Scan policy used : Basic Network Scan
Scanner IP : 172.30.0.2
Port scanner(s) : nessus_syn_scanner
Port range : default
Ping RTT : 35.510 ms
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Assess component installs : yes
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 30
Max checks : 4
Recv timeout : 5
Backports : Detected
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2026/7/23 18:30 EDT (UTC -04:00)
Scan duration : 529 sec
Scan for malware : no
Fully Scan Operational Technology devices : no
Safely Scan Operational Technology devices with OT Discovery : no

209654 - OS Fingerprints Detected

Synopsis

Multiple OS fingerprints were detected.

Description

Using a combination of remote probes (TCP/IP, SMB, HTTP, NTP, SNMP, etc), it was possible to gather one or more fingerprints from the remote system. While the highest-confidence result was reported in plugin 11936, "OS Identification", the complete set of fingerprints detected are reported here.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/02/26, Modified: 2025/03/03

Plugin Output

tcp/0

Following OS Fingerprints were found

Remote operating system : SuSE Linux
Confidence level : 56
Method : MLSinFP
Type : unknown
Fingerprint : unknown

Remote operating system : Linux Kernel 2.6 on Ubuntu 8.04 (hardy)
Confidence level : 95
Method : SSH
Type : general-purpose
Fingerprint : SSH:SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1

Remote operating system : Linux Kernel 2.6 on Ubuntu 8.04 (gutsy)
Confidence level : 95
Method : HTTP
Type : general-purpose
Fingerprint : unknown

Remote operating system : Linux Kernel 2.x
Confidence level : 54
Method : SinFP
Type : general-purpose
Fingerprint : SinFP:
P1:B10113:F0x12:W64240:00204ffff:M1460:
P2:B10113:F0x12:W65160:00204ffff0402080affffff444541440103030a:M1460:
P3:B00000:F0x00:W0:00:M0

P4:191802_7_p=1524

Remote operating system : Unix
Confidence level : 70
Method : smb
Type : general-purpose
Fingerprint : unknown

Remote operating system : Unix
Confidence level : 45
Method : MSRPC
Type : general-purpose
Fingerprint : unknown

Following fingerprints could not be used to determine OS :

SSLcert:!:i/CN:ubuntu804-base.localdomaini/O:OCOSAI/OU:Office for Complication of Otherwise Simple
Affairss/CN:ubuntu804-base.localdomains/O:OCOSAs/OU:Office for Complication of Otherwise Simple
Affairs

ed093088706603bfd5dc237399b498da2d4d31c6

11936 - OS Identification

Synopsis

It is possible to guess the remote operating system.

Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2003/12/09, Modified: 2025/06/03

Plugin Output

tcp/0

```
Remote operating system : Linux Kernel 2.6 on Ubuntu 8.04 (gutsy)
Confidence level : 95
Method : HTTP
```

```
The remote host is running Linux Kernel 2.6 on Ubuntu 8.04 (gutsy)
```

117886 - OS Security Patch Assessment Not Available

Synopsis

OS Security Patch Assessment is not available.

Description

OS Security Patch Assessment is not available on the remote host.

This does not necessarily indicate a problem with the scan.

Credentials may not have been provided, OS security patch assessment may not be supported for the target, the target may not have been identified, or another issue may have occurred that prevented OS security patch assessment from being available. See plugin output for details.

This plugin reports non-failure information impacting the availability of OS Security Patch Assessment. Failure information is reported by plugin 21745 : 'OS Security Patch Assessment failed'. If a target host is not supported for OS Security Patch Assessment, plugin 110695 : 'OS Security Patch Assessment Checks Not Supported' will report concurrently with this plugin.

Solution

n/a

Risk Factor

None

References

XREF IAVB:0001-B-0515

Plugin Information

Published: 2018/10/02, Modified: 2021/07/12

Plugin Output

tcp/0

The following issues were reported :

```
- Plugin      : no_local_checks_credentials.nasl
  Plugin ID   : 110723
  Plugin Name : Target Credential Status by Authentication Protocol - No Credentials Provided
  Message     :
  Credentials were not provided for detected SSH service.
```

181418 - OpenSSH Detection

Synopsis

An OpenSSH-based SSH server was detected on the remote host.

Description

An OpenSSH-based SSH server was detected on the remote host.

See Also

<https://www.openssh.com/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/09/14, Modified: 2026/07/20

Plugin Output

tcp/22/ssh

```
Service      : ssh
Version      : 4.7p1
Banner       : SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1
backported   : 1
```

50845 - OpenSSL Detection

Synopsis

The remote service appears to use OpenSSL to encrypt traffic.

Description

Based on its response to a TLS request with a specially crafted server name extension, it seems that the remote service is using the OpenSSL library to encrypt traffic.

Note that this plugin can only detect OpenSSL implementations that have enabled support for TLS extensions (RFC 4366).

See Also

<https://www.openssl.org/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/11/30, Modified: 2020/06/12

Plugin Output

tcp/5432/postgresql

48243 - PHP Version Detection

Synopsis

It was possible to obtain the version number of the remote PHP installation.

Description

Nessus was able to determine the version of PHP available on the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0936

Plugin Information

Published: 2010/08/04, Modified: 2026/01/22

Plugin Output

tcp/80/www

Nessus was able to identify the following PHP version information :

```
Version : 5.2.4-2ubuntu5.10
Source  : X-Powered-By: PHP/5.2.4-2ubuntu5.10
Backported : 1
```

Synopsis

The remote host is missing several patches.

Description

The remote host is missing one or more security patches. This plugin lists the newest version of each patch to install to make sure the remote host is up-to-date.

Note: Because the 'Show missing patches that have been superseded' setting in your scan policy depends on this plugin, it will always run and cannot be disabled.

Solution

Install the patches listed below.

Risk Factor

None

Plugin Information

Published: 2013/07/08, Modified: 2026/07/17

Plugin Output

tcp/0

```
. You need to take the following action :
```

```
[ Samba Badlock Vulnerability (90509) ]
```

```
+ Action to take : Upgrade to Samba version 4.2.11 / 4.3.8 / 4.4.2 or later.
```

118224 - PostgreSQL STARTTLS Support

Synopsis

The remote service supports encrypting traffic.

Description

The remote PostgreSQL server supports the use of encryption initiated during pre-login to switch from a cleartext to an encrypted communications channel.

See Also

<https://www.postgresql.org/docs/9.2/protocol-flow.html#AEN96066>

<https://www.postgresql.org/docs/9.2/protocol-message-formats.html>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2018/10/19, Modified: 2022/04/11

Plugin Output

tcp/5432/postgresql

```
Here is the PostgreSQL's SSL certificate that Nessus
was able to collect after sending a pre-login packet :
```

```
----- snip -----
Subject Name:

Country: XX
State/Province: There is no such thing outside US
Locality: Everywhere
Organization: OCOSA
Organization Unit: Office for Complication of Otherwise Simple Affairs
Common Name: ubuntu804-base.localdomain
Email Address: root@ubuntu804-base.localdomain

Issuer Name:

Country: XX
State/Province: There is no such thing outside US
Locality: Everywhere
Organization: OCOSA
Organization Unit: Office for Complication of Otherwise Simple Affairs
```

Common Name: ubuntu804-base.localdomain
Email Address: root@ubuntu804-base.localdomain

Serial Number: 00 FA F9 3A 4C 7F B6 B9 CC

Version: 1

Signature Algorithm: SHA-1 With RSA Encryption

Not Valid Before: Mar 17 14:07:45 2010 GMT

Not Valid After: Apr 16 14:07:45 2010 GMT

Public Key Info:

Algorithm: RSA Encryption

Key Length: 1024 bits

Public Key: 00 D6 B4 13 36 33 9A 95 71 7B 1B DE 7C 83 75 DA 71 B1 3C A9
7F FE AD 64 1B 77 E9 4F AE BE CA D4 F8 CB EF AE BB 43 79 24
73 FF 3C E5 9E 3B 6D FC C8 B1 AC FA 4C 4D 5E 9B 4C 99 54 0B
D7 A8 4A 50 BA A9 DE 1D 1F F4 E4 6B 02 A3 F4 6B 45 CD 4C AF
8D 89 62 33 8F 65 BB 36 61 9F C4 2C 73 C1 4E 2E A0 A8 14 4E
98 70 46 61 BB D1 B9 31 DF 8C 99 EE 75 6B 79 3C 40 A0 AE 97
00 90 9D DC 99 0D 33 A4 B5

Exponent: 01 00 01

Signature Length: 128 bytes / 1024 bits

Signature: 00 92 A4 B4 B8 14 55 63 25 51 4A 0B C3 2A 22 CF 3A F8 17 6A
0C CF 66 AA A7 65 2F 48 6D CD E3 3E 5C 9F 77 6C D4 44 54 1F
1E 84 4F 8E D4 8D DD AC 2D 88 09 21 A8 DA 56 2C A9 05 3C 49
68 35 19 75 0C DA 53 23 88 88 19 2D 74 26 C1 22 65 EE 11 68
83 6A 53 4A 9C 27 CB A0 B4 E9 8D 29 0C B2 3C 18 5C 67 CC 53
A6 1E 30 D0 AA 26 7B 1E AE 40 B9 29 01 6C 2E BC A2 19 94 7C
15 6E 8D 30 38 F6 CA 2E 75

----- snip ----- [...]

26024 - PostgreSQL Server Detection

Synopsis

A database service is listening on the remote host.

Description

The remote service is a PostgreSQL database server, or a derivative such as EnterpriseDB.

See Also

<https://www.postgresql.org/>

Solution

Limit incoming traffic to this port if desired.

Risk Factor

None

Plugin Information

Published: 2007/09/14, Modified: 2025/09/24

Plugin Output

tcp/5432/postgresql

```
Service : postgresql
Version : unknown
```

277650 - Remote Services Not Using Post-Quantum Ciphers

Synopsis

Reports remote services that do not offer post-quantum ciphers.

Description

This plugin reports network services that do not offer post-quantum ciphers. Tenable makes no attempt to determine whether the remote service would be vulnerable to a post-quantum attack.

However, cryptography that depends on the classic difficulty of solving the discrete logarithm problem or on the classic difficulty of large prime factorization is broken by Shor's algorithm. Examples of this are RSA asymmetric encryption and Diffie-Hellman key exchange.

See Also

<http://www.nessus.org/u?7a390f87>

<http://www.nessus.org/u?ad7d6b3b>

<http://www.nessus.org/u?1c0c61e0>

<http://www.nessus.org/u?5eec4b28>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/12/08, Modified: 2025/12/08

Plugin Output

tcp/22/ssh

The target SSH server offers no post-quantum ciphers.

277650 - Remote Services Not Using Post-Quantum Ciphers

Synopsis

Reports remote services that do not offer post-quantum ciphers.

Description

This plugin reports network services that do not offer post-quantum ciphers. Tenable makes no attempt to determine whether the remote service would be vulnerable to a post-quantum attack.

However, cryptography that depends on the classic difficulty of solving the discrete logarithm problem or on the classic difficulty of large prime factorization is broken by Shor's algorithm. Examples of this are RSA asymmetric encryption and Diffie-Hellman key exchange.

See Also

<http://www.nessus.org/u?7a390f87>

<http://www.nessus.org/u?ad7d6b3b>

<http://www.nessus.org/u?1c0c61e0>

<http://www.nessus.org/u?5eec4b28>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/12/08, Modified: 2025/12/08

Plugin Output

tcp/5432/postgresql

The target TLS server offers no post-quantum ciphers.

70657 - SSH Algorithms and Languages Supported

Synopsis

An SSH server is listening on this port.

Description

This script detects which algorithms and languages are supported by the remote service for encrypting communications.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2013/10/28, Modified: 2026/01/12

Plugin Output

tcp/22/ssh

```
Nessus negotiated the following encryption algorithm(s) with the server :
```

```
Client to Server: aes256-ctr
Server to Client: aes256-ctr
```

```
The server supports the following options for compression_algorithms_server_to_client :
```

```
none
zlib@openssh.com
```

```
The server supports the following options for mac_algorithms_client_to_server :
```

```
hmac-md5
hmac-md5-96
hmac-ripemd160
hmac-ripemd160@openssh.com
hmac-sha1
hmac-sha1-96
umac-64@openssh.com
```

```
The server supports the following options for server_host_key_algorithms :
```

```
ssh-dss
ssh-rsa
```

```
The server supports the following options for encryption_algorithms_client_to_server :
```

```
3des-cbc
aes128-cbc
```

```
aes128-ctr
aes192-cbc
aes192-ctr
aes256-cbc
aes256-ctr
arcfour
arcfour128
arcfour256
blowfish-cbc
cast128-cbc
rijndael-cbc@lysator.liu.se
```

The server supports the following options for `mac_algorithms_server_to_client` :

```
hmac-md5
hmac-md5-96
hmac-ripemd160
hmac-ripemd160@openssh.com
hmac-sha1
hmac-sha1-96
umac-64@openssh.com
```

The server supports the following options for `kex_algorithms` :

```
diffie-hellman-group-exchange-sha1
diffie-hellman-group-exchange-sha256
diffie-hellman-group1-sha1
diffie-hellman-group14-sha1
```

The server supports the following options for `compression_algorithms_client_to_server` :

```
none
zlib@openssh.com
```

The server supports the following options for `encryption_algorithms_server_to_client` :

```
3des-cbc
aes128-cbc
aes128-ctr
aes192-cbc
aes192-ctr
aes256-cbc
aes256-ctr
arcfour
arcfour128
arcfour256
blowfish-cbc
cast128-cbc
rijndael-cbc@lysator.liu.se
```

149334 - SSH Password Authentication Accepted

Synopsis

The SSH server on the remote host accepts password authentication.

Description

The SSH server on the remote host accepts password authentication.

See Also

<https://tools.ietf.org/html/rfc4252#section-8>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2021/05/07, Modified: 2021/05/07

Plugin Output

tcp/22/ssh

10881 - SSH Protocol Versions Supported

Synopsis

A SSH server is running on the remote host.

Description

This plugin determines the versions of the SSH protocol supported by the remote SSH daemon.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/03/06, Modified: 2026/01/12

Plugin Output

tcp/22/ssh

The remote SSH daemon supports the following versions of the SSH protocol :

- 1.99
- 2.0

153588 - SSH SHA-1 HMAC Algorithms Enabled

Synopsis

The remote SSH server is configured to enable SHA-1 HMAC algorithms.

Description

The remote SSH server is configured to enable SHA-1 HMAC algorithms.

Although NIST has formally deprecated use of SHA-1 for digital signatures, SHA-1 is still considered secure for HMAC as the security of HMAC does not rely on the underlying hash function being resistant to collisions.

Note that this plugin only checks for the options of the remote SSH server.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2021/09/23, Modified: 2022/04/05

Plugin Output

tcp/22/ssh

The following client-to-server SHA-1 Hash-based Message Authentication Code (HMAC) algorithms are supported :

hmac-md5, hmac-sha1, umac-64@openssh.com, hmac-ripemd160, hmac-ripemd160@openssh.com, hmac-sha1-96, hmac-md5-96

The following server-to-client SHA-1 Hash-based Message Authentication Code (HMAC) algorithms are supported :

hmac-md5, hmac-sha1, umac-64@openssh.com, hmac-ripemd160, hmac-ripemd160@openssh.com, hmac-sha1-96, hmac-md5-96

10267 - SSH Server Type and Version Information

Synopsis

An SSH server is listening on this port.

Description

It is possible to obtain information about the remote SSH server by sending an empty authentication request.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0933

Plugin Information

Published: 1999/10/12, Modified: 2024/07/24

Plugin Output

tcp/22/ssh

```
SSH version : SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1
SSH supported authentication : publickey,password
```

56984 - SSL / TLS Versions Supported

Synopsis

The remote service encrypts communications.

Description

This plugin detects which SSL and TLS versions are supported by the remote service for encrypting communications.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/12/01, Modified: 2025/06/16

Plugin Output

tcp/5432/postgresql

This port supports SSLv3/TLSv1.0.

45410 - SSL Certificate 'commonName' Mismatch

Synopsis

The 'commonName' (CN) attribute in the SSL certificate does not match the hostname.

Description

The service running on the remote host presents an SSL certificate for which the 'commonName' (CN) attribute does not match the hostname on which the service listens.

Solution

If the machine has several names, make sure that users connect to the service through the DNS hostname that matches the common name in the certificate.

Risk Factor

None

Plugin Information

Published: 2010/04/03, Modified: 2021/03/09

Plugin Output

tcp/5432/postgresql

The host name known by Nessus is :

8e45b17a1053

The Common Name in the certificate is :

ubuntu804-base.localdomain

10863 - SSL Certificate Information

Synopsis

This plugin displays the SSL certificate.

Description

This plugin connects to every SSL-related port and attempts to extract and dump the X.509 certificate.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2008/05/19, Modified: 2021/02/03

Plugin Output

tcp/5432/postgresql

```
Subject Name:
Country: XX
State/Province: There is no such thing outside US
Locality: Everywhere
Organization: OCOSA
Organization Unit: Office for Complication of Otherwise Simple Affairs
Common Name: ubuntu804-base.localdomain
Email Address: root@ubuntu804-base.localdomain

Issuer Name:
Country: XX
State/Province: There is no such thing outside US
Locality: Everywhere
Organization: OCOSA
Organization Unit: Office for Complication of Otherwise Simple Affairs
Common Name: ubuntu804-base.localdomain
Email Address: root@ubuntu804-base.localdomain

Serial Number: 00 FA F9 3A 4C 7F B6 B9 CC

Version: 1

Signature Algorithm: SHA-1 With RSA Encryption

Not Valid Before: Mar 17 14:07:45 2010 GMT
Not Valid After: Apr 16 14:07:45 2010 GMT

Public Key Info:
Algorithm: RSA Encryption
```

Key Length: 1024 bits

Public Key: 00 D6 B4 13 36 33 9A 95 71 7B 1B DE 7C 83 75 DA 71 B1 3C A9
7F FE AD 64 1B 77 E9 4F AE BE CA D4 F8 CB EF AE BB 43 79 24
73 FF 3C E5 9E 3B 6D FC C8 B1 AC FA 4C 4D 5E 9B 4C 99 54 0B
D7 A8 4A 50 BA A9 DE 1D 1F F4 E4 6B 02 A3 F4 6B 45 CD 4C AF
8D 89 62 33 8F 65 BB 36 61 9F C4 2C 73 C1 4E 2E A0 A8 14 4E
98 70 46 61 BB D1 B9 31 DF 8C 99 EE 75 6B 79 3C 40 A0 AE 97
00 90 9D DC 99 0D 33 A4 B5

Exponent: 01 00 01

Signature Length: 128 bytes / 1024 bits

Signature: 00 92 A4 B4 B8 14 55 63 25 51 4A 0B C3 2A 22 CF 3A F8 17 6A
0C CF 66 AA A7 65 2F 48 6D CD E3 3E 5C 9F 77 6C D4 44 54 1F
1E 84 4F 8E D4 8D DD AC 2D 88 09 21 A8 DA 56 2C A9 05 3C 49
68 35 19 75 0C DA 53 23 88 88 19 2D 74 26 C1 22 65 EE 11 68
83 6A 53 4A 9C 27 CB A0 B4 E9 8D 29 0C B2 3C 18 5C 67 CC 53
A6 1E 30 D0 AA 26 7B 1E AE 40 B9 29 01 6C 2E BC A2 19 94 7C
15 6E 8D 30 38 F6 CA 2E 75

Fingerprints :

SHA-256 Fingerprint: E7 A7 FA 0D 63 E4 57 C7 C4 A5 9B 38 B7 08 49 C6 A7 0B DA 6F
83 0C 7A F1 E3 2D EE 43 6D E8 13 CC

SHA-1 Fingerprint: ED 09 30 88 70 66 03 BF D5 DC 23 73 99 B4 98 DA 2D [...]

70544 - SSL Cipher Block Chaining Cipher Suites Supported

Synopsis

The remote service supports the use of SSL Cipher Block Chaining ciphers, which combine previous blocks with subsequent ones.

Description

The remote host supports the use of SSL ciphers that operate in Cipher Block Chaining (CBC) mode. These cipher suites offer additional security over Electronic Codebook (ECB) mode, but have the potential to leak information if used improperly.

See Also

<https://www.openssl.org/docs/manmaster/man1/ciphers.html>

<http://www.nessus.org/u?cc4a822a>

<https://www.openssl.org/~bodo/tls-cbc.txt>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2013/10/22, Modified: 2021/02/03

Plugin Output

tcp/5432/postgresql

Here is the list of SSL CBC ciphers supported by the remote server :

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
EDH-RSA-DES-CBC3-SHA	0x00, 0x16	DHE	RSA	3DES-CBC(168)	
SHA1					
DES-CBC3-SHA	0x00, 0x0A	RSA	RSA	3DES-CBC(168)	
SHA1					

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
DHE-RSA-AES128-SHA	0x00, 0x33	DHE	RSA	AES-CBC(128)	
SHA1					

DHE-RSA-AES256-SHA	0x00, 0x39	DHE	RSA	AES-CBC(256)
SHA1				
AES128-SHA	0x00, 0x2F	RSA	RSA	AES-CBC(128)
SHA1				
AES256-SHA	0x00, 0x35	RSA	RSA	AES-CBC(256)
SHA1				

The fields above are :

```
{Tenable ciphertype}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}
```

21643 - SSL Cipher Suites Supported

Synopsis

The remote service encrypts communications using SSL.

Description

This plugin detects which SSL ciphers are supported by the remote service for encrypting communications.

See Also

<https://www.openssl.org/docs/man1.0.2/man1/ciphers.html>

<http://www.nessus.org/u?e17ffcd>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2006/06/05, Modified: 2026/04/13

Plugin Output

tcp/5432/postgresql

Here is the list of SSL ciphers supported by the remote server :
Each group is reported per SSL Version.

SSL Version : TLSv1

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	---	-----	---
EDH-RSA-DES-CBC3-SHA	0x00, 0x16	DHE	RSA	3DES-CBC(168)	
SHA1					
DES-CBC3-SHA	0x00, 0x0A	RSA	RSA	3DES-CBC(168)	
SHA1					

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	---	-----	---
DHE-RSA-AES128-SHA	0x00, 0x33	DHE	RSA	AES-CBC(128)	
SHA1					
DHE-RSA-AES256-SHA	0x00, 0x39	DHE	RSA	AES-CBC(256)	
SHA1					
AES128-SHA	0x00, 0x2F	RSA	RSA	AES-CBC(128)	
SHA1					

AES256-SHA	0x00, 0x35	RSA	RSA	AES-CBC(256)
SHA1				
RC4-SHA	0x00, 0x05	RSA	RSA	RC4(128)
SHA1				

SSL Version : SSLv3

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
EDH-RSA-DES-CBC3-SHA	0x00, 0x16	DHE	RSA	3DES-CBC(168)	
SHA1					
DES-CBC3-SHA	0x00, 0x0A	RSA	RSA	3DES-CBC(168)	
SHA1					

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	[...]		

62563 - SSL Compression Methods Supported

Synopsis

The remote service supports one or more compression methods for SSL connections.

Description

This script detects which compression methods are supported by the remote service for SSL connections.

See Also

<http://www.iana.org/assignments/comp-meth-ids/comp-meth-ids.xml>

<https://tools.ietf.org/html/rfc3749>

<https://tools.ietf.org/html/rfc3943>

<https://tools.ietf.org/html/rfc5246>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2012/10/16, Modified: 2022/04/11

Plugin Output

tcp/5432/postgresql

```
Nessus was able to confirm that the following compression method is
supported by the target :
```

```
  DEFLATE (0x01)
```

57041 - SSL Perfect Forward Secrecy Cipher Suites Supported

Synopsis

The remote service supports the use of SSL Perfect Forward Secrecy ciphers, which maintain confidentiality even if the key is stolen.

Description

The remote host supports the use of SSL ciphers that offer Perfect Forward Secrecy (PFS) encryption. These cipher suites ensure that recorded SSL traffic cannot be broken at a future date if the server's private key is compromised.

See Also

<https://www.openssl.org/docs/manmaster/man1/ciphers.html>

https://en.wikipedia.org/wiki/Diffie-Hellman_key_exchange

https://en.wikipedia.org/wiki/Perfect_forward_secrecy

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/12/07, Modified: 2021/03/09

Plugin Output

tcp/5432/postgresql

Here is the list of SSL PFS ciphers supported by the remote server :

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
EDH-RSA-DES-CBC3-SHA SHA1	0x00, 0x16	DHE	RSA	3DES-CBC(168)	

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
DHE-RSA-AES128-SHA SHA1	0x00, 0x33	DHE	RSA	AES-CBC(128)	
DHE-RSA-AES256-SHA SHA1	0x00, 0x39	DHE	RSA	AES-CBC(256)	

The fields above are :

```
{Tenable ciphername}  
{Cipher ID code}  
Kex={key exchange}  
Auth={authentication}  
Encrypt={symmetric encryption method}  
MAC={message authentication code}  
{export flag}
```

156899 - SSL/TLS Recommended Cipher Suites

Synopsis

The remote host advertises discouraged SSL/TLS ciphers.

Description

The remote host has open SSL/TLS ports which advertise discouraged cipher suites. It is recommended to only enable support for the following cipher suites:

TLSv1.3:

- 0x13,0x01 TLS13_AES_128_GCM_SHA256
- 0x13,0x02 TLS13_AES_256_GCM_SHA384
- 0x13,0x03 TLS13_CHACHA20_POLY1305_SHA256

TLSv1.2:

- 0xC0,0x2B ECDHE-ECDSA-AES128-GCM-SHA256
- 0xC0,0x2F ECDHE-RSA-AES128-GCM-SHA256
- 0xC0,0x2C ECDHE-ECDSA-AES256-GCM-SHA384
- 0xC0,0x30 ECDHE-RSA-AES256-GCM-SHA384
- 0xCC,0xA9 ECDHE-ECDSA-CHACHA20-POLY1305
- 0xCC,0xA8 ECDHE-RSA-CHACHA20-POLY1305

This is the recommended configuration for the vast majority of services, as it is highly secure and compatible with nearly every client released in the last five (or more) years.

See Also

https://wiki.mozilla.org/Security/Server_Side_TLS

<https://ssl-config.mozilla.org/>

Solution

Only enable support for recommended cipher suites.

Risk Factor

None

Plugin Information

Published: 2022/01/20, Modified: 2024/02/12

Plugin Output

tcp/5432/postgresql

The remote host has listening SSL/TLS ports which advertise the discouraged cipher suites outlined below:

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
EDH-RSA-DES-CBC3-SHA	0x00, 0x16	DHE	RSA	3DES-CBC(168)	
SHA1					
DES-CBC3-SHA	0x00, 0x0A	RSA	RSA	3DES-CBC(168)	
SHA1					

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
DHE-RSA-AES128-SHA	0x00, 0x33	DHE	RSA	AES-CBC(128)	
SHA1					
DHE-RSA-AES256-SHA	0x00, 0x39	DHE	RSA	AES-CBC(256)	
SHA1					
AES128-SHA	0x00, 0x2F	RSA	RSA	AES-CBC(128)	
SHA1					
AES256-SHA	0x00, 0x35	RSA	RSA	AES-CBC(256)	
SHA1					
RC4-SHA	0x00, 0x05	RSA	RSA	RC4(128)	
SHA1					

The fields above are :

{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}

25240 - Samba Server Detection

Synopsis

An SMB server is running on the remote host.

Description

The remote host is running Samba, a CIFS/SMB server for Linux and Unix.

See Also

<https://www.samba.org/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2022/10/12

Plugin Output

tcp/445/cifs

104887 - Samba Version

Synopsis

It was possible to obtain the samba version from the remote operating system.

Description

Nessus was able to obtain the samba version from the remote operating by sending an authentication request to port 139 or 445. Note that this plugin requires SMB1 to be enabled on the host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2017/11/30, Modified: 2019/11/22

Plugin Output

tcp/445/cifs

```
The remote Samba Version is : Samba 3.0.20-Debian
```


96982 - Server Message Block (SMB) Protocol Version 1 Enabled (uncredentialed check)

Synopsis

The remote host supports the SMBv1 protocol.

Description

The remote host (Windows and/or Samba server) supports Server Message Block Protocol version 1 (SMBv1). Microsoft recommends that users discontinue the use of SMBv1 due to the lack of security features that were included in later SMB versions. Additionally, most security and compliance agencies recommend that users disable SMBv1 per SMB best practices.

See Also

<http://www.nessus.org/u?59bfc3ef>

<http://www.nessus.org/u?b9d9ebf9>

<http://www.nessus.org/u?8dcab5e4>

<http://www.nessus.org/u?234f8ef8>

<http://www.nessus.org/u?4c7e0cf3>

Solution

Disable SMBv1 according to the vendor instructions in Microsoft KB2696547. Additionally, block SMB directly by blocking TCP port 445 on all network boundary devices. For SMB over the NetBIOS API, block TCP ports 137 / 139 and UDP ports 137 / 138 on all network boundary devices.

Risk Factor

None

References

XREF IAVT:0001-T-0710

Plugin Information

Published: 2017/02/03, Modified: 2025/08/13

Plugin Output

tcp/445/cifs

The remote host supports SMBv1.

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/21/ftp

```
An FTP server is running on this port.
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/22/ssh

```
An SSH server is running on this port.
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/23/telnet

```
A telnet server is running on this port.
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/80/www

```
A web server is running on this port.
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/3306/mysql

A MySQL server is running on this port.

Synopsis

Reports remote services potentially vulnerable to Shor's Algorithm.

Description

This plugin reports network services that may be vulnerable now to a future attack by adversaries using a cryptographically relevant quantum computer (CRQC). Shor's is a theoretical algorithm that leverages the unique ability of quantum computation to do massively parallel calculations developed by Peter Shor in 1994.

This algorithm easily computes two classically difficult mathematical problems used in modern cryptography; discrete logarithms, and factoring numbers formed by multiplying large primes. Shor's reduces both of these problems from taking exponential time in chosen cases to being solvable in polynomial time.

Asymmetric encryption algorithms such as RSA, Diffie-Hellman and Elliptic Curve Diffie-Hellman are impacted by Shor's Algorithm. The most common uses of these algorithms are in symmetric key establishment and authentication. These uses render Shor's Algorithm particularly dangerous because it may give an adversary the ability to harvest network communications now, and in the future, when a CRQC becomes available, extract the symmetric key and decrypt the communication.

See Also

<http://www.nessus.org/u?54fba2c1>

Solution

Replace affected ciphers with algorithms chosen to resist CRQC attack.

Risk Factor

None

Plugin Information

Published: 2026/02/09, Modified: 2026/04/13

Plugin Output

tcp/0

```
The TLS service on port 5432/TLSv1 offers these ciphers vulnerable to Shor's:
TLS_RSA_WITH_3DES_EDE_CBC_SHA
TLS_DHE_RSA_WITH_AES_256_CBC_SHA
TLS_RSA_WITH_RC4_128_SHA
TLS_DHE_RSA_WITH_3DES_EDE_CBC_SHA
TLS_RSA_WITH_AES_256_CBC_SHA
TLS_DHE_RSA_WITH_AES_128_CBC_SHA
TLS_RSA_WITH_AES_128_CBC_SHA
```

The SSH service on port 22 offers these ciphers vulnerable to Shor's:

```
diffie-hellman-group14-sha1
diffie-hellman-group-exchange-sha1
diffie-hellman-group1-sha1
diffie-hellman-group-exchange-sha256
```

The TLS service on port 5432/SSLv3 offers these ciphers vulnerable to Shor's:

```
TLS_RSA_WITH_3DES_EDE_CBC_SHA
TLS_DHE_RSA_WITH_AES_256_CBC_SHA
TLS_RSA_WITH_RC4_128_SHA
TLS_DHE_RSA_WITH_3DES_EDE_CBC_SHA
TLS_RSA_WITH_AES_256_CBC_SHA
TLS_DHE_RSA_WITH_AES_128_CBC_SHA
TLS_RSA_WITH_AES_128_CBC_SHA
```


25220 - TCP/IP Timestamps Supported

Synopsis

The remote service implements TCP timestamps.

Description

The remote host implements TCP timestamps, as defined by RFC1323. A side effect of this feature is that the uptime of the remote host can sometimes be computed.

See Also

<http://www.ietf.org/rfc/rfc1323.txt>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2023/10/17

Plugin Output

tcp/0

11819 - TFTP Daemon Detection

Synopsis

A TFTP server is listening on the remote port.

Description

The remote host is running a TFTP (Trivial File Transfer Protocol) daemon. TFTP is often used by routers and diskless hosts to retrieve their configuration. It can also be used by worms to propagate.

Solution

Disable this service if you do not use it.

Risk Factor

None

Plugin Information

Published: 2003/08/13, Modified: 2022/12/28

Plugin Output

udp/69/tftp

110723 - Target Credential Status by Authentication Protocol - No Credentials Provided

Synopsis

Nessus was able to find common ports used for local checks, however, no credentials were provided in the scan policy.

Description

Nessus was not able to successfully authenticate directly to the remote target on an available authentication protocol. Nessus was able to connect to the remote port and identify that the service running on the port supports an authentication protocol, but Nessus failed to authenticate to the remote service using the provided credentials. There may have been a protocol failure that prevented authentication from being attempted or all of the provided credentials for the authentication protocol may be invalid. See plugin output for error details.

Please note the following :

- This plugin reports per protocol, so it is possible for valid credentials to be provided for one protocol and not another. For example, authentication may succeed via SSH but fail via SMB, while no credentials were provided for an available SNMP service.
- Providing valid credentials for all available authentication protocols may improve scan coverage, but the value of successful authentication for a given protocol may vary from target to target depending upon what data (if any) is gathered from the target via that protocol. For example, successful authentication via SSH is more valuable for Linux targets than for Windows targets, and likewise successful authentication via SMB is more valuable for Windows targets than for Linux targets.

Solution

n/a

Risk Factor

None

References

XREF IAVB:0001-B-0504

Plugin Information

Published: 2018/06/27, Modified: 2024/04/19

Plugin Output

tcp/0

```
SSH was detected on port 22 but no credentials were provided.  
SSH local checks were not enabled.
```


10287 - Traceroute Information

Synopsis

It was possible to obtain traceroute information.

Description

Makes a traceroute to the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/11/27, Modified: 2026/04/27

Plugin Output

udp/0

```
For your information, here is the traceroute from 172.30.0.2 to 172.30.1.1 :  
172.30.0.2  
172.30.1.1  
  
Hop Count: 1
```

11154 - Unknown Service Detection: Banner Retrieval

Synopsis

There is an unknown service running on the remote host.

Description

Nessus was unable to identify a service on the remote host even though it returned a banner of some type.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/11/18, Modified: 2022/07/26

Plugin Output

tcp/1524

If you know what this service is and think the banner could be used to identify it, please send a description of the service along with the following output to svc-signatures@nessus.org :

```
Port    : 1524
Type    : spontaneous
Banner  :
0x00:  1B 5D 30 3B 40 38 65 34 35 62 31 37 61 31 30 35    .]0;@8e45b17a105
      0x10:  33 3A 20 2F 07 72 6F 6F 74 40 38 65 34 35 62 31    3: /.root@8e45b1
      0x20:  37 61 31 30 35 33 3A 2F 23 20                    7a1053:/#
```

11424 - WebDAV Detection

Synopsis

The remote server is running with WebDAV enabled.

Description

WebDAV is an industry standard extension to the HTTP specification.

It adds a capability for authorized users to remotely add and manage the content of a web server.

If you do not use this extension, you should disable it.

Solution

<http://support.microsoft.com/default.aspx?kbid=241520>

Risk Factor

None

Plugin Information

Published: 2003/03/20, Modified: 2011/03/14

Plugin Output

tcp/80/www

10150 - Windows NetBIOS / SMB Remote Host Information Disclosure

Synopsis

It was possible to obtain the network name of the remote host.

Description

The remote host is listening on UDP port 137 or TCP port 445, and replies to NetBIOS nbtscan or SMB requests.

Note that this plugin gathers information to be used in other plugins, but does not itself generate a report.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/10/12, Modified: 2021/02/10

Plugin Output

udp/137/netbios-ns

The following 7 NetBIOS names have been gathered :

8E45B17A1053	= Computer name
8E45B17A1053	= Messenger Service
8E45B17A1053	= File Server Service
__MSBROWSE__	= Master Browser
WORKGROUP	= Workgroup / Domain name
WORKGROUP	= Master Browser
WORKGROUP	= Browser Service Elections

This SMB server seems to be a Samba server - its MAC address is NULL.

52703 - vsftpd Detection

Synopsis

An FTP server is listening on the remote port.

Description

The remote host is running vsftpd, an FTP server for UNIX-like systems written in C.

See Also

<http://vsftpd.beasts.org/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/03/17, Modified: 2019/11/22

Plugin Output

tcp/21/ftp

```
Source   : 220 (vsFTPd 2.3.4)
Version  : 2.3.4
```

172.30.2.2



Scan Information

Start time: Thu Jul 23 18:30:17 2026

End time: Thu Jul 23 18:37:48 2026

Host Information

IP: 172.30.2.2

MAC Address: 12:C7:39:85:8B:58

OS: SuSE Linux

Vulnerabilities

50686 - IP Forwarding Enabled

Synopsis

The remote host has IP forwarding enabled.

Description

The remote host has IP forwarding enabled. An attacker can exploit this to route packets through the host and potentially bypass some firewalls / routers / NAC filtering.

Unless the remote host is a router, it is recommended that you disable IP forwarding.

Solution

On Linux, you can disable IP forwarding by doing :

```
echo 0 > /proc/sys/net/ipv4/ip_forward
```

On Windows, set the key 'IPEnableRouter' to 0 under

HKEY_LOCAL_MACHINE\System\CurrentControlSet\Services\Tcpip\Parameters

On Mac OS X, you can disable IP forwarding by executing the command :

```
sysctl -w net.inet.ip.forwarding=0
```

For other systems, check with your vendor.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:A/AC:L/PR:L/UI:N/S:C/C:L/I:L/A:L)

CVSS v2.0 Base Score

5.8 (CVSS2#AV:A/AC:L/Au:N/C:P/I:P/A:P)

References

CVE CVE-1999-0511

Plugin Information

Published: 2010/11/23, Modified: 2023/10/17

Plugin Output

tcp/0

```
IP forwarding appears to be enabled on the remote host.
```

```
Detected local MAC Address      : e68cc3441691
Response from local MAC Address : e68cc3441691
```

```
Detected Gateway MAC Address    : 12c739858b58
Response from Gateway MAC Address : 12c739858b58
```

10114 - ICMP Timestamp Request Remote Date Disclosure

Synopsis

It is possible to determine the exact time set on the remote host.

Description

The remote host answers to an ICMP timestamp request. This allows an attacker to know the date that is set on the targeted machine, which may assist an unauthenticated, remote attacker in defeating time-based authentication protocols.

Timestamps returned from machines running Windows Vista / 7 / 2008 / 2008 R2 are deliberately incorrect, but usually within 1000 seconds of the actual system time.

Solution

Filter out the ICMP timestamp requests (13), and the outgoing ICMP timestamp replies (14).

Risk Factor

Low

CVSS v2.0 Base Score

2.1 (CVSS2#AV:L/AC:L/Au:N/C:P/I:N/A:N)

References

CVE	CVE-1999-0524
XREF	CWE:200

Plugin Information

Published: 1999/08/01, Modified: 2024/10/07

Plugin Output

icmp/0

```
The remote clock is synchronized with the local clock.
```

48204 - Apache HTTP Server Version

Synopsis

It is possible to obtain the version number of the remote Apache HTTP server.

Description

The remote host is running the Apache HTTP Server, an open source web server. It was possible to read the version number from the banner.

See Also

<https://httpd.apache.org/>

Solution

n/a

Risk Factor

None

References

XREF	IAVT:0001-T-0030
XREF	IAVT:0001-T-0530

Plugin Information

Published: 2010/07/30, Modified: 2026/01/22

Plugin Output

tcp/80/www

```
URL      : http://172.30.2.2/
Version  : 2.4.59
Source   : Server: Apache/2.4.59 (Debian)
backported : 1
os       : Debian
```

39519 - Backported Security Patch Detection (FTP)

Synopsis

Security patches are backported.

Description

Security patches may have been 'backported' to the remote FTP server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/06/25, Modified: 2026/01/22

Plugin Output

tcp/21/ftp

Give Nessus credentials to perform local checks.

39520 - Backported Security Patch Detection (SSH)

Synopsis

Security patches are backported.

Description

Security patches may have been 'backported' to the remote SSH server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/06/25, Modified: 2026/01/22

Plugin Output

tcp/22/ssh

Give Nessus credentials to perform local checks.

39521 - Backported Security Patch Detection (WWW)

Synopsis

Security patches are backported.

Description

Security patches may have been 'backported' to the remote HTTP server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/06/25, Modified: 2026/01/22

Plugin Output

tcp/80/www

Give Nessus credentials to perform local checks.

45590 - Common Platform Enumeration (CPE)

Synopsis

It was possible to enumerate CPE names that matched on the remote system.

Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

See Also

<http://cpe.mitre.org/>

<https://nvd.nist.gov/products/cpe>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/04/21, Modified: 2026/06/16

Plugin Output

tcp/0

Following application CPE's matched on the remote system :

```
cpe:/a:apache:http_server:2.4.59 -> Apache Software Foundation Apache HTTP Server
cpe:/a:openbsd:openssh:8.4 -> OpenBSD OpenSSH
cpe:/a:openbsd:openssh:8.4p1 -> OpenBSD OpenSSH
```

54615 - Device Type

Synopsis

It is possible to guess the remote device type.

Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/05/23, Modified: 2025/03/12

Plugin Output

tcp/0

Remote device type : unknown
Confidence level : 56

86420 - Ethernet MAC Addresses

Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/10/16, Modified: 2025/06/10

Plugin Output

tcp/0

The following is a consolidated list of detected MAC addresses:
- 12:C7:39:85:8B:58

10092 - FTP Server Detection

Synopsis

An FTP server is listening on a remote port.

Description

It is possible to obtain the banner of the remote FTP server by connecting to a remote port.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0030

XREF IAVT:0001-T-0943

Plugin Information

Published: 1999/10/12, Modified: 2023/08/17

Plugin Output

tcp/21/ftp

The remote FTP banner is :

220 (vsFTPd 3.0.3)

43111 - HTTP Methods Allowed (per directory)

Synopsis

This plugin determines which HTTP methods are allowed on various CGI directories.

Description

By calling the OPTIONS method, it is possible to determine which HTTP methods are allowed on each directory.

The following HTTP methods are considered insecure:

PUT, DELETE, CONNECT, TRACE, HEAD

Many frameworks and languages treat 'HEAD' as a 'GET' request, albeit one without any body in the response. If a security constraint was set on 'GET' requests such that only 'authenticatedUsers' could access GET requests for a particular servlet or resource, it would be bypassed for the 'HEAD' version. This allowed unauthorized blind submission of any privileged GET request.

As this list may be incomplete, the plugin also tests - if 'Thorough tests' are enabled or 'Enable web applications tests' is set to 'yes'

in the scan policy - various known HTTP methods on each directory and considers them as unsupported if it receives a response code of 400, 403, 405, or 501.

Note that the plugin output is only informational and does not necessarily indicate the presence of any security vulnerabilities.

See Also

<http://www.nessus.org/u?d9c03a9a>

<http://www.nessus.org/u?b019cbdb>

[https://www.owasp.org/index.php/Test_HTTP_Methods_\(OTG-CONFIG-006\)](https://www.owasp.org/index.php/Test_HTTP_Methods_(OTG-CONFIG-006))

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/12/10, Modified: 2022/04/11

Plugin Output

tcp/80/www

Based on the response to an OPTIONS request :

- HTTP methods GET HEAD OPTIONS POST are allowed on :

/

10107 - HTTP Server Type and Version

Synopsis

A web server is running on the remote host.

Description

This plugin attempts to determine the type and the version of the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0931

Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

Plugin Output

tcp/80/www

```
The remote web server type is :  
Apache/2.4.59 (Debian)
```


12053 - Host Fully Qualified Domain Name (FQDN) Resolution

Synopsis

It was possible to resolve the name of the remote host.

Description

Nessus was able to resolve the fully qualified domain name (FQDN) of the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/02/11, Modified: 2025/03/13

Plugin Output

tcp/0

```
172.30.2.2 resolves as proftpd-vuln.labvulnerabilities_vulnnet.
```

24260 - HyperText Transfer Protocol (HTTP) Information

Synopsis

Some information about the remote HTTP configuration can be extracted.

Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

Plugin Output

tcp/80/www

Response Code : HTTP/1.1 200 OK

Protocol version : HTTP/1.1

HTTP/2 TLS Support: No

HTTP/2 Cleartext Support: No

SSL : no

Keep-Alive : yes

Options allowed : (Not implemented)

Headers :

Date: Thu, 23 Jul 2026 22:31:49 GMT

Server: Apache/2.4.59 (Debian)

Last-Modified: Sat, 04 May 2024 06:53:23 GMT

ETag: "29cd-6179b4ad35ec0"

Accept-Ranges: bytes

Content-Length: 10701

Vary: Accept-Encoding

Keep-Alive: timeout=5, max=98

Connection: Keep-Alive

Content-Type: text/html

Response Body :

```
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN" "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">
<html xmlns="http://www.w3.org/1999/xhtml">
```

```

<head>
  <meta http-equiv="Content-Type" content="text/html; charset=UTF-8" />
  <title>Apache2 Debian Default Page: It works</title>
  <style type="text/css" media="screen">
    * {
      margin: 0px 0px 0px 0px;
      padding: 0px 0px 0px 0px;
    }

    body, html {
      padding: 3px 3px 3px 3px;

      background-color: #D8DBE2;

      font-family: Verdana, sans-serif;
      font-size: 11pt;
      text-align: center;
    }

    div.main_page {
      position: relative;
      display: table;

      width: 800px;

      margin-bottom: 3px;
      margin-left: auto;
      margin-right: auto;
      padding: 0px 0px 0px 0px;

      border-width: 2px;
      border-color: #212738;
      border-style: solid;

      background-color: #FFFFFF;

      text-align: center;
    }

    div.page_header {
      height: 99px;
      width: 100%;

      background-color: #F5F6F7;
    }

    div.page_header span {
      margin: 15px 0px 0px 50px;

      font-size: 180%;
      font-weight: bold;
    }

    div.page_header img {
      margin: 3px 0px 0px 40px;

      border: 0px 0px 0px;
    }

    div.table_of_contents {
      clear: left;

      min-width: 200px;

      margin: 3px 3px 3px 3px;

      background-color: #FFFFFF;

      text-align: left;
    }
  </style>
</head>

```

```
div.table_of_contents_item {  
  clear: left;  
  
  width: 100%;  
  
  margin: 4px 0px 0px 0px;  
  
  background-color: #FFFFFF;  
  
  color: #000000;  
  text-align: left;  
}  
  
div.table_of_con [...]
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/21/ftp

```
Port 21/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/22/ssh

```
Port 22/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/80/www

```
Port 80/tcp was found to be open
```

19506 - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2026/07/10

Plugin Output

tcp/0

Information about this scan :

```
Nessus version : 10.12.2
Nessus build : 20029
Plugin feed version : 202607231328
Scanner edition used : Nessus
Scanner OS : LINUX
Scanner distribution : ubuntu1604-x86-64
Scan type : Normal
Scan name : My Basic Network Scan
```



```
Scan policy used : Basic Network Scan
Scanner IP : 172.30.0.2
Port scanner(s) : nessus_syn_scanner
Port range : default
Ping RTT : 75.784 ms
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Assess component installs : yes
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 30
Max checks : 4
Recv timeout : 5
Backports : Detected
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2026/7/23 18:30 EDT (UTC -04:00)
Scan duration : 447 sec
Scan for malware : no
Fully Scan Operational Technology devices : no
Safely Scan Operational Technology devices with OT Discovery : no
```

209654 - OS Fingerprints Detected

Synopsis

Multiple OS fingerprints were detected.

Description

Using a combination of remote probes (TCP/IP, SMB, HTTP, NTP, SNMP, etc), it was possible to gather one or more fingerprints from the remote system. While the highest-confidence result was reported in plugin 11936, "OS Identification", the complete set of fingerprints detected are reported here.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/02/26, Modified: 2025/03/03

Plugin Output

tcp/0

Following OS Fingerprints were found

Remote operating system : SuSE Linux
Confidence level : 56
Method : MLSinFP
Type : unknown
Fingerprint : unknown

Remote operating system : Linux Kernel 2.x
Confidence level : 54
Method : SinFP
Type : general-purpose
Fingerprint : SinFP:

P1:B10113:F0x12:W64240:00204ffff:M1460:
P2:B10113:F0x12:W65160:00204ffff0402080affffff444541440103030a:M1460:
P3:B00000:F0x00:W0:00:M0
P4:191802_7_p=22

Following fingerprints could not be used to determine OS :
SSH::SSH-2.0-OpenSSH_8.4p1 Debian-5+deb11u3
HTTP::Server: Apache/2.4.59 (Debian)

11936 - OS Identification

Synopsis

It is possible to guess the remote operating system.

Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2003/12/09, Modified: 2025/06/03

Plugin Output

tcp/0

```
Remote operating system : SuSE Linux
Confidence level : 56
Method : MLSinFP
```

```
The remote host is running SuSE Linux
```

117886 - OS Security Patch Assessment Not Available

Synopsis

OS Security Patch Assessment is not available.

Description

OS Security Patch Assessment is not available on the remote host.

This does not necessarily indicate a problem with the scan.

Credentials may not have been provided, OS security patch assessment may not be supported for the target, the target may not have been identified, or another issue may have occurred that prevented OS security patch assessment from being available. See plugin output for details.

This plugin reports non-failure information impacting the availability of OS Security Patch Assessment. Failure information is reported by plugin 21745 : 'OS Security Patch Assessment failed'. If a target host is not supported for OS Security Patch Assessment, plugin 110695 : 'OS Security Patch Assessment Checks Not Supported' will report concurrently with this plugin.

Solution

n/a

Risk Factor

None

References

XREF IAVB:0001-B-0515

Plugin Information

Published: 2018/10/02, Modified: 2021/07/12

Plugin Output

tcp/0

The following issues were reported :

```
- Plugin      : no_local_checks_credentials.nasl
  Plugin ID   : 110723
  Plugin Name : Target Credential Status by Authentication Protocol - No Credentials Provided
  Message     :
  Credentials were not provided for detected SSH service.
```

181418 - OpenSSH Detection

Synopsis

An OpenSSH-based SSH server was detected on the remote host.

Description

An OpenSSH-based SSH server was detected on the remote host.

See Also

<https://www.openssh.com/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/09/14, Modified: 2026/07/20

Plugin Output

tcp/22/ssh

```
Service      : ssh
Version      : 8.4p1
Banner       : SSH-2.0-OpenSSH_8.4p1 Debian-5+deb11u3
backported   : 1
```

277650 - Remote Services Not Using Post-Quantum Ciphers

Synopsis

Reports remote services that do not offer post-quantum ciphers.

Description

This plugin reports network services that do not offer post-quantum ciphers. Tenable makes no attempt to determine whether the remote service would be vulnerable to a post-quantum attack.

However, cryptography that depends on the classic difficulty of solving the discrete logarithm problem or on the classic difficulty of large prime factorization is broken by Shor's algorithm. Examples of this are RSA asymmetric encryption and Diffie-Hellman key exchange.

See Also

<http://www.nessus.org/u?7a390f87>

<http://www.nessus.org/u?ad7d6b3b>

<http://www.nessus.org/u?1c0c61e0>

<http://www.nessus.org/u?5eec4b28>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/12/08, Modified: 2025/12/08

Plugin Output

tcp/22/ssh

The target SSH server offers no post-quantum ciphers.

70657 - SSH Algorithms and Languages Supported

Synopsis

An SSH server is listening on this port.

Description

This script detects which algorithms and languages are supported by the remote service for encrypting communications.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2013/10/28, Modified: 2026/01/12

Plugin Output

tcp/22/ssh

```
Nessus negotiated the following encryption algorithm(s) with the server :
```

```
Client to Server: aes256-ctr
Server to Client: aes256-ctr
```

```
The server supports the following options for compression_algorithms_server_to_client :
```

```
none
zlib@openssh.com
```

```
The server supports the following options for mac_algorithms_client_to_server :
```

```
hmac-sha1
hmac-sha1-etm@openssh.com
hmac-sha2-256
hmac-sha2-256-etm@openssh.com
hmac-sha2-512
hmac-sha2-512-etm@openssh.com
umac-128-etm@openssh.com
umac-128@openssh.com
umac-64-etm@openssh.com
umac-64@openssh.com
```

```
The server supports the following options for server_host_key_algorithms :
```

```
ecdsa-sha2-nistp256
rsa-sha2-256
rsa-sha2-512
ssh-ed25519
```

ssh-rsa

The server supports the following options for encryption_algorithms_client_to_server :

aes128-ctr
aes128-gcm@openssh.com
aes192-ctr
aes256-ctr
aes256-gcm@openssh.com
chacha20-poly1305@openssh.com

The server supports the following options for mac_algorithms_server_to_client :

hmac-sha1
hmac-sha1-etm@openssh.com
hmac-sha2-256
hmac-sha2-256-etm@openssh.com
hmac-sha2-512
hmac-sha2-512-etm@openssh.com
umac-128-etm@openssh.com
umac-128@openssh.com
umac-64-etm@openssh.com
umac-64@openssh.com

The server supports the following options for kex_algorithms :

curve25519-sha256
curve25519-sha256@libssh.org
diffie-hellman-group-exchange-sha256
diffie-hellman-group14-sha256
diffie-hellman-group16-sha512
diffie-hellman-group18-sha512
ecdh-sha2-nistp256
ecdh-sha2-nistp384
ecdh-sha2-nistp521
kex-strict-s-v00@openssh.com

The server supports the following options for compression_algorithms_client_to_server :

none
zlib@openssh.com

The server supports the following options for encryption_algorithms_server_to_client :

aes128-ctr
aes128-gcm@openssh.com
aes192-ctr
aes256-ctr
aes256-gcm@openssh.com
chacha20-poly1305@openssh.com

149334 - SSH Password Authentication Accepted

Synopsis

The SSH server on the remote host accepts password authentication.

Description

The SSH server on the remote host accepts password authentication.

See Also

<https://tools.ietf.org/html/rfc4252#section-8>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2021/05/07, Modified: 2021/05/07

Plugin Output

tcp/22/ssh

10881 - SSH Protocol Versions Supported

Synopsis

A SSH server is running on the remote host.

Description

This plugin determines the versions of the SSH protocol supported by the remote SSH daemon.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/03/06, Modified: 2026/01/12

Plugin Output

tcp/22/ssh

The remote SSH daemon supports the following versions of the SSH protocol :

- 1.99
- 2.0

153588 - SSH SHA-1 HMAC Algorithms Enabled

Synopsis

The remote SSH server is configured to enable SHA-1 HMAC algorithms.

Description

The remote SSH server is configured to enable SHA-1 HMAC algorithms.

Although NIST has formally deprecated use of SHA-1 for digital signatures, SHA-1 is still considered secure for HMAC as the security of HMAC does not rely on the underlying hash function being resistant to collisions.

Note that this plugin only checks for the options of the remote SSH server.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2021/09/23, Modified: 2022/04/05

Plugin Output

tcp/22/ssh

The following client-to-server SHA-1 Hash-based Message Authentication Code (HMAC) algorithms are supported :

umac-64-etm@openssh.com,umac-128-etm@openssh.com,hmac-sha2-256-etm@openssh.com,hmac-sha2-512-etm@openssh.com,hmac-sha1-etm@openssh.com,umac-64@openssh.com,umac-128@openssh.com,hmac-sha2-256,hmac-sha2-512,hmac-sha1

The following server-to-client SHA-1 Hash-based Message Authentication Code (HMAC) algorithms are supported :

umac-64-etm@openssh.com,umac-128-etm@openssh.com,hmac-sha2-256-etm@openssh.com,hmac-sha2-512-etm@openssh.com,hmac-sha1-etm@openssh.com,umac-64@openssh.com,umac-128@openssh.com,hmac-sha2-256,hmac-sha2-512,hmac-sha1

10267 - SSH Server Type and Version Information

Synopsis

An SSH server is listening on this port.

Description

It is possible to obtain information about the remote SSH server by sending an empty authentication request.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0933

Plugin Information

Published: 1999/10/12, Modified: 2024/07/24

Plugin Output

tcp/22/ssh

```
SSH version : SSH-2.0-OpenSSH_8.4p1 Debian-5+deb11u3
SSH supported authentication : publickey,password
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/21/ftp

```
An FTP server is running on this port.
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/22/ssh

```
An SSH server is running on this port.
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/80/www

```
A web server is running on this port.
```

Synopsis

Reports remote services potentially vulnerable to Shor's Algorithm.

Description

This plugin reports network services that may be vulnerable now to a future attack by adversaries using a cryptographically relevant quantum computer (CRQC). Shor's is a theoretical algorithm that leverages the unique ability of quantum computation to do massively parallel calculations developed by Peter Shor in 1994.

This algorithm easily computes two classically difficult mathematical problems used in modern cryptography; discrete logarithms, and factoring numbers formed by multiplying large primes. Shor's reduces both of these problems from taking exponential time in chosen cases to being solvable in polynomial time.

Asymmetric encryption algorithms such as RSA, Diffie-Hellman and Elliptic Curve Diffie-Hellman are impacted by Shor's Algorithm. The most common uses of these algorithms are in symmetric key establishment and authentication. These uses render Shor's Algorithm particularly dangerous because it may give an adversary the ability to harvest network communications now, and in the future, when a CRQC becomes available, extract the symmetric key and decrypt the communication.

See Also

<http://www.nessus.org/u?54fba2c1>

Solution

Replace affected ciphers with algorithms chosen to resist CRQC attack.

Risk Factor

None

Plugin Information

Published: 2026/02/09, Modified: 2026/04/13

Plugin Output

tcp/0

```
The SSH service on port 22 offers these ciphers vulnerable to Shor's:
diffie-hellman-group-exchange-sha256
curve25519-sha256
ecdh-sha2-nistp256
ecdh-sha2-nistp521
curve25519-sha256@libssh.org
ecdh-sha2-nistp384
diffie-hellman-group18-sha512
```



```
diffie-hellman-group14-sha256  
diffie-hellman-group16-sha512
```

25220 - TCP/IP Timestamps Supported

Synopsis

The remote service implements TCP timestamps.

Description

The remote host implements TCP timestamps, as defined by RFC1323. A side effect of this feature is that the uptime of the remote host can sometimes be computed.

See Also

<http://www.ietf.org/rfc/rfc1323.txt>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2023/10/17

Plugin Output

tcp/0

110723 - Target Credential Status by Authentication Protocol - No Credentials Provided

Synopsis

Nessus was able to find common ports used for local checks, however, no credentials were provided in the scan policy.

Description

Nessus was not able to successfully authenticate directly to the remote target on an available authentication protocol. Nessus was able to connect to the remote port and identify that the service running on the port supports an authentication protocol, but Nessus failed to authenticate to the remote service using the provided credentials. There may have been a protocol failure that prevented authentication from being attempted or all of the provided credentials for the authentication protocol may be invalid. See plugin output for error details.

Please note the following :

- This plugin reports per protocol, so it is possible for valid credentials to be provided for one protocol and not another. For example, authentication may succeed via SSH but fail via SMB, while no credentials were provided for an available SNMP service.
- Providing valid credentials for all available authentication protocols may improve scan coverage, but the value of successful authentication for a given protocol may vary from target to target depending upon what data (if any) is gathered from the target via that protocol. For example, successful authentication via SSH is more valuable for Linux targets than for Windows targets, and likewise successful authentication via SMB is more valuable for Windows targets than for Linux targets.

Solution

n/a

Risk Factor

None

References

XREF IAVB:0001-B-0504

Plugin Information

Published: 2018/06/27, Modified: 2024/04/19

Plugin Output

tcp/0

```
SSH was detected on port 22 but no credentials were provided.  
SSH local checks were not enabled.
```


10287 - Traceroute Information

Synopsis

It was possible to obtain traceroute information.

Description

Makes a traceroute to the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/11/27, Modified: 2026/04/27

Plugin Output

udp/0

```
For your information, here is the traceroute from 172.30.0.2 to 172.30.2.2 :
172.30.0.2
172.30.2.2

Hop Count: 1
```

Synopsis

The remote web server contains a 'robots.txt' file.

Description

The remote host contains a file named 'robots.txt' that is intended to prevent web 'robots' from visiting certain directories in a website for maintenance or indexing purposes. A malicious user may also be able to use the contents of this file to learn of sensitive documents or directories on the affected site and either retrieve them directly or target them for other attacks.

See Also

<http://www.robotstxt.org/orig.html>

Solution

Review the contents of the site's robots.txt file, use Robots META tags instead of entries in the robots.txt file, and/or adjust the web server's access controls to limit access to sensitive material.

Risk Factor

None

Plugin Information

Published: 1999/10/12, Modified: 2026/03/10

Plugin Output

tcp/80/www

Contents of robots.txt :

```
User-agent: *  
Disallow: security.html  
Disallow: Security-Report.pdf  
Disallow: private.html  
Disallow: Trusted.html
```

52703 - vsftpd Detection

Synopsis

An FTP server is listening on the remote port.

Description

The remote host is running vsftpd, an FTP server for UNIX-like systems written in C.

See Also

<http://vsftpd.beasts.org/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/03/17, Modified: 2019/11/22

Plugin Output

tcp/21/ftp

```
Source   : 220 (vsFTPd 3.0.3)
Version  : 3.0.3
```

172.30.4.1



Scan Information

Start time: Thu Jul 23 18:30:17 2026
End time: Thu Jul 23 18:31:58 2026

Host Information

Netbios Name: HACKEDSAMBA
IP: 172.30.4.1
MAC Address: C2:13:09:60:C2:11
OS: Linux Kernel 6.x on Ubuntu

Vulnerabilities

42411 - Microsoft Windows SMB Shares Unprivileged Access

Synopsis

It is possible to access a network share.

Description

The remote host has one or more Windows shares that can be accessed through the network with the given credentials.

Depending on the share rights, it may allow an attacker to read/write confidential data.

Solution

To restrict access under Windows, open Explorer, right click on each share, go to the 'Sharing' tab, and click on 'Permissions'.

Risk Factor

High

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.5 (CVSS2#E:U/RL:OF/RC:C)

References

BID	8026
CVE	CVE-1999-0519
CVE	CVE-1999-0520

Plugin Information

Published: 2009/11/06, Modified: 2025/02/26

Plugin Output

tcp/445/cifs

```
The following shares can be accessed using a NULL session :
```

```
- data - (readable)
  + Content of this share :
..
```

50686 - IP Forwarding Enabled

Synopsis

The remote host has IP forwarding enabled.

Description

The remote host has IP forwarding enabled. An attacker can exploit this to route packets through the host and potentially bypass some firewalls / routers / NAC filtering.

Unless the remote host is a router, it is recommended that you disable IP forwarding.

Solution

On Linux, you can disable IP forwarding by doing :

```
echo 0 > /proc/sys/net/ipv4/ip_forward
```

On Windows, set the key 'IPEnableRouter' to 0 under

HKEY_LOCAL_MACHINE\System\CurrentControlSet\Services\Tcpip\Parameters

On Mac OS X, you can disable IP forwarding by executing the command :

```
sysctl -w net.inet.ip.forwarding=0
```

For other systems, check with your vendor.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:A/AC:L/PR:L/UI:N/S:C/C:L/I:L/A:L)

CVSS v2.0 Base Score

5.8 (CVSS2#AV:A/AC:L/Au:N/C:P/I:P/A:P)

References

CVE CVE-1999-0511

Plugin Information

Published: 2010/11/23, Modified: 2023/10/17

Plugin Output

tcp/0

IP forwarding appears to be enabled on the remote host.

Detected local MAC Address : e68cc3441691
Response from local MAC Address : e68cc3441691

Detected Gateway MAC Address : c2130960c211
Response from Gateway MAC Address : c2130960c211

57608 - SMB Signing not required

Synopsis

Signing is not required on the remote SMB server.

Description

Signing is not required on the remote SMB server. An unauthenticated, remote attacker can exploit this to conduct man-in-the-middle attacks against the SMB server.

See Also

<http://www.nessus.org/u?df39b8b3>

<http://technet.microsoft.com/en-us/library/cc731957.aspx>

<http://www.nessus.org/u?74b80723>

<https://www.samba.org/samba/docs/current/man-html/smb.conf.5.html>

<http://www.nessus.org/u?a3cac4ea>

Solution

Enforce message signing in the host's configuration. On Windows, this is found in the policy setting 'Microsoft network server: Digitally sign communications (always)'. On Samba, the setting is called 'server signing'. See the 'see also' links for further details.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

Plugin Information

Published: 2012/01/19, Modified: 2022/10/05

Plugin Output

tcp/445/cifs

10114 - ICMP Timestamp Request Remote Date Disclosure

Synopsis

It is possible to determine the exact time set on the remote host.

Description

The remote host answers to an ICMP timestamp request. This allows an attacker to know the date that is set on the targeted machine, which may assist an unauthenticated, remote attacker in defeating time-based authentication protocols.

Timestamps returned from machines running Windows Vista / 7 / 2008 / 2008 R2 are deliberately incorrect, but usually within 1000 seconds of the actual system time.

Solution

Filter out the ICMP timestamp requests (13), and the outgoing ICMP timestamp replies (14).

Risk Factor

Low

CVSS v2.0 Base Score

2.1 (CVSS2#AV:L/AC:L/Au:N/C:P/I:N/A:N)

References

CVE	CVE-1999-0524
XREF	CWE:200

Plugin Information

Published: 1999/08/01, Modified: 2024/10/07

Plugin Output

icmp/0

```
The remote clock is synchronized with the local clock.
```

45590 - Common Platform Enumeration (CPE)

Synopsis

It was possible to enumerate CPE names that matched on the remote system.

Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

See Also

<http://cpe.mitre.org/>

<https://nvd.nist.gov/products/cpe>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/04/21, Modified: 2026/06/16

Plugin Output

tcp/0

```
The remote operating system matched the following CPE :  
  cpe:/o:canonical:ubuntu_linux -> Canonical Ubuntu Linux  
Following application CPE matched on the remote system :  
  cpe:/a:samba:samba:4.5.9 -> Samba Samba
```

54615 - Device Type

Synopsis

It is possible to guess the remote device type.

Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/05/23, Modified: 2025/03/12

Plugin Output

tcp/0

Remote device type : unknown
Confidence level : 56

86420 - Ethernet MAC Addresses

Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/10/16, Modified: 2025/06/10

Plugin Output

tcp/0

```
The following is a consolidated list of detected MAC addresses:  
- C2:13:09:60:C2:11
```

12053 - Host Fully Qualified Domain Name (FQDN) Resolution

Synopsis

It was possible to resolve the name of the remote host.

Description

Nessus was able to resolve the fully qualified domain name (FQDN) of the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/02/11, Modified: 2025/03/13

Plugin Output

tcp/0

```
172.30.4.1 resolves as sambacry.labvulnerabilities_vulnnet.
```

10915 - Microsoft Windows - Local Users Information : User Has Never Logged In

Synopsis

At least one local user has never logged into his or her account.

Description

Using the supplied credentials, Nessus was able to list local users who have never logged into their accounts.

Solution

Delete accounts that are not needed.

Risk Factor

None

Plugin Information

Published: 2002/03/17, Modified: 2018/08/13

Plugin Output

tcp/0

The following local user has never logged in :

- sambacry

Note that, in addition to the Administrator and Guest accounts, Nessus has only checked for local users with UIDs between 1000 and 1200. To use a different range, edit the scan policy and change the 'Start UID' and/or 'End UID' preferences for 'SMB use host SID to enumerate local users' setting, and then re-run the scan.

Synopsis

It is possible to obtain the network name of the remote host.

Description

The remote host listens on tcp port 445 and replies to SMB requests.

By sending an NTLMSSP authentication request it is possible to obtain the name of the remote system and the name of its domain.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/11/06, Modified: 2019/11/22

Plugin Output

tcp/445/cifs

The following 2 NetBIOS names have been gathered :

HACKEDSAMBA	= Computer name
HACKEDSAMBA	= Workgroup / Domain name

17651 - Microsoft Windows SMB : Obtains the Password Policy

Synopsis

It is possible to retrieve the remote host's password policy using the supplied credentials.

Description

Using the supplied credentials it was possible to extract the password policy for the remote Windows host. The password policy must conform to the Informational System Policy.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/03/30, Modified: 2015/01/12

Plugin Output

tcp/445/cifs

The following password policy is defined on the remote host:

```
Minimum password len: 5
Password history len: 0
Maximum password age (d): No limit
Password must meet complexity requirements: Disabled
Minimum password age (d): 0
Forced logoff time (s): Not set
Locked account time (s): 1800
Time between failed logon (s): 1800
Number of invalid logon before locked out (s): 0
```

10859 - Microsoft Windows SMB LsaQueryInformationPolicy Function SID Enumeration

Synopsis

It is possible to obtain the host SID for the remote host.

Description

By emulating the call to LsaQueryInformationPolicy(), it was possible to obtain the host SID (Security Identifier).

The host SID can then be used to get the list of local users.

See Also

<http://technet.microsoft.com/en-us/library/bb418944.aspx>

Solution

You can prevent anonymous lookups of the host SID by setting the 'RestrictAnonymous' registry setting to an appropriate value.

Refer to the 'See also' section for guidance.

Risk Factor

None

Plugin Information

Published: 2002/02/13, Modified: 2024/01/31

Plugin Output

tcp/445/cifs

```
The remote host SID value is : S-1-5-21-2710473868-2173082553-2144423513
```

```
The value of 'RestrictAnonymous' setting is : unknown
```

Synopsis

It was possible to obtain information about the remote operating system.

Description

Nessus was able to obtain the remote operating system name and version (Windows and/or Samba) by sending an authentication request to port 139 or 445. Note that this plugin requires SMB to be enabled on the host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2001/10/17, Modified: 2021/09/20

Plugin Output

tcp/445/cifs

```
The remote Operating System is : Windows 6.1
The remote native LAN manager is : Samba 4.5.9
The remote SMB Domain Name is : HACKEDSAMBA
```

11011 - Microsoft Windows SMB Service Detection

Synopsis

A file / print sharing service is listening on the remote host.

Description

The remote service understands the CIFS (Common Internet File System) or Server Message Block (SMB) protocol, used to provide shared access to files, printers, etc between nodes on a network.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/06/05, Modified: 2021/02/11

Plugin Output

tcp/139/smb

```
An SMB server is running on this port.
```


11011 - Microsoft Windows SMB Service Detection

Synopsis

A file / print sharing service is listening on the remote host.

Description

The remote service understands the CIFS (Common Internet File System) or Server Message Block (SMB) protocol, used to provide shared access to files, printers, etc between nodes on a network.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/06/05, Modified: 2021/02/11

Plugin Output

tcp/445/cifs

```
A CIFS server is running on this port.
```

60119 - Microsoft Windows SMB Share Permissions Enumeration

Synopsis

It was possible to enumerate the permissions of remote network shares.

Description

By using the supplied credentials, Nessus was able to enumerate the permissions of network shares. User permissions are enumerated for each network share that has a list of access control entries (ACEs).

See Also

<https://technet.microsoft.com/en-us/library/bb456988.aspx>

<https://technet.microsoft.com/en-us/library/cc783530.aspx>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2012/07/25, Modified: 2022/08/11

Plugin Output

tcp/445/cifs

```
Share path : \\HACKEDSAMBA\data
Local path : C:\data
Comment : Data
[*] Allow ACE for Everyone (S-1-1-0): 0x001f01ff
    FILE_GENERIC_READ:      YES
    FILE_GENERIC_WRITE:     YES
    FILE_GENERIC_EXECUTE:   YES

Share path : \\HACKEDSAMBA\IPC$
Local path : C:\tmp
Comment : IPC Service (Crying samba)
[*] Allow ACE for Everyone (S-1-1-0): 0x001f01ff
    FILE_GENERIC_READ:      YES
    FILE_GENERIC_WRITE:     YES
    FILE_GENERIC_EXECUTE:   YES
```

10395 - Microsoft Windows SMB Shares Enumeration

Synopsis

It is possible to enumerate remote network shares.

Description

By connecting to the remote host, Nessus was able to enumerate the network share names.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2000/05/09, Modified: 2022/02/01

Plugin Output

tcp/445/cifs

Here are the SMB shares available on the remote host :

- data
- IPC\$

100871 - Microsoft Windows SMB Versions Supported (remote check)

Synopsis

It was possible to obtain information about the version of SMB running on the remote host.

Description

Nessus was able to obtain the version of SMB running on the remote host by sending an authentication request to port 139 or 445.

Note that this plugin is a remote check and does not work on agents.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2017/06/19, Modified: 2019/11/22

Plugin Output

tcp/445/cifs

```
The remote host supports the following versions of SMB :  
SMBv1  
SMBv2
```

106716 - Microsoft Windows SMB2 and SMB3 Dialects Supported (remote check)

Synopsis

It was possible to obtain information about the dialects of SMB2 and SMB3 available on the remote host.

Description

Nessus was able to obtain the set of SMB2 and SMB3 dialects running on the remote host by sending an authentication request to port 139 or 445.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2018/02/09, Modified: 2020/03/11

Plugin Output

tcp/445/cifs

```
The remote host supports the following SMB dialects :
_version_  _introduced in windows version_
2.0.2      Windows 2008
2.1        Windows 7
2.2.2      Windows 8 Beta
2.2.4      Windows 8 Beta
3.0        Windows 8
3.0.2      Windows 8.1
3.1        Windows 10
3.1.1      Windows 10
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/139/smb

```
Port 139/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/445/cifs

```
Port 445/tcp was found to be open
```

19506 - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2026/07/10

Plugin Output

tcp/0

Information about this scan :

```
Nessus version : 10.12.2
Nessus build : 20029
Plugin feed version : 202607231328
Scanner edition used : Nessus
Scanner OS : LINUX
Scanner distribution : ubuntu1604-x86-64
Scan type : Normal
Scan name : My Basic Network Scan
```


Scan policy used : Basic Network Scan
Scanner IP : 172.30.0.2
Port scanner(s) : nessus_syn_scanner
Port range : default
Ping RTT : 75.213 ms
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Assess component installs : yes
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 30
Max checks : 4
Recv timeout : 5
Backports : None
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2026/7/23 18:30 EDT (UTC -04:00)
Scan duration : 97 sec
Scan for malware : no
Fully Scan Operational Technology devices : no
Safely Scan Operational Technology devices with OT Discovery : no

209654 - OS Fingerprints Detected

Synopsis

Multiple OS fingerprints were detected.

Description

Using a combination of remote probes (TCP/IP, SMB, HTTP, NTP, SNMP, etc), it was possible to gather one or more fingerprints from the remote system. While the highest-confidence result was reported in plugin 11936, "OS Identification", the complete set of fingerprints detected are reported here.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/02/26, Modified: 2025/03/03

Plugin Output

tcp/0

Following OS Fingerprints were found

Remote operating system : Linux Kernel 6.x on Ubuntu
Confidence level : 56
Method : MLSinFP
Type : unknown
Fingerprint : unknown

Remote operating system : Linux Kernel 2.x
Confidence level : 54
Method : SinFP
Type : general-purpose
Fingerprint : SinFP:
P1:B10113:F0x12:W64240:00204ffff:M1460:
P2:B10113:F0x12:W65160:00204ffff0402080affffff444541440103030a:M1460:
P3:B00000:F0x00:W0:00:M0
P4:191802_7_p=139

11936 - OS Identification

Synopsis

It is possible to guess the remote operating system.

Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2003/12/09, Modified: 2025/06/03

Plugin Output

tcp/0

```
Remote operating system : Linux Kernel 6.x on Ubuntu  
Confidence level : 56  
Method : MLSinFP
```

```
The remote host is running Linux Kernel 6.x on Ubuntu
```

10860 - SMB Use Host SID to Enumerate Local Users

Synopsis

Nessus was able to enumerate local users.

Description

Using the host security identifier (SID), Nessus was able to enumerate local users on the remote Windows system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/02/13, Modified: 2023/02/28

Plugin Output

tcp/445/cifs

- nobody (id 501, Guest account)
- sambacry (id 1000)

Note that, in addition to the Administrator, Guest, and Kerberos accounts, Nessus has enumerated local users with IDs between 1000 and 1200. To use a different range, edit the scan policy and change the 'Enumerate Local Users: Start UID' and/or 'End UID' preferences under 'Assessment->Windows' and re-run the scan. Only UIDs between 1 and 2147483647 are allowed for this range.

104887 - Samba Version

Synopsis

It was possible to obtain the samba version from the remote operating system.

Description

Nessus was able to obtain the samba version from the remote operating by sending an authentication request to port 139 or 445. Note that this plugin requires SMB1 to be enabled on the host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2017/11/30, Modified: 2019/11/22

Plugin Output

tcp/445/cifs

```
The remote Samba Version is : Samba 4.5.9
```

96982 - Server Message Block (SMB) Protocol Version 1 Enabled (uncredentialed check)

Synopsis

The remote host supports the SMBv1 protocol.

Description

The remote host (Windows and/or Samba server) supports Server Message Block Protocol version 1 (SMBv1). Microsoft recommends that users discontinue the use of SMBv1 due to the lack of security features that were included in later SMB versions. Additionally, most security and compliance agencies recommend that users disable SMBv1 per SMB best practices.

See Also

<http://www.nessus.org/u?59bfc3ef>

<http://www.nessus.org/u?b9d9ebf9>

<http://www.nessus.org/u?8dcab5e4>

<http://www.nessus.org/u?234f8ef8>

<http://www.nessus.org/u?4c7e0cf3>

Solution

Disable SMBv1 according to the vendor instructions in Microsoft KB2696547. Additionally, block SMB directly by blocking TCP port 445 on all network boundary devices. For SMB over the NetBIOS API, block TCP ports 137 / 139 and UDP ports 137 / 138 on all network boundary devices.

Risk Factor

None

References

XREF IAVT:0001-T-0710

Plugin Information

Published: 2017/02/03, Modified: 2025/08/13

Plugin Output

tcp/445/cifs

The remote host supports SMBv1.

Synopsis

The remote service implements TCP timestamps.

Description

The remote host implements TCP timestamps, as defined by RFC1323. A side effect of this feature is that the uptime of the remote host can sometimes be computed.

See Also

<http://www.ietf.org/rfc/rfc1323.txt>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2023/10/17

Plugin Output

tcp/0

10287 - Traceroute Information

Synopsis

It was possible to obtain traceroute information.

Description

Makes a traceroute to the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/11/27, Modified: 2026/04/27

Plugin Output

udp/0

```
For your information, here is the traceroute from 172.30.0.2 to 172.30.4.1 :
172.30.0.2
172.30.4.1

Hop Count: 1
```


Synopsis

It was possible to obtain the network name of the remote host.

Description

The remote host is listening on UDP port 137 or TCP port 445, and replies to NetBIOS nbtscan or SMB requests.

Note that this plugin gathers information to be used in other plugins, but does not itself generate a report.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/10/12, Modified: 2021/02/10

Plugin Output

tcp/445/cifs

The following 2 NetBIOS names have been gathered :

HACKEDSAMBA	= Computer name
HACKEDSAMBA	= Workgroup / Domain name

172.30.6.3



Scan Information

Start time: Thu Jul 23 18:30:17 2026

End time: Thu Jul 23 18:37:11 2026

Host Information

IP: 172.30.6.3

MAC Address: B2:C9:E4:76:21:B9

OS: SuSE Linux

Vulnerabilities

11213 - HTTP TRACE / TRACK Methods Allowed

Synopsis

Debugging functions are enabled on the remote web server.

Description

The remote web server supports the TRACE and/or TRACK methods. TRACE and TRACK are HTTP methods that are used to debug web server connections.

See Also

<http://www.nessus.org/u?e979b5cb>

<http://www.apacheweek.com/issues/03-01-24>

<https://download.oracle.com/sunalerts/1000718.1.html>

Solution

Disable these HTTP methods. Refer to the plugin output for more information.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

References

BID	9506
BID	9561
BID	11604
BID	33374
BID	37995
CVE	CVE-2003-1567
CVE	CVE-2004-2320
CVE	CVE-2010-0386
XREF	CERT:288308
XREF	CERT:867593
XREF	CWE:16
XREF	CWE:200

Plugin Information

Published: 2003/01/23, Modified: 2024/04/09

Plugin Output

tcp/80/www

To disable these methods, add the following lines for each virtual host in your configuration file :

```
RewriteEngine on
RewriteCond %{REQUEST_METHOD} ^(TRACE|TRACK)
RewriteRule .* - [F]
```

Alternatively, note that Apache versions 1.3.34, 2.0.55, and 2.2 support disabling the TRACE method natively via the 'TraceEnable' directive.

```
Nessus sent the following TRACE request : \n\n----- snip
-----\nTRACE /Nessus944645023.html HTTP/1.1
Connection: Close
Host: apache-path-traversal.labvulnerabilities_vulnnet
Pragma: no-cache
User-Agent: Mozilla/4.0 (compatible; MSIE 8.0; Windows NT 5.1; Trident/4.0)
Accept: image/gif, image/x-xbitmap, image/jpeg, image/pjpeg, image/png, */*
Accept-Language: en
Accept-Charset: iso-8859-1,*,utf-8

----- snip -----\n\nand received the
following response from the remote server :\n\n----- snip
-----\nHTTP/1.1 200 OK
Date: Thu, 23 Jul 2026 22:31:09 GMT
Server: Apache/2.4.49 (Unix)
Keep-Alive: timeout=5, max=100
Connection: Keep-Alive
Transfer-Encoding: chunked
Content-Type: message/http

TRACE /Nessus944645023.html HTTP/1.1
Connection: Keep-Alive
Host: apache-path-traversal.labvulnerabilities_vulnnet
Pragma: no-cache
User-Agent: Mozilla/4.0 (compatible; MSIE 8.0; Windows NT 5.1; Trident/4.0)
Accept: image/gif, image/x-xbitmap, image/jpeg, image/pjpeg, image/png, */*
Accept-Language: en
Accept-Charset: iso-8859-1,*,utf-8

----- snip -----\n
```

50686 - IP Forwarding Enabled

Synopsis

The remote host has IP forwarding enabled.

Description

The remote host has IP forwarding enabled. An attacker can exploit this to route packets through the host and potentially bypass some firewalls / routers / NAC filtering.

Unless the remote host is a router, it is recommended that you disable IP forwarding.

Solution

On Linux, you can disable IP forwarding by doing :

```
echo 0 > /proc/sys/net/ipv4/ip_forward
```

On Windows, set the key 'IPEnableRouter' to 0 under

HKEY_LOCAL_MACHINE\System\CurrentControlSet\Services\Tcpip\Parameters

On Mac OS X, you can disable IP forwarding by executing the command :

```
sysctl -w net.inet.ip.forwarding=0
```

For other systems, check with your vendor.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:A/AC:L/PR:L/UI:N/S:C/C:L/I:L/A:L)

CVSS v2.0 Base Score

5.8 (CVSS2#AV:A/AC:L/Au:N/C:P/I:P/A:P)

References

CVE CVE-1999-0511

Plugin Information

Published: 2010/11/23, Modified: 2023/10/17

Plugin Output

tcp/0

IP forwarding appears to be enabled on the remote host.

Detected local MAC Address : e68cc3441691
Response from local MAC Address : e68cc3441691

Detected Gateway MAC Address : b2c9e47621b9
Response from Gateway MAC Address : b2c9e47621b9

10114 - ICMP Timestamp Request Remote Date Disclosure

Synopsis

It is possible to determine the exact time set on the remote host.

Description

The remote host answers to an ICMP timestamp request. This allows an attacker to know the date that is set on the targeted machine, which may assist an unauthenticated, remote attacker in defeating time-based authentication protocols.

Timestamps returned from machines running Windows Vista / 7 / 2008 / 2008 R2 are deliberately incorrect, but usually within 1000 seconds of the actual system time.

Solution

Filter out the ICMP timestamp requests (13), and the outgoing ICMP timestamp replies (14).

Risk Factor

Low

CVSS v2.0 Base Score

2.1 (CVSS2#AV:L/AC:L/Au:N/C:P/I:N/A:N)

References

CVE	CVE-1999-0524
XREF	CWE:200

Plugin Information

Published: 1999/08/01, Modified: 2024/10/07

Plugin Output

icmp/0

```
The remote clock is synchronized with the local clock.
```

48204 - Apache HTTP Server Version

Synopsis

It is possible to obtain the version number of the remote Apache HTTP server.

Description

The remote host is running the Apache HTTP Server, an open source web server. It was possible to read the version number from the banner.

See Also

<https://httpd.apache.org/>

Solution

n/a

Risk Factor

None

References

XREF	IAVT:0001-T-0030
XREF	IAVT:0001-T-0530

Plugin Information

Published: 2010/07/30, Modified: 2026/01/22

Plugin Output

tcp/80/www

```
URL      : http://172.30.6.3/
Version  : 2.4.49
Source   : Server: Apache/2.4.49 (Unix)
backported : 1
os       : Unix
```


39521 - Backported Security Patch Detection (WWW)

Synopsis

Security patches are backported.

Description

Security patches may have been 'backported' to the remote HTTP server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/06/25, Modified: 2026/01/22

Plugin Output

tcp/80/www

Give Nessus credentials to perform local checks.

45590 - Common Platform Enumeration (CPE)

Synopsis

It was possible to enumerate CPE names that matched on the remote system.

Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

See Also

<http://cpe.mitre.org/>

<https://nvd.nist.gov/products/cpe>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/04/21, Modified: 2026/06/16

Plugin Output

tcp/0

Following application CPE matched on the remote system :

cpe:/a:apache:http_server:2.4.49 -> Apache Software Foundation Apache HTTP Server

54615 - Device Type

Synopsis

It is possible to guess the remote device type.

Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/05/23, Modified: 2025/03/12

Plugin Output

tcp/0

Remote device type : unknown
Confidence level : 56

86420 - Ethernet MAC Addresses

Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/10/16, Modified: 2025/06/10

Plugin Output

tcp/0

The following is a consolidated list of detected MAC addresses:
- B2:C9:E4:76:21:B9

43111 - HTTP Methods Allowed (per directory)

Synopsis

This plugin determines which HTTP methods are allowed on various CGI directories.

Description

By calling the OPTIONS method, it is possible to determine which HTTP methods are allowed on each directory.

The following HTTP methods are considered insecure:

PUT, DELETE, CONNECT, TRACE, HEAD

Many frameworks and languages treat 'HEAD' as a 'GET' request, albeit one without any body in the response. If a security constraint was set on 'GET' requests such that only 'authenticatedUsers' could access GET requests for a particular servlet or resource, it would be bypassed for the 'HEAD' version. This allowed unauthorized blind submission of any privileged GET request.

As this list may be incomplete, the plugin also tests - if 'Thorough tests' are enabled or 'Enable web applications tests' is set to 'yes'

in the scan policy - various known HTTP methods on each directory and considers them as unsupported if it receives a response code of 400, 403, 405, or 501.

Note that the plugin output is only informational and does not necessarily indicate the presence of any security vulnerabilities.

See Also

<http://www.nessus.org/u?d9c03a9a>

<http://www.nessus.org/u?b019cbdb>

[https://www.owasp.org/index.php/Test_HTTP_Methods_\(OTG-CONFIG-006\)](https://www.owasp.org/index.php/Test_HTTP_Methods_(OTG-CONFIG-006))

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/12/10, Modified: 2022/04/11

Plugin Output

tcp/80/www

Based on the response to an OPTIONS request :

- HTTP methods GET HEAD OPTIONS POST TRACE are allowed on :

/

10107 - HTTP Server Type and Version

Synopsis

A web server is running on the remote host.

Description

This plugin attempts to determine the type and the version of the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0931

Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

Plugin Output

tcp/80/www

```
The remote web server type is :  
Apache/2.4.49 (Unix)
```

12053 - Host Fully Qualified Domain Name (FQDN) Resolution

Synopsis

It was possible to resolve the name of the remote host.

Description

Nessus was able to resolve the fully qualified domain name (FQDN) of the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/02/11, Modified: 2025/03/13

Plugin Output

tcp/0

```
172.30.6.3 resolves as apache-path-traversal.labvulnerabilities_vulnnet.
```


24260 - HyperText Transfer Protocol (HTTP) Information

Synopsis

Some information about the remote HTTP configuration can be extracted.

Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

Plugin Output

tcp/80/www

Response Code : HTTP/1.1 200 OK

Protocol version : HTTP/1.1

HTTP/2 TLS Support: No

HTTP/2 Cleartext Support: No

SSL : no

Keep-Alive : yes

Options allowed : (Not implemented)

Headers :

Date: Thu, 23 Jul 2026 22:31:11 GMT

Server: Apache/2.4.49 (Unix)

Last-Modified: Mon, 11 Jun 2007 18:53:14 GMT

ETag: "2d-432a5e4a73a80"

Accept-Ranges: bytes

Content-Length: 45

Keep-Alive: timeout=5, max=98

Connection: Keep-Alive

Content-Type: text/html

Response Body :

<html><body><h1>It works!</h1></body></html>

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/80/www

```
Port 80/tcp was found to be open
```

19506 - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2026/07/10

Plugin Output

tcp/0

Information about this scan :

```
Nessus version : 10.12.2
Nessus build : 20029
Plugin feed version : 202607231328
Scanner edition used : Nessus
Scanner OS : LINUX
Scanner distribution : ubuntu1604-x86-64
Scan type : Normal
Scan name : My Basic Network Scan
```

```
Scan policy used : Basic Network Scan
Scanner IP : 172.30.0.2
Port scanner(s) : nessus_syn_scanner
Port range : default
Ping RTT : 70.749 ms
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Assess component installs : yes
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 30
Max checks : 4
Recv timeout : 5
Backports : Detected
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2026/7/23 18:30 EDT (UTC -04:00)
Scan duration : 410 sec
Scan for malware : no
Fully Scan Operational Technology devices : no
Safely Scan Operational Technology devices with OT Discovery : no
```

209654 - OS Fingerprints Detected

Synopsis

Multiple OS fingerprints were detected.

Description

Using a combination of remote probes (TCP/IP, SMB, HTTP, NTP, SNMP, etc), it was possible to gather one or more fingerprints from the remote system. While the highest-confidence result was reported in plugin 11936, "OS Identification", the complete set of fingerprints detected are reported here.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/02/26, Modified: 2025/03/03

Plugin Output

tcp/0

Following OS Fingerprints were found

Remote operating system : SuSE Linux
Confidence level : 56
Method : MLSinFP
Type : unknown
Fingerprint : unknown

Remote operating system : Linux Kernel 2.x
Confidence level : 54
Method : SinFP
Type : general-purpose
Fingerprint : SinFP:

P1:B10113:F0x12:W64240:00204ffff:M1460:
P2:B10113:F0x12:W65160:00204ffff0402080affffffff444541440103030a:M1460:
P3:B00000:F0x00:W0:00:M0
P4:191802_7_p=80

Following fingerprints could not be used to determine OS :
HTTP:!:Server: Apache/2.4.49 (Unix)

11936 - OS Identification

Synopsis

It is possible to guess the remote operating system.

Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2003/12/09, Modified: 2025/06/03

Plugin Output

tcp/0

```
Remote operating system : SuSE Linux
Confidence level : 56
Method : MLSinFP
```

```
The remote host is running SuSE Linux
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/80/www

```
A web server is running on this port.
```

Synopsis

The remote service implements TCP timestamps.

Description

The remote host implements TCP timestamps, as defined by RFC1323. A side effect of this feature is that the uptime of the remote host can sometimes be computed.

See Also

<http://www.ietf.org/rfc/rfc1323.txt>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2023/10/17

Plugin Output

tcp/0

10287 - Traceroute Information

Synopsis

It was possible to obtain traceroute information.

Description

Makes a traceroute to the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/11/27, Modified: 2026/04/27

Plugin Output

udp/0

```
For your information, here is the traceroute from 172.30.0.2 to 172.30.6.3 :  
172.30.0.2  
172.30.6.3  
  
Hop Count: 1
```

172.30.7.1



Scan Information

Start time: Thu Jul 23 18:30:17 2026

End time: Thu Jul 23 18:43:32 2026

Host Information

IP: 172.30.7.1

MAC Address: 3E:FE:E1:EB:E4:21

OS: Linux Kernel 2.x on CentOS release

Vulnerabilities

50686 - IP Forwarding Enabled

Synopsis

The remote host has IP forwarding enabled.

Description

The remote host has IP forwarding enabled. An attacker can exploit this to route packets through the host and potentially bypass some firewalls / routers / NAC filtering.

Unless the remote host is a router, it is recommended that you disable IP forwarding.

Solution

On Linux, you can disable IP forwarding by doing :

```
echo 0 > /proc/sys/net/ipv4/ip_forward
```

On Windows, set the key 'IPEnableRouter' to 0 under

HKEY_LOCAL_MACHINE\System\CurrentControlSet\Services\Tcpip\Parameters

On Mac OS X, you can disable IP forwarding by executing the command :

```
sysctl -w net.inet.ip.forwarding=0
```

For other systems, check with your vendor.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:A/AC:L/PR:L/UI:N/S:C/C:L/I:L/A:L)

CVSS v2.0 Base Score

5.8 (CVSS2#AV:A/AC:L/Au:N/C:P/I:P/A:P)

References

CVE CVE-1999-0511

Plugin Information

Published: 2010/11/23, Modified: 2023/10/17

Plugin Output

tcp/0

```
IP forwarding appears to be enabled on the remote host.
```

```
Detected local MAC Address      : e68cc3441691
Response from local MAC Address  : e68cc3441691
```

```
Detected Gateway MAC Address    : 3efee1ebe421
Response from Gateway MAC Address : 3efee1ebe421
```

10114 - ICMP Timestamp Request Remote Date Disclosure

Synopsis

It is possible to determine the exact time set on the remote host.

Description

The remote host answers to an ICMP timestamp request. This allows an attacker to know the date that is set on the targeted machine, which may assist an unauthenticated, remote attacker in defeating time-based authentication protocols.

Timestamps returned from machines running Windows Vista / 7 / 2008 / 2008 R2 are deliberately incorrect, but usually within 1000 seconds of the actual system time.

Solution

Filter out the ICMP timestamp requests (13), and the outgoing ICMP timestamp replies (14).

Risk Factor

Low

CVSS v2.0 Base Score

2.1 (CVSS2#AV:L/AC:L/Au:N/C:P/I:N/A:N)

References

CVE	CVE-1999-0524
XREF	CWE:200

Plugin Information

Published: 1999/08/01, Modified: 2024/10/07

Plugin Output

icmp/0

```
The remote clock is synchronized with the local clock.
```

45590 - Common Platform Enumeration (CPE)

Synopsis

It was possible to enumerate CPE names that matched on the remote system.

Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

See Also

<http://cpe.mitre.org/>

<https://nvd.nist.gov/products/cpe>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/04/21, Modified: 2026/06/16

Plugin Output

tcp/0

The remote operating system matched the following CPE :

cpe:/o:centos:centos -> CentOS

54615 - Device Type

Synopsis

It is possible to guess the remote device type.

Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/05/23, Modified: 2025/03/12

Plugin Output

tcp/0

Remote device type : unknown
Confidence level : 56

86420 - Ethernet MAC Addresses

Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/10/16, Modified: 2025/06/10

Plugin Output

tcp/0

The following is a consolidated list of detected MAC addresses:
- 3E:FE:E1:EB:E4:21

12053 - Host Fully Qualified Domain Name (FQDN) Resolution

Synopsis

It was possible to resolve the name of the remote host.

Description

Nessus was able to resolve the fully qualified domain name (FQDN) of the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/02/11, Modified: 2025/03/13

Plugin Output

tcp/0

```
172.30.7.1 resolves as juice-shop.labvulnerabilities_vulnnet.
```


Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/3000/www

```
Port 3000/tcp was found to be open
```

19506 - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2026/07/10

Plugin Output

tcp/0

Information about this scan :

```
Nessus version : 10.12.2
Nessus build : 20029
Plugin feed version : 202607231328
Scanner edition used : Nessus
Scanner OS : LINUX
Scanner distribution : ubuntu1604-x86-64
Scan type : Normal
Scan name : My Basic Network Scan
```

Scan policy used : Basic Network Scan
Scanner IP : 172.30.0.2
Port scanner(s) : nessus_syn_scanner
Port range : default
Ping RTT : 71.570 ms
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Assess component installs : yes
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 30
Max checks : 4
Recv timeout : 5
Backports : None
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2026/7/23 18:30 EDT (UTC -04:00)
Scan duration : 788 sec
Scan for malware : no
Fully Scan Operational Technology devices : no
Safely Scan Operational Technology devices with OT Discovery : no

209654 - OS Fingerprints Detected

Synopsis

Multiple OS fingerprints were detected.

Description

Using a combination of remote probes (TCP/IP, SMB, HTTP, NTP, SNMP, etc), it was possible to gather one or more fingerprints from the remote system. While the highest-confidence result was reported in plugin 11936, "OS Identification", the complete set of fingerprints detected are reported here.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/02/26, Modified: 2025/03/03

Plugin Output

tcp/0

Following OS Fingerprints were found

Remote operating system : Linux Kernel 2.x on CentOS release
Confidence level : 56
Method : MLSinFP
Type : unknown
Fingerprint : unknown

Remote operating system : Linux Kernel 2.x
Confidence level : 54
Method : SinFP
Type : general-purpose
Fingerprint : SinFP:
P1:B10113:F0x12:W64240:00204ffff:M1460:
P2:B10113:F0x12:W65160:00204ffff0402080affffff444541440103030a:M1460:
P3:B10120:F0x04:W0:00:M0
P4:191802_7_p=3000

11936 - OS Identification

Synopsis

It is possible to guess the remote operating system.

Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2003/12/09, Modified: 2025/06/03

Plugin Output

tcp/0

```
Remote operating system : Linux Kernel 2.x on CentOS release
Confidence level : 56
Method : MLSinFP
```

```
The remote host is running Linux Kernel 2.x on CentOS release
```

10919 - Open Port Re-check

Synopsis

Previously open ports are now closed.

Description

One of several ports that were previously open are now closed or unresponsive.

There are several possible reasons for this :

- The scan may have caused a service to freeze or stop running.
- An administrator may have stopped a particular service during the scanning process.

This might be an availability problem related to the following :

- A network outage has been experienced during the scan, and the remote network cannot be reached anymore by the scanner.
- This scanner may have been blacklisted by the system administrator or by an automatic intrusion detection / prevention system that detected the scan.
- The remote host is now down, either because a user turned it off during the scan or because a select denial of service was effective.

In any case, the audit of the remote host might be incomplete and may need to be done again.

Solution

Steps to resolve this issue include :

- Increase checks_read_timeout and/or reduce max_checks.
- Disable any IPS during the Nessus scan

Risk Factor

None

References

XREF IAVB:0001-B-0509

Plugin Information

Published: 2002/03/19, Modified: 2023/06/20

Plugin Output

tcp/0

Port 3000 was detected as being open but is now closed

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/3000/www

```
A web server is running on this port.
```


10386 - Web Server No 404 Error Code Check

Synopsis

The remote web server does not return 404 error codes.

Description

The remote web server is configured such that it does not return '404 Not Found' error codes when a nonexistent file is requested, perhaps returning instead a site map, search page or authentication page.

Nessus has enabled some counter measures for this. However, they might be insufficient. If a great number of security holes are produced for this port, they might not all be accurate.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2000/04/28, Modified: 2022/06/17

Plugin Output

tcp/3000/www

The following string will be used :
404

10302 - Web Server robots.txt Information Disclosure

Synopsis

The remote web server contains a 'robots.txt' file.

Description

The remote host contains a file named 'robots.txt' that is intended to prevent web 'robots' from visiting certain directories in a website for maintenance or indexing purposes. A malicious user may also be able to use the contents of this file to learn of sensitive documents or directories on the affected site and either retrieve them directly or target them for other attacks.

See Also

<http://www.robotstxt.org/orig.html>

Solution

Review the contents of the site's robots.txt file, use Robots META tags instead of entries in the robots.txt file, and/or adjust the web server's access controls to limit access to sensitive material.

Risk Factor

None

Plugin Information

Published: 1999/10/12, Modified: 2026/03/10

Plugin Output

tcp/3000/www

```
Contents of robots.txt :
```

```
User-agent: *  
Disallow: /ftp
```

172.30.9.1



Scan Information

Start time: Thu Jul 23 18:30:17 2026

End time: Thu Jul 23 18:37:10 2026

Host Information

IP: 172.30.9.1

MAC Address: 8E:4F:21:9A:DD:B6

OS: SuSE Linux

Vulnerabilities

50686 - IP Forwarding Enabled

Synopsis

The remote host has IP forwarding enabled.

Description

The remote host has IP forwarding enabled. An attacker can exploit this to route packets through the host and potentially bypass some firewalls / routers / NAC filtering.

Unless the remote host is a router, it is recommended that you disable IP forwarding.

Solution

On Linux, you can disable IP forwarding by doing :

```
echo 0 > /proc/sys/net/ipv4/ip_forward
```

On Windows, set the key 'IPEnableRouter' to 0 under

HKEY_LOCAL_MACHINE\System\CurrentControlSet\Services\Tcpip\Parameters

On Mac OS X, you can disable IP forwarding by executing the command :

```
sysctl -w net.inet.ip.forwarding=0
```

For other systems, check with your vendor.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:A/AC:L/PR:L/UI:N/S:C/C:L/I:L/A:L)

CVSS v2.0 Base Score

5.8 (CVSS2#AV:A/AC:L/Au:N/C:P/I:P/A:P)

References

CVE CVE-1999-0511

Plugin Information

Published: 2010/11/23, Modified: 2023/10/17

Plugin Output

tcp/0

```
IP forwarding appears to be enabled on the remote host.
```

```
Detected local MAC Address      : e68cc3441691
Response from local MAC Address  : e68cc3441691
```

```
Detected Gateway MAC Address    : 8e4f219addb6
Response from Gateway MAC Address : 8e4f219addb6
```

10114 - ICMP Timestamp Request Remote Date Disclosure

Synopsis

It is possible to determine the exact time set on the remote host.

Description

The remote host answers to an ICMP timestamp request. This allows an attacker to know the date that is set on the targeted machine, which may assist an unauthenticated, remote attacker in defeating time-based authentication protocols.

Timestamps returned from machines running Windows Vista / 7 / 2008 / 2008 R2 are deliberately incorrect, but usually within 1000 seconds of the actual system time.

Solution

Filter out the ICMP timestamp requests (13), and the outgoing ICMP timestamp replies (14).

Risk Factor

Low

CVSS v2.0 Base Score

2.1 (CVSS2#AV:L/AC:L/Au:N/C:P/I:N/A:N)

References

CVE	CVE-1999-0524
XREF	CWE:200

Plugin Information

Published: 1999/08/01, Modified: 2024/10/07

Plugin Output

icmp/0

```
The remote clock is synchronized with the local clock.
```

48204 - Apache HTTP Server Version

Synopsis

It is possible to obtain the version number of the remote Apache HTTP server.

Description

The remote host is running the Apache HTTP Server, an open source web server. It was possible to read the version number from the banner.

See Also

<https://httpd.apache.org/>

Solution

n/a

Risk Factor

None

References

XREF	IAVT:0001-T-0030
XREF	IAVT:0001-T-0530

Plugin Information

Published: 2010/07/30, Modified: 2026/01/22

Plugin Output

tcp/80/www

```
URL      : http://172.30.9.1/
Version  : 2.4.25
Source   : Server: Apache/2.4.25 (Debian)
backported : 1
os       : Debian
```

39521 - Backported Security Patch Detection (WWW)

Synopsis

Security patches are backported.

Description

Security patches may have been 'backported' to the remote HTTP server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/06/25, Modified: 2026/01/22

Plugin Output

tcp/80/www

Give Nessus credentials to perform local checks.

45590 - Common Platform Enumeration (CPE)

Synopsis

It was possible to enumerate CPE names that matched on the remote system.

Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

See Also

<http://cpe.mitre.org/>

<https://nvd.nist.gov/products/cpe>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/04/21, Modified: 2026/06/16

Plugin Output

tcp/0

Following application CPE matched on the remote system :

cpe:/a:apache:http_server:2.4.25 -> Apache Software Foundation Apache HTTP Server

54615 - Device Type

Synopsis

It is possible to guess the remote device type.

Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/05/23, Modified: 2025/03/12

Plugin Output

tcp/0

Remote device type : unknown
Confidence level : 56

86420 - Ethernet MAC Addresses

Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/10/16, Modified: 2025/06/10

Plugin Output

tcp/0

The following is a consolidated list of detected MAC addresses:
- 8E:4F:21:9A:DD:B6

10107 - HTTP Server Type and Version

Synopsis

A web server is running on the remote host.

Description

This plugin attempts to determine the type and the version of the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0931

Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

Plugin Output

tcp/80/www

```
The remote web server type is :  
Apache/2.4.25 (Debian)
```

12053 - Host Fully Qualified Domain Name (FQDN) Resolution

Synopsis

It was possible to resolve the name of the remote host.

Description

Nessus was able to resolve the fully qualified domain name (FQDN) of the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/02/11, Modified: 2025/03/13

Plugin Output

tcp/0

```
172.30.9.1 resolves as dwwa.labvulnerabilities_vulnnet.
```

24260 - HyperText Transfer Protocol (HTTP) Information

Synopsis

Some information about the remote HTTP configuration can be extracted.

Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

Plugin Output

tcp/80/www

Response Code : HTTP/1.1 302 Found

Protocol version : HTTP/1.1

HTTP/2 TLS Support: No

HTTP/2 Cleartext Support: No

SSL : no

Keep-Alive : yes

Options allowed : (Not implemented)

Headers :

Date: Thu, 23 Jul 2026 22:31:11 GMT

Server: Apache/2.4.25 (Debian)

Expires: Thu, 19 Nov 1981 08:52:00 GMT

Cache-Control: no-store, no-cache, must-revalidate

Pragma: no-cache

Location: login.php

Content-Length: 0

Keep-Alive: timeout=5, max=98

Connection: Keep-Alive

Content-Type: text/html; charset=UTF-8

Response Body :

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/80/www

```
Port 80/tcp was found to be open
```

19506 - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2026/07/10

Plugin Output

tcp/0

Information about this scan :

```
Nessus version : 10.12.2
Nessus build : 20029
Plugin feed version : 202607231328
Scanner edition used : Nessus
Scanner OS : LINUX
Scanner distribution : ubuntu1604-x86-64
Scan type : Normal
Scan name : My Basic Network Scan
```

Scan policy used : Basic Network Scan
Scanner IP : 172.30.0.2
Port scanner(s) : nessus_syn_scanner
Port range : default
Ping RTT : 66.146 ms
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Assess component installs : yes
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 30
Max checks : 4
Recv timeout : 5
Backports : Detected
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2026/7/23 18:30 EDT (UTC -04:00)
Scan duration : 409 sec
Scan for malware : no
Fully Scan Operational Technology devices : no
Safely Scan Operational Technology devices with OT Discovery : no

209654 - OS Fingerprints Detected

Synopsis

Multiple OS fingerprints were detected.

Description

Using a combination of remote probes (TCP/IP, SMB, HTTP, NTP, SNMP, etc), it was possible to gather one or more fingerprints from the remote system. While the highest-confidence result was reported in plugin 11936, "OS Identification", the complete set of fingerprints detected are reported here.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/02/26, Modified: 2025/03/03

Plugin Output

tcp/0

Following OS Fingerprints were found

Remote operating system : SuSE Linux
Confidence level : 56
Method : MLSinFP
Type : unknown
Fingerprint : unknown

Remote operating system : Linux Kernel 2.x
Confidence level : 54
Method : SinFP
Type : general-purpose
Fingerprint : SinFP:

P1:B10113:F0x12:W64240:00204ffff:M1460:
P2:B10113:F0x12:W65160:00204ffff0402080affffff444541440103030a:M1460:
P3:B00000:F0x00:W0:00:M0
P4:191802_7_p=80

Following fingerprints could not be used to determine OS :
HTTP:!:Server: Apache/2.4.25 (Debian)

11936 - OS Identification

Synopsis

It is possible to guess the remote operating system.

Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2003/12/09, Modified: 2025/06/03

Plugin Output

tcp/0

```
Remote operating system : SuSE Linux
Confidence level : 56
Method : MLSinFP
```

```
The remote host is running SuSE Linux
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/80/www

```
A web server is running on this port.
```

25220 - TCP/IP Timestamps Supported

Synopsis

The remote service implements TCP timestamps.

Description

The remote host implements TCP timestamps, as defined by RFC1323. A side effect of this feature is that the uptime of the remote host can sometimes be computed.

See Also

<http://www.ietf.org/rfc/rfc1323.txt>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2023/10/17

Plugin Output

tcp/0

10287 - Traceroute Information

Synopsis

It was possible to obtain traceroute information.

Description

Makes a traceroute to the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/11/27, Modified: 2026/04/27

Plugin Output

udp/0

```
For your information, here is the traceroute from 172.30.0.2 to 172.30.9.1 :
172.30.0.2
172.30.9.1

Hop Count: 1
```

10302 - Web Server robots.txt Information Disclosure

Synopsis

The remote web server contains a 'robots.txt' file.

Description

The remote host contains a file named 'robots.txt' that is intended to prevent web 'robots' from visiting certain directories in a website for maintenance or indexing purposes. A malicious user may also be able to use the contents of this file to learn of sensitive documents or directories on the affected site and either retrieve them directly or target them for other attacks.

See Also

<http://www.robotstxt.org/orig.html>

Solution

Review the contents of the site's robots.txt file, use Robots META tags instead of entries in the robots.txt file, and/or adjust the web server's access controls to limit access to sensitive material.

Risk Factor

None

Plugin Information

Published: 1999/10/12, Modified: 2026/03/10

Plugin Output

tcp/80/www

```
Contents of robots.txt :
```

```
User-agent: *  
Disallow: /
```

172.30.9.2



Scan Information

Start time: Thu Jul 23 18:30:17 2026

End time: Thu Jul 23 18:37:12 2026

Host Information

IP: 172.30.9.2

MAC Address: 46:08:63:9D:C7:09

OS: Linux Kernel 3.13 on Ubuntu 14.04 (trusty)

Vulnerabilities

201408 - Canonical Ubuntu Linux SEoL (14.04.x)

Synopsis

An unsupported version of Canonical Ubuntu Linux is installed on the remote host.

Description

According to its version, Canonical Ubuntu Linux is 14.04.x. It is, therefore, no longer maintained by its vendor or provider.

Lack of support implies that no new security patches for the product will be released by the vendor. As a result, it may contain security vulnerabilities.

See Also

<http://www.nessus.org/u?5afc4199>

Solution

Upgrade to a version of Canonical Ubuntu Linux that is currently supported.

Risk Factor

Critical

CVSS v3.0 Base Score

10.0 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H)

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

Plugin Information

Published: 2024/07/03, Modified: 2025/03/26

Plugin Output

tcp/80/www

```
OS : Ubuntu Linux 14.04
Security End of Life : April 25, 2019
Time since Security End of Life (Est.) : >= 7 years
```


50686 - IP Forwarding Enabled

Synopsis

The remote host has IP forwarding enabled.

Description

The remote host has IP forwarding enabled. An attacker can exploit this to route packets through the host and potentially bypass some firewalls / routers / NAC filtering.

Unless the remote host is a router, it is recommended that you disable IP forwarding.

Solution

On Linux, you can disable IP forwarding by doing :

```
echo 0 > /proc/sys/net/ipv4/ip_forward
```

On Windows, set the key 'IPEnableRouter' to 0 under

HKEY_LOCAL_MACHINE\System\CurrentControlSet\Services\Tcpip\Parameters

On Mac OS X, you can disable IP forwarding by executing the command :

```
sysctl -w net.inet.ip.forwarding=0
```

For other systems, check with your vendor.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:A/AC:L/PR:L/UI:N/S:C/C:L/I:L/A:L)

CVSS v2.0 Base Score

5.8 (CVSS2#AV:A/AC:L/Au:N/C:P/I:P/A:P)

References

CVE CVE-1999-0511

Plugin Information

Published: 2010/11/23, Modified: 2023/10/17

Plugin Output

tcp/0

IP forwarding appears to be enabled on the remote host.

Detected local MAC Address : e68cc3441691
Response from local MAC Address : e68cc3441691

Detected Gateway MAC Address : 4608639dc709
Response from Gateway MAC Address : 4608639dc709

121479 - web.config File Information Disclosure

Synopsis

The remote web server hosts an application that is affected by an information disclosure vulnerability.

Description

An information disclosure vulnerability exists in the remote web server due to the disclosure of the web.config file. An unauthenticated, remote attacker can exploit this, via a simple GET request, to disclose potentially sensitive configuration information.

Solution

Ensure proper restrictions are in place, or remove the web.config file if the file is not required.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2019/01/30, Modified: 2020/04/27

Plugin Output

tcp/80/www

Nessus was able to exploit the issue using the following request :

```
GET /web.config HTTP/1.1
Host: 172.30.9.2
Accept-Charset: iso-8859-1,utf-8;q=0.9,*;q=0.1
Accept-Language: en
Connection: Keep-Alive
User-Agent: Mozilla/4.0 (compatible; MSIE 8.0; Windows NT 5.1; Trident/4.0)
Pragma: no-cache
Accept: image/gif, image/x-xbitmap, image/jpeg, image/pjpeg, image/png, */*
```

This produced the following truncated output (limited to 5 lines) :

```
----- snip -----
<?xml version="1.0"?>
<configuration>
```

```
<configSections>
  <sectionGroup name="system.web.extensions"
    type="System.Web.Configuration.SystemWebExtensionsSectionGroup, System.Web.Extensions,
    Version=3.5.0.0, Culture=neutral, PublicKeyToken=31BF3856AD364E35">
  <sectionGroup name="scripting" type="System.Web.Configuration.ScriptingSectionGroup,
    System.Web.Extensions, Version=3.5.0.0, Culture=neutral, PublicKeyToken=31BF3856AD364E35">
  [...]

----- snip -----
```

10114 - ICMP Timestamp Request Remote Date Disclosure

Synopsis

It is possible to determine the exact time set on the remote host.

Description

The remote host answers to an ICMP timestamp request. This allows an attacker to know the date that is set on the targeted machine, which may assist an unauthenticated, remote attacker in defeating time-based authentication protocols.

Timestamps returned from machines running Windows Vista / 7 / 2008 / 2008 R2 are deliberately incorrect, but usually within 1000 seconds of the actual system time.

Solution

Filter out the ICMP timestamp requests (13), and the outgoing ICMP timestamp replies (14).

Risk Factor

Low

CVSS v2.0 Base Score

2.1 (CVSS2#AV:L/AC:L/Au:N/C:P/I:N/A:N)

References

CVE	CVE-1999-0524
XREF	CWE:200

Plugin Information

Published: 1999/08/01, Modified: 2024/10/07

Plugin Output

icmp/0

```
The remote clock is synchronized with the local clock.
```

18261 - Apache Banner Linux Distribution Disclosure

Synopsis

The name of the Linux distribution running on the remote host was found in the banner of the web server.

Description

Nessus was able to extract the banner of the Apache web server and determine which Linux distribution the remote host is running.

Solution

If you do not wish to display this information, edit 'httpd.conf' and set the directive 'ServerTokens Prod' and restart Apache.

Risk Factor

None

Plugin Information

Published: 2005/05/15, Modified: 2025/03/31

Plugin Output

tcp/0

```
The Linux distribution detected was :  
- Ubuntu 14.04 (trusty)
```

48204 - Apache HTTP Server Version

Synopsis

It is possible to obtain the version number of the remote Apache HTTP server.

Description

The remote host is running the Apache HTTP Server, an open source web server. It was possible to read the version number from the banner.

See Also

<https://httpd.apache.org/>

Solution

n/a

Risk Factor

None

References

XREF	IAVT:0001-T-0030
XREF	IAVT:0001-T-0530

Plugin Information

Published: 2010/07/30, Modified: 2026/01/22

Plugin Output

tcp/80/www

```
URL      : http://172.30.9.2/
Version  : 2.4.7
Source   : Server: Apache/2.4.7 (Ubuntu)
backported : 1
os       : Ubuntu
```

84574 - Backported Security Patch Detection (PHP)

Synopsis

Security patches have been backported.

Description

Security patches may have been 'backported' to the remote PHP install without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/07/07, Modified: 2024/11/22

Plugin Output

tcp/80/www

Give Nessus credentials to perform local checks.

39521 - Backported Security Patch Detection (WWW)

Synopsis

Security patches are backported.

Description

Security patches may have been 'backported' to the remote HTTP server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/06/25, Modified: 2026/01/22

Plugin Output

tcp/80/www

Give Nessus credentials to perform local checks.

45590 - Common Platform Enumeration (CPE)

Synopsis

It was possible to enumerate CPE names that matched on the remote system.

Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

See Also

<http://cpe.mitre.org/>

<https://nvd.nist.gov/products/cpe>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/04/21, Modified: 2026/06/16

Plugin Output

tcp/0

Following application CPE's matched on the remote system :

```
cpe:/a:apache:http_server:2.4.7 -> Apache Software Foundation Apache HTTP Server
cpe:/a:mysql:mysql -> MySQL MySQL
cpe:/a:php:php:5.5.9 -> PHP PHP
cpe:/a:php:php:5.5.9-1ubuntu4.14 -> PHP PHP
```

54615 - Device Type

Synopsis

It is possible to guess the remote device type.

Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/05/23, Modified: 2025/03/12

Plugin Output

tcp/0

```
Remote device type : general-purpose  
Confidence level : 95
```

86420 - Ethernet MAC Addresses

Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/10/16, Modified: 2025/06/10

Plugin Output

tcp/0

The following is a consolidated list of detected MAC addresses:
- 46:08:63:9D:C7:09

10107 - HTTP Server Type and Version

Synopsis

A web server is running on the remote host.

Description

This plugin attempts to determine the type and the version of the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0931

Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

Plugin Output

tcp/80/www

```
The remote web server type is :  
Apache/2.4.7 (Ubuntu)
```

12053 - Host Fully Qualified Domain Name (FQDN) Resolution

Synopsis

It was possible to resolve the name of the remote host.

Description

Nessus was able to resolve the fully qualified domain name (FQDN) of the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/02/11, Modified: 2025/03/13

Plugin Output

tcp/0

```
172.30.9.2 resolves as bwapp.labvulnerabilities_vulnnet.
```

24260 - HyperText Transfer Protocol (HTTP) Information

Synopsis

Some information about the remote HTTP configuration can be extracted.

Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

Plugin Output

tcp/80/www

Response Code : HTTP/1.1 302 Found

Protocol version : HTTP/1.1

HTTP/2 TLS Support: No

HTTP/2 Cleartext Support: No

SSL : no

Keep-Alive : yes

Options allowed : (Not implemented)

Headers :

Date: Thu, 23 Jul 2026 22:31:14 GMT

Server: Apache/2.4.7 (Ubuntu)

X-Powered-By: PHP/5.5.9-1ubuntu4.14

Location: portal.php

Content-Length: 0

Keep-Alive: timeout=5, max=98

Connection: Keep-Alive

Content-Type: text/html

Response Body :

10719 - MySQL Server Detection

Synopsis

A database server is listening on the remote port.

Description

The remote host is running MySQL, an open source database server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0802

Plugin Information

Published: 2001/08/13, Modified: 2025/09/24

Plugin Output

tcp/3306/mysql

```
Service : mysql
Version : unknown
```


Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/80/www

```
Port 80/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/3306/mysql

```
Port 3306/tcp was found to be open
```

19506 - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2026/07/10

Plugin Output

tcp/0

Information about this scan :

```
Nessus version : 10.12.2
Nessus build : 20029
Plugin feed version : 202607231328
Scanner edition used : Nessus
Scanner OS : LINUX
Scanner distribution : ubuntu1604-x86-64
Scan type : Normal
Scan name : My Basic Network Scan
```

Scan policy used : Basic Network Scan
Scanner IP : 172.30.0.2
Port scanner(s) : nessus_syn_scanner
Port range : default
Ping RTT : 70.329 ms
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Assess component installs : yes
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 30
Max checks : 4
Recv timeout : 5
Backports : Detected
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2026/7/23 18:30 EDT (UTC -04:00)
Scan duration : 411 sec
Scan for malware : no
Fully Scan Operational Technology devices : no
Safely Scan Operational Technology devices with OT Discovery : no

209654 - OS Fingerprints Detected

Synopsis

Multiple OS fingerprints were detected.

Description

Using a combination of remote probes (TCP/IP, SMB, HTTP, NTP, SNMP, etc), it was possible to gather one or more fingerprints from the remote system. While the highest-confidence result was reported in plugin 11936, "OS Identification", the complete set of fingerprints detected are reported here.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/02/26, Modified: 2025/03/03

Plugin Output

tcp/0

Following OS Fingerprints were found

Remote operating system : SuSE Linux
Confidence level : 56
Method : MLSinFP
Type : unknown
Fingerprint : unknown

Remote operating system : Linux Kernel 3.13 on Ubuntu 14.04 (trusty)
Confidence level : 95
Method : HTTP
Type : general-purpose
Fingerprint : unknown

Remote operating system : Linux Kernel 2.x
Confidence level : 54
Method : SinFP
Type : general-purpose
Fingerprint : SinFP:

P1:B10113:F0x12:W64240:00204ffff:M1460:
P2:B10113:F0x12:W65160:00204ffff0402080affffff444541440103030a:M1460:
P3:B00000:F0x00:W0:00:M0
P4:191802_7_p=80

11936 - OS Identification

Synopsis

It is possible to guess the remote operating system.

Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2003/12/09, Modified: 2025/06/03

Plugin Output

tcp/0

```
Remote operating system : Linux Kernel 3.13 on Ubuntu 14.04 (trusty)
Confidence level : 95
Method : HTTP
```

```
The remote host is running Linux Kernel 3.13 on Ubuntu 14.04 (trusty)
```

48243 - PHP Version Detection

Synopsis

It was possible to obtain the version number of the remote PHP installation.

Description

Nessus was able to determine the version of PHP available on the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0936

Plugin Information

Published: 2010/08/04, Modified: 2026/01/22

Plugin Output

tcp/80/www

Nessus was able to identify the following PHP version information :

```
Version : 5.5.9-1ubuntu4.14
Source  : X-Powered-By: PHP/5.5.9-1ubuntu4.14
Backported : 1
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/80/www

```
A web server is running on this port.
```


22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/3306/mysql

```
A MySQL server is running on this port.
```

25220 - TCP/IP Timestamps Supported

Synopsis

The remote service implements TCP timestamps.

Description

The remote host implements TCP timestamps, as defined by RFC1323. A side effect of this feature is that the uptime of the remote host can sometimes be computed.

See Also

<http://www.ietf.org/rfc/rfc1323.txt>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2023/10/17

Plugin Output

tcp/0

10287 - Traceroute Information

Synopsis

It was possible to obtain traceroute information.

Description

Makes a traceroute to the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/11/27, Modified: 2026/04/27

Plugin Output

udp/0

```
For your information, here is the traceroute from 172.30.0.2 to 172.30.9.2 :
172.30.0.2
172.30.9.2

Hop Count: 1
```

Synopsis

The remote web server contains a 'robots.txt' file.

Description

The remote host contains a file named 'robots.txt' that is intended to prevent web 'robots' from visiting certain directories in a website for maintenance or indexing purposes. A malicious user may also be able to use the contents of this file to learn of sensitive documents or directories on the affected site and either retrieve them directly or target them for other attacks.

See Also

<http://www.robotstxt.org/orig.html>

Solution

Review the contents of the site's robots.txt file, use Robots META tags instead of entries in the robots.txt file, and/or adjust the web server's access controls to limit access to sensitive material.

Risk Factor

None

Plugin Information

Published: 1999/10/12, Modified: 2026/03/10

Plugin Output

tcp/80/www

Contents of robots.txt :

```
User-agent: GoodBot
Disallow:
User-agent: BadBot
Disallow: /
User-agent: *
Disallow: /admin/
Disallow: /documents/
Disallow: /images/
Disallow: /passwords/
```

172.30.9.3



Scan Information

Start time: Thu Jul 23 18:30:17 2026

End time: Thu Jul 23 18:37:12 2026

Host Information

IP: 172.30.9.3

MAC Address: 82:F2:9F:B3:F2:4F

OS: Linux Kernel 3.13 on Ubuntu 14.04 (trusty)

Vulnerabilities

201408 - Canonical Ubuntu Linux SEoL (14.04.x)

Synopsis

An unsupported version of Canonical Ubuntu Linux is installed on the remote host.

Description

According to its version, Canonical Ubuntu Linux is 14.04.x. It is, therefore, no longer maintained by its vendor or provider.

Lack of support implies that no new security patches for the product will be released by the vendor. As a result, it may contain security vulnerabilities.

See Also

<http://www.nessus.org/u?5afc4199>

Solution

Upgrade to a version of Canonical Ubuntu Linux that is currently supported.

Risk Factor

Critical

CVSS v3.0 Base Score

10.0 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H)

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

Plugin Information

Published: 2024/07/03, Modified: 2025/03/26

Plugin Output

tcp/80/www

```
OS : Ubuntu Linux 14.04
Security End of Life : April 25, 2019
Time since Security End of Life (Est.) : >= 7 years
```

50686 - IP Forwarding Enabled

Synopsis

The remote host has IP forwarding enabled.

Description

The remote host has IP forwarding enabled. An attacker can exploit this to route packets through the host and potentially bypass some firewalls / routers / NAC filtering.

Unless the remote host is a router, it is recommended that you disable IP forwarding.

Solution

On Linux, you can disable IP forwarding by doing :

```
echo 0 > /proc/sys/net/ipv4/ip_forward
```

On Windows, set the key 'IPEnableRouter' to 0 under

HKEY_LOCAL_MACHINE\System\CurrentControlSet\Services\Tcpip\Parameters

On Mac OS X, you can disable IP forwarding by executing the command :

```
sysctl -w net.inet.ip.forwarding=0
```

For other systems, check with your vendor.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:A/AC:L/PR:L/UI:N/S:C/C:L/I:L/A:L)

CVSS v2.0 Base Score

5.8 (CVSS2#AV:A/AC:L/Au:N/C:P/I:P/A:P)

References

CVE CVE-1999-0511

Plugin Information

Published: 2010/11/23, Modified: 2023/10/17

Plugin Output

tcp/0

IP forwarding appears to be enabled on the remote host.

Detected local MAC Address : e68cc3441691
Response from local MAC Address : e68cc3441691

Detected Gateway MAC Address : 82f29fb3f24f
Response from Gateway MAC Address : 82f29fb3f24f

10114 - ICMP Timestamp Request Remote Date Disclosure

Synopsis

It is possible to determine the exact time set on the remote host.

Description

The remote host answers to an ICMP timestamp request. This allows an attacker to know the date that is set on the targeted machine, which may assist an unauthenticated, remote attacker in defeating time-based authentication protocols.

Timestamps returned from machines running Windows Vista / 7 / 2008 / 2008 R2 are deliberately incorrect, but usually within 1000 seconds of the actual system time.

Solution

Filter out the ICMP timestamp requests (13), and the outgoing ICMP timestamp replies (14).

Risk Factor

Low

CVSS v2.0 Base Score

2.1 (CVSS2#AV:L/AC:L/Au:N/C:P/I:N/A:N)

References

CVE	CVE-1999-0524
XREF	CWE:200

Plugin Information

Published: 1999/08/01, Modified: 2024/10/07

Plugin Output

icmp/0

```
The remote clock is synchronized with the local clock.
```

18261 - Apache Banner Linux Distribution Disclosure

Synopsis

The name of the Linux distribution running on the remote host was found in the banner of the web server.

Description

Nessus was able to extract the banner of the Apache web server and determine which Linux distribution the remote host is running.

Solution

If you do not wish to display this information, edit 'httpd.conf' and set the directive 'ServerTokens Prod' and restart Apache.

Risk Factor

None

Plugin Information

Published: 2005/05/15, Modified: 2025/03/31

Plugin Output

tcp/0

```
The Linux distribution detected was :  
- Ubuntu 14.04 (trusty)
```

48204 - Apache HTTP Server Version

Synopsis

It is possible to obtain the version number of the remote Apache HTTP server.

Description

The remote host is running the Apache HTTP Server, an open source web server. It was possible to read the version number from the banner.

See Also

<https://httpd.apache.org/>

Solution

n/a

Risk Factor

None

References

XREF	IAVT:0001-T-0030
XREF	IAVT:0001-T-0530

Plugin Information

Published: 2010/07/30, Modified: 2026/01/22

Plugin Output

tcp/80/www

```
URL      : http://172.30.9.3/
Version  : 2.4.7
Source   : Server: Apache/2.4.7 (Ubuntu)
backported : 1
os       : Ubuntu
```

84574 - Backported Security Patch Detection (PHP)

Synopsis

Security patches have been backported.

Description

Security patches may have been 'backported' to the remote PHP install without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/07/07, Modified: 2024/11/22

Plugin Output

tcp/80/www

Give Nessus credentials to perform local checks.

39521 - Backported Security Patch Detection (WWW)

Synopsis

Security patches are backported.

Description

Security patches may have been 'backported' to the remote HTTP server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/06/25, Modified: 2026/01/22

Plugin Output

tcp/80/www

Give Nessus credentials to perform local checks.

45590 - Common Platform Enumeration (CPE)

Synopsis

It was possible to enumerate CPE names that matched on the remote system.

Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

See Also

<http://cpe.mitre.org/>

<https://nvd.nist.gov/products/cpe>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/04/21, Modified: 2026/06/16

Plugin Output

tcp/0

Following application CPE's matched on the remote system :

```
cpe:/a:apache:http_server:2.4.7 -> Apache Software Foundation Apache HTTP Server
cpe:/a:mysql:mysql -> MySQL MySQL
cpe:/a:php:php:5.5.9 -> PHP PHP
cpe:/a:php:php:5.5.9-1ubuntu4.25 -> PHP PHP
```

54615 - Device Type

Synopsis

It is possible to guess the remote device type.

Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/05/23, Modified: 2025/03/12

Plugin Output

tcp/0

```
Remote device type : general-purpose  
Confidence level : 95
```

86420 - Ethernet MAC Addresses

Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/10/16, Modified: 2025/06/10

Plugin Output

tcp/0

The following is a consolidated list of detected MAC addresses:
- 82:F2:9F:B3:F2:4F

10107 - HTTP Server Type and Version

Synopsis

A web server is running on the remote host.

Description

This plugin attempts to determine the type and the version of the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0931

Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

Plugin Output

tcp/80/www

```
The remote web server type is :  
Apache/2.4.7 (Ubuntu)
```

12053 - Host Fully Qualified Domain Name (FQDN) Resolution

Synopsis

It was possible to resolve the name of the remote host.

Description

Nessus was able to resolve the fully qualified domain name (FQDN) of the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/02/11, Modified: 2025/03/13

Plugin Output

tcp/0

```
172.30.9.3 resolves as mutillidae.labvulnerabilities_vulnnet.
```

24260 - HyperText Transfer Protocol (HTTP) Information

Synopsis

Some information about the remote HTTP configuration can be extracted.

Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

Plugin Output

tcp/80/www

Response Code : HTTP/1.1 302 Found

Protocol version : HTTP/1.1

HTTP/2 TLS Support: No

HTTP/2 Cleartext Support: No

SSL : no

Keep-Alive : yes

Options allowed : (Not implemented)

Headers :

Date: Thu, 23 Jul 2026 22:31:14 GMT

Server: Apache/2.4.7 (Ubuntu)

X-Powered-By: PHP/5.5.9-1ubuntu4.25

Expires: Thu, 19 Nov 1981 08:52:00 GMT

Cache-Control: no-store, no-cache, must-revalidate, post-check=0, pre-check=0

Pragma: no-cache

Location: database-offline.php

Content-Length: 0

Keep-Alive: timeout=5, max=98

Connection: Keep-Alive

Content-Type: text/html

Response Body :

10719 - MySQL Server Detection

Synopsis

A database server is listening on the remote port.

Description

The remote host is running MySQL, an open source database server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0802

Plugin Information

Published: 2001/08/13, Modified: 2025/09/24

Plugin Output

tcp/3306/mysql

```
Service : mysql  
Version : unknown
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/80/www

```
Port 80/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/3306/mysql

```
Port 3306/tcp was found to be open
```

19506 - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2026/07/10

Plugin Output

tcp/0

Information about this scan :

```
Nessus version : 10.12.2
Nessus build : 20029
Plugin feed version : 202607231328
Scanner edition used : Nessus
Scanner OS : LINUX
Scanner distribution : ubuntu1604-x86-64
Scan type : Normal
Scan name : My Basic Network Scan
```

Scan policy used : Basic Network Scan
Scanner IP : 172.30.0.2
Port scanner(s) : nessus_syn_scanner
Port range : default
Ping RTT : 75.119 ms
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Assess component installs : yes
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 30
Max checks : 4
Recv timeout : 5
Backports : Detected
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2026/7/23 18:30 EDT (UTC -04:00)
Scan duration : 411 sec
Scan for malware : no
Fully Scan Operational Technology devices : no
Safely Scan Operational Technology devices with OT Discovery : no

209654 - OS Fingerprints Detected

Synopsis

Multiple OS fingerprints were detected.

Description

Using a combination of remote probes (TCP/IP, SMB, HTTP, NTP, SNMP, etc), it was possible to gather one or more fingerprints from the remote system. While the highest-confidence result was reported in plugin 11936, "OS Identification", the complete set of fingerprints detected are reported here.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/02/26, Modified: 2025/03/03

Plugin Output

tcp/0

Following OS Fingerprints were found

Remote operating system : SuSE Linux
Confidence level : 56
Method : MLSinFP
Type : unknown
Fingerprint : unknown

Remote operating system : Linux Kernel 3.13 on Ubuntu 14.04 (trusty)
Confidence level : 95
Method : HTTP
Type : general-purpose
Fingerprint : unknown

Remote operating system : Linux Kernel 2.x
Confidence level : 54
Method : SinFP
Type : general-purpose
Fingerprint : SinFP:

P1:B10113:F0x12:W64240:00204ffff:M1460:
P2:B10113:F0x12:W65160:00204ffff0402080affffff444541440103030a:M1460:
P3:B00000:F0x00:W0:00:M0
P4:191802_7_p=80

11936 - OS Identification

Synopsis

It is possible to guess the remote operating system.

Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2003/12/09, Modified: 2025/06/03

Plugin Output

tcp/0

```
Remote operating system : Linux Kernel 3.13 on Ubuntu 14.04 (trusty)
Confidence level : 95
Method : HTTP
```

```
The remote host is running Linux Kernel 3.13 on Ubuntu 14.04 (trusty)
```

48243 - PHP Version Detection

Synopsis

It was possible to obtain the version number of the remote PHP installation.

Description

Nessus was able to determine the version of PHP available on the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0936

Plugin Information

Published: 2010/08/04, Modified: 2026/01/22

Plugin Output

tcp/80/www

Nessus was able to identify the following PHP version information :

```
Version : 5.5.9-1ubuntu4.25
Source  : X-Powered-By: PHP/5.5.9-1ubuntu4.25
Backported : 1
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/80/www

A web server is running on this port.

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/3306/mysql

A MySQL server is running on this port.

25220 - TCP/IP Timestamps Supported

Synopsis

The remote service implements TCP timestamps.

Description

The remote host implements TCP timestamps, as defined by RFC1323. A side effect of this feature is that the uptime of the remote host can sometimes be computed.

See Also

<http://www.ietf.org/rfc/rfc1323.txt>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2023/10/17

Plugin Output

tcp/0

10287 - Traceroute Information

Synopsis

It was possible to obtain traceroute information.

Description

Makes a traceroute to the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/11/27, Modified: 2026/04/27

Plugin Output

udp/0

```
For your information, here is the traceroute from 172.30.0.2 to 172.30.9.3 :
172.30.0.2
172.30.9.3

Hop Count: 1
```

Synopsis

The remote web server contains a 'robots.txt' file.

Description

The remote host contains a file named 'robots.txt' that is intended to prevent web 'robots' from visiting certain directories in a website for maintenance or indexing purposes. A malicious user may also be able to use the contents of this file to learn of sensitive documents or directories on the affected site and either retrieve them directly or target them for other attacks.

See Also

<http://www.robotstxt.org/orig.html>

Solution

Review the contents of the site's robots.txt file, use Robots META tags instead of entries in the robots.txt file, and/or adjust the web server's access controls to limit access to sensitive material.

Risk Factor

None

Plugin Information

Published: 1999/10/12, Modified: 2026/03/10

Plugin Output

tcp/80/www

Contents of robots.txt :

```
User-agent: *
Disallow: passwords/
Disallow: config.inc
Disallow: classes/
Disallow: javascript/
Disallow: owasp-esapi-php/
Disallow: documentation/
Disallow: phpmyadmin/
Disallow: includes/
```


172.30.15.1



Scan Information

Start time: Thu Jul 23 18:30:17 2026

End time: Thu Jul 23 18:37:10 2026

Host Information

IP: 172.30.15.1

MAC Address: BE:F5:78:0A:49:34

OS: Linux Kernel 3.x on Ubuntu

Vulnerabilities

50686 - IP Forwarding Enabled

Synopsis

The remote host has IP forwarding enabled.

Description

The remote host has IP forwarding enabled. An attacker can exploit this to route packets through the host and potentially bypass some firewalls / routers / NAC filtering.

Unless the remote host is a router, it is recommended that you disable IP forwarding.

Solution

On Linux, you can disable IP forwarding by doing :

```
echo 0 > /proc/sys/net/ipv4/ip_forward
```

On Windows, set the key 'IPEnableRouter' to 0 under

HKEY_LOCAL_MACHINE\System\CurrentControlSet\Services\Tcpip\Parameters

On Mac OS X, you can disable IP forwarding by executing the command :

```
sysctl -w net.inet.ip.forwarding=0
```

For other systems, check with your vendor.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:A/AC:L/PR:L/UI:N/S:C/C:L/I:L/A:L)

CVSS v2.0 Base Score

5.8 (CVSS2#AV:A/AC:L/Au:N/C:P/I:P/A:P)

References

CVE CVE-1999-0511

Plugin Information

Published: 2010/11/23, Modified: 2023/10/17

Plugin Output

tcp/0

```
IP forwarding appears to be enabled on the remote host.
```

```
Detected local MAC Address      : e68cc3441691
Response from local MAC Address : e68cc3441691
```

```
Detected Gateway MAC Address    : bef5780a4934
Response from Gateway MAC Address : bef5780a4934
```

304671 - nginx 1.3.0 < 1.28.2 / 1.29.x < 1.29.5 SSL Upstream Injection

Synopsis

The remote web server is affected by a vulnerability.

Description

The installed version of nginx is 1.3.0 prior to 1.28.2, or 1.29.x prior to 1.29.5. It is, therefore, affected by the following issue:

- A vulnerability exists in NGINX OSS and NGINX Plus when configured to proxy to upstream Transport Layer Security (TLS) servers. An attacker with a man-in-the-middle (MITM) position on the upstream server side--along with conditions beyond the attacker's control--may be able to inject plain text data into the response from an upstream proxied server. Note: Software versions which have reached End of Technical Support (EoTS) are not evaluated.

(CVE-2026-1642)

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

<https://my.f5.com/manage/s/article/K000159824>

https://nginx.org/en/security_advisories.html

Solution

Upgrade to nginx 1.28.2 / 1.29.5 or later.

Risk Factor

High

CVSS v4.0 Base Score

8.2 (CVSS:4.0/AV:N/AC:L/AT:P/PR:N/UI:N/VC:N/VI:H/VA:N/SC:N/SI:N/SA:N)

CVSS v3.0 Base Score

5.9 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:N/I:H/A:N)

CVSS v3.0 Temporal Score

5.2 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

7.1 (CVSS2#AV:N/AC:M/Au:N/C:N/I:C/A:N)

CVSS v2.0 Temporal Score

5.3 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2026-1642
XREF	IAVA:2026-A-0280

Plugin Information

Published: 2026/04/02, Modified: 2026/07/17

Plugin Output

tcp/80/www

```
URL           : http://172.30.15.1/
Installed version : 1.10.3
Fixed version  : 1.28.2
```

134220 - nginx < 1.17.7 Information Disclosure

Synopsis

The remote web server is affected by an information disclosure vulnerability.

Description

The installed version of nginx is prior to 1.17.7. It is, therefore, affected by an information disclosure vulnerability.

See Also

<http://www.nessus.org/u?fd026623>

Solution

Upgrade to nginx version 1.17.7 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v3.0 Temporal Score

4.8 (CVSS:3.0/E:P/RL:O/RC:C)

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.4 (CVSS2#E:POC/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2019-20372
XREF	IAVB:2020-B-0013-S

Plugin Information

Published: 2020/03/05, Modified: 2026/07/17

Plugin Output

tcp/80/www

```
URL           : http://172.30.15.1/  
Installed version : 1.10.3  
Fixed version  : 1.17.7
```

10114 - ICMP Timestamp Request Remote Date Disclosure

Synopsis

It is possible to determine the exact time set on the remote host.

Description

The remote host answers to an ICMP timestamp request. This allows an attacker to know the date that is set on the targeted machine, which may assist an unauthenticated, remote attacker in defeating time-based authentication protocols.

Timestamps returned from machines running Windows Vista / 7 / 2008 / 2008 R2 are deliberately incorrect, but usually within 1000 seconds of the actual system time.

Solution

Filter out the ICMP timestamp requests (13), and the outgoing ICMP timestamp replies (14).

Risk Factor

Low

CVSS v2.0 Base Score

2.1 (CVSS2#AV:L/AC:L/Au:N/C:P/I:N/A:N)

References

CVE	CVE-1999-0524
XREF	CWE:200

Plugin Information

Published: 1999/08/01, Modified: 2024/10/07

Plugin Output

icmp/0

```
The remote clock is synchronized with the local clock.
```

45590 - Common Platform Enumeration (CPE)

Synopsis

It was possible to enumerate CPE names that matched on the remote system.

Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

See Also

<http://cpe.mitre.org/>

<https://nvd.nist.gov/products/cpe>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/04/21, Modified: 2026/06/16

Plugin Output

tcp/0

```
The remote operating system matched the following CPE :
```

```
cpe:/o:canonical:ubuntu_linux -> Canonical Ubuntu Linux
```

```
Following application CPE's matched on the remote system :
```

```
cpe:/a:igor_sysoev:nginx:1.10.3 -> Nginx
```

```
cpe:/a:nginx:nginx:1.10.3 -> Nginx
```


54615 - Device Type

Synopsis

It is possible to guess the remote device type.

Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/05/23, Modified: 2025/03/12

Plugin Output

tcp/0

Remote device type : unknown
Confidence level : 56

86420 - Ethernet MAC Addresses

Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/10/16, Modified: 2025/06/10

Plugin Output

tcp/0

The following is a consolidated list of detected MAC addresses:
- BE:F5:78:0A:49:34

10107 - HTTP Server Type and Version

Synopsis

A web server is running on the remote host.

Description

This plugin attempts to determine the type and the version of the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0931

Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

Plugin Output

tcp/80/www

```
The remote web server type is :  
nginx/1.10.3
```

12053 - Host Fully Qualified Domain Name (FQDN) Resolution

Synopsis

It was possible to resolve the name of the remote host.

Description

Nessus was able to resolve the fully qualified domain name (FQDN) of the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/02/11, Modified: 2025/03/13

Plugin Output

tcp/0

```
172.30.15.1 resolves as nginx-old.labvulnerabilities_vulnnet.
```

24260 - HyperText Transfer Protocol (HTTP) Information

Synopsis

Some information about the remote HTTP configuration can be extracted.

Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

Plugin Output

tcp/80/www

Response Code : HTTP/1.1 200 OK

Protocol version : HTTP/1.1

HTTP/2 TLS Support: No

HTTP/2 Cleartext Support: No

SSL : no

Keep-Alive : no

Options allowed : (Not implemented)

Headers :

Server: nginx/1.10.3

Date: Thu, 23 Jul 2026 22:31:11 GMT

Content-Type: text/html

Content-Length: 612

Last-Modified: Tue, 31 Jan 2017 15:01:11 GMT

Connection: keep-alive

ETag: "5890a6b7-264"

Accept-Ranges: bytes

Response Body :

<!DOCTYPE html>

<html>

<head>

<title>Welcome to nginx!</title>

<style>

body {

```
        width: 35em;
        margin: 0 auto;
        font-family: Tahoma, Verdana, Arial, sans-serif;
    }
</style>
</head>
<body>
<h1>Welcome to nginx!</h1>
<p>If you see this page, the nginx web server is successfully installed and
working. Further configuration is required.</p>

<p>For online documentation and support please refer to
<a href="http://nginx.org/">nginx.org</a>.<br/>
Commercial support is available at
<a href="http://nginx.com/">nginx.com</a>.</p>

<p><em>Thank you for using nginx.</em></p>
</body>
</html>
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/80/www

```
Port 80/tcp was found to be open
```

19506 - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2026/07/10

Plugin Output

tcp/0

Information about this scan :

```
Nessus version : 10.12.2
Nessus build : 20029
Plugin feed version : 202607231328
Scanner edition used : Nessus
Scanner OS : LINUX
Scanner distribution : ubuntu1604-x86-64
Scan type : Normal
Scan name : My Basic Network Scan
```


Scan policy used : Basic Network Scan
Scanner IP : 172.30.0.2
Port scanner(s) : nessus_syn_scanner
Port range : default
Ping RTT : 75.052 ms
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Assess component installs : yes
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 30
Max checks : 4
Recv timeout : 5
Backports : None
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2026/7/23 18:30 EDT (UTC -04:00)
Scan duration : 409 sec
Scan for malware : no
Fully Scan Operational Technology devices : no
Safely Scan Operational Technology devices with OT Discovery : no

209654 - OS Fingerprints Detected

Synopsis

Multiple OS fingerprints were detected.

Description

Using a combination of remote probes (TCP/IP, SMB, HTTP, NTP, SNMP, etc), it was possible to gather one or more fingerprints from the remote system. While the highest-confidence result was reported in plugin 11936, "OS Identification", the complete set of fingerprints detected are reported here.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/02/26, Modified: 2025/03/03

Plugin Output

tcp/0

Following OS Fingerprints were found

Remote operating system : Linux Kernel 3.x on Ubuntu
Confidence level : 56
Method : MLSinFP
Type : unknown
Fingerprint : unknown

Remote operating system : Linux Kernel 2.x
Confidence level : 54
Method : SinFP
Type : general-purpose
Fingerprint : SinFP:
P1:B10113:F0x12:W64240:00204ffff:M1460:
P2:B10113:F0x12:W65160:00204ffff0402080affffff444541440103030a:M1460:
P3:B00000:F0x00:W0:00:M0
P4:191802_7_p=80

Following fingerprints could not be used to determine OS :
HTTP:!:Server: nginx/1.10.3

11936 - OS Identification

Synopsis

It is possible to guess the remote operating system.

Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2003/12/09, Modified: 2025/06/03

Plugin Output

tcp/0

```
Remote operating system : Linux Kernel 3.x on Ubuntu  
Confidence level : 56  
Method : MLSinFP
```

```
The remote host is running Linux Kernel 3.x on Ubuntu
```

Synopsis

The remote host is missing several patches.

Description

The remote host is missing one or more security patches. This plugin lists the newest version of each patch to install to make sure the remote host is up-to-date.

Note: Because the 'Show missing patches that have been superseded' setting in your scan policy depends on this plugin, it will always run and cannot be disabled.

Solution

Install the patches listed below.

Risk Factor

None

Plugin Information

Published: 2013/07/08, Modified: 2026/07/17

Plugin Output

tcp/0

```
. You need to take the following action :  
[ nginx 1.3.0 < 1.28.2 / 1.29.x < 1.29.5 SSL Upstream Injection (304671) ]  
+ Action to take : Upgrade to nginx 1.28.2 / 1.29.5 or later.
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/80/www

A web server is running on this port.

25220 - TCP/IP Timestamps Supported

Synopsis

The remote service implements TCP timestamps.

Description

The remote host implements TCP timestamps, as defined by RFC1323. A side effect of this feature is that the uptime of the remote host can sometimes be computed.

See Also

<http://www.ietf.org/rfc/rfc1323.txt>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2023/10/17

Plugin Output

tcp/0

10287 - Traceroute Information

Synopsis

It was possible to obtain traceroute information.

Description

Makes a traceroute to the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/11/27, Modified: 2026/04/27

Plugin Output

udp/0

```
For your information, here is the traceroute from 172.30.0.2 to 172.30.15.1 :
172.30.0.2
172.30.15.1

Hop Count: 1
```

106375 - nginx HTTP Server Detection

Synopsis

The nginx HTTP server was detected on the remote host.

Description

Nessus was able to detect the nginx HTTP server by looking at the HTTP banner on the remote host.

See Also

<https://nginx.org/>

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0677

Plugin Information

Published: 2018/01/26, Modified: 2026/07/20

Plugin Output

tcp/80/www

```
URL      : http://172.30.15.1/
Version  : 1.10.3
backported : 0
source    : Server: nginx/1.10.3
```


172.30.15.2



Scan Information

Start time: Thu Jul 23 18:30:17 2026

End time: Thu Jul 23 18:37:11 2026

Host Information

IP: 172.30.15.2

MAC Address: 5A:A1:2B:A4:20:BE

OS: SuSE Linux

Vulnerabilities

88098 - Apache Server ETag Header Information Disclosure

Synopsis

The remote web server is affected by an information disclosure vulnerability.

Description

The remote web server is affected by an information disclosure vulnerability due to the ETag header providing sensitive information that could aid an attacker, such as the inode number of requested files.

See Also

<http://httpd.apache.org/docs/2.2/mod/core.html#FileETag>

Solution

Modify the HTTP ETag header of the web server to not include file inodes in the ETag header calculation. Refer to the linked Apache documentation for more information.

Risk Factor

Medium

CVSS v3.0 Base Score

172.30.15.2

353

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.2 (CVSS2#E:U/RL:OF/RC:C)

References

BID	6939
CVE	CVE-2003-1418
XREF	CWE:200

Plugin Information

Published: 2016/01/22, Modified: 2025/02/11

Plugin Output

tcp/80/www

Nessus was able to determine that the Apache Server listening on port 80 leaks the servers inode numbers in the ETag HTTP Header field :

Source	: ETag: "d06c4a-2c-3e9564c23b600"
Inode number	: 13659210
File size	: 44 bytes
File modification time	: Nov. 20, 2004 at 20:16:24 GMT

50686 - IP Forwarding Enabled

Synopsis

The remote host has IP forwarding enabled.

Description

The remote host has IP forwarding enabled. An attacker can exploit this to route packets through the host and potentially bypass some firewalls / routers / NAC filtering.

Unless the remote host is a router, it is recommended that you disable IP forwarding.

Solution

On Linux, you can disable IP forwarding by doing :

```
echo 0 > /proc/sys/net/ipv4/ip_forward
```

On Windows, set the key 'IPEnableRouter' to 0 under

HKEY_LOCAL_MACHINE\System\CurrentControlSet\Services\Tcpip\Parameters

On Mac OS X, you can disable IP forwarding by executing the command :

```
sysctl -w net.inet.ip.forwarding=0
```

For other systems, check with your vendor.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:A/AC:L/PR:L/UI:N/S:C/C:L/I:L/A:L)

CVSS v2.0 Base Score

5.8 (CVSS2#AV:A/AC:L/Au:N/C:P/I:P/A:P)

References

CVE CVE-1999-0511

Plugin Information

Published: 2010/11/23, Modified: 2023/10/17

Plugin Output

tcp/0

IP forwarding appears to be enabled on the remote host.

Detected local MAC Address : e68cc3441691
Response from local MAC Address : e68cc3441691

Detected Gateway MAC Address : 5aa12ba420be
Response from Gateway MAC Address : 5aa12ba420be

10114 - ICMP Timestamp Request Remote Date Disclosure

Synopsis

It is possible to determine the exact time set on the remote host.

Description

The remote host answers to an ICMP timestamp request. This allows an attacker to know the date that is set on the targeted machine, which may assist an unauthenticated, remote attacker in defeating time-based authentication protocols.

Timestamps returned from machines running Windows Vista / 7 / 2008 / 2008 R2 are deliberately incorrect, but usually within 1000 seconds of the actual system time.

Solution

Filter out the ICMP timestamp requests (13), and the outgoing ICMP timestamp replies (14).

Risk Factor

Low

CVSS v2.0 Base Score

2.1 (CVSS2#AV:L/AC:L/Au:N/C:P/I:N/A:N)

References

CVE	CVE-1999-0524
XREF	CWE:200

Plugin Information

Published: 1999/08/01, Modified: 2024/10/07

Plugin Output

icmp/0

```
The remote clock is synchronized with the local clock.
```

48204 - Apache HTTP Server Version

Synopsis

It is possible to obtain the version number of the remote Apache HTTP server.

Description

The remote host is running the Apache HTTP Server, an open source web server. It was possible to read the version number from the banner.

See Also

<https://httpd.apache.org/>

Solution

n/a

Risk Factor

None

References

XREF	IAVT:0001-T-0030
XREF	IAVT:0001-T-0530

Plugin Information

Published: 2010/07/30, Modified: 2026/01/22

Plugin Output

tcp/80/www

```
URL      : http://172.30.15.2/
Version  : 2.2.34
Source   : Server: Apache/2.2.34 (Unix) mod_ssl/2.2.34 OpenSSL/1.0.1t DAV/2
backported : 1
modules  : mod_ssl/2.2.34 OpenSSL/1.0.1t DAV/2
os       : Unix
```

39521 - Backported Security Patch Detection (WWW)

Synopsis

Security patches are backported.

Description

Security patches may have been 'backported' to the remote HTTP server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/06/25, Modified: 2026/01/22

Plugin Output

tcp/80/www

Give Nessus credentials to perform local checks.

45590 - Common Platform Enumeration (CPE)

Synopsis

It was possible to enumerate CPE names that matched on the remote system.

Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

See Also

<http://cpe.mitre.org/>

<https://nvd.nist.gov/products/cpe>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/04/21, Modified: 2026/06/16

Plugin Output

tcp/0

Following application CPE's matched on the remote system :

```
cpe:/a:apache:http_server:2.2.34 -> Apache Software Foundation Apache HTTP Server
cpe:/a:modssl:mod_ssl:2.2.34 -> mod_ssl
cpe:/a:openssl:openssl:1.0.1t -> OpenSSL Project OpenSSL
```


54615 - Device Type

Synopsis

It is possible to guess the remote device type.

Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/05/23, Modified: 2025/03/12

Plugin Output

tcp/0

Remote device type : unknown
Confidence level : 56

86420 - Ethernet MAC Addresses

Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/10/16, Modified: 2025/06/10

Plugin Output

tcp/0

The following is a consolidated list of detected MAC addresses:
- 5A:A1:2B:A4:20:BE

43111 - HTTP Methods Allowed (per directory)

Synopsis

This plugin determines which HTTP methods are allowed on various CGI directories.

Description

By calling the OPTIONS method, it is possible to determine which HTTP methods are allowed on each directory.

The following HTTP methods are considered insecure:

PUT, DELETE, CONNECT, TRACE, HEAD

Many frameworks and languages treat 'HEAD' as a 'GET' request, albeit one without any body in the response. If a security constraint was set on 'GET' requests such that only 'authenticatedUsers' could access GET requests for a particular servlet or resource, it would be bypassed for the 'HEAD' version. This allowed unauthorized blind submission of any privileged GET request.

As this list may be incomplete, the plugin also tests - if 'Thorough tests' are enabled or 'Enable web applications tests' is set to 'yes'

in the scan policy - various known HTTP methods on each directory and considers them as unsupported if it receives a response code of 400, 403, 405, or 501.

Note that the plugin output is only informational and does not necessarily indicate the presence of any security vulnerabilities.

See Also

<http://www.nessus.org/u?d9c03a9a>

<http://www.nessus.org/u?b019cbdb>

[https://www.owasp.org/index.php/Test_HTTP_Methods_\(OTG-CONFIG-006\)](https://www.owasp.org/index.php/Test_HTTP_Methods_(OTG-CONFIG-006))

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/12/10, Modified: 2022/04/11

Plugin Output

tcp/80/www

Based on the response to an OPTIONS request :

- HTTP methods GET HEAD OPTIONS POST TRACE are allowed on :

/

10107 - HTTP Server Type and Version

Synopsis

A web server is running on the remote host.

Description

This plugin attempts to determine the type and the version of the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0931

Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

Plugin Output

tcp/80/www

```
The remote web server type is :  
Apache/2.2.34 (Unix) mod_ssl/2.2.34 OpenSSL/1.0.1t DAV/2
```

12053 - Host Fully Qualified Domain Name (FQDN) Resolution

Synopsis

It was possible to resolve the name of the remote host.

Description

Nessus was able to resolve the fully qualified domain name (FQDN) of the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/02/11, Modified: 2025/03/13

Plugin Output

tcp/0

```
172.30.15.2 resolves as apache-old.labvulnerabilities_vulnnet.
```

24260 - HyperText Transfer Protocol (HTTP) Information

Synopsis

Some information about the remote HTTP configuration can be extracted.

Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

Plugin Output

tcp/80/www

Response Code : HTTP/1.1 200 OK

Protocol version : HTTP/1.1

HTTP/2 TLS Support: No

HTTP/2 Cleartext Support: No

SSL : no

Keep-Alive : yes

Options allowed : (Not implemented)

Headers :

Date: Thu, 23 Jul 2026 22:31:13 GMT

Server: Apache/2.2.34 (Unix) mod_ssl/2.2.34 OpenSSL/1.0.1t DAV/2

Last-Modified: Sat, 20 Nov 2004 20:16:24 GMT

ETag: "d06c4a-2c-3e9564c23b600"

Accept-Ranges: bytes

Content-Length: 44

Keep-Alive: timeout=5, max=98

Connection: Keep-Alive

Content-Type: text/html

Response Body :

<html><body><h1>It works!</h1></body></html>

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/80/www

```
Port 80/tcp was found to be open
```


19506 - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2026/07/10

Plugin Output

tcp/0

Information about this scan :

```
Nessus version : 10.12.2
Nessus build : 20029
Plugin feed version : 202607231328
Scanner edition used : Nessus
Scanner OS : LINUX
Scanner distribution : ubuntu1604-x86-64
Scan type : Normal
Scan name : My Basic Network Scan
```

Scan policy used : Basic Network Scan
Scanner IP : 172.30.0.2
Port scanner(s) : nessus_syn_scanner
Port range : default
Ping RTT : 79.353 ms
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Assess component installs : yes
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 30
Max checks : 4
Recv timeout : 5
Backports : Detected
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2026/7/23 18:30 EDT (UTC -04:00)
Scan duration : 410 sec
Scan for malware : no
Fully Scan Operational Technology devices : no
Safely Scan Operational Technology devices with OT Discovery : no

209654 - OS Fingerprints Detected

Synopsis

Multiple OS fingerprints were detected.

Description

Using a combination of remote probes (TCP/IP, SMB, HTTP, NTP, SNMP, etc), it was possible to gather one or more fingerprints from the remote system. While the highest-confidence result was reported in plugin 11936, "OS Identification", the complete set of fingerprints detected are reported here.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/02/26, Modified: 2025/03/03

Plugin Output

tcp/0

Following OS Fingerprints were found

Remote operating system : SuSE Linux
Confidence level : 56
Method : MLSinFP
Type : unknown
Fingerprint : unknown

Remote operating system : Linux Kernel 2.x
Confidence level : 54
Method : SinFP
Type : general-purpose
Fingerprint : SinFP:

P1:B10113:F0x12:W64240:00204ffff:M1460:
P2:B10113:F0x12:W65160:00204ffff0402080affffffff444541440103030a:M1460:
P3:B00000:F0x00:W0:00:M0
P4:191802_7_p=80

Following fingerprints could not be used to determine OS :

HTTP:!:Server: Apache/2.2.34 (Unix) mod_ssl/2.2.34 OpenSSL/1.0.1t DAV/2

11936 - OS Identification

Synopsis

It is possible to guess the remote operating system.

Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2003/12/09, Modified: 2025/06/03

Plugin Output

tcp/0

```
Remote operating system : SuSE Linux
Confidence level : 56
Method : MLSinFP
```

```
The remote host is running SuSE Linux
```

57323 - OpenSSL Version Detection

Synopsis

Nessus was able to detect the OpenSSL version.

Description

Nessus was able to extract the OpenSSL version from the web server's banner. Note that security patches in many cases are backported and the displayed version number does not show the patch level. Using it to identify vulnerable software is likely to lead to false detections.

See Also

<https://www.openssl.org/>

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0682

Plugin Information

Published: 2011/12/16, Modified: 2026/01/22

Plugin Output

tcp/80/www

```
Source          : Apache/2.2.34 (Unix) mod_ssl/2.2.34 OpenSSL/1.0.1t DAV/2
Reported version : 1.0.1t
Backported      : 1
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/80/www

```
A web server is running on this port.
```

25220 - TCP/IP Timestamps Supported

Synopsis

The remote service implements TCP timestamps.

Description

The remote host implements TCP timestamps, as defined by RFC1323. A side effect of this feature is that the uptime of the remote host can sometimes be computed.

See Also

<http://www.ietf.org/rfc/rfc1323.txt>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2023/10/17

Plugin Output

tcp/0

10287 - Traceroute Information

Synopsis

It was possible to obtain traceroute information.

Description

Makes a traceroute to the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/11/27, Modified: 2026/04/27

Plugin Output

udp/0

```
For your information, here is the traceroute from 172.30.0.2 to 172.30.15.2 :
172.30.0.2
172.30.15.2

Hop Count: 1
```


11424 - WebDAV Detection

Synopsis

The remote server is running with WebDAV enabled.

Description

WebDAV is an industry standard extension to the HTTP specification.

It adds a capability for authorized users to remotely add and manage the content of a web server.

If you do not use this extension, you should disable it.

Solution

<http://support.microsoft.com/default.aspx?kbid=241520>

Risk Factor

None

Plugin Information

Published: 2003/03/20, Modified: 2011/03/14

Plugin Output

tcp/80/www

172.30.30.1



Scan Information

Start time: Thu Jul 23 18:30:17 2026

End time: Thu Jul 23 18:31:46 2026

Host Information

IP: 172.30.30.1

MAC Address: E2:66:6D:53:49:4E

OS: Linux Kernel 7.0.0-28-generic

Vulnerabilities

41028 - SNMP Agent Default Community Name (public)

Synopsis

The community name of the remote SNMP server can be guessed.

Description

It is possible to obtain the default community name of the remote SNMP server.

An attacker may use this information to gain more knowledge about the remote host, or to change the configuration of the remote system (if the default community allows such modifications).

Solution

Disable the SNMP service on the remote host if you do not use it.

Either filter incoming UDP packets going to this port, or change the default community string.

Risk Factor

High

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.5 (CVSS2#E:U/RL:OF/RC:C)

References

BID	2112
CVE	CVE-1999-0517

Plugin Information

Published: 2002/11/25, Modified: 2022/06/01

Plugin Output

udp/161/snmp

```
The remote SNMP server replies to the following default community
string :

public
```

50686 - IP Forwarding Enabled

Synopsis

The remote host has IP forwarding enabled.

Description

The remote host has IP forwarding enabled. An attacker can exploit this to route packets through the host and potentially bypass some firewalls / routers / NAC filtering.

Unless the remote host is a router, it is recommended that you disable IP forwarding.

Solution

On Linux, you can disable IP forwarding by doing :

```
echo 0 > /proc/sys/net/ipv4/ip_forward
```

On Windows, set the key 'IPEnableRouter' to 0 under

HKEY_LOCAL_MACHINE\System\CurrentControlSet\Services\Tcpip\Parameters

On Mac OS X, you can disable IP forwarding by executing the command :

```
sysctl -w net.inet.ip.forwarding=0
```

For other systems, check with your vendor.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:A/AC:L/PR:L/UI:N/S:C/C:L/I:L/A:L)

CVSS v2.0 Base Score

5.8 (CVSS2#AV:A/AC:L/Au:N/C:P/I:P/A:P)

References

CVE CVE-1999-0511

Plugin Information

Published: 2010/11/23, Modified: 2023/10/17

Plugin Output

tcp/0

IP forwarding appears to be enabled on the remote host.

Detected local MAC Address : e68cc3441691
Response from local MAC Address : e68cc3441691

Detected Gateway MAC Address : e2666d53494e
Response from Gateway MAC Address : e2666d53494e

76474 - SNMP 'GETBULK' Reflection DDoS

Synopsis

The remote SNMP daemon is affected by a vulnerability that allows a reflected distributed denial of service attack.

Description

The remote SNMP daemon is responding with a large amount of data to a 'GETBULK' request with a larger than normal value for 'max-repetitions'. A remote attacker can use this SNMP server to conduct a reflected distributed denial of service attack on an arbitrary remote host.

See Also

<http://www.nessus.org/u?8b551b5c>

Solution

Disable the SNMP service on the remote host if you do not use it.

Otherwise, restrict and monitor access to this service, and consider changing the default 'public' community string.

Risk Factor

Medium

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

References

CVE CVE-2008-4309

Plugin Information

Published: 2014/07/11, Modified: 2023/11/08

Plugin Output

udp/161/snmp

Nessus was able to determine the SNMP service can be abused in an SNMP
Reflection DDoS attack :

Request size (bytes) : 42
Response size (bytes) : 1332

10114 - ICMP Timestamp Request Remote Date Disclosure

Synopsis

It is possible to determine the exact time set on the remote host.

Description

The remote host answers to an ICMP timestamp request. This allows an attacker to know the date that is set on the targeted machine, which may assist an unauthenticated, remote attacker in defeating time-based authentication protocols.

Timestamps returned from machines running Windows Vista / 7 / 2008 / 2008 R2 are deliberately incorrect, but usually within 1000 seconds of the actual system time.

Solution

Filter out the ICMP timestamp requests (13), and the outgoing ICMP timestamp replies (14).

Risk Factor

Low

CVSS v2.0 Base Score

2.1 (CVSS2#AV:L/AC:L/Au:N/C:P/I:N/A:N)

References

CVE	CVE-1999-0524
XREF	CWE:200

Plugin Information

Published: 1999/08/01, Modified: 2024/10/07

Plugin Output

icmp/0

```
The remote clock is synchronized with the local clock.
```


45590 - Common Platform Enumeration (CPE)

Synopsis

It was possible to enumerate CPE names that matched on the remote system.

Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

See Also

<http://cpe.mitre.org/>

<https://nvd.nist.gov/products/cpe>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/04/21, Modified: 2026/06/16

Plugin Output

tcp/0

The remote operating system matched the following CPE :

cpe:/o:linux:linux_kernel -> Linux Kernel

54615 - Device Type

Synopsis

It is possible to guess the remote device type.

Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/05/23, Modified: 2025/03/12

Plugin Output

tcp/0

```
Remote device type : general-purpose  
Confidence level : 98
```

86420 - Ethernet MAC Addresses

Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/10/16, Modified: 2025/06/10

Plugin Output

tcp/0

The following is a consolidated list of detected MAC addresses:
- E2:66:6D:53:49:4E

12053 - Host Fully Qualified Domain Name (FQDN) Resolution

Synopsis

It was possible to resolve the name of the remote host.

Description

Nessus was able to resolve the fully qualified domain name (FQDN) of the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/02/11, Modified: 2025/03/13

Plugin Output

tcp/0

```
172.30.30.1 resolves as snmpd.labvulnerabilities_vulnnet.
```

19506 - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2026/07/10

Plugin Output

tcp/0

Information about this scan :

```
Nessus version : 10.12.2
Nessus build : 20029
Plugin feed version : 202607231328
Scanner edition used : Nessus
Scanner OS : LINUX
Scanner distribution : ubuntu1604-x86-64
Scan type : Normal
Scan name : My Basic Network Scan
```

Scan policy used : Basic Network Scan
Scanner IP : 172.30.0.2
Port scanner(s) : nessus_syn_scanner
Port range : default
Ping RTT : 84.091 ms
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Assess component installs : yes
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 30
Max checks : 4
Recv timeout : 5
Backports : None
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2026/7/23 18:30 EDT (UTC -04:00)
Scan duration : 85 sec
Scan for malware : no
Fully Scan Operational Technology devices : no
Safely Scan Operational Technology devices with OT Discovery : no

209654 - OS Fingerprints Detected

Synopsis

Multiple OS fingerprints were detected.

Description

Using a combination of remote probes (TCP/IP, SMB, HTTP, NTP, SNMP, etc), it was possible to gather one or more fingerprints from the remote system. While the highest-confidence result was reported in plugin 11936, "OS Identification", the complete set of fingerprints detected are reported here.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/02/26, Modified: 2025/03/03

Plugin Output

tcp/0

Following OS Fingerprints were found

Remote operating system : Linux Kernel 7.0.0-28-generic

Confidence level : 98

Method : SNMP

Type : general-purpose

Fingerprint : SNMP:Linux 8233b64ee13e 7.0.0-28-generic #28-Ubuntu SMP PREEMPT_DYNAMIC Sun Jun 21 01:01:36 UTC 2026 x86_64

11936 - OS Identification

Synopsis

It is possible to guess the remote operating system.

Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2003/12/09, Modified: 2025/06/03

Plugin Output

tcp/0

```
Remote operating system : Linux Kernel 7.0.0-28-generic  
Confidence level : 98  
Method : SNMP
```

```
The remote host is running Linux Kernel 7.0.0-28-generic
```


35296 - SNMP Protocol Version Detection

Synopsis

This plugin reports the protocol version negotiated with the remote SNMP agent.

Description

By sending an SNMP 'get-next-request', it is possible to determine the protocol version of the remote SNMP agent.

See Also

https://en.wikipedia.org/wiki/Simple_Network_Management_Protocol

Solution

Disable the SNMP service on the remote host if you do not use it, or filter incoming UDP packets going to this port.

Risk Factor

None

Plugin Information

Published: 2009/01/06, Modified: 2019/11/22

Plugin Output

udp/161/snmp

```
Nessus has negotiated SNMP communications at SNMPv2c.
```

10800 - SNMP Query System Information Disclosure

Synopsis

The System Information of the remote host can be obtained via SNMP.

Description

It is possible to obtain the system information about the remote host by sending SNMP requests with the OID 1.3.6.1.2.1.1.1.

An attacker may use this information to gain more knowledge about the target host.

Solution

Disable the SNMP service on the remote host if you do not use it, or filter incoming UDP packets going to this port.

Risk Factor

None

Plugin Information

Published: 2001/11/06, Modified: 2026/02/17

Plugin Output

udp/161/snmp

```
System information :
sysDescr      : Linux 8233b64ee13e 7.0.0-28-generic #28-Ubuntu SMP PREEMPT_DYNAMIC Sun Jun 21
01:01:36 UTC 2026 x86_64
sysObjectID   : 1.3.6.1.4.1.8072.3.2.10
sysUptime     : 0d 0h 12m 37s
sysContact    : Root <root@localhost> (configure /etc/snmp/snmp.local.conf)
sysName       : 8233b64ee13e
sysLocation   : Unknown (edit /etc/snmp/snmpd.conf)
sysServices   :
```

185519 - SNMP Server Detection

Synopsis

An SNMP server is listening on the remote host.

Description

The remote service is an SNMP agent which provides management data about the device.

See Also

https://en.wikipedia.org/wiki/Simple_Network_Management_Protocol

Solution

Disable this service if it is not needed or restrict access to internal hosts only if the service is available externally.

Risk Factor

None

Plugin Information

Published: 2023/11/14, Modified: 2026/02/17

Plugin Output

udp/161/snmp

```
Nessus detected the following SNMP versions:
- SNMPv1 (public community)
- SNMPv1 (configured community)
- SNMPv2c (public community)
- SNMPv2c (configured community)
- SNMPv3
```

40448 - SNMP Supported Protocols Detection

Synopsis

This plugin reports all the protocol versions successfully negotiated with the remote SNMP agent.

Description

Extend the SNMP settings data already gathered by testing for\ SNMP versions other than the highest negotiated.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/07/31, Modified: 2026/02/17

Plugin Output

udp/161/snmp

Nessus detected the following SNMP versions:

- SNMPv2c
- SNMPv1
- SNMPv3

10287 - Traceroute Information

Synopsis

It was possible to obtain traceroute information.

Description

Makes a traceroute to the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/11/27, Modified: 2026/04/27

Plugin Output

udp/0

```
For your information, here is the traceroute from 172.30.0.2 to 172.30.30.1 :
172.30.0.2
172.30.30.1

Hop Count: 1
```

172.30.40.7



Scan Information

Start time: Thu Jul 23 18:30:17 2026

End time: Thu Jul 23 18:37:12 2026

Host Information

IP: 172.30.40.7

MAC Address: 1E:F4:51:19:D7:F5

OS: SuSE Linux

Vulnerabilities

88098 - Apache Server ETag Header Information Disclosure

Synopsis

The remote web server is affected by an information disclosure vulnerability.

Description

The remote web server is affected by an information disclosure vulnerability due to the ETag header providing sensitive information that could aid an attacker, such as the inode number of requested files.

See Also

<http://httpd.apache.org/docs/2.2/mod/core.html#FileETag>

Solution

Modify the HTTP ETag header of the web server to not include file inodes in the ETag header calculation. Refer to the linked Apache documentation for more information.

Risk Factor

Medium

CVSS v3.0 Base Score

172.30.40.7

398

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.2 (CVSS2#E:U/RL:OF/RC:C)

References

BID	6939
CVE	CVE-2003-1418
XREF	CWE:200

Plugin Information

Published: 2016/01/22, Modified: 2025/02/11

Plugin Output

tcp/80/www

Nessus was able to determine that the Apache Server listening on port 80 leaks the servers inode numbers in the ETag HTTP Header field :

Source	: ETag: "ca6bdb-e2-55ccb691a48c0"
Inode number	: 13265883
File size	: 226 bytes
File modification time	: Oct. 30, 2017 at 22:46:35 GMT

50686 - IP Forwarding Enabled

Synopsis

The remote host has IP forwarding enabled.

Description

The remote host has IP forwarding enabled. An attacker can exploit this to route packets through the host and potentially bypass some firewalls / routers / NAC filtering.

Unless the remote host is a router, it is recommended that you disable IP forwarding.

Solution

On Linux, you can disable IP forwarding by doing :

```
echo 0 > /proc/sys/net/ipv4/ip_forward
```

On Windows, set the key 'IPEnableRouter' to 0 under

HKEY_LOCAL_MACHINE\System\CurrentControlSet\Services\Tcpip\Parameters

On Mac OS X, you can disable IP forwarding by executing the command :

```
sysctl -w net.inet.ip.forwarding=0
```

For other systems, check with your vendor.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:A/AC:L/PR:L/UI:N/S:C/C:L/I:L/A:L)

CVSS v2.0 Base Score

5.8 (CVSS2#AV:A/AC:L/Au:N/C:P/I:P/A:P)

References

CVE CVE-1999-0511

Plugin Information

Published: 2010/11/23, Modified: 2023/10/17

Plugin Output

tcp/0

IP forwarding appears to be enabled on the remote host.

Detected local MAC Address : e68cc3441691
Response from local MAC Address : e68cc3441691

Detected Gateway MAC Address : 1ef45119d7f5
Response from Gateway MAC Address : 1ef45119d7f5

10114 - ICMP Timestamp Request Remote Date Disclosure

Synopsis

It is possible to determine the exact time set on the remote host.

Description

The remote host answers to an ICMP timestamp request. This allows an attacker to know the date that is set on the targeted machine, which may assist an unauthenticated, remote attacker in defeating time-based authentication protocols.

Timestamps returned from machines running Windows Vista / 7 / 2008 / 2008 R2 are deliberately incorrect, but usually within 1000 seconds of the actual system time.

Solution

Filter out the ICMP timestamp requests (13), and the outgoing ICMP timestamp replies (14).

Risk Factor

Low

CVSS v2.0 Base Score

2.1 (CVSS2#AV:L/AC:L/Au:N/C:P/I:N/A:N)

References

CVE	CVE-1999-0524
XREF	CWE:200

Plugin Information

Published: 1999/08/01, Modified: 2024/10/07

Plugin Output

icmp/0

```
The remote clock is synchronized with the local clock.
```

18261 - Apache Banner Linux Distribution Disclosure

Synopsis

The name of the Linux distribution running on the remote host was found in the banner of the web server.

Description

Nessus was able to extract the banner of the Apache web server and determine which Linux distribution the remote host is running.

Solution

If you do not wish to display this information, edit 'httpd.conf' and set the directive 'ServerTokens Prod' and restart Apache.

Risk Factor

None

Plugin Information

Published: 2005/05/15, Modified: 2025/03/31

Plugin Output

tcp/0

```
The Linux distribution detected was :  
- Debian 7.0 (wheezy)  
- Debian unstable (sid)  
- Debian testing (wheezy)
```

48204 - Apache HTTP Server Version

Synopsis

It is possible to obtain the version number of the remote Apache HTTP server.

Description

The remote host is running the Apache HTTP Server, an open source web server. It was possible to read the version number from the banner.

See Also

<https://httpd.apache.org/>

Solution

n/a

Risk Factor

None

References

XREF	IAVT:0001-T-0030
XREF	IAVT:0001-T-0530

Plugin Information

Published: 2010/07/30, Modified: 2026/01/22

Plugin Output

tcp/80/www

```
URL      : http://172.30.40.7/
Version  : 2.2.22
Source   : Server: Apache/2.2.22 (Debian)
backported : 1
os       : Debian
```

39521 - Backported Security Patch Detection (WWW)

Synopsis

Security patches are backported.

Description

Security patches may have been 'backported' to the remote HTTP server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/06/25, Modified: 2026/01/22

Plugin Output

tcp/80/www

Give Nessus credentials to perform local checks.

45590 - Common Platform Enumeration (CPE)

Synopsis

It was possible to enumerate CPE names that matched on the remote system.

Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

See Also

<http://cpe.mitre.org/>

<https://nvd.nist.gov/products/cpe>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/04/21, Modified: 2026/06/16

Plugin Output

tcp/0

Following application CPE matched on the remote system :

cpe:/a:apache:http_server:2.2.22 -> Apache Software Foundation Apache HTTP Server

54615 - Device Type

Synopsis

It is possible to guess the remote device type.

Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/05/23, Modified: 2025/03/12

Plugin Output

tcp/0

Remote device type : unknown
Confidence level : 56

86420 - Ethernet MAC Addresses

Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/10/16, Modified: 2025/06/10

Plugin Output

tcp/0

The following is a consolidated list of detected MAC addresses:
- 1E:F4:51:19:D7:F5

43111 - HTTP Methods Allowed (per directory)

Synopsis

This plugin determines which HTTP methods are allowed on various CGI directories.

Description

By calling the OPTIONS method, it is possible to determine which HTTP methods are allowed on each directory.

The following HTTP methods are considered insecure:

PUT, DELETE, CONNECT, TRACE, HEAD

Many frameworks and languages treat 'HEAD' as a 'GET' request, albeit one without any body in the response. If a security constraint was set on 'GET' requests such that only 'authenticatedUsers' could access GET requests for a particular servlet or resource, it would be bypassed for the 'HEAD' version. This allowed unauthorized blind submission of any privileged GET request.

As this list may be incomplete, the plugin also tests - if 'Thorough tests' are enabled or 'Enable web applications tests' is set to 'yes'

in the scan policy - various known HTTP methods on each directory and considers them as unsupported if it receives a response code of 400, 403, 405, or 501.

Note that the plugin output is only informational and does not necessarily indicate the presence of any security vulnerabilities.

See Also

<http://www.nessus.org/u?d9c03a9a>

<http://www.nessus.org/u?b019cbdb>

[https://www.owasp.org/index.php/Test_HTTP_Methods_\(OTG-CONFIG-006\)](https://www.owasp.org/index.php/Test_HTTP_Methods_(OTG-CONFIG-006))

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/12/10, Modified: 2022/04/11

Plugin Output

tcp/80/www

Based on the response to an OPTIONS request :

- HTTP methods GET HEAD OPTIONS POST are allowed on :

/

10107 - HTTP Server Type and Version

Synopsis

A web server is running on the remote host.

Description

This plugin attempts to determine the type and the version of the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0931

Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

Plugin Output

tcp/80/www

```
The remote web server type is :  
Apache/2.2.22 (Debian)
```

12053 - Host Fully Qualified Domain Name (FQDN) Resolution

Synopsis

It was possible to resolve the name of the remote host.

Description

Nessus was able to resolve the fully qualified domain name (FQDN) of the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/02/11, Modified: 2025/03/13

Plugin Output

tcp/0

```
172.30.40.7 resolves as shellshock-lab.labvulnerabilities_vulnnet.
```

24260 - HyperText Transfer Protocol (HTTP) Information

Synopsis

Some information about the remote HTTP configuration can be extracted.

Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

Plugin Output

tcp/80/www

Response Code : HTTP/1.1 200 OK

Protocol version : HTTP/1.1

HTTP/2 TLS Support: No

HTTP/2 Cleartext Support: No

SSL : no

Keep-Alive : yes

Options allowed : (Not implemented)

Headers :

Date: Thu, 23 Jul 2026 22:31:13 GMT

Server: Apache/2.2.22 (Debian)

Last-Modified: Mon, 30 Oct 2017 22:46:35 GMT

ETag: "ca6bdb-e2-55ccb691a48c0"

Accept-Ranges: bytes

Content-Length: 226

Vary: Accept-Encoding

Keep-Alive: timeout=5, max=98

Connection: Keep-Alive

Content-Type: text/html

Response Body :

<html>

<head><title>Vulnerables | ShellShock</title></head>

<body>

<h1>This image is vulnerable to ShellShock, please exploit it</h1>

```
<pre>The script is at /cgi-bin/vulnerable</pre>
</body>
</html>
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/80/www

```
Port 80/tcp was found to be open
```

19506 - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2026/07/10

Plugin Output

tcp/0

Information about this scan :

```
Nessus version : 10.12.2
Nessus build : 20029
Plugin feed version : 202607231328
Scanner edition used : Nessus
Scanner OS : LINUX
Scanner distribution : ubuntu1604-x86-64
Scan type : Normal
Scan name : My Basic Network Scan
```



```
Scan policy used : Basic Network Scan
Scanner IP : 172.30.0.2
Port scanner(s) : nessus_syn_scanner
Port range : default
Ping RTT : 79.685 ms
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Assess component installs : yes
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 30
Max checks : 4
Recv timeout : 5
Backports : Detected
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2026/7/23 18:30 EDT (UTC -04:00)
Scan duration : 411 sec
Scan for malware : no
Fully Scan Operational Technology devices : no
Safely Scan Operational Technology devices with OT Discovery : no
```

209654 - OS Fingerprints Detected

Synopsis

Multiple OS fingerprints were detected.

Description

Using a combination of remote probes (TCP/IP, SMB, HTTP, NTP, SNMP, etc), it was possible to gather one or more fingerprints from the remote system. While the highest-confidence result was reported in plugin 11936, "OS Identification", the complete set of fingerprints detected are reported here.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/02/26, Modified: 2025/03/03

Plugin Output

tcp/0

Following OS Fingerprints were found

Remote operating system : SuSE Linux
Confidence level : 56
Method : MLSinFP
Type : unknown
Fingerprint : unknown

Remote operating system : Linux Kernel 3.2 on Debian 7.0 (wheezy)
Debian unstable (sid)
Debian testing (wheezy)
Confidence level : 45
Method : HTTP
Type : general-purpose
Fingerprint : unknown

Remote operating system : Linux Kernel 2.x
Confidence level : 54
Method : SinFP
Type : general-purpose
Fingerprint : SinFP:
P1:B10113:F0x12:W64240:00204ffff:M1460:
P2:B10113:F0x12:W65160:00204ffff0402080affffff444541440103030a:M1460:
P3:B00000:F0x00:W0:00:M0
P4:191802_7_p=80

11936 - OS Identification

Synopsis

It is possible to guess the remote operating system.

Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2003/12/09, Modified: 2025/06/03

Plugin Output

tcp/0

```
Remote operating system : SuSE Linux
Confidence level : 56
Method : MLSinFP
```

```
The remote host is running SuSE Linux
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/80/www

```
A web server is running on this port.
```

25220 - TCP/IP Timestamps Supported

Synopsis

The remote service implements TCP timestamps.

Description

The remote host implements TCP timestamps, as defined by RFC1323. A side effect of this feature is that the uptime of the remote host can sometimes be computed.

See Also

<http://www.ietf.org/rfc/rfc1323.txt>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2023/10/17

Plugin Output

tcp/0

10287 - Traceroute Information

Synopsis

It was possible to obtain traceroute information.

Description

Makes a traceroute to the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/11/27, Modified: 2026/04/27

Plugin Output

udp/0

```
For your information, here is the traceroute from 172.30.0.2 to 172.30.40.7 :  
172.30.0.2  
172.30.40.7
```

```
Hop Count: 1
```

172.30.40.8



Scan Information

Start time: Thu Jul 23 18:30:17 2026

End time: Thu Jul 23 18:43:16 2026

Host Information

IP: 172.30.40.8

MAC Address: 12:E4:4C:BD:67:91

OS: SuSE Linux

Vulnerabilities

88098 - Apache Server ETag Header Information Disclosure

Synopsis

The remote web server is affected by an information disclosure vulnerability.

Description

The remote web server is affected by an information disclosure vulnerability due to the ETag header providing sensitive information that could aid an attacker, such as the inode number of requested files.

See Also

<http://httpd.apache.org/docs/2.2/mod/core.html#FileETag>

Solution

Modify the HTTP ETag header of the web server to not include file inodes in the ETag header calculation. Refer to the linked Apache documentation for more information.

Risk Factor

Medium

CVSS v3.0 Base Score

172.30.40.8

423

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.2 (CVSS2#E:U/RL:OF/RC:C)

References

BID	6939
CVE	CVE-2003-1418
XREF	CWE:200

Plugin Information

Published: 2016/01/22, Modified: 2025/02/11

Plugin Output

tcp/80/www

Nessus was able to determine that the Apache Server listening on port 80 leaks the servers inode numbers in the ETag HTTP Header field :

Source	: ETag: "cc1c4a-ab-6574d0bc5b3ea"
Inode number	: 13376586
File size	: 171 bytes
File modification time	: Jul. 23, 2026 at 20:24:41 GMT

88098 - Apache Server ETag Header Information Disclosure

Synopsis

The remote web server is affected by an information disclosure vulnerability.

Description

The remote web server is affected by an information disclosure vulnerability due to the ETag header providing sensitive information that could aid an attacker, such as the inode number of requested files.

See Also

<http://httpd.apache.org/docs/2.2/mod/core.html#FileETag>

Solution

Modify the HTTP ETag header of the web server to not include file inodes in the ETag header calculation. Refer to the linked Apache documentation for more information.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.2 (CVSS2#E:U/RL:OF/RC:C)

References

BID	6939
CVE	CVE-2003-1418
XREF	CWE:200

Plugin Information

Plugin Output

tcp/443/www

Nessus was able to determine that the Apache Server listening on port 443 leaks the servers inode numbers in the ETag HTTP Header field :

Source	: ETag: "cc1c4a-ab-6574d0bc5b3ea"
Inode number	: 13376586
File size	: 171 bytes
File modification time	: Jul. 23, 2026 at 20:24:41 GMT

50686 - IP Forwarding Enabled

Synopsis

The remote host has IP forwarding enabled.

Description

The remote host has IP forwarding enabled. An attacker can exploit this to route packets through the host and potentially bypass some firewalls / routers / NAC filtering.

Unless the remote host is a router, it is recommended that you disable IP forwarding.

Solution

On Linux, you can disable IP forwarding by doing :

```
echo 0 > /proc/sys/net/ipv4/ip_forward
```

On Windows, set the key 'IPEnableRouter' to 0 under

HKEY_LOCAL_MACHINE\System\CurrentControlSet\Services\Tcpip\Parameters

On Mac OS X, you can disable IP forwarding by executing the command :

```
sysctl -w net.inet.ip.forwarding=0
```

For other systems, check with your vendor.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:A/AC:L/PR:L/UI:N/S:C/C:L/I:L/A:L)

CVSS v2.0 Base Score

5.8 (CVSS2#AV:A/AC:L/Au:N/C:P/I:P/A:P)

References

CVE CVE-1999-0511

Plugin Information

Published: 2010/11/23, Modified: 2023/10/17

Plugin Output

tcp/0

IP forwarding appears to be enabled on the remote host.

Detected local MAC Address : e68cc3441691
Response from local MAC Address : e68cc3441691

Detected Gateway MAC Address : 12e44cbd6791
Response from Gateway MAC Address : 12e44cbd6791

10114 - ICMP Timestamp Request Remote Date Disclosure

Synopsis

It is possible to determine the exact time set on the remote host.

Description

The remote host answers to an ICMP timestamp request. This allows an attacker to know the date that is set on the targeted machine, which may assist an unauthenticated, remote attacker in defeating time-based authentication protocols.

Timestamps returned from machines running Windows Vista / 7 / 2008 / 2008 R2 are deliberately incorrect, but usually within 1000 seconds of the actual system time.

Solution

Filter out the ICMP timestamp requests (13), and the outgoing ICMP timestamp replies (14).

Risk Factor

Low

CVSS v2.0 Base Score

2.1 (CVSS2#AV:L/AC:L/Au:N/C:P/I:N/A:N)

References

CVE	CVE-1999-0524
XREF	CWE:200

Plugin Information

Published: 1999/08/01, Modified: 2024/10/07

Plugin Output

icmp/0

```
The remote clock is synchronized with the local clock.
```

18261 - Apache Banner Linux Distribution Disclosure

Synopsis

The name of the Linux distribution running on the remote host was found in the banner of the web server.

Description

Nessus was able to extract the banner of the Apache web server and determine which Linux distribution the remote host is running.

Solution

If you do not wish to display this information, edit 'httpd.conf' and set the directive 'ServerTokens Prod' and restart Apache.

Risk Factor

None

Plugin Information

Published: 2005/05/15, Modified: 2025/03/31

Plugin Output

tcp/0

```
The Linux distribution detected was :  
- Debian 7.0 (wheezy)  
- Debian unstable (sid)  
- Debian testing (wheezy)
```

48204 - Apache HTTP Server Version

Synopsis

It is possible to obtain the version number of the remote Apache HTTP server.

Description

The remote host is running the Apache HTTP Server, an open source web server. It was possible to read the version number from the banner.

See Also

<https://httpd.apache.org/>

Solution

n/a

Risk Factor

None

References

XREF	IAVT:0001-T-0030
XREF	IAVT:0001-T-0530

Plugin Information

Published: 2010/07/30, Modified: 2026/01/22

Plugin Output

tcp/80/www

```
URL      : http://172.30.40.8/
Version  : 2.2.22
Source   : Server: Apache/2.2.22 (Debian)
backported : 1
os       : Debian
```

48204 - Apache HTTP Server Version

Synopsis

It is possible to obtain the version number of the remote Apache HTTP server.

Description

The remote host is running the Apache HTTP Server, an open source web server. It was possible to read the version number from the banner.

See Also

<https://httpd.apache.org/>

Solution

n/a

Risk Factor

None

References

XREF	IAVT:0001-T-0030
XREF	IAVT:0001-T-0530

Plugin Information

Published: 2010/07/30, Modified: 2026/01/22

Plugin Output

tcp/443/www

```
URL      : http://172.30.40.8:443/
Version  : 2.2.22
Source   : Server: Apache/2.2.22 (Debian)
backported : 1
os       : Debian
```


39521 - Backported Security Patch Detection (WWW)

Synopsis

Security patches are backported.

Description

Security patches may have been 'backported' to the remote HTTP server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/06/25, Modified: 2026/01/22

Plugin Output

tcp/80/www

Give Nessus credentials to perform local checks.

39521 - Backported Security Patch Detection (WWW)

Synopsis

Security patches are backported.

Description

Security patches may have been 'backported' to the remote HTTP server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/06/25, Modified: 2026/01/22

Plugin Output

tcp/443/www

Give Nessus credentials to perform local checks.

45590 - Common Platform Enumeration (CPE)

Synopsis

It was possible to enumerate CPE names that matched on the remote system.

Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

See Also

<http://cpe.mitre.org/>

<https://nvd.nist.gov/products/cpe>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/04/21, Modified: 2026/06/16

Plugin Output

tcp/0

Following application CPE matched on the remote system :

cpe:/a:apache:http_server:2.2.22 -> Apache Software Foundation Apache HTTP Server

54615 - Device Type

Synopsis

It is possible to guess the remote device type.

Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/05/23, Modified: 2025/03/12

Plugin Output

tcp/0

```
Remote device type : unknown  
Confidence level : 56
```

86420 - Ethernet MAC Addresses

Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/10/16, Modified: 2025/06/10

Plugin Output

tcp/0

The following is a consolidated list of detected MAC addresses:
- 12:E4:4C:BD:67:91

43111 - HTTP Methods Allowed (per directory)

Synopsis

This plugin determines which HTTP methods are allowed on various CGI directories.

Description

By calling the OPTIONS method, it is possible to determine which HTTP methods are allowed on each directory.

The following HTTP methods are considered insecure:

PUT, DELETE, CONNECT, TRACE, HEAD

Many frameworks and languages treat 'HEAD' as a 'GET' request, albeit one without any body in the response. If a security constraint was set on 'GET' requests such that only 'authenticatedUsers' could access GET requests for a particular servlet or resource, it would be bypassed for the 'HEAD' version. This allowed unauthorized blind submission of any privileged GET request.

As this list may be incomplete, the plugin also tests - if 'Thorough tests' are enabled or 'Enable web applications tests' is set to 'yes'

in the scan policy - various known HTTP methods on each directory and considers them as unsupported if it receives a response code of 400, 403, 405, or 501.

Note that the plugin output is only informational and does not necessarily indicate the presence of any security vulnerabilities.

See Also

<http://www.nessus.org/u?d9c03a9a>

<http://www.nessus.org/u?b019cbdb>

[https://www.owasp.org/index.php/Test_HTTP_Methods_\(OTG-CONFIG-006\)](https://www.owasp.org/index.php/Test_HTTP_Methods_(OTG-CONFIG-006))

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/12/10, Modified: 2022/04/11

Plugin Output

tcp/80/www

Based on the response to an OPTIONS request :

- HTTP methods GET HEAD OPTIONS POST are allowed on :

/

43111 - HTTP Methods Allowed (per directory)

Synopsis

This plugin determines which HTTP methods are allowed on various CGI directories.

Description

By calling the OPTIONS method, it is possible to determine which HTTP methods are allowed on each directory.

The following HTTP methods are considered insecure:

PUT, DELETE, CONNECT, TRACE, HEAD

Many frameworks and languages treat 'HEAD' as a 'GET' request, albeit one without any body in the response. If a security constraint was set on 'GET' requests such that only 'authenticatedUsers' could access GET requests for a particular servlet or resource, it would be bypassed for the 'HEAD' version. This allowed unauthorized blind submission of any privileged GET request.

As this list may be incomplete, the plugin also tests - if 'Thorough tests' are enabled or 'Enable web applications tests' is set to 'yes'

in the scan policy - various known HTTP methods on each directory and considers them as unsupported if it receives a response code of 400, 403, 405, or 501.

Note that the plugin output is only informational and does not necessarily indicate the presence of any security vulnerabilities.

See Also

<http://www.nessus.org/u?d9c03a9a>

<http://www.nessus.org/u?b019cbdb>

[https://www.owasp.org/index.php/Test_HTTP_Methods_\(OTG-CONFIG-006\)](https://www.owasp.org/index.php/Test_HTTP_Methods_(OTG-CONFIG-006))

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/12/10, Modified: 2022/04/11

Plugin Output

tcp/443/www

Based on the response to an OPTIONS request :

- HTTP methods GET HEAD OPTIONS POST are allowed on :

/

10107 - HTTP Server Type and Version

Synopsis

A web server is running on the remote host.

Description

This plugin attempts to determine the type and the version of the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0931

Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

Plugin Output

tcp/80/www

```
The remote web server type is :  
Apache/2.2.22 (Debian)
```

10107 - HTTP Server Type and Version

Synopsis

A web server is running on the remote host.

Description

This plugin attempts to determine the type and the version of the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0931

Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

Plugin Output

tcp/443/www

```
The remote web server type is :  
Apache/2.2.22 (Debian)
```

12053 - Host Fully Qualified Domain Name (FQDN) Resolution

Synopsis

It was possible to resolve the name of the remote host.

Description

Nessus was able to resolve the fully qualified domain name (FQDN) of the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/02/11, Modified: 2025/03/13

Plugin Output

tcp/0

```
172.30.40.8 resolves as heartbleed-lab.labvulnerabilities_vulnnet.
```

24260 - HyperText Transfer Protocol (HTTP) Information

Synopsis

Some information about the remote HTTP configuration can be extracted.

Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

Plugin Output

tcp/80/www

Response Code : HTTP/1.1 200 OK

Protocol version : HTTP/1.1

HTTP/2 TLS Support: No

HTTP/2 Cleartext Support: No

SSL : no

Keep-Alive : yes

Options allowed : (Not implemented)

Headers :

Date: Thu, 23 Jul 2026 22:31:15 GMT

Server: Apache/2.2.22 (Debian)

Last-Modified: Thu, 23 Jul 2026 20:24:41 GMT

ETag: "cc1c4a-ab-6574d0bc5b3ea"

Accept-Ranges: bytes

Content-Length: 171

Vary: Accept-Encoding

Keep-Alive: timeout=5, max=98

Connection: Keep-Alive

Content-Type: text/html

Response Body :

<html>

<head><title>Vulnerables | HeartBleed</title></head>

<body>

<h1>This host is vulnerable to heartbleed, please exploit it</h1>

```
</body>  
</html>
```

24260 - HyperText Transfer Protocol (HTTP) Information

Synopsis

Some information about the remote HTTP configuration can be extracted.

Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

Plugin Output

tcp/443/www

Response Code : HTTP/1.1 200 OK

Protocol version : HTTP/1.1

HTTP/2 TLS Support: No

HTTP/2 Cleartext Support: No

SSL : no

Keep-Alive : yes

Options allowed : (Not implemented)

Headers :

Date: Thu, 23 Jul 2026 22:31:15 GMT

Server: Apache/2.2.22 (Debian)

Last-Modified: Thu, 23 Jul 2026 20:24:41 GMT

ETag: "cc1c4a-ab-6574d0bc5b3ea"

Accept-Ranges: bytes

Content-Length: 171

Vary: Accept-Encoding

Keep-Alive: timeout=5, max=98

Connection: Keep-Alive

Content-Type: text/html

Response Body :

<html>

<head><title>Vulnerables | HeartBleed</title></head>

<body>

<h1>This host is vulnerable to heartbleed, please exploit it</h1>

```
</body>  
</html>
```


Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/80/www

```
Port 80/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/443/www

```
Port 443/tcp was found to be open
```

19506 - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2026/07/10

Plugin Output

tcp/0

Information about this scan :

```
Nessus version : 10.12.2
Nessus build : 20029
Plugin feed version : 202607231328
Scanner edition used : Nessus
Scanner OS : LINUX
Scanner distribution : ubuntu1604-x86-64
Scan type : Normal
Scan name : My Basic Network Scan
```

Scan policy used : Basic Network Scan
Scanner IP : 172.30.0.2
Port scanner(s) : nessus_syn_scanner
Port range : default
Ping RTT : 77.606 ms
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Assess component installs : yes
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 30
Max checks : 4
Recv timeout : 5
Backports : Detected
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2026/7/23 18:30 EDT (UTC -04:00)
Scan duration : 775 sec
Scan for malware : no
Fully Scan Operational Technology devices : no
Safely Scan Operational Technology devices with OT Discovery : no

209654 - OS Fingerprints Detected

Synopsis

Multiple OS fingerprints were detected.

Description

Using a combination of remote probes (TCP/IP, SMB, HTTP, NTP, SNMP, etc), it was possible to gather one or more fingerprints from the remote system. While the highest-confidence result was reported in plugin 11936, "OS Identification", the complete set of fingerprints detected are reported here.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/02/26, Modified: 2025/03/03

Plugin Output

tcp/0

Following OS Fingerprints were found

Remote operating system : SuSE Linux
Confidence level : 56
Method : MLSinFP
Type : unknown
Fingerprint : unknown

Remote operating system : Linux Kernel 3.2 on Debian 7.0 (wheezy)
Debian unstable (sid)
Debian testing (wheezy)
Confidence level : 45
Method : HTTP
Type : general-purpose
Fingerprint : unknown

Remote operating system : Linux Kernel 2.x
Confidence level : 54
Method : SinFP
Type : general-purpose
Fingerprint : SinFP:
P1:B10113:F0x12:W64240:00204ffff:M1460:
P2:B10113:F0x12:W65160:00204ffff0402080affffff444541440103030a:M1460:
P3:B00000:F0x00:W0:00:M0
P4:191802_7_p=80

11936 - OS Identification

Synopsis

It is possible to guess the remote operating system.

Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2003/12/09, Modified: 2025/06/03

Plugin Output

tcp/0

```
Remote operating system : SuSE Linux
Confidence level : 56
Method : MLSinFP
```

```
The remote host is running SuSE Linux
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/80/www

```
A web server is running on this port.
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/443/www

```
A web server is running on this port.
```


25220 - TCP/IP Timestamps Supported

Synopsis

The remote service implements TCP timestamps.

Description

The remote host implements TCP timestamps, as defined by RFC1323. A side effect of this feature is that the uptime of the remote host can sometimes be computed.

See Also

<http://www.ietf.org/rfc/rfc1323.txt>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2023/10/17

Plugin Output

tcp/0

10287 - Traceroute Information

Synopsis

It was possible to obtain traceroute information.

Description

Makes a traceroute to the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/11/27, Modified: 2026/04/27

Plugin Output

udp/0

```
For your information, here is the traceroute from 172.30.0.2 to 172.30.40.8 :  
172.30.0.2  
172.30.40.8  
  
Hop Count: 1
```

172.31.1.1



Scan Information

Start time: Thu Jul 23 18:30:17 2026
End time: Thu Jul 23 18:31:55 2026

Host Information

IP: 172.31.1.1
MAC Address: 16:70:CA:4E:68:8A

Vulnerabilities

50686 - IP Forwarding Enabled

Synopsis

The remote host has IP forwarding enabled.

Description

The remote host has IP forwarding enabled. An attacker can exploit this to route packets through the host and potentially bypass some firewalls / routers / NAC filtering.

Unless the remote host is a router, it is recommended that you disable IP forwarding.

Solution

On Linux, you can disable IP forwarding by doing :

```
echo 0 > /proc/sys/net/ipv4/ip_forward
```

On Windows, set the key 'IPEnableRouter' to 0 under

HKEY_LOCAL_MACHINE\System\CurrentControlSet\Services\Tcpip\Parameters

On Mac OS X, you can disable IP forwarding by executing the command :

```
sysctl -w net.inet.ip.forwarding=0
```

For other systems, check with your vendor.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:A/AC:L/PR:L/UI:N/S:C/C:L/I:L/A:L)

CVSS v2.0 Base Score

5.8 (CVSS2#AV:A/AC:L/Au:N/C:P/I:P/A:P)

References

CVE CVE-1999-0511

Plugin Information

Published: 2010/11/23, Modified: 2023/10/17

Plugin Output

tcp/0

```
IP forwarding appears to be enabled on the remote host.
```

```
Detected local MAC Address      : e68cc3441691
Response from local MAC Address : e68cc3441691
```

```
Detected Gateway MAC Address    : 1670ca4e688a
Response from Gateway MAC Address : 1670ca4e688a
```

10114 - ICMP Timestamp Request Remote Date Disclosure

Synopsis

It is possible to determine the exact time set on the remote host.

Description

The remote host answers to an ICMP timestamp request. This allows an attacker to know the date that is set on the targeted machine, which may assist an unauthenticated, remote attacker in defeating time-based authentication protocols.

Timestamps returned from machines running Windows Vista / 7 / 2008 / 2008 R2 are deliberately incorrect, but usually within 1000 seconds of the actual system time.

Solution

Filter out the ICMP timestamp requests (13), and the outgoing ICMP timestamp replies (14).

Risk Factor

Low

CVSS v2.0 Base Score

2.1 (CVSS2#AV:L/AC:L/Au:N/C:P/I:N/A:N)

References

CVE	CVE-1999-0524
XREF	CWE:200

Plugin Information

Published: 1999/08/01, Modified: 2024/10/07

Plugin Output

icmp/0

```
The remote clock is synchronized with the local clock.
```

86420 - Ethernet MAC Addresses

Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/10/16, Modified: 2025/06/10

Plugin Output

tcp/0

The following is a consolidated list of detected MAC addresses:
- 16:70:CA:4E:68:8A

12053 - Host Fully Qualified Domain Name (FQDN) Resolution

Synopsis

It was possible to resolve the name of the remote host.

Description

Nessus was able to resolve the fully qualified domain name (FQDN) of the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/02/11, Modified: 2025/03/13

Plugin Output

tcp/0

```
172.31.1.1 resolves as ubuntu14.labvulnerabilities_vulnnet.
```

19506 - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2026/07/10

Plugin Output

tcp/0

Information about this scan :

```
Nessus version : 10.12.2
Nessus build : 20029
Plugin feed version : 202607231328
Scanner edition used : Nessus
Scanner OS : LINUX
Scanner distribution : ubuntu1604-x86-64
Scan type : Normal
Scan name : My Basic Network Scan
```


Scan policy used : Basic Network Scan
Scanner IP : 172.30.0.2
Port scanner(s) : nessus_syn_scanner
Port range : default
Ping RTT : 75.250 ms
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Assess component installs : yes
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 30
Max checks : 4
Recv timeout : 5
Backports : None
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2026/7/23 18:30 EDT (UTC -04:00)
Scan duration : 94 sec
Scan for malware : no
Fully Scan Operational Technology devices : no
Safely Scan Operational Technology devices with OT Discovery : no

10287 - Traceroute Information

Synopsis

It was possible to obtain traceroute information.

Description

Makes a traceroute to the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/11/27, Modified: 2026/04/27

Plugin Output

udp/0

```
For your information, here is the traceroute from 172.30.0.2 to 172.31.1.1 :
172.30.0.2
172.31.1.1

Hop Count: 1
```

172.31.1.3



Scan Information

Start time: Thu Jul 23 18:30:17 2026

End time: Thu Jul 23 18:31:55 2026

Host Information

IP: 172.31.1.3

MAC Address: 86:58:3E:F7:E0:BF

Vulnerabilities

50686 - IP Forwarding Enabled

Synopsis

The remote host has IP forwarding enabled.

Description

The remote host has IP forwarding enabled. An attacker can exploit this to route packets through the host and potentially bypass some firewalls / routers / NAC filtering.

Unless the remote host is a router, it is recommended that you disable IP forwarding.

Solution

On Linux, you can disable IP forwarding by doing :

```
echo 0 > /proc/sys/net/ipv4/ip_forward
```

On Windows, set the key 'IPEnableRouter' to 0 under

HKEY_LOCAL_MACHINE\System\CurrentControlSet\Services\Tcpip\Parameters

On Mac OS X, you can disable IP forwarding by executing the command :

```
sysctl -w net.inet.ip.forwarding=0
```

For other systems, check with your vendor.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:A/AC:L/PR:L/UI:N/S:C/C:L/I:L/A:L)

CVSS v2.0 Base Score

5.8 (CVSS2#AV:A/AC:L/Au:N/C:P/I:P/A:P)

References

CVE CVE-1999-0511

Plugin Information

Published: 2010/11/23, Modified: 2023/10/17

Plugin Output

tcp/0

```
IP forwarding appears to be enabled on the remote host.
```

```
Detected local MAC Address      : e68cc3441691
Response from local MAC Address : e68cc3441691
```

```
Detected Gateway MAC Address    : 86583ef7e0bf
Response from Gateway MAC Address : 86583ef7e0bf
```

10114 - ICMP Timestamp Request Remote Date Disclosure

Synopsis

It is possible to determine the exact time set on the remote host.

Description

The remote host answers to an ICMP timestamp request. This allows an attacker to know the date that is set on the targeted machine, which may assist an unauthenticated, remote attacker in defeating time-based authentication protocols.

Timestamps returned from machines running Windows Vista / 7 / 2008 / 2008 R2 are deliberately incorrect, but usually within 1000 seconds of the actual system time.

Solution

Filter out the ICMP timestamp requests (13), and the outgoing ICMP timestamp replies (14).

Risk Factor

Low

CVSS v2.0 Base Score

2.1 (CVSS2#AV:L/AC:L/Au:N/C:P/I:N/A:N)

References

CVE	CVE-1999-0524
XREF	CWE:200

Plugin Information

Published: 1999/08/01, Modified: 2024/10/07

Plugin Output

icmp/0

```
The remote clock is synchronized with the local clock.
```

86420 - Ethernet MAC Addresses

Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/10/16, Modified: 2025/06/10

Plugin Output

tcp/0

The following is a consolidated list of detected MAC addresses:
- 86:58:3E:F7:E0:BF

12053 - Host Fully Qualified Domain Name (FQDN) Resolution

Synopsis

It was possible to resolve the name of the remote host.

Description

Nessus was able to resolve the fully qualified domain name (FQDN) of the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/02/11, Modified: 2025/03/13

Plugin Output

tcp/0

```
172.31.1.3 resolves as debian8.labvulnerabilities_vulnnet.
```

19506 - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2026/07/10

Plugin Output

tcp/0

Information about this scan :

```
Nessus version : 10.12.2
Nessus build : 20029
Plugin feed version : 202607231328
Scanner edition used : Nessus
Scanner OS : LINUX
Scanner distribution : ubuntu1604-x86-64
Scan type : Normal
Scan name : My Basic Network Scan
```


Scan policy used : Basic Network Scan
Scanner IP : 172.30.0.2
Port scanner(s) : nessus_syn_scanner
Port range : default
Ping RTT : 73.214 ms
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Assess component installs : yes
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 30
Max checks : 4
Recv timeout : 5
Backports : None
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2026/7/23 18:30 EDT (UTC -04:00)
Scan duration : 94 sec
Scan for malware : no
Fully Scan Operational Technology devices : no
Safely Scan Operational Technology devices with OT Discovery : no

10287 - Traceroute Information

Synopsis

It was possible to obtain traceroute information.

Description

Makes a traceroute to the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/11/27, Modified: 2026/04/27

Plugin Output

udp/0

```
For your information, here is the traceroute from 172.30.0.2 to 172.31.1.3 :
172.30.0.2
172.31.1.3

Hop Count: 1
```

172.31.1.5



Scan Information

Start time: Thu Jul 23 18:30:17 2026

End time: Thu Jul 23 18:31:55 2026

Host Information

IP: 172.31.1.5

MAC Address: 16:44:84:DE:D6:36

Vulnerabilities

50686 - IP Forwarding Enabled

Synopsis

The remote host has IP forwarding enabled.

Description

The remote host has IP forwarding enabled. An attacker can exploit this to route packets through the host and potentially bypass some firewalls / routers / NAC filtering.

Unless the remote host is a router, it is recommended that you disable IP forwarding.

Solution

On Linux, you can disable IP forwarding by doing :

```
echo 0 > /proc/sys/net/ipv4/ip_forward
```

On Windows, set the key 'IPEnableRouter' to 0 under

HKEY_LOCAL_MACHINE\System\CurrentControlSet\Services\Tcpip\Parameters

On Mac OS X, you can disable IP forwarding by executing the command :

```
sysctl -w net.inet.ip.forwarding=0
```

For other systems, check with your vendor.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:A/AC:L/PR:L/UI:N/S:C/C:L/I:L/A:L)

CVSS v2.0 Base Score

5.8 (CVSS2#AV:A/AC:L/Au:N/C:P/I:P/A:P)

References

CVE CVE-1999-0511

Plugin Information

Published: 2010/11/23, Modified: 2023/10/17

Plugin Output

tcp/0

```
IP forwarding appears to be enabled on the remote host.
```

```
Detected local MAC Address      : e68cc3441691
Response from local MAC Address : e68cc3441691
```

```
Detected Gateway MAC Address    : 164484ded636
Response from Gateway MAC Address : 164484ded636
```

10114 - ICMP Timestamp Request Remote Date Disclosure

Synopsis

It is possible to determine the exact time set on the remote host.

Description

The remote host answers to an ICMP timestamp request. This allows an attacker to know the date that is set on the targeted machine, which may assist an unauthenticated, remote attacker in defeating time-based authentication protocols.

Timestamps returned from machines running Windows Vista / 7 / 2008 / 2008 R2 are deliberately incorrect, but usually within 1000 seconds of the actual system time.

Solution

Filter out the ICMP timestamp requests (13), and the outgoing ICMP timestamp replies (14).

Risk Factor

Low

CVSS v2.0 Base Score

2.1 (CVSS2#AV:L/AC:L/Au:N/C:P/I:N/A:N)

References

CVE	CVE-1999-0524
XREF	CWE:200

Plugin Information

Published: 1999/08/01, Modified: 2024/10/07

Plugin Output

icmp/0

```
The remote clock is synchronized with the local clock.
```

86420 - Ethernet MAC Addresses

Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/10/16, Modified: 2025/06/10

Plugin Output

tcp/0

The following is a consolidated list of detected MAC addresses:
- 16:44:84:DE:D6:36

12053 - Host Fully Qualified Domain Name (FQDN) Resolution

Synopsis

It was possible to resolve the name of the remote host.

Description

Nessus was able to resolve the fully qualified domain name (FQDN) of the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/02/11, Modified: 2025/03/13

Plugin Output

tcp/0

```
172.31.1.5 resolves as centos6.labvulnerabilities_vulnnet.
```

19506 - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2026/07/10

Plugin Output

tcp/0

Information about this scan :

```
Nessus version : 10.12.2
Nessus build : 20029
Plugin feed version : 202607231328
Scanner edition used : Nessus
Scanner OS : LINUX
Scanner distribution : ubuntu1604-x86-64
Scan type : Normal
Scan name : My Basic Network Scan
```


Scan policy used : Basic Network Scan
Scanner IP : 172.30.0.2
Port scanner(s) : nessus_syn_scanner
Port range : default
Ping RTT : 71.518 ms
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Assess component installs : yes
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 30
Max checks : 4
Recv timeout : 5
Backports : None
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2026/7/23 18:30 EDT (UTC -04:00)
Scan duration : 94 sec
Scan for malware : no
Fully Scan Operational Technology devices : no
Safely Scan Operational Technology devices with OT Discovery : no

10287 - Traceroute Information

Synopsis

It was possible to obtain traceroute information.

Description

Makes a traceroute to the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/11/27, Modified: 2026/04/27

Plugin Output

udp/0

```
For your information, here is the traceroute from 172.30.0.2 to 172.31.1.5 :
172.30.0.2
172.31.1.5

Hop Count: 1
```

172.31.1.50



Scan Information

Start time: Thu Jul 23 18:30:17 2026

End time: Thu Jul 23 18:37:09 2026

Host Information

IP: 172.31.1.50

MAC Address: 32:55:BE:CE:EF:F4

OS: Linux Kernel 5.x on Ubuntu

Vulnerabilities

50686 - IP Forwarding Enabled

Synopsis

The remote host has IP forwarding enabled.

Description

The remote host has IP forwarding enabled. An attacker can exploit this to route packets through the host and potentially bypass some firewalls / routers / NAC filtering.

Unless the remote host is a router, it is recommended that you disable IP forwarding.

Solution

On Linux, you can disable IP forwarding by doing :

```
echo 0 > /proc/sys/net/ipv4/ip_forward
```

On Windows, set the key 'IPEnableRouter' to 0 under

HKEY_LOCAL_MACHINE\System\CurrentControlSet\Services\Tcpip\Parameters

On Mac OS X, you can disable IP forwarding by executing the command :

```
sysctl -w net.inet.ip.forwarding=0
```

For other systems, check with your vendor.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:A/AC:L/PR:L/UI:N/S:C/C:L/I:L/A:L)

CVSS v2.0 Base Score

5.8 (CVSS2#AV:A/AC:L/Au:N/C:P/I:P/A:P)

References

CVE CVE-1999-0511

Plugin Information

Published: 2010/11/23, Modified: 2023/10/17

Plugin Output

tcp/0

```
IP forwarding appears to be enabled on the remote host.
```

```
Detected local MAC Address      : e68cc3441691
Response from local MAC Address : e68cc3441691
```

```
Detected Gateway MAC Address    : 3255beceeff4
Response from Gateway MAC Address : 3255beceeff4
```

10114 - ICMP Timestamp Request Remote Date Disclosure

Synopsis

It is possible to determine the exact time set on the remote host.

Description

The remote host answers to an ICMP timestamp request. This allows an attacker to know the date that is set on the targeted machine, which may assist an unauthenticated, remote attacker in defeating time-based authentication protocols.

Timestamps returned from machines running Windows Vista / 7 / 2008 / 2008 R2 are deliberately incorrect, but usually within 1000 seconds of the actual system time.

Solution

Filter out the ICMP timestamp requests (13), and the outgoing ICMP timestamp replies (14).

Risk Factor

Low

CVSS v2.0 Base Score

2.1 (CVSS2#AV:L/AC:L/Au:N/C:P/I:N/A:N)

References

CVE	CVE-1999-0524
XREF	CWE:200

Plugin Information

Published: 1999/08/01, Modified: 2024/10/07

Plugin Output

icmp/0

```
The remote clock is synchronized with the local clock.
```

45590 - Common Platform Enumeration (CPE)

Synopsis

It was possible to enumerate CPE names that matched on the remote system.

Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

See Also

<http://cpe.mitre.org/>

<https://nvd.nist.gov/products/cpe>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/04/21, Modified: 2026/06/16

Plugin Output

tcp/0

The remote operating system matched the following CPE :

cpe:/o:canonical:ubuntu_linux -> Canonical Ubuntu Linux

Following application CPE's matched on the remote system :

cpe:/a:eclipse:jetty:8.1.16 -> Eclipse Jetty

cpe:/a:sonatype:nexus:2.14.4-03 -> Sonatype Nexus

54615 - Device Type

Synopsis

It is possible to guess the remote device type.

Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/05/23, Modified: 2025/03/12

Plugin Output

tcp/0

Remote device type : unknown
Confidence level : 56

194915 - Eclipse Jetty Web Server Detection

Synopsis

The Eclipse Jetty web server was detected on the remote host.

Description

The Eclipse Jetty web server was detected on the remote host.

See Also

<https://eclipse.dev/jetty/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2024/05/02, Modified: 2026/03/23

Plugin Output

tcp/0

```
URL      : http://172.31.1.50:8081/  
Version  : 8.1.16  
Source   : Server: Jetty(8.1.16.v20140903)
```


86420 - Ethernet MAC Addresses

Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/10/16, Modified: 2025/06/10

Plugin Output

tcp/0

The following is a consolidated list of detected MAC addresses:
- 32:55:BE:CE:EF:F4

10107 - HTTP Server Type and Version

Synopsis

A web server is running on the remote host.

Description

This plugin attempts to determine the type and the version of the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0931

Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

Plugin Output

tcp/8081/www

```
The remote web server type is :  
Jetty(8.1.16.v20140903)
```

12053 - Host Fully Qualified Domain Name (FQDN) Resolution

Synopsis

It was possible to resolve the name of the remote host.

Description

Nessus was able to resolve the fully qualified domain name (FQDN) of the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/02/11, Modified: 2025/03/13

Plugin Output

tcp/0

```
172.31.1.50 resolves as nexus2.labvulnerabilities_vulnnet.
```

24260 - HyperText Transfer Protocol (HTTP) Information

Synopsis

Some information about the remote HTTP configuration can be extracted.

Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

Plugin Output

tcp/8081/www

Response Code : HTTP/1.1 404 Not Found

Protocol version : HTTP/1.1

HTTP/2 TLS Support: No

HTTP/2 Cleartext Support: No

SSL : no

Keep-Alive : no

Options allowed : (Not implemented)

Headers :

Date: Thu, 23 Jul 2026 22:31:10 GMT

Cache-Control: must-revalidate,no-cache,no-store

Content-Type: text/html;charset=ISO-8859-1

Content-Length: 1267

Server: Jetty(8.1.16.v20140903)

Response Body :

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/8081/www

```
Port 8081/tcp was found to be open
```

19506 - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2026/07/10

Plugin Output

tcp/0

Information about this scan :

```
Nessus version : 10.12.2
Nessus build : 20029
Plugin feed version : 202607231328
Scanner edition used : Nessus
Scanner OS : LINUX
Scanner distribution : ubuntu1604-x86-64
Scan type : Normal
Scan name : My Basic Network Scan
```

Scan policy used : Basic Network Scan
Scanner IP : 172.30.0.2
Port scanner(s) : nessus_syn_scanner
Port range : default
Ping RTT : 73.295 ms
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Assess component installs : yes
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 30
Max checks : 4
Recv timeout : 5
Backports : None
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2026/7/23 18:30 EDT (UTC -04:00)
Scan duration : 408 sec
Scan for malware : no
Fully Scan Operational Technology devices : no
Safely Scan Operational Technology devices with OT Discovery : no

209654 - OS Fingerprints Detected

Synopsis

Multiple OS fingerprints were detected.

Description

Using a combination of remote probes (TCP/IP, SMB, HTTP, NTP, SNMP, etc), it was possible to gather one or more fingerprints from the remote system. While the highest-confidence result was reported in plugin 11936, "OS Identification", the complete set of fingerprints detected are reported here.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/02/26, Modified: 2025/03/03

Plugin Output

tcp/0

Following OS Fingerprints were found

Remote operating system : Linux Kernel 5.x on Ubuntu
Confidence level : 56
Method : MLSinFP
Type : unknown
Fingerprint : unknown

Remote operating system : Linux Kernel 2.x
Confidence level : 54
Method : SinFP
Type : general-purpose
Fingerprint : SinFP:
P1:B10113:F0x12:W64240:00204ffff:M1460:
P2:B10113:F0x12:W65160:00204ffff0402080affffff444541440103030a:M1460:
P3:B00000:F0x00:W0:00:M0
P4:191802_7_p=8081

Following fingerprints could not be used to determine OS :
HTTP:!:Server: Jetty(8.1.16.v20140903)

11936 - OS Identification

Synopsis

It is possible to guess the remote operating system.

Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2003/12/09, Modified: 2025/06/03

Plugin Output

tcp/0

```
Remote operating system : Linux Kernel 5.x on Ubuntu  
Confidence level : 56  
Method : MLSinFP
```

```
The remote host is running Linux Kernel 5.x on Ubuntu
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/8081/www

```
A web server is running on this port.
```

92468 - Sonatype Nexus Repository Manager Detection

Synopsis

A Sonatype Nexus Repository Manager server application is running on the remote host.

Description

Sonatype Nexus Repository Manager, a software repository management application, is running on the remote host.

See Also

<https://www.sonatype.com/nexus-repository-sonatype>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2016/07/20, Modified: 2026/03/23

Plugin Output

tcp/8081/www

```
URL      : http://172.31.1.50:8081/nexus/index.html
Version  : 2.14.4-03
```

25220 - TCP/IP Timestamps Supported

Synopsis

The remote service implements TCP timestamps.

Description

The remote host implements TCP timestamps, as defined by RFC1323. A side effect of this feature is that the uptime of the remote host can sometimes be computed.

See Also

<http://www.ietf.org/rfc/rfc1323.txt>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2023/10/17

Plugin Output

tcp/0

10287 - Traceroute Information

Synopsis

It was possible to obtain traceroute information.

Description

Makes a traceroute to the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/11/27, Modified: 2026/04/27

Plugin Output

udp/0

```
For your information, here is the traceroute from 172.30.0.2 to 172.31.1.50 :
172.30.0.2
172.31.1.50

Hop Count: 1
```

172.31.1.97



Scan Information

Start time: Thu Jul 23 18:30:17 2026

End time: Thu Jul 23 18:32:02 2026

Host Information

IP: 172.31.1.97

MAC Address: DE:3A:41:AE:BD:66

OS: Linux Kernel 6.x on Ubuntu

Vulnerabilities

50686 - IP Forwarding Enabled

Synopsis

The remote host has IP forwarding enabled.

Description

The remote host has IP forwarding enabled. An attacker can exploit this to route packets through the host and potentially bypass some firewalls / routers / NAC filtering.

Unless the remote host is a router, it is recommended that you disable IP forwarding.

Solution

On Linux, you can disable IP forwarding by doing :

```
echo 0 > /proc/sys/net/ipv4/ip_forward
```

On Windows, set the key 'IPEnableRouter' to 0 under

HKEY_LOCAL_MACHINE\System\CurrentControlSet\Services\Tcpip\Parameters

On Mac OS X, you can disable IP forwarding by executing the command :

```
sysctl -w net.inet.ip.forwarding=0
```

For other systems, check with your vendor.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:A/AC:L/PR:L/UI:N/S:C/C:L/I:L/A:L)

CVSS v2.0 Base Score

5.8 (CVSS2#AV:A/AC:L/Au:N/C:P/I:P/A:P)

References

CVE CVE-1999-0511

Plugin Information

Published: 2010/11/23, Modified: 2023/10/17

Plugin Output

tcp/0

```
IP forwarding appears to be enabled on the remote host.
```

```
Detected local MAC Address      : e68cc3441691
Response from local MAC Address  : e68cc3441691
```

```
Detected Gateway MAC Address    : de3a41aebd66
Response from Gateway MAC Address : de3a41aebd66
```

10114 - ICMP Timestamp Request Remote Date Disclosure

Synopsis

It is possible to determine the exact time set on the remote host.

Description

The remote host answers to an ICMP timestamp request. This allows an attacker to know the date that is set on the targeted machine, which may assist an unauthenticated, remote attacker in defeating time-based authentication protocols.

Timestamps returned from machines running Windows Vista / 7 / 2008 / 2008 R2 are deliberately incorrect, but usually within 1000 seconds of the actual system time.

Solution

Filter out the ICMP timestamp requests (13), and the outgoing ICMP timestamp replies (14).

Risk Factor

Low

CVSS v2.0 Base Score

2.1 (CVSS2#AV:L/AC:L/Au:N/C:P/I:N/A:N)

References

CVE	CVE-1999-0524
XREF	CWE:200

Plugin Information

Published: 1999/08/01, Modified: 2024/10/07

Plugin Output

icmp/0

```
The remote clock is synchronized with the local clock.
```


39519 - Backported Security Patch Detection (FTP)

Synopsis

Security patches are backported.

Description

Security patches may have been 'backported' to the remote FTP server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/06/25, Modified: 2026/01/22

Plugin Output

tcp/21/ftp

Give Nessus credentials to perform local checks.

45590 - Common Platform Enumeration (CPE)

Synopsis

It was possible to enumerate CPE names that matched on the remote system.

Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

See Also

<http://cpe.mitre.org/>

<https://nvd.nist.gov/products/cpe>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/04/21, Modified: 2026/06/16

Plugin Output

tcp/0

```
The remote operating system matched the following CPE :  
cpe:/o:canonical:ubuntu_linux -> Canonical Ubuntu Linux
```

54615 - Device Type

Synopsis

It is possible to guess the remote device type.

Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/05/23, Modified: 2025/03/12

Plugin Output

tcp/0

Remote device type : unknown
Confidence level : 56

86420 - Ethernet MAC Addresses

Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/10/16, Modified: 2025/06/10

Plugin Output

tcp/0

The following is a consolidated list of detected MAC addresses:
- DE:3A:41:AE:BD:66

10092 - FTP Server Detection

Synopsis

An FTP server is listening on a remote port.

Description

It is possible to obtain the banner of the remote FTP server by connecting to a remote port.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0030

XREF IAVT:0001-T-0943

Plugin Information

Published: 1999/10/12, Modified: 2023/08/17

Plugin Output

tcp/21/ftp

The remote FTP banner is :

220 (vsFTPd 3.0.2)

12053 - Host Fully Qualified Domain Name (FQDN) Resolution

Synopsis

It was possible to resolve the name of the remote host.

Description

Nessus was able to resolve the fully qualified domain name (FQDN) of the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/02/11, Modified: 2025/03/13

Plugin Output

tcp/0

```
172.31.1.97 resolves as vsftpd.labvulnerabilities_vulnnet.
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/21/ftp

```
Port 21/tcp was found to be open
```

19506 - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2026/07/10

Plugin Output

tcp/0

Information about this scan :

```
Nessus version : 10.12.2
Nessus build : 20029
Plugin feed version : 202607231328
Scanner edition used : Nessus
Scanner OS : LINUX
Scanner distribution : ubuntu1604-x86-64
Scan type : Normal
Scan name : My Basic Network Scan
```


Scan policy used : Basic Network Scan
Scanner IP : 172.30.0.2
Port scanner(s) : nessus_syn_scanner
Port range : default
Ping RTT : 66.542 ms
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Assess component installs : yes
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 30
Max checks : 4
Recv timeout : 5
Backports : Detected
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2026/7/23 18:30 EDT (UTC -04:00)
Scan duration : 101 sec
Scan for malware : no
Fully Scan Operational Technology devices : no
Safely Scan Operational Technology devices with OT Discovery : no

209654 - OS Fingerprints Detected

Synopsis

Multiple OS fingerprints were detected.

Description

Using a combination of remote probes (TCP/IP, SMB, HTTP, NTP, SNMP, etc), it was possible to gather one or more fingerprints from the remote system. While the highest-confidence result was reported in plugin 11936, "OS Identification", the complete set of fingerprints detected are reported here.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/02/26, Modified: 2025/03/03

Plugin Output

tcp/0

Following OS Fingerprints were found

Remote operating system : Linux Kernel 6.x on Ubuntu
Confidence level : 56
Method : MLSinFP
Type : unknown
Fingerprint : unknown

Remote operating system : Linux Kernel 2.x
Confidence level : 54
Method : SinFP
Type : general-purpose
Fingerprint : SinFP:
P1:B10113:F0x12:W64240:00204ffff:M1460:
P2:B10113:F0x12:W65160:00204ffff0402080affffff444541440103030a:M1460:
P3:B00000:F0x00:W0:00:M0
P4:191802_7_p=21

11936 - OS Identification

Synopsis

It is possible to guess the remote operating system.

Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2003/12/09, Modified: 2025/06/03

Plugin Output

tcp/0

```
Remote operating system : Linux Kernel 6.x on Ubuntu  
Confidence level : 56  
Method : MLSinFP
```

```
The remote host is running Linux Kernel 6.x on Ubuntu
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2026/03/23

Plugin Output

tcp/21/ftp

```
An FTP server is running on this port.
```

25220 - TCP/IP Timestamps Supported

Synopsis

The remote service implements TCP timestamps.

Description

The remote host implements TCP timestamps, as defined by RFC1323. A side effect of this feature is that the uptime of the remote host can sometimes be computed.

See Also

<http://www.ietf.org/rfc/rfc1323.txt>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2023/10/17

Plugin Output

tcp/0

10287 - Traceroute Information

Synopsis

It was possible to obtain traceroute information.

Description

Makes a traceroute to the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/11/27, Modified: 2026/04/27

Plugin Output

udp/0

```
For your information, here is the traceroute from 172.30.0.2 to 172.31.1.97 :  
172.30.0.2  
172.31.1.97
```

```
Hop Count: 1
```

52703 - vsftpd Detection

Synopsis

An FTP server is listening on the remote port.

Description

The remote host is running vsftpd, an FTP server for UNIX-like systems written in C.

See Also

<http://vsftpd.beasts.org/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/03/17, Modified: 2019/11/22

Plugin Output

tcp/21/ftp

```
Source   : 220 (vsFTPd 3.0.2)
Version  : 3.0.2
```