

6.9 Substitution rules function (Class Code = 0x6C)

The substitution rule function has functions such as obtaining the substitution rule number and the substitution rule name. List of substitution rules functions

Address		Function Name	Data Range	Input data			Notes
Attribute	Access			Data	Data Length (Byte)	Data Type	
0x64	Get	Getting of substitution rules number	1 to 99	N/A	0	N/A	See note #1
	Set	Setting of substitution rules number		Number	1	Byte	
0x65	Get	Getting of substitution rules name	-	N/A	0	N/A	See note #2
	Set	Setting of substitution rules name	up to 13 chars	Character+ 0x00	1	UTF8	
0x66	Get	Getting of the start year	-	N/A	0	N/A	See note #3
	Set	Setting of the start year	2000 to 2099	Year Data	2	unsigned short	
0x67	Get	Getting the character string of the substitution rules value (Year)	0 to 23	Number	1	Byte	See note #4
	Set	Setting the character string of the substitution rules value (Year)		Number+ Character+ 0x00	Max 3	Byte UTF8	
0x68	Get	Getting the character string of the substitution rules value (Month)	1 to 12	Number	1	Byte	See note #4
	Set	Setting the character string of the substitution rules value (Month)		Number+ Character+ 0x00	Max 4	Byte UTF8	
0x69	Get	Getting the character string of the substitution rules value (Day)	1 to 31	Number	1	Byte	See note #4
	Set	Setting the character string of the substitution rules value (Day)		Number+ Character+ 0x00	Max 3	Byte UTF8	
0x6A	Get	Getting the character string of the substitution rules value (Hour)	0 to 23	Number	1	Byte	See note #4
	Set	Setting the character string of the substitution rules value (Hour)		Number+ Character+ 0x00	Max 3	Byte UTF8	
0x6B	Get	Getting the character string of the substitution rules value (Minute)	0 to 59	Number	1	Byte	See note #4
	Set	Setting the character string of the substitution rules value (Minute)		Number+ Character+ 0x00	Max 4	Byte UTF8	
0x6C	Get	Getting the character string of the substitution rules value (Week Number)	1 to 53	Number	1	Byte	See note #4
	Set	Setting the character string of the substitution rules value (Week Number)		Number+ Character+ 0x00	Max 4	Byte UTF8	
0x6D	Get	Getting the character string of the substitution rules value (The day of the week)	1 to 7	Number	1	Byte	See note #4
	Set	Setting the character string of the substitution rules value (The day of the week)		Number+ Character+ 0x00	Max 4	Byte UTF8	