Data brief

Breakout boards based on the VL53L1 Time-of-Flight ranging sensor with multi object detection and field of view programming



Features

- Two breakout boards, integrating:
 - VL53L1 ranging Time-of-Flight (ToF) sensor
 - Regulator: 5 to 2.8 V range input voltage (output voltage: 2.8 V)
- · True distance measurement independent of target size and reflectance
- Divisible board enabling use as mini PCB breakout board, easy to integrate in customer device

Description

The VL53L1-SATEL breakout boards can be used for easy integration into customer devices.

Thanks to the voltage regulator and level shifters, the VL53L1 breakout boards can be used in any application with a 2.8 V to 5 V supply.

The PCB section supporting the VL53L1 module is perforated so that developers can break off the mini PCB for use in a 2.8 V supply application using flying leads. This makes it easier to integrate the VL53L1-SATEL breakout boards into development and evaluation devices due to their small size.

Product status link

VL53L1-SATEL



1 VL53L1 overview

The VL53L1 is a state-of-the-art, ToF, laser-ranging, miniature sensor enhancing STMicroelectronics' FlightSense product family. Housed in a miniature and reflowable package, it integrates a SPAD (single photon avalanche diode) array, physical IR filters, and optics to achieve the best ranging performance in various ambient lighting conditions, with a wide range of cover windows.

Unlike conventional IR sensors, the VL53L1 uses ST's latest ToF technology which allows absolute distance measurement whatever the target color and reflectance. It provides accurate ranging above 4 m and can work at fast speeds (60 Hz), which makes it the fastest miniature ToF sensor on the market.

With patented algorithms and ingenious module construction, the VL53L1 is also able to detect different objects within the FoV (field of view) with depth understanding at 60 Hz.

Scene browsing and multi zone detection is now possible with the VL53L1, thanks to a software customizable detection array for quicker "touch-to-focus" or mini depth map use cases.

Note:

The VL53L1 is delivered with a liner, to prevent potential foreign material penetrating the module holes during the assembly process. The liner must be removed at the latest possible step during final assembly and before module calibration.

DB4276 - Rev 1 page 2/7



2 Breakable board

For 2.8 V supply applications, the breakout boards can be broken along the red dotted line as shown in the figure below, to use the "mini PCB". This set up is easier to integrate into a customer device due to its small size.

INT XSON 5V to 2.8V NC1 NCO4 supply SDA application VDD GND INT XSON NC1 2.8V Mini supply SDA application **PCB** VDD GND

Figure 1. Breakout board layout

DB4276 - Rev 1 page 3/7



3 Schematic and list of materials

XC6222B281MR-G VL53L1 breakout board 1 VIN VOUT 5 NC 4 ↓10μF VL53L1 C2_ VL53L1

VDDVCSEL 1 12 GND4

VSSVCSEL 2 11 AVDD

GND 3 10 SCL

GND2 4 9 SDA

XSHUT 5 8 DNC

GND3* 6 7 GPI01 2 VSS CE U2 R21 N/F R18 N/F 1 XSDN_I 3 VDD R19 N/F * Could be or N.C. or Grounded TXS0108EPWR 20 B1 A1 VL53L1 Mini PCB A1 1 19 VCCB VCCA 2 OR VDD 18 B2 A2 3 A3 4 СЗ XSDN 100nF 12 100nF R5 N/F NC1 17 B3 A4 5 6 A5 6 16 B4 NC0 SDA 15 B5 A6 7 VL53L1 SCL 14 B6 R12 OR NC1 A7 8 VDD 13 _{B7} OR XSDN A8 9 R3 1k R1 GND 12 В8 N/F 6 J2 11 GND OE 10 C5 100nF 4.7μF GPIO1 R20 N/F OR OR R11 NC0 R10 R17 N/F SDA R16 N/F R9 0R SCL R15 N/F

Figure 2. Satellite schematic and list of materials

DB4276 - Rev 1 page 4/7



4 Ordering information

Table 1. Ordering information

| Order code | Description |
|--------------|----------------------------|
| VL53L1-SATEL | Two VL53L1 breakout boards |

DB4276 - Rev 1 page 5/7



Revision history

Table 2. Document revision history

| Date | Version | Changes |
|-------------|---------|-----------------|
| 23-Jul-2020 | 1 | Initial release |

DB4276 - Rev 1 page 6/7



IMPORTANT NOTICE - PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, please refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2020 STMicroelectronics - All rights reserved

DB4276 - Rev 1 page 7/7

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

STMicroelectronics: VL53L1-SATEL