

npm-uninstall

Synopsis

```
npm uninstall [<@scope>/]<pkg>...
```

aliases: `un`, `unlink`, `remove`, `rm`, `r`

Description

This uninstalls a package, completely removing everything npm installed on its behalf.

It also removes the package from the `dependencies`, `devDependencies`, `optionalDependencies`, and `peerDependencies` objects in your `package.json`.

Further, if you have an `npm-shrinkwrap.json` or `package-lock.json`, npm will update those files as well.

`--no-save` will tell npm not to remove the package from your `package.json`, `npm-shrinkwrap.json`, or `package-lock.json` files.

`--save` or `-S` will tell npm to remove the package from your `package.json`, `npm-shrinkwrap.json`, and `package-lock.json` files. This is the default, but you may need to use this if you have for instance `save=false` in your `npmrc` file

In global mode (ie, with `-g` or `--global` appended to the command), it uninstalls the current package context as a global package. `--no-save` is ignored in this case.

Scope is optional and follows the usual rules for `scope`.

Examples

```
npm uninstall sax
```

`sax` will no longer be in your `package.json`, `npm-shrinkwrap.json`, or `package-lock.json` files.

```
npm uninstall lodash --no-save
```

`lodash` will not be removed from your `package.json`, `npm-shrinkwrap.json`, or `package-lock.json` files.

Configuration

save

- Default: **true** unless when using **npm update** or **npm dedupe** where it defaults to **false**
- Type: Boolean

Save installed packages to a **package.json** file as dependencies.

When used with the **npm rm** command, removes the dependency from **package.json**.

Will also prevent writing to **package-lock.json** if set to **false**.

workspace

- Default:
- Type: String (can be set multiple times)

Enable running a command in the context of the configured workspaces of the current project while filtering by running only the workspaces defined by this configuration option.

Valid values for the **workspace** config are either:

- Workspace names
- Path to a workspace directory
- Path to a parent workspace directory (will result in selecting all workspaces within that folder)

When set for the **npm init** command, this may be set to the folder of a workspace which does not yet exist, to create the folder and set it up as a brand new workspace within the project.

This value is not exported to the environment for child processes.

workspaces

- Default: null
- Type: null or Boolean

Set to true to run the command in the context of **all** configured workspaces.

Explicitly setting this to false will cause commands like **install** to ignore workspaces altogether. When not set explicitly:

- Commands that operate on the **node_modules** tree (install, update, etc.) will link workspaces into the **node_modules** folder. - Commands that do other things (test, exec, publish, etc.) will operate on the root project, *unless* one or more workspaces are specified in the **workspace** config.

This value is not exported to the environment for child processes.

include-workspace-root

- Default: false
- Type: Boolean

Include the workspace root when workspaces are enabled for a command.

When false, specifying individual workspaces via the **workspace** config, or all workspaces via the **workspaces** flag, will cause npm to operate only on the specified workspaces, and not on the root project.

See Also

- npm prune
- npm install
- npm folders
- npm config
- npmrc