

zh-CN

可通过 `loadMore` 属性实现加载更多功能。

en-US

Load more list with `loadMore` property.

```
import { List, Avatar, Button, Skeleton } from 'antd';

const count = 3;
const fakeDataUrl = `https://randomuser.me/api/?
results=${count}&inc=name,gender,email,nat,picture&noinfo`;

class LoadMoreList extends React.Component {
  state = {
    initLoading: true,
    loading: false,
    data: [],
    list: [],
  };

  componentDidMount() {
    fetch(fakeDataUrl)
      .then(res => res.json())
      .then(res => {
        this.setState({
          initLoading: false,
          data: res.results,
          list: res.results,
        });
      });
  }

  onLoadMore = () => {
    this.setState({
      loading: true,
      list: this.state.data.concat(
        [...new Array(count)].map(() => ({ loading: true, name: {}, picture: {} })),
      ),
    });
    fetch(fakeDataUrl)
      .then(res => res.json())
      .then(res => {
        const data = this.state.data.concat(res.results);
        this.setState(
          {
            data,
            list: data,
            loading: false,
          },
        );
      });
  };
}
```

```

    () => {
      // Resetting window's offsetTop so as to display react-virtualized demo
      underfloor.
      // In real scene, you can using public method of react-virtualized:
      // https://stackoverflow.com/questions/46700726/how-to-use-public-
      method-updateposition-of-react-virtualized
      window.dispatchEvent(new Event('resize'));
    },
  );
});
};

render() {
  const { initLoading, loading, list } = this.state;
  const loadMore =
    !initLoading && !loading ? (
      <div
        style={{
          textAlign: 'center',
          marginTop: 12,
          height: 32,
          lineHeight: '32px',
        }}
      >
        <Button onClick={this.onLoadMore}>loading more</Button>
      </div>
    ) : null;

  return (
    <List
      className="demo-loadmore-list"
      loading={initLoading}
      itemLayout="horizontal"
      loadMore={loadMore}
      dataSource={list}
      renderItem={item => (
        <List.Item
          actions={[<a key="list-loadmore-edit">edit</a>, <a key="list-loadmore-
more">more</a>]}
        >
          <Skeleton avatar title={false} loading={item.loading} active>
            <List.Item.Meta
              avatar={<Avatar src={item.picture.large} />}
              title={<a href="https://ant.design">{item.name.last}</a>}
              description="Ant Design, a design language for background
applications, is refined by Ant UED Team"
            />
            <div>content</div>
          </Skeleton>
        </List.Item>
      )}
    />
  );
}

```

```
    );  
  }  
}  
  
export default () => <LoadMoreList />;
```

```
.demo-loadmore-list {  
  min-height: 350px;  
}
```