zh-CN

当 RangePicker 无法满足业务需求时,可以使用两个 DatePicker 实现类似的功能。

- 通过设置 disabledDate 方法,来约束开始和结束日期。
- 通过 open onOpenChange 来优化交互。

en-US

When RangePicker does not satisfied your requirements, try to implement similar functionality with two DatePicker.

- Use the disabledDate property to limit the start and end dates.
- Improve user experience with open and onOpenChange.

```
import { DatePicker, Space } from 'antd';
class DateRange extends React.Component {
 state = {
   startValue: null,
   endValue: null,
   endOpen: false,
 };
 disabledStartDate = startValue => {
   const { endValue } = this.state;
   if (!startValue || !endValue) {
     return false;
   return startValue.valueOf() > endValue.valueOf();
  };
  disabledEndDate = endValue => {
   const { startValue } = this.state;
   if (!endValue || !startValue) {
     return false;
   return endValue.valueOf() <= startValue.valueOf();</pre>
 };
 onChange = (field, value) => {
   this.setState({
     [field]: value,
   });
 };
 onStartChange = value => {
   this.onChange('startValue', value);
 };
  onEndChange = value => {
```

```
this.onChange('endValue', value);
 };
 handleStartOpenChange = open => {
  if (!open) {
    this.setState({ endOpen: true });
 };
 handleEndOpenChange = open => {
   this.setState({ endOpen: open });
 };
 render() {
   const { startValue, endValue, endOpen } = this.state;
     <Space>
       <DatePicker
         disabledDate={this.disabledStartDate}
         showTime
         format="YYYY-MM-DD HH:mm:ss"
         value={startValue}
         placeholder="Start"
         onChange={this.onStartChange}
         onOpenChange={this.handleStartOpenChange}
        />
       <DatePicker
         disabledDate={this.disabledEndDate}
         showTime
         format="YYYY-MM-DD HH:mm:ss"
         value={endValue}
         placeholder="End"
         onChange={this.onEndChange}
         open={endOpen}
         onOpenChange={this.handleEndOpenChange}
       />
     </Space>
   );
 }
}
export default () => <DateRange />;
```