

npm-docs

Synopsis

```
npm docs [<pkgname> [<pkgname> ...]]
```

alias: home

Description

This command tries to guess at the likely location of a package's documentation URL, and then tries to open it using the `--browser` config param. You can pass multiple package names at once. If no package name is provided, it will search for a `package.json` in the current folder and use the `name` property.

Configuration

browser

- Default: OS X: "open", Windows: "start", Others: "xdg-open"
- Type: null, Boolean, or String

The browser that is called by npm commands to open websites.

Set to `false` to suppress browser behavior and instead print urls to terminal.

Set to `true` to use default system URL opener.

registry

- Default: "https://registry.npmjs.org/"
- Type: URL

The base URL of the npm registry.

workspace

- Default:
- Type: String (can be set multiple times)

Enable running a command in the context of the configured workspaces of the current project while filtering by running only the workspaces defined by this configuration option.

Valid values for the **workspace** config are either:

- Workspace names
- Path to a workspace directory
- Path to a parent workspace directory (will result in selecting all workspaces within that folder)

When set for the **npm init** command, this may be set to the folder of a workspace which does not yet exist, to create the folder and set it up as a brand new workspace within the project.

This value is not exported to the environment for child processes.

workspaces

- Default: null
- Type: null or Boolean

Set to true to run the command in the context of **all** configured workspaces.

Explicitly setting this to false will cause commands like **install** to ignore workspaces altogether. When not set explicitly:

- Commands that operate on the **node_modules** tree (install, update, etc.) will link workspaces into the **node_modules** folder. - Commands that do other things (test, exec, publish, etc.) will operate on the root project, *unless* one or more workspaces are specified in the **workspace** config.

This value is not exported to the environment for child processes.

include-workspace-root

- Default: false
- Type: Boolean

Include the workspace root when workspaces are enabled for a command.

When false, specifying individual workspaces via the **workspace** config, or all workspaces via the **workspaces** flag, will cause npm to operate only on the specified workspaces, and not on the root project.

See Also

- npm view
- npm publish
- npm registry
- npm config
- npmrc

- package.json