zh-CN

可以使用 filterMode 来修改筛选菜单的 UI, 可选值有 menu (默认) 和 tree 。

en-US

You can use filterMode to change default filter interface, options: menu (default) and tree .

filterSearch is used for making filter dropdown items searchable.

```
import { Table } from 'antd';
const columns = [
 {
   title: 'Name',
   dataIndex: 'name',
   filters: [
      text: 'Joe',
      value: 'Joe',
     },
       text: 'Category 1',
       value: 'Category 1',
       children: [
          text: 'Yellow',
          value: 'Yellow',
          text: 'Pink',
          value: 'Pink',
         },
       ],
     },
       text: 'Category 2',
       value: 'Category 2',
       children: [
          text: 'Green',
          value: 'Green',
         },
          text: 'Black',
          value: 'Black',
         },
       ],
     },
   ],
   filterMode: 'tree',
```

```
filterSearch: true,
   onFilter: (value, record) => record.name.includes(value),
   width: '30%',
 },
   title: 'Age',
   dataIndex: 'age',
   sorter: (a, b) => a.age - b.age,
 },
   title: 'Address',
   dataIndex: 'address',
   filters: [
      text: 'London',
      value: 'London',
     },
      text: 'New York',
      value: 'New York',
   ],
   onFilter: (value, record) => record.address.startsWith(value),
   filterSearch: true,
   width: '40%',
 },
];
const data = [
  key: '1',
  name: 'John Brown',
  age: 32,
   address: 'New York No. 1 Lake Park',
 },
  key: '2',
   name: 'Jim Green',
  age: 42,
  address: 'London No. 1 Lake Park',
 },
  key: '3',
  name: 'Joe Black',
   age: 32,
   address: 'Sidney No. 1 Lake Park',
 },
   key: '4',
   name: 'Jim Red',
   age: 32,
   address: 'London No. 2 Lake Park',
```

```
},
];

function onChange(pagination, filters, sorter, extra) {
  console.log('params', pagination, filters, sorter, extra);
}

export default () => <Table columns={columns} dataSource={data} onChange={onChange}
/>;
```