

[Home](#) > [puppeteer](#) > [Page](#) > [reload](#)

Page.reload() method

Signature:

```
reload(options?: WaitForOptions): Promise<HTTPResponse | null>;
```

Parameters

Parameter	Type	Description
options	WaitForOptions	Navigation parameters which might have the following properties:

Returns:

Promise<[HTTPResponse](#) | null>

Promise which resolves to the main resource response. In case of multiple redirects, the navigation will resolve with the response of the last redirect.

Remarks

The argument `options` might have the following properties:

- `timeout` : Maximum navigation time in milliseconds, defaults to 30 seconds, pass 0 to disable timeout.
The default value can be changed by using the [page.setDefaultNavigationTimeout\(timeout\)](#) or [page.setDefaultTimeout\(timeout\)](#) methods.
- `waitFor` : When to consider navigation succeeded, defaults to `load`. Given an array of event strings, navigation is considered to be successful after all events have been fired. Events can be either:
 - `load` : consider navigation to be finished when the load event is fired.
 - `domcontentloaded` : consider navigation to be finished when the DOMContentLoaded event is fired.
 - `networkidle0` : consider navigation to be finished when there are no more than 0 network connections for at least 500 ms.
 - `networkidle2` : consider navigation to be finished when there are no more than 2 network connections for at least 500 ms.