

Basically, antd naming requires **FULL NAME** instead of Abbreviation.

Props

- Initialize prop: `default` + `PropName`
- Force render: `forceRender`
 - Force render sub component: `force` + `Sub Component Name` + `Render`
- Sub render: `Sub Component Name` + `Render`
- Data Source: `dataSource`
- Panel visible: popup only `visible` , dropdown `open` , additional popup `popupName` + `Visible` like `tooltipVisible`
- `children` :
 - Mainly display content. To avoid additional prop name.
 - Option list like `Select.Option` or `Tree.TreeNode` .
 - Customize wrapped component can consider use `component` prop if `children` may have other usage in future.
- Display related naming: `show` + `PropName`
- Functional: `PropName` + `able`
- Disable: `disabled`
 - sub component: `disabled` + `Sub Component Name`
- mainly icon: `icon`
 - Merge with function first: `functionName: { icon }` .e.g. `expandable: { icon: <Smile /> }`
 - Multiple icons: `FunctionName` + `Icon`
- Trigger: `trigger`
 - Sub function trigger: `Sub Function` + `Trigger`
 - Trigger on the time point: `xxx` + `On` + `EventName` (e.g. `destroyOnClose`)
- Component use other component config. Naming as component.(e.g. `<Table pagination={{...}} />`)

Event

- Trigger event: `on` + `EventName`
 - Trigger sub component event: `on` + `SubComponentName` + `EventName` (e.g. `onSearchChange`)
 - Trigger prop event: `on` + `PropName` + `EventName` (e.g. `onDragStart`)
- Before trigger event: `before` + `EventName`
- After trigger event: `after` + `EventName`

Current listing api & Chinese version

ref: [#16048](#)

API standard in the document

Examples

| | | | |
|--|--|--|--|
| | | | |
|--|--|--|--|

| Property | Description | Type | Default |
|-----------|-------------|-----------------------|------------|
| htmlType | xxx | string | button |
| type | xxx | horizontal vertical | horizontal |
| disabled | xxx | boolean | false |
| minLength | xxx | number | 0 |
| style | xxx | CSSProperties | - |
| character | xxx | (props) => ReactNode | - |
| offset | xxx | [number, number] | [0, 0] |
| value | xxx | string number | small |

Promise

- When string type, the **Default** use `` .
- Can also list string optional values in **Type**.
- When boolean type, the **Default** value is true or false.
- When number type, the **Default** value use numbers directly.
- When function type, use an arrow function expression in **Type**.
- No default value use - .
- Capitalize the first letter in **Description** apart from `someProp` .
- No period at the end of the **Description**.
- API order is arranged in alphabetical order, and can be put together under special circumstances (such as: xs sm md).

ref: [#25066](#)