

Customize Bootstrap with our built-in custom variables file and easily toggle global CSS preferences with new `$enable-*` Sass variables. Override a variable's value and recompile with `npm run test` as needed.

You can find and customize these variables for key global options in Bootstrap's `scss/_variables.scss` file.

{{< bs-table "table text-start" >}}

Variable	Values	Description
<code>\$spacer</code>	<code>1rem</code> (default), or any value > 0	Specifies the default spacer value to programmatically generate our [spacer utilities]({{< docsref "/utilities/spacing" >}}).
<code>\$enable-rounded</code>	<code>true</code> (default) or <code>false</code>	Enables predefined <code>border-radius</code> styles on various components.
<code>\$enable-shadows</code>	<code>true</code> or <code>false</code> (default)	Enables predefined decorative <code>box-shadow</code> styles on various components. Does not affect <code>box-shadows</code> used for focus states.
<code>\$enable-gradients</code>	<code>true</code> or <code>false</code> (default)	Enables predefined gradients via <code>background-image</code> styles on various components.
<code>\$enable-transitions</code>	<code>true</code> (default) or <code>false</code>	Enables predefined <code>transitions</code> on various components.
<code>\$enable-reduced-motion</code>	<code>true</code> (default) or <code>false</code>	Enables the [prefers-reduced-motion media query]({{< docsref "/getting-started/accessibility#reduced-motion" >}}), which suppresses certain animations/transitions based on the users' browser/operating system preferences.
<code>\$enable-grid-classes</code>	<code>true</code> (default) or <code>false</code>	Enables the generation of CSS classes for the grid system (e.g. <code>.row</code> , <code>.col-md-1</code> , etc.).
<code>\$enable-caret</code>	<code>true</code> (default) or <code>false</code>	Enables pseudo element caret on <code>.dropdown-toggle</code> .
<code>\$enable-button-pointers</code>	<code>true</code> (default) or <code>false</code>	Add "hand" cursor to non-disabled button elements.
<code>\$enable-rfs</code>	<code>true</code> (default) or <code>false</code>	Globally enables [RFS]({{< docsref "/getting-started/rfs" >}}).
<code>\$enable-validation-</code>	<code>true</code> (default)	Enables <code>background-image</code> icons within textual inputs and some custom forms for validation states.

icons	or false	
\$enable-negative-margins	true or false (default)	Enables the generation of [negative margin utilities]({{< docsref "/utilities/spacing#negative-margin" >}}).
\$enable-deprecation-messages	true (default) or false	Set to false to hide warnings when using any of the deprecated mixins and functions that are planned to be removed in v6.
\$enable-important-utilities	true (default) or false	Enables the !important suffix in utility classes.
\$enable-smooth-scroll	true (default) or false	Applies scroll-behavior: smooth globally, except for users asking for reduced motion through [prefers-reduced-motion media query]({{< docsref "/getting-started/accessibility#reduced-motion" >}})
{{< /bs-table >}}		